

Adaptive Output Tracking Control with Reference Model System Uncertainties: Extensions

Gang Tao

Department of Electrical and Computer Engineering
University of Virginia
Charlottesville, VA 22903, USA

Abstract

This paper develops some extensions to the work of [1] which studied the continuous-time adaptive output tracking control schemes with the reference output signal generated from an unknown reference model system. The presented extensions include adaptive control schemes with reference model system uncertainties for single-input single-output (SISO) discrete-time systems and multi-input multi-output (MIMO) discrete-time, continuous-time and feedback linearizable systems as well. To deal with such reference model system uncertainties, the adaptive controller structures are expanded to include a parametrized estimator of the equivalent reference input signal, to ensure a completely parametrized error system with a known regressor vector, suitable for stable adaptive controller parameter update law design.

Keywords: Adaptive control, discrete-time systems, feedback linearizable systems, output feedback, output tracking, state feedback, parameter uncertainties, plant-model matching, reference model systems, vector relative degree.

1 Introduction

In [1], we considered a linear time-invariant (LTI) system (plant) described by

$$\dot{x}(t) = Ax(t) + bu(t), \quad y(t) = cx(t), \quad (1.1)$$

where $x(t) \in R^n$, $u(t) \in R$ and $y(t) \in R$ are the state vector, input and output signals, and $A \in R^{n \times n}$, $b \in R^n$ and $c \in R^{1 \times n}$ are unknown constant matrices such that $G(s) = c(sI - A)^{-1}b$ has relative degree n^* . The control objective is to design the input signal $u(t)$ to ensure the closed-loop system stability and asymptotic output tracking: $\lim_{t \rightarrow \infty} (y(t) - y_m(t)) = 0$, where $y_m(t)$ is the output of a stable reference model system:

$$\dot{x}_m(t) = A_m x_m(t) + b_m u_m(t), \quad y_m(t) = c_m x_m(t) \quad (1.2)$$

where $x_m(t) \in R^n$, $u_m(t) \in R$ and $y_m(t) \in R$ are the reference system state vector, input and output signals, and $A_m \in R^{n \times n}$, $b_m \in R^n$ and $c_m \in R^{1 \times n}$ are some constant matrices such that $G_m(s) = c_m(sI - A_m)^{-1}b_m$ has relative degree $n_m^* \geq n^*$.

The output tracking problem in [1] was different from the traditional model reference adaptive control problem in which the reference model system has an input-output system form

$$y_m(t) = W_m(s)[r_m](t), \quad (1.3)$$

where $W_m(s) = \frac{1}{P_m(s)}$ for a chosen stable polynomial $P_m(s)$ of degree n^* (as a convenient notation, $y_m(t) = W_m(s)[r_m](t)$ denotes the output $y_m(t)$ of a system $W_m(s)$ with input $r_m(t)$), and $r_m(t)$ is a given (available) reference input. Both $W_m(s)$ and $r_m(t)$ are used in a MRAC scheme.

In terms of $G_m(s)$ and $u_m(s)$, we have $y_m(t) = G_m(s)[u_m](t) = W_m(s)P_m(s)G_m(s)[u_m](t)$, so that $r_m(t) = P_m(s)G_m(s)[u_m](t)$ which is known and available from $u_m(t)$ if $G_m(s)$ is known. The adaptive output tracking problem solved in [1] is for the case when the reference model system (A_m, b_m, c_m) or $G_m(s) = c_m(sI - A_m)^{-1}b_m$ is unknown and the time-derivatives $y_m^{(i)}(t)$, $i = 1, 2, \dots, n^*$, are unknown either (such derivative information is also sufficient for MRAC).

The solutions to such a new MRAC problem, developed in [1], were for SISO continuous-time LTI systems. In this paper, we extend the results of [1] to SISO discrete-time LTI systems (in Section 2), to MIMO LTI systems (in Section 3, with a unified presentation for both discrete-time and continuous-time systems and adaptive control designs), and to MIMO feedback linearizable nonlinear systems (in Section 4). More details of the compact presentations given in this paper about such extensions can be found in [2].

2 Discrete-Time Designs for SISO Systems

The problem can be formulated for a SISO discrete-time LTI plant

$$x(t+1) = Ax(t) + bu(t), \quad y(t) = cx(t), \quad (2.1)$$

where $x(t) \in R^n$, $u(t) \in R$ and $y(t) \in R$ are plant state vector, input and output signals, and $A \in R^{n \times n}$, $b \in R^n$ and $c \in R^{1 \times n}$ are unknown, and so is the plant transfer function $G(z) = c(zI - A)^{-1}b$ which has a known relative degree n^* and all its zeros stable.

The control objective is to design a feedback control signal $u(t)$ to ensure closed-loop signal boundedness and asymptotic $y(t)$ tracking the output $y_m(t)$ of a reference model system

$$x_m(t+1) = A_mx_m(t) + b_mu_m(t), \quad y_m(t) = c_mx_m(t) \quad (2.2)$$

where $u_m(t) \in R$ and $y_m(t) \in R$ (and $x_m(t) \in R^n$) are known, $A_m \in R^{n \times n}$, $b_m \in R^n$ and $c_m \in R^{1 \times n}$ are unknown constant matrices, and so is the reference system transfer function $G_m(z) = c_m(zI - A_m)^{-1}b_m$ which is assumed to have a known relative degree $n_m^* \geq n^*$.

The main adaptive control design idea is similar to that for the continuous-time case [1], but in a discrete-time framework: for a chosen stable polynomial $P_m(z)$ of degree n^* :

$$P_m(z) = z^{n^*} + p_{n^*-1}z^{n^*-1} + \cdots + p_1z + p_0, \quad (2.3)$$

we construct an estimate of the equivalent reference model system input

$$\begin{aligned} r_m(t) &= P_m(z)[y_m](t) \\ &= y_m(t + n^*) + p_{n^*-1}y_m(t + n^* - 1) + \cdots + p_1y_m(t + 1) + p_0y_m(t), \end{aligned} \quad (2.4)$$

such that $y_m(t) = G_m(z)[u_m](t) = \frac{1}{P_m(z)}[r_m](t)$, that is, $r_m(t) = P_m(z)G_m(z)[u_m](t)$.

If the signals $y_m(t + i)$, $i = 1, 2, \dots, n^*$, were known, or $G_m(s)$ were known, we could obtain $r_m(t)$ from either $r_m(t) = P_m(z)[y_m](t)$ or $r_m(t) = P_m(z)G_m(z)[u_m](t)$, for adaptive control design. But, they are unknown in the current control problem, so that $r_m(t)$ needs to be estimated whose estimate is the estimate of $r_m(t) = P_m(z)[y_m](t)$ in a parametrized form.

2.1 State Feedback Control Designs

We first consider adaptive state feedback control designs using either the reference model system signals $u_m(t)$ and $x_m(t)$ or the signals $u_m(t)$ and $y_m(t)$.

2.1.1 Design with $x_m(t)$ Available

We derive a parametrized nominal state feedback controller structure for (A, b, c) and (A_m, b_m, c_m) known, and then develop its adaptive version for (A, b, c) and (A_m, b_m, c_m) unknown.

The condition that the reference system (2.2) with relative degree n_m^* , implies: $c_m A_m^i b_m = 0$ for $i = 0, 1, \dots, n_m^* - 2$, $c_m A_m^{n_m^*-1} b_m \neq 0$, so that

$$y_m(t + i) = \begin{cases} c_m A_m^i x_m(t) & \text{for } i = 0, 1, \dots, n_m^* - 1 \\ c_m A_m^i x_m(t) + c_m A_m^{i-1} b_m u_m(t) & \text{for } i = n_m^*. \end{cases} \quad (2.5)$$

Hence, for $n^* \leq n_m^*$, we can express $r_m(t)$ in (2.4) as

$$r_m(t) = \alpha_1^T x_m(t) + \alpha_2 u_m(t) \quad (2.6)$$

for some parameters $\alpha_1 \in R^n$ and $\alpha_2 \in R$, related to the reference system parameters (A_m, b_m, c_m) .

Nominal control law. The nominal state feedback control law is

$$\begin{aligned} u(t) &= k_1^{*T} x(t) + k_2^* r_m(t) \\ &= k_1^{*T} x(t) + k_{21}^{*T} x_m(t) + k_{22}^* u_m(t), \end{aligned} \quad (2.7)$$

where

$$k_{21}^* = k_2^* \alpha_1, \quad k_{22}^* = k_2^* \alpha_2. \quad (2.8)$$

and $k_1^* \in R^n$ and $k_2^* \in R$ are constant parameters satisfying

$$c(zI - A - bk_1^{*T})^{-1}bk_2^* = W_m(z) = \frac{1}{P_m(z)}. \quad (2.9)$$

The output of the closed-loop control system is

$$y(t) = c(zI - A - bk_1^{*T})^{-1}bk_2^*[r_m](t) = W_m(z)[r_m](t) = y_m(t), \quad (2.10)$$

with the exponentially decaying initial condition effect ignored.

Adaptive control law. The adaptive control law is chosen as

$$u(t) = k_1^T x(t) + k_{21}^T x_m(t) + k_{22}u_m(t), \quad (2.11)$$

where $k_1 \in R^n$, $k_{21} \in R^n$ and $k_{22} \in R$ are the estimates of k_1^* , k_{21}^* and k_{22}^* .

Error model. With (2.11), the closed-loop system with (2.1) is

$$\begin{aligned} x(t+1) &= Ax(t) + b(k_1^{*T}x(t) + k_{21}^{*T}x_m(t) + k_{22}^*u_m(t)) \\ &\quad + b((k_1 - k_1^*)^T x(t) + (k_{21} - k_{21}^*)^T x_m(t) + (k_{22} - k_{22}^*)u_m(t)). \end{aligned} \quad (2.12)$$

With $k_{21}^{*T}x_m(t) + k_{22}^*u_m(t) = k_2^*r_m(t)$ and $y_m(t) = c(zI - A - bk_1^{*T})^{-1}bk_2^*[r_m](t) = W_m(z)[r_m](t) = G_m(z)[u_m](t)$ known, for $\rho^* = \frac{1}{k_2^*}$ and the tracking error $e(t) = y(t) - y_m(t)$ with $y(t) = cx(t)$, from (2.12), we derive the tracking error equation

$$e(t) = \rho^*W_m(z)[(k_1 - k_1^*)^T x + (k_{21} - k_{21}^*)^T x_m + (k_{22} - k_{22}^*)u_m](t). \quad (2.13)$$

We introduce the estimation error signal

$$\epsilon(t) = e(t) + \rho(t)\xi(t), \quad (2.14)$$

where $\rho(t)$ is the estimate of ρ^* , and

$$\xi(t) = \theta^T(t)\zeta(t) - W_m(z)[\theta^T\omega](t) \in R \quad (2.15)$$

$$\theta(t) = [k_1^T(t), k_{21}^T(t), k_{22}(t)]^T \in R^{2n+1} \quad (2.16)$$

$$\omega(t) = [x^T(t), x_m^T(t), u_m(t)]^T \in R^{2n+1} \quad (2.17)$$

$$\zeta(t) = W_m(z)[\omega](t) \in R^{2n+1}. \quad (2.18)$$

For $\theta^* = [k_1^{*T}, k_{21}^{*T}, k_{22}^*]^T \in R^{2n+1}$, it can be verified that

$$\epsilon(t) = \rho^*(\theta(t) - \theta^*)^T \zeta(t) + (\rho(t) - \rho^*)\xi(t), \quad (2.19)$$

which is a completely parametrized linear model, in terms of the transformed plant parameters and reference model system parameters in θ^* and their estimates in $\theta(t)$.

Adaptive laws. The adaptive laws for $\theta(t)$ and $\rho(t)$ are chosen as

$$\theta(t+1) = \theta(t) - \frac{\Gamma \text{sign}[k_p] \zeta(t) \epsilon(t)}{m^2(t)} \quad (2.20)$$

$$\rho(t+1) = \rho(t) - \frac{\gamma \xi(t) \epsilon(t)}{m^2(t)} \quad (2.21)$$

where $0 < \Gamma = \Gamma^T < \frac{2}{|k_p|} I$ and $0 < \gamma < 2$ are adaptation gains, and

$$m(t) = \sqrt{1 + \zeta^T(t) \zeta(t) + \xi^2(t)}. \quad (2.22)$$

This adaptive scheme has the following desired and standard adaptive law properties.

Lemma 2.1 *The adaptive laws (2.20) and (2.21) ensure that $\theta(t) \in L^\infty$, $\rho(t) \in L^\infty$, $\frac{\epsilon(t)}{m(t)} \in L^2 \cap L^\infty$, $\theta(t+1) - \theta(t) \in L^2$, and $\rho(t+1) - \rho(t) \in L^2$.*

2.1.2 Design with $x_m(t)$ Unavailable

Consider the reference model system (2.2):

$$x_m(t+1) = A_m x_m(t) + b_m u_m(t), \quad y_m(t) = c_m x_m(t), \quad (2.23)$$

with $x_m(t)$ unavailable. We can use a nominal reduced-order state observer [3, page 553], [4, page 190], based on the knowledge of $y_m(t)$ and $u_m(t)$, to generate an estimate $\hat{x}_m(t)$ of $x_m(t)$ such that $\lim_{t \rightarrow \infty} (\hat{x}_m(t) - x_m(t)) = 0$ exponentially. Then, replacing $x_m(t)$ with $\hat{x}_m(t)$, we can express $r_m(t) = \alpha_1^T \hat{x}_m(t) + \alpha_2 u_m(t)$ as

$$r_m(t) = \beta_1^T \omega_{u_m}(t) + \beta_2^T \omega_{y_m}(t) + \beta_{20} y_m(t) + \alpha_2 u_m(t) \quad (2.24)$$

for some $\beta_1 \in R^{n-1}$, $\beta_2 \in R^{n-1}$ and $\beta_{20} \in R$, where

$$\omega_{u_m}(t) = F(z)[u_m](t), \quad \omega_{y_m}(t) = F(z)[y_m](t), \quad (2.25)$$

$$F(z) = \frac{a(z)}{\Lambda_e(z)}, \quad a(z) = [1, z, \dots, z^{n-2}]^T, \quad (2.26)$$

for a chosen monic stable polynomial $\Lambda_e(z)$ of degree $n-1$.

Nominal control law. The nominal state feedback control law is

$$\begin{aligned} u(t) &= k_1^{*T} x(t) + k_2^* r_m(t) \\ &= k_1^{*T} x(t) + k_{21}^{*T} \omega_{u_m}(t) + k_{22}^{*T} \omega_{y_m}(t) + k_{20}^* y_m(t) + k_3^* u_m(t), \end{aligned} \quad (2.27)$$

where

$$k_{21}^* = k_2^* \beta_1, \quad k_{22}^* = k_2^* \beta_2, \quad k_{20}^* = k_2^* \beta_{20}, \quad k_3^* = k_2^* \alpha_2. \quad (2.28)$$

Adaptive control law. The adaptive state feedback control law is

$$\begin{aligned} u(t) &= k_1^T x(t) + k_{21}^T \omega_{u_m}(t) + k_{22}^T \omega_{y_m}(t) + k_{20} y_m(t) + k_3 u_m(t) \\ &= \theta^T(t) \omega(t), \end{aligned} \quad (2.29)$$

where k_1 , k_{21} , k_{22} , k_{20} and k_3 are the estimates of k_1^* , k_{21}^* , k_{22}^* , k_{20}^* and k_3^* , and

$$\theta(t) = [k_1^T(t), k_{21}^T(t), k_{22}^T(t), k_{20}(t), k_3(t)]^T \in R^{3n} \quad (2.30)$$

$$\omega(t) = [x^T(t), \omega_{u_m}^T(t), \omega_{y_m}^T(t), y_m(t), u_m(t)]^T \in R^{3n}. \quad (2.31)$$

Error model. With the control law (2.29), the closed-loop tracking error equation for $e(t) = y(t) - y_m(t)$ can be derived as

$$e(t) = \rho^* W_m(z) [(\theta - \theta^*)^T \omega](t), \quad (2.32)$$

which has the same form as that in (2.13), where

$$\theta^* = [k_1^{*T}, k_{21}^{*T}, k_{22}^{*T}, k_{20}^*, k_3^{*T}]^T \in R^{3n}. \quad (2.33)$$

Similarly, based on (2.32), an estimation error $\epsilon(t)$ can be introduced:

$$\epsilon(t) = e(t) + \rho(t) \xi(t), \quad (2.34)$$

where $\rho(t)$ is the estimate of ρ^* , and

$$\xi(t) = \theta^T(t) \zeta(t) - W_m(z) [\theta^T \omega](t) \in R \quad (2.35)$$

$$\zeta(t) = W_m(z) [\omega](t) \in R^{3n}, \quad (2.36)$$

and the adaptive laws for $\theta(t)$ and $\rho(t)$ can be chosen as

$$\theta(t+1) = \theta(t) - \frac{\Gamma \text{sign}[k_p] \zeta(t) \epsilon(t)}{m^2(t)} \quad (2.37)$$

$$\rho(t+1) = \rho(t) - \frac{\gamma \xi(t) \epsilon(t)}{m^2(t)} \quad (2.38)$$

where $0 < \Gamma = \Gamma^T < \frac{2}{|k_p|} I$ and $0 < \gamma < 2$, and $m(t) = \sqrt{1 + \zeta^T(t) \zeta(t) + \xi^2(t)}$, to ensure the desired properties similar to that given in Lemma 2.1.

2.2 Output Feedback Control Designs

An output feedback control law can be designed for the discrete-time plant (2.1): $x(t+1) = Ax(t) + bu(t)$, $y(t) = cx(t)$, with the reference model system (2.2): $x_m(t+1) = A_m x_m(t) + b_m u_m(t)$, $y_m(t) = c_m x_m(t)$, starting with the traditional output feedback controller structure

$$u(t) = \theta_1^T \omega_1(t) + \theta_2^T \omega_2(t) + \theta_{20} y(t) + \theta_3 r_m(t), \quad (2.39)$$

where $r_m(t) = P_m(z)G_m(z)[u_m](t) = P_m(z)[y_m](t)$ with $P_m(z)$ being a chosen stable polynomial of degree n^* equal to the relative degree of $G(z) = c(zI - A)^{-1}b$ and $G_m(z) = c_m(zI - A_m)^{-1}b_m$ whose relative degree is $n_m^* \geq n^*$, $\theta_1 \in R^{n-1}$, $\theta_2 \in R^{n-1}$, $\theta_{20} \in R$ and $\theta_3 \in R$, and

$$\omega_1(t) = \frac{a(z)}{\Lambda(z)}[u](t), \quad \omega_2(t) = \frac{a(z)}{\Lambda(z)}[y](t) \quad (2.40)$$

with $a(z) = [1, z, \dots, z^{n-2}]^T$ and $\Lambda(z)$ being a monic stable polynomial of degree $n - 1$. The parameters $\theta_1 \in R^{n-1}$, $\theta_2 \in R^{n-1}$, $\theta_{20} \in R$ and $\theta_3 \in R$ are the estimates of the constant parameters $\theta_1^* \in R^{n-1}$, $\theta_2^* \in R^{n-1}$, $\theta_{20}^* \in R$ and $\theta_3^* = \frac{1}{k_p}$, which satisfy the polynomial matching equation:

$$\theta_1^{*T} a(z)P(z) + (\theta_2^{*T} a(z) + \theta_{20}^* \Lambda(z))k_p Z(z) = \Lambda(z)(P(z) - k_p \theta_3^* Z(z)P_m(z)), \quad (2.41)$$

for $G(z) = c(zI - A)^{-1}b = k_p \frac{Z(z)}{P(z)}$ with monic polynomials $Z(z)$ and $P(z)$ of degrees $n - n^*$ and n .

Parametrization of $r_m(t)$. In the current output tracking control problem, the reference model system (A_m, b_m, c_m) or $G_m(s)$ is unknown, we cannot directly generate $r_m(t)$ from $r_m(t) = P_m(z)G_m(z)[u_m](t)$ for a traditional adaptive controller. In stead, we use the equivalent expression $r_m(t) = P_m(z)[y_m](t)$ to obtain an estimate of $r_m(t)$, to be embedded in the control law.

As derived in (2.6), $r_m(t)$ has the expression

$$r_m(t) = \alpha_1^T x_m(t) + \alpha_2 u_m(t) \quad (2.42)$$

for some parameters $\alpha_1 \in R^n$ and $\alpha_2 \in R$, related to the reference system parameters (A_m, b_m, c_m) .

When $x_m(t)$ is not available, using (2.24), we have

$$r_m(t) = \beta_1^T \omega_{u_m}(t) + \beta_2^T \omega_{y_m}(t) + \beta_{20} y_m(t) + \alpha_2 u_m(t) \quad (2.43)$$

for some $\beta_1 \in R^{n-1}$, $\beta_2 \in R^{n-1}$ and $\beta_{20} \in R$, where

$$\omega_{u_m}(t) = F(z)[u_m](t), \quad \omega_{y_m}(t) = F(z)[y_m](t), \quad (2.44)$$

$$F(z) = \frac{a(z)}{\Lambda_e(z)}, \quad a(z) = [1, z, \dots, z^{n-2}]^T, \quad (2.45)$$

for a chosen monic stable polynomial $\Lambda_e(z)$ of degree $n - 1$.

2.2.1 Nominal Control Laws

A nominal control law can be designed for $x_m(t)$ available or unavailable, based on the parameters of the plant and the reference model system, whose structure is used for adaptive control design.

Nominal control law for $x_m(t)$ available. With $x_m(t)$ available, the nominal control law is

$$\begin{aligned} u(t) &= \theta_1^{*T} \omega_1(t) + \theta_2^{*T} \omega_2(t) + \theta_{20}^* y(t) + \theta_3^* r_m(t) \\ &= \theta_1^{*T} \omega_1(t) + \theta_2^{*T} \omega_2(t) + \theta_{20}^* y(t) + \theta_3^* (\alpha_1^T x_m(t) + \alpha_2 u_m(t)) \\ &= \theta_1^{*T} \omega_1(t) + \theta_2^{*T} \omega_2(t) + \theta_{20}^* y(t) + \theta_{31}^{*T} x_m(t) + \theta_{32}^* u_m(t) \\ &= \theta^{*T} \omega(t), \end{aligned} \quad (2.46)$$

where

$$\theta_{31}^* = \theta_3^* \alpha_1 \in R^n, \theta_{32}^* = \theta_3^* \alpha_2 \in R \quad (2.47)$$

$$\theta^* = [\theta_1^{*T}, \theta_2^{*T}, \theta_{20}^*, \theta_{31}^{*T}, \theta_{32}^*]^T \in R^{3n} \quad (2.48)$$

$$\omega(t) = [\omega_1^T(t), \theta_2^T(t), y(t), x_m^T(t), u_m(t)]^T \in R^{3n}. \quad (2.49)$$

Such a nominal control law can achieve the desired control objective: all closed-loop system signals are bounded and $\lim_{t \rightarrow \infty} (y(t) - y_m(t)) = 0$ (exponentially).

Nominal control law for $x_m(t)$ unavailable. When $x_m(t)$ is not available, we use (2.43) to construct the control law

$$\begin{aligned} u(t) &= \theta_1^{*T} \omega_1(t) + \theta_2^{*T} \omega_2(t) + \theta_{20}^* y(t) + \theta_3^* r_m(t) \\ &= \theta_1^{*T} \omega_1(t) + \theta_2^{*T} \omega_2(t) + \theta_{20}^* y(t) \\ &\quad + \theta_3^* (\beta_1^T \omega_{u_m}(t) + \beta_2^T \omega_{y_m}(t) + \beta_{20} y_m(t) + \alpha_2 u_m(t)) \\ &= \theta_1^{*T} \omega_1(t) + \theta_2^{*T} \omega_2(t) + \theta_{20}^* y(t) \\ &\quad + \theta_{31}^{*T} \omega_{u_m}(t) + \theta_{32}^{*T} \omega_{y_m}(t) + \theta_{33}^* y_m(t) + \theta_{34}^* u_m(t) \\ &= \theta^{*T} \omega(t), \end{aligned} \quad (2.50)$$

where

$$\theta_{31}^* = \theta_3^* \beta_1, \theta_{32}^* = \theta_3^* \beta_2, \theta_{33}^* = \theta_3^* \beta_{20}, \theta_{34}^* = \theta_3^* \alpha_2 \quad (2.51)$$

$$\theta^* = [\theta_1^{*T}, \theta_2^{*T}, \theta_{20}^*, \theta_{31}^{*T}, \theta_{32}^{*T}, \theta_{33}^*, \theta_{34}^*]^T \in R^{4n-1} \quad (2.52)$$

$$\omega(t) = [\omega_1^T(t), \omega_2^T(t), y(t), \omega_{u_m}^T(t), \omega_{y_m}^T(t), y_m(t), u_m(t)]^T. \quad (2.53)$$

2.2.2 Adaptive Control Schemes

Adaptive control laws use the nominal controller structures with parameter estimates.

Adaptive control law for $x_m(t)$ available. Based on the nominal control law (2.46), the adaptive control law is

$$u(t) = \theta^T(t) \omega(t), \quad (2.54)$$

where $\omega(t)$ is defined in (2.49), and $\theta(t)$ is the estimate of θ^* defined in (2.48).

Adaptive control law for $x_m(t)$ unavailable. Based on the nominal control law (2.50), the adaptive control law is

$$u(t) = \theta^T(t) \omega(t), \quad (2.55)$$

where $\omega(t)$ is defined in (2.53), and $\theta(t)$ is the estimate of θ^* defined in (2.52).

Tracking error equation. In both cases, the tracking error $e(t) = y(t) - y_m(t)$ satisfies

$$e(t) = \rho^* W_m(z) [(\theta - \theta^*)^T \omega](t), \quad (2.56)$$

with different θ , θ^* and $\omega(t)$, which has the same form as (2.13) or (2.32), and can be used to define the estimation error for adaptive laws to update $\theta(t)$ and the estimate $\rho(t)$ of ρ^* .

Adaptive laws. Based on (2.56), we can similarly define the estimation error

$$\epsilon(t) = e(t) + \rho(t)\xi(t), \quad (2.57)$$

where $\rho(t)$ is the estimate of ρ^* , and

$$\xi(t) = \theta^T(t)\zeta(t) - W_m(z)[\theta^T\omega](t) \in R \quad (2.58)$$

$$\zeta(t) = W_m(z)[\omega](t) \in R^{n_\theta}, \quad (2.59)$$

and choose the adaptive laws for $\theta(t)$ and $\rho(t)$ as

$$\theta(t+1) = \theta(t) - \frac{\Gamma \text{sign}[k_p]\zeta(t)\epsilon(t)}{m^2(t)} \quad (2.60)$$

$$\rho(t+1) = \rho(t) - \frac{\gamma \xi(t)\epsilon(t)}{m^2(t)}, \quad (2.61)$$

where $0 < \Gamma = \Gamma^T < \frac{2}{|k_p|}I$ and $0 < \gamma < 2$, and

$$m(t) = \sqrt{1 + \zeta^T(t)\zeta(t) + \xi^2(t)}. \quad (2.62)$$

Adaptive system properties. The estimation error $\epsilon(t)$ satisfies

$$\epsilon(t) = \rho^*\tilde{\theta}^T(t)\zeta(t) + \tilde{\rho}(t)\xi(t), \quad \tilde{\theta}(t) = \theta(t) - \theta^*, \quad \tilde{\rho}(t) = \rho(t) - \rho^*. \quad (2.63)$$

The time-increment of the positive definite function $V(\tilde{\theta}, \tilde{\rho}) = |\rho^*|\tilde{\theta}^T\Gamma^{-1}\tilde{\theta} + \gamma^{-1}\tilde{\rho}^2$, is

$$\begin{aligned} & V(\tilde{\theta}(t+1), \tilde{\rho}(t+1)) - V(\tilde{\theta}(t), \tilde{\rho}(t)) \\ &= - \left(2 - \frac{|k_p|\zeta^T(t)\Gamma\zeta(t) + \gamma\xi^2(t)}{m^2(t)} \right) \frac{\epsilon^2(t)}{m^2(t)} \leq 0. \end{aligned} \quad (2.64)$$

Then, we have the desired adaptive law properties given in Lemma 2.1, based on which we have:

Theorem 2.1 *The adaptive controller (2.54) or (2.55), updated from the adaptive law (2.60)-(2.61) and applied to the plant (2.1), ensures that all closed-loop system signals are bounded and $\lim_{t \rightarrow \infty} (y(t) - y_m(t)) = 0$.*

The results of this theorem also hold for adaptive state feedback control designs developed in Section 2.1. The proofs of these results can be derived in a similar way to that for a traditional model reference adaptive control scheme, as the signal terms related to the reference model system are bounded, and the L^2 properties of the adaptive laws hold.

3 Unified Designs for MIMO Systems

Consider a multi-input multi-output linear time-invariant plant

$$\dot{x}(t) = Ax(t) + Bu(t), \quad y(t) = Cx(t), \quad (3.1)$$

where $x(t) \in R^n$ and $y(t) \in R^M$ are the plant state and output vectors, $u(t) \in R^M$ is the input vector, and (A, B, C) are unknown matrices.

The control objective is to design a feedback control input $u(t)$ to ensure closed-loop system signal boundedness and asymptotic $y(t)$ tracking the output $y_m(t)$ of a given reference system

$$\dot{x}_m(t) = A_m x_m(t) + B_m u_m(t), \quad y_m(t) = C_m x_m(t), \quad (3.2)$$

where $x_m(t) \in R^n$ and $y_m(t) \in R^M$ are the reference system state and output vectors, $u_m(t) \in R^M$ is a given input vector, and, unlike the traditional model reference adaptive control problem, (A_m, B_m, C_m) are unknown parameter matrices, so that $G_m(s) = C_m(sI - A_m)^{-1}B_m$ is unknown.

For adaptive control of a multivariable plant (3.1) whose transfer matrix is $G(s) = C(sI - A)^{-1}B$, its modified interactor matrix $\xi_m(s)$ [4, page 385] (which is a lower triangular $M \times M$ polynomial matrix such that $\lim_{s \rightarrow \infty} \xi_m(s)G(s) = K_p$ is nonsingular and finite, and $\xi_m^{-1}(s)$ is a stable rational matrix) is an important structure information to use, as described in the following assumption:

Assumption (A3.1): The modified interactor matrix $\xi_m(s)$ of the plant $G(s)$ is known, and, for the reference model system $G_m(s)$, $\lim_{s \rightarrow \infty} \xi_m(s)G_m(s)$ is finite.

For stable output tracking control, we also need the assumption:

Assumption (A3.2): The plant (A, B, C) is stabilizable and detectable, and all zeros of $G(s)$ are stable.

The above formulation also holds for the discrete-time case, with the symbol s (which denotes either the time-differentiation operator: $s[x](t) = \dot{x}(t)$ or the Laplace transform variable in the continuous-time case) replaced by the symbol z (which denotes either the time-advance operator: $z[x](t) = x(t+1)$ or the z -transform variable), that is, the discrete-time plant is

$$x(t+1) = Ax(t) + Bu(t), \quad y(t) = Cx(t), \quad (3.3)$$

and the discrete-time reference model system is

$$\dot{x}_m(t) = A_m x_m(t) + B_m u_m(t), \quad y_m(t) = C_m x_m(t). \quad (3.4)$$

With a unified symbol D to denote either s or z , we can present a unified development of adaptive control schemes for both the continuous-time and discrete-time cases.

3.1 State Feedback Control Laws

We first develop the nominal and adaptive state feedback output tracking control laws using the reference model systems signals $x_m(t)$ and $u_m(t)$.

3.1.1 Nominal Control Law

With the knowledge of the plant (A, B, C) , the nominal state feedback control law is

$$u(t) = K_1^{*T} x(t) + K_2^* r_m(t), \quad (3.5)$$

where the parameter matrices $K_1^* \in R^{n \times M}$ and $K_2^* \in R^{M \times M}$ satisfy

$$C(DI - A - BK_1^{*T})^{-1} BK_2^* = \xi_m^{-1}(D), K_2^{*-1} = K_p, \quad (3.6)$$

whose existence is guaranteed [5], and $r_m(t)$ is such that

$$y_m(t) = W_m(D)[r_m](t), W_m(D) = \xi_m^{-1}(D). \quad (3.7)$$

From (3.2), for $G_m(D) = C_m(DI - A_m)^{-1} B_m$, we have

$$y_m(t) = G_m(D)[u_m](t) \quad (3.8)$$

so that $r_m(t) = \xi_m(D)G_m(D)[u_m](t)$ and $r_m(t) = \xi_m(D)[y_m](t)$. Since $G_m(s)$ is unknown or the time-derivatives of $y_m(t)$ are not available, the signal $r_m(t)$ is not available for implementing the control law (3.5), and we need to parametrize its uncertainty for estimation.

Recall the operator D which is such that, for a scalar signal $w(t)$, $D[w](t) = \dot{w}(t)$ in the continuous-time case or $D[w](t) = w(t+1)$ in the discrete-time case. Then, under Assumption (A3.1): $\lim_{s \rightarrow \infty} \xi_m(D)G_m(D)$ is finite, from the reference system model (3.2), we can express

$$r_m(t) = \xi_m(D)[y_m](t) = A_1^T x_m(t) + A_2 u_m(t), \quad (3.9)$$

for some parameter matrices $A_1 \in R^{n \times M}$ and $A_2 \in R^{M \times M}$ (similar to (2.42) for the $M = 1$ case), which depend on the reference system parameters (A_m, B_m, C_m) (the matrix A_2 may not be nonsingular). Hence, we can modify the nominal control law (3.5) as

$$\begin{aligned} u(t) &= K_1^{*T} x(t) + K_2^* r_m(t) \\ &= K_1^{*T} x(t) + K_2^* (A_1^T x_m(t) + A_2 u_m(t)) \\ &= K_1^{*T} x(t) + K_{21}^{*T} x_m(t) + K_{22}^* u_m(t), \end{aligned} \quad (3.10)$$

where $K_{21}^{*T} = K_2^* A_1^T$, $K_{22}^* = K_2^* A_2$.

Such a nominal control law ensures that $y(t) = W_m(D)[r_m](t) = y_m(t)$ for the output $y_m(t)$ of a given reference model system: $D[x_m](t) = A_m x_m(t) + B_m u_m(t)$, $y_m(t) = C_m x_m(t)$.

3.1.2 Adaptive Control Law

The adaptive controller structure is chosen as

$$u(t) = K_1^T x(t) + K_{21}^T x_m(t) + K_{22} u_m(t), \quad (3.11)$$

where K_1 , K_{21} and K_{22} are the estimates of K_1^* , K_{21}^* and K_{22}^* .

With the control law (3.11) applied to the unified form plant:

$$D[x](t) = Ax(t) + Bu(t), \quad y(t) = Cx(t), \quad (3.12)$$

for the tracking error $e(t) = y(t) - y_m(t)$, we obtain

$$e(t) = W_m(D)K_p[(\Theta - \Theta^*)^T \omega](t), \quad (3.13)$$

where

$$\omega(t) = [x^T(t), x_m^T(t), u_m^T(t)]^T \in R^{2n+M} \quad (3.14)$$

$$\Theta(t) = [K_1^T(t), K_{21}^T(t), K_{22}^T(t)]^T \in R^{(2n+M) \times M} \quad (3.15)$$

$$\Theta^* = [K_1^{*T}, K_{21}^{*T}, K_{22}^{*T}]^T \in R^{(2n+M) \times M}. \quad (3.16)$$

3.2 Output Feedback Control Laws

The output feedback control laws uses either an observer-based controller structure or a plant-model matching controller structure. We now study their nominal form and adaptive version using the signals $x_m(t)$ and $u_m(t)$ of the reference model system (3.2).

3.2.1 Nominal Control Law

The baseline nominal output feedback controller structure is

$$u(t) = \Theta_1^{*T} \omega_1(t) + \Theta_2^{*T} \omega_2(t) + \Theta_{20}^* y(t) + \Theta_3^* r_m(t), \quad (3.17)$$

where $\Theta_1^* = [\Theta_{11}^*, \dots, \Theta_{1\nu-1}^*]^T$, $\Theta_2^* = [\Theta_{21}^*, \dots, \Theta_{2\nu-1}^*]^T$, with $\Theta_{ij}^* \in R^{M \times M}$, $i = 1, 2, j = 1, \dots, \nu - 1$, with either $\nu = n - M$ or $\nu = \nu_p$ being the observability index of the plant (3.12), $\Theta_{20}^* \in R^{M \times M}$ and $\Theta_3 \in R^{M \times M}$, and

$$\omega_1(t) = F(D)[u](t), \quad \omega_2(t) = F(D)[y](t), \quad (3.18)$$

$$F(D) = \frac{A(D)}{\Lambda(D)}, \quad A(D) = [I_M, DI_M, \dots, D^{\nu-2} I_M]^T, \quad (3.19)$$

for a chosen monic and stable polynomial $\Lambda(D)$ of degree $\nu - 1$.

The nominal controller parameters Θ_1^* , Θ_2^* , Θ_{20}^* and Θ_3^* satisfy

$$\begin{aligned} & \Theta_1^{*T} A(D)P(D) + (\Theta_2^{*T} A(D) + \Theta_{20}^* \Lambda(D))Z(D) \\ & = \Lambda(D)(P(D) - \Theta_3^* \xi_m(D)Z(D)), \end{aligned} \quad (3.20)$$

for a pair of right matrix-fraction polynomial matrices $P(D)$ and $Z(D)$ of $G(D) = C(DI - A)^{-1}B$: $G(D) = Z(D)P^{-1}(D)$. With (3.20), the closed-loop system transfer matrix is $W_m(s) = \xi_m^{-1}(D)$.

Using (3.9), we have

$$\begin{aligned} u(t) &= \Theta_1^{*T} \omega_1(t) + \Theta_2^{*T} \omega_2(t) + \Theta_{20}^* y(t) + \Theta_3^*(A_1^T x_m(t) + A_2 u_m(t)) \\ &= \Theta_1^{*T} \omega_1(t) + \Theta_2^{*T} \omega_2(t) + \Theta_{20}^* y(t) + \Theta_{31}^{*T} x_m(t) + \Theta_{32}^* u_m(t) \end{aligned} \quad (3.21)$$

where $\Theta_{31}^{*T} = \Theta_3^* A_1^T$, $\Theta_{32}^* = \Theta_3^* A_2$.

Remark 3.1 In the controller structure (3.17), either $\nu = n - M$ (with which the controller structure is observed-based, from using the reduced-order estimate $\hat{x}(t)$ of $x(t)$ such that $\lim_{t \rightarrow \infty} (\hat{x}(t) - x(t)) = 0$), or $\nu = \nu_p \leq n - M$ being the observability index of the plant (3.12) (with which the controller structure has the desired plant-model matching property (3.20) which makes the closed-loop system transfer matrix equal to the reference model system $W_m(s) = \xi_m^{-1}(D)$). \square

3.2.2 Adaptive Control Law

We then choose the adaptive control law

$$u(t) = \Theta_1^T \omega_1(t) + \Theta_2^T \omega_2(t) + \Theta_{20} y(t) + \Theta_{31}^T x_m(t) + \Theta_{32} u_m(t) \quad (3.22)$$

with the estimates $\Theta_1, \Theta_2, \Theta_{20}, \Theta_{31}$ and Θ_{32} of $\Theta_1^*, \Theta_2^*, \Theta_{20}^*, \Theta_{31}^*$ and Θ_{32}^* .

With the control law (3.22) applied to the plant (3.12), we can derive the dynamic equation for the tracking error $e(t) = y(t) - y_m(t)$:

$$e(t) = W_m(D)K_p[(\Theta - \Theta^*)^T \omega](t), \quad (3.23)$$

where

$$\omega(t) = [\omega_1^T(t), \omega_2^T(t), y^T(t), x_m^T(t), u_m^T(t)]^T \quad (3.24)$$

$$\Theta(t) = [\Theta_1^T(t), \Theta_2^T, \Theta_{20}, \Theta_{31}^T(t), \Theta_{32}(t)]^T \quad (3.25)$$

$$\Theta^* = [\Theta_1^{*T}, \Theta_2^{*T}, \Theta_{20}^*, \Theta_{31}^{*T}, \Theta_{32}^*]^T. \quad (3.26)$$

This error equation has the same form as that in (3.13) for the state feedback control case, for which a unified adaptive law design can be derived.

3.3 Adaptive Laws

The state feedback and output feedback control designs lead to the tracking error equation (3.13) or (3.23) which can be written in the form

$$\begin{aligned} \xi_m(D)[e](t) &= K_p \tilde{\Theta}^T(t) \omega(t), \quad \tilde{\Theta}(t) = \Theta(t) - \Theta^* \\ &= K_p (u(t) - \Theta^{*T}(t) \omega(t)), \quad u(t) = \Theta^T(t) \omega(t). \end{aligned} \quad (3.27)$$

Effectively dealing with the uncertainty of K_p is a key step in developing a stable adaptive scheme to update the controller parameter matrix $\Theta(t)$, more sophisticated than the case of $M = 1$ when $K_p = k_p$ is a scalar. There are different adaptive schemes using different information of K_p [4].

3.3.1 A Basic Design

We first present a basic adaptive scheme, using a gain matrix S_p analogous to the sign of k_p in the SISO case of $M = 1$, specified in the following assumption:

Assumption (A3.3): A matrix $S_p \in R^{M \times M}$ is known such that, for the continuous-time case, $K_p S_p = (K_p S_p)^T > 0$, and for the discrete-time case, $0 < K_p S_p = (K_p S_p)^T < 2I$ [4].

For the first equation of (3.27), we choose a stable and monic polynomial $f(D)$ of degree equal to the maximum degree of $\xi_m(D)$, and operate both sides of (3.27) by $h(D) = \frac{1}{f(D)}$, to obtain

$$\bar{e}(t) \triangleq h(D)\xi_m(D)[e](t) = K_p h(D)[\tilde{\Theta}^T \omega](t). \quad (3.28)$$

We then introduce the auxiliary signals

$$\zeta(t) = h(D)[\omega](t) \quad (3.29)$$

$$\xi(t) = \Theta^T(t)\zeta(t) - h(D)[\Theta^T \omega](t) \quad (3.30)$$

and define the estimation error

$$\epsilon(t) = \bar{e}(t) + \Psi(t)\xi(t), \quad (3.31)$$

where $\Psi(t)$ is the estimate of $\Psi^* = K_p$. It follows from (3.28)-(3.31) that

$$\epsilon(t) = K_p \tilde{\Theta}^T(t)\zeta(t) + \tilde{\Psi}(t)\xi(t), \quad \tilde{\Psi}(t) = \Psi(t) - \Psi^*. \quad (3.32)$$

Adaptive laws. We choose the adaptive laws for $\Theta(t)$ and $\Psi(t)$:

$$\left. \begin{array}{l} \dot{\Theta}^T(t) \\ \Theta^T(t+1) - \Theta^T(t) \end{array} \right\} = -\frac{S_p \epsilon(t) \zeta^T(t)}{m^2(t)} \quad (3.33)$$

$$\left. \begin{array}{l} \dot{\Psi}(t) \\ \Psi(t+1) - \Psi(t) \end{array} \right\} = -\frac{\Gamma \epsilon(t) \xi^T(t)}{m^2(t)}, \quad (3.34)$$

where S_p satisfies Assumption (A3.3), $\Gamma = \Gamma^T > 0$ for the continuous-time case and $0 < \Gamma = \Gamma^T < 2I$ for the discrete-time case, and $m(t) = \sqrt{1 + \zeta^T(t)\zeta(t) + \xi^T(t)\xi(t)}$.

Stability analysis. Consider the the positive definite function

$$V = \text{tr}[\tilde{\Theta} \Gamma_p \tilde{\Theta}^T] + \text{tr}[\tilde{\Psi}^T \Gamma^{-1} \tilde{\Psi}], \quad \Gamma_p = K_p^T S_p^{-1} = \Gamma_p^T > 0, \quad (3.35)$$

we derive, for the continuous-time case, its time-derivative as

$$\begin{aligned} \dot{V} &= 2\text{tr}[\tilde{\Theta} \Gamma_p \dot{\Theta}^T] + 2\text{tr}[\tilde{\Psi}^T \Gamma^{-1} \dot{\Psi}] \\ &= -2\text{tr}[\tilde{\Theta} \Gamma_p \frac{S_p \epsilon(t) \zeta^T(t)}{m^2(t)}] - 2\text{tr}[\tilde{\Psi}^T \Gamma^{-1} \frac{\Gamma \epsilon(t) \xi^T(t)}{m^2(t)}] \\ &= -2\text{tr}[\zeta^T(t) \tilde{\Theta} \Gamma_p S_p \frac{\epsilon(t)}{m^2(t)}] - 2\text{tr}[\xi^T(t) \tilde{\Psi}^T \frac{\epsilon(t)}{m^2(t)}] \\ &= -2(\zeta^T(t) \tilde{\Theta} K_p^T + \xi^T(t) \tilde{\Psi}^T) \frac{\epsilon(t)}{m^2(t)} \\ &= -\frac{2\epsilon^T(t) \epsilon(t)}{m^2(t)} \leq 0, \end{aligned} \quad (3.36)$$

or, for the discrete-time case, its time-increment as

$$\begin{aligned}
& V(\tilde{\Theta}(t+1), \tilde{\Psi}(t+1)) - V(\tilde{\Theta}(t), \tilde{\Psi}(t)) \\
&= \text{tr}[\tilde{\Theta}(t+1)\Gamma_p\tilde{\Theta}^T(t+1)] + \text{tr}[\tilde{\Psi}^T(t+1)\Gamma^{-1}\tilde{\Psi}(t+1)] \\
&\quad - \text{tr}[\tilde{\Theta}(t)\Gamma_p\tilde{\Theta}^T(t)] - \text{tr}[\tilde{\Psi}^T(t)\Gamma^{-1}\tilde{\Psi}(t)] \\
&= \text{tr}\left[\left(\tilde{\Theta}^T(t) - \frac{S_p\epsilon(t)\zeta^T(t)}{m^2(t)}\right)^T\Gamma_p\left(\tilde{\Theta}^T(t) - \frac{S_p\epsilon(t)\zeta^T(t)}{m^2(t)}\right)\right] - \text{tr}[\tilde{\Theta}(t)\Gamma_p\tilde{\Theta}^T(t)] \\
&\quad + \text{tr}\left[\left(\tilde{\Psi}(t) - \frac{\Gamma\epsilon(t)\xi^T(t)}{m^2(t)}\right)^T\Gamma^{-1}\left(\tilde{\Psi}(t) - \frac{\Gamma\epsilon(t)\xi^T(t)}{m^2(t)}\right)\right] - \text{tr}[\tilde{\Psi}^T(t)\Gamma^{-1}\tilde{\Psi}(t)] \\
&= -2\text{tr}\left[\frac{\zeta(t)\epsilon^T(t)S_p^T\Gamma_p\tilde{\Theta}^T(t)}{m^2(t)}\right] + \text{tr}\left[\frac{\zeta(t)\epsilon^T(t)S_p^T\Gamma_pS_p\epsilon(t)\zeta^T(t)}{m^4(t)}\right] \\
&\quad - 2\text{tr}\left[\frac{\xi(t)\epsilon^T(t)\Gamma\Gamma^{-1}\tilde{\Psi}(t)}{m^2(t)}\right] + \text{tr}\left[\frac{\xi(t)\epsilon^T(t)\Gamma\Gamma^{-1}\Gamma\epsilon(t)\xi^T(t)}{m^4(t)}\right] \\
&= -\frac{2\epsilon^T(t)\epsilon(t)}{m^2(t)} + \frac{\zeta^T(t)\zeta(t)}{m^2(t)}\frac{\epsilon^T(t)K_pS_p\epsilon(t)}{m^2(t)} + \frac{\xi^T(t)\xi(t)}{m^2(t)}\frac{\epsilon^T(t)\Gamma\epsilon(t)}{m^2(t)} \\
&\leq -\frac{\alpha_1\epsilon^T(t)\epsilon(t)}{m^2(t)}, \tag{3.37}
\end{aligned}$$

for $0 < \alpha_1 \leq 2 - \max\{\lambda_{\max}[\Gamma_p], \lambda_{\max}[\Gamma]\}$.

Based on this result, we can derive the following properties:

Lemma 3.1 *The adaptive laws (3.33)-(3.34) ensure:*

- (i) $\Theta(t) \in L^\infty$, $\Psi(t) \in L^\infty$, and $\frac{\epsilon(t)}{m(t)} \in L^2 \cap L^\infty$;
- (ii) $\dot{\Theta}(t) \in L^2 \cap L^\infty$ and $\dot{\Psi}(t) \in L^2 \cap L^\infty$ (the continuous-time case); and
- (iii) $\Theta(t+1) - \Theta(t) \in L^2$ and $\Psi(t+1) - \Psi(t) \in L^2$ (the discrete-time case).

3.3.2 K_p Decomposition Based Designs

The knowledge of the plant high frequency gain matrix K_p , needed for adaptive control design, can be reduced by using the LDS, LDU and SDU decompositions of K_p [4].

The LDS based design can be derived, by reparametrizing the first equation of (3.27) as

$$\xi_m(D)[e](t) + \Theta_0^*\xi_m(D)[e](t) = D_sS\tilde{\Theta}^T(t)\omega(t), \tag{3.38}$$

where $K_p = L_sD_sS$ with L_s being a unity lower triangular matrix (D_s being a diagonal matrix and S being a symmetric and positive definite matrix), and $\Theta_0^* = L_s^{-1} - I_M$ has the special structure:

$$\Theta_0^* = \begin{bmatrix} 0 & 0 & 0 & \cdots & 0 \\ \theta_{21}^* & 0 & 0 & \cdots & 0 \\ \theta_{31}^* & \theta_{32}^* & 0 & \cdots & 0 \\ \cdots & \cdots & \cdots & \cdots & \cdots \\ \theta_{M-11}^* & \cdots & \theta_{M-1M-2}^* & 0 & 0 \\ \theta_{M1}^* & \cdots & \theta_{MM-2}^* & \theta_{MM-1}^* & 0 \end{bmatrix}. \tag{3.39}$$

The LDU decomposition of K_p : $K_p = LD_pU$, with L being a unity lower triangular matrix and U being a unity upper triangular matrix (and D_p being a diagonal matrix), can also be used for an adaptive design. In this case, the second equation of (3.27) is reparametrized as

$$\begin{aligned}\xi_m(D)[e](t) + \Theta_0^* \xi_m(D)[e](t) &= D_p U(u(t) - \Theta^{*T} \omega(t)) \\ &= D_p(u(t) - \Phi_0^* u(t) - U \Theta^{*T} \omega(t)),\end{aligned}\tag{3.40}$$

where $\Phi_0^* = I - U = \begin{bmatrix} 0 & \phi_{12}^* & \phi_{13}^* & \cdots & \phi_{1M}^* \\ 0 & 0 & \phi_{23}^* & \cdots & \phi_{2M}^* \\ \vdots & \vdots & \vdots & \vdots & \vdots \\ 0 & 0 & \cdots & 0 & \phi_{M-1M}^* \\ 0 & \cdots & \cdots & 0 & 0 \end{bmatrix}$ whose elements ϕ_{ij}^* can be estimated.

The parameters Θ_0^* , D_s and Θ^* (in $\tilde{\Theta}(t) = \Theta(t) - \Theta^*$) in (3.38) can be estimated, using the sign information of the diagonal elements of D_s . The parameters Θ_0^* , Φ_0^* , $U\Theta^{*T}$ and $D_p = \text{diag}\{d_1^*, d_2^*, \dots, d_M^*\}$ in (3.40) can be estimated, using the sign information of d_i^* . Such sign information depends on the leading principal minors of K_p , which are assumed to be all non-zero. For the discrete-time case design, some bound information $d_i^0 \geq |d_i^*|$ is needed for the adaptive law. For details of such K_p decomposition based adaptive control designs, see [4, pages 448-452].

3.4 Further Extensions

We now present some additional designs of the adaptive control schemes for the reference model system (3.2) with uncertain (A_m, B_m, C_m) , and their performance analysis and applications.

3.4.1 Design with $x_m(t)$ Unavailable

When the state vector $x_m(t)$ of the reference system (3.2):

$$D[x_m](t) = A_m x_m(t) + B_m u_m(t), \quad y_m(t) = C_m x_m(t),\tag{3.41}$$

is not available, a nominal reduced-order state observer [3, page 272] can be used, based on the knowledge of $y_m(t) \in R^M$ and $u_m(t) \in R^M$, to generate an estimate $\hat{x}_m(t)$ of $x_m(t)$ such that $\lim_{t \rightarrow \infty} (\hat{x}_m(t) - x_m(t)) = 0$ exponentially. With such an $\hat{x}_m(t)$, the term $A_1^T x_m(t)$ in (3.9) can be replaced with $A_1^T \hat{x}_m(t)$ which can be further expressed as

$$A_1^T \hat{x}_m(t) = B_1^T \omega_{u_m}(t) + B_2^T \omega_{y_m}(t) + B_{20} y_m(t),\tag{3.42}$$

for some constant matrices B_1 , B_2 , B_{20} , and $\omega_{u_m}(t) = F_m(D)[u_m](t)$, $\omega_{y_m}(t) = F_m(D)[y_m](t)$, with $F_m(D) = \frac{A_m(D)}{\Lambda_e(D)}$, $A_m(D) = [I_M, DI_M, \dots, D^{n-M-1}I_M]^T$, for a chosen monic and stable polynomial $\Lambda_e(D)$ of degree $n - M - 1$.

We then can express $r_m(t)$ in (3.9) as

$$r_m(t) = B_1^T \omega_{u_m}(t) + B_2^T \omega_{y_m}(t) + B_{20} y_m(t) + A_2 u_m(t),\tag{3.43}$$

which can be combined with the control law (3.5) or (3.17) to derive a control law in terms of the reference model system signals $u_m(t)$ and $y_m(t)$.

3.4.2 Partial-State Feedback Control Designs

In [6], a partial-state feedback adaptive control scheme is developed for MIMO systems to achieve output tracking, using an available partial-state vector $y_0(t) = C_0x(t) \in R^{n_0}$ with (A, C_0) observable and $\text{rank}[C_0] = n_0$, to build an observer-based control law. In [1], a partial-state feedback adaptive control scheme with uncertain reference model system parameters is developed for SISO systems.

For a MIMO plant, the baseline nominal partial-state feedback controller structure [6] is

$$u(t) = \Theta_1^{*T} \omega_1(t) + \Theta_2^{*T} \omega_2(t) + \Theta_{20}^* y_0(t) + \Theta_3^* r_m(t), \quad (3.44)$$

where $\Theta_1^* \in R^{M(n-n_0) \times M}$, $\Theta_2^* \in R^{n_0(n-n_0) \times M}$, $\Theta_{20}^* \in R^{M \times n_0}$ and $\Theta_3^* \in R^{M \times M}$, and

$$\omega_1(t) = \frac{A_1(D)}{\Lambda(D)}[u](t), \quad \omega_2(t) = \frac{A_2(D)}{\Lambda(D)}[y_0](t) \quad (3.45)$$

with $A_1(D) = [I_M, DI_M, \dots, D^{n-n_0-1}I_M]^T$ and $A_2(D) = [I_{n_0}, DI_{n_0}, \dots, D^{n-n_0-1}I_{n_0}]^T$, and $\Lambda(D)$ being a monic stable polynomial of degree $n - n_0$.

In our control problem, $r_m(t) = \xi_m(D)[y_m](t)$ is not available and we reparametrize it. With the parametrization scheme (3.9): $r_m(t) = \xi_m(D)[y_m](t) = A_1^T x_m(t) + A_2 u_m(t)$, we express

$$\Theta_3^* r_m(t) = \Theta_3^* (A_1^T x_m(t) + A_2 u_m(t)) \triangleq \Theta_{31}^{*T} x_m(t) + \Theta_{32}^* u_m(t), \quad (3.46)$$

to form the nominal control law (which uses $x_m(t)$ and $u_m(t)$):

$$u(t) = \Theta_1^{*T} \omega_1(t) + \Theta_2^{*T} \omega_2(t) + \Theta_{20}^* y_0(t) + \Theta_{31}^{*T} x_m(t) + \Theta_{32}^* u_m(t), \quad (3.47)$$

whose adaptive version is

$$u(t) = \Theta_1^T \omega_1(t) + \Theta_2^T \omega_2(t) + \Theta_{20} y_0(t) + \Theta_{31}^T x_m(t) + \Theta_{32} u_m(t), \quad (3.48)$$

with the estimates Θ_1 , Θ_2 , Θ_{20} , Θ_{31} and Θ_{32} of Θ_1^* , Θ_2^* , Θ_{20}^* , Θ_{31}^* and Θ_{32}^* .

With the parametrization scheme (3.43) (using the observer-based estimate $\hat{x}_m(t)$ of $x_m(t)$): $r_m(t) = B_1^T \omega_{u_m}(t) + B_2^T \omega_{y_m}(t) + B_{20} y_m(t) + A_2 u_m(t)$, we express

$$\begin{aligned} \Theta_3^* r_m(t) &= \Theta_3^* (B_1^T \omega_{u_m}(t) + B_2^T \omega_{y_m}(t) + B_{20} y_m(t) + A_2 u_m(t)) \\ &\triangleq \Theta_{31}^{*T} \omega_{u_m}(t) + \Theta_{32}^{*T} \omega_{y_m}(t) + \Theta_{33}^* y_m(t) + \Theta_{34}^* u_m(t), \end{aligned} \quad (3.49)$$

to form the nominal control law (which uses $y_m(t)$ and $u_m(t)$):

$$u(t) = \Theta_1^{*T} \omega_1(t) + \Theta_2^{*T} \omega_2(t) + \Theta_{20}^* y_0(t) + \Theta_{31}^{*T} \omega_{u_m}(t) + \Theta_{32}^{*T} \omega_{y_m}(t) + \Theta_{33}^* y_m(t) + \Theta_{34}^* u_m(t), \quad (3.50)$$

whose adaptive version is

$$u(t) = \Theta_1^T \omega_1(t) + \Theta_2^T \omega_2(t) + \Theta_{20} y_0(t) + \Theta_{31}^T \omega_{u_m}(t) + \Theta_{32}^T \omega_{y_m}(t) + \Theta_{33} y_m(t) + \Theta_{34} u_m(t), \quad (3.51)$$

with the estimates Θ_1 , Θ_2 , Θ_{20} , Θ_{31} , Θ_{32} , Θ_{33} and Θ_{34} of Θ_1^* , Θ_2^* , Θ_{20}^* , Θ_{31}^* , Θ_{32}^* , Θ_{33}^* and Θ_{34}^* .

With these adaptive control laws, the tracking error equations can be derived and the estimation error signals can be defined to design the adaptive laws to update the controller parameters.

3.4.3 Design for Continuous-Time Relative-Degree-One Systems

A continuous-time relative-degree-one system is

$$\dot{x}(t) = Ax(t) + Bu(t), \quad y(t) = Cx(t), \quad (3.52)$$

with the modified interactor matrix $\xi_m(s) = sI + P_0$ for $P_0 = \text{diag}\{a_1, a_2, \dots, a_M\} > 0$.

In this case, the state feedback tracking error equation (3.13) and the output feedback tracking error equation (3.23) have the form

$$\dot{e}(t) = A_0 e(t) + K_p(\Theta - \Theta^*)^T(t)\omega(t), \quad (3.53)$$

where $A_0 = -P_0 = \text{diag}\{-a_1, -a_2, \dots, -a_M\}$ with $a_i > 0$, $i = 1, 2, \dots, M$, that is, A_0 is a stable matrix. In this case, a Lyapunov design of the adaptive law for $\Theta(t)$ can be derived, and the closed-loop system stability and tracking performance can be analyzed in a straightforward way.

Adaptive law. We choose the adaptive law

$$\dot{\Theta}^T(t) = -S^T P e(t) \omega^T(t), \quad (3.54)$$

where $P = P^T > 0$ satisfying $PA_0 + A_0^T P = -Q$ for $Q = Q^T > 0$ chosen, and $S_p \in R^{M \times M}$ is such that $M_s = K_p^{-1} S = M_s^T > 0$ (the knowledge of S needs to be assumed for such an adaptive law, which may be relaxed using an LDU decomposition of K_p [4, page 375]).

Stability analysis. Consider the positive definite function

$$V = e^T P e + \text{tr}[\tilde{\Theta} M_s^{-1} \tilde{\Theta}^T], \quad \tilde{\Theta} = \Theta - \Theta^*, \quad (3.55)$$

and derived its time-derivative as

$$\begin{aligned} \dot{V} &= 2e^T(t)P(A_0 e(t) + K_p \tilde{\Theta}^T \omega(t)) - 2\text{tr}[\tilde{\Theta} M_s^{-1} S^T P e(t) \omega^T(t)] \\ &= -e^T(t)Qe(t) + 2e^T(t)K_p \tilde{\Theta}^T(t)\omega(t) - 2\omega^T(t)\tilde{\Theta} M_s^{-1} S^T P e(t) \\ &= -e^T(t)Qe(t), \end{aligned} \quad (3.56)$$

Hence, $e(t) \in L^2$ for $e(t) = y(t) - y_m(t)$, and $e(t)$ and $\tilde{\Theta}(t) = \Theta(t) - \Theta^*$ are bounded, and so are $y(t)$ and $\Theta(t)$. It can be further shown that $u(t)$ is bounded, and $\lim_{t \rightarrow \infty} e(t) = 0$.

3.4.4 Asymptotic Tracking Performance

The control objective is to ensure closed-loop signal boundedness and asymptotic output tracking: $\lim_{t \rightarrow \infty} (y(t) - y_m(t)) = 0$, without the knowledge of the equivalent reference system input $r_m(t) = \xi_m(D)G_m(D)[u_m](t)$ as $G_m(D)$ is unknown for the reference model system (3.2) or (3.41), which can be achieved by the control laws (3.11) and (3.22).

The control scheme with (3.11) has the terms $K_{21}^T x_m(t) + K_{22} u_m(t)$ replacing $K_2 r_m(t)$ in a standard adaptive state feedback control scheme [4]. Similarly, the scheme with (3.22) has the terms $\Theta_{31}^T x_m(t) + \Theta_{32} u_m(t)$ replacing $\Theta_3 r_m(t)$ in an adaptive output feedback control scheme [4]. Since these terms are all bounded, the closed-loop system signal boundedness is ensured. Then, the L^2 properties in Lemma 3.1, ensure the L^2 property of the tracking error $e(t) = y(t) - y_m(t)$ and the asymptotic convergence property of $e(t)$.

3.4.5 Applications

The developed new adaptive control technique ensures that the output $y(t)$ of the plant: $D[x](t) = Ax(t) + Bu(t)$, $y(t) = Cx(t)$, tracks the output $y_m(t)$ of the reference system: $D[x_m](t) = A_m x_m(t) + B_m u_m(t)$, $y_m(t) = C_m x_m(t)$ (with known $y_m(t)$ and $u_m(t)$, and possibly $x_m(t)$) whose parameters (A_m, B_m, C_m) are unknown, while in the traditional model reference control framework, the reference model system $y_m(s) = W_m(D)[r_m](t)$ is assumed to be completely known.

An immediate application is adaptive control of a follower system with unknown parameters to follow a leader system also with unknown parameters.

The adaptive control technique, developed for the leader-follower control problem (with the reference model system with unknown parameters being the leader), can be generalized for adaptive control of multi-agent systems whose leader system parameters are unknown, in addition to the uncertainties of the follower agent systems. It is meaningful to consider the parameter uncertainties of the leader agent for an adaptive multi-agent control problem.

4 Adaptive Feedback Linearization Control

Consider a nonlinear plant of the form

$$\begin{aligned} \dot{x}(t) &= \sum_{i=1}^l \theta_i^* f_i(x) + \sum_{i=1}^M g_i(x) u_i(t) = F(x)\theta^* + G(x)u \\ y &= h(x) = [h_1(x), h_2(x), \dots, h_M(x)]^T \in R^M, \end{aligned} \quad (4.1)$$

with $\theta^* = [\theta_1^*, \theta_2^*, \dots, \theta_l^*]^T \in R^l$ unknown, and $F(x) = [f_1(x), f_2(x), \dots, f_l(x)] \in R^{n \times l}$ and $G(x) = [g_1(x), g_2(x), \dots, g_M(x)] \in R^{n \times M}$ known, and assume that the plant has a vector relative degree $\text{diag}\{\rho_1, \rho_2, \dots, \rho_M\}$ and stable zero dynamics [7].

The control objective is to design a feedback control signal $u(t) \in R^M$ for (4.1), to ensure the control system signal boundedness and asymptotic tracking of a bounded reference output signal $y_m(t) \in R^M$ by the plant output $y(t)$.

In a traditional adaptive feedback linearization control system [8], [9], [10], [11], the reference output signal $y_m(t)$ is a given signal whose certain orders of time-derivatives are assumed to be bounded and known. In our study, $y_m(t)$ is the output of a reference model system (a leader system) whose parameters are unknown.

4.1 Feedback Linearization Parametrization

We first give a review of the standard feedback linearization parametrization procedure.

Letting $\xi(s) = \text{diag}\{s^{\rho_1}, s^{\rho_2}, \dots, s^{\rho_M}\}$, and following the standard feedback linearization procedure [8], we can derive the plant expression

$$\xi(s)[y](t) = b(x) + A(x)u(t), \quad (4.2)$$

for some parametrizable $b(x) \in R^n$ and $A(x) \in R^{M \times M}$ being nonsingular.

With $\hat{A}(x)$ and $\hat{b}(x)$ being the estimates (to be parametrized) of $A(x)$ and $b(x)$, we choose the adaptive linearizing control law

$$u = (\hat{A}(x))^{-1}(v - \hat{b}(x)). \quad (4.3)$$

Then, we have $\hat{A}(x)u = v - \hat{b}(x)$, and

$$\begin{aligned} & b(x) + A(x)u \\ &= A(x)u - \hat{A}(x)u + v + b(x) - \hat{b}(x), \end{aligned} \quad (4.4)$$

which leads the plant expression (4.2) to

$$\xi(s)[y](t) = A(x)u - \hat{A}(x)u + b(x) - \hat{b}(x) + v. \quad (4.5)$$

For $\xi_m(s) = \text{diag}\{d_1(s), d_2(s), \dots, d_M(s)\}$ with $d_i(s) = s^{\rho_i} + \alpha_{i1}s^{\rho_i-1} + \dots + \alpha_{i\rho_i-1}s + \alpha_{i\rho_i}$ stable, $i = 1, 2, \dots, M$, and $v = [v_1, v_2, \dots, v_M]^T$, we choose

$$v_i = y_{mi}^{(\rho_i)} + \alpha_{i1}(y_{mi}^{(\rho_i-1)} - \widehat{L_f^{\rho_i-1}h_i(x)}) + \dots + \alpha_{i\rho_i-1}(y_{mi}^{(1)} - \widehat{L_f^1h_i(x)}) + \alpha_{i\rho_i}(y_{mi} - y_i), \quad (4.6)$$

as the adaptive control law, where $\widehat{L_f^{\rho_i-1}h_i(x)} = L_f^{\rho_i-1}h_i(x), \dots, \widehat{L_f^1h_i(x)} = L_f^1h_i(x)$ are parametrized by the estimates of θ_i^* in the plant (4.1), and $y_{mi}(t)$, $i = 1, 2, \dots, M$, are the components of the reference output vector signal $y_m(t) = [y_{m1}(t), y_{m2}(t), \dots, y_{mM}(t)]^T \in R^M$, which and whose time-derivatives of certain orders as shown in (4.6) are assumed to be bounded and known.

Recall the Lie Derivatives defined as $L_f^k h_i = L_f(L_f^{k-1}h_i) = \frac{\partial L_f^{k-1}h_i}{\partial x}f$, $L_f^0 h_i = h_i$, $L_{g_j} L_f^k h_i = \frac{\partial L_f^k h_i}{\partial x}g_j$ [7]. Using the control law (4.6) in (4.4), for $e = y(t) - y_m(t) = [e_1, e_2, \dots, e_M]^T$ with $e_i = y_i - y_{mi}$, we obtain the error equation

$$\begin{aligned} & \begin{bmatrix} e_1^{(\rho_1)} + \alpha_{11}e_1^{(\rho_1-1)} + \dots + \alpha_{1\rho_1}e_1 \\ e_2^{(\rho_2)} + \alpha_{21}e_2^{(\rho_2-1)} + \dots + \alpha_{2\rho_2}e_2 \\ \vdots \\ e_M^{(\rho_M)} + \alpha_{M1}e_M^{(\rho_M-1)} + \dots + \alpha_{M\rho_M}e_M \end{bmatrix} = \tilde{b}(x) + \tilde{A}(x)u(t) \\ & + \begin{bmatrix} \alpha_{11}(y_1^{(\rho_1-1)} - \widehat{L_f^{\rho_1-1}h_1(x)}) + \dots + \alpha_{1\rho_1-1}(\dot{y}_1 - \widehat{L_f h_1(x)}) \\ \alpha_{21}(y_2^{(\rho_2-1)} - \widehat{L_f^{\rho_2-1}h_2(x)}) + \dots + \alpha_{2\rho_2-1}(\dot{y}_2 - \widehat{L_f h_2(x)}) \\ \vdots \\ \alpha_{M1}(y_M^{(\rho_M-1)} - \widehat{L_f^{\rho_M-1}h_M(x)}) + \dots + \alpha_{M\rho_M-1}(\dot{y}_M - \widehat{L_f h_M(x)}) \end{bmatrix}, \end{aligned} \quad (4.7)$$

where $y_i^{(\rho_i-1)} = L_f^{\rho_i-1} h_i(x), \dots, y_i^{(1)} = L_f^1 h_i(x)$ are parametrized by the parameters in θ^* , $\tilde{b}(x) = b(x) - \hat{b}(x)$ and $\tilde{A}(x) = A(x) - \hat{A}(x)$.

Parametrizing $b(x) = \Theta_1^{*T} \omega_1$ and $\hat{b}(x) = \Theta_1^T \omega_1$ for some known vector ω_1 and unknown parameter matrix Θ_1^* and its estimate Θ_1 , $A(x)u(t) = \Theta_2^{*T} \omega_2$ and $\hat{A}(x)u(t) = \Theta_2^T \omega_2$ for some known vector ω_2 and unknown parameter matrix Θ_2^* and its estimate Θ_2 , we express

$$\tilde{b}(x) = \tilde{\Theta}_1^T \omega_1, \quad \tilde{\Theta}_1 = \Theta_1^* - \Theta_1 \quad (4.8)$$

$$\tilde{A}(x)u(t) = \tilde{\Theta}_2^T \omega_2, \quad \tilde{\Theta}_2 = \Theta_2^* - \Theta_2. \quad (4.9)$$

Similarly, we can express the last term in (4.7) as $\tilde{\Theta}_3^T \omega_3$ for some known vector ω_3 and $\tilde{\Theta}_3 = \Theta_3^* - \Theta_3$ with some unknown parameter matrix Θ_3^* and its estimate Θ_3 . Then, denoting $\Theta^* = [\Theta_1^{*T}, \Theta_2^{*T}, \Theta_3^{*T}]^T$, $\Theta = [\Theta_1^T, \Theta_2^T, \Theta_3^T]^T$, $\tilde{\Theta} = \Theta^* - \Theta$ and $\omega = [\omega_1^T, \omega_2^T, \omega_3^T]^T$, we rewrite (4.7) as

$$\begin{aligned} & \begin{bmatrix} e_1^{(\rho_1)} + \alpha_{11} e_1^{(\rho_1-1)} + \dots + \alpha_{1\rho_1} e_1 \\ e_2^{(\rho_2)} + \alpha_{21} e_2^{(\rho_2-1)} + \dots + \alpha_{2\rho_2} e_2 \\ \vdots \\ e_M^{(\rho_M)} + \alpha_{M1} e_M^{(\rho_M-1)} + \dots + \alpha_{M\rho_M} e_M \end{bmatrix} \\ &= \tilde{\Theta}_1^T \omega_1 + \tilde{\Theta}_2^T \omega_2 + \tilde{\Theta}_3^T \omega_3 = \tilde{\Theta}^T \omega. \end{aligned} \quad (4.10)$$

Thus, we have expressed the adaptive control error system as

$$\xi_m(s)[e](t) = (\Theta^* - \Theta(t))^T \omega(t). \quad (4.11)$$

Based on such an error system, adaptive laws can be developed to update the parameter estimate $\Theta(t)$ to implement the adaptive control scheme with the control laws (4.3) and (4.6), under the stable zero dynamics condition of the plant (4.1), using the knowledge of the certain orders of derivatives of $y_m(t)$, that is, $\xi_m(s)[y_m](t)$, which is however not available in our adaptive control problem.

4.2 Leader-Follower Tracking Error Equation

Now we develop the standard adaptive feedback linearization control design, with an expanded parametrization, for the adaptive leader-follower tracking problem: the output $y(t)$ of the plant (4.1) (the follower) with unknown parameters is expected to track the output $y_m(t)$ of a leader system (a reference model system) with unknown parameters.

Reference system. Assume that $y_m(t)$ is the output of a reference model system:

$$\begin{aligned} \dot{x}_m &= f_m(x_m) + g_m(x_m)u_m \\ y_m &= h_m(x_m), \end{aligned} \quad (4.12)$$

with the vector relative degree no less than $\text{diag}\{\rho_1, \rho_2, \dots, \rho_M\}$ of the follower system (4.1), that is, for $\xi(s) = \text{diag}\{s^{\rho_1}, s^{\rho_2}, \dots, s^{\rho_M}\}$, it holds that

$$\xi(s)[y_m](t) = b_{m0}(x_m) + A_m(x_m)u_m(t), \quad (4.13)$$

for some $b_{m0}(x) \in R^n$ and $A_m(x) \in R^{M \times M}$ (which may be singular), and

$$\xi_m(s)[y_m](t) = b_m(x_m) + A_m(x_m)u_m(t), \quad (4.14)$$

for some $b_m(x) \in R^n$, where $\xi_m(s) = \text{diag}\{d_1(s), d_2(s), \dots, d_M(s)\}$ with $d_i(s) = s^{\rho_i} + \alpha_{i1}s^{\rho_i-1} + \dots + \alpha_{i\rho_i-1}s + \alpha_{i\rho_i}$ stable, $i = 1, 2, \dots, M$.

To design the adaptive control schemes, we make the following assumption:

Assumption (A4.1): the reference system (leader system) signals $u_m(t)$, $x_m(t)$ and $y_m(t)$ are known and bounded but the dynamic functions $f_m(\cdot)$, $g_m(\cdot)$ and $h_m(\cdot)$ are unknown.

Our objective is to design an adaptive control law $u(t)$ for the follower system (4.1), to ensure that all system signals are bounded, and $\lim_{t \rightarrow \infty} (y(t) - y_m(t)) = 0$, without the information of $\xi_m(s)[y_m](t)$ (except that $y_m(t)$ is available and $\xi_m(s)$ is chosen).

The control law (4.6) can be written as

$$v(t) = \xi_m(s)[y_m](t) - \hat{v}_y(x), \quad (4.15)$$

where

$$\hat{v}_y(x) = \begin{bmatrix} \alpha_{11} \widehat{L_f^{\rho_1-1} h_1}(x) + \dots + \alpha_{1\rho_1-1} \widehat{L_f^1 h_1}(x) + \alpha_{1\rho_1} y_1 \\ \alpha_{21} \widehat{L_f^{\rho_2-1} h_2}(x) + \dots + \alpha_{2\rho_2-1} \widehat{L_f^1 h_2}(x) + \alpha_{2\rho_2} y_2 \\ \vdots \\ \alpha_{M1} \widehat{L_f^{\rho_M-1} h_M}(x) + \dots + \alpha_{M\rho_M-1} \widehat{L_f^1 h_M}(x) + \alpha_{M\rho_M} y_M \end{bmatrix}. \quad (4.16)$$

Since the parameters of the dynamic functions $f_m(\cdot)$, $g_m(\cdot)$ and $h_m(\cdot)$ are unknown, the functions $b_m(x_m)$ and $A_m(x_m)$ in (4.14) are also unknown, and so is $\xi_m(s)[y_m](t)$, so that the control law (4.15) cannot be implemented.

Estimation of $\xi_m(s)[y_m](t)$. From (4.14), denoting and parametrizing

$$r_m(t) = \xi_m(s)[y_m](t) = b_m(x_m) + A_m(x_m)u_m(t) = \Theta_m^{*T} \omega_m, \quad (4.17)$$

for some unknown parameter matrix Θ_m^* and some known vector signal $\omega_m(t)$, we introduce the estimate of $r_m(t)$ as

$$\hat{r}_m(t) = \widehat{\xi_m(s)[y_m]}(t) = \Theta_m^T \omega_m, \quad (4.18)$$

where Θ_m is the estimate of Θ_m^* . We modify the control law (4.15) as

$$v(t) = \widehat{\xi_m(s)[y_m]}(t) - \hat{v}_y(x) = \Theta_m^T \omega_m - \hat{v}_y(x), \quad (4.19)$$

which, with $\tilde{\Theta}_m = \Theta_m^* - \Theta_m$, can be expressed as

$$\begin{aligned} v(t) &= -\tilde{\Theta}_m^T \omega_m + \Theta_m^{*T} \omega_m - \hat{v}_y(x) \\ &= -\tilde{\Theta}_m^T \omega_m + \xi_m(s)[y_m](t) - \hat{v}_y(x). \end{aligned} \quad (4.20)$$

Similar to (4.7)-(4.10), it follows from (4.5) and (4.20) that

$$\begin{aligned} & \begin{bmatrix} e_1^{(\rho_1)} + \alpha_{11}e_1^{(\rho_1-1)} + \cdots + \alpha_{1\rho_1}e_1 \\ e_2^{(\rho_2)} + \alpha_{21}e_2^{(\rho_2-1)} + \cdots + \alpha_{2\rho_2}e_2 \\ \vdots \\ e_M^{(\rho_M)} + \alpha_{M1}e_M^{(\rho_M-1)} + \cdots + \alpha_{M\rho_M}e_M \end{bmatrix} \\ &= \tilde{\Theta}_1^T \omega_1 + \tilde{\Theta}_2^T \omega_2 + \tilde{\Theta}_3^T \omega_3 - \tilde{\Theta}_m^T \omega_m = \tilde{\Theta}^T \omega, \end{aligned} \quad (4.21)$$

where

$$\tilde{\Theta} = \Theta^* - \Theta \quad (4.22)$$

$$\Theta^T = [\Theta_1^T, \Theta_2^T, \Theta_3^T, \Theta_m^T]^T \quad (4.23)$$

$$\Theta^{*T} = [\Theta_1^{*T}, \Theta_2^{*T}, \Theta_3^{*T}, \Theta_m^{*T}]^T \quad (4.24)$$

$$\omega = [\omega_1^T, \omega_2^T, \omega_3^T, -\omega_m^T]^T. \quad (4.25)$$

The tracking error equation (4.21) has the same form as (4.11):

$$\xi_m(s)[e](t) = (\Theta^* - \Theta(t))^T \omega(t), \quad (4.26)$$

based on which, a stable adaptive scheme can be designed, using the knowledge of the measured $e(t) = y(t) - y_m(t)$ and $\omega(t)$ and the chosen $\xi_m(s)$ formed based on the vector relative degree $\text{diag}\{\rho_1, \rho_2, \dots, \rho_M\}$ of the plant (4.1).

4.3 Adaptive Law

We rewrite (4.26) as

$$e(t) = W_m(s)[\tilde{\Theta}^T \omega](t), \quad \tilde{\Theta}(t) = \Theta^* - \Theta(t), \quad (4.27)$$

where $W_m(s) = \xi_m^{-1}(s) = \text{diag}\{w_1(s), w_2(s), \dots, w_M(s)\}$ with $w_i(s) = d_i^{-1}(s)$ stable for the chosen $\xi_m(s) = \text{diag}\{d_1(s), d_2(s), \dots, d_M(s)\}$. Letting $\tilde{\theta}_i(t) = \theta^* - \theta_i(t)$ be the i th column of $\tilde{\Theta}(t) = \Theta^* - \Theta(t)$, $i = 1, 2, \dots, M$, we express the i th component of $e(t) = [e_1(t), e_2(t), \dots, e_M(t)]^T$ as

$$e_i(t) = w_i(s)[\tilde{\theta}_i^T \omega](t), \quad i = 1, 2, \dots, M. \quad (4.28)$$

For $i = 1, 2, \dots, M$, introducing the auxiliary signals

$$\xi_i(t) = w_i(s)[\theta_i^T \omega](t) - \theta_i^T(t)\zeta_i(t) \quad (4.29)$$

$$\zeta_i(t) = w_i(s)[\omega](t), \quad (4.30)$$

we define the estimation error signals

$$\epsilon_i(t) = e_i(t) + \xi_i(t), \quad (4.31)$$

and, with (4.28)-(4.30), obtain $\epsilon_i(t) = \tilde{\theta}_i^T(t)\zeta_i(t)$.

This error equation motivates the choice of the adaptive law for $\theta_i(t)$:

$$\dot{\theta}_i(t) = \frac{\Gamma_i \zeta_i(t) \epsilon_i(t)}{m_i^2(t)}, \quad (4.32)$$

where $\Gamma_i = \Gamma_i^T > 0$, and

$$m_i(t) = \sqrt{1 + \zeta_i^T(t) \zeta_i(t)}. \quad (4.33)$$

For the positive definite function $V_i = \frac{1}{2} \tilde{\theta}_i^T \Gamma_i^{-1} \tilde{\theta}_i$, we have its time-derivative

$$\dot{V}_i = -\frac{\tilde{\theta}_i^T \zeta_i(t) \epsilon_i(t)}{m_i^2(t)} = -\frac{\epsilon_i^2(t)}{m_i^2(t)}, \quad (4.34)$$

from which we can derive the desired properties:

- (i) $\theta_i(t)$, $\dot{\theta}_i(t)$ and $\frac{\epsilon_i(t)}{m_i(t)}$ are bounded; and
- (ii) $\frac{\epsilon_i(t)}{m_i(t)} \in L^2$, and $\dot{\theta}_i(t) \in L^2$, for $i = 1, 2, \dots, M$.

These properties are crucial for the closed-loop system signal boundedness and asymptotic tracking performance: $\lim_{t \rightarrow \infty} (y(t) - y_m(t)) = 0$, which can be established using the analysis procedure for a standard adaptive feedback linearization control scheme [8], [9], [10], [11].

5 Concluding Remarks

In this paper, we have studied the extensions of the solution in [1] for the new model reference adaptive control problem in which the parameters of the reference model system are unknown.

If a dynamic system (plant) has a vector relative degree $\text{diag}\{\rho_1, \rho_2, \dots, \rho_M\}$, its output $y(t)$, with $\xi(s) = \text{diag}\{s^{\rho_1}, s^{\rho_2}, \dots, s^{\rho_M}\}$, can be expressed as

$$\xi(s)[y](t) = b(x) + A(x)u(t), \quad (5.35)$$

where $b(x) \in R^M$ and $A(x) \in R^{M \times M}$ being nonsingular.

For the linear system case, $\xi(s)$ or $\xi(z)$ can be generalized as a lower triangular polynomial matrix $\xi(D)$ (called the system interactor matrix), and $b(x) = K_0^{*T} x(t)$ and $A(x) = K_p$ for some constant matrices $K_0^* \in R^{n \times M}$ and $K_p \in R^{M \times M}$, for (5.35) with $\xi(D)$. For the nonlinear system case in the literature, the concept of $\xi(s)$ has not been generalized to a nondiagonal matrix. The modified interactor matrix $\xi_m(s)$ is $\xi_m(s) = \text{diag}\{d_1(s), d_2(s), \dots, d_M(s)\}$ with $d_i(s) = s^{\rho_i} + \alpha_{i1} s^{\rho_i-1} + \dots + \alpha_{i\rho_i-1} s + \alpha_{i\rho_i}$ stable ($i = 1, 2, \dots, M$) (for the linear system case, $\xi_m(s)$ or $\xi_m(z)$ can be a lower triangular polynomial matrix) such that $\xi_m^{-1}(s)$ ($\xi_m^{-1}(z)$) is stable.

With $\xi_m(s)$, the plant output $y(t)$ satisfies

$$\xi_m(s)[y](t) = b(x) + b_1(x) + A(x)u(t), \quad (5.36)$$

for an additional vector $b_1(x) \in R^M$ ($b_1(x) = K_{01}^{*T}x(t)$ for the linear case). If the output $y_m(t)$ of the reference model system with the state vector $x_m(t)$ and input vector $u_m(t)$ satisfies

$$\xi_m(s)[y_m](t) = b_m(x_m) + A_m(x_m)u_m(t), \quad (5.37)$$

then, the results of this paper, as the extensions of that in [1], are applicable as the solutions to the output tracking problems with unknown reference model system parameters.

For the linear continuous-time or discrete-time system case, we have

$$\xi_m(D)[y](t) = (K_0^* + K_{01}^*)^T x(t) + K_p u(t), \quad (5.38)$$

which indicates that the solution K_1^* to (3.6) is $K_1^{*T} = -K_p^{-1}(K_0^* + K_{01}^*)^T$.

References

- [1] Tao, G., “Adaptive output tracking control with reference model system uncertainties,” arXiv: 2406.05580 [eess.SY], 2024 (to appear in *Automatica*).
- [2] Tao, G., *Adaptive Control under System Structure, Reference Model and Sensor Uncertainties*, Manuscript (to be published), 2024.
- [3] Rugh, W. J., *Linear System Theory*, 2nd ed., Prentice-Hall, Englewood Cliffs, NJ, 1996.
- [4] Tao, G., *Adaptive Control Design and Analysis*, John Wiley and Sons, New York, 2003.
- [5] Wen, L. Y., G. Tao, and Y. Liu, “Multivariable adaptive output rejection of unmatched input disturbances,” *International Journal of Adaptive Control and Signal Processing*, vol. 30, no. 8-10, pp. 1203-1227, 2016.
- [6] Song, G. and G. Tao, “Partial-state feedback multivariable MRAC and reduced-order designs,” *Automatica*, vol. 129, 109622, July 2021.
- [7] Isidori, A., *Nonlinear Control Systems*, 3rd ed., Springer-Verlag, Berlin, 1995.
- [8] Sastry, S. and M. Bodson, *Adaptive Control: Stability, Convergence, and Robustness*, Prentice-Hall, Englewood Cliffs, NJ, 1989.
- [9] Sastry, S. and A. Isidori, “Adaptive control of linearizable systems,” *IEEE Transactions on Automatic Control*, vol. AC-34, no. 11, pp. 1123–1131, 1989.
- [10] Wen, L. Y., G. Tao and G. Song, “Higher-order tracking properties of nonlinear adaptive control systems,” *Systems and Control Letters*, vol. 145, Paper 104781, November 2020.
- [11] Wen, L. Y., G. Tao, H. Yang and Y. J. Zhang, “An adaptive disturbance rejection control scheme for multivariable nonlinear systems,” *International Journal of Control*, vol. 89, no. 3, pp. 594–610, March 2016.