# Experimental Study of Low-Latency Video Streaming in an ORAN Setup with Generative AI

Andreas Casparsen, Van-Phuc Bui, Shashi Raj Pandey, Jimmy Jessen Nielsen, Petar Popovski Department of Electronic Systems, Aalborg University, Denmark Emails: {aca, vpb, srp, jjn, petarp}@es.aau.dk

Abstract—Video streaming services depend on the underlying communication infrastructure and available network resources to offer ultra-low latency, high-quality content delivery. Open Radio Access Network (ORAN) provides a dynamic, programmable, and flexible RAN architecture that can be configured to support the requirements of time-critical applications. This work considers a setup in which the constrained network resources are supplemented by Generative AI (GAI) and Mobile Edge computing (MEC) techniques in order to reach a satisfactory video quality. Specifically, we implement a novel semantic control channel that enables MEC to support low-latency applications by tight coupling among the ORAN xApp, MEC, and the control channel. The proposed concepts are experimentally verified with an actual ORAN setup that supports video streaming. The performance evaluation includes the Peak signal-to-noise ratio (PSNR) metric and end-

 setup that supports video streaming. The performance evaluation includes the Peak signal-to-noise ratio (PSNR) metric and end-to-end latency. Our findings reveal that latency adjustments can yield gains in image PSNR, underscoring the trade-off potential for optimized video quality in resource-limited environments.
 *Index Terms*—Internet of Things, ORAN, Generative AI.
 I. INTRODUCTION
 The Open Radio Access Network (ORAN) paradigm [1] offers a promising solution to address challenges of network resource management due to growing demand for real-time data processing and communication in several Industry 4.0 use case scenarios. ORAN architecture empowers cellular communication with a flexible, software-defined framework and open interfaces that promote interoperability and multi-vendor participation. Unlike traditional, proprietary Radio Access Network (RAN) systems, ORAN's open architecture reduces both capital expenditure and operational expenditure [2], while enabling monitoring and control through the RAN Intelligent Controller (RIC) modules: the non-real-time (non-RT)-RIC and near-real-time (near-RT)-RIC. xApps in the near-RT-RIC correstes long-time (near-RT)-RIC. xApps in the near-RT-RIC coversees long-time (near-RT)-RIC. the non-RT-RIC oversees long-time interior inte balancing in near real-time. The non-RT-RIC oversees longterm optimization via control loops in rApps exceeding 1s cycle time [3].

The integration of video streaming supported by ORAN is driven by the increasing demand for reliable, high-quality realtime multimedia services in scenarios with constrained network resources, such as industrial IoT, remote monitoring, and smart



Fig. 1: Proposed system for GAI-based Edge and core network.

cities [4]. Traditional architectures often struggle to balance the dynamic requirements of such applications, especially under unstable environmental conditions. ORAN's open and softwaredefined framework, with its real-time control via RIC modules, enables adaptive management of network resources. In constrained networks unable to support high-quality video streaming, Generative AI (GAI) presents a solution to reduce the data rate of applications, enabling communication resource savings. Applying GAI as a mechanism to improve the video quality after lossy compression, can save communication resources. This paper presents an experimental evaluation of a system that integrates ORAN, Mobile Edge computing (MEC), and GAI to optimize video transmission under constrained network conditions. The primary objective is to present the Real-Time Interaction (RTI) design [5], which aims to optimize network efficiency to fulfill real-time transmission requirements. We focus on scenarios where the transmission channel between the transmitter (TX) and the Base Station (BS) node is either unstable or of limited capacity. Such conditions often occur when the TX consists of cameras or sensors operating with limited power or bandwidth or when positioned in locations that contribute to channel instability. Conversely, we assume that the channel from the BS to receiving users or operators is stable. While it is possible to extend this problem to consider intelligent computation at the receiver (RX) to conserve resources across the TX-BS and BS-RX links, as seen in common peer-to-peer video streaming applications such as Microsoft Teams, Zoom, or Facebook calls, these scenarios are left for future works. In the configuration presented in

This work was supported by the Villum Investigator Grant "WATER" from the Velux Foundation, Denmark

Fig. 1, we apply a one-way control channel to support endto-end traffic through centralized intelligence at a MEC server, enabling the MEC to guide the behavior of the User Equipment (UE). The setup uses GAI to present high-fidelity video to the user even when communication resources are limited. Through MEC, further end-to-end performance optimization is achieved by dynamically balancing computational and communication resources. The RIC's Service Model (SM) facilitates RAN performance monitoring via xApps, which the GAI-module at the MEC utilizes to improve communication with a UE in response to real-time conditions. A control channel is present, which the GAI module uses to guide the UE regarding how it should transmit video data.

The functionality of the control channel and its effect on the UE and video is depicted in Fig. 2, where the MEC applies upscaling if video frames are compressed, which induces extra processing latency, otherwise these are just forwarded. From the MEC, control messages are sent to UE in terms of how it should behave when transmitting the video feed, which depends on information from the xApp.

1) Related works : The advances made feasible already with the application of ORAN is obvious in terms of RAN-slicing [6], [7]. Different approaches, both based on simulation and experimental work, have shown improvements for Ultra Reliable Low-Latency Communication (URLLC) and Enhanced Mobile BroadBand (eMBB) traffic. This is done through RAN control and monitoring thereof to support different requirements. While these works clearly show control of the RAN can be used to meet latency and bitrate requirements, the joint use of MEC and RAN resources, e.g., to reduce latency, is not fully explored.

Research in semantic communication and its integration with ORAN aims to reduce information redundancy and latency, enhancing network efficiency. Previous works, such as [8], propose frameworks that incorporate semantic and goaloriented communication within ORAN by establishing new control channels to transmit semantic information between UE and Multi-access MEC platforms. This approach introduces semantic modules on both nodes, expanding the ORAN paradigm to facilitate higher-level communication processes. Similarly, authors in [9] explore the application of semantic communication and GAI in UAV networks, where GAI supports latency reduction and efficient data transmission. They argue semantic communication, empowered by GAI, enables proactive management of latency and bandwidth, where ORAN facilitates further improvements of UAV behavior through xApps and rApps. These studies underscore the potential of leveraging ORAN and semantic insights at the application layer, yet they fall short of fully addressing real-time link variability and dynamic traffic conditions. Existing solutions mainly rely on non-realtime reactive adjustments by end devices, often failing to provide prompt responses to fluctuating link quality. Our work extends these frameworks by integrating a control channel along ORAN, allowing seamless cross-layer optimization between MEC and UE, actively guiding video streaming clients based on real-time network feedback, overcoming the delay limitations in earlier approaches.



Balancing video quality and latency under varying bitrates is crucial for maintaining optimal user experience, yet current solutions have limitations in handling real-time network dynamics. For instance, [10] proposes a system that predicts bitrates and adjusts compression to network conditions, effectively reducing latency issues like freezing in cellular networks; however, it relies on bitrate prediction alone, which may not respond quickly to sudden changes. Similarly, ABR algorithms in [11] highlight the importance of adaptive bitrate adjustment in low-latency streaming but often react to changes, leading to potential delays. A server-side approach in [12] manages video quality and latency by allowing server-controlled encoding, which reduces bitrate fluctuations but limits adaptability on the client side. These approaches emphasize matching video quality to network capacity to prevent congestion and latency spikes, yet their reactive nature can degrade the viewing experience. To address these shortcomings, this paper introduces a proactive framework that leverages ORAN and GAI within a MEC environment. By integrating a control channel between MEC and UEs, our approach enables real-time adjustments based on network feedback, enhancing latency management and video quality for a more seamless streaming experience.

2) Contribution: As a key use case, we apply GAI-based video upscaling, demonstrating its potential to enhance image Peak signal-to-noise ratio (PSNR) under variable link quality. We analyze trade-offs between latency and PSNR gains, demonstrating that proactive adaptation using ORAN with a control channel enables improved performance, particularly in low-PSNR ranges. The control channel enables behavioral control of the UE's data transmission to the MEC, through semantic functionality. The primary contributions of this paper are:

- Analysis of latency vs. PSNR trade-offs enabled by GAI upscaling within an ORAN framework.
- Implementation of a control channel between MEC and UE to leverage cross-layer optimization using ORAN-provided network insights.
- Deployment of this implementation<sup>1</sup> on a physical testbed to evaluate its performance under real-world conditions.

The rest of the paper is organized as follows: Section II formulates the system model; Section III shows experimental

<sup>1</sup>Github repository with code.

setup with the results, and Section IV concludes our findings.

#### **II. SYSTEM MODEL**

Our proposed system architecture, is illustrated in Fig. 1. The MEC node houses a GAI-based video-upscaling module and an xApp, which continuously monitors RAN conditions and provides the GAI model with updated channel quality metrics, received on a millisecond basis, enabling dynamic adjustment of video transmission quality. A control channel is established following the principles in [8], through which communication between the MEC and UE enables a cross-layer optimization that instructs the UE to dynamically adjust video compression in response to real-time channel assessments. This process is depicted in Fig. 2, where "reduce" and "no reduction" control messages are sent to UE1, altering its state to either compress and transmit or simply transmit the video. When sending a video frame, UE1 includes the frame status in the header information, informing the MEC on how to process the frame-whether to upscale and forward or simply forward. Through ORAN and control channels, we enable cross-layer optimization through awareness of the status of other layers. We make a proactive solution feasible for managing dynamic physical channels while enhancing compressed video quality, allowing energy savings on the receiving user. In traditional Adaptive Bit Rate (ABR), control information passes between users in a control loop, only adjusting after buffering or freezing is observed, at which point video quality reductions would be requested [13]. The behavior is based on reacting to the observed status of the communication link and adjusting the video quality accordingly.

#### A. GAI-Based Frame Processing in MEC

To address the challenge of maintaining high video quality under latency constraints, the GAI block is responsible for enhancing downscaled video frames that are transmitted when the available birate is insufficient to support full-resolution video transmission. When the channel conditions are poor, the video frame  $\mathbf{X}(t)$  is downscaled to  $\mathbf{X}_{\text{down}}(t) \in \mathbb{R}^{m' \times n'}$ , where m' < m and n' < n. This downscaled frame is transmitted, and the MEC uses the GAI model  $G(\cdot)$  to reconstruct the original frame  $\mathbf{X}(t)$ . The reconstructed frame  $\hat{\mathbf{X}}(t)$  is produced by the GAI model as

$$\hat{\mathbf{X}}(t) = G(\mathbf{X}_{\text{down}}(t), \theta), \tag{1}$$

where  $\theta$  are the learnable parameters of the GAI model. The GAI model minimizes a loss function that measures the difference between the original and reconstructed frames, which is expressed by

$$\mathcal{L}_{\text{GAI}} = \mathbb{E}\left[ \|\mathbf{X}(t) - \hat{\mathbf{X}}(t)\|^2 \right].$$
 (2)

By deploying the GAI model at the MEC, the system can reconstruct higher-quality video frames from downscaled versions, reducing the required number of Physical Resource Blocks (PRBs) at a given channel quality while still maintaining high video quality. This approach also helps meet latency constraints by processing the enhancement at the edge, reducing the time required for the user device to perform any local processing if applying GAI itself.

We define a utility function  $f(\mathbf{X}(t), \hat{\mathbf{X}}(t))$  to measure the similarity between the original transmitted frame  $\mathbf{X}(t)$  and the received or reconstructed frame  $\hat{\mathbf{X}}(t)$ . This function could be based on various metrics such as structural similarity (SSIM) or PSNR. For this work, we use a general form as

$$f(\mathbf{X}(t), \hat{\mathbf{X}}(t)) = \frac{1}{C} \sum_{c=1}^{C} \frac{1}{mn} \sum_{i=1}^{m} \sum_{j=1}^{n} \left( 1 - \frac{|x_{ij}(t) - \hat{x}_{ij}(t)|}{MAX_I} \right),$$
(3)

where  $MAX_I$  is the maximum possible pixel value (e.g., 255 for 8-bit color channel), and C is number of color channels in a video frame. The objective is maximizing  $f(\mathbf{X}(t), \hat{\mathbf{X}}(t))$ , which increases as the similarity between  $\mathbf{X}(t)$  and  $\hat{\mathbf{X}}(t)$  improves.

## B. Modeling

Traditional upscaling methods (e.g., interpolation) are fast but limited in quality, especially when the video is highly compressed. GAI-based upscaling, in contrast, offers superior visual quality at the cost of increased processing time, We consider the availability of two methods to upscale a video to a desired resolution  $u_{trad}(\mathbf{X}(t))$  and  $u_{GAI}(\mathbf{X}(t))$  where  $u_{trad}$ applies a traditional method to upscale video frame,  $\mathbf{X}(t)$ , of size  $\mathbf{X}(t)_s$ , and is used on the receiving UE if no GAI is employed. The alternative is to apply  $u_{GAI}$  to upscale the video frame  $\mathbf{X}(t)$  at the MEC, resulting in an enhanced frame  $\hat{X}(t)$ with size  $\hat{\mathbf{X}}(t)_s$ , which is forwarded to the receiving UE. It has been shown [5] that applying GAI improves the picture quality compared to traditional upscaling when a video frame has been compressed for transmission. We build on these findings and analyze the trade-off, particularly in terms of latency.

The latency model for the traditional approach is as follows:

$$L_{\text{trad}} = t_{\text{RAN}}(\mathbf{X}(t)) + t_{\text{CN}}(\mathbf{X}(t)) + t_{\text{UE2}}(\mathbf{X}(t))$$
(4)

where  $t_{\text{RAN}}(\mathbf{X}(t))$  represents the time to transmit  $\mathbf{X}(t)$  over the RAN Uplink (UL) channel,  $t_{\text{CN}}(\mathbf{X}(t))$  reflects the time required to pass through the Core Network (CN), and  $t_{\text{UE2}}(\mathbf{X}(t))$  denotes the Downlink (DL) latency for the receiving UE, including further processing. This processing includes upscaling of the video frame if it has been compressed.

In addition to the above model in Eq (4), our GAI-based approach includes further steps:  $t_{\text{MEC}}(\mathbf{X}(t)) + t_{\text{CN}}(\hat{\mathbf{X}}(t))$ , accounting for MEC processing to improve frame quality from X(t) to f', resulting in an enhanced frame size  $\hat{\mathbf{X}}(t)_s$ . Thus, the total latency for the GAI-based upscaling is:

$$L_{\text{GAI}} = t_{\text{RAN}}(\mathbf{X}(t)) + t_{\text{CN}}(\mathbf{X}(t)) + t_{\text{MEC}}(\mathbf{X}(t))t_{\text{CN}}(\hat{\mathbf{X}}(t)) + t_{\text{UE2}}(\hat{\mathbf{X}}(t))$$
(5)

In our system, the GAI method activates whenever the channel is in a poor state, indicated by a low channel Signal-to-Noise-Ratio (SNR) and thus a limited bitrate. Otherwise, video frames are simply passed through the MEC without additional processing, meaning  $\mathbf{X}(t) = \hat{\mathbf{X}}(t)$ .



III. EXPERIMENTAL RESULTS

To evaluate our proposed methodology, we extended the ORAN experimental platform proposed in [14]. We analyze the impact our GAI-upscaling solution has on the end-to-end latency of the video stream, and how it behaves in a live setting in our testbed. We evaluate the performance of the traditional and GAI upscaling methods in terms of video frame PSNR and the end-to-end latency of video frames. We conduct experiments employing the MOB dataset [15], specifically scrutinizing a random selection of 50 videos from the dataset.

## A. Experimental Setup

The experimental platform we evaluate our method on can be seen in Fig. 3. The RAN is orchestrated via the OpenAirInterface [16] for the base station where we deployed an eNB. For the UEs srsRAN [17] is used, and open5gs [18] for the core network functions. The RIC is implemented from the FlexRIC project [19]. Clocks on the involved computers are synchronized using Chrony to ensure sub-ms level latency measurements. We utilize a computer equipped with augmented processing power and a dedicated Graphical Processing Unit (GPU), NVIDIA RTX 4080, which we refer to as our MEC, to facilitate the execution of the GAI model. Within our experimental setup, TX's traffic is directed to the MEC.

In cases where the picture quality has been compromised (caused by a reduced channel quality), the RealSR module [20] running in the MEC is employed to enhance the video quality before forwarding to the receiving UE as seen in Fig. 3 to maintain the high-quality real-time experience to users. Otherwise, the video feed is forwarded without modifications. To have a fair representation of periods where the GAI module is applied, we modified the TX UE to have a time-varying transmit power, causing periods of alternating high and low UL Modulation and coding scheme (MCS). This directly causes improved and reduced bitrate availability of the UE, respectively. The channel switches every 15 seconds, where the system itself is unaware of this and acts according to the observed channel status through fresh data reports via the xApp.



Fig. 4: CDF of PSNR under different resolution factor ( $\epsilon$ ).

To acquire end-to-end latency in our system, we developed two programs based on Python to transmit and receive the video stream. These are placed on UE1 and UE2, to represent a video streaming scenario. Regarding functionalities, we integrate a control channel in the program on UE1, which allows the MEC to control how UE performs compression and reduces video resolution. For our comparison, UE2 also has the option to apply traditional upscaling if the resolution is reduced upon reception of the video. We place these programs on the respective UEs. For data processing and performance analysis, the program on UE1 logs when a video frame is available before size reduction. Upon reception at UE2, the program receiving video frames, logs the timestamp after resizing the video frame by traditional means, if applicable. During this, the GAI-module logs the channel SNR every 1 millisecond through the xApp. We save these for further analysis of our system, but these are in the live setting, what the GAI-module uses to instruct UE1 what to do.

#### B. Results

Fig. 4 illustrates the CDF of PSNR between received and transmitted frames by deploying our strategy (*GAI-based*) versus the *Traditional* scheme (normal transmit and receive frames) under different resolution factor ( $\epsilon$ ). These factors are used to compress the video images, reducing the image resolution by the specified factor. Specifically, with  $\epsilon = 0.2$ , there are 60% frames of *Traditional* with a PSNR below 25 dB. Thanks to the advanced *GAI-based*, the proposed architecture provides less than 20% of the frames having a PSNR below 25 dB. This result confirms that integrating GAI into the ORAN network enhances PSNR efficiency while demonstrating how the ORAN framework leverages innovative techniques to create a flexible architecture adaptable to real-time 6G applications.

To study the latency, we have sent the random assortment of 50 videos from [15] through our ORAN testbed 10 times each. Fig. 5 illustrates the performance of the two considered scaling methods as well as a *No scaling* baseline. The *GAIbased* scaling is applied to images with reduced resolution, which happens as a result of what the GAI-module instructs UE1 to do, dictated by the ORAN information. The *Traditional* scaling also uses the control channel from the GAI-module and ORAN information to guide the usage of compression. The offset between the curves is due to 1) GAI processing time and 2) the video frame of *Traditional* scaling will send a smaller



data packet to the RX UE, which is upscaled locally, but GAIbased upscaling happens in the MEC and, therefore, always sends data packets of the same size to the RX UE, causing some small increases in the latency from DL transmissions. The No scaling curve initially follows the GAI-based scaling, since a similar downlink latency from MEC to UE2 is experienced. The large tail of high latency values shows that buffering is occurring caused by the changes in link quality.

Fig. 6 shows a time-series view of both video frame PSNR and channel SNR for the two considered scaling methods for a part of a considered video. In the first and last part, where the channel SNR is relatively low, the PSNR of the GAIbased scaling is greater than Traditional scaling. This effectively improves the image quality, compared to the traditional strategy. While we have illustrated how GAI can be used in collaboration with ORAN to find new tradeoff opportunities for latency and application-level key performance indicators such as image similarity, it does not fully encompass the actual impact and improvement of latency. In the Traditional setting, we also apply tools from the proposed control channel and data acquired from ORAN, showing how applications at the edge can support video-streaming. As previously stated, realistically, other application-layer methods would be employed to handle ABR. If not addressed correctly, this may cause freezing of the feed as congestion occurs. Our analysis has not fully covered the area of utilizing the control channel compared to ABR but rather addressed how a control channel along ORAN and the GAI module can be applied to support the communication channel and add new features and opportunities through GAI to support end-to-end application.

# **IV. CONCLUSION**

This work explored how a control channel between Mobile Edge computing (MEC) and User Equipment (UE) can enhance video streaming via Open Radio Access Network (ORAN) support, particularly through Generative AI (GAI)based video upscaling at the MEC node. By strategically sacrificing some latency, we demonstrated improvements in video quality through GAI upscaling. A key distinction of our approach is that, unlike traditional application-based control, the control channel enables proactive adaptation to changing channel conditions. This responsiveness, enabled by ORAN and cross-layer control, outpaces conventional Adaptive Bit Rate (ABR) approaches, which rely on reactive birate adjustments. Our findings underscore the significance of integrating ORAN and control channels for cross-layer optimization between the Radio Access Network (RAN), application, and MEC. This setup supports real-time decision-making at the UE, improving network efficiency and video quality.

#### REFERENCES

- [1] M. Polese et al., "Understanding o-ran: Architecture, interfaces, algo-rithms, security, and research challenges," IEEE Commun. Surv. Tutor., vol. 25, no. 2, pp. 1376-1411, 2023.
- A. K. U and G. Gundu Hallur, "Economic and technical implications of implementation of openran by "rakuten mobile"," in *Proc. DASA*, 2022, pp. 959-964.
- [3] M. Polese *et al.*, "Understanding o-ran: Architecture, interfaces, algorithms, security, and research challenges," *IEEE Commun. Surv. Tutor.*, 2023.
- [4] B. Agarwal et al., "Qoe-driven optimization in 5g o-ran-enabled hetnets for enhanced video service quality," IEEE Commun. Mag., vol. 61, no. 1, pp. 56–62, 2023. V-P. Bui *et al.*, "The role of game networking in the fusion of physical
- [5] and digital worlds through 6g wireless networks," IEEE Commun. Mag.,
- pp. 1–8, 2024.
  [6] D. Johnson *et al.*, "Nexran: Closed-loop ran slicing in powder-a top-to-bottom open-source open-ran use case," in *Proceedings of the 15th* ACM Workshop on Wireless Network Testbeds, Experimental evaluation & *CHaracterization*, 2022, pp. 17–23. [7] R. Wiebusch *et al.*, "Towards open 6g: Experimental o-ran framework
- for predictive uplink slicing," 2023.
- [8] E. C. Strinati *et al.*, "Goal-oriented and semantic communication in 6g ai-native networks: The 6g-goals approach," *arXiv preprint arXiv:2402.07573*, 2024.
  [9] Z. Kaleem *et al.*, "Emerging trends in uavs: From placement, semantic
- communications to generative ai for mission-critical networks," IEEE Trans. Consum. Electron., 2024.
- Y. Li et al., "Fleet: Improving quality of experience for low-latency live [10] video streaming," IEEE Trans. Circuits Syst. Video Technol., vol. 33, no. 9, pp. 5242–5256, 2023. [11] B. Taraghi *et al.*, "Lll-cadvise: live low-latency cloud-based adaptive
- video streaming evaluation framework," IEEE Access, vol. 11, pp. 25723-25734, 2023
- [12] R. Belda et al., "A dash server-side delay-based representation switching solution to improve the quality of experience for low-latency live video streaming," *Computer Networks*, vol. 235, p. 109961, 2023.
- [13] J. Kua et al., "A survey of rate adaptation techniques for dynamic adaptive streaming over http," IEEE Commun. Surv. Tutor., vol. 19, no. 3, pp. 1842–1866, 2017. V.-P. Bui, S. R. Pandey, A. Casparsen, F. Chiariotti, and P. Popovski,
- [14] "The role of game networking in the fusion of physical and digital worlds through 6g wireless networks," *IEEE Communications Magazine*, 2024.
- [15] S. H. Ahmed, M. J. Khan, H. Qaisar, and G. Sukthankar, "Malicious or benign? towards effective content moderation for children's videos, arXiv preprint arXiv:2305.15551, 2023.
- [16] OpenAirInterface. [Online]. Available: https://gitlab.eurecom.fr/oai/ openairinterface5g srSRAN. [Online]. Available: https://github.com/srsran/srsRAN\_4G
- [17]
- Open5GS. [Online]. Available: https://github.com/open5gs [18]
- [19] Flexric. [Online]. Available: https://gitlab.eurecom.fr/mosaic5g/flexric
- X. Ji et al., "Real-world super-resolution via kernel estimation and noise injection," in Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. [20] Workshops, 2020, pp. 466-467.