# TAME: TEMPORAL AUDIO-BASED MAMBA FOR ENHANCED DRONE TRAJECTORY ESTIMATION AND CLASSIFICATION

Zhenyuan Xiao, Huanran Hu, \*Guili Xu, Junwei He

College of Automation Engineering, Nanhang University, China

# ABSTRACT

The increasing prevalence of compact UAVs has introduced significant risks to public safety, while traditional drone detection systems are often bulky and costly. To address these challenges, we present TAME, the Temporal Audio-based Mamba for Enhanced Drone Trajectory Estimation and Classification. This innovative anti-UAV detection model leverages a parallel selective state-space model to simultaneously capture and learn both the temporal and spectral features of audio, effectively analyzing propagation of sound. To further enhance temporal features, we introduce a Temporal Feature Enhancement Module, which integrates spectral features into temporal data using residual cross-attention. This enhanced temporal information is then employed for precise 3D trajectory estimation and classification. Our model sets a new standard of performance on the MMUAD benchmarks, demonstrating superior accuracy and effectiveness. The code and trained models are publicly available on GitHub https://github.com/AmazingDay1/TAME.

*Index Terms*— Anti-UAV, Audio, Trajectory Estimation, Classification, Mamba.

# 1. INTRODUCTION

Compact unmanned aerial vehicles (UAVs) are popular for their portability, ease of use, and affordability, making them valuable in fields such as transportation [1], photography [2, 3], search and rescue [4, 5]. However, these same features also make them difficult to detect when used maliciously, posing threats to air traffic control and security and being exploited in warfare and border drug smuggling, as shown in Fig. 1.

Existing anti-UAV detection methods often rely on singlemodality techniques [6–11], such as radio signals, radar, or images, but these approaches can be error-prone, particularly due to limitations in radar cross section [12–14] or pixel size [15]. While some methods attempt to overcome these issues through multi-modal fusion [16, 17], combining inputs like multi-spectral images and audio data, they often rely on unrealistic assumptions [18], such as perfect targeting or high vantage points, making them less practical in real-world scenarios. Audio, however, presents a distinct advantage by



providing reliable information about the direction [19, 20], type, and distance of sound sources [21, 22], which is largely unaffected by environmental conditions. This is particularly useful given the significant noise generated by UAVs, making them easier to detect through audio [16]. Recognizing these benefits, recent studies [17] have begun to advocate for integrating audio-based solutions to improve UAV detection accuracy.

In response to these challenges, we propose a novel anti-UAV model using audio, called Temporal Audio-based Mamba for Enhanced Drone Trajectory Estimation and Classification (TAME), which utilizes the selective state-space model (SSM) [23] to effectively process temporal sequences in audio data for UAV detection. This model enables omnidirectional 3D spatial area detection, addressing the limitations of current methods that are primarily focused on classification, tracking, and position estimation using visual data. While effective, traditional multi-modal fusion approaches demand high computational power, which limits their feasibility for mobile or wearable applications. By leveraging the efficiency of SSM, TAME offers a more practical solution for accurate and efficient UAV detection, especially in challenging real-world environments. Our contributions are summarized as follows:

- 1. We propose the first temporal-spectral mamba for feature extraction, using learnable patches to capture and enhance differential features, effectively mapping the temporal and spectral dynamics of sound propagation.
- We propose the Temporal Feature Enhancement Module, which integrates spectral and temporal audio features with cross-attention and uses residual connections and learnable patches to enhance trajectory estimation and classification.





3. We benchmarked against SOTA methods, achieved the best results in all challenging conditions, and made our solution open-source.

# 2. METHOD

In this section, we introduce TAME, an end-to-end architecture for UAV trajectory estimation and classification using audio. The overall architecture is illustrated in Fig. 2. TAME consists of the temporal spectral mamba (TSMamba) backbone, the temporal feature enhancement (TFE) neck, and the detection head. TSMamba takes the mel-spectrogram of audio as input, extracts temporal and spectral features using Temporal Mamba (TMamba) and Spectral Mamba (SMamba), respectively, and integrates these features through TFE, before sending them to the detection head for final output. TMamba extracts the temporal difference of arrival as a feature, while SMamba captures spectral attenuation as a feature.

## 2.1. Temporal Spectral Mamba

Audio features are extracted by TSMamba, as shown in Fig. 2. Let \* denote the temporal (t) or spectral (s) axis. Denote  $\kappa$  as the number of microphone channels, R as the temporal width of the spectrogram, S as the spectral height, W is the width of the patch, and H as the height of the patch. To extract audio features, multi-channel audio is converted into mel-spectrograms  $\chi \in \mathbb{R}^{\kappa \times R \times S}$ , which serve as the input to our model. As the standard Mamba is a 1D sequence model, the spectrogram is split and flattened along the temporal and spectral axis to obtain  $\mathbf{p}_*$ , which consists of the temporal patch sequence  $\mathbf{p}_t \in \mathbb{R}^{\tilde{J} \times (\kappa WS)}$  and the spectral patch sequence  $\mathbf{p}_s \in \mathbb{R}^{J \times (\kappa RH)}$ . Inspired by ViT [24], we append learnable tokens  $\mathbf{c}_*$  in both temporal and spectral directions. These tokens are utilized by selective SSM to summarize the temporal difference and spectral attenuation features of the entire patch sequence. To utilize those tokens,  $\mathbf{p}_*$  is linearly projected to a vector of size D, and position embeddings  $\mathbf{E}_{pos} \in \mathbb{R}^{(J+1) \times D}$  are added. With the linearly



Fig. 3: Temporal Feature Enhancement Module projected vector, we can generalize the overall feature vector **X**<sub>\*</sub>:

$$\mathbf{X}_* = [\mathbf{p}_*^1 \mathbf{W}; \mathbf{p}_*^2 \mathbf{W}; ...; \mathbf{p}_*^J \mathbf{W}; \mathbf{c}_*] + \mathbf{E}_{pos}$$
(1)

Non-overlapping convolutions are employed for patch splitting. For the temporal patch split (horizontal), the height is kept the same as the spectrogram, and TMamba scans from left to right along the temporal axis to extract the temporal difference of the arrival, capturing sound propagation feature. For the spectral patch split (vertical), the width is kept the same as the spectrogram, and SMamba scans from top to bottom along the spectral axis to extract global spectral attenuation features. Both TMamba and SMamba are composed of selective SSM. The selective SSM fuses audio features from the previous patch with those of the current patch.

## 2.2. Temporal Feature Enhancement

In the TSMamba feature backbone, differences between patch features are filtered. The propagation time of sound correlates with distance. When scanning each patch from left to right, different spectrograms exhibit varying degrees of attenuation at the same distance. Thus, temporal features encode both location and some category information. While the spectral features capture global spectral ratios over time and also encode category information. Simultaneously using both features can lead to information redundancy, negatively impacting the final outcome. Therefore, we design a Temporal Feature Enhancement (TFE) module, as shown in Fig. 3.

Modality	Network	Light				Dark				APE	$\overline{\text{Acc}}(\%)$		
		$D_x$	$D_y$	$D_z$	APE	Acc(%)	$D_x$	$D_y$	$D_z$	APE	Acc(%)		
Visual	VisualNet [21]	0.24	0.39	0.32	0.65	<u>99.7</u>	1.98	6.10	8.13	11.45	11.3	6.05	55.5
	DarkNet [26]	0.23	0.46	0.23	<u>0.63</u>	100	1.84	5.50	4.57	8.31	25.9	4.47	63.0
Audio-Visual	TalkNet [22]	0.31	0.69	0.44	0.99	100	1.13	3.39	3.92	5.82	47.4	3.41	73.7
	AV-PED [21]	0.31	0.50	0.59	0.97	98.5	0.58	1.54	2.26	3.13	80.7	2.01	89.6
	AV-FDTI [17]	0.13	<u>0.31</u>	0.38	0.58	99.6	<u>0.35</u>	1.06	<u>1.10</u>	<u>1.89</u>	88.3	1.24	<u>94.0</u>
Audio	AudioNet [21]	0.60	1.76	1.59	2.80	79.8	0.60	1.76	1.59	2.80	79.8	2.80	79.8
	DroneChase [16]	0.54	1.59	1.51	2.64	80.6	0.54	1.59	1.51	2.64	80.6	2.64	80.6
	TAME(Ours)	0.11	0.30	0.34	0.55	98.0	0.11	0.30	0.34	0.55	98.0	0.55	98.0

Table 1: 3D trajectory estimations and accuracy for MMAUD V1 Dataset [25].

Best results are highlighted in **bold**, and second best in <u>underline</u>. This notation is used throughout the paper. Overline: the mean value of day and night.

This module employs cross-attention to integrate spectral features into temporal features, enabling UAV classification and trajectory estimation solely based on temporal features. The TFE calculation is as follows:

$$TFE(\mathbf{T}, \mathbf{S}) = \mathbf{T} + \text{Attention}(q_2, \mathbf{SW}^{k_2}, \mathbf{SW}^{v_2})\mathbf{W}$$

$$q_2 = \text{Attention}(\mathbf{TW}^{q_1}, \mathbf{SW}^{k_1}, \mathbf{SW}^{v_1})$$

$$\text{Attention}(\mathbf{Q}, \mathbf{K}, \mathbf{V}) = \text{softmax}(\frac{\mathbf{QK}^{\mathrm{T}}}{\sqrt{d_k}})\mathbf{V}$$
(2)

where  $\mathbf{W} \in \mathbb{R}^{d_m \times d_k}$  represents learnable parameter matrices.  $\mathbf{T} \in \mathbb{R}^{(J+1) \times d_m}$  represents temporal features, and  $\mathbf{S} \in \mathbb{R}^{(J+1) \times d_m}$  represents spectral features. Meanwhile,  $\mathbf{Q}$ ,  $\mathbf{K}$  and  $\mathbf{V}$  are divided into n attention heads.

## 2.3. Detection Head

First, the learnable temporal token  $c_t$  is extracted from the enhanced temporal features. The token is then sent to a detector for UAV trajectory estimation and classification. The detection head consists of two heads: a trajectory prediction head and a drone classification head. Both heads utilize multilayer perceptrons (MLPs) to map outputs.

**Trajectory prediction head:** UAV audio often contains various noises that can result in inaccurate trajectory predictions. To ensure model stability against noise during training, we use L1 loss. This approach prevents the model from deviating from the expected training trajectory due to noise. The loss function is defined as follows:

$$L_{pos} = \frac{1}{N} \sum_{i=1}^{N} \left| \hat{O}_i - O_i \right| \tag{3}$$

where N denotes the total number of UAV trajectory,  $\hat{O}$  represents the ground truth 3D trajectory, and o denotes the predicted trajectory.

**Classification prediction head:** Attributes of the UAV, such as size and audio, are indicative of its category. It is

crucial for anti-UAV systems. Classification information enhances the system's ability to pinpoint the UAV's 3D coordinates. Additionally, the anti-UAV system can take appropriate actions based on the UAV type. Therefore, a classification head is designed to perform UAV classification, using crossentropy loss, defined as follows:

$$L_{cls} = -\frac{1}{N} \sum_{i=1}^{N} y_i log(p_i) \tag{4}$$

where N denotes the total number of UAV type,  $y_i$  represents the ground truth class, and  $p_i$  represents the predicted class.

Therefore, the overall training loss function is given by

$$L_{total} = L_{cls} + \gamma L_{pos} \tag{5}$$

where  $\gamma$  is the balancing factor for the multi-task loss.

#### 3. EXPERIMENT

#### 3.1. Dataset

We use the MMAUD anti-UAV dataset [25], containing images, lidar, millimeter-wave point clouds, four-channel audio, and ground truth. The UAV flight range is 7 m × 25 m × 22 m. Audio data, sampled at 48 kHz, is segmented into 0.2-second intervals and converted to mel-spectrograms (224 × 16 resolution). The dataset is split 7:3 for training and testing.

# 3.2. Experimental Setting

**Implementation Details:** The model is trained on an NVIDIA RTX 3090 GPU using Adam, with a batch size of 64, a learning rate of 0.0001, and 200 epochs. For patch splitting, J=16, W=4, H=1; for TSMamba, L=12; for TFE, n = 6,  $d_m = d_k = 192$ . The multi-task balance factor is  $\gamma=2$ . Brightness attenuation is applied during training/testing.



Fig. 4: Test set trajectory estimation: Red curves represent ground truth, blue curves show predicted trajectories.



Fig. 5: The confusion matrix for the classification results.

**Evaluation Metrics:** We use the L1 norm for center distances  $(Dx, Dy, D_z)$  and average trajectory error (APE) for trajectory estimation, and accuracy (Acc) for classification performance.

#### 3.3. Baseline Selections

We compare our model against several anti-UAV approaches using visual [21, 26], audio [16, 21], and audiovisual fusion [17,21,22]. The baselines include self-supervised, active speaker detection, pedestrian detection, and multi-task models, focusing on different modalities and feature extraction methods.

## 3.3.1. Trajectory Estimation and UAV Classification

Table 1 shows that TAME achieves state-of-the-art results in both  $\overline{APE}$  and  $\overline{Acc}$ , outperforming audio, visual, and audiovisual fusion methods, especially at night. TAME's ability to capture global temporal features in audio spectrograms gives it an edge over other models like DroneChase and AudioNet. While visual-based models excel during the day, their performance declines at night, and audio-visual fusion methods

**Table 2**: The ablation study of TAME with different modules and feature fusion. SFE is a spectral feature enhancement.

TMamba	SMamba	SFE	TFE	APE	$\overline{\text{Acc}}(\%)$
$\checkmark$				0.59	97.7
	$\checkmark$			0.87	95.4
$\checkmark$	$\checkmark$	$\checkmark$		0.68	96.7
$\checkmark$	$\checkmark$		$\checkmark$	0.55	98.0

struggle with lighting changes. Although attention mechanisms in AV-PED and AV-FDTI improve performance, they still fall short of TAME. This highlights the superiority of single-modal approaches like TAME in UAV trajectory estimation and classification. Fig. 4 and 5 illustrate UAV position estimates and classification results, showing that most UAVs are accurately detected, except for some cases like M300, where weak audio signals are masked by environmental noise.

#### 3.4. Ablation Study and Analysis

To verify the effectiveness of the proposed TAME, we conducted ablation experiments to assess the significance of various features and fusion methods. Table 2 demonstrates that TAME achieves the highest overall performance in both the  $\overline{APE}$  and  $\overline{Acc}$ . This improvement is attributed to the use of TFE, which enhances temporal features.

#### 4. CONCLUSION

We propose TAME, an audio-based model for detecting UAV threats that integrates spectral and temporal features for top performance in trajectory estimation and classification. Despite its effectiveness, TAME has limitations, including position estimation errors and reliance on large datasets. Future work will aim to enhance trajectory estimation and explore unsupervised methods using point cloud data.

#### 5. REFERENCES

- Muqing Cao, Kun Cao, Shenghai Yuan, Thien-Minh Nguyen, and Lihua Xie, "Neptune: nonentangling trajectory planning for multiple tethered unmanned vehicles," *IEEE Transactions* on *Robotics*, vol. 39, no. 4, pp. 2786–2804, 2023.
- [2] Fen Liu, Shenghai Yuan, Kun Cao, Wei Meng, and Lihua Xie, "Distance-based multiple noncooperative ground target encirclement for complex environments," *IEEE Transactions on Control Systems Technology*, 2024.
- [3] Xinhang Xu, Muqing Cao, Shenghai Yuan, Thien Hoang Nguyen, Thien-Minh Nguyen, and Lihua Xie, "A costeffective cooperative exploration and inspection strategy for heterogeneous aerial system," in *Proceedings of the IEEE International Conference on Control and Automation*, 2024.
- [4] Shenghai Yuan, Han Wang, and Lihua Xie, "Survey on localization systems and algorithms for unmanned systems," Unmanned Systems, vol. 9, no. 02, pp. 129–163, 2021.
- [5] Muqing Cao, Kun Cao, Xiuxian Li, Shenghai Yuan, Yang Lyu, Thien-Minh Nguyen, and Lihua Xie, "Distributed multi-robot sweep coverage for a region with unknown workload distribution," *Autonomous Intelligent Systems*, 2021.
- [6] J Zhao, G Wang, J Li, L Jin, N Fan, M Wang, X Wang, T Yong, Y Deng, Y Guo, et al., "The 2nd anti-uav workshop & challenge: Methods and results," *arXiv preprint arXiv:2108.09909*, 2021.
- [7] Jian Zhao, Jianan Li, Lei Jin, Jiaming Chu, Zhihao Zhang, Jun Wang, Jiangqiang Xia, Kai Wang, Yang Liu, Sadaf Gulshad, et al., "The 3rd anti-uav workshop & challenge: Methods and results," arXiv preprint arXiv:2305.07290, 2023.
- [8] Adnan Munir, Abdul Jabbar Siddiqui, and Saeed Anwar, "Investigation of uav detection in images with complex backgrounds and rainy artifacts," in *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, 2024.
- [9] Ye Zheng, Zhang Chen, Dailin Lv, Zhixing Li, Zhenzhong Lan, and Shiyu Zhao, "Air-to-air visual detection of microuavs: An experimental evaluation of deep learning," *IEEE Robotics and automation letters*, 2021.
- [10] Hanfang Liang, Yizhuo Yang, Jinming Hu, Jianfei Yang, Fen Liu, and Shenghai Yuan, "Unsupervised uav 3d trajectories estimation with sparse point clouds," *arXiv preprint arXiv:2412.12716*, 2024.
- [11] Allen Lei, Tianchen Deng, Han Wang, Jianfei Yang, and Shenghai Yuan, "Audio array-based 3d uav trajectory estimation with lidar pseudo-labeling," arXiv preprint arXiv:2412.12698, 2024.
- [12] Tianchen Deng, Yi Zhou, Wenhua Wu, Mingrui Li, Jingwei Huang, Shuhong Liu, Yanzeng Song, Hao Zuo, Yanbo Wang, Yutao Yue, et al., "Multi-modal uav detection, classification and tracking algorithm-technical report for cvpr 2024 ug2 challenge," arXiv preprint arXiv:2405.16464, 2024.
- [13] Guangyu Wu, Fuhui Zhou, Kai Kit Wong, and Xiang-Yang Li, "A vehicle-mounted radar-vision system for precisely positioning clustering uavs," *IEEE Journal on Selected Areas in Communications*, 2024.

- [14] Matouš Vrba, Viktor Walter, Václav Pritzl, Michal Pliska, Tomáš Báča, Vojtěch Spurný, Daniel Heřt, and Martin Saska, "On onboard lidar-based flying object detection," *IEEE Transactions on Robotics*, 2024.
- [15] Yanyi Lyu, Zhunga Liu, Huandong Li, Dongxiu Guo, and Yimin Fu, "A real-time and lightweight method for tiny airborne object detection," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2023.
- [16] Neel Vora, Yi Wu, Jian Liu, and Phuc Nguyen, "Dronechase: A mobile and automated cross-modality system for continuous drone tracking," in *Proceedings of the Ninth Workshop on Micro Aerial Vehicle Networks, Systems, and Applications*, 2023.
- [17] Yizhuo Yang, Shenghai Yuan, Jianfei Yang, Thien Hoang Nguyen, Muqing Cao, Thien-Minh Nguyen, Han Wang, and Lihua Xie, "Av-fdti: Audio-visual fusion for drone threat identification," *Journal of Automation and Intelligence*, 2024.
- [18] Bo Huang, Jianan Li, Junjie Chen, Gang Wang, Jian Zhao, and Tingfa Xu, "Anti-uav410: A thermal infrared benchmark and customized scheme for tracking drones in the wild," *IEEE Trans. Pattern Anal. Mach. Intell (TPAMI)*, 2023.
- [19] Yaqin Wang, Zhiwei Chu, Ilmun Ku, E Cho Smith, and Eric T Matson, "A large-scale uav audio dataset and audio-based uav classification using cnn," in *International Conference on Robotic Computing (IRC)*. IEEE, 2022.
- [20] Murtiza Ali and Karan Nathwani, "Exploiting wavelet scattering transform & 1d-cnn for unmanned aerial vehicle detection," *IEEE Signal Processing Letters*, 2024.
- [21] Yizhuo Yang, Shenghai Yuan, Muqing Cao, Jianfei Yang, and Lihua Xie, "Av-pedaware: Self-supervised audio-visual fusion for dynamic pedestrian awareness," in *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2023.
- [22] Ruijie Tao, Zexu Pan, Rohan Kumar Das, Xinyuan Qian, Mike Zheng Shou, and Haizhou Li, "Is someone speaking? exploring long-term temporal features for audio-visual active speaker detection," in *Proceedings of the 29th ACM international conference on multimedia*, 2021, pp. 3927–3935.
- [23] Albert Gu and Tri Dao, "Mamba: Linear-time sequence modeling with selective state spaces," arXiv preprint arXiv:2312.00752, 2023.
- [24] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al., "An image is worth 16x16 words: Transformers for image recognition at scale," *International Conference on Learning Representations (ICLR)*, 2021.
- [25] Shenghai Yuan, Yizhuo Yang, Thien Hoang Nguyen, Thien-Minh Nguyen, Jianfei Yang, Fen Liu, Jianping Li, Han Wang, and Lihua Xie, "MMAUD: A Comprehensive Multi-Modal Anti-UAV Dataset for Modern Miniature Drone Threats," in Proceedings of the 2024 IEEE International Conference on Robotics and Automation (ICRA). 2024, IEEE.
- [26] Alexey Bochkovskiy, Chien-Yao Wang, and Hong-Yuan Mark Liao, "Yolov4: Optimal speed and accuracy of object detection," arXiv preprint arXiv:2004.10934, 2020.