LMUNIT: Fine-grained Evaluation with Natural Language Unit Tests

Jon Saad-Falcon^{1,2*}, Rajan Vivek^{1*}, William Berrios^{1*} Nandita Shankar Naik¹, Matija Franklin¹, Bertie Vidgen¹ Amanpreet Singh¹, Douwe Kiela^{1,2}, Shikib Mehri¹

¹Contextual AI

²Stanford University, Department of Computer Science

jonsaadfalcon@stanford.edu,shikib@contextual.ai

Abstract

As language models become integral to critical workflows, assessing their behavior remains a fundamental challenge - human evaluation is costly and noisy, while automated metrics provide only coarse, difficult-to-interpret signals. We introduce natural language unit tests, a paradigm that decomposes response quality into explicit, testable criteria, along with a unified scoring model, LMUNIT, which combines multi-objective training across preferences, direct ratings, and natural language rationales. Through controlled human studies, we show this paradigm significantly improves inter-annotator agreement and enables more effective LLM development workflows. LMUNIT achieves stateof-the-art performance on evaluation benchmarks (FLASK, BigGenBench) and competitive results on RewardBench. These results validate both our proposed paradigm and scoring model, suggesting a promising path forward for language model evaluation and development.

1 Introduction

The evaluation of generative language models remains one of the most fundamental challenges in natural language processing (Jones and Galliers, 1995; Deriu et al., 2021; Smith et al., 2022; Chang et al., 2024) – it determines how we measure progress and validate improvements, and it ultimately shapes the field's trajectory. As these models transition from research prototypes to production systems, real users increasingly rely on them for critical workflows (Lin et al., 2024), creating an urgent need for evaluation methods that identify response strengths/weaknesses, ensure reliability, detect context-dependent failures, and prevent costly regressions. Yet current approaches fall short: human evaluation is expensive, noisy, and struggles to discern subtle differences among top-performing models (Hosking et al., 2023; Clark et al., 2021;



Figure 1: **Natural Language Unit Tests:** Overview of the three-step process: (1) unit test creation, (2) LMUnit-based scoring with natural language rationales, and (3) score aggregation for overall quality assessment.

Karpinska et al., 2021), while automated metrics compress the rich, multi-dimensional nature of response quality into coarse, difficult-to-interpret scores (Stent et al., 2005; Liu et al., 2016) that rely on implicitly learned, often biased evaluation criteria (Dubois et al., 2024a; Shankar et al., 2024; Zhang et al., 2024a). As models become more capable and deeply integrated into essential workflows, it is imperative that our evaluation methodologies evolve in tandem, empowering LLM practitioners to reliably **detect subtle failures**, meaningfully **distinguish among top-performing systems**, and **generate actionable insights** that drive sustained

^{*}Co-first author.

improvements in capabilities.

We focus on one of the most critical challenges in evaluating language models: measuring response quality. Defining "response quality" is inherently complex - what constitutes a good response depends on multiple factors, including factual accuracy, logical coherence, and alignment with user-specific objectives, among other dimensions, all of which vary by domain, application, style, and context (Mehri and Eskenazi, 2020a; Ye et al., 2023; Krishna et al., 2023). Existing evaluation approaches struggle with this complexity, which results in an unreliable evaluation signal: (1) reference-based comparisons are ill-suited to openended scenarios and subtle failure modes where no single "correct" response exists (Liu et al., 2016; Lowe et al., 2017), (2) human evaluations become inconsistent and costly as models grow more capable and errors subtler (Walker et al., 2007; Pan et al., 2024; Christiano et al., 2023), and (3) preference models or prompted LLM judges compress nuanced assessments into opaque, coarse-grained metrics that are difficult to interpret or steer (Dubois et al., 2024b; D'Oosterlinck et al., 2024; Singhal et al., 2023). To address these limitations, we propose natural language unit tests, a paradigm that decomposes response quality into explicit, testable criteria that humans can define, refine, and guide over time (Figure 1). While this approach enhances transparency and adaptability, it introduces a key technical challenge: how to reliably score and integrate these fine-grained assessments in a manner that remains aligned with human values.

Building an effective scoring model for unit tests presents a significant challenge: it must accurately evaluate a wide range of criteria - ranging from broad notions of quality to detailed rubrics that capture intricate, context-specific requirements. Existing approaches each address part of the problem: prompted LLM judges can be instructed to consider certain criteria (Liu et al., 2023), but their accuracy is limited by generic instructionfollowing abilities and the inability to learn directly from preference data (Wang et al., 2024b; Zhong et al., 2022); preference models, while closely aligned with human judgments, lack promptability and struggle to handle more granular, humandefined criteria (Singhal et al., 2023; Lambert and Calandra, 2023). To address these challenges, we propose LMUNIT¹, a unified modeling approach

that optimizes large language models as preference models while supporting flexible, user-defined evaluation criteria. By combining diverse training signals with natural language rationales, LMUNIT achieves strong results across preference modeling, direct scoring, and fine-grained unit test evaluations, laying a robust foundation for more adaptive and transparent evaluation methodologies.

To demonstrate how our paradigm enables human stakeholders to effectively intervene and steer the assessment and LLM development process, we assess its real-world impact beyond standard offline benchmarks through human studies. First, in a controlled annotation study, expert raters achieved substantially higher inter-annotator agreement when evaluating outputs against explicit unit tests compared to standard preference annotations. Second, in a case study with LLM developers, we found that LMUNIT's transparent, test-driven evaluations enabled the identification of more errors than conventional LLM judges, demonstrating the value of the proposed paradigm.

Our key contributions include: (1) proposing the paradigm of natural language unit tests, and validating it at scale, (2) developing LMUNIT as a unified scoring model that achieves state-ofthe-art performance, (3) demonstrating improved performance with post-training of rationales, (4) showing the benefits and challenges of effective unit test creation and weighting strategies, and (5) validating our approach through human studies that demonstrate improved inter-annotator agreement and more effective LLM development workflows.

2 Related Work

2.1 Evaluation of Generative Language Models

As LLM development continues to progress, robust and interpretable evaluation methodologies become increasingly critical. While human evaluation is often considered the gold standard (Ouyang et al., 2022; Touvron et al., 2023), its cost and scalability limitations (Hosking et al., 2023; Schoch et al., 2020) have driven the development of automated approaches. These include word overlap metric (Papineni et al., 2002; Lin, 2004), embeddingbased scoring methods (Yuan et al., 2021; Zhang et al., 2019), model-based evaluations (Lowe et al., 2017; Mehri and Eskenazi, 2020b; Zhong et al., 2022; Saad-Falcon et al., 2023), reward modeling (Christiano et al., 2017; Askell et al., 2021; Kim et al., 2023), and LM judges (Zheng et al., 2023;

¹https://lmunit.contextual.ai/

Liu et al., 2023; Es et al., 2023; Ravi et al., 2024; Kim et al., 2024a; Li et al., 2024b). However, automated methods face significant limitations. They often lack interpretability and can exhibit biases that diverge from human evaluations (Shankar et al., 2024; Wang et al., 2023b; Chaudhari et al., 2024). Recent work has defined more fine-grained LM evaluators (Ye et al., 2023; Wang et al., 2024b; Ribeiro et al., 2020; Lin and Chen, 2023; Cook et al., 2024) and unified different paradigms within LM evaluation (Wang et al., 2024b; Kim et al., 2024c; Wu et al., 2023). Furthermore, for code generation tasks, LLM-based unit test generation has led to performance improvements by comparing different responses against compiler-compatible synthetic unit tests (Chen et al., 2022; Yuan et al., 2023; Saad-Falcon et al., 2024).

2.2 LM Judges

LLMs can be prompted to evaluate responses without additional training, showing high correlation with human ratings (Liu et al., 2023; Wang et al., 2023a; Fu et al., 2023; Chiang and Lee, 2023; Es et al., 2023; Kocmi and Federmann, 2023). While some approaches focus on in-context examples and evaluation instructions (Fu et al., 2023), others leverage chain-of-thought prompting (Liu et al., 2023) or fine-tune specialized judges (Saad-Falcon et al., 2023; Tang et al., 2024). However, these approaches face key limitations: poor generalization across evaluation tasks (Es et al., 2023; Saad-Falcon et al., 2023; Ravi et al., 2024) and systematic biases in position, verbosity, and self-preference (Chen et al., 2024; Pan et al., 2024; Zheng et al., 2023; Koo et al., 2023).

2.3 Reward Models

Reward models have gained widespread adoption for evaluating and aligning language models (Bradley and Terry, 1952; Christiano et al., 2017; Liu and Zeng, 2024). However, these models face fundamental challenges: low inter-annotator agreement in human preference data (e.g., 65% - 75% in early RLHF papers) (Askell et al., 2021; Ouyang et al., 2022; Wang et al., 2024a), preferences can be noisy and inconsistent (Dubois et al., 2024b), and models often learn spurious correlations like favoring longer responses (Lambert and Calandra, 2023; Singhal et al., 2023; Dubois et al., 2024a). Recent advances have shown promise in addressing these limitations: Helpsteer-2 (Wang et al., 2023c) demonstrated improved performance through higher-quality preference data collection, while GenRM-COT (Zhang et al., 2024b) leveraged chain-of-thought reasoning for more reliable evaluation. Despite these improvements, challenges with reward underspecification and alignment persist (Eisenstein et al., 2023; Chaudhari et al., 2024).

2.4 Fine-Grained Evaluators

Breaking down complex evaluation problems into simpler components has been a foundational principle in NLP evaluation (Walker et al., 2000), and remains central to solving challenging problems with language models (Saha et al., 2024). While some approaches use fixed evaluation dimensions (Liu et al., 2016; Lowe et al., 2017; Zhong et al., 2022), the emergence of more flexible language models has enabled more dynamic, fine-grained evaluation criteria (Mehri and Eskenazi, 2020a; Lin and Chen, 2023; Ye et al., 2023; Kim et al., 2024b). However, pre-defining criteria likely won't generalize well to real-world settings (Shankar et al., 2024). Most similar to our proposed paradigm is CheckList (Ribeiro et al., 2020), which introduced a structured, behavioral testing paradigm for NLP models, and TICK (Cook et al., 2024), which employed model-generated test criteria to demonstrate the benefits of decomposition. Our work builds on these foundational concepts while extending them in key ways: we train a dedicated scoring model that synthesizes multiple training signals for more accurate and scalable fine-grained evaluation, we conduct broader and more rigorous evaluations across diverse benchmarks, and we validate our paradigm through human studies.

2.5 Unified Evaluators

Recent work has focused on unifying different evaluation paradigms. DJPO (Wang et al., 2024b) improves human correlation by training LM judges through preference optimization (Rafailov et al., 2023), while Prometheus (Kim et al., 2024a,c) combines direct assessment and pairwise ranking capabilities through model weight merging. These approaches, along with fine-grained reward functions (Wu et al., 2023), show promise in both human and automatic evaluations.

Our work, LMUNIT, extends these unified approaches while addressing their key limitations. While previous work has made progress in combining different evaluation paradigms, they still face challenges in interpretability, generalization, and fine-grained control. LMUNIT addresses these



Figure 2: LMUNIT Training Setup: We leverage several different data sources (direct rating, preference, unit test direct, unit test preference) along with three different loss functions, to optimize the fine-grained scoring of LMUNIT.

by decomposing evaluation into explicit testable criteria that can be defined and refined by human experts, while leveraging the strengths of both LM judges (natural language understanding, flexible criteria) and reward models (precise scoring, preference learning). This enables more reliable, interpretable, and actionable evaluation that can adapt to diverse real-world requirements.

3 LMUNIT Methodology

To enable reliable scoring of natural language unit tests, we develop LMUNIT, a unified modeling approach that combines multi-objective training with natural language rationale generation. The key challenge lies in effectively integrating diverse training signals while maintaining both high accuracy and interpretable outputs. Here we detail our approach to addressing this challenge through careful problem formulation, synthetic data generation, and our training methodology.

3.1 Problem Formulation

The core challenge in language model evaluation is developing scoring models that can reliably evaluate responses against specific criteria while providing interpretable reasoning. Our formulation centers on unit tests: given a unit test u, prompt p, and response r, we train models to generate both rationales and scores through the mapping $f(u, p, r) \rightarrow$ rationale, score.

Our approach builds on two existing forms of evaluation data: direct rating data $(p,r) \rightarrow \text{score}$

and preference data $(p,r_1,r_2) \rightarrow$ preference. We extend these into unit test-based formats:

- 1. Unit test direct data: $(u, p, r) \rightarrow$ score or $(u, p, r) \rightarrow$ rationale, score
- 2. Unit test preference data: $(u, p, r_1, r_2) \rightarrow \text{pref}$ or $(u, p, r_1, r_2) \rightarrow \text{rationale}_1$, rationale₂, pref

This formulation leverages two complementary data sources: naturally occurring preference and rating data to capture human preferences and calibrate against absolute quality scales, alongside synthetic data that enables fine-grained evaluation of specific criteria with interpretable rationales. At inference time, LMUNIT can flexibly operate with or without rationale generation.

3.2 Synthetic Data Pipeline

Our data generation pipeline operationalizes the unit test formulation through three key stages, producing examples scored on a 1-5 scale where higher scores indicate better satisfaction of the criteria:

1. Unit Test Generation: For each prompt, we generate diverse unit tests targeting finegrained quality criteria. To encourage focus on response-specific details, we optionally provide one or two responses during generation. We also maintain a set of coarse-grained global tests (see Table 10 for details) to ensure broad coverage of general quality dimensions.

- 2. Contrastive Response Generation: For each (u, p, r) triplet, we generate contrastive responses that vary systematically in how well they satisfy the unit test criteria. This creates rich training signal for learning fine-grained quality distinctions.
- 3. **Rationale and Score Generation**: For a subset of examples, we generate chain-of-thought rationales that explicitly reason through the evaluation criteria. Each rationale concludes with a score that must align with any existing seed data scores to maintain consistency.

We seed our synthetic data pipeline with prompts, responses, tests and scores from diverse sources including Nectar (Zhu et al., 2024), Prometheus (Kim et al., 2024a), Tulu3 (Lambert et al., 2024a), Complex Instructions (He et al., 2024), Infinity-Instruct (of Artificial Intelligence , BAAI), and HelpSteer2 (Wang et al., 2024d,c).

3.3 Training

LMUnit combines the strengths of generative judge models and classifier-based reward models through a unique multi-objective training approach. Given a unit test u, prompt p, and response r, the model outputs a sequence of rationale tokens rat = $(rat_1, ..., r_T)$ followed by a score token s. The probability distribution over possible score values $k \in 0, 1, ..., 6$ is:

$$P(s=k \mid u, p, r, \operatorname{rat}) = \operatorname{softmax}(\mathbf{h}^T \mathbf{W}_s)_k$$
 (1)

We compute a continuous score prediction through a weighted sum:

$$\hat{y} = \sum_{k=0}^{6} k \cdot P(s = k \mid u, p, r, \text{rat})$$
 (2)

The training objective combines three losses. First, SFT loss on the rationale and score tokens:

$$\mathcal{L}_{\text{sft}} = -\sum_{t=1}^{T} \log P(x_t \mid u, p, r, x_{< t}) \qquad (3)$$

where $x_{1:t}$ represents tokens in both rationale and score sequences.

Second, MSE loss on the continuous score prediction:

$$\mathcal{L}_{\rm mse} = (y - \hat{y})^2 \tag{4}$$

Third, preference loss:

$$\mathcal{L}_{\text{pref}} = -\log(\sigma(\hat{y}_1 - \hat{y}_2)) \cdot \mathbf{1}_{\{\text{pref}=y_1\}} \\ -\log(\sigma(\hat{y}_2 - \hat{y}_1)) \cdot \mathbf{1}_{\{\text{pref}=y_2\}} \\ + (\hat{y}_1 - \hat{y}_2)^2 \cdot \mathbf{1}_{\{\text{pref}=\text{tie}\}}$$
(5)

Here, σ is the sigmoid function. The final loss is a weighted combination:

$$\mathcal{L} = \alpha \mathcal{L}_{\text{sft}} + \beta \mathcal{L}_{\text{mse}} + \gamma \mathcal{L}_{\text{pref}} \tag{6}$$

3.4 Post-Training of Rationales

While our initial model learns to generate rationales through imitation learning, there is no guarantee that these rationales actually improve scoring performance. We address this by collecting pairs of desirable and undesirable rationales for direct preference optimization (Rafailov et al., 2023), training the model to prefer rationales that lead to correct scoring over those that don't. We employ several strategies for collecting these pairs. Through the Refined strategy, we collect on-policy rationales from our trained model and use the teacher to refine them through revisions (D'Oosterlinck et al., 2024) that improve scoring accuracy. With the Harmonized strategy, we provide the teacher with two rationales from our trained model from a preference pair and prompt the teacher to harmonize the rationales, ensuring that the independent reasoning traces are consistent with the relative quality of the two samples. In the Teacher-based strategy, we sample multiple rationales from the teacher on samples with known scores and use rationales with correct score outcomes as chosen samples and rationales with incorrect score outcomes as rejected. We compare these approaches in Table 4.

3.5 Bayesian Optimization of Global Unit Tests

Natural language unit tests decompose evaluation into fine-grained, interpretable criteria through K global tests that assess dimensions like accuracy, safety, and coherence. The aggregation of these individual assessments into an overall score is crucial for valid evaluation. While the standard approach would be to use uniform weighting of test scores, we investigate whether this can be improved through learned weights. Using Bayesian optimization over human preference data, we learn optimal weights $w_1, ..., w_K$ that maximize alignment between weighted test scores and human judgments. This optimization process starts from uniform weights and iteratively updates them based on agreement with held-out human preferences, demonstrating the potential of principled aggregation strategies.

4 Experiments

We conduct extensive experiments to evaluate LMUNIT and the natural language unit test

		ct Assessment	Classification		Pairwise Ranking		
Model	Flask	BiGGen-Bench	Human-Internal	InfoBench	RewardBench	LFQA	Average*
GPT-40	69.00	65.00	81.80	92.80	84.60	76.54	78.29
Claude-3.5 Sonnet	67.25	61.83	84.53	91.58	84.23	77.24	77.78
Prometheus-2-7B	47.00	50.00	75.58	48.60	72.0	72.31	60.90
Prometheus-2-8x7B	54.00	52.00	77.82	87.85	74.5	74.23	70.06
Prometheus-2-BGB-8x7B	31.00	44.00	78.57	83.87	68.3	71.54	62.87
Llama-3-OffsetBias-8B	29.00	21.00	68.15	72.15	84.0	63.08	56.22
Skywork-Critic-Llama-3.1-8B	-	-	-	-	89.0	64.23	-
SFR-LLaMA-3.1-8B-Judge	52.00	59.00	-	92.80	88.7	68.85	73.19
SFR-LLaMA-3.1-70B-Judge	66.00	65.00	-	92.58	92.7	75.00	78.50
LMUNIT _{LLaMA3.1-8B}	60.02	64.46	94.14	91.26	83.23	71.54	74.10
LMUNIT _{LLaMA3.1-70B}	72.03	67.69	93.63	89.00	91.56	76.15	79.29
LMUNIT _{LLaMA3.1-70B} -Decomposed	72.03	67.69	93.63	89.00	90.54	74.62	78.78
LMUNIT _{LLaMA3.1-70B} -Decomposed-Weighted †	72.03	67.69	93.63	89.00	93.45	76.53	79.74

Table 1: **Comprehensive Model Performance Comparison**: Evaluation results across multiple benchmarks showing model performance on various tasks. Metrics: (i) Pearson correlation coefficient for direct assessment, (ii) binary accuracy for classification tasks, and (iii) pairwise preference accuracy for pairwise comparisons. † represents our result with Bayesian optimization over pairwise benchmarks for learning global unit test weights, as described in Section 3.5. We learned dataset-level weights for LFQA and section-level weights for RewardBench by optimizing over model predictions on a 50% split of the dataset, following prior work (Wang et al., 2024d). We confirm that this technique generalizes to a held-out split of RewardBench in Table 5. Note that the Average column excludes Human-Internal scores in order to compare fairly against the non-public SFR-LLaMA baselines (as of December 2024).

paradigm. First, we evaluate the performance of LMUNIT on several evaluation benchmarks, comparing to LLMs as judges, reward models, and trained evaluation models. Next, we perform ablations to understand the impact of different methodologies, including loss functions and data mixture choices. Finally, we examine improving rationales through post-training and analyze the impact of decomposition through several unit test strategies.

4.1 Experimental Setup

4.1.1 Model Configuration and Training Data

Our training data encompasses a diverse mix of preference judgments, direct scores, and rationales across multiple sources: (i) HELPSTEER 2 (50K pairs with ratings spanning five dimensions), (ii) PROMETHEUS (10K unpaired samples with ratings), (iii) SYNTH NON-RUBRIC (11K pairs with ratings and rationales), (iv) SYNTH RUBRIC (13K unpaired samples with ratings and rationales).

We train several variants of LMUNIT initialized from instruction-tuned LLaMa-3.1 models (8B, 70B). We train our models for 2000 steps using fixed weights (i.e., $\alpha = \beta = \gamma = 1$) for the different loss components, with a 5x loss multiplier applied to the rationale samples. The training uses the Adam optimizer (Kingma and Ba, 2017) with a learning rate of 1e-6 and a cosine learning rate scheduler, using a batch size of 64 and a sequence length of 8K.

4.1.2 Evaluation Benchmarks

We evaluate our models on six evaluation benchmarks spanning different capabilities and evaluation criteria:

- **RewardBench** (Lambert et al., 2024b): A benchmark of pairwise model outputs across chat, reasoning, and safety domains. We measure agreement with human preference judgments.
- LFQA (Xu et al., 2023): A benchmark of longform question answering responses. We measure agreement with expert preference judgments.
- **BiGGen Bench** (Kim et al., 2024b): A comprehensive benchmark spanning 77 tasks across instruction-following, content refinement, grounding, and tool usage. We measure correlation with human assessment scores.
- FLASK (Ye et al., 2023): An evaluation framework covering 12 skills across logical thinking, knowledge application, problem handling, and user alignment. We measure correlation with human assessment scores.
- **InfoBench** (Qin et al., 2024): A collection of instruction-following tasks. Using the expert-validated split, we measure binary classification accuracy against expert consensus.

• Internal Unit Test Set: A targeted evaluation of 190 questions in the finance and engineering domains, with an average of five validated unit tests per question. We measure binary classification accuracy against human expert annotations.

4.2 Key Results

Our models demonstrate strong performance across diverse evaluation settings (Table 1). On direct assessment tasks, LMUNIT achieves state-of-the-art results with correlations of **72.03** on FLASK and **67.69** on BiGGen-Bench, where fine-grained evaluation is particularly important.

In aggregate, LMUNIT achieves strong overall performance with scores of 79.74 (eight weighted global unit tests) and 79.29 (single unit test), outperforming general-purpose models like GPT-4 (78.29) and Claude-3.5 Sonnet (77.78). Even our smaller LMUNIT_{LLaMA3.1-8B} variant remains highly competitive with a 74.10 average score. For pairwise ranking tasks, using unweighted global unit tests slightly decreases overall performance to 78.78 (-0.96), but LMUNIT remains stronger than all other baselines. We recover this minor performance loss through Bayesian optimization of the global unit test weights while reaching 93.45 on RewardBench (+2.91) - though we note this weighting is learned on a subset of RewardBench itself, analogous to tuning hyperparameters on the test set (following a similar experimental setup as Wang et al. (2024d)). A more rigorous analysis using a proper held-out evaluation set is provided in Section 4.3.4, confirming the generalization of this method. These strong results across direct assessment, classification, and pairwise ranking tasks validate the effectiveness of our synthetic data pipeline, training setup, and unified scoring methodology, establishing LMUNIT as a state-of-the-art model for reliable evaluation.

4.3 Ablation Studies

4.3.1 Impact of Loss Functions

Our ablation studies examine the complementary benefits of different training objectives: SFT, MSE, and preference loss. As shown in Table 2, each additional loss provides measurable improvements across our evaluation benchmarks (+0.5). While we observe incremental gains from each additional loss, there is a meaningful improvement across different evaluation scenarios, validating the effectiveness of our multi-objective training approach.

4.3.2 Data Mixture Effects

We analyze how different compositions of training data affect LMUNIT's performance to identify the most effective mixture for robust evaluation capabilities. As shown in Table 3, rubric data is essential for strong performance on fine-grained direct assessment and that our synthetic data pipeline provides dramatic performance gains (+3.52) when synthetic rubric data is incorporated. We also observe that non-rubric synthetic data is most effective as preference pairs (+4.04) rather than direct scoring data (-2.75), likely due to the improved contrastive signal.

4.3.3 Impact of Rationales

Moving beyond simple imitation learning of rationales, we examine strategies to optimize rationale generation for better evaluation. As shown in Table 4, training with rationales improves model performance even when rationales are not used at test time (+0.2). While including rationales during inference initially leads to lower scores, our post-training optimization through DPO helps recover performance, with teacher-based pairs providing the largest gains (+1.1).

4.3.4 Unit Test Decomposition Analysis

Our experiments with different unit test strategies on RewardBench (Table 5) reveal two key findings. First, global-level tests significantly outperform query-level tests across all categories, with sectionlevel learned weights achieving the strongest results (+2.4 over unweighted aggregation). Second, the performance of fine-grained query-level tests degrades substantially, particularly on harder examples, though this can be partially mitigated by placing greater weight on earlier tests (+1.5).

These results highlight both the promise and challenges of our approach: while global unit tests provide a robust foundation for evaluation, developing effective fine-grained testing criteria remains difficult. The success of weighted global unit tests, coupled with the challenges of query-level decomposition, suggests an important direction for future work in developing more sophisticated test generation and aggregation strategies.

	Direct Assessment		Classifica	ation	PairWise Ra		
Training Loss	Flask	BiGGen-Bench	Human-Internal	InfoBench	RewardBench	LFQA	Average
LMUNIT _{LLaMA3.1-8B}							
SFT	51.31	59.12	94.19	90.29	83.56	68.85	74.55
SFT + MSE	60.46	63.94	94.29	92.92	83.44	71.54	77.77
SFT + MSE + PREF	60.02	64.46	94.14	91.26	83.23	71.54	77.44
LMUNIT _{LLaMA3.1-70B}							
SFT	69.09	67.14	93.88	90.83	89.98	76.15	81.18
SFT + MSE	70.25	67.34	93.73	87.59	91.03	75.77	80.95
SFT + MSE + PREF	72.03	67.69	93.63	89.00	91.56	76.15	81.68

Table 2: **Training Loss Ablation Results**: Adding SFT, MSE, and preference loss components each contribute modest but consistent improvements to LMUNIT's performance across direct assessment (Pearson correlation), classification (binary accuracy), and pairwise ranking (preference accuracy) tasks.

		ect Assessment	Classification		PairWise Ranking		
Data Mix	Flask	BiGGen-Bench	Human-Internal	InfoBench	RewardBench	LFQA	Average
Direct only							
HS2	57.0	42.26	94.74	88.60	91.31	69.23	73.86
HS2 + SYNTH NON-RUBRIC	47.00	42.00	93.83	88.80	86.00	69.00	71.11
HS2 + PROMETHEUS	64.90	59.27	93.43	87.50	91.40	71.15	77.94
HS2+ PROMETHEUS + SYNTH RUBRIC	71.60	67.94	94.89	89.19	91.70	73.50	81.46
Preference only							
SYNTH NON-RUBRIC	65.94	62.80	92.37	91.69	80.73	66.92	76.74
HS2	59.26	44.00	94.19	87.49	90.54	69.62	74.18
HS2 + Synth Non-Rubric	64.89	62.13	93.88	87.70	91.49	69.23	78.22
Full Data Mix							
ALL	72.03	67.69	93.63	89.00	91.56	76.15	81.68

Table 3: **Training Data Mix Ablations**: Our direct-only synthetic mix with rubrics dramatically improves model performance over baselines trained on open-source data only. Our synthetic preference data also strongly improves performance even without rubrics, likely due to fine-grained contrastive signal. Training on our full data mix yields our SOTA LMUNIT model. All models are initialized with Llama-3.1-70B. HS2 refers to HelpSteer2.



Figure 3: LMUNIT Unit Test Scoring Improves Inter-Annotator Agreement on Preference Data: Instructing annotators to answer gold-standard unit tests improves inter-annotated agreement by 48% and 20% compared to pairwise judging of responses or rubric-based scoring ("Spec"), respectively.

5 LMUNIT Human Subject Studies

We conducted two studies to validate key claims about natural language unit tests: (1) Whether this paradigm, implemented through LMUNIT, provides concrete advantages over traditional LM judges for developers working on real systems, and (2) Whether decomposing evaluation into explicit criteria can improve the quality of human preference data.

5.1 Case Study with LLM Developers

To evaluate whether decomposed evaluation helps developers better understand and improve language models, we conducted a controlled study with 16 LLM researchers and engineers. Participants were asked to analyze model outputs from Arena Hard Auto (Li et al., 2024a) and a multi-domain commercial benchmark using both LMUNIT and

Training Process	Ration	ales?		Benchmarks		
	Train	Test	RewardBench	BigGenBench	Flask	Average
LMUNIT Losses	×	X	91.1	67.4	72.1	76.9
LMUNIT Losses	\checkmark	X	91.6	67.7	72.0	77.1
LMUNIT Losses	\checkmark	\checkmark	83.8	62.1	64.2	70.0
LMUNIT Losses + DPO (Harmonized)	\checkmark	\checkmark	84.4	62.0	64.6	70.4
LMUNIT Losses + DPO (Refined)	\checkmark	\checkmark	84.2	61.8	<u>65.0</u>	70.3
LMUNIT Losses + DPO (Teacher)	\checkmark	\checkmark	85.4	<u>63.1</u>	64.9	<u>71.1</u>

Table 4: Rationale Ablations: Training on rationale data improves LMUNIT_{LLaMA3.1-70B} performance with no rationales at test time, though test-time rationale generation decreases overall performance. The rationale generation can be improved by DPO post-training, with the greatest gains coming from chosen and rejected pairs teacher examples. **Bolded** numbers indicate the best overall performance, and the <u>underlined</u> numbers indicate the best performance with rationales enabled at test time.

Technique		RewardBench Subset					
reemique	Chat	Chat Hard	Safety	Reasoning	Average		
Global-Level Unit Tests							
Single Test	96.1	86.0	92.7	91.6	91.6		
Unweighted Tests	97.2	79.9	93.2	93.4	91.0		
Dataset-Level Learned Weights	95.6	84.3	93.2	95.7	92.2		
Section-Level Learned Weights	97.8	86.5	93.5	95.8	93.4		
Query-Level Unit Tests							
Single Test	92.8	78.6	84.1	83.7	84.8		
Unweighted Tests	92.8	67.6	84.6	82.1	81.8		
Exponentially Decaying Weights	93.9	72.9	84.9	81.4	83.3		

Table 5: Unit Test Decomposition: Reward Bench samples are scored according to either 8 coarse-grained global tests (see Table 10 for details) or 8 fine-grained, query-specific tests generated by Claude-3.5-Sonnet. Learned weights are computed via Bayesian optimization over the predictions of LMUNIT_{LLaMA3.1-70B} on a 50% subset of RewardBench. For decaying weights, we weigh each n_{th} unit test by 0.8^n in the order they were generated. All results are reported on a 50% held-out subset of Reward Bench. Single unit test results correspond to using only the "Is the response helpful?" global unit test or the first generated query-level test.

traditional "LLM as a Judge".

LMUNIT enabled substantially more detailed analysis: participants identified **157%** more response attributes (10.8 vs 4.2) and **131%** more error modes (7.4 vs 3.2), rating both as significantly more important than those found through LM judges. In practice, LMUNIT led to concrete improvements: 13 of 16 researchers made targeted improvements to data selection and preprocessing after identifying critical error modes, with six reporting 10+ point gains in instruction-following and reasoning tasks. Detailed examples and analysis are provided in Appendix A.2.

5.2 Reducing Noise in Human Evaluation

Human preference data is crucial for training reward models (Christiano et al., 2017; Askell et al., 2021). However, inter-annotator agreement is often low (Wang et al., 2024a), with annotators struggling to weigh different factors consistently and give reliable signal (Howcroft et al., 2020). Since reducing task ambiguity has been shown to help improve agreement (Novikova et al., 2018; Huynh et al., 2021; Rottger et al., 2022), we investigated the benefits of decomposing evaluation into explicit criteria. We conducted an experiment with 15 experienced annotators on expressing judgements with 20 queries, comparing three approaches: unstructured preference judgments (Control), standardized evaluation criteria (Specification), and unit testbased evaluation (Unit Test). The Control group selected their preferred response with no additional guidance, the Specification group assessed each response against a five-point quality specification before selecting their preferred response, and the Unit Test group answered gold-standard targeted unit tests before picking. The gold-standard unit tests were pre-written by trained human annotators to ensure quality. More details on the human-written unit tests are in Appendix A.1.

As shown in Figure 3, the Control group showed low inter-annotator reliability (Fleiss' Kappa = 0.04), while the Unit Tests group achieved substantially higher agreement (Fleiss' Kappa = 0.52), demonstrating that structured decomposition significantly improves consistency in human evaluation. Annotators chose their preferred response after completing the unit tests and 89% of the time they selected the response with the largest number of satisfied unit tests. This further shows that answering unit tests guided their preference decisions.

6 Discussion

Our experiments and analyses reveal several key insights about the effectiveness of our unit test-based evaluation framework and highlight important directions for future work:

LMUnit Shows Benefits of Unified Training: Our empirical results validate the benefits of a unified scoring approach through three key findings: combining multiple training objectives improves performance across all evaluation settings (Table 2), incorporating diverse data types enhances model capabilities (Table 3), and LMU-NIT's approach achieves state-of-the-art results on fine-grained evaluation benchmarks like FLASK and BiGGen-Bench (Table 1). These results suggest significant untapped potential in synthesizing different sources of evaluation signal – from human preferences and ratings to targeted synthetic data – particularly for fine-grained assessment tasks.

Unit Tests Enable Rich Human-in-the-Loop Evaluation: Language model evaluation frameworks should enable precise human steering while reducing noise and manual effort. Our results show this paradigm achieves both goals: structured criteria dramatically improve evaluation consistency and inter-annotator agreement (Figure 3), while offering multiple meaningful intervention points. Humans can write or refine test criteria, optimize test weights (Table 5), and guide development through decomposed feedback leading to significantly more detailed error analysis in practice (subsection 5.1). This suggests unit tests can enable deeper, more reliable human-AI collaboration in evaluation.

Rationale Post-Training Improves Task Performance: A fundamental challenge in language models is developing genuine reasoning capabilities rather than simply learning to imitate human-like explanations. While training models to generate rationales through supervised learning can produce plausible-sounding explanations, this doesn't necessarily improve their underlying ca-

pabilities. Our work demonstrates two key insights about moving beyond imitation: first, training with rationales improves model performance even when not generating them at inference time (Table 4), and second, post-training optimization of rationales for task performance rather than imitation leads to further gains. This suggests a promising direction for developing better reasoning capabilities: using rationales not just as outputs to mimic but as a trainable intermediate step that can improve task performance while maintaining interpretability and enabling human feedback. Beyond LMU-NIT, this approach can be extended to improve general-purpose model reasoning by optimizing rationales for downstream task performance rather than merely imitating ground-truth rationales.

Query-Level Unit Test Creation Remains Challenging: While our work advanced scoring and evaluation methodology, generating effective query-specific unit tests proved difficult. Global-level unit tests with learned weights significantly outperform query-level unit tests (Table 5), highlighting the need for better test generation approaches. Future work should explore end-to-end training of test generation, evaluate human-created tests at scale, and investigate when fine-grained decomposition justifies its complexity. These findings collectively point to both the promise and challenges of the unit testing paradigm for language model evaluation. The strong performance of LMUNIT demonstrates the potential of unified training approaches, while our human studies show how structured evaluation can enable more reliable and meaningful human oversight. Though challenges remain in test generation and optimal decomposition strategies, our results suggest this paradigm offers a practical path toward more reliable, interpretable, and human-aligned evaluation of language models.

7 Conclusion

This paper introduces natural language unit tests, a paradigm for language model evaluation that enables precise assessment through explicit, testable criteria. To implement this paradigm effectively, we develop LMUNIT, a unified scoring model that combines multi-objective training across preferences, direct ratings, and natural language rationales to achieve state-of-the-art performance on major evaluation benchmarks. Our results validate both the broader paradigm of decomposed evaluation and our novel scoring methodology. Looking ahead, this work opens several promising research directions: deeper integration of human feedback loops, enhanced scoring models with improved reasoning capabilities, and end-to-end training of unit test generation and scoring.

8 Acknowledgements

We are grateful to Ishan Sinha, Nikita Bhargava, and Randy White for their guidance and support throughout this project. We thank Amy Stone and Josh Pennington for managing our human annotation study and to the human annotation team at ContextualAI for their efforts. Thanks to Robby Manihani and Tanvir Bhathal for their help with developer case studies, and to Niklas Muennighoff for his helpful advice.

References

- Amanda Askell, Yuntao Bai, Anna Chen, Dawn Drain, Deep Ganguli, Tom Henighan, Andy Jones, Nicholas Joseph, Ben Mann, Nova DasSarma, et al. 2021.
 A General Language Assistant as a Laboratory for Alignment. ArXiv Preprint arXiv:2112.00861.
- Ralph Allan Bradley and Milton E Terry. 1952. Rank Analysis of Incomplete Block Designs: I. The Method of Paired Comparisons. *Biometrika*, 39(3/4):324–345.
- Yupeng Chang, Xu Wang, Jindong Wang, Yuan Wu, Linyi Yang, Kaijie Zhu, Hao Chen, Xiaoyuan Yi, Cunxiang Wang, Yidong Wang, et al. 2024. A Survey on Evaluation of Large Language Models. ACM Transactions on Intelligent Systems and Technology, 15(3):1–45.
- Shreyas Chaudhari, Pranjal Aggarwal, Vishvak Murahari, Tanmay Rajpurohit, Ashwin Kalyan, Karthik Narasimhan, Ameet Deshpande, and Bruno Castro da Silva. 2024. RLHF Deciphered: A Critical Analysis of Reinforcement Learning from Human Feedback for LLMs.
- Bei Chen, Fengji Zhang, Anh Nguyen, Daoguang Zan, Zeqi Lin, Jian-Guang Lou, and Weizhu Chen. 2022. Codet: Code generation with generated tests. *arXiv preprint arXiv:2207.10397*.
- Guiming Hardy Chen, Shunian Chen, Ziche Liu, Feng Jiang, and Benyou Wang. 2024. Humans or LLMs as the Judge? A Study on Judgement Bias. *ArXiv Preprint arXiv:2402.10669*.
- Cheng-Han Chiang and Hung-yi Lee. 2023. Can Large Language Models Be an Alternative to Human Evaluations? In Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers).
- Paul Christiano, Jan Leike, Tom B. Brown, Miljan Martic, Shane Legg, and Dario Amodei. 2023. Deep

reinforcement learning from human preferences. *Preprint*, arXiv:1706.03741.

- Paul F Christiano, Jan Leike, Tom Brown, Miljan Martic, Shane Legg, and Dario Amodei. 2017. Deep Reinforcement Learning from Human Preferences. Advances in Neural Information Processing Systems, 30.
- Elizabeth Clark, Tal August, Sofia Serrano, Nikita Haduong, Suchin Gururangan, and Noah A Smith. 2021. All That's 'Human' is Not Gold: Evaluating Human Evaluation of Generated Text. *Proceedings* of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers).
- Jonathan Cook, Tim Rocktäschel, Jakob Foerster, Dennis Aumiller, and Alex Wang. 2024. TICKing All the Boxes: Generated Checklists Improve LLM Evaluation and Generation.
- Jan Deriu, Alvaro Rodrigo, Arantxa Otegi, Guillermo Echegoyen, Sophie Rosset, Eneko Agirre, and Mark Cieliebak. 2021. Survey on Evaluation Methods for Dialogue Systems. *Artificial Intelligence Review*, 54:755–810.
- Karel D'Oosterlinck, Winnie Xu, Chris Develder, Thomas Demeester, Amanpreet Singh, Christopher Potts, Douwe Kiela, and Shikib Mehri. 2024. Anchored Preference Optimization and Contrastive Revisions: Addressing Underspecification in Alignment. *ArXiv Preprint arXiv:2408.06266*.
- Yann Dubois, Balázs Galambosi, Percy Liang, and Tatsunori B Hashimoto. 2024a. Length-Controlled AlpacaEval: A Simple Way to Debias Automatic Evaluators. *ArXiv Preprint arXiv:2404.04475*.
- Yann Dubois, Chen Xuechen Li, Rohan Taori, Tianyi Zhang, Ishaan Gulrajani, Jimmy Ba, Carlos Guestrin, Percy S Liang, and Tatsunori B Hashimoto. 2024b. AlpacaFarm: A Simulation Framework for Methods that Learn from Human Feedback. *Advances in Neural Information Processing Systems*, 36.
- Jacob Eisenstein, Jonathan Berant, Chirag Nagpal, Alekh Agarwal, Ahmad Beirami, Alexander Nicholas D'Amour, Krishnamurthy Dj Dvijotham, Katherine A Heller, Stephen Robert Pfohl, and Deepak Ramachandran. 2023. Reward Model Underspecification in Language Model Alignment. In *NeurIPS 2023 Workshop on Distribution Shifts: New Frontiers with Foundation Models.*
- Shahul Es, Jithin James, Luis Espinosa-Anke, and Steven Schockaert. 2023. RAGAs: Automated Evaluation of Retrieval Augmented Generation. *ArXiv Preprint arXiv:2309.15217*.
- Jinlan Fu, See-Kiong Ng, Zhengbao Jiang, and Pengfei Liu. 2023. GPTScore: Evaluate as You Desire. Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers).

- Qianyu He, Jie Zeng, Qianxi He, Jiaqing Liang, and Yanghua Xiao. 2024. From complex to simple: Enhancing multi-constraint complex instruction following ability of large language models. *ArXiv Preprint arXiv:2404.15846*.
- Tom Hosking, Phil Blunsom, and Max Bartolo. 2023. Human feedback is not gold standard. *ArXiv Preprint arXiv:2309.16349*.
- David M Howcroft, Anya Belz, Miruna Clinciu, Dimitra Gkatzia, Sadid A Hasan, Saad Mahamood, Simon Mille, Emiel Van Miltenburg, Sashank Santhanam, and Verena Rieser. 2020. Twenty Years of Confusion in Human Evaluation: NLG Needs Evaluation Sheets and Standardised Definitions. In *13th International Conference on Natural Language Generation 2020*, pages 169–182. Association for Computational Linguistics.
- Jessica Huynh, Jeffrey Bigham, and Maxine Eskenazi. 2021. A Survey of NLP-Related Crowdsourcing Hits: What Works and What Does Not. *ArXiv Preprint arXiv:2111.05241*.
- Karen Sparck Jones and Julia R Galliers. 1995. Evaluating natural language processing systems: An analysis and review.
- Marzena Karpinska, Nader Akoury, and Mohit Iyyer. 2021. The Perils of Using Mechanical Turk to Evaluate Open-Ended Text Generation.
- Seungone Kim, Jamin Shin, Yejin Cho, Joel Jang, Shayne Longpre, Hwaran Lee, Sangdoo Yun, Seongjin Shin, Sungdong Kim, James Thorne, and Minjoon Seo. 2024a. Prometheus: Inducing Fine-grained Evaluation Capability in Language Models.
- Seungone Kim, Juyoung Suk, Ji Yong Cho, Shayne Longpre, Chaeeun Kim, Dongkeun Yoon, Guijin Son, Yejin Cho, Sheikh Shafayat, Jinheon Baek, Sue Hyun Park, Hyeonbin Hwang, Jinkyung Jo, Hyowon Cho, Haebin Shin, Seongyun Lee, Hanseok Oh, Noah Lee, Namgyu Ho, Se June Joo, Miyoung Ko, Yoonjoo Lee, Hyungjoo Chae, Jamin Shin, Joel Jang, Seonghyeon Ye, Bill Yuchen Lin, Sean Welleck, Graham Neubig, Moontae Lee, Kyungjae Lee, and Minjoon Seo. 2024b. The BiGGen Bench: A Principled Benchmark for Fine-grained Evaluation of Language Models with Language Models.
- Seungone Kim, Juyoung Suk, Shayne Longpre, Bill Yuchen Lin, Jamin Shin, Sean Welleck, Graham Neubig, Moontae Lee, Kyungjae Lee, and Minjoon Seo. 2024c. Prometheus 2: An open source language model specialized in evaluating other language models.
- Sungdong Kim, Sanghwan Bae, Jamin Shin, Soyoung Kang, Donghyun Kwak, Kang Min Yoo, and Minjoon Seo. 2023. Aligning large language models through synthetic feedback. *ArXiv Preprint* arXiv:2305.13735.

- Diederik P. Kingma and Jimmy Ba. 2017. Adam: A method for stochastic optimization. *Preprint*, arXiv:1412.6980.
- Tom Kocmi and Christian Federmann. 2023. Large language models are state-of-the-art evaluators of translation quality. *ArXiv Preprint arXiv:2302.14520*.
- Dahyun Koo, Yejin Choi, and Eunsol Choi. 2023. Cognitive Biases in Large Language Models as Evaluators. *ArXiv Preprint arXiv:2312.05441*.
- Kalpesh Krishna, Erin Bransom, Bailey Kuehl, Mohit Iyyer, Pradeep Dasigi, Arman Cohan, and Kyle Lo. 2023. Longeval: Guidelines for human evaluation of faithfulness in long-form summarization. *ArXiv Preprint arXiv:2301.13298*.
- Nathan Lambert and Roberto Calandra. 2023. The alignment ceiling: Objective mismatch in reinforcement learning from human feedback. *ArXiv Preprint arXiv:2311.00168*.
- Nathan Lambert, Jacob Morrison, Valentina Pyatkin, Shengyi Huang, Hamish Ivison, Faeze Brahman, Lester James V Miranda, Alisa Liu, Nouha Dziri, Shane Lyu, et al. 2024a. TÜLU 3: Pushing Frontiers in Open Language Model Post-Training. *ArXiv Preprint arXiv:2411.15124*.
- Nathan Lambert, Valentina Pyatkin, Jacob Morrison, LJ Miranda, Bill Yuchen Lin, Khyathi Chandu, Nouha Dziri, Sachin Kumar, Tom Zick, Yejin Choi, Noah A. Smith, and Hannaneh Hajishirzi. 2024b. RewardBench: Evaluating Reward Models for Language Modeling.
- Tianle Li, Wei-Lin Chiang, Evan Frick, Lisa Dunlap, Tianhao Wu, Banghua Zhu, Joseph E Gonzalez, and Ion Stoica. 2024a. From crowdsourced data to highquality benchmarks: Arena-hard and benchbuilder pipeline. ArXiv Preprint arXiv:2406.11939.
- Zhen Li, Xiaohan Xu, Tao Shen, Can Xu, Jia-Chen Gu, Yuxuan Lai, Chongyang Tao, and Shuai Ma. 2024b. Leveraging Large Language Models for NLG Evaluation: Advances and Challenges. In *Proceedings of the* 2024 Conference on Empirical Methods in Natural Language Processing, pages 16028–16045.
- Bill Yuchen Lin, Yuntian Deng, Khyathi Chandu, Faeze Brahman, Abhilasha Ravichander, Valentina Pyatkin, Nouha Dziri, Ronan Le Bras, and Yejin Choi. 2024. WILDBENCH: Benchmarking LLMs with Challenging Tasks from Real Users in the Wild. *ArXiv Preprint arXiv:2406.04770*.
- Chin-Yew Lin. 2004. Rouge: A package for automatic evaluation of summaries. In *Text summarization branches out*, pages 74–81.
- Yen-Ting Lin and Yun-Nung Chen. 2023. Llm-eval: Unified multi-dimensional automatic evaluation for open-domain conversations with large language models. *ArXiv Preprint arXiv:2305.13711*.

- Chia-Wei Liu, Ryan Lowe, Iulian V Serban, Michael Noseworthy, Laurent Charlin, and Joelle Pineau. 2016. How not to evaluate your dialogue system: An empirical study of unsupervised evaluation metrics for dialogue response generation. *ArXiv Preprint* arXiv:1603.08023.
- Chris Yuhao Liu and Liang Zeng. 2024. Skywork Reward Model Series. https: //huggingface.co/Skywork.
- Yang Liu, Dan Iter, Yichong Xu, Shuohang Wang, Ruochen Xu, and Chenguang Zhu. 2023. G-eval: Nlg evaluation using gpt-4 with better human alignment. *ArXiv Preprint arXiv:2303.16634*.
- Ryan Lowe, Michael Noseworthy, Iulian V Serban, Nicolas Angelard-Gontier, Yoshua Bengio, and Joelle Pineau. 2017. Towards an automatic turing test: Learning to evaluate dialogue responses. *ArXiv Preprint arXiv:1708.07149*.
- Shikib Mehri and Maxine Eskenazi. 2020a. Unsupervised evaluation of interactive dialog with dialogpt. *ArXiv Preprint arXiv:2006.12719*.
- Shikib Mehri and Maxine Eskenazi. 2020b. USR: An Unsupervised and Reference Free Evaluation Metric for Dialog Generation. *ArXiv Preprint arXiv:2005.00456*.
- Jekaterina Novikova, Ondřej Dušek, and Verena Rieser. 2018. Rankme: Reliable human ratings for natural language generation. *ArXiv Preprint arXiv:1803.05928*.
- Beijing Academy of Artificial Intelligence (BAAI). 2024. Infinity instruct. *ArXiv Preprint arXiv:2406.XXXX*.
- Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. 2022. Training language models to follow instructions with human feedback. Advances in Neural Information Processing Systems, 35:27730–27744.
- Qian Pan, Zahra Ashktorab, Michael Desmond, Martín Santillán Cooper, James Johnson, Rahul Nair, Elizabeth Daly, and Werner Geyer. 2024. Human-Centered Design Recommendations for LLM-as-ajudge. In *Proceedings of the 1st Human-Centered Large Language Modeling Workshop*, pages 16–29.
- Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. BLEU: A Method for Automatic Evaluation of Machine Translation. In *Proceedings* of the 40th annual meeting of the Association for Computational Linguistics, pages 311–318.
- Yiwei Qin, Kaiqiang Song, Yebowen Hu, Wenlin Yao, Sangwoo Cho, Xiaoyang Wang, Xuansheng Wu, Fei Liu, Pengfei Liu, and Dong Yu. 2024. Infobench: Evaluating instruction following ability in large language models. *ArXiv Preprint arXiv:2401.03601*.

- Rafael Rafailov, Archit Sharma, Eric Mitchell, Stefano Ermon, Christopher D. Manning, and Chelsea Finn. 2023. Direct Preference Optimization: Your Language Model is Secretly a Reward Model.
- Selvan Sunitha Ravi, Bartosz Mielczarek, Anand Kannappan, Douwe Kiela, and Rebecca Qian. 2024. Lynx: An Open Source Hallucination Evaluation Model.
- Marco Tulio Ribeiro, Tongshuang Wu, Carlos Guestrin, and Sameer Singh. 2020. Beyond Accuracy: Behavioral Testing of NLP Models with CheckList. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, Online. Association for Computational Linguistics.
- Paul Rottger, Bertie Vidgen, Dirk Hovy, and Janet Pierrehumbert. 2022. Two Contrasting Data Annotation Paradigms for Subjective NLP Tasks. In Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, pages 175–190, Seattle, United States. Association for Computational Linguistics.
- Jon Saad-Falcon, Omar Khattab, Christopher Potts, and Matei Zaharia. 2023. ARES: An Automated Evaluation Framework for Retrieval-Augmented Generation Systems. *ArXiv Preprint arXiv:2311.09476*.
- Jon Saad-Falcon, Adrian Gamarra Lafuente, Shlok Natarajan, Nahum Maru, Hristo Todorov, Etash Guha, E Kelly Buchanan, Mayee Chen, Neel Guha, Christopher Ré, et al. 2024. Archon: An architecture search framework for inference-time techniques. *arXiv preprint arXiv:2409.15254*.
- Swarnadeep Saha, Omer Levy, Asli Celikyilmaz, Mohit Bansal, Jason Weston, and Xian Li. 2024. Branch-Solve-Merge Improves Large Language Model Evaluation and Generation.
- Stephanie Schoch, Diyi Yang, and Yangfeng Ji. 2020. "This is a Problem, Don't You Agree?" Framing and Bias in Human Evaluation for Natural Language Generation. In *Proceedings of the 1st Workshop on Evaluating NLG Evaluation*, pages 10–16.
- Shreya Shankar, JD Zamfirescu-Pereira, Björn Hartmann, Aditya Parameswaran, and Ian Arawjo. 2024. Who Validates the Validators? Aligning LLM-Assisted Evaluation of LLM Outputs with Human Preferences. In Proceedings of the 37th Annual ACM Symposium on User Interface Software and Technology, pages 1–14.
- Prasann Singhal, Tanya Goyal, Jiacheng Xu, and Greg Durrett. 2023. A long way to go: Investigating length correlations in rlhf. *ArXiv Preprint arXiv:2310.03716*.
- Eric Michael Smith, Orion Hsu, Rebecca Qian, Stephen Roller, Y-Lan Boureau, and Jason Weston. 2022. Human Evaluation of Conversations is an Open Problem: Comparing the Sensitivity of Various Methods for Evaluating Dialogue Agents. *ArXiv Preprint arXiv:2201.04723*.

- Amanda Stent, Matthew Marge, and Mohit Singhai. 2005. Evaluating evaluation methods for generation in the presence of variation. In *International Conference on Intelligent Text Processing and Computational Linguistics*, pages 341–351. Springer.
- Liyan Tang, Philippe Laban, and Greg Durrett. 2024. MiniCheck: Efficient Fact-Checking of LLMs on Grounding Documents.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. 2023. Llama 2: Open foundation and finetuned chat models. ArXiv Preprint arXiv:2307.09288.
- Marilyn Walker, Candace Kamm, and Diane Litman. 2000. Towards developing general models of usability with PARADISE. *Natural Language Engineering*, 6(3-4):363–377.
- Marilyn A Walker, Amanda Stent, François Mairesse, and Rashmi Prasad. 2007. Individual and domain adaptation in sentence planning for dialogue. *Journal* of Artificial Intelligence Research, 30:413–456.
- Binghai Wang, Rui Zheng, Lu Chen, Yan Liu, Shihan Dou, Caishuang Huang, Wei Shen, Senjie Jin, Enyu Zhou, Chenyu Shi, Songyang Gao, Nuo Xu, Yuhao Zhou, Xiaoran Fan, Zhiheng Xi, Jun Zhao, Xiao Wang, Tao Ji, Hang Yan, Lixing Shen, Zhan Chen, Tao Gui, Qi Zhang, Xipeng Qiu, Xuanjing Huang, Zuxuan Wu, and Yu-Gang Jiang. 2024a. Secrets of RLHF in Large Language Models Part II: Reward Modeling.
- Jiaan Wang, Yunlong Liang, Fandong Meng, Zengkui Sun, Haoxiang Shi, Zhixu Li, Jinan Xu, Jianfeng Qu, and Jie Zhou. 2023a. Is ChatGPT a good NLG Evaluator? A Preliminary Study. *ArXiv Preprint arXiv*:2303.04048.
- Peifeng Wang, Austin Xu, Yilun Zhou, Caiming Xiong, and Shafiq Joty. 2024b. Direct Judgement Preference Optimization. ArXiv Preprint arXiv:2409.14664.
- Yuhang Wang, Ruochen Xu, Zhenrui Xu, Yihuai Jiang, Zhen Xu, and Wenpeng Yin. 2023b. Large Language Models are Inconsistent and Biased Evaluators. *ArXiv Preprint arXiv:2311.16881*.
- Zhilin Wang, Alexander Bukharin, Olivier Delalleau, Daniel Egert, Gerald Shen, Jiaqi Zeng, Oleksii Kuchaiev, and Yi Dong. 2024c. HelpSteer2-Preference: Complementing Ratings with Preferences.
- Zhilin Wang, Yi Dong, Olivier Delalleau, Jiaqi Zeng, Gerald Shen, Daniel Egert, Jimmy J Zhang, Makesh Narsimhan Sreedhar, and Oleksii Kuchaiev. 2024d. HelpSteer2: Open-Source Dataset for Training Top-Performing Reward Models. ArXiv Preprint arXiv:2406.08673.
- Zhilin Wang, Yi Dong, Jiaqi Zeng, Virginia Adams, Makesh Narsimhan Sreedhar, Daniel Egert, Olivier Delalleau, Jane Polak Scowcroft, Neel Kant, Aidan

Swope, and Oleksii Kuchaiev. 2023c. HelpSteer: Multi-Attribute Helpfulness Dataset for SteerLM.

- Zeqiu Wu, Yushi Hu, Weijia Shi, Nouha Dziri, Alane Suhr, Prithviraj Ammanabrolu, Noah A Smith, Mari Ostendorf, and Hannaneh Hajishirzi. 2023. Fine-Grained Human Feedback Gives Better Rewards for Language Model Training. Advances in Neural Information Processing Systems, 36:59008–59033.
- Can Xu, Qingfeng Sun, Kai Zheng, Xiubo Geng, Pu Zhao, Jiazhan Feng, Chongyang Tao, and Daxin Jiang. 2023. WizardLM: Empowering Large Language Models to Follow Complex Instructions.
- Seonghyeon Ye, Doyoung Kim, Sungdong Kim, Hyeonbin Hwang, Seungone Kim, Yongrae Jo, James Thorne, Juho Kim, and Minjoon Seo. 2023. FLASK: Fine-grained Language Model Evaluation based on Alignment Skill Sets.
- Weizhe Yuan, Graham Neubig, and Pengfei Liu. 2021. Bartscore: Evaluating generated text as text generation. Advances in Neural Information Processing Systems, 34:27263–27277.
- Zhiqiang Yuan, Yiling Lou, Mingwei Liu, Shiji Ding, Kaixin Wang, Yixuan Chen, and Xin Peng. 2023. No more manual tests? evaluating and improving chatgpt for unit test generation. *arXiv preprint arXiv*:2305.04207.
- Chen Zhang, Luis Fernando D'Haro, Yiming Chen, Malu Zhang, and Haizhou Li. 2024a. A Comprehensive Analysis of the Effectiveness of Large Language Models as Automatic Dialogue Evaluators. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 19515–19524.
- Lunjun Zhang, Arian Hosseini, Hritik Bansal, Mehran Kazemi, Aviral Kumar, and Rishabh Agarwal. 2024b. Generative Verifiers: Reward Modeling as Next-Token Prediction.
- Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q Weinberger, and Yoav Artzi. 2019. Bertscore: Evaluating text generation with bert. *ArXiv Preprint arXiv*:1904.09675.
- Lianmin Zheng, Dacheng Xu, Jiajun Dong, Andy Zeng, Shuo Xie, Eric P Xing, and Percy Liang. 2023. Evaluation Biases for Large Language Models. *ArXiv Preprint arXiv:2305.17926*.
- Ming Zhong, Yang Liu, Da Yin, Yuning Mao, Yizhu Jiao, Pengfei Liu, Chenguang Zhu, Heng Ji, and Jiawei Han. 2022. Towards a unified multi-dimensional evaluator for text generation. *Conference on Empirical Methods in Natural Language Processing*.
- Banghua Zhu, Evan Frick, Tianhao Wu, Hanlin Zhu, Karthik Ganesan, Wei-Lin Chiang, Jian Zhang, and Jiantao Jiao. 2024. Starling-7b: Improving Helpfulness and Harmlessness with RLAIF. In *First Conference on Language Modeling*.

A Appendix

A.1 Assisting Humans with Preference Annotations

This subsection of the Appendix contains additional information on the experiment to reduce noise in human evaluation of preference data.

A.1.1 Human-Written Unit Tests

We conducted a pilot study to develop gold-standard unit tests for 20 queries, which were later used to reduce noise in preference data. Four experienced annotators used a Google Sheets interface to create 4-8 unit tests per query. These tests were designed to verify that model responses were both accurate and grounded in the retrieved documents. Annotators wrote specific criteria defining the expected behavior and content that would constitute a complete, well-grounded response to each query.

	Agreement Overall	Kappa Overall	# Cases with 100% Agreement	# Queries with High Disagreement
Pairwise Judging	71%	0.04	3	12
Spec	80%	0.32	7	7
Unit Tests	86%	0.52	11	5

Table 6: Unit Tests Improve Inter-Rater Agreement: Unit test-based evaluation achieves substantially higher agreement rates and fewer cases of high disagreement compared to alternative approaches, such as pairwise judging and rubric-based scoring (i.e. "Spec"). High disagreement refers to queries in the 40-60% agreement range.

A.2 LMUNIT Case Study

This section contains additional details regarding the LMUNIT case study described in Section 5. For the annotation regarding error attributes and failure modes, we provide an overview of the annotation guidelines in Table 7, annotation row examples in Table 8, and completed annotations in Table 9.

We also gathered some illustrative anecdotes from study participants to reflect the benefits of unit test-based evaluation methods with LMUNIT:

- Motivating LM System Decisions: "We had suspected for a while that some of our training data was not diverse enough, but it was hard to prove with just LM judge feedback. The LMUNIT unit tests revealed that the model was performing better on certain types of queries (i.e. summarization and multi-hop queries) while creating generic answers for others (i.e. analysis and calculation queries). This led us to augment the dataset with more varied examples and improve our retrieval process, leading to a performance increase for the LM system overall."
- **High-Resolution Feedback**: "With LM judges, we would often get long-winded explanations that did not really explain the issue clearly, which made it hard to figure out what was going on. Sometimes the judge verdict did not align with the explanation at all! However, LMUNIT gave us clear Passed/Failed results with specific criteria, allowing us to know what went wrong and where to fix it."
- **Improved Annotator Alignment**: "For our project, we noticed a frustrating gap between LM judge evaluations and the feedback from our annotators. The LM judges would pass responses that skipped crucial reasoning steps as long as the final answer was correct but annotators rejected responses for lacking logical progression. After switching to LMUNIT, the alignment with the annotators improved significantly. LMUNIT unit tests flagged responses that missed intermediate steps, just like the annotators. This allowed us to retrain the model with more targeted feedback, leading to better performance in tasks requiring step-by-step reasoning and saving us time on annotations."

	Instruction	Response #1	Response #2	LM Judge Verdict	LMUNIT Unit Tests with Verdicts for Better Response
Examples #1	How does the inte- gration of healthcare analytics with electronic health records (EHRs) and the establishment of common technical standards contribute to improving patient care?	The integration of healthcare ana- lytics with electronic health records (EHRs) and the establishment of common technical standards significantly contribute to improving patient care by providing a more co- ordinated, efficient, and data-driven approach to healthcare delivery	**Integration of Healthcare Analyt- ics with Electronic Health Records (EHRs)** * Enables the collection, aggregation, and analysis of vast amounts of clinical data from diverse sources, including EHRs, medical devices, and laboratory results. * Provides insights and analytics that help identify trends, predict outcomes, and improve patient care.	Response #1	Does the response explain how healthcare analytics integration with EHRs impacts patient care? [Passed] Does the response mention the role of common technical standards in improving interoperabil- ity? [Passed] Does the response detail the major challenges addressed by the ONC's Federal Health IT Strategic Plan 2015-2020? [Failed] Does the response cover how privacy concerns are addressed according to the ONC's plan? [Passed]
Examples #2	How might changes in the regulation and public perception of unmanned aircraft systems (UAS) influence the growth and application of urban drone technology?	The influence of changes in reg- ulation and public perception of unmanned aircraft systems (UAS) on the growth and application of drone technology in urban environments over the next decade is significant and multifaceted	**Regulations and Public Percep- tion:** **1. Regulatory Landscape:** - Increased regulations governing airspace usage, safety, and privacy. - Stricter licensing and registration processes for drone operators	Response #1	 Does the response adequately address how changes in regulation might impact the growth of UAS technology in urban environments? [Passed] Does the response explain how changes in public perception might influence the application of UAS technology in urban environments? [Passed] Does the response mention specific regulations that could affect UAS usage in urban areas? [Passed]

Table 8: Comparison of LMUNIT vs. LM Judge for Human Feedback

	Instruction	Response	Response Attributes	Error Modes
Example #1	How does the integration of healthcare analytics with electronic health records (EHRs) and the establishment of com- mon technical standards contribute to improving patient care, while address- ing the challenges related to privacy, data accuracy, and interoperability?	The integration of healthcare analytics with electronic health records (EHRs) and the establishment of common tech- nical standards significantly contribute to improving patient care by providing a more coordinated, efficient, and data- driven approach to healthcare delivery. Several key strategies and challenges need to be addressed to achieve these improvements while safeguarding privacy, data accuracy, and interoper- ability. Firstly, healthcare analytics	Explanation of Healthcare Analytics Integration, Discussion of EHRs (Elec- tronic Health Records), Description of Common Technical Standards, Addressing Privacy Concerns, Focus on Data Accuracy, Discussion of Interoperability, Reference to ONC's Federal Health IT Strategic Plan, Use of Evidence-Based Examples, Explanation of Cost Reduction in Healthcare, Description of Stakeholder Collaboration	Hallucination of Unrelated Information, Omission of Key Concepts, Redun- dancy in Explanation, Inconsistent Use of Terminology, Lack of Coher- ence between Sections, Incomplete Explanation of Critical Points, Overly Generalized Statements
Example #2	How might changes in the regulation and public perception of unmanned aircraft systems (UAS) influence the growth and application of drone technology in urban environments over the next decade?	The influence of changes in regulation and public perception of unmanned aircraft systems (UAS) on the growth and application of drone technology in urban environments over the next decade is significant and multifaceted. Regulatory changes could impose stricter licensing and airspace regu- lations, while public concerns about safety and privacy might limit drone use in specific areas.	Explanation of UAS Regulation, Ref- erence to Safety Standards, Discussion of Operational Restrictions, Mention of Air Traffic Management Systems, Integration of Collision Avoidance Technologies, Privacy Concerns in Ur- ban Environments, Public Perception and Security Issues, Transparency in Data Capture and Processing	Failure to Address Privacy Concerns, Overlooking Public Perception and Security Issues, Vague Discussion on Commercial Applications, Inconsistent Explanation of Regulatory Compliance, Inaccurate Reference to Urban Growth Impact, Failure to Mention Innovation Amidst Regulations

A.3 LMUNIT in LLM Pipelines

Instruction	Response	Response	LM Judge	LMUNIT Unit Tests +	LMUNIT Unit Tests +
	#1	#2	Verdict	Verdicts for Response#1	Verdicts for Response#2
{text}	{text}	{text}	{#1 or #2}	Bulleted Queries + Verdicts	Bulleted Queries + Verdicts

Table 7: **Information for Comparing LM Judge and LMUNIT**: Given the following information, annotators then provide the response attributes, error modes, and their importances identified by each evaluation approach. We provide annotated row examples in Table 8 and completed annotations in Table 9.

To test the utility of LMUNIT unit test generation and evaluation, we incorporated the models into LLM development pipelines for 16 researchers and engineers covering domains in finance, publishing, software, hardware development, and more. The surveyed individuals were volunteer researchers working in NLP labs who utilized LMUNIT models over the course of 1-2 days, continuing their original evaluation workflows but with added LMUNIT models. The researchers regularly develop LLM systems that integrate 70B+ parameter models with retrieval systems, frequently undergoing additional instruction fine-tuning and preference alignment datasets. These demands necessitate the development of reliable evaluation systems for understanding 1) error modes of existing systems and 2) actionable steps for

improving existing approaches. We breakdown existing ways LMUNIT has bolstered current pipelines.

The insights provided by LMUNIT proved instrumental for improving both RAG systems and LLM systems more generally. 13 out of the 16 researchers surveyed stated that LMUNIT *helped them identify current error modes in their training pipelines*, inspiring them to make data selection and preprocessing decisions to address the failures directly. Eight researchers also said LMUNIT sparked them to make training pipeline decisions surrounding hyperparameters, dataset weighting, and in-context learning. Furthermore, six researchers said the decisions lead to a *10+ point boost in evaluation performance for instruction-following and reasoning tasks*. Most importantly, 15 of the 16 researchers said they would be *interested in using unit test-based frameworks for building ML pipelines going forward*, assuming they are aligned with evaluation metrics and human preferences for instruction-following and reasoning tasks.



Figure 4: **LMUNIT Favored Over LM Judges for Identified Response Attributes and Error Modes**: LMUNIT is favored by LM researchers and engineers surveyed, allowing users to find greater numbers of important response attributes and error modes identified in LLM responses. Out of the 16 individuals surveyed, all of them favored LMUNIT over traditional LM judges.

Test ID	Unit Test
GUT-1	Is the response helpful and aligned with the spirit of what the prompt was asking for?
GUT-2	Does the response directly address the prompt's query or topic?
GUT-3	Are the facts and information presented in the response correct and reliable?
GUT-4	Is the response articulated in a clear and understandable manner?
GUT-5	Does the response provide a thorough answer, covering all aspects of the prompt?
GUT-6	Is the response succinct without omitting essential information?
GUT-7	Does the response maintain the reader's interest and encourage further thought or action?
GUT-8	Does the response adhere to ethical guidelines and avoid promoting harmful content?

Table 10: Global Unit Tests used for pairwise evaluations on RewardBench and LFQA