# Which Imputation Fits Which Feature Selection Method? A Survey-Based Simulation Study

Andrés Romero<sup>a,\*</sup>, Jakob Schwerter<sup>a,\*</sup>, Florian Dumpert<sup>b</sup> and Markus Pauly<sup>a,c</sup>

\*Shared first authorship;

<sup>a</sup>TU Dortmund University, Dortmund, Germany;

<sup>b</sup>Federal Statistical Office of Germany, Wiesbaden, Germany;

<sup>c</sup>Research Center Trustworthy Data Science and Security, Dortmund, Germany

### ARTICLE HISTORY

Compiled December 19, 2024

#### Abstract

Tree-based learning methods such as Random Forest and XGBoost are still the goldstandard prediction methods for tabular data. Feature importance measures are usually considered for feature selection as well as to assess the effect of features on the outcome variables in the model. This also applies to survey data, which are frequently encountered in the social sciences and official statistics. These types of datasets often present the challenge of missing values. The typical solution is to impute the missing data before applying the learning method. However, given the large number of possible imputation methods available, the question arises as to which should be chosen to achieve the 'best' reflection of feature importance and feature selection in subsequent analyses. In the present paper, we investigate this question in a survey-based simulation study for eight state-of-the art imputation methods and three learners. The imputation methods comprise listwise deletion, three MICE options, four missRanger options as well as the recently proposed mixGBoost imputation approach. As learners, we consider the two most common treebased methods, Random Forest and XGBoost, and an interpretable linear model with regularization.

#### **KEYWORDS**

Feature Selection, Interpretable Machine Learning, Multiple Imputation

This study was not preregistered.

The data is based on (NEPS Network 2022, SC6:13.0.0) and can be requested at www.neps-data.de/Mainpage.

CONTACT Jakob Schwerter (ORCID: 0000-0001-5818-2431), TU Dortmund University, Department of Statistics, Martin-Schmeisser-Weg 13, D-44227 Dortmund, Germany. Email: jakob.schwerter@tu-dortmund.de.

The project "From Prediction to Agile Interventions in the Social Sciences (FAIR)" is receiving funding from the program "Profilbildung 2020", an initiative of the Ministry of Culture and Science of the State of Northrhine Westphalia. The sole responsibility for the content of this publication lies with the authors.

# 1. Introduction

Machine learning (ML) is increasingly crucial for all kinds of quantitative analyses. This particularly holds for official statistics (Beck et al. 2018; United Nations Economic Commission for Europe 2021; Dumpert 2023; Measure 2023; Dumpert 2024) based on survey data, which is of particular importance in countries such as Canada or Germany. Data processing includes integrating data from different sources, classifying and coding units, reviewing and validating input data (e.g., validating data against pre-defined edit rules), as well as editing and imputing incorrect, missing, unreliable or outdated information (United Nations Economic Commission for Europe 2019). Social science research presents a similar case. Here, ML offers significant advantages in areas like double machine learning for selecting key control variables (Chernozhukov et al. 2018, 2024) and predicting student success with learning analytics. Unlike traditional regression methods, which excel at confirmatory hypothesis testing but limit the number of predictor variables (Byrnes and Miller 2007), interpretable machine learning techniques incorporate built-in feature importance and selection. Such capabilities are critical in contexts such as large-scale assessment and learning analytics, where the potential pool of control variables is large (Arizmendi et al. 2022; Belloni et al. 2014; Schwerter et al. 2024c).

Complex machine learning models, such as deep neural networks, often sacrifice interpretability, a drawback that has led to the development of interpretable machine learning (Molnar 2022; Ewald et al. 2024), which is now widely used in the social sciences (Foster et al. 2020). When discussing quality aspects of machine learning in official statistics (van Delden et al. 2023, p. 200, 202), it is advisable not to give too little thought to feature selection, manual or automatic, see also Molladavoudi and Yung (2023) and Saidani et al. (2023, Section 3.3). Approaches including Lasso, Elastic Net regression, and tree-based models such as Random Forest and XGBoost are widely used for high-dimensional data and feature selection, see, e.g., Park et al. (2023), Lupyan and Goldstone (2019), and Arizmendi et al. (2022) for some examples in learning analytics. These methods can handle large sets of variables while preserving interpretability – an essential factor in social science research and, albeit to a somewhat lesser degree, in official statistics.

Missing data poses a significant challenge in the application of machine learning, particularly in psychological and social science research. For example, Peng et al. (2006) found that at least 48% of articles in eleven education journals between 1998 and 2004 reported missing data, highlighting the prevalence of this issue. Ignoring missing data can lead to bias, reduced statistical power, and increased standard errors (van Buuren 2018; Dong and Peng 2013). Recognizing this, advanced techniques like multiple imputation were introduced by Schafer and Graham (2002), building on Rubin (1976) and further developed by Rubin (1987). According to Enders (2023), this work is the most cited paper in Psychological Methods, underscoring its impact. Recent technological and software advancements have improved imputation models (Enders 2023), facilitating their adoption in the social sciences and official statistics, where imputation is also common practice (Chen and Haziza 2019). This underscores the necessity to evaluate whether machine learning methods can effectively handle missingness, thereby enhancing their applicability in fields where missing data is prevalent.

While multiple imputation effectively handles missing data, researchers have to choose from several imputation methods (Dagdoug et al. 2023; El Badisy et al. 2024; Schwerter et al. 2024a). Among these, Multiple Imputation by Chained Equations (MICE) is very popular, with Predictive Mean Matching (PMM) being one of the most widely used strategies (van Buuren and Groothuis-Oudshoorn 2011; van Buuren 2018). MICE with PMM is broadly used in social science research because of its flexibility in handling different patterns of missing data and taking into account dependencies among variables (e.g., Gopalakrishna et al. 2022; van Ginkel et al. 2020; Zettler et al. 2022; Hajovsky et al. 2020; Hollenbach et al. 2021; Westermeier and Grabka 2016; DeFranza et al. 2021; Costantini et al. 2023). The fact that theoretical or empirical relationships exist between variables is also often used in official statistics to define so-called edit rules. Responses and imputations must fulfill these edit rules in order to be considered plausible. Correctly mapping the dependencies between variables is therefore often an important additional criterion for a good imputation (de Waal et al. 2011, p. 299).

There are also alternative MICE methods that have good properties and are in widespread use. For example, MICE Norm (van Buuren and Groothuis-Oudshoorn 2011; van Buuren 2018) uses a Bayesian linear normal model to predict missing values, and recent simulation studies in official statistics favor MICE Norm for its high univariate and multi-variate imputation accuracy with metric variables (Thurow et al. 2021, 2024). This approach effectively preserves the underlying distributions and accurately reflects true correlations. In addition, biostatistical research has shown that MICE Norm provides reliable type I error control after imputation (Ramosaj et al. 2020).

Since both MICE PMM and MICE Norm rely on linear models, they cannot directly impute non-metric variables. This limitation has led to the emergence of tree-based methods that can handle mixed data types as a promising alternative. Tree-based approaches excel at handling missing data in complex, high-dimensional datasets by imputing based on observed patterns, making them effective even when missingness is not entirely random (Hayes 2018; Hayes and McArdle 2017). They efficiently handle numerous variables and interactions without overfitting, a challenge for MICE PMM (Hayes 2018).

Three prominent tree-based imputation methods are MICE with Random Forest (RF), Chained Random Forest (missRanger) (Mayer 2024), and Extreme Gradient Boosting (mixGB) (Deng and Lumley 2023). MICE with RF and Chained RF have demonstrated high imputation accuracy – measured by the absolute distance between true and imputed data – and strong performance in subsequent classification or prediction tasks (Stekhoven and Bühlmann 2012; Ramosaj and Pauly 2019; Thurow et al. 2021; Ramosaj et al. 2022; Buczak et al. 2023). Although their distributional accuracy for metric variables is not entirely satisfactory (Thurow et al. 2021, 2024), tree-based methods have recently shown robust power properties for hypothesis testing in linear models after imputation (Schwerter et al. 2024a). Another (Bayesian) tree-based approach using full conditional distributions – which in particular takes the fulfillment of nested equality and inequality edit rules for the variables into account – is presented by Aßmann et al. (2024).

This study addresses the important issue of missing data in a survey by examining how different imputation methods affect the performance of machine learning regression models in terms of accuracy and feature selection, with the latter being the main focus of the study. In official statistics, feature selection occurs when a statistical office conducts analyses itself by fitting models based on official data after imputation, or when researchers use official microdata after (suitable and legally unobjectionable) provision for scientific research via a research data center. In a simulation study, we evaluate eight advanced imputation techniques – including three MICE variants (van Buuren and Groothuis-Oudshoorn 2011), four missRanger options (Mayer 2024), and the recently proposed mixGBoost method (Deng and Lumley 2023) – and their compatibility with three popular algorithms (Grinsztajn et al. 2022): LASSO (Hastie et al. 2009), Random Forest (Breiman 2001), and XGBoost (Chen and Guestrin 2016). For comparison, we also include listwise deletion. Through a realistic simulation study, we aim to identify the optimal imputation-prediction pairings that improve feature selection and accurately reflect feature importance, thereby advancing the application of interpretable machine learning in survey analyses. This research bridges classical data science techniques with the practical challenges of missing data in empirical surveys.

Following this, the structure of this document is as follows: in Section Materials and Methods, the dataset selected for the simulations and the techniques used to deal with missingness are presented. Then, in Section Simulation, the design and the machine learning methods used for variable selection are described. Next, in Section Feature Selection Results, the outcomes of the simulations are detailed and discussed. Finally, the paper concludes with a summary and outlook for future work.

## 2. Materials and Methods

# 2.1. The NEPS Dataset

To ensure a realistic comparison of methods, we use a simulation approach that leverages existent survey data to create simulated data, drawing inspiration from recent studies (Friedrich and Friede 2023; Thurow et al. 2023; Schwerter et al. 2024a). Our data generation process for the simulations is closely aligned with the National Education Panel Study for the Starting Cohort of Adults (NEPS, SC6: 13.0.0, NEPS Network 2022), which examines adult education, career trajectories, and skill development in Germany for individuals born between 1944 and 1986 (FDZ-LIfBi 2022). The link between income and education is of interest to the public sector for planning and evaluation purposes and is also considered in other statistics. Examples in Germany are the microcensus and the Earnings Survey, although these set different areas of focus than the NEPS in terms of variables and type of survey.

We used data from the sixth wave of the NEPS (the 5th NEPS survey, covering data collected between 2013 and 2014), ensuring that only cases with complete data (i.e., observations with no missing entries) were included. This dataset consists of 22 variables, grouped according to the scale type for each case, as summarized in Table 1.

Working hours (workinghrs), age in years (age), work experience in years (workexp), and political orientation on a scale from left (0.00) to right (10.00) (leftright) comprise four continuous variables. While these are treated as continuous, only workexp and workinghrs contain non-integer values in the selected dataset. The number of siblings (siblings), number of contact attempts made before completing the survey (contactattempts), and number of children under 6 years old in the respondent's household (children) are three discrete variables included in the dataset.

Next, we included binary variables such as gender (*gender*), fixed-term contract status (*fixedterm*), participation in further training since the last interview (wb), country of birth (Germany or not) (birthcountry), involvement in informal learning since the last interview (*ilearn*), and whether the respondent listens to classical music (*classicmusic*). A ternary variable captures volunteering involvement (never, once, or at least twice) (volunteering). Additionally, there are variables with four levels including the Classification of Profession Requirements (kldb), marital status (marital status), highest education level attained (ed*ucation*), company size (*compsize*), and industry sector (*sector*). There is also a five-level variable that captures parental school qualification (schoolparents) and the federal state of residence at the time of the survey (*fedstate*). Detailed information for factor variables with four or more levels is provided in Appendix A. All the factor variables were encoded following a one-hot encoding approach (also known as dummy encoding): it replaces a k-level variable with k-1 binary indicator features by removing the most frequent category in the variable. This is in order to avoid collinearity with an intercept (James et al. 2023, p 126). Table 1 shows in bold all the levels that were removed for each factor variable after the one-hot encoding was applied to the dataset.

Finally, the target variable is  $ln_real_inc$ , representing the natural logarithm of the respondent's monthly income, serving as the continuous outcome variable. For a comprehensive understanding of the variables and their distributions, histograms or count plots for each variable are available in Appendix B.

In total, the dataset used for our evaluation has 3,886 complete observations of 49 features, of which 4 are metric, 3 are integer and 42 binary variables stemming from the factor encoding. The 50th variable is the outcome.

Variable	Туре	Statistics
Metric variables		
workinghrs	Continuous	Min: 0.00, Median: 40.00, Max: 90.00
age	Continuous	Min: 26.00, Median: 49.00, Max: 69.00
workexp	Continuous	Min: 0.50, Median: 25.00, Max: 55.58
leftright	Continuous	Min: 0.00, Median: 5.00, Max: 10.00
Integer variables	_	
siblings	Discrete	Min: 0.00, Median: 1.00, Max: 23.00
contactattempts	Discrete	Min: 1, Median: 6, Max: 117
children	Discrete	Min: 0, Median: 0, Max: 3
Factor variables		
aender	- Factor - 2 levels	male: 1971, female: 1915
fixedterm	Factor - 2 levels	<b>no: 3643</b> , ves: 243
wb	Factor - 2 levels	<b>no: 2802</b> , ves: 1084
birthcountry	Factor - 2 levels	<b>in Germany: 3647</b> , abroad: 239
ilearn	Factor - 2 levels	yes: 2743, no: 1143
classic music	Factor - 2 levels	<b>yes: 2094</b> , no: 1792
volunteering	Factor - 3 levels	no: 1875, 2orMore: 1482, once: 529
kldb	Factor - 4 levels	Skilled: 1861, HighComplx: 1162, Complx: 639, LowComplx: 224
marital status	Factor - 4 levels	<b>married: 2742</b> , single: 804, divorced: 286, widowed: 54
education	Factor - 4 levels	Secondary: 1336, University: 1293, Abitur: 677, LowerSec: 580
comnsize	Factor - 4 levels	<b>3: 1465</b> . 4: 1431. 1: 589. 2: 401
sector	Factor - 4 levels	<b>3: 1506</b> , 2: 1187, 1: 1151, 4: 42
schoolparents	Factor - 5 levels	HauptS: 2120. HighSDip: 936. RealS: 780.
		NoSCert: 43. Other: 7
fedstate	Factor - 16 levels	<b>NW: 845</b> , BY: 622, BW: 457, NI: 421, HE:
		332, RP: 215, SN: 205, BE: 136, ST: 124, TH:
		114, BB: 113, SH: 109, HH: 72, MV : 55, SL: 46, HB: 20
Target variable		
ln_real_inc	Continuous	Min: 3.83, Median: 8.04, Max: 9.97

Table 1.: Variables from the NEPS Dataset with their Scale Type and their most Important Summary Statistics

*Note:* For numeric and integer variables: minimum, median and maximum values are shown. For factors: all the levels with their count in decreasing order and the most frequent in **bold** letters.

# 2.2. Methods to Handle Missing Data

The investigated imputation methods cover listwise deletion, three MICE options (van Buuren and Groothuis-Oudshoorn 2011), four missRanger options (Stekhoven and Bühlmann 2012; Mayer 2024) as well as the recently proposed mixGBoost imputation approach (Deng and Lumley 2023).

Listwise Deletion, or complete-case analysis, removes all observations with any missing values in either the predictors or the outcome. This method is simple to implement, requiring no data modification or imputation, and produces unbiased estimates if data are missing completely at random (MCAR). However, it can lead to significant information loss, especially with many variables affected by non-response, and may result in biased estimates if the data are not MCAR (van Buuren 2018; van Ginkel et al. 2020; Schwerter et al. 2024a).

In contrast to this rather simple benchmark approach, we considered state-of-theart prediction-model-based imputation approaches. These treat the imputation of missing values as a prediction problem, where the variable with missing data is predicted using the remaining variables as predictors. To this end, several statistical and ML-based prediction models are in use. In the present paper, we consider approaches based on (Bayesian) linear models, Random Forests and XGBoost. We start by explaining the former, which usually appear in the context of Multiple Imputations.

Multiple Imputation (MI) addresses the problem of missing data by generating several plausible values for each missing entry rather than a single estimate. By repeatedly imputing missing values based on all available information and creating multiple imputed versions of the dataset, MI allows for subsequent analysis with measurable uncertainty, accounting for variability in the imputation (Rubin 1996; Raghunathan 2015). Currently, Multivariate Imputation by Chained Equations (MICE) (van Buuren and Groothuis-Oudshoorn 2011) is one of the most popular MI algorithms that can impute multiple variables simultaneously. We study three different MICE approaches:

MICE Norm is a Bayesian imputation approach under the normal linear model which is based on early ideas from Rubin (1987). Thereby, the observed data is used to estimate the posterior distribution from which the parameters of the linear model are drawn, which in turn is used for the prediction-model-based imputation.

**MICE PMM** extends MICE Norm by selecting a set of so-called candidate donors (by default: k = 5) from the observed data whose outcome values are closest to the predicted ones (obtained from the Bayesian linear model). One donor is randomly chosen, ensuring that only observed outcome values are imputed.

The MICE package (van Buuren and Groothuis-Oudshoorn 2011) also contains the MICE RF algorithm (Doove et al. 2014). It uses k individual decision trees trained on bootstrap samples from the observed data. For each missing value, the data point is passed through all trees, landing in a terminal node for each. A random donor is selected from

the observations in these nodes, and one donor is randomly chosen from the k donors for imputation.

Another popular and highly cited (almost 5,000 Google Scholar citations at the time of submission) imputation method is given by the missForest algorithm proposed in Stekhoven and Bühlmann (2012), which can also be used with mixed-type data. It iteratively refines initial imputations using Random Forests as prediction models. As the process progresses, previously imputed values are used for further (improved) predictions. In the present paper, we use the computationally fast **missRanger** implementation (Mayer 2024).

Unlike MICE RF, the original missForest algorithm doesn't rely on reflecting uncertainty in its imputation mechanism. To counteract this somewhat, the implementation Mayer (2024) additionally offers **missRanger with predictive mean matching** as an option. This not only ensures that imputation is restricted to observed values but also tries to better reflect the underlying (but unknown) variable distributions with the imputed values. Since there are no default values for the number of donors k when applying **missRanger**, we explore three typical options: k = 3, 5, 10. In addition, the choice k = 0 gives the missForest implementation.

Similar to Random Forest-based imputation approaches, Deng and Lumley (2023) introduced mixgb, an XGBoost-based imputation method (Chen and Guestrin 2016). It can also handle mixed-type data and offers predictive mean matching. We use the default values for predictive mean matching as recommended in (Deng and Lumley 2023): k = 5 for the imputation of continuous variables and no PMM in the case of categorical data.

### 3. Simulation

The study employs a nested resampling approach initiated with an outer 3-fold cross-validation (see Figure 1 for a graphical overview). For each fold, the dataset is partitioned into training  $(\mathcal{D}_{outf}^{train})$  and test sets  $(\mathcal{D}_{outf}^{test})$ . The following sequence is applied to each outer fold with 100 iterations:

Amputation and Imputation: Missing data is introduced following an MAR mechanism as described by Thurow et al. (2021), with missing rates of 10%, 30%, 50%, and 70%. Subsequently, imputation methods listed in Table 2 are applied with default R package parameters with m = 5 imputations. After imputation, metrics such as NRMSE, IPM, and correlation distances are recorded. Given the focus on feature selection, these results together with the definition of the metrics are only reported in the Appendix C.

Hyperparameter Tuning and Model Evaluation: An inner 4-fold cross-validation is employed for hyperparameter tuning for each statistical learner, optimizing for MSE. The optimal hyperparameters are then used to train the five multiply imputed training datasets. The best model is applied on the respective test set, yielding m = 5 MSE values. To analyze the effect on feature selection, we save the best feature sets per multiply imputed training

Table 2.: The Nine Imputation Methods under Investigation with the Chosen Number of Multiple Imputations m and the used R Functions and Parameters for Their Implementation

Method		R Function and Parameters	
Listwise (listwise) Bayesian Linear (norm) Predictive Mean Matching (pmm) Random Forests (RF) Chained RF (missRanger0) Chained RF (missRanger3)		<pre>stats::complete.cases() mice(method = "norm") mice(method = "pmm") mice(method = "rf") missRanger(pmm.k = 0) + replicate(5,) missRanger(pmm.k = 3) + replicate(5,)</pre>	
Chained RF (missRanger5) Chained RF (missRanger10) XGBoost (mixGB)		<pre>missRanger(pmm.k = 5) + replicate(5,) missRanger(pmm.k = 10) + replicate(5,) mixGB()</pre>	

data. The details on the process followed for feature selection is presented with a more detailed explanation below. Moreover, a single MSE is derived by averaging the pooled MSEs across folds and, again, given the focus on feature selection, these results are only reported in the Appendix C.

**Performance**: To establish a performance baseline and explore regression capabilities on the full dataset, the entire procedure is also conducted without the amputation, providing benchmark results with the complete data. All tasks are executed using the mlr3 framework (Bischl et al. 2024) in R (R Core Team 2022).

#### 3.1. Hyperparameter Tuning and Feature Selection

To efficiently perform hyperparameter tuning for LASSO, Random Forest and XGBoost, a nested cross-validation with four inner folds is applied to each imputed dataset (see the red loops for the Tuning step as depicted in Figure 1 for a graphical overview). This evaluation is conducted using grid search with a resolution and batch size of 5, implemented via the method mlr3tuning:tnr within the automatic tuning process mlr3tuning:auto\_tuner, using Mean Squared Error (MSE) as the loss function to identify the optimal set of parameters.

For the Lasso Regularized Linear Model, we utilize the regr.glmnet learner from mlr3learners (Friedman et al. 2010). Parameters include alpha = 1 to enable only the LASSO penalty, nfolds = 5 for a 5-fold cross-validation method to tune the parameter  $\lambda$ , and lambda.min.ratio set to be tuned in the interval between 0.005 and 0.03, where MSE results converge with the complete dataset. If a variable coefficient is not set equal to zero, the variable is selected by LASSO.

For Random Forest, the regr.ranger model from mlr3learners uses the ranger package, implementing the method described by Wright and Ziegler (2017). As a compromise between accuracy and run-time, we used 200 trees for the implementation of Random Forest.

Based on the hyperparameter tuning suggestions by Probst et al. (2019) and the best results obtained for the *complete* dataset, the following hyperparameters are used: mtry.ratio =  $\{0.15, 0.3, 0.45\}$  to vary the number of columns used to train each tree between  $\sqrt{p}$  and p/3 for p = 50 (= 49 predictors + 1 imputation indicator); sample.fraction = [0.2, 0.9] to vary the fraction of observations used to train the trees between 20% and 90%; and min.node.size =  $\{5, 7, 10\}$  to set the minimum number of observations per leaf. Unlike linear regression models, Random Forests do not deliver concrete parameter estimates but only feature importances of variables (importance = "impurity") that can be used for feature / model selection. If the variable importance was higher than the median importance, we counted the feature as selected, following the filter-based Feature Selection approach introduced by (Bischl et al. 2024, Section 6.1.4).

For XGBoost models, regr.xgboost from mlr3learners is employed. Following the tuning suggestions by Putatunda and Rama (2018) and Srinivas and Katarya (2022), as well as testing on the *complete* dataset, the tuned parameters include: eta = [0.1, 1] chosen to form a grid of values on a logarithmic scale, controlling the learning rate or shrinkage parameter; nrounds = [50, 100] controlling the number of trees; maxdepth =  $\{1, 5, 10\}$  controlling tree depth; and colsample\_bytree =  $\{0.2, 0.5, 0.75, 1\}$  controlling the percentage of parameters p used as candidates to train the trees. As with Random Forests, if the variable importance was higher than the median importance, we counted the feature as selected. Therefore, the hyperparameter tuning step involves evaluating five combinations for LASSO, 45 for Random Forests, and 120 for XGBoost.

After tuning and evaluation, we end up with m = 5 models, each with possibly distinct features that, following the pooling approach presented by Zahid et al. (2020), akin to pooling metrics for feature selection after multiple imputation, is used to choose the most important among them as follows:

select 
$$X_j$$
, if  $\frac{\sum_{t=1}^m \mathbb{1}(X_{j,t} \text{ is chosen})}{m} \ge \delta$ , (1)

where  $\mathbb{1}(X_{j,t} \text{ is chosen})$  is one if feature  $X_j$  is chosen for iteration (or imputation) t, and zero otherwise. A feature is selected if it appears in a proportion greater than or equal to  $\delta = 0.6$  (Zahid et al. 2020). Thus, for m = 5, a feature is chosen if retained in at least three of the five models.

Afterward, resulting in one model per outer fold, the selection undergoes another pooling between the 3 feature subsets, applying the same  $\delta = 0.6$  to select features present in at least two out of the three folds. We then sum up how often per simulation run a variable was selected to compare the results across the 100 simulations.



Figure 1.: Overview of our simulation Design with Nested Cross Validation

# 4. Feature Selection Results

Here, we present the results for each learner when paired with one of the 9 imputation methods, beginning with the feature selection for LASSO (Figures 2-3), followed by the feature importances of Random Forests (Figures 4-5), and XGBoost (Figures 6-7). For each learner, we first show the results for true positives (Figures 2, 4 and 6) with increasing missing rates (from left 10% to right 70%). Thereby, a deeper shade of blue signifies more frequent selection or importance of a feature across the 100 iterations. For false positives (Figures 3, 5, and 7), a red color scheme is employed to this end.

The focus of this study is on feature selection. However, additional results regarding imputation accuracy (NRMSE, IPM, and correlation) and predictive performance of the regression learners (MSE) are shown in the Appendix C and are only briefly addressed in this article.

# 4.1. LASSO

**True Positives:** Figure 2 shows the frequency with which each feature was selected by LASSO during the prediction of respondents' income across 100 iterations for both the complete dataset and the various imputed datasets. For the complete data (column to the left as a comparison in each subpanel), 30 features (corresponding to the number of displayed rows) were selected from the 50 (49 original plus 1 imputation indicator) features in at least one of the 100 iterations by LASSO.

When comparing the imputation methods (represented by the other nine columns in each subpanel), listwise deletion is often unable to perform feature selection, as explained in the previous section. It is therefore excluded from the following discussion, which focuses solely on the remaining eight imputation approaches. Among these, missRangerO stands out as the most effective at selecting features compared to the baseline (Complete), particularly at the two highest missing rates.

For the 10% missingness case, nearly half of the features selected in the baseline are retained by almost all imputation methods with high selection frequencies (more than 50 times across 100 runs). Among the 20 features that were almost always selected by the baseline, only 13 were also (almost) always selected after the amputation and imputation process. For the next eight most frequently selected features by the baseline, missRanger without PMM, and then MICE RF, missRanger with PMM and mixGB demonstrated greater alignment with the feature selection patterns observed in the complete data. MICE Norm and MICE PMM showed less alignment (see particularly the features *compsize\_2*, *fedstate\_ST*, *fedstate\_MV*, *fedstate\_BB*, *education\_LowerSec*, *sector\_4*).

In cases where the LASSO selection frequency for the complete data was significantly below 100 (e.g., for features from *children* to *leftright*), the selection frequency after the imputation consistently remained below 100 as well. This indicates that the amputation and imputation process did not lead to any noticeable improvement in the selection.

This pattern holds true across the other three missing rates with only minor exceptions, generally showing a clear reduction in the feature selection frequency. At the 30% missing rate, ten features were still selected in each iteration after imputation. However, this number drops to three at the 50% missing rate and six at the 70% missing rate. That is, the increase in missingness leads to a reduction in the number of chosen features until the 50% rate and then slightly increases again at 70%. However, the feature selection frequency is much lower than observed at the 30% case.

Irrespective of the missing rate, most true positive features are selected when missing values were imputed using **missRanger** without PMM. Overall, MICE Norm appears to perform the worst among the eight imputation methods in enabling LASSO to retain the same features as in the complete dataset.

Only three features: workinghrs, kldb\_HighComplx and compsize\_4 were chosen very

frequently by all models and at any missing rate.



Figure 2.: Feature Selection for the Lasso Penalized Linear Models: True Positives

False Positives: The number of false positives, defined as selected features after the amputation and imputation process that were not selected for the complete data (baseline), is nearly zero for LASSO (see Figure 3). Only the different missRanger variants and mixGB selected a false positive in at most four out of 100 iterations for the 10%, 30% and 70% missing rate: the feature *schoolparents\_HighSDip* was only chosen in four iterations after imputing with missRanger10. Thus, compared to the baseline, LASSO seems to select a sparse set of variables after amputation and imputation with hardly any false positives.

Figure 3.: Feature Selection for the Lasso Penalized Linear Models: False Positives



# 4.2. Random Forests

**True Positives:** Figure 4 highlights two important differences between Random Forests and LASSO with respect to feature selection. The sensitivity of feature selection to the missing rate is less pronounced in Random Forests than in LASSO. In particular, almost half of the features selected in the baseline cases are consistently selected across all imputation models, with a frequency greater than 50 out of 100 iterations, regardless of the proportion of missing data in the dataset.

Interestingly, while 29 features were selected at least once using the Random Forest on the complete dataset, five features not selected by the LASSO (Figure 2) were included in some of the Random Forests: *contactattempts, volunteering\_2orMore, classicmusic\_no, schoolparents\_HighSDip* and *age*. Among these, the first four were identified as false positives in some LASSO selections (Figure 3), whereas *age* was not chosen by LASSO in any case. The *imputed* feature was consistently excluded in both baseline model sets.

When examining the effect of the missing rate on the selection of features for Random Forests, the results are similar to those of LASSO, although the variation in the number of features at different rates is less pronounced. The number of features selected is lowest at 50%, while the results at the 30% and 70% missing rates are more similar. When comparing imputation models, the tendency for one method to select significantly more or fewer true positive features is less pronounced with Random Forests than with LASSO.

In general, the methods show consistent and similar behavior at the same missing rate. Interestingly, even the listwise deletion approach achieves considerable feature selection at the 10% missing rate. However, some of the results differ from the baseline case. Moreover, for higher missing rates, listwise deletion did not lead to feature selection in almost all cases (with maximum 2 times out of 100 for 30% and none for the 2 highest rates). At the two highest missing rates, the three missRanger models with PMM struggled to select features with the same frequency in the bottom half of commonly selected features compared to baseline.

False Positives: Investigating the false positives shown in Figure 5, it is clear that all of the remaining features are selected by at least one model, with significantly higher selection frequencies compared to LASSO. The most striking example is the feature  $fedstate_BW$ , which is incorrectly selected by Random Forests more than 90 times for the two highest missing rates when imputation is done with mixGB.

The influence of the missing rate on the erroneous selection of features using Random Forests manifests itself as an increase in false positives up to a missing rate of 50%, followed by a decrease at 70%. An exception is listwise deletion: Here, the Random Forest consistently selects more false positives at the lowest missing rate of 10%. With increasing missing rates up to 50%, Random Forest is particularly prominent in selecting several features that were not considered relevant in the baseline cases for MICE Norm. For the



Figure 4.: Feature Selection for the Random Forests: True Positives

tree-based methods MICE RF, mixGB and the missRanger approaches with PMM, only three to five features were wrongly selected with a high frequency, at missing rates from 30% to 70%. For missRanger without PMM, this was only the case at the 30% missing rate.

### 4.3. XGBoost

**True Positives:** At first glance, Figure 6 shows that XGBoost exhibits greater selectivity in feature selection compared to the Random Forest, reflecting its improved ability to filter and select features (Chen and Guestrin 2016). Although 29 features were selected in at least one of the 100 baseline simulations (i.e., using XGBoost on the complete data), the specific features selected differ and are selected less frequently compared to Random Forests. In particular, nine features were consistently selected by XGBoost across all evaluated missing rates using all imputation models.

Regarding the impact of missingness on feature selection, the results were not significantly different from those observed with the other two learners. As the missingness increases, fewer features are selected up to a missing rate of 50%. At 70%, the number of selected features slightly increases, but does not reach the level observed at 30%.



Figure 5.: Feature Selection for the Random Forests: False Positives

Comparing the different imputation models, listwise deletion only has a nonnegligible feature selection at the 10% missing rate and again mostly fails to capture the same features as those identified in the baseline runs. In addition, MICE Norm emerges as the method that selects more features overall, with some features being selected even more frequently than in the baseline. This is in contrast to the results for the LASSO and (but to a lesser extent) the Random Forest.

False Positives: Examining the false positives for the XGBoost model, as shown in Figure 7, it is apparent that listwise deletion is responsible for selecting more false features at the lowest missing rate compared to the baseline scenario. Conversely, at the higher missing rates, MICE Norm, together with the missRanger PMM versions and mixGB, are more prone to generating false positives. In particular, at 50% and 70% missing rates, the largest number of false positive features occurs after imputation with MICE Norm. Here, the features *schoolparents\_Other* and *fedstate\_HB* are the most frequently misidentified, appearing in 53 and 51 cases at the 50% missing rate, respectively. Thus, even though MICE Norm was best for selecting true positives with XGBoost, it is also the worst in terms of false positives when the missing rate is high.

# 5. Discussion

In this study, we evaluated how nine different imputation methods – listwise deletion, MICE Norm, MICE PMM, MICE RF, missRanger without PMM, missRanger with 3, 5, or 10 donors, and mixGB – affect the feature selection performance of three state-of-the art regression models: LASSO, Random Forest, and XGBoost. To this end, we used a subset of the NEPS Adult Cohort SC6 survey and examined how the feature selection of models trained



Figure 6.: Feature Selection for XGBoost: True Positives



Figure 7.: Feature Selection for XGBoost: False Positives

on the full dataset compared to those trained on the imputed datasets.. Our results show that the choice of imputation method significantly affects the effectiveness of feature selection, with certain imputation-model pairings outperforming others under certain missing data conditions.

## 5.0.1. LASSO

When using LASSO, missRanger without Predictive Mean Matching (PMM) consistently retained the highest number of true positive features across all missing rates. In fact, it was the method that best replicated the feature selection from the complete dataset compared to all other options. MICE Random Forest (MICE RF), missRanger with PMM, and mixGB also performed well, particularly at lower missing rates (10% and 30%). However, LASSO struggles to retain features when using listwise deletion and MICE Norm. LASSO inherently produced very few false positives across all imputation methods. Any observed false positives were minimal and primarily occurred with missRanger variants and mixGB, but these instances were negligible.

MissRanger without PMM offered the best balance for LASSO, maximizing true positives while virtually eliminating false positives. MICE RF and mixGB also provided a reasonable balance, though slightly less effective than missRanger without PMM.

# 5.0.2. Random Forest

Random Forests were robust in retaining true positives across all imputation methods, showing little sensitivity to the choice of imputation. Nearly half of the features selected in the complete data were consistently chosen, even at higher missing rates. However, Random Forests tended to select more false positives. In particular, MICE Norm and listwise deletion resulted in higher false positive rates, especially at lower missing rates (10% and 30%). At higher missing rates (50% and 70%), MICE Norm continued to produce more false positives.

No single imputation method stood out for Random Forests in balancing true and false positives. Avoiding MICE Norm and listwise deletion, however, reduced the number of false positives without compromising true positive selection.

## 5.0.3. XGBoost

MICE Norm facilitated the selection of more true positive features with XGBoost. However, it also led to a higher rate of false positives at increased missing rates. missRanger with PMM and mixGB introduced fewer false positives compared to MICE Norm.

MICE with PMM, MICE RF, missRanger with PMM, and mixGB provided a balanced approach with XGBoost, maintaining a reasonable number of true positives while minimizing false positives.

# 5.0.4. Comparing the Machine Learning Methods

Regarding feature selection, LASSO was the most conservative of the machine learning methods, yielding fewer true positives, particularly at higher missing rates. However, it also introduced the fewest false positives, making it ideal when minimizing false positives is essential. In contrast, Random Forests maintained the highest number of true positives across all imputation methods and missing rates, albeit with a higher count of false positives. XGBoost struck a balance, providing a moderate number of both true and false positives, particularly when paired with effective imputation methods like MICE with PMM or mixGB. This positioned XGBoost as a reasonable trade-off between true and false positives. However, combining XGBoost with MICE Norm at higher missing rates (50% or 70%) led to a significant rise in false positives, with the lowest false positive rates observed using MICE PMM or MICE RF.

#### 5.0.5. Relation to Previous Literature

Our findings align with prior research emphasizing the importance of selecting suitable imputation methods in conjunction with machine learning models. The strong performance of tree-based imputation methods, such as missRanger without PMM, corroborates their effectiveness in handling complex, high-dimensional datasets with mixed data types (Hayes 2018; Hayes and McArdle 2017). The increased false positives associated with MICE Norm, particularly with Random Forest and XGBoost at higher missing rates, support concerns about the limitations of linear model-based imputations in datasets with nonlinear relationships (Thurow et al. 2021). Compared to Schwerter et al. (2024b), who examined the impact of imputation methods on the use of tree-based prediction rule ensembles (Fokkema and Strobl 2020), the differences between tree-based imputation methods in our study are small.

As is typically observed in the literature, listwise deletion yielded inferior results (van Ginkel et al. 2020; Pepinsky 2018; Myers 2011). It demonstrated consistent underperformance across all combinations of imputation models, missing rates, and ML models, yielding to misaligned feature selections in comparison to the baseline cases.

In the context of feature selection, the application of PMM to missRanger resulted in the selection of a greater number of false positive features than in its absence. Even though missRanger with PMM might be better suited for statistical inference (Schwerter et al. 2024a), it might be worse for feature selection.

### 5.0.6. Recommendations

Our results add to the body of research that recommends avoiding listwise deletion. Furthermore, MICE standards for imputing missing data should be avoided when the primary goal is feature selection, as these methods tend to underperform in preserving important features and may lead to higher false positive rates. To achieve a sparse model with minimal false positives, LASSO is recommended, especially when paired with tree-based imputation methods. XGBoost provides a balanced approach between true positives and false positives, making it suitable for broader variable selection. The choice of feature selection method should be based on the research objectives: LASSO is ideal for identifying a sparse set of variables, while Random Forest selects a larger number of features, with XGBoost positioned in between. However, researchers should note that an increase in true positives often correlates with an increase in false positives, with LASSO generally being more effective than XGBoost, which in turn outperforms Random Forest in minimizing false positives. In addition, Random Forest and XGBoost are more resilient to missing data than LASSO when missingness exceeds 30%. Therefore, using XGBoost as a statistical learner after multiple imputation can achieve a good balance with optimal mean squared error results, while the right imputation method will further help reduce false positives.

### 5.1. Conclusions

Identifying a universally optimal combination of imputation and machine learning models for feature selection tasks is challenging. Practitioners must balance the importance of retaining true positives against the risk of introducing false positives. In our study, XGBoost also demonstrated superior Mean Squared Error (MSE) performance (see Appendix C), paired with imputation methods like MICE with PMM or RF and mixGB. It thus offers a pragmatic balance. Ultimately, the choice should align with the specific goals of the research, the nature of the data, and acceptable levels of false positives within the study's context. Furthermore, other considerations, such as interpretability or the ability to quantify uncertainty, could influence this recommendation and should also be factored into the decision.

# 5.2. Outlook

To generalize our results and more thoroughly evaluate imputation models, future studies should use datasets with different parameters and observations and include different variable types (numeric, categorical, integer). In addition, tuning hyperparameters for imputation methods such as Random Forests or XGBoost could improve their results and help practitioners identify the most relevant features during the imputation process.

A deeper investigation of threshold selection for feature filtering after training Random Forests or XGBoost could determine whether these methods can match or exceed the performance of LASSO in terms of false positives. In addition, examining the effects of retraining these models using the most significant features from the initial filtering could provide valuable insights.

Finally, while many false positives were associated with dummy variables corresponding to true positive features, future research could explore whether broader hot-encoding strategies – such as grouping similar states – could reduce the number of input features without sacrificing explanatory power, resulting in fewer false positives.

Finally, while our study found that missRanger without PMM performed better for feature selection, it underperformed in statistical inference in other studies (Gurtskaia et al. 2024; Schwerter et al. 2024a). Conversely, MICE Norm, while not effective for feature selection in our study, has demonstrated strong performance in official statistics, particularly in terms of univariate and multivariate distributional imputation accuracy for metric variables (Thurow et al. 2021, 2021, 2024), and provided reliable type I error control after imputation (Ramosaj et al. 2020). This raises the question of whether a single study, especially one aimed at selecting features for post-selection regressions (Belloni et al. 2014; Schwerter et al. 2022), should use different imputation methods for feature selection and regression analysis, at least when traditional distributional assumptions (like normality) are not met.

### Acknowledgments

This document uses data from the National Educational Panel Study (NEPS Network (2022); see Blossfeld and Roßbach (2019)). The NEPS is carried out by the Leibniz Institute for Educational Trajectories (LIfBi, Germany) in cooperation with a nationwide network.

The authors gratefully acknowledge the computing time provided on the Linux HPC cluster at Technical University Dortmund (LiDO3), partially funded as part of the Large-Scale Equipment Initiative by the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) as project 271512359.

Moreover, this work has been partly supported by the Research Center for Trustworthy Data Science and Security (https://rc-trust.ai), one of the Research Alliance centers within the https://uaruhr.de.

#### Declarations

### **Open Practice**

Materials and analysis code for the simulation study are available at ?.

# Funding

The project "From Prediction to Agile Interventions in the Social Sciences (FAIR)" has received funding from the programme "Profilbildung 2020" (PROFILNRW-2020-068), an initiative of the Ministry of Culture and Science of the State of North Rhine Westphalia. Sole responsibility for the content of this publication lies with the authors.

The authors gratefully acknowledge the computing time provided on the Linux HPC cluster at Technical University Dortmund (LiDO3), partially funded as part of the Large-Scale Equipment Initiative by the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation) as project 271512359.

### Conflict of interest

There is no conflict of interest

### Authors contribution

Author contributions: Conceptualization: AR, JS, MP; Data curation: AR; Formal analysis: AR; Funding acquisition: MP; Investigation: AR; Methodology: AR, JS, FD, MP; Project administration: JS; Resources: AR, JS; Software: AR; Supervision: JS, MP; Validation: AR; Visualization: AR, JS; Writing – original draft: AR, JS, MP; Writing – review & editing: AR, JS, FD, MP

### References

- Arizmendi CJ, Bernacki ML, Raković M, Plumley RD, Urban CJ, Panter AT, Greene JA, Gates KM. 2022. Predicting student outcomes using digital logs of learning behaviors: Review, current standards, and suggestions for future work. Behavior Research Methods:3026–3054. Available from: https://doi.org/10.3758/s13428-022-01939-9.
- Aßmann C, Würbach A, Saidani Y, Dumpert F. 2024. Full conditional distributions for handling restrictions in the context of automated statistical data editing. Conference paper, UN-ECE Expert Meeting on Statistical Data Editing, https://uneceorg/sites/default/files/2024-09/SDE2024\_S3\_LIFBI\_A%C3%9Fmann\_Dpdf.
- Beck M, Dumpert F, Feuerhake J. 2018. Machine learning in official statistics. arXiv preprint arXiv:181210422.
- Belloni A, Chernozhukov V, Hansen C. 2014. Inference on treatment effects after selection among high-dimensional controls. Review of Economic Studies. 81(2):608–650.
- Bischl B, Sonabend R, Kotthoff L, Lang M, editors. 2024. Applied machine learning using mlr3 in R. CRC Press. Available from: https://mlr3book.mlr-org.com.

Blossfeld HP, Roßbach HG. 2019. Education as a lifelong process. vol. 2. Springer VS Wiesbaden.

- Breiman L. 2001. Random forests. Machine learning. 45:5–32.
- Buczak P, Chen JJ, Pauly M. 2023. Analyzing the Effect of Imputation on Classification Performance under MCAR and MAR Missing Mechanisms. Entropy. 25(3):521.
- Byrnes JP, Miller DC. 2007. The relative importance of predictors of math and science achievement: An opportunity-propensity analysis. Contemporary Educational Psychology. 32(4):599–629.

Chen S, Haziza D. 2019. Recent developments in dealing with item non-response in surveys: A

critical review. International Statistical Review. 87(S1):S192-S218. Available from: https://onlinelibrary.wiley.com/doi/abs/10.1111/insr.12305.

- Chen T, Guestrin C. 2016. Xgboost: A scalable tree boosting system. In: Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining. p. 785–794.
- Chernozhukov V, Chetverikov D, Demirer M, Duflo E, Hansen C, Newey W, Robins J. 2018. Double/debiased machine learning for treatment and structural parameters. Econometrics Journal. 21(1):C1–C68.
- Chernozhukov V, Hansen C, Kallus N, Spindler M, Vasilis S. 2024. Applied Causal Inference Powered by ML and AI.
- Costantini E, Lang KM, Sijtsma K, Reeskens T. 2023. Solving the many-variables problem in MICE with principal component regression. Behavior Research Methods.
- Dagdoug M, Goga C, Haziza D. 2023. Imputation procedures in surveys using nonparametric and machine learning methods: An empirical comparison. Journal of Survey Statistics and Methodology. 11(1):141–188. Available from: https://doi.org/10.1093/jssam/smab004.
- de Waal T, Pannekoek J, Scholtus S. 2011. Handbook of statistical data editing and imputation. Wiley-Blackwell. Available from: http://dx.doi.org/10.1002/9780470904848.
- DeFranza D, Lindow M, Harrison K, Mishra A, Mishra H. 2021. Religion and Reactance to COVID-19 Mitigation Guidelines. American Psychologist. 76(5):744–754.
- Deng Y, Lumley T. 2023. Multiple imputation through xgboost. Journal of Computational and Graphical Statistics:1–19. Available from: https://doi.org/10.1080/10618600.2023.2252501.
- Dong Y, Peng CYJ. 2013. Principled missing data methods for researchers. SpringerPlus. 2:1–17.
- Doove LL, Van Buuren S, Dusseldorp E. 2014. Recursive partitioning for missing data imputation in the presence of interaction effects. Computational statistics & data analysis. 72:92–104.
- Dumpert F. 2023. Machine learning in german official statistics. In: Snijkers G, Bavdaž M, Bender S, Jones J, MacFeely S, Sakshaug JW, Thompson KJ, van Delden A, editors. Advances in business statistics, methods and data collection. John Wiley & Sons, Ltd; chap. 23; p. 537–560. Available from: https://onlinelibrary.wiley.com/doi/abs/10.1002/9781119672333.ch23.
- Dumpert F. 2024. Maschinelles Lernen im Statistischen Bundesamt Ein Uberblick über die Historie seit 2015 und aktuelle Entwicklungen. WISTA Wirtschaft und Statistik. 76(4):17–28.
- El Badisy I, Graffeo N, Khalis M, Giorgi R. 2024. Multi-metric comparison of machine learning imputation methods with application to breast cancer survival. BMC Medical Research Methodology. 24(1):191.
- Enders CK. 2023. Missing data: An update on the state of the art. Psychological Methods.
- Ewald FK, Bothmann L, Wright MN, Bischl B, Casalicchio G, König G. 2024. A guide to feature importance methods for scientific inference. In: Longo L, Lapuschkin S, Seifert C, editors. Explainable Artificial Intelligence; Cham. Springer Nature Switzerland. p. 440–464.

- FDZ-LIfBi. 2022. Data manual neps starting cohort 6– adults, adult education and lifelong learning, scientific use file version 13.0.0. Bamberg, Germany: Leibniz Institute for Educational Trajectories, National Educational Panel Study.
- Fokkema M, Strobl C. 2020. Fitting Prediction Rule Ensembles to Psychological Research Data: An Introduction and Tutorial. Psychological Methods. 25(5):636–652.
- Foster I, Ghani R, Jarmin RS, Kreuter F, Lane J, editors. 2020. Big data and social science: Data science methods and tools for research and practice. 2nd ed. CRC Press.
- Friedman JH, Hastie T, Tibshirani R. 2010. Regularization paths for generalized linear models via coordinate descent. Journal of Statistical Software. 33(1):1-22. Available from: https://www.jstatsoft.org/index.php/jss/article/view/v033i01.
- Friedrich S, Friede T. 2023. On the role of benchmarking data sets and simulations in method comparison studies. Biometrical Journal:2200212. Available from: https://doi.org/10.1002/ bimj.202200212.
- Gopalakrishna G, ter Riet G, Vink G, Stoop I, Wicherts JM, Bouter LM. 2022. Prevalence of questionable research practices, research misconduct and their potential explanatory factors: A survey among academic researchers in the Netherlands. PLoS ONE. 17(2 February):1–16. Available from: http://dx.doi.org/10.1371/journal.pone.0263023.
- Grinsztajn L, Oyallon E, Varoquaux G. 2022. Why do tree-based models still outperform deep learning on typical tabular data? Advances in Neural Information Processing Systems. 35(NeurIPS):507– 520.
- Gurtskaia K, Schwerter J, Doebler P. 2024. Adapting tree-based multiple imputation methods for multi-level data? A simulation study. arXiv preprint.
- Hajovsky DB, Chesnut SR, Jensen KM. 2020. The role of teachers' self-efficacy beliefs in the development of teacher-student relationships. Journal of School Psychology. 82(September):141– 158. Available from: https://doi.org/10.1016/j.jsp.2020.09.001.
- Hastie T, Tibshirani R, Friedman JH, Friedman JH. 2009. The elements of statistical learning: data mining, inference, and prediction. vol. 2. Springer.
- Hayes T. 2018. Investigating The Performance Of CART- And Random Forest-Based Procedures For Dealing With Longitudinal Dropout In Small Sample Designs Under MNAR Missing Data. In: Ferrer E, Boker SM, Grimm KJ, editors. Longitudinal multivariate psychology. New York: Routledge; chap. 10; p. 212 – 239.
- Hayes T, McArdle JJ. 2017. Evaluating the performance of CART-based missing data methods under a missing not at random mechanism. Multivariate Behavioral Research. 52(1):113–114. Available from: http://dx.doi.org/10.1080/00273171.2016.1264287.
- Hollenbach FM, Bojinov I, Minhas S, Metternich NW, Ward MD, Volfovsky A. 2021. Multiple Imputation Using Gaussian Copulas. Sociological Methods and Research. 50(3):1259–1283.
- Jadhav A, Pramod D, Ramanathan K. 2019. Comparison of performance of data imputation methods for numeric dataset. Applied Artificial Intelligence. 33(10):913–933.

- James G, Witten D, Hastie T, Tibshirani R. 2023. An introduction to statistical learning: With applications in python. Springer Nature.
- Lupyan G, Goldstone RL. 2019. Introduction to special issue. Beyond the lab: Using big data to discover principles of cognition. Behavior Research Methods. 51(4):1473–1476.
- Mayer M. 2024. missranger: Fast imputation of missing values. R package version 2.6.0, https://mayer79.github.io/missRanger/; Available from: https://github.com/mayer79/ missRanger.
- Measure A. 2023. Six years of machine learning in the bureau of labor statistics. In: Snijkers G, Bavdaž M, Bender S, Jones J, MacFeely S, Sakshaug JW, Thompson KJ, van Delden A, editors. Advances in business statistics, methods and data collection. John Wiley & Sons, Ltd; chap. 24; p. 561-572. Available from: https://onlinelibrary.wiley.com/doi/abs/10.1002/ 9781119672333.ch24.
- Molladavoudi S, Yung W. 2023. Exploring quality dimensions in trustworthy machine learning in the context of official statistics: model explainability and uncertainty quantification. AStA Wirtschafts-und Sozialstatistisches Archiv. 17(3):223–252.
- Molnar C. 2022. Interpretable machine learning. a guide for making black box models explainable. 2nd ed. https://christophm.github.io/interpretable-ml-book.
- Myers TA. 2011. Goodbye, listwise deletion: Presenting hot deck imputation as an easy and effective tool for handling missing data. Communication methods and measures. 5(4):297–310.
- NEPS Network. 2022. National educational panel study, scientific use file of starting cohort adults. Leibniz Institute for Educational Trajectories (LIfBi).
- Park JY, Dedja K, Pliakos K, Kim J, Joo S, Cornillie F, Vens C, Van den Noortgate W. 2023. Comparing the prediction performance of item response theory and machine learning methods on item responses for educational assessments. Behavior Research Methods. 55(4):2109–2124. Available from: https://doi.org/10.3758/s13428-022-01910-8.
- Peng CYJ, Harwell M, Liou SM, Ehman LH, et al. 2006. Advances in missing data methods and implications for educational research. Real data analysis. 3178:102.
- Pepinsky TB. 2018. A note on listwise deletion versus multiple imputation. Political Analysis. 26(4):480–488.
- Probst P, Wright MN, Boulesteix AL. 2019. Hyperparameters and tuning strategies for random forest. Wiley Interdisciplinary Reviews: data mining and knowledge discovery. 9(3):e1301.
- Putatunda S, Rama K. 2018. A comparative analysis of hyperopt as against other approaches for hyper-parameter optimization of xgboost. In: Proceedings of the 2018 international conference on signal processing and machine learning. p. 6–10.
- R Core Team. 2022. R: A language and environment for statistical computing. Vienna, Austria: R Foundation for Statistical Computing. Available from: https://www.R-project.org/.

Raghunathan T. 2015. Missing data analysis in practice. CRC press.

- Ramosaj B, Amro L, Pauly M. 2020. A cautionary tale on using imputation methods for inference in matched-pairs design. Bioinformatics. 36(10):3099–3106.
- Ramosaj B, Pauly M. 2019. Predicting missing values: A comparative study on non-parametric approaches for imputation. Computational Statistics. 34(4):1741–1764.
- Ramosaj B, Tulowietzki J, Pauly M. 2022. On the relation between prediction and imputation accuracy under missing covariates. Entropy. 24(3):386.
- Rubin DB. 1976. Inference and missing data. Biometrika. 63(3):581-592.
- Rubin DB. 1987. Multiple imputation for nonresponse in surveys. John Wiley and Sons, Inc.
- Rubin DB. 1996. Multiple imputation after 18+ years. Journal of the American Statistical Association. 91(434):473–489.
- Saidani Y, Dumpert F, Borgs C, Brand A, Nickl A, Rittmann A, Rohde J, Salwiczek C, Storfinger N, Straub S. 2023. Qualitätsdimensionen maschinellen Lernens in der amtlichen Statistik. AStA Wirtschafts-und Sozialstatistisches Archiv. 17(3):253–303.
- Schafer JL, Graham JW. 2002. Missing data: our view of the state of the art. Psychological methods. 7(2):147.
- Schwerter J, Dimpfl T, Bleher J, Murayama K. 2022. Benefits of additional online practice opportunities in higher education. Internet and Higher Education. 53:100834.
- Schwerter J, Gurtskaia K, Romero A, Zeyer-Gliozzo B, Pauly M. 2024a. Evaluating tree-based imputation methods as an alternative to mice pmm for drawing inference in empirical studies. Working paper.
- Schwerter J, Schroeder V, Fokkema M, Doebler P. 2024b. Interpretable Prediction Rule Ensembles in the Presence of Missing Data. Arxivorg:1–35. Available from: http://arxiv.org/abs/2410. 16187.
- Schwerter J, Stang-Rabrig J, Kleinkorres R, Bleher J, Doebler P, McElvany N. 2024c. Importance of students' social resource factors for academic achievement and well-being in elementary school. European Journal of Psychology of Education. 39:4515–4552.
- Srinivas P, Katarya R. 2022. hyoptxg: Optuna hyper-parameter optimization framework for predicting cardiovascular disease using xgboost. Biomedical Signal Processing and Control. 73:103456.
- Stekhoven DJ, Bühlmann P. 2012. Missforest—non-parametric missing value imputation for mixedtype data. Bioinformatics. 28(1):112–118.
- Suh H, Song J. 2023. A comparison of imputation methods using machine learning models. Communications for Statistical Applications and Methods. 30(3):331–341.
- Thurow M, Dormuth I, Sauer C, Ditzhaus M, Pauly M. 2023. How to Simulate Realistic Survival Data? A Simulation Study to Compare Realistic Simulation Models. Working paper.
- Thurow M, Dumpert F, Ramosaj B, Pauly M. 2021. Imputing missings in official statistics for general tasks–our vote for distributional accuracy. Statistical Journal of the IAOS. 37(4):1379–1390.

- Thurow M, Dumpert F, Ramosaj B, Pauly M. 2024. Assessing the multivariate distributional accuracy of common imputation methods. Statistical Journal of the IAOS. 40(1):99–108.
- United Nations Economic Commission for Europe. 2019. Generic statistical business process model (gsbpm), v5.1. https://unece.org/sites/default/files/2023-11/GSBPM
- United Nations Economic Commission for Europe. 2021. Machine learning for official statistics. UN-ECE project report, https://unece.org/statistics/publications/machine-learning-official-statistics.
- van Buuren S. 2018. Flexible imputation of missing data. second edition. Boca Raton, FL.: CRC Press.
- van Buuren S, Groothuis-Oudshoorn K. 2011. mice: Multivariate imputation by chained equations in R. Journal of Statistical Software. 45(3):1–67.
- van Delden A, Burger J, Puts M. 2023. Ten propositions on machine learning in official statistics. AStA Wirtschafts-und Sozialstatistisches Archiv. 17(3):195–221.
- van Ginkel JR, Linting M, Rippe RC, van der Voort A. 2020. Rebutting Existing Misconceptions About Multiple Imputation as a Method for Handling Missing Data. Journal of Personality Assessment. 102(3):297–308. Available from: https://doi.org/10.1080/00223891.2018.1530680.
- Westermeier C, Grabka MM. 2016. Longitudinal wealth data and multiple imputation an evaluation study. Survey Research Methods. 10(3):237–252.
- Wright MN, Ziegler A. 2017. ranger: A fast implementation of random forests for high dimensional data in C++ and R. Journal of Statistical Software. 77(1):1–17.
- Zahid FM, Faisal S, Heumann C. 2020. Variable selection techniques after multiple imputation in high-dimensional data. Statistical Methods & Applications. 29(3):553–580.
- Zettler I, Schild C, Lilleholt L, Kroencke L, Utesch T, Moshagen M, Böhm R, Back MD, Geukes K. 2022. The Role of Personality in COVID-19-Related Perceptions, Evaluations, and Behaviors: Findings Across Five Samples, Nine Traits, and 17 Criteria. Social Psychological and Personality Science. 13(1):299–310.

# Appendix A. Mappings and Detailed Descriptions for Factor Variables

Along this section are listed the different levels for each feature in frequency descending order.

# A.1. Classification of Profession Requirement

The requirement for the profession of the respondent according to the KldB (in German: Klassifikation der Berufe).

Final Level	Description
Skilled	Specialized activities
HighComplx	Highly complex activities
Complx	Complex specialist activities
LowComplx	Helpers and semi-skilled work

# A.2. Marital Status

Table A2.: Levels Available in maritalstatus.

Final Level	Description
married	Married or in registered civil partnership
single	Single
divorced	Divorced
widowed	Widowed

### A.3. Educational Level

For this feature, eight levels were initially available but they were reduced to just 4 in order to reduce the dimensionality of the data. In Table A3 are shown the mappings made and the former levels with their descriptions.

# Table A3.: Mappings and Detailed Description for education.

Final Level	Former Level / Description
LowerSec	no qualification Lower secondary school leaving certificate without vocational training Lower secondary school leaving certificate with vocational training
Secondary	Secondary school leaving certificate without vocational training Secondary school leaving certificate with vocational training
Abitur	Abitur without vocational training Abitur with vocational training
University	University of Applied Sciences degree University degree

# A.4. Company Size

The size of the company in terms of number of employees.

Table A4.: Levels Available in compsize.

Final Level	Description
$     \begin{array}{c}       3 \\       4 \\       1 \\       2     \end{array} $	20 to less than 200 persons 200 persons or more Less than 10 persons 10 to less than 20 persons

# A.5. Sector

The industry sector of the company in which the respondent is working.

Final Level	Description
3	Public and personal services
2	Economic services
1	Manufacturing
4	Other industries

# A.6. Parents' Qualification

Highest school-leaving qualification from surveyed's parents.

Table A6.: Mappings and Detailed Description for schoolparents.

Final Level	Former Level / Description
HauptS HighSDip RealS NoSCert Other	Secondary school leaving certificate I $\rightarrow$ Haupt-, Volksschulabschluss Secondary school leaving certificate III $\rightarrow$ (Technical) Abitur Secondary school leaving certificate II $\rightarrow$ Mittlere Reife, Realschulabschluss No school-leaving qualification Other school-leaving qualification

# A.7. Federal States

Mapping according to the code for each German State.

Final Level	Former Level / Description	
NW	Nordrhein-Westfalen	
BY	Bayern	
BW	Baden-Württemberg	
NI	Niedersachsen	
HE	Hessen	
RP	Rheinland-Pfalz	
SN	Sachsen	
BE	Berlin (Gesamt)	
ST	Sachsen-Anhalt	
TH	Thüringen	
BB	Brandenburg	
SH	Schleswig-Holstein	
HH	Hamburg	
MV	Mecklenburg-Vorpommern	
SL	Saarland	
HB	Bremen	

Table A7.: Mappings and Detailed Description for fedstate.

# Appendix B. Distribution Plots

In this section are plotted the histogram or count plots for each of the variables present in the dataset before they were encoded.

# B.1. Numeric Variables









Figure B2.: Distribution Plots for the Integer Variables









# B.4. Target Variable



Figure B5.: Distribution Plots for the Target Variable

### Appendix C. Additional Imputation and Regression Results

We compare the eight imputation methods on three different dimensions: 1. Imputation accuracy. We use two metrics to measure the preservation of true values by the imputation methods, the Normalized Root Mean Squared Error (NRMSE) and a so-called imputation performance measure (IPM). Here, NRMSE allows for fair comparisons in presence of the different scales (Jadhav et al. 2019) while IPM was proposed by Suh and Song (2023) as a summarizing metric for both, numerical and categorical variables, based on the Gower distance. 2. Estimation accuracy of correlation coefficients. Using either Pearson or Spearman correlation coefficients, we compare the resulting correlation matrices of the true and the imputed data sets by means of the Frobenius distance, Mean Absolute Error and RMSE. 3. Feature Selection. We additionally assess the effect of the eight imputation methods on the interpretability of subsequently applied prediction models. To this end we analyze feature selection after imputation of three common prediction models: An interpretable linear model with LASSO regularization, see, e.g., Hastie et al. (2009), and the two tree-based learners Random Forest (Breiman 2001) and XGBoost (Chen and Guestrin 2016). While the LASSO approach performs an automatic feature selection, the two treebased approaches build their selection on the resulting feature importances (Hastie et al. 2009; Chen and Guestrin 2016) by choosing a predefined number of the most important features. In case of multiple imputation, the process has to be adapted as outlined in the Simulation section below.

### C.1. Imputation Results

#### C.1.1. NRMSE

The NRMSE results shown in Figure C1 indicate that *missRanger0* consistently provides the best performance. The *listwise* deletion method is excluded from this analysis because it requires imputed values to compute the distance to the true values, which is not present in this approach.

Looking at the three implementations of MICE, both PMM and *norm* show similar NRMSE trends across all missingness levels, with NRMSE increasing as missing data rates increase. Compared to Random Forests, these two MICE implementations outperform at missingness rates below 30%, but underperform at rates of 50% and 70%. In particular, the NRMSE for Random Forest imputation worsens as the missingness rate increases.

For missRanger and mixGB, both show a similar pattern across all missingness levels: missRanger0 leads in performance, followed by mixGB, and then by missRanger implementations with PMM. There is no clear improvement in NRMSE with respect to the number of donors selected. However, higher missingness rates consistently result in higher NRMSE values, with missRanger without PMM maintaining the lowest NRMSE regardless of the missingness rate.



Figure C1.: NRMSE Results for the chosen Imputation Methods and Missingness Rates

# C.1.2. IPM

Figure C2 shows the IPM values for each imputation method over different missingness rates. Notably, the *listwise* deletion method is excluded because IPM measures imputation quality and this method does not perform any imputation, only removes observations with missing data.

Bayesian linear regression (norm) ranks first for missingness rates of 30% and above. Within the *MICE* framework, Random Forests (RF) outperforms Predictive Mean Matching (pmm) for all missingness rates. Both methods show deteriorating IPM results as missingness increases up to 50%, but at 70% IPM decreases again, although it remains higher than at 30%.

For *missRanger*, PMM results are similar across donor numbers (3, 5, and 10), but consistently worse than *missRanger0* for missingness below 30%, with the gap narrowing at 70% missingness. Variance increases for *missRanger* without PMM at 50% and 70% missingness, but the number of donors does not significantly affect IPM. Imputations with

*mixGB* show similar median results to *missRanger0*, though slightly worse with lower variance. However, *mixGB* consistently outperforms any *missRanger* implementation with PMM in terms of median IPM.

In summary, excluding *norm* methods, Random Forests in MICE (RF) delivers the best IPM results, followed by *missRanger0* and *mixGB* over all missingness rates. At 70%, *mixGB* surpasses *missRanger* in median performance, although *missRanger* has a wider range of results compared to XGBoost imputations.



Figure C2.: IPM Results for each Imputation Method and Missingness Rate

# C.1.3. Correlations Review

Having focused on the predictive accuracy of imputation methods, we now examine how these methods affect data correlations and potential shifts in variable distributions.

Figure C3 illustrates the distances between the correlation matrix of the original dataset (before value amputation) and the correlation matrices of the datasets after imputation. The most significant deviations between metrics are observed for *missRanger0*, especially at missingness rates of 50% and 70%.

While Spearman's coefficients generally indicate similar results, the differences are more pronounced at the 50% rate compared to the 70% rate. With the exception of *missRanger* without PMM, most methods show robustness. However, *norm*, *pmm*, and *mixGB* show slightly larger deviations in correlation distances compared to the other methods.

Figure C3.: Mean Correlation Distances between the Imputed and the Original Dataset, shown by Imputation Method and Missingness Rate



C.1.4. Discussion of the Imputation Results

Table C1 provides a summary of the imputation method performance across the three metrics NRMSE, IMP and correlation. Methods are categorized based on their effectiveness for each metric: those in the top three are marked with three stars (\*\*\*), those between fourth and seventh are marked with two stars (\*\*), and the bottom three are marked with one star (\*).

For brevity, the results of the NRMSE and IPM have been combined into a single metric, with the calculation details outlined in the Appendix E. In this context, missRanger0 and norm showed the best performance, followed by MICE RF, mixGB, and MICE PMM. In terms of correlation distances, the smallest deviations from the baseline case were observed with MICE RF, missRanger3, and missRanger5, followed closely by missRanger10, MICE norm, and mixGB.

Concluding, although norm shows strong performance in terms of (predictive) accuracy, it is important to note, as highlighted by Thurow et al. (2021), that high accuracy in data reproducibility does not necessarily imply that probability distributions are wellpreserved. This is evident from the correlation results, where norm does not rank among the top performers. Taking this into account, the methods RF, missRanger0, mixGB and missRanger10 appear to strike a favorable balance across the two metrics. They provide relatively accurate results within expected ranges and maintain correlation distances better than other methods.

Table C1.: Imputation Results Summary. According to each metric the top 3 get 3 stars  $(^{***})$ , the next 3 get 2 stars  $(^{**})$  and the lowest 3 get 1 star  $(^{*})$ .

[2 pt] Method	Accuracy	Correlation
listwise	*	*
MICE norm	***	**
MICE PMM	**	*
MICE RF	***	***
missRanger.0	***	*
missRanger.3	*	***
missRanger.5	*	***
missRanger.10	**	**
mixGB	**	**
[2 pt]		

### C.2. Regression

#### C.2.1. Baseline Regression Results

Table C2 provides the summary statistics from 100 iterations used to train the three statistical learners models for the complete dataset as a baseline or best case scenario. From these results, XGBoost (regr.xgboost) achieves the lowest MSE minimum, median, mean and maximum, closely followed by Random Forests (regr.ranger), and then LASSO (regr.cv\_glmnet). I.e. the outcome variable is best explained using XGBoost when using the complete data.

[2 pt] ML Method	Min	1st. Qu.	Median	Mean	3rd. Qu.	Max	$\mathbf{SD}$
LASSO Random Forest XGBoost	$0.182 \\ 0.138 \\ 0.132$	$0.185 \\ 0.141 \\ 0.134$	$0.186 \\ 0.142 \\ 0.135$	$0.186 \\ 0.142 \\ 0.136$	$0.187 \\ 0.143 \\ 0.137$	$0.189 \\ 0.146 \\ 0.140$	$0.002 \\ 0.002 \\ 0.002$
[2 pt]							

Table C2.: Summary Statistics for the MSE computed in the Complete Dataset.

# C.2.2. Regression Results in Comparison

Figure C4 shows the Mean Squared Errors (MSEs) for each combination of statistical learner and imputation method for each of the missingness rates per panel. In addition, the horizontal lines indicate the median MSE using the complete data, as detailed in Table C2. The color coding of these lines is consistent with the legend.

Figure C4.: Mean Squared Error for each Imputation Method. The horizontal Lines are the Median of the MSEs obtained for the Complete Dataset



The results for listwise deletion are omitted from Figure C4 to improve the overview, because combination of the statistical learners and listwise deletion resulted in outliers making it difficult to detect smaller differences between the other combinations<sup>1</sup>. Results incorporating listwise deletion can be found in Appendix D.

When evaluating the machine learning models, LASSO consistently has the highest error relative to the other models under identical missingness rates and imputation methods, which is in-line with the baseline using complete data. XGBoost consistently achieves the lowest MSE, except at a 50% missingness rate for the MICE norm and pmm imputations, where the Random Forest models show a slightly lower median MSE.

The influence of increasing missingness rates generally leads to increased MSEs, peaking at 50% before declining slightly at 70%, though not to the levels observed at 30%. Notably, the norm, and missRanger0 imputation methods show a less pronounced increase in MSE with increasing missingness, suggesting improved robustness. These three methods also consistently outperform other imputation techniques in terms of MSE across the range of missingness rates examined. In all contexts, the model predictions fail to exceed the median MSE achieved with the complete dataset. The only exception is that the minimum of the combination of LASSO with missRanger without PMM at 10% missingness was lower than the median baseline.

Examining missRanger, the inclusion of PMM appears to increase the MSE compared to its counterpart without PMM. The number of donors (3, 5, and 10) does not significantly change the MSE results when PMM is applied. Tree-based imputation methods generally perform similarly across MSE assessments at all missingness rates, with mixGB showing slightly better results at missingness rates of 50%.

# C.3. Discussion of MSE results

In terms of MSE results, XGBoost shows superior performance, especially with non-PMM methods such as missRanger0 and norm and a missingness rate of 10%, 30% and 70%. Only for 50% are the MSE results for XGBoost and Random Forest mostly overlapping. Regardless of the statistical learner, listwise consistently produces the worst results. In addition, increasing the missingness rate generally increases the MSE up to 50%, followed by a slight decrease at 70%, but not enough to reach the levels observed at 30%. There is also no evidence that using the same methods for imputation and regression (e.g., mixGB and XGBoost) is better than using different methods for imputation than for regression (e.g., MICE PMM and XGBoost).

<sup>&</sup>lt;sup>1</sup>Particularly for the highest missingness rates 50% and 70%, listwise deletion reduces the size of the dataset to the point where there is insufficient data to train valid models under the nested resampling framework employed. In some cases, datasets were completely depleted of entries. In addition, training the LASSO model proved at times infeasible in certain scenarios due to features with singular observations (such as subsets containing only one gender), which resulted in computational failures. In addition, the MSE values for scenarios where simulations yielded results ranged from 0.5 to 1.25, making the box plots for other methods too small for meaningful analysis.

For missRanger, including the number of donors pmm.k tends to increase the MSE, and there is no significant improvement or reduction in MSE between values 3, 5, and 10. Using mixGB for imputation produces very similar (missingness rate = 10% or 30%) or slightly better results than missRanger with PMM (missingness rate = 50% or 70%).

# Appendix D. Additional MSE Results

# D.1. MSE including listwise deletion

Figure D1.: Mean Squared Error for each Imputation Method including listwise deletion. The horizontal Lines are the Median of the MSEs obtained for the Complete Dataset



# Appendix E. Imputation Accuracy Normalization Details

Table E1 has the results of the normalizations for both NRMSE and IPM into one single average. The second and the third column show the median of the metrics for each imputation method (at all missingness rates). Then, these values are normalized each to a scale between 0 and 1, being 0 the value for the lowest calculation and 1 for the maximum. And then these two normalized values are averaged per method.

Method	NRMSE (median)	IPM (median)	Norm. NRMSE	Norm. IPM	Average
missRanger0	1.034	0.251	0.000	0.548	0.274
norm	1.330	0.225	0.909	0.000	0.455
$\mathbf{RF}$	1.305	0.244	0.832	0.393	0.613
mixGB	1.250	0.256	0.664	0.640	0.652
pmm	1.330	0.263	0.909	0.785	0.847
missRanger10	1.310	0.269	0.848	0.909	0.878
missRanger5	1.315	0.269	0.863	0.909	0.886
missRanger3	1.315	0.269	0.863	0.909	0.886
listwise	1.360	0.273	1.0000	1.0000	1.000

Table E1.: Detailed Calculations for the normalization of the NRMSE and IPM

For the listwise deletion case, given that there was no computation, both the NRMSE and IPM were assigned to be equal to the maximum observed value per case plus 10% of the difference between the maximum and the minimum (the range) observed values per metric. These values are shown with <u>underlined</u> numbers.

# E.1. Discussion

With regard to the performance of the imputation models, the results indicated that missRanger.0 and MICE norm exhibited promising outcomes with respect to accuracy, as evidenced by the NRMSE and IPM metrics, which are measures of reproducibility. However, the results indicated that there were significant discrepancies between the imputed and original datasets, as evidenced by the significant correlation distances observed between the two.

The results of imputation models indicate that MICE with PMM and RF, along with missRanger.3 and mixGB, offer an optimal balance between accuracy and minimal correlation variance, while maintaining efficient computational times (not shown in the manuscript).

With regard to the MSE results obtained subsequent to imputation, XGBoost demonstrated superior performance relative to LASSO and Random Forests under identical missingness rates and imputation methods. Specifically, at missingness rates exceeding 30%, XGBoost in conjunction with missRanger.0 and MICE norm exhibited lower MSEs than other imputation methods.

With regard to missRanger, the study revealed that in the absence of PMM, it demon-

strated consistent and robust imputation accuracy (NRMSE and IPM) and prediction error (MSE) across a range of missingness rates. However, it was observed that the correlation distances were relatively larger, particularly above 30%. The incorporation of PMM resulted in enhanced correlation distances, yet it led to a deterioration in NRMSE, IPM, and MSE. No notable alterations were observed when the number of donors was varied.