# Towards Efficient and Explainable Hate Speech Detection via Model Distillation

Paloma  $Piot^{[0000-0002-7069-3389]}$  and Javier  $Parapar^{[0000-0002-5997-8252]}$ 

IRLab, CITIC, Universidade da Coruña, Spain paloma.piot@udc.es javier.parapar@udc.es

Abstract. Automatic detection of hate and abusive language is essential to combat its online spread. Moreover, recognising and explaining hate speech serves to educate people about its negative effects. However, most current detection models operate as black boxes, lacking interpretability and explainability. In this context, Large Language Models (LLMs) have proven effective for hate speech detection and to promote interpretability. Nevertheless, they are computationally costly to run. In this work, we propose distilling big language models by using Chain-of-Thought to extract explanations that support the hate speech classification task. Having small language models for these tasks will contribute to their use in operational settings. In this paper, we demonstrate that distilled models deliver explanations of the same quality as larger models while surpassing them in classification performance. This dual capability —classifying and explaining— advances hate speech detection making it more affordable, understandable and actionable.<sup>1</sup>

This article contains illustrative instances of hateful language.

Keywords: hate speech  $\cdot$  explainable AI  $\cdot$  knowledge distillation

## 1 Introduction

Social media and internet platforms have considerably enhanced global networking and communication. But this rise in connectivity has also exacerbated the propagation of hate speech, which is affecting people globally [43,21]. The literature consensus [11,15,30,13,14,41,10] on the hate speech definition frames it as "language characterized by offensive, derogatory, humiliating, or insulting discourse [15] that promotes violence, discrimination, or hostility towards individuals or groups [11] based on attributes such as race, religion, ethnicity, or gender [13,14,10]". In the rest of this paper, we will assume that definition, which highly aligns with the United Nations one [32], differentiating hate from offensive and neutral speech. Regarding the gravity of this phenomenon in the online world, studies reveal that about 30% of youth experience cyberbullying [24], and 46% of Black and African American adults encounter online racial harassment [2].

<sup>&</sup>lt;sup>1</sup> Our code, models and prompts are available at https://github.com/palomapiot/ distil-metahate.

It was already in 1997 when researchers suggested to use Machine Learning (ML) models to identify different types of harmful messages [42]. Since then, there have been efforts for detecting hate speech spanning from linear models like Support Vector Machines (SVM) or Logistic Regressors [46,11,36] to more recent state-of-the-art methods based on transformers [37,19,35] or LLMs [25,12,3].

Many ML models have limitations because they operate as black boxes, making them hard to interpret. Also, these models only classify without explaining the reasons. Explaining why content is blocked or flagged as hate speech is essential for transparency and trust in online platforms [18,28].

The Digital Services Act (DSA) [9], which came into force for all platforms in 2024, is a landmark regulation that sets clear obligations for online platforms, including social media, on content moderation practices. Platforms must provide clear explanations for content removal or restrictions, along with an appeals process for users. Existing efforts for content moderation span from automatic moderation to manual revision of publications, including new approaches like Community Notes by X (formerly Twitter). This feature provides additional information and context about a post. Ideally, automatic detection and explanation of hate speech could be implemented in a similar way (see Figure 1). Clear natural language rationales help users understand the reasons behind hateful actions, promoting fairness and reducing misunderstandings [8]. To generate such rationales, LLMs were proposed in Zero-Shot, Few-Shot, or



Fig. 1. X's Community Notes feature for adding post context.

fine-tuned settings [3,16,34]. However, although, LLMs excel in reasoning and offer remarkable capabilities, they come with notable challenges, particularly in terms of cost, deployment, and resource requirements [40,4].

We propose a method that leverages LLM-generated rationales with Few-Shot and Chain-of-Thought (CoT) [47] prompts to distil smaller models. This approach retains the advanced capabilities of larger models while being more cost-effective [48,33,50]. Our method involves extracting rationales with 70B LLMs using Few-Shot CoT prompting, followed by employing them to fine-tune a smaller model within a multi-task learning framework. This framework enables models to learn both classification (generating labels) and explanation (providing supporting rationales). We evaluate our method against state-of-the-art models and conduct qualitative analysis with human reviewers to assess the quality of the rationales.

Our contributions are the following: (i) we propose a hate speech detection approach that uses sample data from 36 diverse human-curated datasets, en-

hancing its generalisation capabilities; (ii) we fine-tune a small language model, transferring knowledge from a larger one, to predict both labels and rationales using a multi-task learning framework; (iii) we evaluate the classification task against four state-of-the-art models and conduct a human evaluation to assess the quality of the generated rationales.

# 2 Related Work

Most traditional approaches for hate speech classification have focused on predicting whether a piece of text is hate speech or not [17,37,19]. Additionally, some works have addressed multicategory and multilabel approaches [46,11]. Recent studies have also explored the use of LLMs for hate speech classification [45,25]. These methods require large amounts of data to achieve generalisation and often lack explainability, making it difficult to understand why a text is labelled as hate speech.

More recently, some studies have attempted to add explanations to hate speech posts, typically by marking the spans of text where the hate speech is present [30] or providing vague explanations that lack sufficient detail [39,7]. Other researchers have explored generating explanations using LLMs [48,50,33]. For example, Nirmal et al. [33] propose using LLMs to extract features from input texts to train BERT classifiers, aiming to improve interpretability. Their framework maintains classification performance while enhancing the model's explainability. While these studies have improved over traditional binary hate speech classification approaches, they often use explanations to enhance the detection process without assessing the quality of the explanations.

These new approaches using big LLM are very costly to run. This opens up an avenue for knowledge distillation, a mechanism of transferring expertise from a large model to a smaller, more affordable one. This technique started with BERT and transformer-based models [38,20]. However, with the rise of LLMs, this method has become particularly important, as it enables LLMs' capabilities to be transferred to smaller models, improving efficiency, speed, and scalability while reducing costs and resource requirements. Hsieh et al. [23] propose a novel approach to generate step-by-step explanations with LLMs and distil this knowledge into smaller models. Other recent works have also focused on similar methods to improve LLMs' reasoning skills [44] and enhance their performance in commonsense reasoning and arithmetic tasks [29,22].

In this line of distilling LLMs, Yang et al. propose a method for generating hate speech explanations using LLMs, which are then used to fine-tune other models (knowledge distillation) [48]. They generate explanations in a zero-shot scenario, and also using human-authored reasoning. The study assesses the classification improvement gained by using these rationales but does not evaluate the quality of the generated explanations. Zhang et al. have distilled LLMs for toxic content detection using Decision-Tree-of-Thought (DToT) prompting [50]. Their approach improves the classification accuracy of baseline models, but the quality of the generated rationale is only evaluated by checking if the model generates

more than a binary response (toxic yes/no) without assessing the explanation's quality. Our work aligns with this research, focusing on detecting hate speech in social media posts and generating supporting evidence to improve detection. However, we also evaluate the quality of the generated rationales, assessing both their completeness and correctness.

# 3 Proposal

We propose performing knowledge distillation using the Llama-3-70B-Instruct model as the **big**, **teacher** model, transferring its knowledge to the **small**, **student** Llama-3-8B-Instruct model [1]. We prepared two hate speech datasets as explained in §4.1. With the first, we extracted from the teacher model binary labels for hate speech together with the explanations (rationales), using Few-Shot CoT prompting. Then, we transferred the knowledge to the student model and distilled it following the procedure described in §3.1, resulting in Llama-3-8B-Distil-MetaHate. For evaluation, we employed the second dataset, and we tested the **teacher** model, its smaller version (**base**), and the new distilled version (**distilled**). Figure 2 shows the experimental setup of our current work.



Fig. 2. LLM Knowledge distillation with CoT overview.

### 3.1 Knowledge Distillation

Knowledge Distillation is a machine learning technique designed to transfer knowledge from a large pre-trained model, called **teacher**, to a smaller **student** model. The goal of knowledge distillation is to train a smaller, more efficient model to replicate the behaviour of a larger, more complex model. Next, we explain how we performed this process.

**Extract Rationales** The first phase is to extract knowledge from the large model. For this, we employed Chain-of-Thought In-Context Learning [5,47] to

extract rationales from the teacher model. To achieve this, we created a prompt template p that explains how to solve the task, focusing on two main points: (1) providing the model with the definition of hate speech, and (2) instructing the model on what to do. Each prompt p was structured as a tuple  $(H, [x_p, r_p, y_p])$ , where H is the hate speech definition, and  $[x_p, r_p, y_p]$  is a list of examples containing: an input text  $x_p$ , its corresponding label  $y_p$ , and a human-authored rationale  $r_p$  explaining why  $x_p$  is categorized as  $y_p$ . Let  $D = \{(x_i, y_i)\}_{i=1}^N$  represent our dataset, where each  $x_i$  denotes an input and  $y_i$  is its corresponding label, we appended each dataset instance  $x_i \in D$  to the prompt p and used it to instruct the model to generate both the rationale  $\hat{r}_i$  and the classification  $\hat{y}_i$ for each  $x_i$ . The rationales included in our context prompt are used to guide the model towards our task objective: generate the dataset's D rationales  $\hat{r}_i$  and labels  $\hat{y}_i$ . Although the text's label is already in our data, we generated both the label and an explanation, as matching label generations are more likely to have a correct explanation. This allows us to use them to train our smaller model.

**Train Small Model with Rationales** After obtaining the labels and rationales, we incorporated them into the training process of our distilled model. Now our dataset D also includes the generated rationale  $\hat{r}_i$ . We only included the samples where the teacher model's label matched the gold label, therefore  $y_i = \hat{y}_i$ . In this work, we are treating this proposal as a multi-task problem where the model  $f(x_i) \to (\hat{y}_i, \hat{r}_i)$  learns both to predict labels  $\hat{y}_i$  and generate rationales  $\hat{r}_i$ . The overall objective combines these two tasks, leading to the total optimization goal of  $\mathcal{L} = \alpha \mathcal{L}_{\text{label}} + \beta \mathcal{L}_{\text{rationale}}$  [23] where  $\mathcal{L}_{\text{label}}$  focuses on the label prediction  $\mathcal{L}_{\text{label}} = \frac{1}{N} \sum_{i=1}^{N} \ell(y_i, \hat{y}_i)$ , where  $\ell()$  is the cross-entropy loss, and  $\mathcal{L}_{\text{rationale}}$  is:

$$\mathcal{L}_{\text{rationale}} = \frac{1}{N} \sum_{i=1}^{N} \sum_{t=1}^{T_i} \ell(f(x_i)_t, \hat{r}_{it})$$
(1)

Equation (1) represents the average loss over N samples, where for each sample *i* the model generates a sequence of  $T_i$  rationale tokens. The loss function  $\ell(f(x_i)_t, \hat{r}_{it})$  –cross-entropy– measures the discrepancy between the predicted token  $f(x_i)_t$  and the true token  $\hat{r}_{it}$  at each step *t*. The goal is to minimize this loss across all tokens and samples to improve the rationale generation. The rationale generation helps the model produce intermediate reasoning steps, which can enhance its label prediction accuracy, i.e. by reasoning step-by-step, the model can better analyse the messages, improving its accuracy in the labelling.

## 4 Experiments

Now, we describe the datasets, the models, and the experiments conducted.

#### 4.1 Datasets

We conducted our experiments on two subsamples of MetaHate [35]. MetaHate is a meta-collection of 1.2 million entries, labelled in a binary fashion, compiled

from 36 different datasets across various social networks. This made it an ideal choice for our study, given the diversity of the data it contains.

For our task, we created two balanced subsamples from this dataset, with around 2000 messages each. Each subsample was balanced in two ways: (1) they contained an equal number of entries labelled as hate and non-hate, and (2) the ratio of posts from each original dataset was maintained, reflecting the source distribution in MetaHate. Due to the high computational cost of inferring and fine-tuning LLMs, we chose to work with these samples instead of using the full collection. Moreover, inspired by the results of Hsieh et al. [23], which showed that distilling step-by-step explanations outperforms standard fine-tuning with much less data, we decided that using only part of the dataset was adequate.

- MiniMetaHate Distil: The first subsample was created to extract rationales and labels with the large model, where 2993 samples were inferred. Later, together with the generated explanations, it was used to distil the smaller model, but only using the entries where the gold label was equal to the generated label. This ended up in a 2296 sample of corrected classified posts. Size: 2296 posts.
- MiniMetaHate Eval: The second subsample was designed to evaluate the models, focusing on both classification performance and the quality of the generated explanations. This set is used to test and validate the model's effectiveness. Size: 2001 posts.

## 4.2 Chosen LLMs

For knowledge distillation, we need a large model with strong reasoning capabilities and a smaller counterpart that can learn from it. Based on recent reports [31], we decided to include the most capable open-source models available to date in this experiment.

- Llama-3-70B-Instruct (Teacher) [1]: This instruction-tuned model is optimized for dialogue use cases, offering exceptional performance in conversational tasks. This model surpasses many available open-source chat models on industry-standard benchmarks, providing superior accuracy and responsiveness. It also demonstrates exceptional ability in reasoning tasks.
- Llama-3-8B-Instruct (Student) [1]: This is the same model as the Teacher but with 8B parameters instead of 70B. It is known for being fast and costeffective, making it an ideal choice for learning from a larger model and for use in production environments.

#### 4.3 Experimental Settings

Our experimental approach consists of two steps:

First, we used a large language model (Llama-3-70B-Instruct) and a labelled dataset ("MiniMetaHate Distil") to generate output labels along with explanations, called rationales, that justify the labels. These rationales are natural language explanations that support the model's predicted labels. For this, we employed Few-Shot Chain-of-Thought prompting, where 12 human-authored examples were provided. We used unsloth 4-bit pre-quantized Llama-3-70-Instruct model, with a max sequence of 4096 and max tokens generation of 2048. To facilitate processing, we asked the model to return a JSON object that includes the hate speech classification decision and a list of tuples with input fragments and their explanations.

Second, we used the output rationales pairs and classification labels to train a smaller model (Llama-3-8B-Instruct). The rationales provide detailed information about why an input text is assigned a specific label and include relevant knowledge that helps clarify why that label was given [23]. We fine-tuned Llama-3-8B-Instruct using the 2296 inferred instances of "Mini MetaHate Distil". During this fine-tuning, the model was provided with both labels and rationales to learn the classification and explanation of hate speech texts. We only included samples where the big model's label matched the gold label, where  $y_i = \hat{y}_i$ . For fine-tuning, we used Quantized Low-Rank Adaptation (QLoRA) for causal language modelling, with an attention dimension of 16 and  $\alpha$  set to 32. The model was trained with 4-bit quantization for 1000 steps, using a learning rate of 2.5e<sup>-5</sup>.

Figure 3 illustrates this procedure, showing how the rationales enhance the training of the smaller model by providing context and relevant knowledge that support the labels.

After curating the distilled model, we inferred over "MiniMetaHate Eval" using three language models: (1) the big model (LLama-3-70B-Instruct), (2) the small model (Llama-3-8B-Instruct), and (3) the distilled model (Llama-3-8B-Distil-MetaHate). For the big and small models, we provided the same Few-Shot CoT examples used for extracting the rationales in §3.1. For the distilled model, we only included the task instruction in the context (see Table 1), as it had already been fine-tuned with "MiniMetaHate Distil" and had seen over 2000 examples during training. We used a max sequence of 4096 and max tokens generation of 2048. This step resulted in 2001 posts with their explanations and labels for each model.

To evaluate its quality, we proposed two experiments: the hate speech classification task and the explanation task.

#### 4.4 Experiment 1: Classification Task

Our distilled model is trained to classify hate speech and provide explanations. To assess its classification performance, along with the base LLMs, and compare the results to established methods, we selected four state-of-the-art models for hate speech detection as baselines:

- MetaHateBERT [35]: We chose this model because of its training on a large dataset from multiple social networks, providing diverse data. To ensure no overlap with our MiniMetaHate subsamples, we fine-tuned it again, ensuring the training sample did not include any posts that are in MiniMetaHate

8 Paloma Piot and Javier Parapar



Fig. 3. Overview of our proposed approach for explaining and detecting hate speech: First, we extract rationales from an LLM using Few-Shot CoT. We then use these rationales, along with the labels, to train a small model within a multi-task learning framework. This enables the small model to explain and detect hate speech effectively.

Table 1. Task instruction.

#### Instruction

You must explain why a social media message is hateful or not and then tell me your decision. You must always reply with only a JSON containing one field 'hate\_speech' including a Boolean value ("True" for hate speech messages, "False" for neutral ones); and a field 'explanations' containing a list with each message phrase and its corresponding explanation. Do not include text outside the JSON. This is the definition of hate speech: "language characterised by offensive, derogatory, humiliating, or insulting discourse that promotes violence, discrimination, or hostility towards individuals or groups based on attributes such as race, religion, ethnicity, or gender". Generate step-by-step explanation for: <Message> message </Message>

subsamples. We followed the same steps as the original publication and finetuned bert-base-uncased model for 3 epochs with a learning rate of  $5e^{-5}$ and a batch size of 32. Efficient and Explainable Hate Speech Detection via Model Distillation

- HateBERT [6]: This model is a well-established baseline in the hate speech community, trained on Reddit data (RAL-E dataset). Its proven effectiveness in hate speech detection makes it a valuable comparison.
- HateXplain [30]: Trained on the HateXplain dataset, this model detects both hate speech and offensive content, and neutral posts. Despite our binary classification focus, we included it for its strong acceptance in the community. We mapped offensive content to non-hate for our purposes.
- Perspective API [27]: We selected Perspective API for its widespread use in evaluating online toxicity. The API provides a toxicity score between 0 and 1, therefore, for obtaining a binary classification decision from the score, we use a threshold of 0.5.

## 4.5 Experiment 2: Explanation Task

As we mentioned, our work involves distilling the model for classifying hate speech and generating rationales to support the classification decision. Therefore, for evaluating the generated rationales, we performed a human evaluation on a 100 entries subsample per model. We recruited three annotators with experience in hate speech detection and explainability to annotate a sample of the generated responses. Next, we present the annotation guidelines and procedure performed.

**Hate Speech Definition** We framed our work under hate speech, as defined in section §1, differentiating hate speech from non-hate and offensive speech. We define offensive speech as *posts containing any form of unacceptable language* (*profanity*) or a targeted offence, which can be veiled or direct; this includes insults, threats, and posts containing profane language or swear words [49].

**Annotation process** First, a group of experts defined the annotation guidelines, identifying two crucial aspects: completeness and correctness.

- Completeness refers to whether an annotation fully captures all instances of hate speech within a post. It ensures that every hateful sentence or fragment in the original post is addressed, making sure nothing is overlooked. This aspect is evaluated at the **post level** using *true* if all hate sentences or fragments in the original post are covered, and *false* if any parts are missing.
- Correctness refers to the accuracy of the explanations provided for each sentence or fragment within a post. It focuses on whether the explanations correctly identify and justify why a fragment is considered hate speech or not. This is evaluated at the **sentence or fragment level**, with *true* indicating a correct explanation and *false* indicating an incorrect one.

The annotators received the guidelines, some examples, and the definition of hate speech. They received a training session and discussed the outcomes, checking and revising the guidelines for any missing aspects. Then, they annotated the full subsample. After annotation, we reported the Inter Annotator Agreement (IAA), showing the percentage of instances where all three annotators fully agreed. For the completeness labelling, we report the percentage of posts where all three annotators provided the same label. For correctness, we report the percentage of fragments within a post where all three annotators have assigned the same label.

**Annotators** We recruited three annotators aged 25-30 with diverse backgrounds to evaluate the LLM outputs: one PhD student specializing in hate speech, one psychologist specializing in hate speech and mental health, and another PhD student focused on mental health and Explainable AI. Two annotators are male and one is female. Annotators were presented with labels and explanations in a blind, random setting.

# 5 Results

Next, we present the results regarding both tasks (classification and explanation).

### 5.1 Experiment 1: Classification Task

For evaluating the classification task, we extracted the predicted label for the three LLMs (teacher, small and distilled) and compared it to the golden label. Then, we reported the F1-score, weighted, micro and macro. Moreover, we included four state-of-the-art models with which to compare the hate speech detection task. Table 2 shows the detection results of the three models under evaluation, together with the four baselines, evaluated on "MiniMetaHate Eval".

Among the three LLMs evaluated, the distilled model demonstrates the highest performance, achieving an F1-score of approximately 0.85. This is followed by the Teacher model, which achieves an F1-score of 0.78, representing an approximate 9% improvement by the distilled model over the teacher model. The smaller model reports an F1-score of less than 0.75, showing the distilled model an enhancement of about 13% over this baseline. These results highlight the efficacy of our distillation process, which effectively enhances model performance compared to the larger teacher model and the smaller baseline. The improvement of the distilled model over the teacher model is due to the difference in training. The distilled model was fine-tuned for hate speech classification, as well as explanation, using over 2000 examples for learning. In contrast, the teacher model performs in a Few-Shot CoT setting, with fewer than 20 examples to guide it.

When comparing these results with the selected baselines, it is notable that MetaHateBERT achieves superior performance, with F1-scores exceeding 0.90. However, MetaHateBERT was trained in over one million instances and when training this architecture using the same instances of those used to fine-tune the LLM, the F1 score was about 0.78 ( $\sim$ 7% of improvement). Moreover, our distilled model surpasses all the other benchmarks. Specifically, it surpasses HateBERT ( $\sim$ 60.4% of improvement), HateXplain ( $\sim$ 32.9% of improvement) and the Perspective API ( $\sim$ 11.1%).

<sup>10</sup> Paloma Piot and Javier Parapar

These findings indicate that the distillation process and the approach used to integrate rationales contribute considerably to improving performance. The strong performance of the distilled model suggests that our method of multitask learning, where both classification and rationale generation are optimized, provides substantial benefits.

Table 2. Hate Speech detection results run on "MiniMetaHate Eval".

	$\mathbf{F1}$	$F1_{MICRO}$	$F1_{MACRO}$
Llama-3-70B (Few-Shot CoT)	0.7796	0.7806	0.7796
Llama-3-8B (Few-Shot $CoT$ )	0.7467	0.7491	0.7467
Llama -3-8B-Distil-MetaHate	0.8499	<u>0.8500</u>	<u>0.8499</u>
MetaHateBERT [35]	0.9037	0.9040	0.9037
HateBERT [6]	0.5291	0.5917	0.5290
HateXplain [30]	0.6397	0.6662	0.6396
Perspective API [27]	0.7650	0.7676	0.7650

#### 5.2 Experiment 2: Explanation Task

This task was evaluated using human annotators as described in §4.5. Table 3 shows the percentage of agreement in the manual evaluation of 100 instances. We report the percentage of agreement when all three have annotators assigned the same annotation label. For the correctness attribute, we measured agreement at the phrase level. As shown in Table 3, for the "Complete" annotation, all annotators perfectly agreed on 95% or more for the three models. For the "Correct" annotation, the agreement is certainly good, with values around 90%.

	Complete	Correct
Llama-3-70B (Few-Shot CoT)	96.00%	90.91%
<b>Llama-3-8B</b> (Few-Shot $CoT$ )	95.00%	88.85%
Llama-3-8B-Distil-MetaHate	95.00%	88.55%

 
 Table 3. Inter Annotator Agreement of the manual evaluation of explanations generated.

Next, we present the results based on the majority decision i.e. where two or more annotators agreed on the label. In Table 4, we can see that both the teacher model and the distilled model achieved a perfect score for completeness, with

all instances being complete. The small base model, however, had 97% complete examples. When evaluating correctness, we report the percentage of posts from the 100-sample subset where all explanations were correct over all fragments of the post. The teacher model performed best, with 92% of the post explanations being correct, closely followed by the distilled, with 91%. The small base model had a lower correctness rate, with only 83% of the posts being correct. This shows that our distilled model is just as effective as the larger language model while being more efficient. Moreover, in Table 5 we provide an error analysis of both the teacher and distilled models in terms of their classification and explanation performance.

Table -	4.	Percentage	of	correct	and	complete	posts	on	majority	decision.
		0								

	Complete	Correct
Llama-3-70B (Few-Shot CoT)	100%	92.00%
<b>Llama-3-8B</b> (Few-Shot $CoT$ )	97.00%	83.00%
Llama-3-8B-Distil-MetaHate	100%	91.00%

**Table 5.** Comparison of teacher and distil model explanations for hate speech in-stances.

Text	Model	Explanation
A word to all the ladies in very short skirts or shorts this summer - 'Thanks'.	Teacher	The phrase is hate speech because it objectifies and reduces women to their clothing choices, implying that they are grateful for male attention or approval. It promotes a sexist and patriarchal attitude, where women's bodies are policed and judged.
	Distil	This phrase is a message of appreciation and grati- tude, not promoting hate or discrimination towards any individual or group based on their attire.
I love it when married bitches start posting inspirational memes	Teacher	This phrase is a humorous prediction about the out- come of the relationship, rather than a hateful or dis- criminatory statement.
about having a strong relationship Single in 3-2-1	<sup>lg</sup> Distil	'Married bitches' is a derogatory term used to demean and objectify women, particularly those who are mar- ried. This language promotes discrimination and hos- tility towards women. 'Single in 3-2-1' is a form of mockery towards single people, implying that they will remain single for a certain period of time.

In conclusion, our results show that model distillation is effective. The distilled model matches the teacher model in explainability and outperforms it in classifying hate speech.

In our experiments, we used quantized 4-bit models (Llama-3-70B-Instruct and Llama-3-8B -Instruct) from unsloth, where the distilled model processes tokens at 0.4143 tokens per second, while the larger model does so at 0.1879 tokens per second (~54% slower). The distilled model requires 8.1 GB of GPU memory, compared to 42.5 GB for the larger model. In production, an NVIDIA A100 is needed for the large model, whereas the distilled model runs well on an NVIDIA L4. Environmental impact is lower with the L4: it emits 0.04 kg  $CO_2eq$  per hour, compared to 0.22 kg  $CO_2eq$  for the A100. Cost-wise, running an A100 for 30 hours per month on Google Cloud costs \$152.06, while the L4 costs significantly less at \$21.20, for the same duration. The large model requirements limit its practical use, making the distilled model a convenient option for broader applications.

Based on our experimental results, we propose the following hate speech detection pipeline for social media. First, we suggest using MetaHateBERT to classify posts as hate or non-hate speech. Next, the distilled model, Llama-3-8B-Distil-MetaHate, will generate explanations for each classification, clarifying the rationale behind the labels. This pipeline aims to improve detection accuracy while enhancing transparency and fairness, contributing to a better online environment.

# 6 Conclusion

In this study, we explored how to detect hate speech in an explainable way on social media and suggested a way to transfer knowledge from large language models to smaller ones. We used a multi-task learning approach, where the models are trained to not only identify hate speech but also provide explanations for their decisions. We evaluated these explanations with humans to check if the generated content agrees with human judgment. Our results show thet the distilled small model, which is faster, greener and more efficient, can both detect and explain hate speech as well as larger models, with solid improvements in classification. Future lines will involve distilling different models to compare with our proposed approach, distilling the model using more examples, and applying other prompting techniques such as Tree-of-Thought (ToT). We also aim to investigate how these methods generalise across different languages and cultural contexts.

## **Computational Resources**

Experiments were conducted using a private infrastructure, which has a carbon efficiency of  $0.432 \text{ kgCO}_2 \text{eq/kWh}$ . A cumulative of 15 hours of computation was performed on hardware of type RTX A6000 (TDP of 300W). Total emissions are estimated to be  $1.94 \text{ kgCO}_2 \text{eq}$  of which 0 percent were directly offset. Estimations were conducted using the MachineLearning Impact calculator presented in [26].

Acknowledgments. The authors thank the funding from the Horizon Europe research and innovation programme under the Marie Skłodowska-Curie Grant Agreement No. 101073351. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or the European Research Executive Agency (REA). Neither the European Union nor the granting authority can be held responsible for them. The authors also thank the financial support supplied by the Consellería de Cultura, Educación, Formación Profesional e Universidades (accreditation 2019-2022 ED431G/01, ED431B 2022/33) and the European Regional Development Fund, which acknowledges the CITIC Research Center in ICT as a Research Center of the Galician University System and the project PID2022-137061OB-C21 (Ministerio de Ciencia e Innovación supported by the European Regional Development Fund). The authors also thank the funding of project PLEC2021-007662 (MCIN/AEI/10.13039/501100011033, Ministerio de Ciencia e Innovación, Agencia Estatal de Investigación, Plan de Recuperación, Transformación y Resiliencia, Unión Europea-Next Generation EU).

# References

- AI@Meta: Llama 3 model card (2024), https://github.com/meta-llama/llama3/ blob/main/MODEL\_CARD.md
- Anti-Defamation League: Online hate and harassment: The american experience 2024 (2024), https://www.adl.org/resources/report/ online-hate-and-harassment-american-experience-2024
- 3. Plaza-del arco, F.M., Nozza, D., Hovy, D.: Respectful or toxic? using zero-shot learning with language models to detect hate speech. In: Chung, Y.I., R\"ottger, P., Nozza, D., Talat, Z., Mostafazadeh Davani, A. (eds.) The 7th Workshop on Online Abuse and Harms (WOAH). pp. 60–68. Association for Computational Linguistics, Toronto, Canada (Jul 2023). https://doi.org/10.18653/v1/2023.woah-1.6
- 4. Bender, E.M., Gebru, T., McMillan-Major, A., Shmitchell, S.: On the dangers of stochastic parrots: Can language models be too big? In: Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency. p. 610–623. FAccT '21, Association for Computing Machinery, New York, NY, USA (2021). https://doi.org/10.1145/3442188.3445922
- 5. Brown, T., Mann, B., Ryder, N., Subbiah, M., Kaplan, J.D., Dhariwal, P., Neelakantan, A., Shyam, P., Sastry, G., Askell, A., Agarwal, S., Herbert-Voss, A., Krueger, G., Henighan, T., Child, R., Ramesh, A., Ziegler, D., Wu, J., Winter, C., Hesse, C., Chen, M., Sigler, E., Litwin, M., Gray, S., Chess, B., Clark, J., Berner, C., McCandlish, S., Radford, A., Sutskever, I., Amodei, D.: Language models are few-shot learners. In: Larochelle, H., Ranzato, M., Hadsell, R., Balcan, M., Lin, H. (eds.) Advances in Neural Information Processing Systems. vol. 33, pp. 1877–1901. Curran Associates, Inc. (2020), https://proceedings.neurips.cc/paper\_files/ paper/2020/file/1457c0d6bfcb4967418bfb8ac142f64a-Paper.pdf
- 6. Caselli, T., Basile, V., Mitrović, J., Granitzer, M.: HateBERT: Retraining BERT for abusive language detection in English. In: Mostafazadeh Davani, A., Kiela, D., Lambert, M., Vidgen, B., Prabhakaran, V., Waseem, Z. (eds.) Proceedings of the 5th Workshop on Online Abuse and Harms (WOAH 2021). pp. 17–25. Association for Computational Linguistics, Online (Aug 2021). https://doi.org/10.18653/v1/2021.woah-1.3

<sup>14</sup> Paloma Piot and Javier Parapar

Efficient and Explainable Hate Speech Detection via Model Distillation

- Caselli, T., Basile, V., Mitrović, J., Kartoziya, I., Granitzer, M.: I feel offended, don't be abusive! implicit/explicit messages in offensive and abusive language. In: Calzolari, N., Béchet, F., Blache, P., Choukri, K., Cieri, C., Declerck, T., Goggi, S., Isahara, H., Maegaard, B., Mariani, J., Mazo, H., Moreno, A., Odijk, J., Piperidis, S. (eds.) Proceedings of the Twelfth Language Resources and Evaluation Conference. pp. 6193–6202. European Language Resources Association, Marseille, France (May 2020), https://aclanthology.org/2020.lrec-1.760
- Caton, S., Haas, C.: Fairness in machine learning: A survey. ACM Comput. Surv. 56(7) (apr 2024). https://doi.org/10.1145/3616865
- Commision, E.: The digital services act (2024), https://commission.europa. eu/strategy-and-policy/priorities-2019-2024/europe-fit-digital-age/ digital-services-act\_en, accessed: 03/09/2024
- Das, M., Raj, R., Saha, P., Mathew, B., Gupta, M., Mukherjee, A.: Hatemm: A multi-modal dataset for hate video classification. Proceedings of the ICWSM 2023 17, 1014–1023 (Jun 2023). https://doi.org/10.1609/icwsm.v17i1.22209
- Davidson, T., Warmsley, D., Macy, M., Weber, I.: Automated hate speech detection and the problem of offensive language. Proceedings of the ICWSM 2017 11(1), 512-515 (May 2017). https://doi.org/10.1609/icwsm.v11i1.14955
- 12. De Oliveira, A.B., Baptista, C.d.S., Firmino, A.A., De Paiva, A.C.: A large language model approach to detect hate speech in political discourse using multiple language corpora. In: Proceedings of the 39th ACM/SIGAPP Symposium on Applied Computing. p. 1461–1468. SAC '24, Association for Computing Machinery, New York, NY, USA (2024). https://doi.org/10.1145/3605098.3635964
- ElSherief, M., Kulkarni, V., Nguyen, D., Yang Wang, W., Belding, E.: Hate lingo: A target-based linguistic analysis of hate speech in social media. Proceedings of the ICWSM 2018 12(1) (Jun 2018). https://doi.org/10.1609/icwsm.v12i1.15041
- ElSherief, M., Nilizadeh, S., Nguyen, D., Vigna, G., Belding, E.: Peer to peer hate: Hate speech instigators and their targets. Proceedings of the ICWSM 2018 12(1) (Jun 2018). https://doi.org/10.1609/icwsm.v12i1.15038
- Founta, A., Djouvas, C., Chatzakou, D., Leontiadis, I., Blackburn, J., Stringhini, G., ..., Kourtellis, N.: Large scale crowdsourcing and characterization of twitter abusive behavior. Proceedings of the ICWSM 2018 12(1) (Jun 2018). https:// doi.org/10.1609/icwsm.v12i1.14991
- García-Díaz, J.A., Pan, R., Valencia-García, R.: Leveraging zero and few-shot learning for enhanced model generality in hate speech detection in spanish and english. Mathematics 11(24), 5004 (Dec 2023). https://doi.org/10.3390/ math11245004
- de Gibert, O., Perez, N., García-Pablos, A., Cuadros, M.: Hate speech dataset from a white supremacy forum. In: Fišer, D., Huang, R., Prabhakaran, V., Voigt, R., Waseem, Z., Wernimont, J. (eds.) Proceedings of the 2nd Workshop on Abusive Language Online (ALW2). pp. 11–20. Association for Computational Linguistics, Brussels, Belgium (Oct 2018). https://doi.org/10.18653/v1/W18-5102
- Gillespie, T.: Custodians of the Internet: Platforms, Content Moderation, and the Hidden Decisions That Shape Social Media. Yale University Press (2018). https: //doi.org/10.12987/9780300235029
- Gupta, S., Priyadarshi, P., Gupta, M.: Hateful comment detection and hate target type prediction for video comments. In: Proceedings of the 32nd ACM International Conference on Information and Knowledge Management. p. 3923–3927. CIKM '23, Association for Computing Machinery, New York, NY, USA (2023). https://doi. org/10.1145/3583780.3615260

- 16 Paloma Piot and Javier Parapar
- 20. He, H., Shi, X., Mueller, J., Zha, S., Li, M., Karypis, G.: Distiller: A systematic study of model distillation methods in natural language processing. In: Moosavi, N.S., Gurevych, I., Fan, A., Wolf, T., Hou, Y., Marasović, A., Ravi, S. (eds.) Proceedings of the Second Workshop on Simple and Efficient Natural Language Processing. pp. 119–133. Association for Computational Linguistics, Virtual (Nov 2021). https://doi.org/10.18653/v1/2021.sustainlp-1.13
- Hickey, D., Schmitz, M., Fessler, D., Smaldino, P.E., Muric, G., Burghardt, K.: Auditing elon musk's impact on hate speech and bots. In: Proceedings of the ICWSM 2023. pp. 1133-1137. AAAI (2023). https://doi.org/10.1609/icwsm. v17i1.22222
- 22. Ho, N., Schmid, L., Yun, S.Y.: Large language models are reasoning teachers. In: Rogers, A., Boyd-Graber, J., Okazaki, N. (eds.) Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers). pp. 14852–14882. Association for Computational Linguistics, Toronto, Canada (Jul 2023). https://doi.org/10.18653/v1/2023.acl-long.830
- 23. Hsieh, C.Y., Li, C.L., Yeh, C.k., Nakhost, H., Fujii, Y., Ratner, A., Krishna, R., Lee, C.Y., Pfister, T.: Distilling step-by-step! outperforming larger language models with less training data and smaller model sizes. In: Rogers, A., Boyd-Graber, J., Okazaki, N. (eds.) Findings of the Association for Computational Linguistics: ACL 2023. pp. 8003-8017. Association for Computational Linguistics, Toronto, Canada (Jul 2023). https://doi.org/10.18653/v1/2023.findings-acl.507
- Kansok-Dusche, J., Ballaschk, C., Krause, N., Zeißig, A., Seemann-Herz, L., Wachs, S., Bilz, L.: A systematic review on hate speech among children and adolescents: definitions, prevalence, and overlap with related phenomena. Trauma, violence, & abuse 24(4), 2598–2615 (2023)
- Kumarage, T., Bhattacharjee, A., Garland, J.: Harnessing artificial intelligence to combat online hate: Exploring the challenges and opportunities of large language models in hate speech detection (2024), https://arxiv.org/abs/2403.08035
- Lacoste, A., Luccioni, A., Schmidt, V., Dandres, T.: Quantifying the carbon emissions of machine learning. arXiv preprint arXiv:1910.09700 (2019)
- 27. Lees, A., Tran, V.Q., Tay, Y., Sorensen, J., Gupta, J., Metzler, D., Vasserman, L.: A new generation of perspective api: Efficient multilingual character-level transformers. In: Proceedings of the 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining. p. 3197–3207. KDD '22, Association for Computing Machinery, New York, NY, USA (2022). https://doi.org/10.1145/3534678.3539147
- Liu, H., Yin, Q., Wang, W.Y.: Towards explainable NLP: A generative explanation framework for text classification. In: Korhonen, A., Traum, D., Màrquez, L. (eds.) Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics. pp. 5570–5581. Association for Computational Linguistics, Florence, Italy (Jul 2019). https://doi.org/10.18653/v1/P19-1560
- Magister, L.C., Mallinson, J., Adamek, J., Malmi, E., Severyn, A.: Teaching small language models to reason. In: Rogers, A., Boyd-Graber, J., Okazaki, N. (eds.) Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers). pp. 1773–1781. Association for Computational Linguistics, Toronto, Canada (Jul 2023). https://doi.org/10.18653/v1/2023. acl-short.151
- Mathew, B., Saha, P., Yimam, S.M., Biemann, C., Goyal, P., Mukherjee, A.: Hatexplain: A benchmark dataset for explainable hate speech detection. In: Proceedings of the AAAI 2020 (2020), https://api.semanticscholar.org/CorpusID: 229332119

Efficient and Explainable Hate Speech Detection via Model Distillation

17

- Meta: Introducing meta llama 3: The most capable openly available llm to date (Apr 2024), https://ai.meta.com/blog/meta-llama-3/, accessed: 24/06/2024
- 32. Nations, U.: What is hate speech? (2023), https://www.un.org/en/hate-speech/ understanding-hate-speech/what-is-hate-speech, accessed: 15/11/2023
- Nirmal, A., Bhattacharjee, A., Sheth, P., Liu, H.: Towards interpretable hate speech detection using large language model-extracted rationales (2024), https://arxiv. org/abs/2403.12403
- 34. Pan, R., García-Díaz, J.A., Valencia-García, R.: Comparing fine-tuning, zero and few-shot strategies with large language models in hate speech detection in english. Computer Modeling in Engineering & Sciences 140(3), 2849–2868 (2024). https: //doi.org/10.32604/cmes.2024.049631
- 35. Piot, P., Martín-Rodilla, P., Parapar, J.: Metahate: A dataset for unifying efforts on hate speech detection. Proceedings of the International AAAI Conference on Web and Social Media 18(1), 2025–2039 (May 2024). https://doi.org/10.1609/ icwsm.v18i1.31445
- 36. Salminen, J., Almerekhi, H., Milenković, M., Jung, S.g., An, J., Kwak, H., Jansen, B.: Anatomy of online hate: Developing a taxonomy and machine learning models for identifying and classifying hate in online news media. Proceedings of the International AAAI Conference on Web and Social Media 12(1) (Jun 2018). https://doi.org/10.1609/icwsm.v12i1.15028
- 37. Samory, M., Sen, I., Kohne, J., Flöck, F., Wagner, C.: "call me sexist, but...": Revisiting sexism detection using psychological scales and adversarial samples. Proceedings of the International AAAI Conference on Web and Social Media 15, 573–584 (May 2021). https://doi.org/10.1609/icwsm.v15i1.18085
- Sanh, V., Debut, L., Chaumond, J., Wolf, T.: Distilbert, a distilled version of bert: smaller, faster, cheaper and lighter (2020), https://arxiv.org/abs/1910.01108
- 39. Sap, M., Gabriel, S., Qin, L., Jurafsky, D., Smith, N.A., Choi, Y.: Social bias frames: Reasoning about social and power implications of language. In: Jurafsky, D., Chai, J., Schluter, N., Tetreault, J. (eds.) Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics. pp. 5477–5490. Association for Computational Linguistics, Online (Jul 2020). https://doi.org/10.18653/v1/2020. acl-main.486
- 40. Schwartz, R., Dodge, J., Smith, N.A., Etzioni, O.: Green ai. Commun. ACM 63(12), 54–63 (nov 2020). https://doi.org/10.1145/3381831
- Silva, L., Mondal, M., Correa, D., Benevenuto, F., Weber, I.: Analyzing the targets of hate in online social media. Proceedings of the ICWSM 2021 10(1), 687–690 (Aug 2021). https://doi.org/10.1609/icwsm.v10i1.14811
- 42. Spertus, E.: Smokey: automatic recognition of hostile messages. In: Proceedings of the Fourteenth National Conference on Artificial Intelligence and Ninth Conference on Innovative Applications of Artificial Intelligence. p. 1058–1065. AAAI'97/IAAI'97, AAAI Press (1997)
- Vogels, E.A.: The state of online harassment (Jan 2021), https://www. pewresearch.org/internet/2021/01/13/the-state-of-online-harassment, accessed: 03/01/2024
- Wang, P., Chan, A., Ilievski, F., Chen, M., Ren, X.: Pinto: Faithful language reasoning using prompt-generated rationales (2023), https://arxiv.org/abs/2211. 01562
- Wang, Y.S., Chang, Y.: Toxicity detection with generative prompt-based inference (2022), https://arxiv.org/abs/2205.12390

- 18 Paloma Piot and Javier Parapar
- 46. Waseem, Z., Hovy, D.: Hateful symbols or hateful people? predictive features for hate speech detection on Twitter. In: Andreas, J., Choi, E., Lazaridou, A. (eds.) Proceedings of the NAACL Student Research Workshop. pp. 88–93. Association for Computational Linguistics, San Diego, California (Jun 2016). https://doi. org/10.18653/v1/N16-2013
- 47. Wei, J., Wang, X., Schuurmans, D., Bosma, M., Ichter, B., Xia, F., Chi, E.H., Le, Q.V., Zhou, D.: Chain-of-thought prompting elicits reasoning in large language models. In: Proceedings of the 36th International Conference on Neural Information Processing Systems. NIPS '22, Curran Associates Inc., Red Hook, NY, USA (2024)
- Yang, Y., Kim, J., Kim, Y., Ho, N., Thorne, J., Yun, S.Y.: HARE: Explainable hate speech detection with step-by-step reasoning. In: Bouamor, H., Pino, J., Bali, K. (eds.) Findings of the Association for Computational Linguistics: EMNLP 2023. pp. 5490-5505. Association for Computational Linguistics, Singapore (Dec 2023). https://doi.org/10.18653/v1/2023.findings-emnlp.365
- 49. Zampieri, M., Malmasi, S., Nakov, P., Rosenthal, S., Farra, N., Kumar, R.: Predicting the type and target of offensive posts in social media. In: Burstein, J., Doran, C., Solorio, T. (eds.) Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers). pp. 1415–1420. Association for Computational Linguistics, Minneapolis, Minnesota (Jun 2019). https: //doi.org/10.18653/v1/N19-1144
- Zhang, J., Wu, Q., Xu, Y., Cao, C., Du, Z., Psounis, K.: Efficient toxic content detection by bootstrapping and distilling large language models. Proceedings of the AAAI Conference on Artificial Intelligence 38(19), 21779–21787 (Mar 2024). https://doi.org/10.1609/aaai.v38i19.30178