Operator Splitting for Convex Constrained Markov Decision Processes

Panagiotis D. Grontas, Anastasios Tsiamis, John Lygeros

Abstract—We consider finite Markov decision processes (MDPs) with convex constraints and known dynamics. In principle, this problem is amenable to off-the-shelf convex optimization solvers, but typically this approach suffers from poor scalability. In this work, we develop a first-order algorithm, based on the Douglas-Rachford splitting, that allows us to decompose the dynamics and constraints. Thanks to this decoupling, we can incorporate a wide variety of convex constraints. Our scheme consists of simple and easy-to-implement updates that alternate between solving a regularized MDP and a projection. The inherent presence of regularized updates ensures last-iterate convergence, numerical stability, and, contrary to existing approaches, does not require us to regularize the problem explicitly. If the constraints are not attainable, we exploit salient properties of the Douglas-Rachord algorithm to detect infeasibility and compute a policy that minimally violates the constraints. We demonstrate the performance of our algorithm on two benchmark problems and show that it compares favorably to competing approaches.

Index Terms—Constrained Markov Decision Process, Optimization Algorithms, Operator Splitting, Infeasibility Detection

I. INTRODUCTION

MARKOV Decision Processes (MDPs) model an agent that seeks to act optimally in its environment in terms of a scalar cost signal. This formulation of stochastic optimal control has enjoyed considerable success, all the way from games [1] to fusion reactor control [2], and is also the mathematical formalism behind Reinforcement Learning (RL) [3]. Yet, real-world problems often involve multiple conflicting specifications which can be challenging to incorporate in a single cost function, e.g., as a weighted sum of task-specific costs. Such problems can naturally be cast in the framework of constrained MDPs (CMDPs) [4], by prescribing auxiliary specifications as constraints. Applications of CMDPs include finance [5], [6], power grids [7] and robotic locomotion [8], among others.

Arguably, the most studied constraints are the ones that impose an upper bound on the value function of auxiliary costs, and correspond to linear constraints in the occupancy measure space. When the CMDP has finite states and actions, and its dynamics and costs are perfectly known, an optimal policy can be computed by solving a linear program (LP) [4]. LP-based approaches find limited applicability as they involve a large number of constraints, which render them computationally challenging even for small state-action spaces [3, Sec. 4.7]. In this vein, [9], [10] cast CMDPs as unconstrained MDPs by augmenting the state with continuous variables that represent cumulative auxiliary costs. The resulting MDP can in principle be solved using dynamic programming (DP) techniques, but the presence of continuous states renders tabular methods effectively intractable. Differently, the authors in [11] efficiently solve the dual formulation of CMDPs by exploiting geometric insights, but their algorithm is tailored to a single linear constraint.

In the RL setting where the CMDP is unknown, a major line of research focuses on primal-dual methods to handle linear constraints [8], [12], [13]. The key observation is that, minimizing the Lagrangian for a fixed value of the multipliers associated with the linear constraints is equivalent to solving an MDP with modified cost [14]. Then, optimal multipliers can be computed via dual methods. Nonetheless reconstructing a primal solution, i.e., an occupancy measure or policy, from a dual solution is generally no easier than solving the original problem [15] since the Lagrangian is not strictly convex. Some ways to circumvent this include performing primal averaging [16], and augmenting the MDP state with the multipliers and deploying dual ascent during system operation [14]. Another approach is to add strongly convex regularization to the Lagrangian. For instance, in [17] the authors consider a discounted entropy regularization on the policy, while in [18] an additional quadratic regularization of the dual variables is considered. Since this method solves a modified problem, it is not trivial to ensure that the modified solution is close to the original one. Further, many safe RL algorithms only provide average-iterate convergence guarantees, i.e., one needs to average the primal solution over the entire algorithm trajectory. This is an undesirable property, especially since primal solutions are typically represented via non-linear functions, e.g., neural networks, thus precluding a straightforward averaging of parameters. In [19] an augmented Lagrangian method is employed to achieve last-iterate convergence. A regularized primal-dual approach based on policy gradient methods is developed in [20], along with non-asymptotic lastiterate convergence guarantees. A host of other approaches exist that are inspired from optimistic mirror descent [21], interior-point methods [22], or projection methods [23].

All aforementioned methodologies are tailored to linearlyconstrained MDPs. Yet, MDP formulations with a generic convex objective and constraints have recently gained traction in the RL community [24]. For instance, such formulations pertain to apprenticeship learning [25], exploration [26] and diverse skill recovery [27]. From an algorithmic point of view, the

This work was supported as a part of NCCR Automation, a National Centre of Competence in Research, funded by the Swiss National Science Foundation (grant number 51NF40_225155)

Authors are with the Automatic Control Laboratory, Department of Electrical Engineering and Information Technology, ETH Zürich, Physikstrasse 3 8092 Zürich, Switzerland. (e-mail:{pgrontas, atsiamis, jlygeros}@ethz.ch).

setting of convex constraints is significantly more challenging than linear ones due to the lack of a straightforward Lagrangianbased reformulation. In [28], a primal-dual gradient method for convex-constrained MDPs is developed, that exploits the variational policy gradient theorem [29]. The authors in [30] use game-theoretic tools to compute feasible policies for convex CMDPs. The proposed algorithm can also be used to solve convex CMDPs via multiple calls to a feasibility problem [31].

In this work, we consider finite and known MDPs with convex constraints. Although this problem setting is amenable to convex optimization solvers, it suffers from the same limitations as LP approaches for linearly-constrained MDPs. To address this problem, we propose a first-order method derived from the Douglas-Rachford Algorithm (DRA) [32, Sec. 28.3] which is equivalent to the alternating direction method of multipliers [33], [34]. Our contributions are:

- To apply the DRA, we introduce a convenient decomposition of the MDP dynamics and the constraints. This allows us to exploit potential structure in the constraints and reduce the computational footprint. Further, we can deploy our scheme to a wide range of convex constraints, namely any set for which an approximate projection can be computed.
- Our algorithm involves regularized updates that enjoy numerically favorable properties, without having to regularize the original CMDP or its Lagrangian. This inherent regularization facilitates recovering a primal solution and, thus, ensures last-iterate convergence.
- We study problem settings where the specified convex constraints are not attainable, and we exploit salient properties of the DRA to endow our approach with an infeasibility detection mechanism and meaningful characterization of its iterates. To the best of our knowledge, there are limited works that address infeasible CMDPs, see e.g., [30], [31], [35].

Finally, we deploy our algorithm on two well-studied benchmark problems. We verify its ability to rapidly retrieve mediumaccuracy solutions, outperform popular competing methodologies, and we motivate the usefulness of our infeasibility detection analysis with intuitive numerical examples.

Notation: We denote by \mathbb{N}, \mathbb{R} , and $\mathbb{R}_{\geq 0}$ the set of natural, real, and non-negative real numbers, respectively. We use $\|\cdot\|$ to denote the Euclidean norm. We let $\mathbf{1}_n \in \mathbb{R}^n$ be the vector of all ones. For a finite set S with cardinality |S|, we denote the unit simplex by $\Delta(S) \coloneqq \{x \in \mathbb{R}_{\geq 0}^{|S|} \mid \mathbf{1}_{|S|}^\top x = 1\}$. The indicator function of a set $\mathcal{X} \subseteq \mathbb{R}^n$ is $\mathcal{I}_{\mathcal{X}}(x) = 0$ if $x \in \mathcal{X}$, and equals $+\infty$ otherwise. A function $f : \mathbb{R}^n \to \mathbb{R} \cup \{-\infty, +\infty\}$ is called proper if dom $f \coloneqq \{x \in \mathbb{R}^n \mid f(x) < +\infty\} \neq \emptyset$, and f does not take the value $-\infty$. The proximal operator of a proper, closed, convex function f with parameter $\sigma > 0$ is given by $\operatorname{prox}_{\sigma f}(x) \coloneqq \operatorname{argmin}_y \{f(y) + \frac{1}{2\sigma} ||x - y||^2\}$.

II. PRELIMINARIES AND PROBLEM FORMULATION

A. Markov Decision Processes

We consider infinite-horizon discounted tabular MDPs, specified by the tuple $(S, A, P, c, \gamma, \rho)$, where S and A are the finite sets of states and actions with respective cardinality

S := |S| and A := |A|, $P : S \times A \to \Delta(S)$ is the transition kernel, $c : S \times A \to \mathbb{R}$ is the cost function, $\gamma \in (0, 1)$ is the discount factor, and $\rho \in \Delta(S)$ is the initial state distribution. We represent $P \in \mathbb{R}^{SA \times S}$ as a row-stochastic matrix, and $c \in \mathbb{R}^{SA}$, $\rho \in \Delta(\mathbb{R}^S)$ as vectors, and we enumerate stateaction pairs lexicographically as $(s_1, a_1), (s_2, a_1)$, and so on. At each time step t, the agent is at state s_t and chooses action a_t . As a result, it transitions to a next state s_{t+1} with probability $P(s_{t+1} | s_t, a_t)$ and incurs a cost $c(s_t, a_t)$. The agent's goal is to minimize the cumulative discounted cost, assuming that the initial state is distributed according to ρ .

A stationary Markov policy is a mapping $\pi : S \to \Delta(\mathcal{A})$ such that the probability of applying action a in state s is $\pi(a | s)$. The value function of a policy π associated with the cost c starting from the initial state s is $V_{\pi}^{c}(s) :=$ $(1 - \gamma)\mathbb{E}^{\pi} \left[\sum_{t=0}^{\infty} \gamma^{t} c(s_{t}, a_{t}) | s_{0} = s \right]$, where the expectation is taken with respect to system trajectories under π . For conciseness, we let $V_{\pi}^{c} := \mathbb{E}_{s \sim \rho} [V_{\pi}^{c}(s)]$. Solving an MDP amounts to finding a policy π^{*} such that

$$\pi^{\star} \in \operatorname*{argmin}_{\pi \in \Pi} V_{\pi}^{c}, \tag{1}$$

where Π denotes the set of all stationary Markov policies.

The non-convex optimal control problem (1) can equivalently be cast as a convex one by introducing the (normalized discounted) occupancy measure of π , which is defined as $d_{\pi}(s, a) := (1 - \gamma) \sum_{t=0}^{\infty} \gamma^{t} \mathbb{P}^{\pi}[s_{t} = s, a_{t} = a | s_{0} \sim \rho]$. Intuitively, $d_{\pi}(s, a)$ measures the discounted frequency of observing the pair (s, a). Any d_{π} takes values in the bounded polytope

$$\mathcal{D} \coloneqq \left\{ d \in \mathbb{R}_{\geq 0}^{SA} \mid \sum_{a} d(s, a) = (1 - \gamma)\rho(s) + \gamma \sum_{a', s'} P(s \mid s', a')d(s', a') \right\};$$
⁽²⁾

indeed, $\mathcal{D} = \{d_{\pi} \mid \pi \in \Pi\}$. Conversely, given any $d \in \mathcal{D}$, the policy $\pi(a \mid s) = d(s, a) / \sum_{a} d(s, a)$ induces an occupancy measure d_{π} such that $d_{\pi} = d$ [4, Th. 3.2]; if $\sum_{a} d(s, a) = 0$, then $\pi(\cdot \mid s)$ can be arbitrary. By definition of $d_{\pi}, V_{\pi}^{c} = c^{\top} d_{\pi}$, which allows us to reformulate (1) as the following LP:

$$\underset{d \in \mathbb{R}^{SA}}{\text{minimize}} \quad c^{\top}d \tag{3a}$$

subject to
$$d \in \mathcal{D}$$
. (3b)

B. Convex-Constrained Markov Decision Processes

We consider convex-constrained MDPs specified as the following convex program:

$$\underset{d \in \mathbb{R}^{SA}}{\text{minimize}} \quad c^{\top}d \tag{4a}$$

subject to
$$d \in \mathcal{C} \cap \mathcal{D}$$
, (4b)

where the set C satisfies the following standing assumption, which is valid throughout the paper.

Standing Assumption 1: The set $C \subseteq \mathbb{R}^{SA}$ is non-empty, closed, and convex.

For concreteness, we adopt a representation of the form $C = \{d \in \mathbb{R}^{SA} | C_i(d) \leq b_i, i = 1, ..., n_c\}$, where each C_i

is a convex real-valued function and b_i is a scalar. Depending on the structure of C, we can prescribe various performance or safety specifications, as discussed next.

Example 1: Arguably, the most common setting corresponds to polytopic sets of the form $C = \{d \in \mathbb{R}^{SA} | Ed \leq b\}$, where $E \in \mathbb{R}^{n_c \times SA}, b \in \mathbb{R}^{n_c}$. We let $E_i \in \mathbb{R}^{SA}$ denote the rows of E, and observe that $\mathbb{E}_{s \sim \rho}[V_{\pi}^{E_i}(s)] = E_i^{\top} d_{\pi} \leq b_i$. Therefore, we can interpret E_i as an auxiliary cost, whose associated value function is upper-bounded by b_i .

Example 2: We can encode imitation learning objectives via ℓ_p -ball constraints such as $C = \{d \in \mathbb{R}^{SA} \mid ||d - \hat{d}||_p \le \varepsilon\}$, where $\varepsilon > 0$, $p \in [1, +\infty]$, and $\hat{d} \in \mathcal{D}$. Intuitively, we require the optimal occupancy measure to remain close to some expert measure \hat{d} . Such constraints could also arise in a setting where we have a nominal MDP model that is only reliable in the neighborhood of a nominal policy.

Example 3: Using the convex set $C = \{d \in \mathbb{R}^{SA} \mid \sum_{s,a} d(s,a) \log(d(s,a)) \ge \varepsilon\}$ involving the entropy of the occupancy measure we can promote exploratory behavior, e.g., when using a nominal MDP model to obtain new data.

Example 4: Non-linear convex constraints can be used to ensure robustness of the induced policy. For example, assume that c is only an approximation of the true cost function, which is unknown but guaranteed to live on the convex set \mathcal{A} . Then, we can control the worst-case performance degradation due to the uncertain cost by enforcing $d \in \mathcal{C} = \{d \in \mathbb{R}^{SA} \mid \sup_{c' \in \mathcal{A}} (c' - c)^{\top} d \leq \varepsilon\}.$

For various types of constraints C, one could solve (4) as a convex program using existing solvers, e.g., Example 1 and Example 2, with p = 1 or $p = +\infty$, give rise to an LP, while Example 2 with p = 2 corresponds to a second-order cone program. But, as noted in the introduction, these approaches are significantly less scalable than DP-based methods. The latter are solely applicable to linearly-constrained MDPs and come with their own set of challenges, namely state augmentation with continuous variables or average-iterate convergence. To bridge this gap, we aim to derive a DP-inspired algorithm that works for generic convex constraints.

III. ALGORITHM DESIGN

Our main algorithmic idea is to decouple the dynamics of the problem in \mathcal{D} from the constraints in \mathcal{C} , and then exploit the individual structure of the two parts to derive an efficient and modular algorithm. To achieve this, we draw inspiration from distributed optimization techniques and, specifically, we deploy the Douglas-Rachford Algorithm (DRA). The DRA is used to solve composite optimization problems of the form

$$\begin{array}{ll} \text{minimize} & f(x) + g(x), \\ (5) \end{array}$$

where f and g are convex, closed, and proper functions. The iterations of the DRA require evaluating the proximal operators of f and g. Therefore, splitting the sum f + g onto individual functions f and g is a critical design choice for the efficiency of the algorithm.

We express the CMDP in (4) in composite form as follows:

$$\underset{d \in \mathbb{R}^{SA}}{\text{minimize}} \underbrace{c^{\top}d + \mathcal{I}_{\mathcal{D}}(d)}_{=:f(d)} + \underbrace{\mathcal{I}_{\mathcal{C}}(d)}_{=:g(d)} .$$
(6)

Notice that our choice of f corresponds to the objective of an unconstrained MDP as in (3). A similar idea is explored in [36] in the context of optimal control of linear deterministic systems. Applying the DRA for the proposed splitting yields the following iteration, initialized with $w_0 \in \mathbb{R}^{SA}$:

$$d_k = \operatorname{prox}_{\sigma f}(w_k) \tag{7a}$$

$$k \in \mathbb{N}) \qquad \qquad \nu_k = \frac{1}{\sigma} (w_k - d_k) \tag{7b}$$

$$z_k = \operatorname{prox}_{\sigma g}(2d_k - w_k) \tag{7c}$$

$$w_{k+1} = w_k + (z_k - d_k)$$
 (7d)

where $\sigma > 0$ is a scaling parameter. Intuitively, the algorithm proceeds by performing proximal minimization of f and g in an alternating fashion, and uses w_k to integrate the difference of the minimizers. In Section IV we will show that, under appropriate conditions, the pair of iterates (d_k, ν_k) converges to a primal-dual solution of (4).

Implementing (7) is not straightforward as it requires solving the subproblems (7a) and (7c). Next, we elaborate on how to perform these updates efficiently. All derivations for the following subsections are given in Appendix A.

A. Quadratically-regularized MDPs

(∀

The update (7a) corresponds to solving an MDP with quadratic regularization:

$$\underset{d \in \mathbb{R}^{SA}}{\text{minimize}} \quad c^{\top}d + \frac{1}{2\sigma} \|d - w_k\|^2$$
(8a)

subject to
$$\Xi^{\top} d = (1 - \gamma)\rho + \gamma P^{\top} d,$$
 (8b)

$$d(s,a) \ge 0, \ \forall s \in \mathcal{S}, a \in \mathcal{A}, \tag{8c}$$

where, for conciseness, we define the matrix $\Xi^{\top} := \mathbf{1}_A^{\top} \otimes I_S \in \mathbb{R}^{S \times SA}$ that acts on d as $[\Xi^{\top}d]_s = \sum_a d(s, a)$. Directly solving the quadratic program (8) is disadvantegeous from a computational perspective due to the large number of affine constraints. Instead, we pursue an approach inspired from the regularized MDP literature [37], [38] that exploits the dynamical system interpretation of the constraints (8b), (8c).

To do so, we introduce the Largrange multipliers $V \in \mathbb{R}^S$ and $\varphi \in \mathbb{R}^{SA}$ associated with (8b) and (8c), respectively. Then, we derive (see Appendix A) the dual of (8) that reads:

$$\begin{array}{l} \underset{V \in \mathbb{R}^{S}, \varphi \in \mathbb{R}_{\geq 0}^{\leq A}}{\text{maximize}} & \kappa(V, \varphi) := -\frac{\sigma}{2} \| c + \gamma PV - \Xi V - \varphi \|_{2}^{2} \\ & + w_{k}^{\top}(c + \gamma PV - \Xi V - \varphi) + (1 - \gamma)\rho^{\top}V. \end{array}$$
(9)

Recall that, in the primal and dual LP formulation of MDPs without regularization [4, Subsec. 3.2], the multipliers of the equality constraints (8b) correspond to the value function. For this reason, in the context of (8) we interpret V as a regularized value function, similarly to [37]. Further, complementary slackness dictates that $0 \le \varphi \perp d \ge 0$, hence, $\varphi(s, a) > 0$ implies that d(s, a) = 0 for any state-action pair (s, a). As such, φ acts as a dual occupancy measure that indicates which state-action pairs are never visited.

With these connections in mind, we observe that given an optimal φ^* , we can retrieve the corresponding optimal value function V^* by maximizing (9) with respect to V. Indeed,

setting $\nabla_V \kappa(V, \varphi^*)$ to zero and solving for V yields a linear system of equations, akin to policy evaluation:

$$(\gamma P - \Xi)^{\top} (\gamma P - \Xi) V = (\gamma P - \Xi)^{\top} (w_k / \sigma - c + \varphi^{\star}) + \frac{1}{\sigma} (1 - \gamma) \rho.$$
(10)

Noticing that $\gamma P - \Xi$ has trivial nullspace (see Lemma 1 in Appendix A), we deduce that (10) has a unique solution. Conversely, in a policy improvement fashion, given an optimal regularized value function V^* we derive the corresponding φ^* by maximizing (9) as follows:

$$\varphi^{\star} = \max(c - \Xi V^{\star} + \gamma P V^{\star} - w_k / \sigma, 0).$$
(11)

Finally, we can retrieve the solution of (8) from the dual solution by exploiting strong duality:

$$d^{\star} = \sigma \max(-c + \Xi V^{\star} - \gamma P V^{\star} + w_k/\sigma, 0).$$
(12)

The expressions in (10), (11), and (12) motivate solving (9) through the following iterative scheme, which we refer to as quadratically regularized policy iteration (QRPI):

$$V_{\ell+1}^{\text{in}} \leftarrow ((\gamma P - \Xi)^{\top} (\gamma P - \Xi))^{-1} \\ ((\gamma P - \Xi)^{\top} (\frac{1}{\sigma} w_k - c + \varphi_{\ell}^{\text{in}}) + \frac{1}{\sigma} (1 - \gamma)\rho)$$
(13a)

$$\varphi_{\ell+1}^{\text{in}} \leftarrow \max(c + \gamma P V_{\ell+1}^{\text{in}} - \Xi V_{\ell+1}^{\text{in}} - \frac{1}{\sigma} w_k, 0) \tag{13b}$$

$$d_{\ell+1}^{\text{in}} \leftarrow \sigma \max\left(-c - \gamma P V_{\ell+1}^{\text{in}} + \Xi V_{\ell+1}^{\text{in}} + \frac{1}{\sigma} w_k, 0\right) .$$
(13c)

As a remark, QRPI can be shown to be a quasi-Newton method to solve (8). Similarly, in standard MDPs, policy iteration is known to be a Newton method to solve the Bellman optimality equation [39], and has inspired quasi-Newton approaches as in [40].

Notice that, QRPI forms an inner loop which is used to solve subproblem (7a) of the DRA. We highlight this by using a distinct index, $\ell \in \mathbb{N}$, and the superscript "in" for the inner loop iterates. In Section IV we establish convergence of (13) to a primal-dual solution of (8).

Interestingly, notice that (13b) and (13c) can be expressed as $\varphi_{\ell+1}^{\text{in}} = \max(A(V_{\ell+1}^{\text{in}}), 0)$ and $d_{\ell+1}^{\text{in}} = \sigma \max(-A(V_{\ell+1}^{\text{in}}), 0)$, where $A(V) \coloneqq c + \gamma PV - \Xi V - w_k/\sigma$. Explicitly writing the components $[A(V)]_{(s,a)} = c(s,a) + \gamma \sum_{s'} P(s' \mid s, a)V(s') - V(s) - w_k(s,a)/\sigma$, we observe that A is a (dis)advantage function, encoding the dynamics and cost, plus a term arising from the quadratic regularization, encoding a preference towards w_k . Further, we can decompose the positive and negative entries of A(V) onto φ and d, respectively, as indicated in Figure 1.

B. Constraint Projection

We express the update (7c) in a more familiar form, by recalling that $g = I_c$, as follows:

$$\operatorname{prox}_{\sigma g}(2d_k - w_k) = \operatorname*{argmin}_{d' \in \mathcal{C}} \|d' - (2d_k - w_k)\|^2$$
$$= \mathbb{P}_{\mathcal{C}}(2d_k - w_k) . \tag{14}$$

The projection onto a closed convex set is a well-studied operation and admits efficient, often closed-form, implementation for various convex sets of interest, such as norm balls



Fig. 1: Decomposition of A(V) onto d and φ . Informally, if $[A(V_{\ell}^{\text{in}})]_{(s,a)} < 0$ then playing action a at state s will improve performance, up to a slack of w_k/σ , therefore, we use it to compute d_{ℓ}^{in} . Conversely, state-action pairs satisfying $[A(V_{\ell}^{\text{in}})]_{(s,a)} > 0$ are undesirable as they would deteriorate performance, hence are placed in the dual occupancy $\varphi_{\ell}^{\text{in}}$.

[32, Examples 3.18, 29.27], convex cones [32, Examples 6.29, 29.32] or sublevel sets of support functions.

As previously highlighted, polyhedral constraints are of particular interest yet, in general, do not admit a closed-form projection. Specifically, for polyhedral sets $C = \{d \in \mathbb{R}^{SA} | Ed \leq b\}$, where $E \in \mathbb{R}^{n_c \times SA}$, the projection (14) amounts to solving a quadratic program. Yet, the dimensionality of d renders solving (14) at each iteration expensive. Nonetheless, for most interesting problems it is often the case that $n_c \ll SA$. Hence, it is advantageous to solve the, significantly smaller, dual of (14) instead:

$$\lambda^{\star} \in \operatorname*{argmax}_{\lambda \in \mathbb{R}^{n_c}_{>0}} \quad -\frac{1}{4} \lambda^{\top} E E^{\top} \lambda + (E(2d_k - w_k) - b)^{\top} \lambda,$$
(15)

and retrieve the projection as $\mathbb{P}_{\mathcal{C}}(2d_k - w_k) = 2d_k - w_k - \frac{1}{2}E^{\top}\lambda^*$.

C. Overall Algorithm

Combining the general DRA in (7) with the specific update rules (13) and (14) we derive Alg. 1, which we refer to as Operator Splitting for Constrained MDPs (OS-CMDP). It comprises a double loop: the outer loop iteration, indexed by k, implements the DRA, while the inner loop iteration, indexed by ℓ , (approximately) solves the regularized MDP (8) by performing $\overline{\ell}$ iterations of QRPI (13). Design guidelines for the hyperparameters $\overline{\ell}$ and σ are discussed in Section V. Note that Alg. 1 keeps track of φ_k , i.e., the optimal dual occupancy for (8) given w_k . Then, we use φ_k to warm-start QRPI to solve (8) for w_{k+1} . In the next section, we study the asymptotic behavior of Alg. 1 and establish appropriate termination criteria.

IV. CONVERGENCE ANALYSIS

In this section, we establish convergence of QRPI, in the inner loop of Alg. 1, to a primal-dual solution of (8). Then, we study the asymptotic behavior of Alg. 1 for both feasible and infeasible instances of (4), which we employ to design

ALGORITHM 1. Operator Splitting for Constrained MDPs

Inputs: $\sigma > 0, \ \overline{\ell} \in \mathbb{N}.$ **Initialization:** $k \leftarrow 0, w_0 \leftarrow 0, \varphi_{-1} \leftarrow 0.$ **Repeat until terminal criterion:** Solve Regularized MDP via QRPI: *Initialization:* $\ell \leftarrow 0$ *Warmstart:* $\varphi_0^{\text{in}} = \varphi_{k-1}$ For $\ell = 0, \ldots, \overline{\ell} - 1$: $V_{\ell+1}^{\text{in}} \leftarrow \text{Update using (13a)}$ $\varphi_{\ell+1}^{\text{in}} \leftarrow \text{Update using (13b)}$ $d_{\ell+1}^{\text{in}} \leftarrow \text{Update using (13c)}$ Update outer loop variables: $\varphi_k \leftarrow \varphi_{\overline{\ell}}^{\text{in}}$ $d_k \leftarrow d_{\overline{\rho}}^{in}$ Dual update: $| \nu_k \leftarrow \frac{1}{\sigma} (w_k - d_k)$ Project onto C: $z_k \leftarrow \mathbb{P}_{\mathcal{C}}(2d_k - w_k)$ Auxiliary update: $| w_{k+1} \leftarrow w_k + (z_k - d_k)$ $k \leftarrow k+1$ **Output:** d_k

termination criteria. The proofs for the technical statements in this section are provided in Appendix B.

A. Convergence of QRPI

Our convergence proof hinges on the fact that the dual updates (13a), and (13b) of QRPI can be viewed as applying block coordinate maximization to the dual problem (9). In particular, the dual updates are equivalent to:

$$V^{\ell+1} = \underset{V}{\operatorname{argmax}} \kappa(V, \varphi^{\ell}) \tag{16a}$$

where κ is the dual function in (9). The primal updates simply follow from the relation between primal and dual solutions established in (12).

Proposition 1: For any $w_k \in \mathbb{R}^{SA}$ and $\varphi_0 \in \mathbb{R}^S$ the sequence $(d_\ell^{\text{in}}, V_\ell^{\text{in}}, \varphi_\ell^{\text{in}})_{\ell \in \mathbb{N}}$ generated by (13) converges to a primal-dual solution of (8) with R-linear rate. In particular, $d_\ell^{\text{in}} \to \text{prox}_{\sigma f}(w_k)$.

B. Feasible Problem Instances

Now, we turn our attention to the asymptotic behavior of Alg. 1 under the following assumption.

Assumption 1: One of the following holds: (i) $\mathcal{D} \cap \mathrm{ri} \mathcal{C} \neq \emptyset$, where ri denotes the relative interior; (ii) \mathcal{C} is a polyhedron and $\mathcal{D} \cap \mathcal{C} \neq \emptyset$.

Assumptions 1(i) and 1(ii) are standard and, respectively, correspond to strict feasibility and feasibility.

If we allow full convergence of the inner QRPI loop, i.e., we set $\overline{\ell} = +\infty$, then we can readily establish convergence of Alg. 1 as an instance of the DRA.

Proposition 2: Under Assumption 1, the sequence $(d_k, z_k, \nu_k)_{k \in \mathbb{N}}$ generated by Alg. 1, where the inner problem is solved to optimality, converges to some (d^*, d^*, ν^*) , where d^* is a primal and ν^* is a dual solution of (4).

In practice, we observe that using a small finite $\overline{\ell}$, instead of solving the inner problem to optimality, yields similar performance, as we discuss in Section V and Appendix C.

C. Infeasible Problem Instances

Next, we focus on cases where the constraint set C is not compatible with the dynamics, i.e., $C \cap D = \emptyset$. This means that there exists no occupancy measure, or equivalently Markov policy, that satisfies the specifications in C. In this setting, it is well-known that the sequence $(w_k)_{k \in \mathbb{N}}$ diverges, but, nonetheless, we can extract useful information from the rate at it which it does so [41].

Proposition 3: Let $v \coloneqq \operatorname{argmin}_{\beta \in \mathcal{D}-\mathcal{C}} \|\beta\|$. It holds true that $w_k - w_{k+1} \to v$.

The vector v, that corresponds to the so-called minimal displacement vector [42], represents the minimum-norm translation of C such that $C \cap D \neq \emptyset$. Intuitively, a system designer can interpret v as the direction along which the constraints should be relaxed to render the problem feasible. Moreover, it follows that $v \neq 0$ if and only if $C \cap D = \emptyset$. In fact, it can be shown that if the problem is infeasible the non-zero v generates a strongly separating hyperplane between C and D, i.e., $\min_{d \in D} v^{\top} d > \sup_{z \in C} v^{\top} z$ (see Lemma 2 in Appendix B). Similar results have been shown in the context of quadratic and conic programs [43]–[45].

Despite infeasibility, we can still extract a meaningful policy from the limit of $(d_k)_{k \in \mathbb{N}}$ by exploiting the asymptotic properties of the DRA established in [41], [42].

Proposition 4: It holds true that $d_{k+1} - d_k \to 0$ and any limit point $(\overline{d}, \overline{z})$ of $(d_k, z_k)_{k \in \mathbb{N}}$ satisfies $(\overline{d}, \overline{z}) \in \operatorname{argmin}_{d \in \mathcal{D}, z \in \mathcal{C}} ||d - z||$. In addition, if \mathcal{C} is a polyhedron, then,

$$d_k \to \underset{d \in \mathbb{R}^{SA}}{\operatorname{argmin}} \quad c^{\top} d$$
subject to $d \in \mathcal{D} \cap (\mathcal{C} - v)$. (17)

This result is particularly interesting when $C \cap D = \emptyset$. Plainly, we learn that any limit point of $(d_k)_{k \in \mathbb{N}}$ is an occupancy measure that is "closest", in the norm sense, to C. Moreover, for polyhedral C, $(d_k)_{k \in \mathbb{N}}$ converges to an optimal solution of the modified and by-construction feasible CMDP (17). Pictorially, the behavior of Alg. 1 for infeasible CMDPs is shown in Figure 2.

We stress that the results of this subsection only require Standing Assumption 1, and not Assumption 1. Propositions 3 and 4 characterize the asymptotic behavior of the DRA irrespective of feasibility.

D. Termination Criteria

To specify meaningful termination criteria, we derive the optimality conditions of (6). First, we introduce the auxiliary



Fig. 2: Asymptotic behavior of Alg. 1 for infeasible problems. Any limit point $(\overline{d}, \overline{z})$ of the iterates (d_k, z_k) minimizes the distance between the sets C and D. The difference of iterates $w_k - w_{k+1}$ converges to the minimal displacement vector v.

variable $z \in \mathbb{R}^{SA}$ and equivalently express (6) as:

$$\underset{d,z \in \mathbb{R}^{SA}}{\text{minimize}} \quad f(d) + g(z) \tag{18a}$$

subject to
$$d-z=0$$
. (18b)

Then, (d^*, z^*, ν^*) is a primal-dual solution if and only if [46, Th. 11.50]:

$$0 \in \partial f(d^*) - \nu^* \tag{19a}$$

$$0 \in \partial g(z^{\star}) + \nu^{\star} \tag{19b}$$

$$d^{\star} - z^{\star} = 0 \ . \tag{19c}$$

Observe that, by Fermat's rule [32, Th. 16.3], the optimality condition of (7a) reads $0 \in \partial f(d_k) - \nu_k$, which implies that (19a) is satisfied at each iteration. In turn, the optimality condition for (7c) is $-\sigma^{-1}(z_k - d_k) \in \partial g(z_k) + \nu_k$. By Proposition 2, $z_k - d_k \to 0$, therefore both (19b) and (19c) are satisfied in the limit.

Therefore, we terminate the algorithm with the approximate primal-dual solution (d_k, z_k, ν_k) if:

$$\|d_k - z_k\|_{\infty} \le \varepsilon_{\text{opt}}, \quad \text{and} \\ \max(C_i(d_k) - b_i, 0) \le \varepsilon_{\text{con}}(1 + |b_i|), \quad \forall i = 1, \dots, n_c,$$
(20)

where $\varepsilon_{\text{opt}}, \varepsilon_{\text{con}} > 0$ are specified tolerances. The first condition is in line with (19), while the second one explicitly controls the allowable constraint violation, recalling that $\mathcal{C} = \{d \in \mathbb{R}^{SA} | C_i(d) \leq b_i, i = 1, ..., n_c\}.$

Conversely, characterizing a problem instance as infeasible could be achieved by testing that $w_{k+1} - w_k$ converges to a nonzero vector. Unfortunately, such a criterion can be misleading since it is possible that $w_{k+1}-w_k$ stagnates at a particular value for a number of iterations, without having reached its limit point. Instead, since Proposition 4 guarantees that $d_{k+1} - d_k \rightarrow 0$, we flag a problem as infeasible if $d_{k+1} - d_k$ is small, but d_{k+1} does not satisfy the constraints up to the required tolerance. Concretely, we check the following condition of infeasibility for some small tolerance $\varepsilon_{inf} > 0$:

$$\|d_{k+1} - d_k\|_{\infty} \le \varepsilon_{\inf}, \text{ and} \\ \max(C_i(d_k) - b_i, 0) > \varepsilon_{\operatorname{con}}(1 + |b_i|), \ \forall i = 1, \dots, n_c .$$
(21)

V. PRACTICAL IMPLEMENTATION

Inexact QRPI: From a practical standpoint, executing the inner loop to full convergence is computationally demanding but, as we discuss next, unnecessary. Instead, it suffices to solve (8) up to some tolerance that decreases with the iteration k. Formally, let $e_k := ||d_k - \text{prox}_{\sigma f}(w_k)||$ and notice that, in general, $e_k > 0$ unless we execute infinitely many QRPI iterations. If e_k decays sufficiently fast, formally $\sum_{k=0}^{\infty} e_k < \infty$, then the convergence certificate of Proposition 2 remains valid [47, Th. 7].

In principle, we could estimate an upper bound on e_k , e.g., using [48, Lemma 4.5] and execute enough QRPI iterations to ensure the necessary decrease in e_k . Yet, in practice, we have observed that warm-starting QRPI and running a small fixed number of inner iterations, specifically $\overline{\ell} = 2$, generates trajectories of Alg. 1 that behave similarly to the case where QRPI is run to convergence (see Appendix C). We adopt this approximate but efficient approach in our implementation.

Regularized Policy Evaluation: The main computational bottleneck of Alg. 1 is solving the linear system (13a), for which we propose two approaches. In the direct approach, we factorize $(\gamma P - \Xi)^{\top}(\gamma P - \Xi)$ and solve (13a) through a computationally-inexpensive forward and backward substitution. As shown in Lemma 1, the matrix $(\gamma P - \Xi)^{\top}(\gamma P - \Xi)$ is positive definite therefore we factorize it via a Cholesky decomposition. Further, since this matrix does not change across iterations we only need to factorize it once during the initialization of Alg. 1. While efficient, factorizing, or even computing, $(\gamma P - \Xi)^{\top}(\gamma P - \Xi)$ can be prohibitive when P is very large.

Instead, in the indirect approach, we solve (13a) via an iterative method, such as the conjugate gradient method [49], which only requires matrix-vector product evaluations of $(\gamma P - \Xi)^{\top}((\gamma P - \Xi)V)$. This approach is particularly useful when $\gamma P - \Xi$ is large and sparse, but is generally less efficient than the direct one, whenever the latter is applicable. In our simulations we use the direct method.

Choosing σ : The value of σ significantly affects the speed and transient behavior of Alg. 1. Intuitive design guidelines can be drawn by interpreting σ as a scaling constant for the objective of problem (6). Since the only term affected by σ is $c^{\top}d$, we can conclude that large values of σ prioritize cost minimization, whereas small ones prioritize constraint satisfaction. These intuitions match our numerical experience.

Relaxation: A popular variant of the DRA is obtained by applying relaxation to the updates of w_k , i.e., replacing (7d) by $w_{k+1} = w_k + \omega(z_k - d_k)$, where $\omega \in (0, 2)$. The relaxed iteration retains theoretical guarantees, and numerical studies have reported faster convergence for $\omega > 1$ [50], [51]. In our implementation we use $\omega = 1.5$.

VI. NUMERICAL SIMULATIONS

We deploy OS-CMDP on two benchmark problems. First, we consider Garnet MDPs [52, Sec. 8], a well-studied class of randomly-generated MDPs, and compare the performance of OS-CMDP against competing approaches for CMDPs with polyhedral and more general convex constraints. Second, we consider a grid world problem which we use to qualitatively study the behavior of our algorithm for both feasible and infeasible problem instances.

The parameters of Alg. 1 are set to $\sigma = 2 \times 10^{-5}, \omega = 1.5, \ \bar{\ell} = 2, \ \varepsilon_{opt} = 10^{-5}, \ \varepsilon_{con} = 10^{-4}, \ \varepsilon_{inf} = 10^{-6}.$ All simulations ran on a Macbook Pro with 16 GB RAM. Our code is implemented in Python using PyTorch [53].

A. Garnet MDPs

Garnet problems are a class of abstract, parametrized and randomly-generated MDPs which have often been used as benchmarks [54]–[56]; see [52, Sec. 8] for a detailed description of Garnet MDPs. An important parameter of this problem is the branching factor f_b , that determines the fraction of possible next states for each (s, a) pair or, in other words, the fraction of non-zeros entries for each row of P. In this study, we use two values of f_b corresponding to dense $(f_b = 0.5)$, and sparse $(f_b = 0.05)$ transition matrices P. We consider MDPs with A = 10 actions and an increasing number of states S to study the scalability of different algorithms. The costs c(s, a) are generated randomly from a normal distribution $\mathcal{N}(0, 1)$, and we consider $\gamma = 0.95$.

First, we consider linear constraints with the entries of $E \in$ $\mathbb{R}^{10 \times SA}$ drawn from $\mathcal{N}(0,1)$ and b from $\mathcal{N}(-0.2,1)$. We compare Alg. 1 with Gurobi [57], a commercial LP solver, and a primal-dual method (PDM) (see, e.g., [58, Alg. 1]), that solves an uncostrained MDP using policy iteration at each step (for implementation details see Appendix D). To ensure a fair comparison, we implemented an inexact version of the primaldual method by executing finitely many policy iteration updates at each step. For Gurobi, we deploy its concurrent optimizer that simultaneously executes a barrier, a primal simplex and dual simplex method, and terminates once any method satisfies its termination tolerances which are set to 10^{-4} for both optimality and constraint violation. The termination conditions for PDM are outlined in Appendix D. We note that, all three approaches employ the same tolerance for constraint violation but different criteria of optimality; we chose the corresponding tolerances such that the resulting objective values are similar. In Table I, we report the computation times (averaged over 10 runs) and attained objective for each approach.

We observe that in all cases OS-CMDP performs on par with other solvers in terms of objective value. In particular, it typically yields a better objective than PDM and slightly worse than Gurobi (in the order of 1 - 5% worse). This is a consequence of the fact that Gurobi is suited to finding high-accuracy solutions. In terms of computation time, OS-CMDP significantly outperforms other approaches, especially as the problem dimension increases. We observe that OS-CMDP performs similarly regardless of density, whereas Gurobi is able to exploit sparsity in the problem. We note that for OS-CMDP we take into account both the execution time and the setup time, i.e., the computation and factorization of $(\gamma P - \Xi)^{T} (\gamma P - \Xi)$.

Next, we consider ℓ_2 -norm constraints as in Example 2, with randomly generated $\hat{d} \in \mathcal{D}$ and $\varepsilon = 0.2$. We compare Alg. 1 against Gurobi and SCS [59], a first-order solver for conic programs. We use SCS instead of a primal-dual scheme since the latter is not directly applicable for non-linear constraints. We set the optimality and feasibility tolerance of SCS to 10^{-4} . Results are presented in Table II.

Again, we note that OS-CMDP retrieves a solution significantly faster than competing methods, though with a slightly worse objective value. Obtaining a high-accuracy solution can be challenging for OS-CMDP, since it is a first-order method, but its strength lies in rapidly solving the problem up to medium accuracy. To highlight this, we remark that if we fix the computational budget to the time that OS-CMDP needs to converge, then other approaches yield highly-suboptimal solutions, or no solutions at all.

B. Grid world

Next, we study the qualitative behavior of Alg. 1 for both feasible and infeasible constraints by deploying it on a grid world problem, wherein an agent tries to navigate from a start location to a destination while avoiding obstacles and minimizing path length. The environment of the agent is represented as a grid whose cells correspond to states, some of which are occupied by obstacles. The agent can play the actions $\{up, down, left, right\}$ that induce a transition to the corresponding neighboring cell¹ with probability $1 - \delta$, where $\delta \in [0, 1)$. Conversely, with probability δ the agent ends up in a (uniformly) randomly-selected neighboring cell. This problem is inspired from case studies in [6], [11], [60]. Since this benchmark features very sparse P, we will focus on qualitative characteristics of Alg. 1 rather than computational performance.

In our simulations, we consider a 25×25 grid, consisting of 625 states and 45 obstacles, and we set $\gamma = 0.99$, and $\delta = 0.05$. The top left and bottom right cells are the respective start and destination of the agent. To minimize path length, we set the cost c to 1 for all non-destination states and to 0 for the destination. We enforce obstacle avoidance as a linear constraint $E_0^{\top} d \leq b_0$, where $E_0(s, a)$ is equal to 1 if state scorresponds to an obstacle, and 0 otherwise. The threshold $b_0 > 0$ prescribes the allowable (discounted) probability of collision.

We note that the stage cost c only encourages, but does not force, the agent to reach its destination. To achieve that, we impose the additional constraint $c^{\top}d \leq b_p$ for $b_p \in [0,1]$. Intuitively, decreasing b_p increases the probability of reaching the destination and decreases the resulting path length. We remark that $c^{\top}d = 1$ if the agent almost surely does not reach the destination, whereas if the agent disregards the obstacles and only minimizes path length we compute that $c^{\top}d = 0.396$ by solving the same MDP without constraints.

We will study the occupancy measure returned by Alg. 1 for various choices of b_0 and b_p . We remark that certain combinations of b_0 and b_p render the problem numerically challenging, for which we utilize smaller tolerances and scaling parameter σ .

In Figures 3a and 3b, we consider $(b_p, b_0) = (0.9, 10^{-3})$ and $(b_p, b_0) = (0.9, 2 \times 10^{-4})$, respectively. Colors represent the state-marginal occupancy measure of each cell *s*, i.e.,

¹For simplicity, we assume that executing actions that lead outside the grid do not affect the agent's position.

TABLE I: Solver comparison for linear constraints, in terms of computation times and objective value, reported in parantheses. The best performing solver is shown in bold, for each metric and setting.

		$f_b = 0.05$			$f_b = 0.5$	
Solver	OS-CMDP	Gurobi	PDM	OS-CMDP	Gurobi	PDM
S = 100	0.48s (-1.06)	0.05s (-1.12)	0.89s (-1.11)	0.39s (-1.05)	0.07s (-1.10)	0.69s (-1.09)
S = 1000	1.00s (-1.07)	1.80s (-1.08)	3.64s (-1.04)	0.63s (-1.08)	2.96s (-1.11)	3.22s (-1.08)
S = 3000	11.52s (-1.06)	20.13s (-1.07)	70.66s (-1.02)	4.98s (-1.08)	118.15s (-1.09)	30.54s (-1.04)
S = 5000	11.89s (-1.03)	71.98s (-1.07)	88.37s (-1.01)	10.58s (-1.05)	756.65 <i>s</i> (-1.08)	86.28s (-1.02)

TABLE II: Solver comparison for ℓ_2 -constraints, in terms of computation times and objective value, reported in parantheses. OOM indicates that the solver ran out of memory. The best performing solver is shown in bold, for each metric and setting.

		$f_b = 0.05$		$f_b = 0.5$		
Solver	OS-CMDP	Gurobi	SCS	OS-CMDP	Gurobi	SCS
S = 100	0.01s (-0.55)	0.03s (-0.55)	0.016s (-0.55)	0.01s (-0.58)	0.68s (-0.58)	0.06s (-0.58)
S = 1000	0.38s (-1.39)	2.72s (-1.39)	1.29s (-1.39)	0.39s (-1.45)	224.02s (-1.46)	8.77s (-1.46)
S = 3000	3.19s (-1.49)	44.61s (-1.53)	39.80s (-1.53)	3.18s (-1.51)	OOM	194.85 (-1.55)
S = 5000	10.44s (-1.51)	$97.33s\ (-1.52)$	185.73 <i>s</i> (-1.53)	10.45s (-1.52)	OOM	984.81s (-1.54)

 $\sum_{a} d(s, a)$, and arrows indicate that the corresponding action is chosen with non-zero probability, formally $d(s, a) > 10^{-10}$. Under both choices of thresholds, the problem is feasible and for smaller b_0 the agent sacrifices path length in favor of obstacle avoidance.

In Figure 4a, we consider $(b_p, b_0) = (0.9, 2 \times 10^{-5})$, that renders the problem infeasible, i.e., the agent cannot reach the destination without collision. The resulting policy simply tries to avoid the obstacles but, interestingly, if the agents ends up close to the destination then it will try to reach it. In Figure 4b, we set $(b_p, b_0) = (0.6, 2 \times 10^{-5})$ which is again infeasible, but tighter in terms of the path length constraint. Now, the resulting policy appears to randomly choose between two "strategies". One leads the agent to the destination via a path that is not sufficiently safe, and the other makes the agent wander in a safe and obstacle-free part of the grid. Our results highlight the ability of OS-CMDP to extract meaningful policies even from infeasible specifications, and indicate how individual constraints affect feasibility.

We remark that regions where d seems inconsistent with the dynamics, e.g., arrows from coloured cells pointing into white cells at the top right of Figure 4b, are numerical artifacts from approximately enforcing $d \in \mathcal{D}$.

VII. CONCLUSION

In this work, we developed a first-order algorithm for MDPs with convex constraints by deploying the Douglas-Rachford splitting. The main challenge in our approach is solving a quadratically-regularized MDP, for which we proposed an efficient scheme inspired by policy iteration. We demonstrated that our algorithm compares favorably against existing approaches on a benchmark problem, and is able to gracefully handle infeasible specifications. The main limitation of our work is that it requires perfect knowledge of the underlying MDP and relies on a direct parametrization of the occupancy measure. Future work includes extending our algorithm to the safe RL setting and employing function approximation.

APPENDIX

A. Derivations of Section III

Derivation of (8): To derive the dual problem of the regularized MDP (8), we first write the Lagrangian:

$$\mathcal{L}(d; V, \varphi) = (c + \gamma P V - \Xi V)^{\top} d + (1 - \gamma) \rho^{\top} V + \frac{1}{2\sigma} \|d - w_k\|^2 - \varphi^{\top} d , \qquad (22)$$

where $\varphi \ge 0$. We derive the dual function by minimizing \mathcal{L} with respect to d. The Lagrangian is a strongly convex function of d, so we find the unique minimizer by setting $\nabla_d \mathcal{L}(d; V, \varphi) = 0$, and solving for d yields:

$$d = w_k + \sigma(-c - \gamma PV + \Xi V + \varphi) . \tag{23}$$

Substituting (23) onto (22) yields the dual function κ , as shown in (9).

Lemma 1: The matrix $\gamma P - \Xi \in \mathbb{R}^{SA \times S}$ has trivial nullspace.

Proof: The matrices Ξ and P are given by:

$$\Xi := \begin{bmatrix} I_S \\ \vdots \\ I_S \end{bmatrix}, \ P := \begin{bmatrix} (P(s' \mid s = 1, a = 1))_{s' \in \mathcal{S}} \\ (P(s' \mid s = 2, a = 1))_{s' \in \mathcal{S}} \\ \vdots \\ (P(s' \mid s = S, a = A))_{s' \in \mathcal{S}} \end{bmatrix}.$$
(24)

Then, notice that

$$\gamma P - \Xi = \begin{bmatrix} \gamma P_{a=1} - I_S \\ \vdots \\ \gamma P_{a=A} - I_S \end{bmatrix}$$
(25)

where $P_{a=i}$ denotes the transition matrix induced by the policy that always chooses action $i \in A$. Standard dynamic



Fig. 3: State marginal occupancy measure (in color) and policy (as arrows) for two feasible choices of (b_p, b_0) . The thresholds b_p and b_0 correspond to the constraints of reaching the destination and avoiding collisions, respectively. Black circles indicate obstacles. Values below 10^{-10} are shown in white.



Fig. 4: State marginal occupancy measure (in color) and policy (as arrows) for two infeasible choices of (b_p, b_0) . The thresholds b_p and b_0 correspond to the constraints of reaching the destination and avoiding collisions, respectively. Black circles indicate obstacles. Values below 10^{-10} are shown in white.

programming arguments [61, Th. 6.1.1] guarantee that, for any $i \in A$, the matrix $\gamma P_{a=i} - I_S$ is invertible, hence $\gamma P - \Xi$ has trivial nullspace.

Derivation of (11): The maximizer of the dual function κ for a fixed V^* can be expressed as follows:

$$\begin{aligned} \underset{\varphi \ge 0}{\operatorname{argmax}} & -\frac{\sigma}{2} \| c + \gamma P V^{\star} - \Xi V^{\star} - \varphi \|^{2} \\ & + w_{k}^{\top} (c + \gamma P V^{\star} - \Xi V^{\star} - \varphi) + (1 - \gamma) \rho^{\top} V^{\star} \\ \overset{(a)}{=} \underset{\varphi \ge 0}{\operatorname{argmax}} - \| c + \gamma P V^{\star} - \Xi V^{\star} - \varphi \|^{2} \\ & + 2 w_{k}^{\top} / \sigma (c + \gamma P V - \Xi V - \varphi) - \| w_{k} / \sigma \|^{2} \\ \overset{(b)}{=} \underset{\varphi \ge 0}{\operatorname{argmax}} - \| \varphi - (c + \gamma P V - \Xi V - w_{k} / \sigma) \|^{2} \\ \overset{(c)}{=} \max (c + \gamma P V - \Xi V - w_{k} / \sigma, 0), \end{aligned}$$

where (a) is by multiplying with $2/\sigma > 0$ and adding/removing terms that do not depend on φ , (b) by factorizing the square, and (c) by noting that the problem in (b) is an orthogonal projection onto the non-negative orthant.

B. Proofs of Section IV

Proof of Proposition 1: To prove the claim, we will invoke [48, Th. 2.1], hence we proceed to verify that its preconditions hold. For ease of reference, in this proof we will use the notation in [48], i.e., let $g(\cdot) := \|c + \cdot\|_2^2, E := [\gamma P - \Xi - I], b := [(\gamma P - \Xi)^\top w_k + (1 - \gamma \rho) - w_k]$. Observe that, since $\gamma P - \Xi$ and -I are full column rank, then E has no zero column.

Next, we will establish that Assumption A1(a) in [48] holds. Observe that, strong duality holds for (8), by virtue of Slater's condition since all the constraints of the convex program (8) are affine, and the problem is feasible [62, §5.2.3]. Feasibility is guaranteed by the fact that any stationary Markov policy generates an occupancy measure that satisfies (8b), and (8c) [4, Th. 3.2]. The primal problem (8) is strongly convex, hence the optimal value is attained and finite. As such, the dual problem (9) admits a solution, which verifies Assumption A1(a) in [48].

Points (b) and (c) in Assumption A1 directly follow from g being strongly convex. Finally, notice that the iteration (16), coincides with the Coordinate Descent Method given in [48, Eq. (8),(9)] under a cyclic update rule and employing block coordinate updates (which does not compromise the convergence guarantees, as discussed in [48, Sec. 6]). The result follows by invoking [48, Th. 2.1].

Proof of Proposition 2: Under the assumption that the inner loop of Alg. 1 is executed to full convergence, Alg. 1 coincides with the DRA (7) applied to problem (4). To prove the claim we will invoke [32, Cor. 28.3]. The functions f and g are proper, closed, and convex. Further, Assumption 1 ensures that $0 \in \partial f + \partial g$ by virtue of [32, Cor. 27.6]. Having established its preconditions, [32, Cor. 28.3] yields the claim.

Proof of Proposition 3: By Fact 2.1 and Proposition 3.2 of [41], we know that $w_k - w_{k+1} \rightarrow v := \mathbb{P}_{\overline{\mathrm{dom}\,f-\mathrm{dom}\,g}\cap\overline{\mathrm{dom}\,f^*+\mathrm{dom}\,g^*}}(0)$, and $v = v_P + v_D$ where $v_P := \mathbb{P}_{\overline{\mathrm{dom}\,f-\mathrm{dom}\,g}}(0)$ and $v_D := \mathbb{P}_{\overline{\mathrm{dom}\,f^*+\mathrm{dom}\,g^*}}(0)$. To establish the claim, we will show that for the considered f and g it holds $v_D = 0$ and $v_P = \operatorname{argmin}_{\beta \in \mathcal{D}-\mathcal{C}} \|\beta\|$.

First, to show that $v_D = 0$ we proceed along the lines of [42, Example 6.2]. We have that \mathcal{D} is a compact polyhedron [4, Th. 3.2], hence ∂f is a maximally monotone operator [32, Th. 20.25] with a bounded domain dom $\partial f \subseteq \mathcal{D}$. Then, invoking [32, Cor. 21.25] we deduce that ran $\partial f = \mathbb{R}^{SA}$ and, since, ran $\partial f = \text{dom } \partial f^* \subseteq \text{dom } f^*$ [32, Cor. 16.30], we learn that dom $f^* = \mathbb{R}^{SA}$. Further, g^* is equal to the support function of \mathcal{C} , and since $\mathcal{C} \neq \emptyset$ we have $0 \in \text{dom } g^* \neq \emptyset$. Therefore, we conclude that $0 \in \text{dom } f^* + \text{dom } g^*$, which immediately implies $v_D = 0$.

Next, we observe that dom f = D and dom g = C. The set D is compact and C is closed, therefore $\overline{D} - \overline{C} = \overline{D} - \overline{C} = D - C$. The claim follows by noting that $v_P = \mathbb{P}_{D-C}(0) = \operatorname{argmin}_{\beta \in D-C} \|\beta\|$.

Lemma 2: Assume that $C \cap D = \emptyset$. Then, the minimal displacement vector v is the normal vector of a hyperplane that strongly separates C and D. Formally,

$$\min_{d \in \mathcal{D}} v^{\top} d > \sup_{z \in \mathcal{C}} v^{\top} z .$$
(26)

Proof: By Proposition 4 we know that any limit point $(\overline{d}, \overline{z}) \in \operatorname{argmin}_{d \in \mathcal{D}, z \in \mathcal{C}} ||d - z||$. The optimality conditions of the latter problem are:

$$\begin{cases} 0 \in \overline{d} - \overline{z} + \mathcal{N}_{\mathcal{D}}(\overline{d}) \\ 0 \in \overline{z} - \overline{d} + \mathcal{N}_{\mathcal{C}}(\overline{z}) \end{cases} \iff \begin{cases} -v \in \mathcal{N}_{\mathcal{D}}(\overline{d}) \\ v \in \mathcal{N}_{\mathcal{C}}(\overline{z}) \end{cases}, \quad (27) \end{cases}$$

where the equivalence follows by definition of \overline{d} and \overline{z} . The conditions (27) imply that

$$\inf_{d\in\mathcal{D}} v^{\top}d = v^{\top}\overline{d} \tag{28a}$$

$$\sup_{z \in \mathcal{C}} v^{\top} z = v^{\top} \overline{z} .$$
 (28b)

Subtracting the two equations yields

$$\inf_{d \in \mathcal{D}} v^{\top} d - \sup_{z \in \mathcal{C}} v^{\top} z = v^{\top} (\overline{d} - \overline{z}) = \|v\|^2,$$
(29)

which implies that $\inf_{d \in \mathcal{D}} v^{\top} d > \sup_{z \in \mathcal{C}} v^{\top} z$, since $v \neq 0$ due to $\mathcal{C} \cap \mathcal{D} = \emptyset$ and Proposition 3. We conclude the proof by noting that \mathcal{D} is compact and, hence, the infimum is attained.

Proof of Proposition 4: Combining [41, Th. 3.4] with the fact that $v_D = 0$ implies that $d_{k+1} - d_k \to 0$. The sequences $(d_k)_{k \in \mathbb{N}}, (z_k)_{k \in \mathbb{N}}$ are bounded by virtue of [42, Cor. 5.1], thus their respective set of limit points is non-empty. By the update rule (7d) it holds $w_k - w_{k+1} = d_k - z_k$ and, hence, $v = \overline{d} - \overline{z}$ for any convergent subsequence of (d_k, z_k) with limit $(\overline{d}, \overline{z})$. Recalling that $v = \operatorname{argmin}_{\beta \in \mathcal{D} - \mathcal{C}} \|\beta\|$, we can readily observe that $(\overline{d}, \overline{z}) \in \operatorname{argmin}_{d \in \mathcal{D}, z \in \mathcal{C}} \|d - z\|$ which establishes the first claim.

For the second claim, i.e., for polyhedral C, we will invoke [42, Th. 6.1(i)], and so we verify that its assumptions hold in our setting. First, in the proof of Proposition 3 we have shown that $0 \in \text{dom } f^* + g^*$. Additionally, we note that [42, Example 6.1(i)] guarantees that $Z \neq \emptyset$, hence $v \in \text{ran}(\text{Id} - T)$, where Z and T are defined in equations (14) and (3) in [42], respectively.

To show that $\operatorname{zer}(\partial f + \partial g(\cdot - v)) \neq \emptyset$, we recall that $v \in \operatorname{dom} f - \operatorname{dom} g$, hence $0 \in \operatorname{dom} f - (v + \operatorname{dom} g) \Longrightarrow \operatorname{dom} f \cap \operatorname{dom} g(\cdot - v) \neq \emptyset$. Thus, invoking [32, Cor. 27.3(i),(ii)] (under its precondition (c)) we obtain $\operatorname{zer}(\partial f + \partial g(\cdot - v)) \neq \emptyset$, since $\operatorname{argmin}_x f(x) + g(x - v)$ is non-empty (because f + g is a proper, closed, convex function with a compact domain [32, Th. 11.10]). We have established all the assumptions of [42, Th. 6.1(i)] and the claim follows. \Box

C. Inexact QRPI

In this section, we provide numerical verification that the inexact version of QRPI with $\overline{\ell} = 2$ performs similarly to the exact version. For the exact version, we use $\overline{\ell} = 100$ to approximate an infinite number of QRPI iterations. We compare the performance of exact and inexact QRPI in terms of three metrics: objective value, constraint violation, and compatibility with dynamics; we recall that if we execute finitely many QRPI iterations it is not guaranteed that $d_k \in \mathcal{D}$, i.e., d_k might not be a valid occupancy measure that is compatible with the dynamics.

For the objective value, we use the relative suboptimality of the iterates, namely $(c^{\top}d_k - c^{\top}d^{\star})/|c^{\top}d^{\star}|$ where d^{\star} is an optimal solution of (4) computed to high accuracy. For constraint violation, we use $\max_i \{\max(C_i(d_k) - b_i, 0)\}$. To measure compatibility with dynamics, we use $\|\Xi^{\top}d - (1-\gamma)\rho - \gamma P^{\top}d\|_{\infty}$ to quantify the violation of the equality constraint in (2). Note that, non-negativity of d_k is satisfied by design due to the update (13c).

In Figures 5a and 5b we plot the three metrics as a function of the iteration k for an instance of the linearly-constrained Garnet problem and the grid world, respectively, as introduced in Section VI. The continuous line corresponds to the exact variant while the dotted line indicates the inexact one.



Fig. 5: Performance comparison of Alg. 1 with exact (continuous line) and inexact (dotted line) QRPI in the inner loop.

We observe that the performance of exact and inexact QRPI closely match in terms of objective and constraint violation. In terms of dynamics, the exact version consistently attains a high compatibility, whereas the inexact variant is initially incompatible but gradually improves. We stress that this transient incompatibility is a minor issue, since we are only interested that $d_k \in \mathcal{D}$ for the final iterate. Practically, once the termination criteria are met, one can always run an additional iteration of Alg. 1 and execute enough QRPI iterations such that $d_k \in \mathcal{D}$ up to the desired accuracy. In our implementation we have included this safeguard.

D. Implementation of PDM

In the case of linear constraints $C = \{d \in \mathbb{R}^{SA} | Ed \leq b\}$ we can solve (4) via primal-dual schemes that exploit the structure of the Lagrangian:

$$\mathcal{L}(d;\lambda) = c^{\top}d + \mathcal{I}_{\mathcal{D}}(d) + \lambda^{\top}(Ed - b)$$
$$= (c + E^{\top}\lambda)^{\top}d + \mathcal{I}_{\mathcal{D}}(d) - \lambda^{\top}b$$

Then, we seek a solution of the saddle-point problem:

$$\max_{\lambda \ge 0} \min_{d \in \mathcal{D}} (c + E^{\top} \lambda)^{\top} d - \lambda^{\top} b .$$

Exploiting the fact that the inner minimization is an unconstrained MDP with cost $c + E^{\top}\lambda$, we can deploy a dual ascent scheme. Specifically, let $\lambda_0 \in \mathbb{R}_{>0}^{n_c}$ and iterate:

$$(\forall k \in \mathbb{N}) \qquad \qquad d_k \leftarrow \underset{d \in \mathcal{D}}{\operatorname{argmin}} (c + E^\top \lambda_k)^\top d \qquad (30a)$$

$$\left[\lambda_{k+1} \leftarrow \max(\lambda_k + \alpha_k(Ed_k - b), 0) \quad (30b)\right]$$

where $\alpha_k > 0$ is a step-size that satisfies $\alpha_k \to 0$ and $\sum_{k=0}^{\infty} \alpha_k = \infty$. For our benchmarks, we tested different step sizes and we used the one that achieved fastest convergence, specifically $\alpha_k = 10/(k+1)$. By virtue of [16, Th. 6], the sequence $(\frac{1}{k} \sum_{i=0}^{k} d_i, \lambda_k)_{k \in \mathbb{N}}$ converges to primal-dual solution of (4). The unconstrained MDP (30a) can be solved using any DP technique. In our implementation, we use policy

iteration. To ensure a fair comparison with OS-CMDP, we only run a finite number of policy iterations and, specifically we found that 2 iterations produce a good tradeoff between computational performance and accuracy. Further, similarly to OS-CMDP, we warm-start policy iteration for (30a) at iteration k using the approximately optimal value function computed at k - 1. We terminate (30) when $\|\lambda_{k+1} - \lambda_k\|_{\infty} \le 10^{-4}$ and $\max(a_i^\top d_k - b_i, 0) \le 10^{-4}(1 + |b_i|)$ for all $i = 1, \ldots, N_c$.

REFERENCES

- D. Silver, J. Schrittwieser, K. Simonyan, I. Antonoglou, A. Huang, A. Guez, T. Hubert, L. Baker, M. Lai, A. Bolton, *et al.*, "Mastering the game of go without human knowledge," *Nature*, vol. 550, no. 7676, pp. 354–359, 2017.
- [2] J. Degrave, F. Felici, J. Buchli, M. Neunert, B. Tracey, F. Carpanese, T. Ewalds, R. Hafner, A. Abdolmaleki, D. de Las Casas, *et al.*, "Magnetic control of tokamak plasmas through deep reinforcement learning," *Nature*, vol. 602, no. 7897, pp. 414–419, 2022.
- [3] R. S. Sutton and A. G. Barto, *Reinforcement learning: An introduction*. MIT press, 2018.
- [4] E. Altman, Constrained Markov decision processes. Routledge, 2021.
- [5] A. Tamar, D. Di Castro, and S. Mannor, "Policy gradients with variance related risk criteria," in *Proceedings of the twenty-ninth international conference on machine learning*, pp. 387–396, 2012.
- [6] Y. Chow, M. Ghavamzadeh, L. Janson, and M. Pavone, "Risk-constrained reinforcement learning with percentile risk criteria," *Journal of Machine Learning Research*, vol. 18, no. 167, pp. 1–51, 2018.
- [7] I. Koutsopoulos and L. Tassiulas, "Control and optimization meet the smart power grid: Scheduling of power demands for optimal energy management," in *Proceedings of the 2nd International Conference on Energy-efficient Computing and Networking*, pp. 41–50, 2011.
- [8] J. Achiam, D. Held, A. Tamar, and P. Abbeel, "Constrained policy optimization," in *Proceedings of the 34th International Conference on Machine Learning* (D. Precup and Y. W. Teh, eds.), vol. 70 of *Proceedings* of *Machine Learning Research*, pp. 22–31, PMLR, 06–11 Aug 2017.
- [9] R. Chen and G. Blankenship, "Dynamic programming equations for discounted constrained stochastic control," *IEEE Transactions on Automatic Control*, vol. 49, no. 5, pp. 699–709, 2004.
- [10] A. B. Piunovskiy, "Dynamic programming in constrained Markov decision processes," *Control and Cybernetics*, vol. 35, no. 3, pp. 645–660, 2006.
- [11] S. Khairy, P. Balaprakash, and L. X. Cai, "A gradient-aware search algorithm for constrained Markov decision processes," arXiv preprint arXiv:2005.03718, 2020.

- [12] D. Ding, K. Zhang, T. Basar, and M. Jovanovic, "Natural policy gradient primal-dual method for constrained Markov decision processes," in *Advances in Neural Information Processing Systems* (H. Larochelle, M. Ranzato, R. Hadsell, M. Balcan, and H. Lin, eds.), vol. 33, pp. 8378– 8390, Curran Associates, Inc., 2020.
- [13] T. Liu, R. Zhou, D. Kalathil, P. Kumar, and C. Tian, "Learning policies with zero or bounded constraint violation for constrained MDPs," *Advances in Neural Information Processing Systems*, vol. 34, pp. 17183– 17193, 2021.
- [14] M. Calvo-Fullana, S. Paternain, L. F. O. Chamon, and A. Ribeiro, "State augmented constrained reinforcement learning: Overcoming the limitations of learning with rewards," *arXiv preprint arXiv:2102.11941*, 2023.
- [15] C. Szepesvári, "Constrained MDPs and the reward hypothesis." https://readingsml.blogspot.com/2020/03/ constrained-mdps-and-reward-hypothesis.html.
- [16] K. M. Anstreicher and L. A. Wolsey, "Two "well-known" properties of subgradient optimization," *Mathematical Programming*, vol. 120, pp. 213– 220, 2009.
- [17] E. Gladin, M. Lavrik-Karmazin, K. Zainullina, V. Rudenko, A. Gasnikov, and M. Takac, "Algorithm for constrained Markov decision process with linear convergence," in *International Conference on Artificial Intelligence* and Statistics, pp. 11506–11533, PMLR, 2023.
- [18] T. Li, Z. Guan, S. Zou, T. Xu, Y. Liang, and G. Lan, "Faster algorithm and sharper analysis for constrained Markov decision process," *arXiv* preprint arXiv:2110.10351, 2021.
- [19] A. Müller, P. Alatur, G. Ramponi, and N. He, "Cancellation-free regret bounds for lagrangian approaches in constrained Markov decision processes," arXiv preprint arXiv:2306.07001, 2023.
- [20] D. Ding, C.-Y. Wei, K. Zhang, and A. Ribeiro, "Last-iterate convergent policy gradient primal-dual methods for constrained MDPs," *arXiv* preprint arXiv:2306.11700, 2024.
- [21] T. Moskovitz, B. O'Donoghue, V. Veeriah, S. Flennerhag, S. Singh, and T. Zahavy, "Reload: Reinforcement learning with optimistic ascentdescent for last-iterate convergence in constrained MDPs," in *International Conference on Machine Learning*, pp. 25303–25336, PMLR, 2023.
- [22] Y. Liu, J. Ding, and X. Liu, "Ipo: Interior-point policy optimization under constraints," in *Proceedings of the AAAI conference on artificial intelligence*, vol. 34, pp. 4940–4947, 2020.
- [23] T.-Y. Yang, J. Rosca, K. Narasimhan, and P. J. Ramadge, "Projectionbased constrained policy optimization," arXiv preprint arXiv:2010.03152, 2020.
- [24] T. Zahavy, B. O'Donoghue, G. Desjardins, and S. Singh, "Reward is enough for convex MDPs," *Advances in Neural Information Processing Systems*, vol. 34, pp. 25746–25759, 2021.
- [25] P. Abbeel and A. Y. Ng, "Apprenticeship learning via inverse reinforcement learning," in *Proceedings of the twenty-first international conference* on Machine learning, p. 1, 2004.
- [26] E. Hazan, S. Kakade, K. Singh, and A. Van Soest, "Provably efficient maximum entropy exploration," in *International Conference on Machine Learning*, pp. 2681–2691, PMLR, 2019.
- [27] B. Eysenbach, A. Gupta, J. Ibarz, and S. Levine, "Diversity is all you need: Learning skills without a reward function," *arXiv preprint* arXiv:1802.06070, 2018.
- [28] D. Ying, M. A. Guo, Y. Ding, J. Lavaei, and Z.-J. Shen, "Policy-based primal-dual methods for convex constrained Markov decision processes," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 37, pp. 10963–10971, 2023.
- [29] J. Zhang, A. Koppel, A. S. Bedi, C. Szepesvari, and M. Wang, "Variational policy gradient method for reinforcement learning with general utilities," *Advances in Neural Information Processing Systems*, vol. 33, pp. 4572– 4583, 2020.
- [30] S. Miryoosefi, K. Brantley, H. Daume III, M. Dudik, and R. E. Schapire, "Reinforcement learning with convex constraints," *Advances in neural information processing systems*, vol. 32, 2019.
- [31] S. Miryoosefi and C. Jin, "A simple reward-free approach to constrained reinforcement learning," in *International Conference on Machine Learning*, pp. 15666–15698, PMLR, 2022.
- [32] H. Bauschke and P. Combettes, Convex Analysis and Monotone Operator Theory in Hilbert Spaces. CMS Books in Mathematics, Springer International Publishing, 2017.
- [33] S. Boyd, N. Parikh, E. Chu, B. Peleato, J. Eckstein, *et al.*, "Distributed optimization and statistical learning via the alternating direction method of multipliers," *Foundations and Trends*® *in Machine learning*, vol. 3, no. 1, pp. 1–122, 2011.

- [34] W. M. Moursi and Y. Zinchenko, "A note on the equivalence of operator splitting methods," *Splitting Algorithms, Modern Operator Theory, and Applications*, pp. 331–349, 2019.
- [35] T. Yu, Y. Tian, J. Zhang, and S. Sra, "Provably efficient algorithms for multi-objective competitive RL," in *International Conference on Machine Learning*, pp. 12167–12176, PMLR, 2021.
- [36] B. O'Donoghue, G. Stathopoulos, and S. Boyd, "A splitting method for optimal control," *IEEE Transactions on Control Systems Technology*, vol. 21, no. 6, pp. 2432–2442, 2013.
- [37] G. Neu, A. Jonsson, and V. Gómez, "A unified view of entropy-regularized Markov decision processes," arXiv preprint arXiv:1705.07798, 2017.
- [38] M. Geist, B. Scherrer, and O. Pietquin, "A theory of regularized Markov decision processes," in *Proceedings of the 36th International Conference* on Machine Learning (K. Chaudhuri and R. Salakhutdinov, eds.), vol. 97 of *Proceedings of Machine Learning Research*, pp. 2160–2169, PMLR, 09–15 Jun 2019.
- [39] M. Gargiani, A. Zanelli, D. Liao-McPherson, T. Summers, and J. Lygeros, "Dynamic programming through the lens of semismooth Newton-type methods," *IEEE Control Systems Letters*, vol. 6, pp. 2996–3001, 2022.
- [40] M. A. S. Kolarijani and P. M. Esfahani, "From optimization to control: quasi policy iteration," arXiv preprint arXiv:2311.11166, 2023.
- [41] G. Banjac, "On the minimal displacement vector of the Douglas–Rachford operator," *Operations Research Letters*, vol. 49, no. 2, pp. 197–200, 2021.
- [42] H. H. Bauschke and W. M. Moursi, "On the Douglas–Rachford algorithm for solving possibly inconsistent optimization problems," *Mathematics* of Operations Research, 2023.
- [43] A. U. Raghunathan and S. Di Cairano, "Infeasibility detection in alternating direction method of multipliers for convex quadratic programs," in 53rd IEEE Conference on Decision and Control, pp. 5819–5824, IEEE, 2014.
- [44] Y. Liu, E. K. Ryu, and W. Yin, "A new use of Douglas-Rachford splitting and admm for identifying infeasible, unbounded, and pathological conic programs," arXiv preprint arXiv:1706.02374, 2017.
- [45] G. Banjac, P. Goulart, B. Stellato, and S. Boyd, "Infeasibility detection in the alternating direction method of multipliers for convex optimization," *Journal of Optimization Theory and Applications*, vol. 183, pp. 490–519, 2019.
- [46] R. T. Rockafellar and R. J.-B. Wets, Variational analysis, vol. 317. Springer Science & Business Media, 2009.
- [47] J. Eckstein and D. P. Bertsekas, "On the Douglas—Rachford splitting method and the proximal point algorithm for maximal monotone operators," *Mathematical programming*, vol. 55, pp. 293–318, 1992.
- [48] Z.-Q. T. Luo and P. Tseng, "On the convergence of the coordinate descent method for convex differentiable minimization," *Journal of Optimization Theory and Applications*, vol. 72, pp. 7–35, 1992.
- [49] J. Nocedal and S. Wright, *Numerical Optimization*. Springer Series in Operations Research and Financial Engineering, Springer New York, 2006.
- [50] J. Eckstein and M. C. Ferris, "Operator-splitting methods for monotone affine variational inequalities, with a parallel application to optimal control," *INFORMS Journal on Computing*, vol. 10, no. 2, pp. 218–235, 1998.
- [51] J. Eckstein, "Parallel alternating direction multiplier decomposition of convex programs," *Journal of Optimization Theory and Applications*, vol. 80, no. 1, pp. 39–62, 1994.
- [52] S. Bhatnagar, R. Sutton, M. Ghavamzadeh, and M. Lee, "Natural Actor-Critic Algorithms," *Automatica*, vol. 45, July 2009.
- [53] A. Paszke, S. Gross, F. Massa, A. Lerer, J. Bradbury, G. Chanan, T. Killeen, Z. Lin, N. Gimelshein, L. Antiga, *et al.*, "Pytorch: An imperative style, high-performance deep learning library," *Advances in neural information processing systems*, vol. 32, 2019.
- [54] A.-m. Farahmand and M. Ghavamzadeh, "PID accelerated value iteration algorithm," in *International Conference on Machine Learning*, pp. 3143– 3153, PMLR, 2021.
- [55] J. Grand-Clément and C. Kroer, "Scalable first-order methods for robust MDPs," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 35, pp. 12086–12094, 2021.
- [56] A. Tamar, D. Di Castro, R. Meir, and P. Dayan, "Integrating a partial model into model free reinforcement learning.," *Journal of Machine Learning Research*, vol. 13, no. 6, 2012.
- [57] Gurobi Optimization, LLC, "Gurobi Optimizer Reference Manual," 2023.
- [58] S. Paternain, M. Calvo-Fullana, L. F. Chamon, and A. Ribeiro, "Safe policies for reinforcement learning via primal-dual methods," *IEEE Transactions on Automatic Control*, vol. 68, no. 3, pp. 1321–1336, 2022.
- [59] B. O'donoghue, E. Chu, N. Parikh, and S. Boyd, "Conic optimization via operator splitting and homogeneous self-dual embedding," *Journal of Optimization Theory and Applications*, vol. 169, pp. 1042–1068, 2016.

- [60] C. Tessler, D. J. Mankowitz, and S. Mannor, "Reward constrained policy optimization," *arXiv preprint arXiv:1805.11074*, 2018.
 [61] M. L. Puterman, "Markov decision processes," *Handbooks in operations research and management science*, vol. 2, pp. 331–434, 1990.
 [62] S. P. Boyd and L. Vandenberghe, *Convex optimization*. Cambridge university press, 2004.