# Fast Leaderless Byzantine Total Order Broadcast

MATTEO MONTI, HES-SO Valais-Wallis MARTINA CAMAIONI, Ecole Polytechnique Fédérale de Lausanne (EPFL) PIERRE-LOUIS ROMAN

This paper presents the Byzantine fault-tolerant agreement protocols Flutter and Blink. Both algorithms are deterministic, leaderless and signature-free; both assume partial synchrony and at least (5f+1) servers, where f bounds the number of faults. The main contribution, Flutter, is a Total-Order Broadcast implementation that achieves faster broadcast-to-delivery latency by removing the extra message delay associated with serializing messages through a leader. In the "good case" where all processes are correct, the network is synchronous, and local clocks are well-synchronized, Flutter delivers client requests in  $(2\Delta+\epsilon)$  time units,  $\Delta$  being the message delay and  $\epsilon$  an arbitrarily small constant. Under the same conditions, state-of-the-art protocols require  $3\Delta$  time units. Flutter's good-case latency is quasi-optimal, meaning it cannot be improved upon by any finite amount. Under the hood, Flutter builds upon Blink, a (Representative) Binary Consensus implementation whose fast path enables decisions in  $\Delta$  time units when all correct servers propose the same value. Blink generalizes the existing Binary Consensus solution Bosco from the (7f+1) to the (5f+1) setting.

#### 1 INTRODUCTION

Byzantine Consensus and Total-Order Broadcast [31, 61] are among the most studied abstractions in the field of distributed computing [14, 18, 21, 25, 43, 54, 56, 74, 87, 97], powering State Machine Replication [58, 81] and unlocking universal, transparent, reliable computing in the face of arbitrary failures. Real-world implementations of these abstractions can power a great variety of fault-tolerant applications, as exemplified most prominently by blockchain-based financial systems [17, 44, 57, 69, 90–92]. The two abstractions are closely related [19, 36]: Consensus has servers agree on a common decision, while Total-Order Broadcast has servers agree on a totally-ordered sequence of client-issued messages. Indeed, Total-Order Broadcast is often implemented using multiple instances of Consensus, achieving a common sequence of messages by having servers successively agree on which message to deliver next.

Following a similar scheme, this paper contributes two algorithms. The first, Blink, implements Representative Binary Consensus. The second, Flutter, uses multiple instances of Representative Binary Consensus to implement Total-Order Broadcast. Both algorithms are deterministic, work in the partially synchronous model, and assume at least (5f+1) servers, where f bounds the number of faulty servers. The design of our algorithms revolves around four fundamental goals: simplicity, leader-freedom, signature-freedom and optimism.

Goal 1: Simplicity. Simple algorithms bring several advantages, many tied to the fundamental goal of Byzantine computing to secure applications in the face of malicious failures. Simpler algorithms are easier to reason about [74, 78, 96], cheaper to implement and maintain [8], more amenable to formal verification [59], and better compatible with hardware-accelerated systems [48, 53, 85] and constrained hardware architectures [50, 93]. Simpler algorithms come with a smaller trusted computing base, inherently mitigating the danger that a single implementation vulnerability will nullify a system's bid for fault-tolerance and security [15, 26]. The pseudocode of a Flutter server spans 48 lines, using only low-level fundamentals such as individual message handlers and basic data structures like sets and maps. Blink is shorter, requiring only 24 lines of pseudocode, but does depend on an underlying instance of Binary Consensus (see §§2 and 3) whose implementation can be as short as 43 lines of pseudocode [13].


Goal 2: Leader-freedom. The algorithms are leaderless [6, 29], meaning they do not rely on any individual server to make progress. Leader-freedom brings three key advantages. First, leaderless algorithms result in lower best-case latency, as they avoid the extra message delay associated with serializing messages through a leader (see Fig. 1). Second, they sidestep the extensive logic that leader-based solutions require to elect [5, 18], suspect [22, 23, 82], and rotate [27, 94] leaders. This translates into a significantly shorter worst-case latency, avoiding the adaptive-adversary scenario where a linear number of faulty leaders has to be detected and discarded before any progress is made [38, 45]. Third, leaderless algorithms have the potential for improved fairness. Unless dedicated logic is put in place to ensure fair ordering [52, 99], leader-based implementations are usually vulnerable to a malicious leader affecting the order of messages, e.g., by censoring or front-running correct clients [32, 80]. In Flutter, every message that reaches all correct servers in a timely fashion is certainly delivered, and cannot be delayed.

Goal 3: Signature-freedom. The algorithms avoid signatures, rather relying on authenticated point-to-point channels to ensure integrity. Signatures are among the most expensive tools in the standard cryptographic toolbox, dwarfing the complexity of symmetric primitives such as hashes, ciphers and message authentication codes. As such, signature-free solutions [3, 98] relieve a fundamental bottleneck in Byzantine computing [30, 67, 89], while promoting hardware acceleration via easier deployment on specialized hardware [48, 53, 85]. Signature-freedom also provides an easy solution to quantum-powered attacks. Most popular signature schemes in classical cryptography rely on hard problems – such as computing the discrete logarithm of an element of a prime field – against which a quantum computer has an exponential advantage [83]. Post-quantum signature schemes, which negate this advantage, are being standardized [77], but tend to be even more expensive than their classical counterparts. In contrast, a quantum attacker only has a quadratic advantage against symmetric primitives used to implement authenticated point-to-point channels. Hence, securing Flutter and Blink against practical quantum attacks reduces to doubling the bits security of whatever scheme is employed to authenticate the system's links.

Goal 4: Optimism. The algorithms are designed to take advantage of the good case. Both Flutter and Blink uphold all their properties under standard assumptions, most notably partial synchrony [40] and Byzantine failures. These assumptions are conservative, but capture well the worst-case behavior, e.g., of an open-Internet system, prone to hacks and unpredictable latency spikes. In practice, however, even Wide Area Networks are synchronous most of the time, local clocks are well-synchronized, and malicious faults are rare, especially when accountability mechanisms [22, 23, 82] are put in place to purge the system of misbehaving processes. We refer to these conditions as the good case. Flutter takes advantage of the good case to achieve unprecedented latency.

Blink. Blink is the first (5f + 1) implementation of Byzantine (Representative) Binary Consensus to enable a single-message-delay fast path if all correct servers propose the same value. In brief, Representative Binary Consensus requires the decided value to be proposed by at least (f + 1) correct servers, in contrast to the single correct server required by Binary Consensus. Blink builds Representative Binary Consensus on top of an existing instance dep of Binary Consensus [28, 74].

Blink involves a single step of all-to-all communication, wherein every correct server disseminates its proposal as a *suggestion*. Upon collecting (4f+1) suggestions, a correct server proposes to *dep* whichever value it was suggested the most (i.e., whichever value it was suggested at least (2f+1) times). A correct server always decides whatever *dep* decides. Unless at least (f+1) correct servers suggest some value v, no correct server will ever collect the (2f+1) suggestions required to propose v to *dep*, meaning that, by the Validity of *dep*, v will not be decided. This also enables Blink's fast path. If every correct server proposes v, within one message delay every correct






Fig. 1. **Good-case latencies of Flutter and FaB Paxos** [72]. Other fast Byzantine Total-Order Broadcast protocols follow FaB Paxos' leader-based pattern: (1) the client  $\theta$  sends its message to the leader  $\pi_1$ , (2) which disseminates it to all servers  $\pi_1 \dots \pi_n$ , (3) each of which disseminates a confirmation message, (4) upon which all servers decide. These protocols have a good-case latency of  $3\Delta$ . Flutter skips the forwarding leader, saving a message delay as in Fast Paxos [60], but adds an arbitrarily small delay  $\epsilon$  for a good-case latency of  $(2\Delta + \epsilon)$ .

server collects (4f + 1) suggestions for v, thus ensuring that no correct server will collect (f + 1) suggestions for  $\bar{v}$ . As such, every correct server can decide v immediately, without waiting for the slower dep to come to the same decision.

Blink generalizes to the (5f + 1) setting a previous result, Bosco [86], a one-step Binary Consensus in the (7f + 1) setting. Blink's analysis includes a thorough comparison with Bosco, and explains why Blink does not infringe on Bosco's result that "one-step" (5f + 1) Consensus is impossible.

Flutter. Flutter is the first implementation of Byzantine Total-Order Broadcast to attain a goodcase latency of  $(2\Delta + \epsilon)$ , where  $\Delta$  bounds the message delay and  $\epsilon$  is an arbitrarily small interval of time, e.g., the shortest interval of time that a processor can represent. Such a latency is quasi-optimal, meaning it cannot be improved upon by any finite amount. Flutter relies on Representative Binary Consensus for correctness, and leverages Blink's fast path (see Fig. 1).

Existing implementations of Total-Order Broadcast usually have clients entrust their messages to one [2, 11, 18, 56, 97] or multiple [9, 88, 89] leaders. In leader-based algorithms, a leader submits the messages it collects to Consensus, which successively selects which messages are delivered next; if a leader is suspected having crashed or misbehaved, a new leader is selected to replace it.

Flutter's core idea is to sidestep leaders, shifting to clients the responsibility of proposing how messages should be ordered. Flutter does so by leveraging real time as a natural source of ordering, as done in some crash-stop protocols [39, 41]. Intuitively, unlike a leader, a client cannot easily submit to Consensus that its message should be delivered next, or that its message should be delivered n-th – what a client can submit is that its message was disseminated by some time t.

To broadcast a message m, a correct Flutter client attaches to m a bet b, which is a timestamp representing the client's best estimate for "one message delay in the future". The client then disseminates (m,b) to all servers. Intuitively, the client wagers: "I bet I can get my message m to every correct server by time b!". Upon delivering (m,b), a correct server checks its local clock to find out if the bet paid off: if b is still in the future, the server proposes True to Representative Binary Consensus to support m's delivery; the server proposes False otherwise. Bets provide a natural Total Order to client-issued messages: once Representative Binary Consensus has decided which messages get delivered, servers deliver them in increasing order of bet. If the client underestimates b and m is rejected, it retries broadcasting with a more conservative bet – eventually, the client is guaranteed to disseminate m in time, and get m delivered.

In the good case, clocks are well-synchronized and the network is synchronous, meaning that processes correctly estimate the message delay  $\Delta$ . When broadcasting m at time t, a correct client

can thus set  $b=(t+\Delta+\epsilon)$ : by time  $(t+\Delta)$ , every correct server receives (m,b) and proposes that m should be delivered. This unlocks Blink's fast path: because every correct server proposes the same value, every correct server decides that m should be delivered within one message delay, i.e., by time  $(t+2\Delta)$ . By time  $(t+2\Delta+\epsilon)$ , every correct server can be certain to have observed any message with a lower bet than b, and delivers m.

Contributions summary. We propose Flutter and Blink. To the best of our knowledge, Flutter is the first implementation of Byzantine Total-Order Broadcast with a good-case latency of  $(2\Delta + \epsilon)$ , where  $\Delta$  bounds the message delay, and  $\epsilon$  is an arbitrarily small interval of time (e.g., the shortest interval of time that a processor can represent). Such a latency is quasi-optimal, meaning it cannot be improved upon by any finite amount. To the best of our knowledge, Blink is the first implementation of Byzantine Binary Consensus to enable a single-message-delay fast path in the (5f+1) model.

Roadmap. §2 states the model and recalls abstraction definitions. §3 overviews Blink, leaving most of its details to Appx. A for brevity. §4 presents Flutter, its inner workings and algorithm. §5 discusses related work and §6 future work. Appx. A discusses Blink, its differences with Bosco, and proves its correctness, good-case latency and complexity. Appx. B proves Flutter's correctness, good-case latency and complexity. Appx. C proves that Flutter's good-case latency is quasi-optimal.

#### 2 MODEL AND BACKGROUND

#### 2.1 Model

System, links and scheduling. We assume a message-passing system where processes are organized in two sets: **servers** ( $\Pi$ ) and **clients** ( $\Theta$ ). We use  $n = |\Pi|$ . Servers are fixed and permissioned, meaning every correct process knows  $\Pi$ . Any two processes communicate via reliable, authenticated, FIFO links, i.e., messages are delivered in the order they are sent. We assume partial synchrony [40]: the message delay between processes is bounded by an unknown constant  $\Delta$ ; the difference between real time and the local time of any process is bounded by an unknown constant  $\Psi$ . We include in  $\Delta$  the duration of any constant-time computing required to produce a message on the sender side, or deliver a message on the receiver side. While partially synchronous algorithms often make no distinction between  $\Delta$  and  $\Psi$ , the availability of cheap and accurate real-time clocks, time servers, and synchronization mechanisms such as GPS make the distinction relevant, as  $\Psi \ll \Delta$  in practice [62, 64, 66, 76]. The proposed algorithms still uphold all their security properties if  $\Psi \geq \Delta$ .

Adversary and faults. Faulty processes are Byzantine [61], i.e., they may deviate arbitrarily from the algorithm they are assigned. Byzantine processes know each other, and may collude and coordinate their actions. We assume that at most f servers are Byzantine, with n=(5f+1); we make no assumption about the number of faulty clients. We assume an adaptive adversary, meaning that, subject to the Byzantine threshold constraint, the adversary can choose which processes to compromise based on system and protocol state. We make no assumption about confidentiality, the adversary can eavesdrop on any link. As the algorithms presented in this paper make no use of cryptography, we make no assumption about the adversary being computationally bounded.  $^5$ 

 $<sup>^1\</sup>mathrm{Servers}$  and clients can be disjoint or overlap – the results apply to both settings.

 $<sup>^2\</sup>mathrm{TCP}$  can be used as a reliable, FIFO transport layer for practical implementations.

 $<sup>^{3}</sup>$ We underline that real time is arbitrarily defined, and used just for convenience. It would be equivalent to bound the difference between any two local times by  $2\Psi$ , then label as "real time" the local time of any correct process.

<sup>&</sup>lt;sup>4</sup>If client and servers overlap, the maximum number of faulty clients might be constrained by the server Byzantine threshold. For example, if every process is both server and client, less than one-fifth of clients will end up being faulty.

<sup>&</sup>lt;sup>5</sup>In practice, authenticated links over Wide Area Networks are often established by means of cryptographic key exchange protocols and message authentication codes, e.g., using TLS. Relying on cryptographic primitives may require additional assumptions on the power of the adversary to ensure the safety of the implementations.

#### 2.2 Abstractions

This paper studies two fundamental abstractions in Byzantine distributed computing: Representative Binary Consensus and Total-Order Broadcast [13].

Representative Binary Consensus. In brief, Representative Binary Consensus is a variant of Binary Consensus, which has correct servers agree on a binary value v ( $v \in \mathbb{B}$ , with  $\mathbb{B} = \{\text{True}, \text{False}\}$ ). The interface to a Representative Binary Consensus instance con comprises two events: a **request**  $\langle con.\text{Propose} \mid p \in \mathbb{B} \rangle$ , which every correct server uses once to submit its proposal p; and an **indication**  $\langle con.\text{Decide} \mid d \in \mathbb{B} \rangle$ , which a correct server uses to relay that d was decided. Representative Binary Consensus ensures **Integrity**: no correct server decides more than once; **Agreement**: no two correct servers decide different values; **Termination**: every correct server eventually decides; and **Representative Validity**: the decided value was proposed by at least (f+1) correct servers. The latter contrasts with Binary Consensus's Validity stating that a value can be decided as long as it is proposed by a single correct server.

Total-Order Broadcast. **Total-Order Broadcast** has correct servers agree on a totally-ordered sequence of client-issued messages. Let  $\mathcal{M}$  be the set of all possible messages. The interface to a Total-Order Broadcast instance tob comprises two events: a **request**  $\langle tob$ .Broadcast  $\mid m \in \mathcal{M} \rangle$ , which a correct client uses to broadcast a message (we assume no correct client broadcasts the same message twice); and an **indication**  $\langle tob$ .Deliver  $\mid \theta \in \Theta, m \in \mathcal{M} \rangle$ , which a correct server uses to indicate the delivery of m from  $\theta$ . Total-Order Broadcast ensures **No Duplication**: no correct server delivers the same message from the same sender twice; **Integrity**: a correct server delivers a message m from a correct client  $\theta$  only if  $\theta$  broadcast m; **Validity**: all messages broadcast by a correct client are eventually delivered by a correct server; and **Agreement and Total Order**: all correct servers eventually deliver the same messages in the same order.

#### 2.3 Good Case Scenario

Good-case assumptions. The algorithms presented in this paper uphold all their properties under the assumptions we introduced in §2.1. Flutter, however, attains its minimal latency under more stringent conditions we refer to as the **good case**. In the good case: all processes are correct; local computation is instantaneous; and the system is synchronous, meaning that  $\Delta$  is known and  $\Psi=0$ . We set  $\Psi=0$  only to streamline the proofs: every good-case latency result (see Appx. B.6) can be generalized to any synchronous model where both  $\Delta$  and  $\Psi$  are known.

*Transient good case.* All the latency proofs assume that the good case applies to an entire execution of Flutter (see Appx. B.6). This is only done to streamline the analysis. In practice, for messages to be delivered with minimal latency, it is sufficient for the good case to apply long enough for all messages that caused disagreement to be processed. Flutter resumes delivering all messages with minimal latency as soon as all "bad messages" are flushed out of the system.

# 3 BLINK

This section overviews our Representative Binary Consensus implementation Blink (Fig. 2). Additional details on Blink's algorithm, its differences with Bosco [86], proof sketches and full proofs of both Blink's correctness and latency, as well as a complexity analysis can be found in Appx. A.

In a blink. Blink builds Representative Binary Consensus on top of a Binary Consensus instance dep, while also enabling a single-message-delay fast path whenever all correct servers propose the same value. Blink does so by means of a single step of all-to-all communication, wherein each correct server disseminates its proposal as a suggestion. Upon collecting (4f + 1) suggestions, a




Fig. 2. **Blink algorithm.** A correct server disseminates its proposal as a suggestion, then proposes to Binary Consensus whichever value it was suggested the most. In the fast path, a correct server decides after receiving (4f + 1) matching suggestions. In the slow path, a correct server decides whatever Binary Consensus decides. Notation: a correct server's engagement in Binary Consensus is marked by a crossed bar; proposals and decisions are indicated at the beginning and end of each bar;  $\checkmark$  represents True.

correct server proposes to *dep* whichever value it was suggested the most; a correct server decides whatever *dep* decides.

Representative Validity. All-to-all suggestions are the key to upgrade dep's Validity into Representative Validity: a correct server  $\pi$  that submits v to dep must have received at least (2f+1) suggestions for v, (f+1) of which came from correct servers. As such, unless at least (f+1) correct servers propose v, no correct server submits v to dep, and since dep ensures Validity, v cannot be decided. As (f+1) proposals are needed to decide v, Blink satisfies Representative Validity.

Blink's fast path. Suggestions also unlock Blink's fast path. Even after submitting a value to dep, a correct server keeps gathering suggestions. If, at any point, a correct server collects (4f+1) suggestions for v, it immediately decides v without waiting for dep's slower output. No need to wait: out of those (4f+1) suggestions, at least (3f+1) came from correct servers, hence no more than f correct servers proposed  $\bar{v}$ . As such, no correct server will ever collect the (2f+1) suggestions necessary to propose  $\bar{v}$  to dep: again by Validity, dep can only decide v. If every correct server proposes the same value v, every correct server collects (4f+1) suggestions for v, thus deciding within a single message delay. We use this insight in the design of Flutter (see §4), where we tailor our good-case execution around all correct servers proposing the same value.

#### 4 FLUTTER

This section describes our Total-Order Broadcast implementation Flutter. Flutter relies on Representative Binary Consensus (see §2.2) to decide which messages are delivered, and takes advantage of Blink, our Representative Binary Consensus implementation, described in §3. Thanks to Blink's fast path, Flutter achieves a good-case latency of  $(2\Delta + \epsilon)$ , with  $\epsilon$  an arbitrarily small constant.

§4.1 overviews the intuition behind Flutter. §4.2 discusses Flutter's inner mechanisms. §4.3 presents an example execution of Flutter from the point of view of a correct server. §4.4 details Flutter's algorithm. §4.5 proposes proof sketches arguing for Flutter's correctness. §4.6 briefly discusses Flutter's good- and bad-case latencies. §4.7 discusses Flutter's complexity.

Further, Appx. B fully proves Flutter's correctness and good-case latency, as well as discusses the impact of denial of services on Flutter. Appx. C proves Flutter's good-case latency is quasi-optimal.

#### 4.1 Overview

Total-Order Broadcast implementations usually delegate the responsibility of ordering messages to one [11, 18, 72, 87, 97] or several [7, 39, 41, 71, 73, 88] leaders. By contrast, Flutter is leaderless. This

section outlines Flutter's approach to leader-freedom, and underlines the *problem of convergence* that such an approach entails. §4.2 discusses how Flutter solves the problem of convergence.

Bets. To bypass leaders, Flutter shifts to clients the responsibility to propose how messages should be ordered. Correct clients attach to each message a timestamp, which we call **bet**. Correct servers always deliver messages in increasing order of bet. By issuing a message m with bet b, a client proposes that m should be delivered with rank b, i.e., that b should determine where m appears in the common sequence of delivered messages.

Algorithm intuition. In Flutter, clients are free to propose the delivery of any message with any bet; correct servers use Representative Binary Consensus to determine which proposals are accepted. More in detail, upon broadcasting a message m, a correct client  $\theta$  checks its local clock, estimates some future time b (m's bet) by which it expects to reach all correct servers, then disseminates (m, b). To reach all correct servers in time,  $\theta$  sets  $b = (t + \tilde{\Delta} + \epsilon)$ , where t is  $\theta$ 's local time,  $\tilde{\Delta}$  is  $\theta$ 's best estimate of the message delay  $\Delta$  and  $\epsilon$  is an arbitrarily small constant. While  $\theta$  cannot reliably determine  $\Delta$  in partial synchrony, it can in practice obtain  $\tilde{\Delta}$  heuristically, e.g., by measuring its latency to (4f+1) servers. Should (m,b) be rejected for being too late (see below),  $\theta$  will update b to a more conservative value and try again. Because  $\Delta$  is fixed,  $\theta$  is guaranteed to eventually reach all correct servers in time and get m delivered.

Upon receiving (m, b), correct servers decide whether to accept (m, b), i.e., whether to accept  $\theta$ 's proposal to deliver m with rank b. To do so, servers use Representative Binary Consensus. A correct server  $\pi$  proposes to accept (m, b) (proposes True) if and only (by  $\pi$ 's local clock)  $\pi$  receives (m, b) before b;  $\pi$  delivers m with rank b if and only if (m, b) is accepted. (m, b) might be rejected, e.g., if  $\theta$  is late or crashes while disseminating (m, b) (see Fig. 4b).

The problem of convergence. Total-Order Broadcast has correct servers deliver (1) the same messages (Agreement), (2) in the same order (Total Order). In most implementations, these two conditions are facilitated by a leader that attaches a monotonic counter to each message. This counter enables correct servers to (1) detect missing messages, simply by finding gaps in the enumeration, and (2) achieve a common message order. Bets naturally ensure condition (2), but not (1): unlike *contiguous* counters, bets are *sparse* in nature. Because of this, a server cannot determine to have missed a message from bets alone.

In Flutter, a correct server must (1) deliver all messages for which Representative Binary Consensus decides True, (2) in increasing order of bet. To uphold these guarantees, when delivering a message m with rank b a correct server  $\pi$  must be certain to have already delivered every message predating m (i.e., every message whose bet is earlier than b) for which Representative Binary Consensus could possibly decide True. We call this the *problem of convergence*. Note that, to ensure convergence, it is not sufficient for  $\pi$  to wait for Representative Binary Consensus to decide on all the messages that  $\pi$  already observed predating  $m-\pi$  must be convinced that Representative Binary Consensus would reject any new message m' predating m that  $\pi$  could discover in the future. Failing that,  $\pi$  could later find some m' it should have delivered before m, forcing  $\pi$  to skip m', breaking Agreement, or deliver m' out of order, breaking Total Order.

### 4.2 Achieving Convergence in Flutter

Flutter solves the problem of convergence by having servers update each other on the messages and bets that they *observe*, as well as their *local time*. At a glance: by the Representative Validity of Representative Binary Consensus, if many enough processes announce having reached some time t without ever observing some (m, b < t), (m, b) will be certainly rejected. This guarantee

 $<sup>^6 {\</sup>rm In}$  a practical implementation,  $\epsilon$  would be the smallest unit of time that  $\theta$  can represent.




Fig. 3. Example client messages in Flutter, noted a to p, as seen by a correct server at a given time. Messages are organized on a timeline, appearing at the time of their bet. The Consensus status of each message is represented by the two symbols on top of the message: the server's proposal on top ( $\checkmark$  to deliver the message, X to reject it), Representative Binary Consensus's decision on the bottom ( $\checkmark$  or X to deliver or reject, ? if Representative Binary Consensus is still running). The server already delivered all messages whose decision is boxed. Messages marked by a solid line are candidates, those marked by a dashed line are not.

allows a correct server to converge in finite time on a finite set of candidates, which includes every message predating t that Representative Binary Consensus could accept delivering. Servers deliver, in increasing order of bet, all converged candidates that Representative Binary Consensus decides to accept.

*Observations.* Upon first receiving a message m with bet b from any source (server or client), a correct server relays (m, b) to every other server via an Observe message.

Local time and lock time. Regularly, a correct server  $\pi$  announces its local time to other servers via a Time message. At any point in time, we call  $\pi$ 's **lock time** the highest local time that  $\pi$  witnessed (via Time messages) being reached by at least (4f+1) servers. As all (4f+1) correct servers regularly disseminate their growing local time,  $\pi$ 's lock time is guaranteed to grow indefinitely.

The role of Representative Validity. As discussed in §4.1, a correct server  $\pi$  proposes accepting some (m,b) only if (according to its local clock)  $\pi$  receives (m,b) before time b. This means that, after announcing its local time being t,  $\pi$  will propose rejecting any (m',b'<t) that  $\pi$  did not already receive, propose accepting, and relay. Flutter solves convergence by generalizing this observation to a quorum of servers. Let  $\rho$  be a correct server. If at least (4f+1) servers announce to  $\rho$  that they reached some time t without any of them relaying (m',b'<t), then (m',b') will certainly be rejected. Indeed, at least (3f+1) correct servers reached local time t without ever observing (m',b'), and will certainly propose rejecting it. By the Representative Validity of Representative Binary Consensus, (m',b') will certainly be rejected. Note that the same argument would not apply if Binary Consensus was employed instead of Representative Binary Consensus: with Validity, a single slow-but-correct server might cause (m',b') to be accepted.

Candidates. Putting all of the above together, a correct server  $\pi$  maintains a set of **candidates** containing every (m,b) that  $\pi$  observed before its lock time reached b. By definition of lock time, if some (m',b') is not among  $\pi$ 's candidates, then at least (4f+1) processes announced reaching time b' without ever observing and relaying (m',b')-(m',b') will certainly be rejected. Once  $\pi$ 's lock time reaches some time t, the set of candidates predating t is fixed:  $\pi$  simply waits for Representative Binary Consensus to decide which candidates are accepted, and delivers each message in increasing order of bet.

#### 4.3 A Server's Timeline

Fig. 3 depicts an example timeline of the client-issued messages a correct server  $\pi$  has discovered at a given point of its execution. Each message appears at the time of its bet (and not, e.g., at the time it was first received by  $\pi$ ). Hence, the same message appears at the same location on every correct server's timeline.

The timeline is partitioned by three dividers:  $\pi$ 's local time,  $\pi$ 's lock time, and the bet of the last message that  $\pi$  delivered. Assuming server clocks are well-synchronized,  $\pi$ 's local time should be greater than  $\pi$ 's lock time by approximately one message delay. If every correct server disseminated its local time at time t,  $\pi$  would receive all updates one message delay later, updating its lock time to t as its local time reaches approximately  $(t + \Delta)$ .  $\pi$ 's lock time can overtake its local time if  $\pi$ 's local clock experiences a delay. The following explanations apply regardless of the order between  $\pi$ 's local and lock time.

Upon first receiving a message m with bet b,  $\pi$  marks m as a candidate if and only if b is greater than  $\pi$ 's current lock time. This explains why all messages to the right of  $\pi$ 's lock time are candidates: non-candidates like c and i can only appear to the left of  $\pi$ 's lock time. If a message m is not a candidate,  $\pi$  can trust that Representative Binary Consensus will decide to reject  $m - \pi$  knows that m cannot be delivered. Other correct servers, however, could have marked m as a candidate, and might rely on Representative Binary Consensus to make progress. To ensure liveness,  $\pi$  engages in Representative Binary Consensus for every message it receives, regardless of it being a candidate. Should a new message m appear on  $\pi$ 's timeline:  $\pi$  would propose delivering m if and only if mappeared to the right of  $\pi$ 's local time;  $\pi$  would mark m as a candidate if and only if m appeared to the right of  $\pi$ 's lock time. This explains why  $\pi$  proposed to deliver all messages to the right of its local time, and why all the messages to the right of  $\pi$ 's lock time are marked as candidates. As no new candidates can ever appear to the left of  $\pi$ 's lock time,  $\pi$  can deliver, in increasing order of bet, all messages to the left of its lock time that Representative Binary Consensus decides to deliver (in the example,  $\pi$  already delivered b, d and f). Of course, this means that  $\pi$  has to sequentially wait for each Representative Binary Consensus instance to terminate – e.g.,  $\pi$  cannot yet deliver h, as Representative Binary Consensus might still decide to deliver q. Because Representative Binary Consensus ensures Termination, and because no new candidates can be added to the left of  $\pi$ 's lock time,  $\pi$  is guaranteed to sequentially progress through each candidate, eventually delivering every message that Representative Binary Consensus decides should be delivered, in increasing order of bet.

### 4.4 Algorithm

Flutter implements Total-Order Broadcast using multiple instances *con* of Representative Binary Consensus. Alg. 1 describes Flutter's server side. The client algorithm is simple hence is left to Appx. B.1 due to space constraints.

Variables. A correct server  $\pi$  maintains: an observed set (line 7), containing all (client, message, bet) tuples  $\pi$  received (from clients or servers); a proposed set (line 8), containing all elements of observed for which  $\pi$  submitted its Representative Binary Consensus proposal; a candidates set (line 9), containing all elements of observed that qualify as candidates (see §4.1); a delivered set (line 10), tracking which (client, message) tuples  $\pi$  already delivered (this ensures deduplication should a client, e.g., attempt broadcasting the same message with several different bets); a remote\_times map (line 11), tracking the highest local time each server ever announced reaching; a decisions map (line 12), eventually recording Representative Binary Consensus's decision for each element of observed; a last\_processed tuple (line 13), tracking the last element of candidates that was delivered or rejected (last\_processed sequentially takes the value of every decided candidate, see §4.1).

### **Algorithm 1** Flutter server (see Appx. B.1 for Flutter client)

```
1: Implements:
          TotalOrderBroadcast, instance tob
 2:
 3: Uses:
 4:
          AuthenticatedFifoLinks, instance af
          RepresentativeBinaryConsensus, multiple instances in con
 6: upon event \langle tob.Init \rangle do
 7:
          observed : Set(\Theta \times \mathcal{M} \times \mathbb{T}) = \{\}
 8:
          proposed : Set(\Theta \times \mathcal{M} \times \mathbb{T}) = \{\}
          candidates : Set(\Theta \times \mathcal{M} \times \mathbb{T}) = \{\}
 9:
          delivered : Set(\Theta \times \mathcal{M}) = \{\}
10:
11:
          remote\_times : Map(\Pi \to \mathbb{T}) = \{\pi \to -\infty\}_{\pi \in \Pi}
12:
          decisions : Map((\Theta \times \mathcal{M} \times \mathbb{T}) \to \mathbb{B}) = \{\}
13:
          last\_processed : \Theta \times \mathcal{M} \times \mathbb{T} = (\bot, \bot, -\infty)
14: procedure beat() is
15:
          for all \pi \in \Pi do
               trigger \langle af.Send \mid [Time, local\_time()] \rangle
16:
17: upon event \langle af. Deliver | \sigma, [Time, t] \rangle do
          remote\_times[\sigma] = \max(remote\_times[\sigma], t)
18:
19: procedure lock_time() is
          return max t s.t. |\{\pi \text{ s.t. } remote\_times[\pi] \ge t\}| \ge (4f+1)
20:
21: procedure spot(\theta, m, b) is
22:
          if b > lock time() then
23:
               candidates \leftarrow (\theta, m, b)
          if (\theta, m, b) \notin observed then
24:
               for all \pi \in \Pi do
25:
                    trigger \langle af.Send | [Observe, \theta, m, b]\rangle
26:
27:
               schedule beat() at time b
               observed \leftarrow (\theta, m, b)
28:
29: upon event \langle af. Deliver | \sigma, [Observe, \theta, m, b]\rangle do
30:
          spot(\theta, m, b)
31: upon event \langle af. Deliver | \theta, [Message, m, b] \rangle do
32:
          spot(\theta, m, b)
33:
          if (\theta, m, b) \notin proposed then
34:
               in\_time : \mathbb{B} = (b > local\_time())
35:
               trigger \langle con[(\theta, m, b)].Propose | in\_time \rangle
36:
               proposed \leftarrow (\theta, m, b)
37: upon exists (\theta, m, b) \in (observed \setminus proposed) such that b \leq local\_time() do
          trigger \langle con[(\theta, m, b)].Propose | False \rangle
38:
          proposed \leftarrow (\theta, m, b)
39:
40: upon event \langle con[(\theta, m, b)]. Decide |v\rangle do
41:
          trigger \langle af. Send \mid \theta, [Decision, m, b, v] \rangle
42:
          decisions[(\theta, m, b)] = v
43: upon min (\theta, m, b) \in candidates such that (\theta, m, b) > last\_processed satisfies (\theta, m, b) \in decisions and b \le decisions
     lock time() do
44:
          if decisions[(\theta, m, b)] = True then
45:
               order(\theta, m, b)
46:
          last\_processed = (\theta, m, b)
47: procedure order(\theta, m, b) is
          if (\theta, m) \notin delivered then
48:
49:
               trigger \langle tob. Deliver \mid \theta, m \rangle
50:
               delivered \leftarrow (\theta, m)
```

*Time.* Procedure *beat* (line 14) disseminates  $\pi$ 's local time to all servers using a Time message (lines 15 and 16). Upon delivering a Time message (line 17),  $\pi$  updates the relevant entry in *remote\_times* (line 18, note the use of max to ensure that every value in *remote\_times* is non-decreasing). Procedure *lock\_time* (line 19, see §4.1) returns the highest local time that at least (4f+1) announced reaching, as recorded in *remote\_times* (line 20).

Dissemination. Procedure spot (line 21) handles the discovery and propagation of new client-issued messages. Upon executing  $spot(\theta, m, b)$ : if b is greater than  $\pi$ 's lock time,  $\pi$  marks  $(\theta, m, b)$  as a candidate (lines 22 and 23, see §4.1); if  $\pi$  never observed  $(\theta, m, b)$  before (i.e.,  $\pi$  never executed  $spot(\theta, m, b)$  before, lines 24 and 28),  $\pi$  relays  $(\theta, m, b)$  to every server by means of an Observe message (lines 25 and 26), then schedules beat() for execution at time b (line 27) –  $\pi$  does so to ensure that every correct server's lock time eventually reaches b, enabling the delivery of m should Representative Binary Consensus decide that m should be delivered (see §4.1). Upon receiving an Observe message (line 29)  $\pi$  invokes spot (line 30), thus ensuring that the message is propagated.

*Proposals.* Upon receiving a Message message conveying a message m with bet b from client  $\theta$  (line 31):  $\pi$  invokes spot to record and propagate  $(\theta, m, b)$  (line 32); if  $\pi$  never proposed delivering or rejecting m (lines 33 and 36),  $\pi$  proposes delivering m (line 35) if and only if b is in the future according to  $\pi$ 's local time (line 34, see §4.1). If  $\pi$ 's local time reaches the bet b of some message m that  $\pi$  never proposed delivering or rejecting (lines 37 and 39),  $\pi$  proposes rejecting m (line 38). This condition triggers for  $(\theta, m, b)$  only if  $\pi$  discovered  $(\theta, m, b)$  from another server's Observe message (lines 29, 32, 21, 24, then 28), but  $\pi$  never received m directly from  $\theta$  (lines 31, 35, then 36). In that case,  $\pi$  could not authenticate  $\theta$  having issued m, and thus could not propose delivering m (lest m be spuriously attributed to  $\theta$  by a malicious server). To ensure liveness, however, every correct server must submit a proposal to every Consensus instance. As soon as  $\pi$ 's local time reaches b,  $\pi$  would propose to reject m (lines 34 and 35) even if  $\pi$  received m from  $\theta$  (line 31): as such,  $\pi$  can safely propose rejecting m.

Decision and delivery. Upon deciding whether or not to deliver a message m issued by client  $\theta$  with bet b (line 40),  $\pi$  relays the decision to  $\theta$  by means of a Decision message (line 41), then records the decision (line 42).  $\pi$  processes (i.e., delivers or rejects) each candidate in strict ascending order;  $\pi$  is ready to process the next candidate ( $\theta$ , m, b) as soon as a decision is recorded for ( $\theta$ , m, b) and  $\pi$ 's lock time reaches b (line 43, see §4.1). Upon processing ( $\theta$ , m, b),  $\pi$  invokes procedure order (line 45) if and only if  $\pi$  decided that m should be delivered (line 44, see §4.1). Procedure order (line 47) delivers ( $\theta$ , m) (line 49) if ( $\theta$ , m) was not delivered before (lines 48 and 50).

Example: good case, bad case. The example in Fig. 4 shows two ways a broadcast could unfold. Scenario (a) happens under good-case conditions (see §2.3): the message delay between processes is bounded by a known constant  $\Delta$ , clocks are perfectly synchronized, and computation is instantaneous. At time 0, a client  $\theta$  broadcasts some message m with bet  $b = (\Delta + \epsilon)$ , where  $\epsilon > 0$  is an arbitrarily small constant (remember:  $\theta$  knows  $\Delta$ ). At time  $\Delta$ , every correct server receives and proposes delivering m. At time  $\Delta$ , every correct server announces its local time. Assuming Blink (§3) is used to implement Representative Binary Consensus, at time  $\Delta$  every correct server decides to deliver  $\Delta$ 0, sending the decision back to  $\Delta$ 1. At time  $\Delta$ 2, the lock time of every correct server reaches ( $\Delta$ 1 +  $\epsilon$ 2) and  $\Delta$ 2 is delivered. Scenario (b) captures a bad scenario instead: client  $\Delta$ 3 overestimates its bet  $\Delta$ 5. At the crashes while disseminating  $\Delta$ 6, then crashes while disseminating  $\Delta$ 7. At time  $\Delta$ 8, every correct server receives  $\Delta$ 8. Those correct servers that did not receive  $\Delta$ 8 directly from  $\Delta$ 9, however, cannot propose to deliver  $\Delta$ 9. At time  $\Delta$ 9, every correct server that did not submit a proposal for  $\Delta$ 9 proposes to reject  $\Delta$ 9. At the same time, every correct server announces its local time. Because proposals are split, Representative




Fig. 4. Examples of (a) good case and (b) bad case executions of Flutter. Broadcast times are indicated with a question mark; delivery times with an exclamation mark; a correct server's engagement in Representative Binary Consensus is marked by a striped bar; proposals and decisions are indicated at the beginning and end of each bar; ✓ represents True; X represents False.

Binary Consensus takes longer than one message delay to decide. Eventually, every correct server decides to reject m, sending the decision back to  $\theta$ .

#### 4.5 Correctness Proof Sketches

This section includes proof sketches of the correctness of each of Flutter's property. Proofs to the fullest extent of formal detail are provided in Apps. B.3 to B.5.

No Duplication. The delivered set guards the deliveries, it is extended upon delivery.

Integrity. A correct server proposes to deliver a message m from a client  $\theta$  only upon receiving m directly from  $\theta$ . As such, unless  $\theta$  issued m, no correct server ever proposes delivering m and, by Representative Binary Consensus's Representative Validity, m is rejected.

Agreement and Total Order. Upon receiving a message m issued by client  $\theta$  with bet b, a correct server  $\pi$  relays  $(\theta, m, b)$  to every other server. As a result, every correct server eventually observes  $(\theta, m, b)$  (i.e., adds  $(\theta, m, b)$  to observed). Moreover, if  $\pi$  does not submit any proposal to  $con[(\theta, m, b)]$  by time b,  $\pi$  eventually proposes False to  $con[(\theta, m, b)]$ . Hence, every correct server eventually submits a proposal to  $con[(\theta, m, b)]$ : by the Termination and Agreement of Representative Binary Consensus, every correct server eventually records the same decision from  $con[(\theta, m, b)]$ . Moreover, if  $\pi$  does not mark  $(\theta, m, b)$  as a candidate (i.e.,  $\pi$  does not add  $(\theta, m, b)$  to candidates), then  $con[(\theta, m, b)]$  decides False. Indeed, if  $\pi$  does not mark  $(\theta, m, b)$  as a candidate then, upon observing  $(\theta, m, b)$ ,  $\pi$ 's lock time is greater or equal to b. Because links are FIFO, at least (4f+1) servers, of which at least (3f+1) are correct, announced that their local time reached b before relaying  $(\theta, m, b)$  to  $\pi$ . A correct server  $\rho$  proposes False to  $con[(\theta, m, b)]$  unless  $\rho$  observes (and relays)  $(\theta, m, b)$  before b. This proves that at least (3f+1) correct servers propose False to  $con[(\theta, m, b)]$  and, by the Representative Validity of Representative Binary Consensus,  $con[(\theta, m, b)]$  decides False.

Every time a correct server  $\sigma$  observes a new message,  $\sigma$  schedules beat() for execution at some time in the future. This means that, unless a finite number of messages is broadcast throughout the entire execution of the protocol,  $\sigma$  executes beat() an infinite number of times. Upon executing beat(),  $\sigma$  disseminates its local time to every server. As a result, for every correct server  $\sigma$ , a correct server  $\pi$  indefinitely increases the value of  $remote\_times[\pi]$ . Noting that (4f+1) servers are correct, this means that  $\pi$ 's lock time grows indefinitely. As a consequence of this, for any time t,  $\pi$  marks as candidates only a finite number of messages preceding t. This is obvious if a finite number

of messages is broadcast throughout the entire execution of the protocol. If infinite messages are broadcast,  $\pi$  accepts new candidates preceding t only until  $\pi$ 's lock time grows past t – before that happens,  $\pi$  can only collect a finite number of such candidates. Because  $\pi$ 's candidates preceding any t are always finite,  $\pi$ 's candidates can be enumerated by a unique, strictly increasing sequence.

A correct server  $\pi$  processes candidates in a strictly increasing fashion.  $\pi$  processes the next candidate  $(\theta, m, b)$  once  $con[(\theta, m, b)]$  decides, and  $\pi$ 's lock time reaches b. This means that, once  $\pi$  has processed  $(\theta, m, b)$ ,  $\pi$  will not mark any  $(\theta', m', b') < (\theta, m, b)$  as candidate. In other words,  $\pi$  is guaranteed to never skip a candidate: if  $\pi$  was ever to mark  $(\theta', m', b')$  as candidate,  $\pi$  would have done so before processing  $(\theta, m, b)$ . Finally, because  $\pi$ 's candidates can be enumerated,  $\pi$  is guaranteed to eventually process every message it will ever mark as candidate, in strictly increasing order. Upon processing  $(\theta, m, b)$ ,  $\pi$  invokes  $order(\theta, m, b)$  if and only if  $con[(\theta, m, b)]$  decided True. Because every  $(\theta', m', b')$  for which Representative Binary Consensus decides True is eventually marked by  $\pi$  as candidate,  $\pi$  invokes order on a strictly increasing sequence of messages containing all and only those messages for which Representative Binary Consensus decides True. Because such sequence is unique, every correct server issues the exact same sequence of calls to order. Finally, order simply functions as a deterministic state machine (its state being the delivered variable) to deterministically deduplicate and deliver messages. This proves that every correct server delivers the same sequence of messages.

Validity. The implementation of a Flutter client is presented in Alg. 3. The logic of a Flutter client is simple: a correct client  $\theta$  broadcasts a message m by first setting a bet that, according to  $\theta$ 's clock, is  $(\tilde{\Delta} + \epsilon)$  in the future, where  $\tilde{\Delta}$  is  $\theta$ 's best estimate for  $\Delta$  (under partial synchrony,  $\pi$  cannot reliably estimate  $\Delta$ , hence  $\tilde{\Delta}$  is an arbitrary constant) and  $\epsilon$  is an arbitrarily small constant. If m is rejected,  $\theta$  retries with a bet  $(2\tilde{\Delta} + \epsilon)$  in the future, then  $(4\tilde{\Delta} + \epsilon)$ , and so on. As both  $\Delta$  and  $\Psi$  are finite,  $\theta$  is guaranteed to eventually select a bet b such that (m,b) reaches each correct server before its local time reaches b. When this happens, every correct server proposes delivering m and, by the Representative Validity of Representative Binary Consensus, m is delivered.

#### 4.6 Good-case and Bad-case Latency Sketches

Good-case latency. We prove to the fullest extent of formal detail in Appx. B.6 (Theorem 10) that, in the good case, a correct client  $\theta$  broadcasting its message m at time t gets m delivered by every correct server by time  $(t+2\Delta+\epsilon)$ . The result is fairly intuitive when tracking an individual message. In the good case (see §2.3), clocks are perfectly synchronized ( $\Psi=0$ ) and  $\Delta$  is known. This means that  $\theta$ 's estimate for  $\Delta$  is accurate:  $\tilde{\Delta}=\Delta$ . At time t,  $\theta$  broadcasts m with bet  $b=(t+\Delta+\epsilon)$ . By time  $(t+\Delta)$ , every correct server receives and proposes delivering m. At time  $(t+\Delta+\epsilon)$ , every correct server announces its time being exactly  $(t+\Delta+\epsilon)$ . Because every correct server proposes the same value, and assuming Representative Binary Consensus is implemented by Blink, every correct server fast-path decides to deliver m by time  $(t+2\Delta)$ . By time  $(t+2\Delta+\epsilon)$ , every correct server's lock time reaches  $b=(t+\Delta+\epsilon)$ , and every correct server delivers m. Additionally, we prove that Flutter's good-case latency is quasi-optimal in Appx. C

Bad-case latency. Several factors contribute to increasing Flutter's latency in the bad case. First, the delivery of m is delayed if  $\theta$  overestimates  $\Delta$ . This is because no correct server can deliver m before its lock time reaches b. Second, if  $\theta$  disseminates m only to a fraction of correct servers before b, correct servers will disagree on whether or not m should be delivered. This forces Representative Binary Consensus out of Blink's fast path, resulting in longer decision times. Finally, some message m' with bet b' < b very close to b might force Representative Binary Consensus out of Blink's

fast path. Because messages are delivered in order of bet, correct servers might still be deciding whether or not to deliver m', if it took Blink's slow path, when they decide to deliver m.

However, Flutter's leaderless nature sidesteps the problem of finding a correct leader. A leader-based algorithm [2, 18, 56, 72, 97] might sequentially force the protocol through (f + 1) leaders before a message is delivered [38]. Flutter's worst case, instead, only involves running slow-path Representative Binary Consensus once.

### 4.7 Complexity

A broadcast attempt in Flutter involves: a client-to-servers Message message (O(l)) bits per message, where l is the length of the message being broadcast); a servers-to-servers Observe message (O(l)) bits per message); a servers-to-servers Time message (O(1)) bits per message); an execution of Representative Binary Consensus (whose complexity is lower bound by  $O(n^2)$  [37]); and a servers-to-client Decision message (O(l)) bits per message). Assuming Flutter depends on an optimal implementation of Representative Binary Consensus, this results in an  $O(ln^2)$  complexity per broadcast attempt, which could be dominated by l if the message being broadcast is large enough. Several mitigations to this problem exist in literature, usually involving encoding the message in multiple, shorter codewords which correct servers decode after dissemination [24, 34, 70, 95]. Using one such solution, the complexity of Flutter would be reduced to  $O(nl + n^2 \log(n))$ . Optimizing Flutter's bit complexity, however, is beyond the scope of this paper.

# 5 RELATED WORK

Classic Byzantine agreement protocols employ leaders and require multiple message delays to safely terminate. PBFT [18], BFT-SMaRt [11] and ICC [17] need three rounds of one message delay each to solve Consensus in the good case (see §2.3). HotStuff [97], SQuad [21] and Lewis-Pye [65] reduce worst-case message complexity [37] and in doing so increase the latency of the prior state-of-the-art approaches. These protocols have rounds composed of two message delays each even in the good case, which increases the latency experienced by clients and, ultimately, users. In comparison, Flutter and Blink have an optimistic latency of one and two message delays for decision and delivery, respectively.

One-message-delay Consensus. Multiple protocols have been proposed to solve  $\operatorname{crash}$  fault-tolerant Consensus in one message delay and/or Total-Order Broadcast in two message delays in the good case [12, 35, 75, 79]. Friedman, Mostefaoui and Raynal [42] have proposed the first one-message-delay Byzantine Consensus in the good case, it requires a resiliency of (5f+1) and the existence of oracles. Such oracles may be implemented using a random common coin abstraction which in practice requires cryptographic tools to construct. In comparison, Flutter and Blink are deterministic and free of costly cryptographic primitives.

Bosco [86] resembles Blink: it tolerates Byzantine failures, with a (7f+1) resiliency, enables one-message-delay latency in the good case, is simple and deterministic. Compared to Blink, servers in Bosco operate in the stricter model of *communication steps* where each server can only "1) send messages; 2) receive messages; and 3) do local computations, in that order" [86]. In comparison, servers in Blink can perform these operations in any order. Bosco's fast path can be used only if the first (4f+1) values received by a server are the same; a single faulty server can force the slow path for all servers. Blink's fast path can be used as long as all correct servers propose the same value, even if up to f faulty servers propose other values. Appx. A.2 compares Blink and Bosco in detail.

Two-message-delay Consensus. Additional protocols have been proposed to solve Byzantine Consensus in two message delays, and Byzantine Total-Order Broadcast in three message delays, using a fast path in the good case. Kursawe [55] first proposed a Consensus algorithm assuming an

even "stronger" good case whereby all processes have to be correct to benefit from the fast path. A single process failure results in all processes having to use the slow path. FaB Paxos [72] was the first protocol designed with a Byzantine fault-tolerant fast path in two message delays assuming a (5f+1) resiliency. More than a decade later, two concurrent publications [2, 56] proved that fast Byzantine Consensus could actually be solved assuming an improved resiliency of (5f-1). This seemingly small difference is relevant for small systems since it means that the fast path is optimally resilient: 3f+1=5f-1 when f=1. This approach has since been further improved by reducing the size of quorums in some of its steps [47], leading to better latencies in practice, without affecting the number of message delays. Sync HotStuff [1] reduces the three-message-delay version of HotStuff [97] down to two message delays assuming synchrony, instead of partial synchrony, and can operate with an improved (2f+1) resiliency. VBFT [49] proposes two-message-delay latency with an optimal resiliency threshold of (3f+1) by relaxing the safety of Consensus which may lead to temporary revocations of decisions.

Banyan [94] is the first Byzantine Total-Order Broadcast with a two-message-delay fast path when the leader broadcasts a value, hence with a three-message-delay fast path when any process broadcasts a value. Banyan builds upon ICC [17] and defines a parameterizable resiliency threshold of 3f + 2p - 1 = n where f is the maximum number of Byzantine faults and p is freely set such that  $1 \le p \le f$ . Banyan rapidly delivers a value if (n - p) processes are correct and respond fast enough. SBFT [46] needs four message delays in the good case for Byzantine Total-Order Broadcast but could likely only need three message delays by not using collectors to aggregate signatures, at the cost of increased computation for processes hence lower Total-Order Broadcast throughput.

Zyzzyva, Zyzzyva5 [54] and AZyzzyva [8] are Byzantine replication protocols that optimistically achieve broadcast-to-delivery latencies of two message delays thanks to speculative execution. These protocols execute client requests before agreement is reached, thus save one message delay compared to other approaches. However, the effectiveness of speculative execution depends on the workload, unlike Flutter. Speculative execution may also lead to diverging state across servers which must be accounted for via state checkpointing and state restoration mechanisms. Flutter's algorithm is simpler by design. Speculative execution is an orthogonal, and possibly complementary, approach to that of Flutter.

To the best of our knowledge, Flutter is the first Byzantine Total-Order Broadcast with a non-speculative fast path offering two-message-delay latencies.

#### 6 FUTURE WORK

We note several avenues for future work on Flutter and Blink: (1) Flutter requires Representative Binary Consensus – is there an algorithm that offers the same advantages as Flutter but only requires Binary Consensus? (2) Should such an algorithm exist, would it improve the resiliency threshold to (5f-1) or even the optimal (3f+1)? (3) If not, could a trusted (hardware or software) computing base [10] be leveraged to achieve (3f+1) resiliency, as done in other Byzantine protocols [4, 20, 50, 63, 68, 93]? (4) How well do Flutter and Blink perform in practice, particularly when using hardware acceleration [48, 53, 68, 85], considering that the typical bottlenecks of leaders and signatures have been removed?

#### **ACKNOWLEDGMENTS**

This work has been funded in part by BRIDGE (#40B1-0\_222426).

#### REFERENCES

- [1] Ittai Abraham, Dahlia Malkhi, Kartik Nayak, Ling Ren, and Maofan Yin. 2020. Sync HotStuff: Simple and Practical Synchronous State Machine Replication. In *IEEE Symposium on Security and Privacy (SP)*. https://doi.org/10.1109/SP40000.2020.00044
- [2] Ittai Abraham, Kartik Nayak, Ling Ren, and Zhuolun Xiang. 2021. Good-case Latency of Byzantine Broadcast: a Complete Categorization. In ACM Symposium on Principles of Distributed Computing (PODC). https://doi.org/10.1145/ 3465084.3467899
- [3] Ittai Abraham and Gilad Stern. 2021. Information Theoretic HotStuff. In 24th International Conference on Principles of Distributed Systems (OPODIS). https://doi.org/10.4230/LIPIcs.OPODIS.2020.11
- [4] Marcos K. Aguilera, Naama Ben-David, Rachid Guerraoui, Antoine Murat, Athanasios Xygkis, and Igor Zablotchi. 2023. uBFT: Microsecond-Scale BFT using Disaggregated Memory. In ACM International Conference on Architectural Support for Programming Languages and Operating Systems (ASPLOS). https://doi.org/10.1145/3575693.3575732
- [5] Marcos K. Aguilera, Carole Delporte-Gallet, Hugues Fauconnier, and Sam Toueg. 2001. Stable Leader Election. In *Distributed Computing (DC)*. https://doi.org/10.1007/3-540-45414-4 8
- [6] Karolos Antoniadis, Julien Benhaim, Antoine Desjardins, Elias Poroma, Vincent Gramoli, Rachid Guerraoui, Gauthier Voron, and Igor Zablotchi. 2023. Leaderless consensus. Journal of Parallel and Distributed Computing (JPDC) (2023). https://doi.org/10.1016/j.jpdc.2023.01.009
- [7] Balaji Arun, Sebastiano Peluso, Roberto Palmieri, Giuliano Losa, and Binoy Ravindran. 2017. Speeding up Consensus by Chasing Fast Decisions. In IEEE/IFIP International Conference on Dependable Systems and Networks (DSN). https://doi.org/10.1109/DSN.2017.35
- [8] Pierre-Louis Aublin, Rachid Guerraoui, Nikola Knežević, Vivien Quéma, and Marko Vukolić. 2015. The Next 700 BFT Protocols. ACM Transactions on Computer Systems (TOCS) (2015). https://doi.org/10.1145/2658994
- [9] Zeta Avarikioti, Lioba Heimbach, Roland Schmid, Laurent Vanbever, Roger Wattenhofer, and Patrick Wintermeyer. 2023. FnF-BFT: A BFT protocol with provable performance under attack. In *International Colloquium on Structural Information and Communication Complexity (SIROCCO)*. https://doi.org/10.1007/978-3-031-32733-9\_9
- [10] Naama Ben-David and Kartik Nayak. 2021. Brief Announcement: Classifying Trusted Hardware via Unidirectional Communication. In ACM Symposium on Principles of Distributed Computing (PODC). https://doi.org/10.1145/3465084. 3467948
- [11] Alysson Bessani, Joao Sousa, and Eduardo E.P. Alchieri. 2014. State Machine Replication for the Masses with BFT-SMaRt. In IEEE/IFIP International Conference on Dependable Systems and Networks (DSN). https://doi.org/10.1109/DSN.2014.43
- [12] Francisco Brasileiro, Fabíola Greve, Achour Mostefaoui, and Michel Raynal. 2001. Consensus in One Communication Step. In Parallel Computing Technologies (PaCT). https://doi.org/10.1007/3-540-44743-1\_4
- [13] Christian Cachin, Rachid Guerraoui, and Luís Rodrigues. 2011. Introduction to Reliable and Secure Distributed Programming. Springer Science. https://doi.org/10.1007/978-3-642-15260-3
- [14] Christian Cachin, Klaus Kursawe, and Victor Shoup. 2005. Random Oracles in Constantinople: Practical Asynchronous Byzantine Agreement Using Cryptography. Journal of Cryptology (JCrypt) (2005). https://doi.org/10.1007/s00145-005-0318-0
- [15] Christian Cachin and Marko Vukolic. 2017. Blockchain Consensus Protocols in the Wild (Keynote Talk). In International Symposium on Distributed Computing (DISC). https://doi.org/10.4230/LIPIcs.DISC.2017.1
- [16] Martina Camaioni, Rachid Guerraoui, Matteo Monti, Pierre-Louis Roman, Manuel Vidigueira, and Gauthier Voron. 2024. Chop Chop: Byzantine Atomic Broadcast to the Network Limit. In 18th USENIX Symposium on Operating Systems Design and Implementation (OSDI). https://www.usenix.org/conference/osdi24/presentation/camaioni
- [17] Jan Camenisch, Manu Drijvers, Timo Hanke, Yvonne-Anne Pignolet, Victor Shoup, and Dominic Williams. 2022. Internet Computer Consensus. In ACM Symposium on Principles of Distributed Computing (PODC). https://doi.org/10. 1145/3519270.3538430
- [18] Miguel Castro and Barbara Liskov. 2002. Practical Byzantine Fault Tolerance and Proactive Recovery. ACM Transactions on Computer Systems (TOCS) (2002). https://doi.org/10.1145/571637.571640
- [19] Tushar Deepak Chandra and Sam Toueg. 1996. Unreliable Failure Detectors for Reliable Distributed Systems. *Journal of the ACM (JACM)* (1996). https://doi.org/10.1145/226643.226647
- [20] Byung-Gon Chun, Petros Maniatis, Scott Shenker, and John Kubiatowicz. 2007. Attested Append-Only Memory: Making Adversaries Stick to their Word. In ACM SIGOPS Symposium on Operating Systems Principles (SOSP). https://doi.org/10.1145/1294261.1294280
- [21] Pierre Civit, Muhammad Ayaz Dzulfikar, Seth Gilbert, Vincent Gramoli, Rachid Guerraoui, Jovan Komatovic, and Manuel Vidigueira. 2022. Byzantine Consensus Is  $\Theta(n^2)$ : The Dolev-Reischuk Bound Is Tight Even in Partial Synchrony!. In *International Symposium on Distributed Computing (DISC)*. https://doi.org/10.4230/LIPIcs.DISC.2022.14
- [22] Pierre Civit, Seth Gilbert, and Vincent Gramoli. 2021. Polygraph: Accountable Byzantine Agreement. In *IEEE International Conference on Distributed Computing Systems (ICDCS)*. https://doi.org/10.1109/ICDCS51616.2021.00046

- [23] Pierre Civit, Seth Gilbert, Vincent Gramoli, Rachid Guerraoui, and Jovan Komatovic. 2022. As easy as ABC: Optimal (A)ccountable (B)yzantine (C)onsensus is easy!. In IEEE International Parallel and Distributed Processing Symposium (IPDPS). https://doi.org/10.1109/IPDPS53621.2022.00061
- [24] Pierre Civit, Seth Gilbert, Rachid Guerraoui, Jovan Komatovic, Matteo Monti, and Manuel Vidigueira. 2023. Every Bit Counts in Consensus. In *International Symposium on Distributed Computing (DISC)*. https://doi.org/10.4230/LIPIcs. DISC.2023.13
- [25] Pierre Civit, Seth Gilbert, Rachid Guerraoui, Jovan Komatovic, and Manuel Vidigueira. 2023. On the Validity of Consensus. In ACM Symposium on Principles of Distributed Computing (PODC). https://doi.org/10.1145/3583668.3594567
- [26] Allen Clement, Edmund Wong, Lorenzo Alvisi, Mike Dahlin, and Mirco Marchetti. 2009. Making Byzantine Fault Tolerant Systems Tolerate Byzantine Faults. In USENIX Symposium on Networked Systems Design and Implementation (NSDI). https://www.usenix.org/conference/nsdi-09/making-byzantine-fault-tolerant-systems-tolerate-byzantine-faults
- [27] Shir Cohen, Rati Gelashvili, Lefteris Kokoris-Kogias, Zekun Li, Dahlia Malkhi, Alberto Sonnino, and Alexander Spiegelman. 2022. Be Aware of Your Leaders. In Financial Cryptography and Data Security (FC). https://doi.org/10. 1007/978-3-031-18283-9\_13
- [28] Tyler Crain. 2020. Two More Algorithms for Randomized Signature-Free Asynchronous Binary Byzantine Consensus with t < n/3 and  $O(n^2)$  Messages and O(1) Round Expected Termination. arXiv:2002.08765 [cs.DC] https://arxiv.org/abs/2002.08765
- [29] Tyler Crain, Vincent Gramoli, Mikel Larrea, and Michel Raynal. 2018. DBFT: Efficient Leaderless Byzantine Consensus and its Application to Blockchains. In IEEE International Symposium on Network Computing and Applications (NCA). https://doi.org/10.1109/NCA.2018.8548057
- [30] Tyler Crain, Christopher Natoli, and Vincent Gramoli. 2021. Red Belly: A Secure, Fair and Scalable Open Blockchain. In IEEE Symposium on Security and Privacy (SP). https://doi.org/10.1109/SP40001.2021.00087
- [31] Flaviu Cristian, Houtan Aghili, Ray Strong, and Danny Dolev. 1995. Atomic Broadcast: From Simple Message Diffusion to Byzantine Agreement. *Information and Computation (IC)* (1995). https://doi.org/10.1006/inco.1995.1060
- [32] Philip Daian, Steven Goldfeder, Tyler Kell, Yunqi Li, Xueyuan Zhao, Iddo Bentov, Lorenz Breidenbach, and Ari Juels. 2020. Flash Boys 2.0: Frontrunning in Decentralized Exchanges, Miner Extractable Value, and Consensus Instability. In IEEE Symposium on Security and Privacy (SP). https://doi.org/10.1109/SP40000.2020.00040
- [33] George Danezis, Lefteris Kokoris-Kogias, Alberto Sonnino, and Alexander Spiegelman. 2022. Narwhal and Tusk: A DAG-Based Mempool and Efficient BFT Consensus. In Proceedings of the Seventeenth European Conference on Computer Systems (EuroSys). https://doi.org/10.1145/3492321.3519594
- [34] Sourav Das, Zhuolun Xiang, and Ling Ren. 2021. Asynchronous Data Dissemination and its Applications. In ACM SIGSAC Conference on Computer and Communications Security (CCS). https://doi.org/10.1145/3460120.3484808
- [35] Dan Dobre and Neeraj Suri. 2006. One-step Consensus with Zero-Degradation. In *International Conference on Dependable Systems and Networks (DSN)*. https://doi.org/10.1109/DSN.2006.55
- [36] Danny Dolev, Cynthia Dwork, and Larry Stockmeyer. 1987. On the Minimal Synchronism Needed for Distributed Consensus. *Journal of the ACM (JACM)* (1987). https://doi.org/10.1145/7531.7533
- [37] Danny Dolev and Rüdiger Reischuk. 1985. Bounds on Information Exchange for Byzantine Agreement. *Journal of the ACM (JACM)* (1985). https://doi.org/10.1145/2455.214112
- [38] Danny Dolev and H. Raymond Strong. 1983. Authenticated Algorithms for Byzantine Agreement. SIAM J. Comput. (1983). https://doi.org/10.1137/0212045
- [39] Jiaqing Du, Daniele Sciascia, Sameh Elnikety, Willy Zwaenepoel, and Fernando Pedone. 2014. Clock-RSM: Low-Latency Inter-datacenter State Machine Replication Using Loosely Synchronized Physical Clocks. In IEEE/IFIP International Conference on Dependable Systems and Networks (DSN). https://doi.org/10.1109/DSN.2014.42
- [40] Cynthia Dwork, Nancy A. Lynch, and Larry J. Stockmeyer. 1988. Consensus in the presence of partial synchrony. *Journal of the ACM (JACM)* (1988). https://doi.org/10.1145/42282.42283
- [41] Vitor Enes, Carlos Baquero, Alexey Gotsman, and Pierre Sutra. 2021. Efficient Replication via Timestamp Stability. In European Conference on Computer Systems (EuroSys). https://doi.org/10.1145/3447786.3456236
- [42] Roy Friedman, Achour Mostefaoui, and Michel Raynal. 2005. Simple and Efficient Oracle-Based Consensus Protocols for Asynchronous Byzantine Systems. IEEE Transactions on Dependable and Secure Computing (TDSC) (2005). https://doi.org/10.1109/TDSC.2005.13
- [43] Rati Gelashvili, Lefteris Kokoris-Kogias, Alberto Sonnino, Alexander Spiegelman, and Zhuolun Xiang. 2022. Jolteon and Ditto: Network-Adaptive Efficient Consensus with Asynchronous Fallback. In Financial Cryptography and Data Security (FC). https://doi.org/10.1007/978-3-031-18283-9\_14
- [44] Yossi Gilad, Rotem Hemo, Silvio Micali, Georgios Vlachos, and Nickolai Zeldovich. 2017. Algorand: Scaling Byzantine Agreements for Cryptocurrencies. In ACM Symposium on Operating Systems Principles (SOSP). https://doi.org/10. 1145/3132747.3132757

- [45] Giacomo Giuliari, Alberto Sonnino, Marc Frei, Fabio Streun, Lefteris Kokoris-Kogias, and Adrian Perrig. 2024. An Empirical Study of Consensus Protocols' DoS Resilience. In Proceedings of the 19th ACM Asia Conference on Computer and Communications Security (ASIA CCS). https://doi.org/10.1145/3634737.3656997
- [46] Guy Golan Gueta, Ittai Abraham, Shelly Grossman, Dahlia Malkhi, Benny Pinkas, Michael Reiter, Dragos-Adrian Seredinschi, Orr Tamir, and Alin Tomescu. 2019. SBFT: A Scalable and Decentralized Trust Infrastructure. In IEEE/IFIP International Conference on Dependable Systems and Networks (DSN). https://doi.org/10.1109/DSN.2019.00063
- [47] Kexin Hu, Zhenfeng Zhang, Kaiwen Guo, Weiyu Jiang, Xiaoman Li, and Jiang Han. 2023. An optimisation for a two-round good-case latency protocol. *IET Information Security* (2023). https://doi.org/10.1049/ise2.12123
- [48] Zsolt István, David Sidler, Gustavo Alonso, and Marko Vukolic. 2016. Consensus in a Box: Inexpensive Coordination in Hardware. In *USENIX Symposium on Networked Systems Design and Implementation (NSDI)*. https://www.usenix.org/conference/nsdi16/technical-sessions/presentation/istvan
- [49] Mohammad M. Jalalzai, Chen Feng, and Victoria Lemieux. 2024. VBFT: Veloce Byzantine Fault Tolerant Consensus for Blockchains. arXiv:2310.09663 [cs.DC] https://arxiv.org/abs/2310.09663
- [50] Rüdiger Kapitza, Johannes Behl, Christian Cachin, Tobias Distler, Simon Kuhnle, Seyed Vahid Mohammadi, Wolfgang Schröder-Preikschat, and Klaus Stengel. 2012. CheapBFT: Resource-Efficient Byzantine Fault Tolerance. In ACM European Conference on Computer Systems (EuroSys). https://doi.org/10.1145/2168836.2168866
- [51] Idit Keidar and Sergio Rajsbaum. 2001. On the Cost of Fault-Tolerant Consensus When There Are No Faults A Tutorial. Technical Report MIT-LCS-TR-821.
- [52] Mahimna Kelkar, Fan Zhang, Steven Goldfeder, and Ari Juels. 2020. Order-Fairness for Byzantine Consensus. In Advances in Cryptology – CRYPTO. https://doi.org/10.1007/978-3-030-56877-1\_16
- [53] Marios Kogias and Edouard Bugnion. 2020. HovercRaft: Achieving Scalability and Fault-Tolerance for Microsecond-Scale Datacenter Services. In European Conference on Computer Systems (EuroSys). https://doi.org/10.1145/3342195. 3387545
- [54] Ramakrishna Kotla, Lorenzo Alvisi, Mike Dahlin, Allen Clement, and Edmund Wong. 2007. Zyzzyva: Speculative Byzantine Fault Tolerance. In ACM SIGOPS Symposium on Operating Systems Principles (SOSP). https://doi.org/10. 1145/1294261.1294267
- [55] Klaus Kursawe. 2002. Optimistic Byzantine agreement. In IEEE Symposium on Reliable Distributed Systems (SRDS). https://doi.org/10.1109/RELDIS.2002.1180196
- [56] Petr Kuznetsov, Andrei Tonkikh, and Yan X Zhang. 2021. Revisiting Optimal Resilience of Fast Byzantine Consensus. In ACM Symposium on Principles of Distributed Computing (PODC). https://doi.org/10.1145/3465084.3467924
- [57] Aptos Labs. 2022. The Aptos Blockchain: Safe, Scalable, and Upgradeable Web3 Infrastructure. https://github.com/aptos-labs/aptos-core/blob/main/developer-docs-site/static/papers/whitepaper.pdf.
- [58] Leslie Lamport. 1978. Time, Clocks, and the Ordering of Events in a Distributed System. Communications of the ACM (CACM) 21, 7 (1978). https://doi.org/10.1145/359545.359563
- [59] Leslie Lamport. 2002. Specifying Systems: The TLA+ Language and Tools for Hardware and Software Engineers. Addison-Wesley.
- [60] Leslie Lamport. 2006. Fast Paxos. Distributed Computing (DC) (2006). https://doi.org/10.1007/s00446-006-0005-x
- [61] Leslie Lamport, Robert Shostak, and Marshall Pease. 1982. The Byzantine Generals Problem. ACM Transactions on Programming Languages and Systems (TOPLAS) 4, 3 (1982). https://doi.org/10.1145/357172.357176
- [62] Ki Suh Lee, Han Wang, Vishal Shrivastav, and Hakim Weatherspoon. 2016. Globally Synchronized Time via Datacenter Networks. In ACM SIGCOMM Conference (SIGCOMM). https://doi.org/10.1145/2934872.2934885
- [63] Dave Levin, John R. Douceur, Jacob R. Lorch, and Thomas Moscibroda. 2009. TrInc: Small Trusted Hardware for Large Distributed Systems. In USENIX Symposium on Networked Systems Design and Implementation (NSDI).
- [64] W. Lewandowski, J. Azoubib, and W.J. Klepczynski. 1999. GPS: Primary tool for time transfer. Proc. IEEE (1999). https://doi.org/10.1109/5.736348
- [65] Andrew Lewis-Pye. 2022. Quadratic worst-case message complexity for State Machine Replication in the partial synchrony model. arXiv:2201.01107 [cs.DC] https://arxiv.org/abs/2201.01107
- [66] Yuliang Li, Gautam Kumar, Hema Hariharan, Hassan Wassel, Peter Hochschild, Dave Platt, Simon Sabato, Minlan Yu, Nandita Dukkipati, Prashant Chandra, and Amin Vahdat. 2020. Sundial: Fault-tolerant Clock Synchronization for Datacenters. In USENIX Symposium on Operating Systems Design and Implementation (OSDI). https://www.usenix.org/conference/osdi20/presentation/li-yuliang
- [67] Zhuolun Li, Alberto Sonnino, and Philipp Jovanovic. 2023. Performance of EdDSA and BLS Signatures in Committee-Based Consensus. In Workshop on Advanced Tools, Programming Languages, and PLatforms for Implementing and Evaluating Algorithms for Distributed Systems (ApPLIED). https://doi.org/10.1145/3584684.3597265
- [68] Jian Liu, Wenting Li, Ghassan O. Karame, and N. Asokan. 2019. Scalable Byzantine Consensus via Hardware-Assisted Secret Sharing. IEEE Transactions on Computers (TC) (2019). https://doi.org/10.1109/TC.2018.2860009

- [69] Marta Lokhava, Giuliano Losa, David Mazières, Graydon Hoare, Nicolas Barry, Eli Gafni, Jonathan Jove, Rafal Malinowsky, and Jed McCaleb. 2019. Fast and Secure Global Payments with Stellar. In ACM Symposium on Operating Systems Principles (SOSP). https://doi.org/10.1145/3341301.3359636
- [70] Yuan Lu, Zhenliang Lu, Qiang Tang, and Guiling Wang. 2020. Dumbo-MVBA: Optimal Multi-Valued Validated Asynchronous Byzantine Agreement, Revisited. In ACM Symposium on Principles of Distributed Computing (PODC). https://doi.org/10.1145/3382734.3405707
- [71] Yanhua Mao, Flavio P. Junqueira, and Keith Marzullo. 2008. Mencius: Building Efficient Replicated State Machines for WANs. In USENIX Symposium on Operating Systems Design and Implementation (OSDI). https://www.usenix.org/event/osdi08/tech/full\_papers/mao/mao\_html
- [72] Jean-Philippe Martin and Lorenzo Alvisi. 2005. Fast Byzantine consensus. In International Conference on Dependable Systems and Networks (DSN). https://doi.org/10.1109/DSN.2005.48
- [73] Iulian Moraru, David G. Andersen, and Michael Kaminsky. 2013. There Is More Consensus in Egalitarian Parliaments. In ACM Symposium on Operating Systems Principles (SOSP). https://doi.org/10.1145/2517349.2517350
- [74] Achour Mostéfaoui, Hamouma Moumen, and Michel Raynal. 2015. Signature-Free Asynchronous Binary Byzantine Consensus with t < n/3, O(n2) Messages, and O(1) Expected Time. *Journal of the ACM (JACM)* (2015). https://doi.org/10.1145/2785953
- [75] Achour Mostefaoui and Michel Raynal. 2000. Low cost consensus-based Atomic Broadcast. In Pacific Rim International Symposium on Dependable Computing (PRDC). https://doi.org/10.1109/PRDC.2000.897283
- [76] Ali Najafi and Michael Wei. 2022. Graham: Synchronizing Clocks by Leveraging Local Clock Properties. In USENIX Symposium on Networked Systems Design and Implementation (NSDI). https://www.usenix.org/conference/nsdi22/ presentation/najafi
- [77] NIST. 2022. NIST Announces First Four Quantum-Resistant Cryptographic Algorithms. https://www.nist.gov/news-events/news/2022/07/nist-announces-first-four-quantum-resistant-cryptographic-algorithms.
- [78] Diego Ongaro and John Ousterhout. 2014. In Search of an Understandable Consensus Algorithm. In USENIX Annual Technical Conference (USENIX ATC). https://www.usenix.org/conference/atc14/technical-sessions/presentation/ongaro
- [79] Fernando Pedone and André Schiper. 1998. Optimistic Atomic Broadcast. In *Distributed Computing (DC)*. https://doi.org/10.1007/BFb0056492
- [80] Kaihua Qin, Liyi Zhou, and Arthur Gervais. 2022. Quantifying Blockchain Extractable Value: How dark is the forest?. In IEEE Symposium on Security and Privacy (SP). https://doi.org/10.1109/SP46214.2022.9833734
- [81] Fred B. Schneider. 1990. Implementing Fault-Tolerant Services Using the State Machine Approach: A Tutorial. ACM Computing Surveys (CSUR) (1990). https://doi.org/10.1145/98163.98167
- [82] Peiyao Sheng, Gerui Wang, Kartik Nayak, Sreeram Kannan, and Pramod Viswanath. 2021. BFT Protocol Forensics. In ACM SIGSAC Conference on Computer and Communications Security (CCS). https://doi.org/10.1145/3460120.3484566
- [83] Peter W. Shor. 1994. Algorithms for quantum computation: discrete logarithms and factoring. In *Symposium on Foundations of Computer Science (FOCS)*. https://doi.org/10.1109/SFCS.1994.365700
- [84] Atul Singh, Tathagata Das, Petros Maniatis, Peter Druschel, and Timothy Roscoe. 2008. BFT Protocols under Fire. In USENIX Symposium on Networked Systems Design and Implementation (NSDI).
- [85] Man-Kit Sit, Manuel Bravo, and Zsolt István. 2021. An experimental framework for improving the performance of BFT consensus for future permissioned blockchains. In ACM International Conference on Distributed and Event-Based Systems (DEBS). https://doi.org/10.1145/3465480.3466922
- [86] Yee Jiun Song and Robbert van Renesse. 2008. Bosco: One-Step Byzantine Asynchronous Consensus. In International Symposium on Distributed Computing (DISC). https://doi.org/10.1007/978-3-540-87779-0\_30
- [87] Alexander Spiegelman, Neil Giridharan, Alberto Sonnino, and Lefteris Kokoris-Kogias. 2022. Bullshark: DAG BFT Protocols Made Practical. In ACM SIGSAC Conference on Computer and Communications Security (CCS). https://doi.org/10.1145/3548606.3559361
- [88] Chrysoula Stathakopoulou, Matej Pavlovic, and Marko Vukolić. 2022. State Machine Replication Scalability Made Simple. In European Conference on Computer Systems (EuroSys). https://doi.org/10.1145/3492321.3519579
- [89] Chrysoula Stathakopoulou, David Tudor, Matej Pavlovic, and Marko Vukolić. 2022. [Solution] Mir-BFT: Scalable and Robust BFT for Decentralized Networks. *Journal of Systems Research (JSys)* (2022). https://doi.org/10.5070/SR32159278
- [90] Espresso Systems. 2023. The Espresso Sequencer: HotShot Consensus and Tiramisu Data Availability. https://github.com/EspressoSystems/HotShot/blob/main/docs/espresso-sequencer-paper.pdf.
- [91] The Diem Team. 2021. DiemBFT v4: State Machine Replication in the Diem Blockchain. https://developers.diem.com/papers/diem-consensus-state-machine-replication-in-the-diem-blockchain/2021-08-17.pdf.
- [92] The MystenLabs Team. 2022. The Sui Smart Contracts Platform. https://github.com/MystenLabs/sui/blob/main/doc/paper/sui.pdf.

- [93] Giuliana Santos Veronese, Miguel Correia, Alysson Neves Bessani, Lau Cheuk Lung, and Paulo Verissimo. 2013. Efficient Byzantine Fault-Tolerance. IEEE Transactions on Computers (TC) (2013). https://doi.org/10.1109/TC.2011.221
- [94] Yann Vonlanthen, Jakub Sliwinski, Massimo Albarello, and Roger Wattenhofer. 2024. Banyan: Fast Rotating Leader BFT. In *International Middleware Conference (Middleware)*. https://doi.org/10.1145/3652892.3700788
- [95] Zizhong Wang, Tongliang Li, Haixia Wang, Airan Shao, Yunren Bai, Shangming Cai, Zihan Xu, and Dongsheng Wang. 2020. CRaft: An Erasure-coding-supported Version of Raft for Reducing Storage Cost and Network Cost. In USENIX Conference on File and Storage Technologies (FAST). https://www.usenix.org/conference/fast20/presentation/wang-zizhong
- [96] Michael Whittaker, Neil Giridharan, Adriana Szekeres, Joseph Hellerstein, and Ion Stoica. 2021. SoK: A Generalized Multi-Leader State Machine Replication Tutorial. Journal of Systems Research (JSys) (2021). https://doi.org/10.5070/ SR31154817
- [97] Maofan Yin, Dahlia Malkhi, Michael K. Reiter, Guy Golan Gueta, and Ittai Abraham. 2019. HotStuff: BFT Consensus with Linearity and Responsiveness. In ACM Symposium on Principles of Distributed Computing (PODC). https://doi.org/10.1145/3293611.3331591
- [98] Qianyu Yu, Giuliano Losa, and Xuechao Wang. 2024. TetraBFT: Reducing Latency of Unauthenticated, Responsive BFT Consensus. In *Proceedings of the 43rd ACM Symposium on Principles of Distributed Computing (PODC).* https://doi.org/10.1145/3662158.3662783
- [99] Yunhao Zhang, Srinath Setty, Qi Chen, Lidong Zhou, and Lorenzo Alvisi. 2020. Byzantine Ordered Consensus without Byzantine Oligarchy. In *USENIX Symposium on Operating Systems Design and Implementation (OSDI)*. https://www.usenix.org/conference/osdi20/presentation/zhang-yunhao

# Contents

Abst	tract	1
1	Introduction	1
2	Model and Background	4
2.1	Model	4
2.2	Abstractions	5
2.3	Good Case Scenario	5
3	Blink	5
4	Flutter	6
4.1	Overview	6
4.2	Achieving Convergence in Flutter	7
4.3	A Server's Timeline	9
4.4	Algorithm	9
4.5	Correctness Proof Sketches	12
4.6	Good-case and Bad-case Latency Sketches	13
4.7	Complexity	14
5	Related Work	14
6	Future Work	15
Ackı	nowledgments	15
References		16
Contents		21
A	Blink	22
A.1	Algorithm	22
A.2	Comparison with Bosco	23
A.3	Correctness Sketches	23
A.4	Latency Sketches and Complexity	24
A.5	Termination	24
A.6	Representative Validity	25
A.7	Integrity and Agreement	26
A.8	Latency	26
В	Flutter	28
B.1	Client Algorithm	28
B.2	Auxiliary Results	28
B.3	No Duplication and Integrity	31
B.4	Agreement and Total Order	31
B.5	Validity	37
B.6	Good-case Latency	38
B.7	Denial of Service	41
C	Quasi-optimality of Flutter	43

#### A BLINK

Appx. A.1 presents Blink's simple algorithm. Appx. A.2 details the differences between Blink and the similar algorithm Bosco [86]. Appx. A.3 discusses proof sketches of the correctness of Blink and Appx. A.4 similarly discusses the latency and complexity of Blink. Finally, Apps. A.5 to A.7 provide full proofs of Blink's correctness and Appx. A.8 full proofs of Blink's latency.

# A.1 Algorithm

# Algorithm 2 Blink

```
1: Implements:
         RepresentativeBinaryConsensus, instance con
 3: Uses:
 4:
         AuthenticatedLinks, instance al
         BinaryConsensus, instance dep
 5:
 6: upon event (con.Init) do
         suggestions : Map(\Pi \rightarrow \mathbb{B}) = \{\}
 7:
 8:
         proposed : \mathbb{B} = False
         decided : \mathbb{B} = False
10: upon event \langle con.Propose \mid v \rangle do
11:
         for all \pi \in \Pi do
             trigger \langle al. Send \mid \pi, [Suggest, v] \rangle
12:
13: upon event \langle al. \text{Deliver} \mid \sigma, [\text{Suggest}, v] \rangle do
14:
         suggestions[\sigma] = v
15: upon (|suggestions| \ge (4f + 1)) and proposed = False do
         m = v such that |\{\pi \text{ s.t. } suggestions[\pi] = v\}| \ge (2f + 1)
17:
         trigger \langle dep. Propose \mid m \rangle
18:
         proposed = True
19: upon exists v such that |\{\pi \text{ s.t. } suggestions[\pi] = v\}| \ge (4f + 1) do
         if decided = False then
21:
             trigger \langle con. Decide \mid v \rangle
22:
             decided = True
23: upon event \langle dep. Decide |v\rangle do
         if decided = False then
24:
25:
             trigger \langle con. Decide \mid v \rangle
26:
             decided = True
```

Blink implements a Representative Binary Consensus instance con on top of a Binary Consensus instance dep, as described in Alg. 2. Upon proposing a value v (line 10), a correct server  $\pi$  sends v to all servers by means of a Suggest message (lines 11 and 12);  $\pi$  records the suggestions it receives (line 13) in its suggestions map (line 14). Upon first collecting (4f+1) suggestions (line 15),  $\pi$  identifies whichever majority value m it was suggested the most (line 16), then proposes m to dep (line 17). Note that, as (4f+1) is odd and only two values (True and False) are possible, one and only one value is guaranteed to be backed by at least (2f+1) suggestions.  $\pi$  decides v (line 21 or 25) upon collecting (4f+1) suggestions for v (fast path, line 19) or upon dep deciding v (slow path, line 23).

# A.2 Comparison with Bosco

The goal of this section is twofold. First, we compare Blink with Bosco, the algorithm presented by Song and van Renesse at DISC '08 [86], which Blink generalizes to the (5f + 1) setting. Second, we address the impossibility result, presented in the same paper, stating that (5f + 1) Consensus cannot be solved in one communication step if any server is faulty.

Blink vs. Bosco. Like Blink, Bosco [86, Algorithm 1] has every correct server disseminate its proposal (line 1) by means of a Vote message (akin to Blink's Suggest message). Also like Blink, Bosco has every correct server collect (n-f) Vote messages (line 2), then propose to an underlying instance of Consensus (line 8) the majority value, i.e., the value (if it exists) that received more than (n-f)/2 votes (lines 5 to 8). A majority value is guaranteed to exist for Blink (which solves Binary Consensus), but not for Bosco (which solves multi-valued Consensus) – in Bosco, if a correct server does not observe any value having the majority of votes, the server proposes its original proposal. Unlike Blink, however, Bosco's fast-path decision (lines 3 and 4) can only occur at the same time as the proposal to the underlying Consensus, i.e., as soon as (n - f) Vote messages are collected (line 2). By contrast, a correct Blink server keeps collecting Suggest messages even after proposing to Consensus: if, at any time, either value collects (4f + 1) suggestions, the server decides that value. Due to this difference, Bosco cannot guarantee a one-message-delay decision in the (5f + 1)setting, even if all correct servers propose the same value. In the (5f + 1) setting, a correct Bosco server would fast-path decide only if all the first (4f + 1) votes it received were for the same value. Even assuming all correct servers propose the same value, the arbitrary vote of a single faulty server would be sufficient to inhibit Bosco's fast path. That is not the case in Blink: regardless of the arbitrary behavior of faulty processes, if every correct server proposes the same value, every correct server collects (4f + 1) matching suggestions and fast-path decides within one message delay.

Message delays vs. communication steps. Importantly, the goal of Bosco is not to enable fast-path termination within one message delay, but rather within one communication step. The difference is subtle but noteworthy. Bosco abides by a model of asynchronous networking [51] that defines a communication step as a period of time where each process can (1) send messages; (2) receive messages; and (3) do local computations, in that order. Conversely, this paper denotes a message delay as the bound  $\Delta$  on communication delay (see §2.1). In the (7f+1) setting, and assuming all correct servers propose the same value, Bosco does ensure one-step termination (with its thresholds adapted to the (7f+1) setting, Blink would do the same). Remarkably, the paper proves [86, Theorem 1] that Bosco is optimal in that regard, meaning one-step termination cannot be ensured by any algorithm with less than (7f+1) servers. Blink's one-message-delay termination does not conflict with this result. Indeed, Blink does not, in general, terminate within one communication step. Consider the case where all correct servers propose the same value v. If even a single faulty server issues a [Suggest,  $\bar{v}$ ] message, the first (4f+1) suggestions a correct server  $\pi$  collects are by no means guaranteed to be all for v. Upon triggering the event at line 15,  $\pi$  would thus engage in local computation, exhausting its first step of communication without deciding v.

#### A.3 Correctness Sketches

This section provides proof sketches for each property. We prove the correctness of Blink to the fullest extent of formal detail in Apps. A.5 to A.7 (Theorems 1 to 4, respectively proving Termination, Representative Validity, Integrity and Agreement).

*Termination.* As we assume at least (4f + 1) correct servers, every correct server is guaranteed to eventually collect (4f + 1) suggestions and submit a majority value to dep. By the Termination property of dep, every correct server is guaranteed to eventually trigger dep's decision and decide.

Representative Validity. If less than (f+1) correct servers propose some value v, no correct server can collect the (2f+1) suggestions required to propose v to dep, or the (4f+1) required to decide v via the fast path; by the Validity of dep, no correct server decides v via the slow path either.

Integrity. Decisions are guarded by a decided flag, which is set when a correct server first decides.

Agreement. If a correct server decides v via the fast path, it collected at least (4f+1) suggestions for v. This means that no more than f correct servers proposed  $\bar{v}$ , hence no correct server ever collects (2f+1) suggestions for  $\bar{v}$ . As a result, no correct server decides  $\bar{v}$  via the fast path or proposes  $\bar{v}$  to dep. Because dep satisfies Validity, dep cannot decide  $\bar{v}$ . In summary, if any correct server decides v via the fast path, no correct server decides  $\bar{v}$ . If all correct server decide via the slow path, Agreement follows immediately from the Agreement of dep.

### A.4 Latency Sketches and Complexity

Fast path latency. We prove to the fullest extent of formal detail in Appx. A.8 (Theorem 5) that, if every every correct server proposes the same value v to an instance of Blink, every correct server decides within one message delay. The result is fairly intuitive: as we assume at least (4f+1) correct servers, within one message delay every correct server delivers (4f+1) suggestions for v and decides v via the fast path.

Slow path latency. If Blink fails to decide via the fast path, Blink's latency is one message delay higher than its underlying implementation of Binary Consensus. We conjecture this being the unavoidable cost of upgrading Weak Validity to Validity. We underline that leaderless Binary Consensus algorithms exist in literature whose latency is constant (at least in expectancy), e.g., in the asynchronous setting [28, 74]. To be precise, asynchronous algorithms implement a variant of Binary Consensus that ensures Termination only with probability 1 – building on one such algorithm, Blink and Flutter would inherit its probability-1 guarantees.

Complexity. Blink involves a single step of constant-sized, all-to-all communication, resulting in  $O(n^2)$  bit complexity and matching the complexity lower bound for Binary Consensus [37]. This means that Blink will never bottleneck Binary Consensus – rather, Blink inherits the complexity of whatever Binary Consensus implementation it depends upon.

#### A.5 Termination

**Lemma 1.** Every correct server eventually triggers (dep.Decide).

PROOF. Upon triggering  $\langle con. Propose \rangle$  (line 10), every correct server sends a Suggest message to every server (lines 11 and 12). Let  $\pi$  be a correct server. Upon delivering a Suggest message from a server  $\sigma$  (line 13)  $\pi$  adds  $\sigma$  to the keys of *suggestions* (line 14). As we assume (4f+1) correct servers,  $\pi$  eventually adds at least (4f+1) keys to *suggestions*. Noting that  $\pi$  never removes keys from *suggestions*,  $\pi$  eventually satisfies  $|suggestions| \geq (4f+1)$ .

Upon initialization,  $\pi$  sets proposed = False (line 8);  $\pi$  updates proposed to True (line 18 only) only after triggering  $\langle dep. Propose \rangle$  (line 17). This proves that  $\pi$  eventually triggers  $\langle dep. Decide \rangle$ . Indeed, let us assume for the sake of contradiction that  $\pi$  never triggers  $\langle dep. Decide \rangle$ .  $\pi$  would eventually permanently satisfy  $|suggestions| \geq (4f+1)$  and proposed = False. As a result, the event at line 15 would eventually trigger, causing  $\pi$  to trigger  $\langle dep. Propose \rangle$ .

In summary, every correct server eventually triggers  $\langle dep. Propose \rangle$ . By the Termination property of dep, every correct server eventually triggers  $\langle dep. Decide \rangle$ , and the lemma is proved.

## **Theorem 1.** Blink satisfies Termination.

PROOF. Upon initialization, a correct server sets decided = False (line 9). A correct server updates decided to True (lines 22 and 26 only) only after triggering  $\langle con.Decide \rangle$  (lines 21 and 25). Moreover, by Lemma 1, every correct server eventually triggers  $\langle dep.Decide \rangle$ . Upon doing so (line 23), a correct server either satisfies decided = True, in which case it previously triggered  $\langle con.Decide \rangle$ , or decided = False (line 24), in which case it immediately triggers  $\langle con.Decide \rangle$  (line 25). In summary, every correct server eventually triggers  $\langle con.Decide \rangle$ , and the theorem is proved.

# A.6 Representative Validity

**Observation 1.** Let  $\pi$  be a correct server. Upon initialization,  $\pi$  sets  $suggestions = \{\}$  (line 7).  $\pi$  sets  $suggestions[\sigma] = v$  (line 14 only) only upon delivering a [Suggest, v] message from  $\sigma$  (line 13). This means that, if  $suggestions[\sigma] = v$  at  $\pi$ , then  $\pi$  delivered a [Suggest, v] message from  $\sigma$ .

**Lemma 2.** Let  $v \in \mathbb{B}$ . If any correct server eventually satisfies

$$|\{\sigma \in \Pi \text{ s.t. suggestions}[\sigma] = v\}| \ge (4f + 1) \tag{1}$$

then no correct server ever satisfies

$$|\{\sigma \in \Pi \text{ s.t. suggestions}[\sigma] = \bar{v}\}| \ge (2f+1) \tag{2}$$

PROOF. Let us assume, for the sake of contradiction, that two correct servers  $\pi$ ,  $\rho$  exist such that  $\pi$  satisfies Equation 1 and  $\rho$  satisfies Equation 2. Let  $\Sigma_{\pi}$ ,  $\Sigma_{\rho}$  respectively denote  $\pi$ 's suggestions for v and  $\rho$ 's suggestions for  $\bar{v}$ :

$$\Sigma_{\pi} = \{ \sigma \in \Pi \text{ s.t. } suggestions[\sigma] = v \text{ at } \pi \}$$
  
$$\Sigma_{\rho} = \{ \sigma \in \Pi \text{ s.t. } suggestions[\sigma] = \bar{v} \text{ at } \rho \}$$

Note that  $|\Sigma_{\pi}| = (4f+1)$ ,  $|\Sigma_{\rho}| = (2f+1)$ . As we assume at most f faulty servers,  $\Sigma_{\pi}$  and  $\Sigma_{\rho}$  respectively contain (3f+1) and (f+1) servers that are certainly correct. This proves that at least one correct server  $\sigma$  belongs to both  $\Sigma_{\pi}$  and  $\Sigma_{\rho}$ .

By Observation 1, for  $\sigma$  to belong to both  $\Sigma_{\pi}$  and  $\Sigma_{\rho}$ ,  $\sigma$  must have sent a [Suggest, v] message to  $\pi$ , as well as a [Suggest,  $\bar{v}$ ] message to  $\rho$ .  $\sigma$  issues Suggest messages only once (lines 11 and 12), upon triggering  $\langle con.$ Propose  $|x\rangle$  (line 10). Upon doing so,  $\sigma$  sends the same message [Suggest, x] to every server. This contradicts  $\sigma$  sending [Suggest, v] to  $\pi$  and [Suggest, v] to  $\rho$  and proves the lemma.

**Lemma 3.** Let  $v \in \mathbb{B}$ . If any correct server eventually satisfies

$$|\{\sigma \in \Pi \text{ s.t. suggestions}[\sigma] = v\}| \ge (4f + 1)$$
(3)

then every correct server that triggers  $\langle dep.Decide \rangle$  triggers  $\langle dep.Decide | v \rangle$ .

PROOF. By Lemma 2, no correct server satisfies

$$|\{\sigma \in \Pi \text{ s.t. suggestions}[\sigma] = \bar{v}\}| \ge (2f+1)$$

This means that no correct server ever triggers  $\langle dep. Propose \mid \bar{v} \rangle$ . Indeed, a correct server triggers  $\langle dep. Propose \mid x \rangle$  (line 17 only) only if x satisfies  $|\{\sigma \in \Pi \text{ s.t. } suggestions[\sigma] = x\}| \geq (2f+1)$  (line 16). By the Validity property of dep, no correct server triggers  $\langle dep. Decide \mid \bar{v} \rangle$ , which proves the lemma.

**Lemma 4.** If a correct server triggers both  $\langle dep.Decide \mid v \rangle$  and  $\langle con.Decide \mid w \rangle$ , then v = w.

PROOF. Let  $\pi$  be a correct server that triggers both  $\langle dep. \text{Decide} \mid v \rangle$  (line 23) and  $\langle con. \text{Decide} \mid w \rangle$  (line 21 or 25). Upon triggering  $\langle dep. \text{Decide} \mid v \rangle$  (line 23),  $\pi$  satisfies either decided = False or decided = True. If decided = False (line 24), then  $\pi$  immediately triggers  $\langle con. \text{Decide} \mid v \rangle$  (line 25), hence w = v. Throughout the remainder of this proof, we assume that, upon triggering  $\langle dep. \text{Decide} \mid v \rangle$ ,  $\pi$  satisfies decided = True.

Upon initialization,  $\pi$  sets decided = False (line 9). By the Integrity property of dep,  $\pi$  does not trigger  $\langle dep$ .Decide $\rangle$  more than once. As a result,  $\pi$  cannot have previously set decided = False by executing line 26 - the line is guarded by  $\langle dep$ .Decide $\rangle$  (line 23). The only other option is that  $\pi$  previously set decided = False by executing line 22. To do so,  $\pi$  must have satisfied

$$|\{\sigma \in \Pi \text{ s.t. suggestions}[\sigma] = w\}| \ge (4f + 1)$$

(line 19), as  $\pi$  also immediately triggers  $\langle con.Decide \mid w \rangle$  (line 21). By Lemma 3, however,  $\pi$  can only trigger  $\langle dep.Decide \mid w \rangle$ , which proves v = w and concludes the lemma.

**Theorem 2.** Blink satisfies Representative Validity.

PROOF. Let us assume that some correct server  $\pi$  triggers  $\langle con.Decide \mid v \rangle$  for some  $v \in \mathbb{B}$ . By Lemma 1,  $\pi$  eventually triggers  $\langle dep.Decide \rangle$ . By Lemma 4,  $\pi$  triggers  $\langle dep.Decide \mid v \rangle$ . By the Validity property of dep, at least one correct server  $\rho$  triggered  $\langle dep.Propose \mid v \rangle$ .  $\rho$  does so (line 17 only) only if  $\rho$  satisfies

$$|\{\sigma \in \Pi \text{ s.t. suggestions}[\sigma] = \bar{v}\}| \ge (2f+1)$$

By Observation 1,  $\rho$  delivered a [Suggest, v] message from (2f + 1) distinct servers. As we assume at most f faulty servers, at least (f + 1) correct servers issued a [Suggest, v] message.

A correct server issues a [Suggest, v] message (line 12 only) only upon triggering  $\langle con.Propose \mid v \rangle$  (line 10). This proves that at least (f+1) correct servers triggered  $\langle con.Propose \mid v \rangle$  and concludes the theorem.

#### A.7 Integrity and Agreement

**Theorem 3.** Blink satisfies Integrity.

PROOF. A correct server triggers  $\langle con.Decide \rangle$  (line 21 or 25) only if decided = False (lines 20 and 24). Immediately after triggering  $\langle con.Decide \rangle$ , a correct server sets decided = True (line 22 or 26). A correct server never sets decided back to False. Hence, a correct server triggers  $\langle con.Decide \rangle$  at most once, and the theorem is proved.

**Theorem 4.** Blink satisfies Agreement.

PROOF. By Lemma 1, every correct server eventually triggers  $\langle dep. \text{Decide} \rangle$ . By the Agreement property of dep, every correct server eventually triggers  $\langle dep. \text{Decide} \mid v \rangle$  for the same value v. By Lemma 4, every correct server that triggers  $\langle con. \text{Decide} \rangle$  triggers  $\langle con. \text{Decide} \mid v \rangle$ , and the theorem is proved

# A.8 Latency

**Theorem 5.** If every correct server triggers  $\langle con.Propose \mid v \rangle$  for the same  $v \in \mathbb{B}$ , every correct server triggers  $\langle con.Decide \rangle$  within one message delay.

PROOF. Let  $v \in \mathbb{B}$ , let us assume that every correct server triggers  $\langle con. \text{Propose} \mid v \rangle$ . Let  $\rho$  be a correct server. Upon triggering  $\langle con. \text{Propose} \mid v \rangle$  (line 10)  $\rho$  sends a [Suggest, v] message to every server (lines 11 and 12). Because  $\rho$  never issues a Suggest message other than upon triggering  $\langle con. \text{Propose} \rangle$ , and because  $\rho$  never triggers  $\langle con. \text{Propose} \rangle$  more than once,  $\rho$  never issues any [Suggest, v] message.

Let  $\pi$  be a correct server. As we assume at most f faulty servers, within one message delay  $\pi$  delivers at least (4f+1) [Suggest, v] messages from correct sources. Upon delivering a [Suggest, v] message from a correct server  $\sigma$  (line 13),  $\pi$  sets  $suggestions[\sigma] = v$  (line 14). Because  $\sigma$  never issues a [Suggest,  $\bar{v}$ ] message, and because  $\pi$  sets  $suggestions[\sigma] = x$  (line 14 only) only upon delivering a [Suggest, x] message from  $\sigma$  (line 13), within one message delay  $\pi$  satisfies

$$|\{\sigma \in \Pi \text{ s.t. suggestions}[\sigma] = v\}| \ge (4f + 1)$$

and triggers the event at line 19.

Upon initialization,  $\pi$  sets decided = False (line 9).  $\pi$  updates decided to True (lines 22 and 26 only) only after triggering  $\langle con.Decide \rangle$  (lines 21 and 25). Upon triggering the event at line 19,  $\pi$  satisfies either decided = True or decided = False. If decided = True, then  $\pi$  previously triggered  $\langle con.Decide \rangle$ . If decided = False (line 20) then  $\pi$  triggers  $\langle con.Decide \rangle$  (line 21). This proves that  $\pi$  triggers  $\langle con.Decide \rangle$  within one message delay and concludes the theorem.

#### **B FLUTTER**

Appx. B.1 first presents Flutter's client algorithm. Appx. B.2 presents auxiliary notations and results required for the following sections. Appx. B.3, Appx. B.4, and Appx. B.5 present proofs to the fullest extent of formal details for Flutter's No Duplication and Integrity properties, Agreement and Total Order properties, and Validity property, respectively. Appx. B.6 fully proves Flutter's good-case latency. Appx. B.7 discusses the impact of denial of services attacks on Flutter.

# **B.1** Client Algorithm

Alg. 3 describes Flutter's client algorithm and complements Alg. 1 describing Flutter's server algorithm presented in §4.4 of the main document.

### Algorithm 3 Flutter client

```
1: Implements:
         TotalOrderBroadcast, instance tob
 3: Uses:
         AuthenticatedFifoLinks, instance af
 5: Parameters:
         \Delta \in \mathbb{T}: message delay estimate
                                                                                         ▶ Equals ∆ under synchrony, arbitrary otherwise
         \epsilon \in \mathbb{T}^+: bet margin
                                                                                                                               ▶ Arbitrarily small
 8: upon event \langle tob.Init \rangle do
         submissions : Map(\mathcal{M} \to (\mathbb{N} \times \mathbb{T})) = \{\}
10:
         decisions : Map((\mathcal{M} \times \mathbb{T} \times \Pi) \to \mathbb{B})
11: procedure submit(m, r) is
         b = local \ time() + 2^r \tilde{\Delta} + \epsilon
12:
13:
         for all \pi \in \Pi do
              trigger \langle af. Send \mid \pi, [Message, m, b] \rangle
         submissions[m] = (r, b)
16: upon event \langle tob.Broadcast | m \rangle do
         submit(m,0)
18: upon event \langle af. Deliver | \pi, [Decision, m, b, v] \rangle do
         decisions[(m, b, \pi)] = v
19:
20: upon exists (m \to (r, b)) \in submissions such that |\{\pi \text{ s.t. } decisions[(m, b, \pi)] = \text{False}\}| \geq (f + 1) do
21:
         submit(m, r+1)
```

### **B.2** Auxiliary Results

**Notation 1** (Set crop). Let *X* be a totally ordered set, let  $x \in X$ . We use

$$(X|_{\le x}) = \{ y \in X \text{ s.t. } y \le x \}$$
  
 $(X|_{< x}) = \{ y \in X \text{ s.t. } y < x \}$ 

**Notation 2** (Range). Let  $a, b \in \mathbb{N}$  such that  $a \leq b$ . We use

$$a..b = \{a, a + 1, ..., b\}$$

**Lemma 5.** Let *X* be a totally ordered set such that

$$\forall x \in X, \ |(X|_{\leq x})| < \infty$$

A strictly increasing sequence z exists such that

$$\forall x \in X, \exists n \text{ s.t. } z_n = x$$

PROOF. Let  $\phi: X \to \mathbb{N}$  be defined by

$$\phi(x) = |(X|_{\le x})|$$

The lemma is proved by showing that  $\phi$  is a bijection between X and  $\{n \in \mathbb{N} \text{ s.t. } n \leq |X|\}$ , and that  $\phi^{-1}$  is strictly increasing.

**Result 5.1.** Let  $x, y \in X$  such that x < y. We have  $(X|_{\leq x}) \subset (X|_{\leq y})$ .

PROOF. Let  $h \in (X|_{\leq x})$ . We have  $h \leq x < y$ , which proves  $h \in (X|_{\leq y})$ . Moreover, because x < y, we have  $y \notin (X|_{\leq x})$ . Finally, because  $y \leq y$ , we obviously have  $y \in (X|_{\leq y})$ . In summary,  $(X|_{\leq x}) \subseteq (X|_{\leq y})$  and  $(X|_{\leq y}) \setminus (X|_{\leq x}) \supseteq \{y\} \neq \emptyset$ , hence  $(X|_{\leq x}) \subset (X|_{\leq y})$ .

**Result 5.2.**  $\phi$  *is injective.* 

PROOF. Let  $x, y \in X$  such that  $x \neq y$ . Let us assume without loss of generality x < y. By Result 5.1, we have

$$\phi(x) = |(X|_{\leq x})| < |(X|_{\leq y})| = \phi(y)$$

which proves  $\phi(x) \neq \phi(y)$ .

**Result 5.3.** Let  $x \in X$ . For all  $n \in 1...\phi(x)$ , some  $h \in X$  exists such that  $\phi(h) = n$ .

PROOF. We start by noting that the result obviously holds true for  $n = \phi(x)$ .

Let  $y \in (X|_{< x})$ . Noting that  $y \le y$ , we obviously have  $(X|_{\le y}) \supseteq \{y\}$ , hence  $\phi(y) \ge 1$ . Moreover, because y < x, by Result 5.1 we have  $\phi(y) < \phi(x)$ . In summary, for every  $y \in (X|_{< x})$ , we have  $\phi(y) \in 1...(\phi(x) - 1)$ .

Noting that

$$(X|_{< x}) = \{y \in X \text{ s.t. } y < x\} = \{y \in X \text{ s.t. } y \le x, y \ne x\} = \{y \in X \text{ s.t. } y \le x\} \setminus \{x\} = (X|_{\le x}) \setminus \{x\}$$
 we have  $|(X|_{< x})| = \phi(x) - 1$ .

In summary,  $|(X|_{< x})|$  contains  $\phi(x) - 1$  elements. For every  $y \in (X|_{< x})$  we have  $\phi(y) \in 1...(\phi(x) - 1)$ . For every  $y, w \in (X|_{< x})$  such that  $y \neq w$ , we have  $\phi(y) \neq \phi(w)$ . By the pigeonhole principle, for all  $n \in 1...(\phi(x) - 1)$  some  $h \in (X|_{< x})$  exists such that  $\phi(h) = n$ , and the result is proved.

**Result 5.4.** *If* X *is finite, then*  $\phi$  *is surjective on* 1..|X|.

PROOF. Because X is finite, X has a maximum. Let  $x = \max X$ . By definition we have  $\phi(x) = |X|$ , and the result follows immediately from Result 5.3.

**Result 5.5.** *If* X *is infinite, then*  $\phi$  *is surjective on*  $\mathbb{N}$ .

PROOF. By hypothesis, for all  $x \in X$  we have  $|(X|_{\le x})| < \infty$ . As a result we have

$$\forall x \in X, \ (X \setminus (X|_{\leq x})) \neq \emptyset$$

This proves the existence of some function  $\alpha: X \to X$  such that

$$\alpha(x) \in (X \setminus (X|_{\leq x}))$$

By definition, for all  $x \in X$  we have  $\alpha(x) > x$ . By Result 5.1, we then have

$$\phi(\alpha(x)) > \phi(x)$$

or equivalently

$$\phi(\alpha(x)) \ge \phi(x) + 1$$

Noting that, for all  $x \in X$ , we have  $x \le x$  hence  $\phi(x) \ge 1$ , by induction we have

$$\forall x \in X, \forall n \in \mathbb{N}, \ \phi(\alpha^n(x)) \ge n$$

We can now prove the surjectivity of  $\phi$ . Let  $n \in \mathbb{N}$ . Let  $x \in X$ , let  $y = \alpha^n(x)$ , we have  $\phi(y) \ge n$ . By Result 5.3, some  $h \in X$  exists such that  $\phi(h) = n$ . Because this holds for every n,  $\phi$  is surjective on  $\mathbb{N}$ .

By Results 5.2, 5.4 and 5.5,  $\phi$  is a bijection between X and  $\{n \in \mathbb{N} \text{ s.t. } n \leq |X|\}$ .

**Result 5.6.** *Let*  $n, m \le |X|$  *such that* n < m. *We have*  $\phi^{-1}(n) < \phi^{-1}(m)$ .

PROOF. For the sake of readability, let  $x = \phi^{-1}(n)$ , let  $y = \phi^{-1}(m)$ . Note that, by the injectivity of  $\phi^{-1}$ , we have  $x \neq y$ . Let us assume for the sake of contradiction that x > y. By Result 5.1 we would have

$$n = \phi(x) > \phi(y) = m$$

which contradicts n < m and proves the result.

By Result 5.6,  $\phi^-1$  is increasing, and the lemma is proved.

**Lemma 6.** Let X be a totally ordered set. Let z, z' be strictly increasing sequences such that

$$\forall x \in X, \exists n \text{ s.t. } z_n = x$$

$$\forall x \in X, \exists n' \text{ s.t. } z'_{n'} = x$$

We have z = z'.

PROOF. Let us assume for the sake of contradiction that  $z \neq z'$ . Let

$$n = \min m \in \mathbb{N} \text{ s.t. } z_m \neq z'_m$$

We have

$$\forall m < n, z_m = z'_m$$

we have  $z_n, z'_n \in X$ , but  $z_n \neq z'_n$ . Let us assume without loss of generality that  $z_n < z'_n$ . Because z is strictly increasing we have

$$\forall m < n, \ (z'_m = z_m) \neq z_n$$

and because z' is strictly increasing we have

$$\forall m>n,\ z'_m>z'_n>z_n$$

In summary, we have

$$\forall m < n, \ z'_m \neq z_n$$
 
$$z'_n \neq z_n$$

$$\forall m > n, \ z'_m \neq z_n$$

Which proves that  $z_n \in X$  does not appear anywhere in z', contradicts the hypothesis, and proves the lemma.

# B.3 No Duplication and Integrity

**Observation 2.** Let  $\pi$  be a correct server. Upon initialization,  $\pi$  sets  $delivered = \{\}$  (line 10).  $\pi$  never removes elements from delivered. This means delivered is non-decreasing at  $\pi$ . Equivalently,  $\pi$  satisfies  $(\theta, m) \in delivered$  if and only if  $\pi$  added  $(\theta, m)$  to delivered.

**Observation 3.** Let  $\pi$  be a correct server. Upon initialization,  $\pi$  sets  $proposed = \{\}$  (line 8).  $\pi$  never removes elements from proposed. This means proposed is non-decreasing at  $\pi$ . Equivalently,  $\pi$  satisfies  $(\theta, m, b) \in proposed$  if and only if  $\pi$  added  $(\theta, m, b)$  to proposed.

**Theorem 6.** Flutter satisfies No Duplication.

PROOF. Let  $\pi$  be a correct server.  $\pi$  triggers  $\langle tob. \text{Deliver} \mid \theta, m \rangle$  (line 49 only) only if  $(\theta, m) \notin delivered$  (line 48). Immediately after triggering  $\langle tob. \text{Deliver} \mid \theta, m \rangle$ ,  $\pi$  adds  $(\theta, m)$  to delivered (line 50). The theorem follows immediately from Observation 2

**Lemma 7.** Let  $\theta$  be a correct client. For every  $m \in submissions$  at  $\theta$ ,  $\theta$  triggered  $\langle tob.Broadcast \mid m \rangle$ .

PROOF. Upon initialization,  $\theta$  sets  $submissions = \{\}$  (line 9).  $\theta$  sets submissions[m] (line 15 only) only upon executing  $submit(m, \_)$  (line 11).  $\theta$  invokes  $submit(m, \_)$  only from lines 17 and 21, respectively: upon triggering  $\langle tob.$ Broadcast  $|m\rangle$  (line 16); and only if  $m \in submissions$  (line 20). By induction, for every  $m \in submissions$  at  $\pi$ ,  $\pi$  triggered  $\langle tob.$ Broadcast  $|m\rangle$ .

**Lemma 8.** Let  $\theta$  be a correct client, let  $m \in \mathcal{M}$ . If  $\theta$  issues any [Message, m, \_] message, then  $\theta$  triggered  $\langle tob.Broadcast \mid m \rangle$ .

PROOF. Immediately after issuing a [Message, m, \_] message (line 14 only),  $\theta$  sets submissions[m] (line 15). The lemma immediately follows from Lemma 7.

**Theorem 7.** Flutter satisfies Integrity.

PROOF. Let  $\pi$  be a correct server, let  $\theta$  be a correct client, let  $m \in \mathcal{M}$  such that  $\pi$  triggers  $\langle tob. \text{Deliver} \mid \theta, m \rangle$ .  $\pi$  triggers  $\langle tob. \text{Deliver} \mid \theta, m \rangle$  (line 49 only) only upon executing  $order(\theta, m, b)$  for some  $b \in \mathbb{T}$  (line 47).  $\pi$  invokes  $order(\theta, m, b)$  (line 45 only) only if  $decisions[(\theta, m, b)] = \text{True}$  (line 44).  $\pi$  sets  $decisions[(\theta, m, b)] = \text{True}$  (line 42 only) only upon triggering  $\langle con[(\theta, m, b)]. \text{Decide} \mid \text{True} \rangle$  (line 40). By the Representative Validity property of  $con[(\theta, m, b)]$ , at least one correct server  $\rho$  triggered  $\langle con[\theta, m, b]. \text{Propose} \mid \text{True} \rangle$ .  $\rho$  triggers  $\langle con[(\theta, m, b)]. \text{Propose} \mid \text{True} \rangle$  (line 35 only) only upon delivering a [Message, m, b] from b. By Lemma 8, b0 triggered  $\langle tob. \text{Broadcast} \mid m \rangle$ , and the theorem is proved.

# **B.4** Agreement and Total Order

**Assumption 1.**  $(\Theta \times \mathcal{M} \times \mathbb{T})$  is ordered by successively comparing the time, client, and message components:

$$\left((\theta, m, b) \geq (\theta', m', b')\right) \overset{def}{\Longleftrightarrow} \left((b > b') \vee (b = b' \wedge \theta > \theta') \vee (b = b' \wedge \theta = \theta' \wedge m \geq m')\right)$$

The ordering criterion chosen for clients and messages is not important. Adequate criteria include, e.g., lexicographic ordering of message payloads / client identifiers.

**Observation 4.** Let  $\pi$  be a correct server. Upon initialization,  $\pi$  sets  $observed = \{\}$  (line 7).  $\pi$  never removes elements from observed. This means observed is non-decreasing at  $\pi$ . Equivalently,  $\pi$  satisfies  $(\theta, m, b) \in observed$  if and only if  $\pi$  added  $(\theta, m, b)$  to observed.

**Definition 1** (Universe). The **universe**  $\mathcal{U} \subseteq (\Theta \times \mathcal{M} \times \mathbb{T})$  includes  $(\theta, m, b)$  if and only if any correct server eventually adds  $(\theta, m, b)$  to *observed*.

**Notation 3** (Universe, time-cropped). For all  $t \in \mathbb{T}$ , we use

$$\mathcal{U}|_{\leq t} = \{(\theta, m, b) \in \mathcal{U} \text{ s.t. } b \leq t\}$$

**Lemma 9.** Let  $\pi$  be a correct server, let  $(\theta, m, b) \in (\Theta, \mathcal{M}, \mathbb{T})$ . Upon returning from an invocation to  $spot(\theta, m, b)$ ,  $\pi$  satisfies  $(\theta, m, b) \in observed$ .

PROOF. Upon invoking  $spot(\theta, m, b)$ ,  $\pi$  either satisfies  $(\theta, m, b) \in observed$  or  $(\theta, m, b) \notin observed$ . If  $(\theta, m, b) \in observed$ , the lemma holds trivially. If  $(\theta, m, b) \notin observed$  (line 24) then  $\pi$  adds  $(\theta, m, b)$  to observed (line 28).

**Lemma 10.** Let  $(\theta, m, b) \in \mathcal{U}$ . Eventually, every correct server adds  $(\theta, m, b)$  to observed.

PROOF. By Definition 1, some correct server  $\pi$  eventually adds  $(\theta, m, b)$  to *observed*.  $\pi$  does so only by executing line 28. Immediately before doing so,  $\pi$  sends an [Observe,  $\theta, m, b$ ] message to every server (lines 25 and 26). Upon delivering  $\pi$ 's [Observe,  $\theta, m, b$ ] message (line 29), a correct server  $\rho$  invokes  $spot(\theta, m, b)$  (line 30). The lemma immediately follows from Lemma 9 and Observation 4.

**Lemma 11.** Let  $(\theta, m, b) \in \mathcal{U}$ . Eventually, every correct server triggers  $\langle con[(\theta, m, b)]. Decide \rangle$ .

PROOF. By Lemma 10, every correct server eventually adds  $(\theta, m, b)$  to *observed*. Let  $\pi$  be a correct server. Let a denote the time when  $\pi$  adds  $(\theta, m, b)$  to *observed*. By Observation 4,  $\pi$  satisfies  $(\theta, m, b) \in observed$  forever after a.

Upon initialization,  $\pi$  sets  $proposed = \{\}$  (line 8). Moreover,  $\pi$  adds  $(\theta, m, b)$  to proposed (lines 36 and 39) only after triggering  $\langle con[(\theta, m, b)].Propose \rangle$  (lines 35 and 38). Finally,  $\pi$  never triggers  $\langle con[(\theta, m, b)].Propose \rangle$  (lines 35 and 38) unless  $(\theta, m, b) \notin proposed$  (lines 33 and 37). In summary, if  $(\theta, m, b) \in proposed$  at  $\pi$ , then  $\pi$  triggered  $\langle con[(\theta, m, b)].Propose \rangle$  exactly once.

At all times after max (a, b),  $\pi$  satisfies  $(\theta, m, b) \in observed$  and  $b < local\_time()$ . As a result,  $\pi$  eventually adds  $(\theta, m, b)$  to proposed. Indeed, let us assume, for the sake of contradiction, that  $\pi$  never adds  $(\theta, m, b)$  to proposed.  $\pi$  would forever satisfy the condition at line 37. This would result in  $\pi$  eventually triggering the condition, thus adding  $(\theta, m, b)$  to proposed (line 39).

In summary,  $\pi$  eventually adds  $(\theta, m, b)$  to proposed. As a result,  $\pi$  triggers  $\langle con[(\theta, m, b)]$ . Propose  $\rangle$  once. By the Termination property of  $con[(\theta, m, b)]$ ,  $\pi$  eventually triggers  $\langle con[(\theta, m, b)]$ . Decide  $\rangle$ , and the lemma is proved.

**Definition 2** (Filtered universe). The **filtered universe**  $\mathcal{F} \subseteq \mathcal{U}$  includes  $(\theta, m, b)$  if and only if the decision of  $con[(\theta, m, b)]$  is True.

We underline that, by Lemma 11 and the Agreement property of Consensus, Definition 2 is well-formed.

**Notation 4** (Filtered universe, time-cropped). For all  $t \in \mathbb{T}$ , we use

$$\mathcal{F}|_{\leq t} = \mathcal{F} \cap \mathcal{U}|_{\leq t}$$

**Observation 5.** Let  $\pi$  be a correct server, let  $\rho$  be a server. Upon initialization,  $\pi$  sets  $remote\_times[\rho] = -\infty$  (line 11).  $\pi$  updates  $remote\_times[\rho]$  only to a value greater or equal to  $remote\_times[\rho]$  (line 18). This means that  $remote\_times[\rho]$  is non-decreasing at  $\pi$ .

**Observation 6.** Let  $\pi$  be a correct server.  $lock\_time()$  (line 19) returns the largest t such that at least (4f+1) values in  $remote\_times$  are greater or equal to t. By Observation 5, this means that  $lock\_time()$  is non-decreasing at  $\pi$ .

**Lemma 12.** Let  $\pi$  be a correct server, let  $t \in \mathbb{T}$ . If  $|\mathcal{U}| = \infty$ , then  $\pi$  eventually satisfies lock\_time()  $\geq t$ .

PROOF. We start by noting that a correct server adds an element to *observed* (line 28) only after scheduling beat() for execution (line 27). By Lemma 10, every correct server invokes beat() infinite times. Let  $t^*$  denote any moment when every correct server satisfies  $local\_time() \ge t$ . Eventually, every correct server  $\rho$  invokes beat() after  $t^*$ . Upon doing so,  $\rho$  sends a

[Time, 
$$(t' = local\_time()) \ge t$$
]

message to  $\pi$  (lines 15 and 16). Upon delivering  $\rho$ 's [Time, t'] message (line 17)  $\pi$  sets  $remote\_times[\rho] \ge t'$  (line 18). By Observation 5,  $\pi$  eventually satisfies  $remote\_times[\rho] \ge t$  for every correct server  $\rho$ . As we assume at most f faulty servers,  $\pi$  eventually has (4f+1) values in  $remote\_times$  that are greater or equal to  $t.lock\_time()$  (line 19) returns the highest  $\hat{t}$  such that at least (4f+1) values in  $remote\_times$  are greater or equal to t (line 20). Eventually, we have  $\hat{t} \ge t$ , and the lemma is proved.

**Observation 7.** Let  $\pi$  be a correct server. Upon initialization,  $\pi$  sets  $candidates = \{\}$  (line 9).  $\pi$  never removes elements from candidates. This means candidates is non-decreasing at  $\pi$ . Equivalently,  $\pi$  satisfies  $(\theta, m, b) \in candidates$  if and only if  $\pi$  added  $(\theta, m, b)$  to candidates.

**Definition 3** (Candidates). Let  $\pi$  be a correct server.  $\pi$ 's **candidates**  $C[\pi] \subseteq (\Theta \times \mathcal{M} \times \mathbb{T})$  includes  $(\theta, m, b)$  if and only if  $\pi$  eventually adds  $(\theta, m, b)$  to *candidates*.

**Lemma 13.** Let  $\pi$  be a correct server. We have  $C[\pi] \subseteq \mathcal{U}$ .

PROOF. Let  $(\theta, m, b) \in C[\pi]$ .  $\pi$  adds  $(\theta, m, b)$  to *candidates* (line 23 only) only upon executing  $spot(\theta, m, b)$ . By Lemma 9 and Definition 1 we then have  $(\theta, m, b) \in \mathcal{U}$ , and the lemma is proved.  $\square$ 

**Notation 5** (Candidates, time-cropped). Let  $\pi$  be a correct server. For all  $t \in \mathbb{T}$ , we use

$$C[\pi]|_{\leq t} = \{(\theta, m, b) \in C[\pi] \text{ s.t. } b \leq t\}$$

**Lemma 14.** Let  $\pi$  be a correct server, let  $t \in \mathbb{T}$ . We have  $|C[\pi]|_{\leq t} < \infty$ .

PROOF. We start by noting that  $\pi$  adds  $(\theta, m, b)$  to *candidates* (line 23 only) only upon invoking  $spot(\theta, m, b)$ . By Lemma 9, at any point in time  $\pi$  must thereofore satisfy

$$|candidates| \leq |observed| + 1$$

(the equality can only hold, briefly, whenever  $\pi$  has added some  $(\theta, m, b)$  to *candidates* (line 23) but not yet to *observed* (line 28)). As a result, if  $|\mathcal{U}| < \infty$ , by Definition 1  $\pi$  always satisfies

$$|candidates| \leq |observed| + 1 \leq |\mathcal{U}| + 1 < \infty$$

and the lemma is immediately proved. Throughout the remainder of this proof, we assume  $|\mathcal{U}| = \infty$ . Let  $t^*$  denote any time when  $\pi$  satisfies  $lock\_time() > t$ . By Lemma 12,  $t^*$  is guaranteed to exist.  $\pi$  invokes spot (lines 32 and 30 only) only upon delivering a Message (line 31) or Observe (line 30) message. Moreover,  $\pi$  adds  $(\theta, m, b \le t)$  to candidates (line 23 only) only if  $\pi$  satisfies  $lock\_time() < (t \ge b)$  (line 22). By the two above, Observation 5 and Notation 5, we then have that  $|C[\pi]|_{\le t}|$  is bounded by the number of messages  $\pi$  delivers by time  $t^*$ . As  $\pi$  cannot deliver infinite messages in finite time, we have  $|C[\pi]|_{\le t}| < \infty$ , and the lemma is proved.

**Lemma 15.** Let  $(\theta, m, b) \in \mathcal{U}$  such that some correct server  $\pi$  triggers  $\langle con[(\theta, m, b)].Propose | True \rangle$ .  $\pi$  sends an [Observe,  $\theta$ , m, b] message to every server before sending any [Time,  $t \geq b$ ] to any server.

PROOF. We start by noting that, by Observation 4, if  $\pi$  satisfies  $(\theta, m, b) \in observed$ , then  $\pi$  previously sent an [Observe,  $\theta, m, b$ ] message to every server. Indeed,  $\pi$  adds  $(\theta, m, b)$  to observed (line 28 only) only after sending an [Observe,  $\theta, m, b$ ] message to every server (lines 25 and 26).

 $\pi$  triggers  $\langle con[(\theta, m, b)]$ .Propose | True $\rangle$  (line 35 only) only if, upon evaluating line 34 at some time  $t^*$ ,  $\pi$  finds that  $local\_time() < b$ . Before evaluating line 34,  $\pi$  invokes  $spot(\theta, m, b)$  (line 32). Consequently, by Lemma 9, by time  $t^*$   $\pi$  sent an [Observe,  $\theta$ , m, b] message to every server.

 $\pi$  issues a [Time,  $t \ge b$ ] (line 16 only) only if  $\pi$  satisfies  $local\_time() \ge b$ . Because a correct server's local time is non-decreasing, if  $\pi$  issues any [Time,  $t \ge b$ ] message,  $\pi$  does so after  $t^*$ : the lemma is proved.

**Lemma 16.** Let  $\pi$  be a correct server. We have  $\mathcal{F} \subseteq C[\pi]$ .

PROOF. Let  $(\theta, m, b) \in \mathcal{F}$ . Let  $\Sigma$  denote the set of correct servers that trigger  $\langle con[(\theta, m, b)]$ . Propose | True $\rangle$ . By Definition 2 and the Representative Validity property of  $con[(\theta, m, b)]$ , we have  $|\Sigma| \geq (f+1)$ . As an immediate consequence, we have  $(\theta, m, b) \in \mathcal{U}$ . Indeed, let  $\rho \in \Sigma$ . Immediately before triggering  $\langle con[(\theta, m, b)]$ . Propose | True $\rangle$  (line 35 only),  $\rho$  invokes  $spot(\theta, m, b)$  (line 32): by Lemma 9,  $(\theta, m, b) \in \mathcal{U}$ .

The lemma trivially holds true if  $\pi$  never satisfies  $lock\_time() \ge b$ . In that case, before adding  $(\theta, m, b)$  to observed (line 28 only),  $\pi$  finds that  $b > lock\_time()$  (line 22) and adds  $(\theta, m, b)$  to candidates (line 23). Throughout the remainder of this proof, we assume that server eventually satisfies  $lock\_time() \ge b$ .

Let  $t^+$  denote the moment when  $\pi$  first satisfies  $lock\_time() \ge b$ :  $\pi$  satisfies  $lock\_time() < b$  at all times before  $t^+$ . In order for  $\pi$  to satisfy  $lock\_time() \ge b$  (line 19),  $remote\_times$  must contain at least (4f+1) values that are greater or equal to b. This means that the set  $\Phi \subseteq \Pi$  that includes  $\sigma$  if and only if  $remote\_times[\sigma] > b$  at  $\pi$  at time  $t^+$  contains at least (4f+1) elements.

By the pigeonhole principle,  $\Sigma$  and  $\Phi$  intersect in at least one correct server  $\rho$ .  $\pi$  sets  $remote\_times[\rho] \ge b$  (line 18 only) only upon delivering a [Time,  $t \ge b$ ] message from  $\rho$  (line 17). This means that, by time  $t^+$ ,  $\pi$  delivered a [Time,  $t \ge b$ ] message from  $\rho$ . By Lemma 15 and the FIFO property of FIFO links,  $\pi$  does not deliver any [Time,  $t \ge b$ ] message from  $\rho$  before delivering  $\rho$ 's [Observe,  $\theta$ , m, b] message. In summary,  $\pi$  delivers a [Observe,  $\theta$ , m, b] message before  $t^*$ . Upon doing so (line 29),  $\pi$  invokes  $spot(\theta, m, b)$  (line 30), finds that  $lock\_time() < b$  (line 22) and adds  $(\theta, m, b)$  to candidates (line 23). This proves  $(\theta, m, b) \in C[\pi]$  and concludes the lemma.  $\square$ 

**Corollary 1.** For all  $t \in \mathbb{T}$  we have  $|\mathcal{F}|_{\leq t} < \infty$ .

**PROOF.** By Definitions 2 and 3 and Lemmas 14 and 16, for any correct server  $\pi$  we have

$$|(\mathcal{F}|_{\leq t} \subseteq \mathcal{C}[\pi]|_{\leq t})| < \infty$$

**Corollary 2.** One and only one strictly increasing sequence  $\mathcal F$  exists such that

$$\forall (\theta, m, b) \in \mathcal{F}, \exists n \text{ s.t. } \mathcal{F}_n = (\theta, m, b)$$

PROOF. It follows immediately from Corollary 1 and Lemmas 5 and 6.

**Notation 6** (Filtered universe as a sequence). We use  $\mathcal{F}$  to interchangeably denote the filtered universe as a set (Definition 2) and as a strictly increasing enumeration (Corollary 2).

**Definition 4** (Order calls). Let  $\pi$  be a correct server.  $\pi$ 's sequence of **order calls** 

$$O[\pi] \in (\Theta \times \mathcal{M} \times \mathbb{T})^{\leq \infty}$$

captures the sequence of invocations  $\pi$  makes to the *order* procedure (line 47).

For example, if  $\pi$  invokes *order* exactly three times,  $order(\theta, m, b)$  first,  $order(\theta', m', b')$  second and  $order(\theta'', m'', b'')$  third, then

$$O[\pi] = [(\theta, m, b), (\theta', m', b'), (\theta'', m'', b'')]$$

**Lemma 17.** Let  $\pi$  be a correct server.  $O[\pi]$  is strictly increasing.

PROOF. Let  $k,n \leq |O[\pi]|$  such that k < n. Let  $(\theta,m,b) = O[\pi]_k$ , let  $(\theta',m',b') = O[\pi]_n$ . Immediately after invoking  $order(\theta,m,b)$  (line 45),  $\pi$  sets  $last\_processed = (\theta,m,b)$  (line 46). By Observation 8, when  $\pi$  invokes  $order(\theta',m',b')$  we still have  $last\_order \geq (\theta,m,b)$ .  $\pi$  invokes  $order(\theta',m',b')$  (line 45), however, only if  $(\theta',m',b') > last\_processed$  (line 43). To summarize, when  $\pi$  invokes  $order(\theta',m',b')$ , we have

$$(\theta', m', b') > last processed \geq (\theta, m, b)$$

which proves  $O[\pi]_k < O[\pi]_n$  and concludes the lemma.

**Lemma 18.** Let  $\pi$  be a correct server, let  $n \leq |O[\pi]|$ . We have  $O[\pi]_n \in \mathcal{F}$ .

PROOF.  $\pi$  invokes  $order(\theta, m, b)$  (line 45 only) only if  $decisions[(\theta, m, b)] = True$  (line 44). Upon initialization,  $\pi$  sets  $decisions = \{\}$  (line 12).  $\pi$  sets  $decisions[(\theta, m, b)] = True$  (line 42 only) only upon triggering  $\langle con[(\theta, m, b)]$ . Decide | True $\rangle$  (line 40). The lemma follows immediately from Definition 2.

**Observation 8.** Let  $\pi$  be a correct server.  $\pi$  updates  $last\_processed$  to  $(\theta, m, b)$  (line 46 only) only if  $(\theta, m, b) > last\_processed$  (line 43). This means that  $last\_processed$  is non-decreasing at  $\pi$ .

**Lemma 19.** Let  $\pi$  be a correct server, let  $(\theta, m, b) \in C[\pi]$ . Upon adding  $(\theta, m, b)$  to candidates,  $\pi$  satisfies  $(\theta, m, b) > last$  delivered.

PROOF. Let  $(\theta^*, m^*, b^*)$  denote the value of  $last\_delivered$  at  $\pi$  when  $\pi$  adds  $(\theta, m, b)$  to candidates. The lemma trivially holds if  $b^* = -\infty$  (line 13). Throughout the remainder of this proof, we assume  $b^* > -\infty$ . Upon setting  $last\_processed = (\theta^*, m^*, b^*)$  (line 46 only),  $\pi$  satisfied  $b^* \leq lock\_time()$  (line 43). When  $\pi$  adds  $(\theta, m, b)$  to candidates (line 23 only), however,  $\pi$  satisfies  $b > lock\_time()$  (line 22). By Observation 6, we then have  $b > b^*$ , and the lemma immediately follows from Assumption 1.

**Lemma 20.** Let  $\pi$  be a correct server. Let  $(\theta, m, b) \in C[\pi]$ .  $\pi$  does not satisfy last\_processed  $\geq (\theta, m, b)$ , before invoking order $(\theta, m, b)$ .

PROOF. Let us assume  $\pi$  eventually satisfies  $last\_processed \ge (\theta, m, b)$ . Let  $(\theta^+, m^+, b^+)$  denote the first value  $last\_processed$  takes at  $\pi$  such that  $(\theta^+, m^+, b^+) \ge (\theta, m, b)$ . Let  $(\theta^-, m^-, b^-)$  denote the value  $last\_processed$  had immediately before being updated to  $(\theta^+, m^+, b^+)$ . We have

$$(\theta^-, m^-, b^-) < (\theta, m, b) \le (\theta^+, m^+, b^+)$$

Noting that  $\pi$  initializes  $last\_processed$  to  $(\bot, \bot, -\infty < b)$  (line 13),  $\pi$  can set  $last\_processed = (\theta^+, m^+, b^+)$  (line 46 only) only if

$$(\theta^+, m^+, b^+) = \min\{(\theta', m', b') \in candidates \text{ s.t. } (\theta', m', b') > (\theta^-, m^-, b^-)\}$$
(4)

(line 43).

By Definition 3,  $\pi$  eventually adds  $(\theta, m, b)$  to *candidates*. By Lemma 19, when  $\pi$  does so,  $\pi$  satisfies *last\_processed* <  $(\theta, m, b)$ . As such,  $\pi$  satisfies  $(\theta, m, b) \in candidates$  before setting

 $last\_processed = (\theta^+, m^+, b^+), \pi$ . By Equation 4, this proves  $(\theta^+, m^+, b^+) \le (\theta, m, b)$ . In summary, we have

$$(\theta^+, m^+, b^+) \ge (\theta, m, b)$$
$$(\theta^+, m^+, b^+) \le (\theta, m, b)$$

Which proves that  $\pi$  eventually sets  $last\_processed = (\theta, m, b)$ .  $\pi$  does so (line 43) only when  $(\theta, m, b) \in decisions$ . Because  $(\theta, m, b) \in \mathcal{F}$ , we must then have  $decisions[(\theta, m, b)] = \mathsf{True}$ . This means that, immediately before setting  $last\_processed = (\theta, m, b)$ ,  $\pi$  satisfies the condition at line 44. As a result,  $\pi$  invokes  $order(\theta, m, b)$  (line 45), and the result is proved.

**Lemma 21.** Let  $\pi$  be a correct server. Let  $(\theta, m, b) \in \mathcal{F}$ . For some n, we have  $O[\pi]_n = (\theta, m, b)$ .

PROOF. By Definition 4, the lemma reduces to proving that  $\pi$  eventually invokes  $order(\theta, m, b)$ . We start by noting that, unless  $last\_processed = (\bot, \bot, -\infty)$  (line 13), we have  $last\_processed \in C[\pi]$ . Indeed,  $\pi$  sets  $last\_processed = (\theta', m', b')$  (line 46 only) only if  $(\theta', m', b') \in candidates$  (line 43). Moreover, by Observation 8,  $last\_processed$  is non-decreasing. Finally, because by Lemma 14 we have  $|C[\pi] \le b| < \infty$ ,  $\pi$  can update the value of  $last\_processed$  only a finite number of times before  $last\_processed \ge (\theta, m, b)$ . Every time  $\pi$  triggers the condition at line 43,  $last\_processed$  is updated to a new value (line 46). At any point in time, let

$$(\theta',m',b') = \min\left(\hat{\theta},\hat{m},\hat{b}\right) \in candidates \text{ s.t. } \left(\hat{\theta},\hat{m},\hat{b}\right) > last\_processed$$

(line 43). As long as  $last\_processed < (\theta, m, b)$ ,  $(\theta', m', b')$  is guaranteed to exist. By Lemma 11,  $\pi$  eventually satisfies  $(\theta', m', b') \in decisions$ . By Lemma 12,  $\pi$  eventually satisfies  $b' \leq lock\_time()$ . This means that the condition at line 43 is eventually guaranteed to trigger, and  $\pi$  will update  $last\_processed$  to a new value. In summary,  $\pi$  keeps updating  $last\_processed$  to a new value as long as  $last\_processed < (\theta, m, b)$ . Having done so a finite number of times,  $\pi$  eventually satisfies  $last\_processed \geq (\theta, m, b)$ . Moreover, by Lemma 16, we have  $(\theta, m, b) \in C[\pi]$ . As a result, by Lemma 20,  $\pi$  eventually invokes  $order(\theta, m, b)$ , and the lemma is proved.

**Corollary 3.** Let  $\pi$  be a correct server. We have  $O[\pi] = \mathcal{F}$ .

PROOF. It follows immediately from Lemmas 17, 18, 21 and 6.

**Corollary 4.** Let  $\pi$ ,  $\pi'$  be correct servers. We have  $O[\pi] = O[\pi']$ .

PROOF. It follows immediately from Corollary 3.

### **Theorem 8.** Flutter satisfies Agreement and Total Order.

PROOF. A correct server triggers  $\langle tob. Deliver \rangle$  (line 49 only) only upon executing *order* (line 47). Procedure *order* implements a deterministic state machine, using only *delivered* as state: *order* reads from / writes to only *delivered*, *delivered* is read from / written to only by *order*. Moreover, every correct server initializes *delivered* to the same value (line 10). Finally, by Corollary 4, every correct server issues the same sequence of invocations to *order*. As a result, every correct server triggers the same sequence of  $\langle tob. Deliver \rangle$  events, and the theorem is proved.

### **B.5** Validity

**Lemma 22.** Let  $\pi$  be a correct server, let  $\theta$  be a client, let  $m \in \mathcal{M}$ . If  $\pi$  eventually invokes order  $(\theta, m, b)$  for any  $b \in \mathbb{T}$ , then  $\pi$  eventually triggers  $\langle tob.Deliver | \theta, m \rangle$ .

PROOF. By Observation 2, delivered is initially empty at  $\pi$ .  $\pi$  adds  $(\theta, m)$  to delivered (line 50 only) only after triggering  $\langle tob. Deliver \mid \theta, m \rangle$  (line 49). Upon invoking  $order(\theta, m, b)$  (line 47),  $\pi$  either satisfies  $(\theta, m) \in delivered$  or  $(\theta, m) \notin delivered$ . If  $(\theta, m) \in delivered$ , then  $\pi$  already triggered  $\langle tob. Deliver \mid \theta, m \rangle$ . If  $(\theta, m) \notin delivered$  (line 18), then  $\pi$  triggers  $\langle tob. Deliver \mid \theta, m \rangle$  (line 49), and the lemma is proved.

**Corollary 5.** Let  $(\theta, m, b) \in \mathcal{F}$ . Every correct server eventually triggers  $\langle tob.Deliver \mid \theta, m \rangle$ .

PROOF. It follows immediately from Lemma 21, Definition 4 and Lemma 22.

**Lemma 23.** Let  $\theta$  be a correct client, let  $m \in \mathcal{M}$ , let  $K \in \mathbb{N}$  such that  $\theta$  invokes submit $(m, \_)$  at least K times. Let  $k \le K$ . The k-th time  $\theta$  invokes submit $(m, \_)$ ,  $\theta$  invokes submit(m, k - 1).

PROOF. We prove the lemma by induction on k. Let assume  $K \ge 1$ . Upon initialization,  $\theta$  sets  $submissions = \{\}$  (line 9).  $\theta$  sets submission[m] (line 15 only) only upon executing  $submit(m, \_)$  (line 11). This means that, before ever invoking  $submit(m, \_)$ ,  $\theta$  satisfies  $m \notin submissions$ . As a consequence,  $\theta$  cannot invoke  $order(m, \_)$  for the first time from line 21, as that would require  $m \in submissions$  (line 20). The only other possibility is that  $\theta$  first invokes  $order(m, \_)$  from line 17. We underline that  $\theta$  does so only upon triggering  $\langle tob$ .Broadcast  $|m\rangle$  (this will be useful later in the proof). Upon invoking  $order(m, \_)$  from line 17,  $\theta$  invokes order(m, 0), proving the induction for k = 1.

Let us assume that the induction holds for some k < K: upon invoking  $submit(m, \_)$  for the k-th time,  $\theta$  invoked submit(m, k - 1). Because  $\theta$  first invoked  $submit(m, \_)$  upon triggering  $\langle tob$ .Broadcast  $| m \rangle$ ,  $\theta$  cannot invoke  $submit(m, \_)$  for the (k + 1)-th time from line 17, as no correct client triggers  $\langle tob$ .Broadcast  $| m \rangle$  more than once. The only other possibility is that  $\theta$  invokes  $order(m, \_)$  for the (k + 1)-th time from line 21. By induction hypothesis, upon last invoking  $submit(m, \_)$  (line 11),  $\theta$  set  $submissions[m] = (k - 1, \_)$  (line 15). Because  $\theta$  only sets submissions[m] upon executing  $submit(m, \_)$ , when  $\theta$  invokes  $submit(m, \_)$  for the (k + 1)-th time,  $\theta$  still satisfies  $submissions[m] = ((k - 1), \_)$ . This proves (line 21) that the (k + 1)-th time  $\theta$  invokes  $submit(m, \_)$ , client invokes submit(m, k). By induction, the lemma is proved.

**Lemma 24.** Let  $\theta$  be a correct client, let  $m \in \mathcal{M}$  such that  $\theta$  triggers  $\langle tob.Broadcast \mid m \rangle$ . If no correct server ever triggers  $\langle tob.Deliver \mid \theta, m \rangle$ , then  $\theta$  invokes submit  $(m, \_)$  an infinite number of times.

PROOF. Let us assume that no correct server ever triggers  $\langle tob. \text{Deliver} \mid \theta, m \rangle$ . We prove by induction that, for all  $k \in \mathbb{N}$ ,  $\theta$  invokes  $submit(m, \_)$  at least k times. Upon triggering  $\langle tob. \text{Broadcast} \mid m \rangle$  (line 16),  $\theta$  invokes  $submit(m, \_)$  (line 17). This proves the induction for k = 1.

Let us assume that induction holds for some  $k \geq 1$ . Let submit(m,r) capture  $\theta$ 's k-th  $submit(m,\_)$  invocation. Upon executing submit(m,r) (line 11),  $\theta$  sends the same [Message, m, b] to every server (lines 13 and 14), for some  $b \in \mathbb{T}$  (line 12).  $\theta$  then sets submissions[m] = (r,b) (line 15). Noting that  $\theta$  updates submissions[m] (line 15) only upon executing  $submit(m,\_)$  (line 11), submission[m] stays unchanged until  $\theta$  invokes  $submit(m,\_)$  for the (k+1)-th time.

Upon delivering  $\theta$ 's [Message, m, b] message (line 31), every correct server triggers  $\langle con[\theta, m, b]$ .Propose $\rangle$ . By the Termination property of  $con[(\theta, m, b)]$  and Corollary 5, every correct server eventually triggers  $\langle con[(\theta, m, b)]$ .Decide | False $\rangle$ . Upon doing so (line 40) every correct server sends a [Decision, m, b, False] back message to  $\theta$  (line 41).

Let  $\pi$  be a correct server. Upon delivering a [Decision, m, b, False] message from  $\pi$  (line 18),  $\theta$  sets  $decisions[(m,b,\pi)] = \text{False}$  (line 19).  $\pi$  updates  $decisions[(m,b,\pi)]$  to some  $v \in \mathbb{B}$  (line 19 only) only upon delivering a [Decision, m, b, v] message from  $\pi$  (line 18). In turn,  $\pi$  sends a [Decision, m, b, v] (line 41 only) only upon triggering  $\langle con[(\theta, m, b)].Decide \mid v \rangle$  (line 40). By the No Duplication property of  $con[(\theta, m, b)]$ , we then have that  $\theta$  never updates  $decisions[(m, b, \pi)]$  again.

As we assume at least (f + 1) correct servers, eventually  $\pi$  satisfies

$$|\pi \text{ s.t. } decisions[(m, b, \pi)] = \text{False}| \ge (f + 1)$$

Because  $\theta$  satisfies submissions[m] = (r, b) until  $\theta$  invokes  $submit(m, \_)$  for the (k + 1)-th time,  $\theta$  eventually triggers the condition at line 20, and invokes  $submit(m, \_)$  (line 21). This proves that the induction holds for (k + 1) and concludes the lemma.

**Corollary 6.** Let  $\theta$  be a correct client, let  $m \in \mathcal{M}$  such that  $\theta$  triggers  $\langle tob.Broadcast \mid m \rangle$ . If no correct server ever triggers  $\langle tob.Deliver \mid m \rangle$ , then  $\theta$  eventually invokes submit(m, r) for every  $r \in \mathbb{N}$ .

PROOF. It follows immediately from Lemmas 23 and 24.

#### **Theorem 9.** Flutter satisfies Validity.

PROOF. Let  $\theta$  be a correct client, let  $m \in \mathcal{M}$  such that  $\theta$  triggers  $\langle tob$ .Broadcast  $| m \rangle$ . Let us assume, for the sake of contradiction, that no correct server ever triggers  $\langle tob$ .Deliver  $| \theta, m \rangle$ . By Corollary 6,  $\theta$  eventually invokes submit(m, r) for every  $r \in \mathbb{N}$ .

Let  $r^* \in \mathbb{N}$  such that

$$2^{r^*}>\frac{(\Delta+2\Psi)}{\hat{\Delta}}$$

At some time  $t \in \mathbb{T}$ ,  $\theta$  invokes  $submit(m, r^*)$  (line 11). As we assume partial synchrony, and noting that  $\epsilon > 0$  (line 7), upon evaluating line 12  $\theta$  sets  $b > \left(t - \Psi + 2^{r^*}\hat{\Delta}\right)$ .  $\theta$  then sends a [Message, m, b] message to every server (lines 13 and 14).

Let  $\pi$  be any correct server.  $\pi$  delivers  $\theta$ 's [Message, m, b] message by time  $(t + \Delta)$ . When  $\pi$  does so (line 31),  $\pi$ 's local time is at most  $(t + \Delta + \Psi)$ . As a result, upon evaluating line 34,  $\pi$  finds

$$b > t - \Psi + 2^{r^*} \hat{\Delta} > t + \Delta + \Psi \ge local\_time()$$

and triggers  $\langle con[(\theta, m, b)]$ . Propose | True $\rangle$  (line 10). By the Representative Validity property of  $con[(\theta, m, b)]$ , every correct server eventually triggers  $\langle con[(\theta, m, b)]$ . Decide | True $\rangle$ . By Corollary 5, every correct server eventually triggers  $\langle con$ . Deliver |  $\theta$ ,  $m \rangle$ . This contradicts no correct server ever triggering  $\langle con$ . Deliver |  $\theta$ ,  $m \rangle$  and proves the theorem.

# **B.6** Good-case Latency

All results in this section rest on the good-case assumptions introduced in §2.3. We also assume that all Representative Binary Consensus instances in *con* are implemented by Blink.

**Lemma 25.** Let  $(\theta, m, b) \in \mathcal{U}$ .  $\theta$  eventually issues a [Message, m, b] message.

PROOF. Let  $\pi$  denote the server that first adds  $(\theta, m, b)$  to observed.  $\pi$  does so (line 28 only) only upon executing  $spot(\theta, m, b)$  (line 21).  $\pi$  invokes  $spot(\theta, m, b)$  only from lines 32 and 30. If  $\pi$  invokes  $spot(\theta, m, b)$  from line 32, then  $\pi$  delivered a [Message, m, b] from  $\theta$  (line 31) and the lemma trivially holds true.

Let us assume, for the sake of contradiction, that  $\pi$  invokes  $spot(\theta, m, b)$  from line 30 instead.  $\pi$  does so upon delivering an [Observe,  $\theta$ , m, b] message from some server  $\rho$  (line 29). Instantaneously after issuing an [Observe,  $\theta$ , m, b] message (line 26 only)  $\rho$  adds ( $\theta$ , m, b) to observed. This

contradicts  $\pi$  being the first server to add  $(\theta, m, b)$  to observed, proves that  $\pi$  invokes  $spot(\theta, m, b)$  from line 32, and concludes the lemma.

**Lemma 26.** Let  $\theta$  be a client, let  $m \in \mathcal{M}$ , let  $b \in \mathbb{T}$  such that  $\theta$  issues a [Message, m, b] message. Every server delivers [Message, m, b] by time  $(b - \epsilon)$ .

PROOF.  $\theta$  issues a [Message, m, b] message (line 14 only) only upon executing submit(m, r) (line 11) for some  $r \ge 0$ . Let t denote the time when  $\theta$  invokes submit(m, r). Upon doing so (line 11),  $\theta$  instantaneously evaluates

$$b = t + 2^r \hat{\Delta} + \epsilon = t + 2^r \Delta + \epsilon \ge t + \Delta + \epsilon$$

(line 12) and sends a [Message, m, b] to every server (lines 13 and 14). As a result, every server delivers [Message, m, b] by time  $(t + \Delta) = (b - \epsilon)$ , which proves the lemma.

**Lemma 27.** Every server always satisfies lock time()  $\leq$  local\_time().

PROOF. Let  $\pi$  be a server, let  $t \in \mathbb{T}$ . Let us assume, for the sake of contradiction, that at time t  $\pi$  satisfies  $lock\_time() > (local\_time() = t)$ . This means (line 20) that at least (4f + 1) values in  $remote\_times$  are greater than t. Let  $\rho$  be any server such that, at time t,  $\pi$  satisfies  $remote\_times[\rho] > t$ .  $\pi$  sets  $remote\_times[\rho] > t$  (line 18 only) only upon delivering a [Time, t' > t] message from  $\rho$  (line 17). This means that, by time t,  $\rho$  issues a [Time, t'] message. Noting that  $\rho$  only issues a [Time, t'] message at time t' (line 16 only), however,  $\rho$  cannot issue a [Time, t'] message by t < t'. We thus reach a contradiction, and the lemma is proved.

**Lemma 28.** Let  $\pi$  be a server. Let  $\theta$  be a client, let  $m \in \mathcal{M}$ , let  $b \in \mathbb{T}$  such that  $\pi$  adds  $(\theta, m, b)$  to proposed before time b.  $\pi$  triggers  $\langle con[(\theta, m, b)].Propose | True \rangle$ .

PROOF.  $\pi$  adds  $(\theta, m, b)$  to proposed (lines 36 and 39 only) only after triggering  $\langle con[(\theta, m, b)]$ .Propose $\rangle$  (lines 35 and 38). This means that  $\pi$  triggers  $\langle con[(\theta, m, b)]$ .Propose $\rangle$  before time b.  $\pi$ , however, triggers  $\langle con[(\theta, m, b)]$ .Propose | False $\rangle$  (lines 35 and 38 only) only if  $local\_time() \geq b$  (lines 34 and 37). This proves that  $\pi$  triggers  $\langle con[(\theta, m, b)]$ .Propose | True $\rangle$  and concludes the lemma.

**Lemma 29.** Let  $(\theta, m, b) \in \mathcal{U}$ . By time  $(b - \epsilon)$ , every server adds  $(\theta, m, b)$  to candidates and triggers  $\langle con[(\theta, m, b)]. Propose \mid True \rangle$ .

PROOF. Let  $\pi$  be a server. By Lemmas 25 and 26,  $\pi$  delivers a [Message, m, b] message from  $\theta$  at some time  $t \leq (b - \epsilon)$ . Upon doing so (line 31),  $\pi$  instantaneously invokes  $spot(\theta, m, b)$  (line 32, observes that

$$b \ge t + \epsilon > local time() \ge lock time()$$

(line 22) and adds  $(\theta, m, b)$  to candidates (line 23).

Upon returning from  $spot(\theta, m, b)$ ,  $\rho$  instantaneously moves on to check if  $(\theta, m, b) \in proposed$ . If  $(\theta, m, b) \in proposed$ , then by Lemma 28  $\rho$  triggered  $\langle con[(\theta, m, b)]$ . Propose | True $\rangle$ . If  $(\theta, m, b) \notin proposed$  (line 33), then  $\rho$  verifies

$$b \ge t + \epsilon > local time$$

(line 34 and instantaneously triggers  $\langle con[(\theta, m, b)]$ .Propose | True $\rangle$  (line 35). This proves that  $\pi$  triggers  $\langle con[(\theta, m, b)]$ .Propose | True $\rangle$  by time  $(b - \epsilon)$  and concludes the lemma.

**Corollary 7.** Let  $(\theta, m, b) \in \mathcal{U}$ . By time  $(b + \Delta - \epsilon)$ , every server triggers  $\langle con[(\theta, m, b)].Decide \mid True \rangle$ .

PROOF. It follows immediately from Lemma 29 and Theorem 5.

**Lemma 30.** Let  $(\theta, m, b) \in \mathcal{U}$ . By time  $(b + \Delta)$ , every server satisfies lock\_time()  $\geq b$ .

PROOF. We start by noting that, upon adding  $(\theta, m, b)$  to *observed* (line 28 only), a correct server schedules *beat*() for execution at time *b* (line 27).

Let  $\rho$  be a server. By Lemmas 25 and 26,  $\rho$  delivers a [Message, m, b] message from  $\theta$  by time  $(b-\epsilon)$ . Upon doing so (line 31),  $\rho$  instantaneously invokes  $spot(\theta, m, b)$  (line 32). By Lemma 9,  $\rho$  adds  $(\theta, m, b)$  to observed before time b. As a result,  $\rho$  executes beat() at time b. Upon doing so (line 14),  $\rho$  sends a [Time, b] message to every server (lines 13 and 14). In summary, at time b, every server sends a [Time, b] message to every server.

Let  $\pi$  be a server. By time  $(b+\Delta)$ ,  $\pi$  delivers a [Time, b] message from every server. Upon doing so (line 17),  $\pi$  instantaneously sets every value in  $remote\_times$  to a value greater or equal to b (line 18). Having done so, by Observation 5,  $\pi$  forever satisfies  $remote\_times[\rho] \geq b$  for every server  $\rho$ . Because  $lock\_time()$  (line 19) returns a value greater or equal to b if at least (4f+1) values in  $remote\_times$  are greater or equal to b (line 20),  $\pi$  forever satisfies  $lock\_time() \geq b$ , and the lemma is proved.

**Lemma 31.** Let  $(\theta, m, b) \in \mathcal{U}$ . By time  $(b + \Delta)$ , every server triggers  $\langle tob.Deliver \mid \theta, m \rangle$ .

PROOF. We start by noting that, by Lemma 29 and Corollary 7, we have

$$\mathcal{U} = C[\pi] = \mathcal{F}$$

Moreover, again by Lemma 29 and Corollary 7, by time  $(b + \Delta)$   $\pi$  satisfies

$$C[\pi]|_{\leq b} \subseteq candidates$$

$$C[\pi]|_{\leq b} \subseteq decisions$$

Finally, by Lemma 30, by time  $(b + \Delta) \pi$  satisfies

$$lock\ time() \ge b$$

As such, until *last\_processed*  $\geq (\theta, m, b)$ ,  $\pi$  keeps satisfying the condition at line 43.

Unless  $last\_processed = (\bot, \bot, -\infty)$  (line 13), we have  $last\_processed \in C[\pi]$ . Indeed,  $\pi$  sets  $last\_processed = (\theta', m', b')$  (line 46) only if  $(\theta', m', b') \in candidates$  (line 43). Moreover, by Observation 8,  $last\_processed$  is non-decreasing. Finally, because by Lemma 14 we have  $|C[\pi]|_{\le b}| < \infty$ ,  $\pi$  can update the value of  $last\_processed$  only a finite number of times before  $last\_processed \ge (\theta, m, b)$ .

To summarize, by time  $(b + \Delta)$ ,  $\pi$  keeps instantaneously triggering the condition at line 43 until  $last\_processed \geq (\theta, m, b)$ . Every time  $\pi$  triggers the condition at line 43,  $\pi$  updates  $last\_processed$  (line 46) to a larger element of  $C[\pi]$  (line 43). Having instantaneously done so a finite number of times,  $\pi$  satisfies  $last\_processed \geq (\theta, m, b)$ . As such, by Lemma 20,  $\pi$  instantaneously invokes  $order(\theta, m, b)$ . By Lemma 22,  $\pi$  also instantaneously triggers  $\langle tob$ . Deliver  $|\theta, m\rangle$ , and the lemma is proved.

**Theorem 10.** Let  $\theta$  be a client, let  $m \in \mathcal{M}$ , let  $t \in \mathbb{T}$  such that  $\theta$  triggers  $\langle tob.Broadcast \mid m \rangle$  at time t. Every server triggers  $\langle tob.Deliver \mid \theta, m \rangle$  by time  $(t + 2\Delta + \epsilon)$ .

PROOF. Upon triggering  $\langle tob$ .Broadcast  $\mid m \rangle$  (line 16),  $\theta$  instantaneously invokes submit(m, 0) (line 17), thus sending a [Message, m, b] message to every server, with

$$b = t + \hat{\Delta} + \epsilon = t + \Delta + \epsilon$$

(lines 13 and 14). Upon delivering  $\pi$ 's [Message, m, b] message (line 31), a server invokes  $spot(\theta, m, b)$  (line 32). By Lemma 9 and Definition 1 we then have  $(\theta, m, b) \in \mathcal{U}$ , and the theorem follows from Lemma 31.

#### B.7 Denial of Service

Flutter spawns an instance of Representative Binary Consensus for every message and bet that a client submits to Total-Order Broadcast. Such an amplification makes Flutter vulnerable to denial-of-service attacks, wherein a malicious client overwhelms the system with spurious or useless requests. While a full discussion of these attacks is beyond the scope of this theoretical paper, in this section we briefly argue that Flutter's vulnerability to denial of service is not qualitatively different from that of other Total-Order Broadcast solutions, and that the same mitigation strategies that apply to those also apply to Flutter.

One consensus per broadcast. It is a fundamental result that Total-Order Broadcast is as powerful a primitive as Consensus [19, 36]. Indeed, implementing Consensus using Total-Order Broadcast is fairly straightforward: each process broadcast its proposal; upon delivering (4f+1) proposals, a process decides the majority proposal, resorting to a deterministic tiebreak in the case of a draw. As such, we believe that no Total-Order Broadcast implementation can deliver a message without solving a problem equivalent to Consensus.

Batching. Total-Order Broadcast implementations in systems literature employ a variety of batching techniques to amortize the cost of Consensus [16, 18, 33, 84]. Broadly speaking, batching involves multiple clients entrusting their messages to the same *broker*, which packages them for bulk delivery by the servers. Batched solutions usually offer a trade-off between latency and efficiency, as brokers wait to collect multiple messages in the same batch. At a similar cost in terms of latency, Flutter can also accommodate batching. A batched variant of Flutter would shift to brokers the responsibility of selecting a batch's bet; clients would authenticate their messages with signatures or symmetric message authentication codes.

Broadcast vs. broadcast attempt. A noteworthy design difference between Flutter and other Total-Order Broadcast implementations is that Flutter spawns an instance of Representative Binary Consensus every time a client attempts to broadcast a message. Upon failing to get its message delivered, a client updates its bet and tries again, thus triggering a new instance of Representative Binary Consensus. Such a difference, however, does not qualitatively affect Flutter's vulnerability to denial of service. Even against a system that guarantees one delivery per Consensus instance, a malicious client could simply broadcast messages that are malformed, invalid or semantically "useless". In doing so, the client would still force the expenditure of a Consensus instance for every message it disseminates, while also pulling the application layer into the computation required to process or discard the message.

Client authentication and rate limiting. As we discussed in §2.1, Flutter assumes a permissionless set of clients. In settings where denial-of-service attacks are an issue, such an assumption can be dangerous. It is worth underlying, however, that Flutter trivially generalizes to the permissioned setting. As links are authenticated, servers can easily ignore messages from unauthorized clients [45]. Similarly, Flutter is compatible with rate-limiting [45] (e.g., each client gets to broadcast once per minute). Such systems-oriented mechanisms, however, are beyond the scope of this theoretical paper.

Exponential backoff. Correct Flutter clients double their bet margin every time their messages are rejected. This behavior can also be forced onto malicious clients. To mitigate denial-of-service attacks, servers could force a client that failed to broadcast n times to issue bets spaced by at least  $2^n$  units of time. Such a simple technique quickly neutralizes any mis-betting client.

*Leader denial-of-service.* Finally, it is worth underlining that Flutter's leaderless nature naturally sidesteps the scenario where an attacker overwhelms with requests whichever server is currently the leader, repeatedly causing expensive suspicion and re-election.

#### C QUASI-OPTIMALITY OF FLUTTER

In this section, we prove that Flutter's good-case latency is **quasi-optimal**, meaning that no Total-Order Broadcast implementation can undercut Flutter's good-case latency by any finite amount. As we proved in Appx. B.6, in the good case (see §2.3) Flutter attains a broadcast-to-delivery latency of  $(2\Delta + \epsilon)$ , where  $\Delta$  represents the network's message delay and  $\epsilon$  is an arbitrarily small constant (e.g., the smallest unit of time that a computer can represent). Here, we prove Flutter's quasi-optimality by showing that no Total-Order Broadcast implementation can achieve a latency smaller than  $2\Delta$ , not even in the good case. Whether or not a good-case latency of *exactly*  $2\Delta$  is achievable remains an open problem, albeit one with limited practical implications, as Flutter's good-case latency is already arbitrarily close to  $2\Delta$ .

The impossibility of Total-Order Broadcast in less than two message delays is fairly intuitive. Let us consider the example of a client broadcasting some message m at some time t. Let  $\pi$  be a correct server. In order to deliver m before  $(t+2\Delta)$ ,  $\pi$  would have to deliver m based only on the messages it directly receives from  $\theta$ , thus foregoing any form of coordination with the other servers. Indeed, two message delays are required for  $\pi$  to simply determine whether or not the other servers received m from  $\theta$ : one for  $\theta$  to disseminate m to the other servers, and one for the other servers to report their observations to  $\pi$ .

**Definition 5** (Bounded-latency Total-Order Broadcast implementation). Let  $\mathcal{A}$  be an implementation of Total-Order Broadcast under the assumptions presented in §2.1.  $\mathcal{A}$  is T-bounded if and only if, for every execution  $\mathcal{E}$  of  $\mathcal{A}$  abiding by the good-case assumptions presented in §2.3, if a client  $\theta$  broadcasts a message m by time t, then every server delivers m by time t.

We underline that, by Definition 5 and Theorem 10, Flutter is  $(2\Delta + \epsilon)$ -bounded for every  $\epsilon > 0$ .

**Theorem 11.** Let  $T < 2\Delta$ . No Total-Order Broadcast implementation is T-bounded.

PROOF. Let us assume towards a contradiction (see Definition 5) that some T-bounded implementation  $\mathcal A$  of Total-Order Broadcast does exists. We can reach a contradiction using indistinguishable executions.

Let  $\mathcal{E}$ ,  $\mathcal{E}'$  be executions of  $\mathcal{A}$ , abiding by the good-case assumptions presented in §2.3, such that: the delay of every message in  $\mathcal{E} / \mathcal{E}'$  is exactly  $\Delta$ ; throughout all  $\mathcal{E}$  (resp.,  $\mathcal{E}'$ ), a single client  $\theta$  broadcasts a single message m (resp.,  $m' \neq m$ ) at some time  $t_0$ . Let  $\pi$ ,  $\pi' \neq \pi$  be servers. By Definition 5, in  $\mathcal{E}$  (resp.,  $\mathcal{E}'$ ),  $\pi$  (resp.,  $\pi'$ ) delivers m (resp., m') as first and only message (see §2.2) at some time t (resp., t'), with t,  $t' \leq (t_0 + T)$ .

We start by noting that  $\mathcal{E}$  and  $\mathcal{E}'$  are identical up to  $t_0$ . Indeed, prior to  $t_0$ , no process is provided with any input in either execution, and  $\mathcal{A}$  unfolds deterministically: the processes issue the same messages at the same times, each message is delivered with the same delay, resulting in identical executions for  $\mathcal{E}$  and  $\mathcal{E}'$ . Moreover, between  $t_0$  and  $(t_0 + \Delta)$ , the execution of every process other than  $\theta$  is identical in  $\mathcal{E}$  and  $\mathcal{E}'$ . Indeed, before  $(t_0 + \Delta)$ , a process receives only messages that were sent before  $t_0$ . By the above, this means that every process other than  $\theta$  receives the same messages at the same times, unfolding deterministically and identically in both  $\mathcal{E}$  and  $\mathcal{E}'$ . Finally, let  $\chi$  be any process other than  $\theta$ . Before  $(t_0 + 2\Delta)$ ,  $\pi$  (resp.,  $\pi'$ ) receives the same sequence of messages from  $\chi$  in both  $\mathcal{E}$  and  $\mathcal{E}'$ . Indeed, before  $(t_0 + 2\Delta)$ ,  $\pi$  (resp.,  $\pi'$ ) receives only messages that were sent before  $(t_0 + \Delta)$ , and by the above, before  $(t_0 + \Delta)$ ,  $\chi$  issues the same sequence of messages in both  $\mathcal{E}$  and  $\mathcal{E}'$ .

Now, let  $\mathcal{E}^*$  be a variant of  $\mathcal{E}$  /  $\mathcal{E}'$ , identical in all aspects except that  $\theta$  is faulty. In  $\mathcal{E}^*$ ,  $\theta$  sends to  $\pi$  the same messages it would send in  $\mathcal{E}$ , and to  $\pi'$  the same messages it would send in  $\mathcal{E}'$ . By the above,  $\pi$  receives the same messages at the same times in both  $\mathcal{E}$  and  $\mathcal{E}^*$ , thus delivering m at time  $t \leq (t_0 + T) < (t_0 + 2\Delta)$ . Similarly,  $\pi'$  delivers m' at time t'. In summary, in  $\mathcal{E}^*$   $\pi$  and  $\pi'$ 

respectively deliver m and  $m' \neq m$  as first and only message. This violates the Agreement and Total Order property (see §2.2) and contradicts  $\mathcal A$  being an implementation of Total-Order Broadcast, thus concluding the theorem.