Embedding Cultural Diversity in Prototype-based Recommender Systems

Armin Moradi^{1,2}, Nicola Neophytou¹, Florian Carichon^{1,3}, and Golnoosh Farnadi^{1,3}

¹ Mila - Quebec AI Institute
 ² Université de Montréal
 ³ McGill University

Abstract. Popularity bias in recommender systems can increase cultural overrepresentation by favoring norms from dominant cultures and marginalizing underrepresented groups. This issue is critical for platforms offering cultural products, as they influence consumption patterns and human perceptions. In this work, we address popularity bias by identifying demographic biases within prototype-based matrix factorization methods. Using the country of origin as a proxy for cultural identity, we link this demographic attribute to popularity bias by refining the embedding space learning process. First, we propose filtering out irrelevant prototypes to improve representativity. Second, we introduce a regularization technique to enforce a uniform distribution of prototypes within the embedding space. Across four datasets, our results demonstrate a 27% reduction in the average rank of long-tail items and a 2% reduction in the average rank of items from underrepresented countries. Additionally, our model achieves a 2% improvement in HitRatio@10 compared to the state-of-the-art, highlighting that fairness is enhanced without compromising recommendation quality. Moreover, the distribution of prototypes leads to more inclusive explanations by better aligning items with diverse prototypes.

Keywords: Popularity Bias \cdot Demographic Fairness \cdot Prototype-based Matrix Factorization \cdot Explainability \cdot Culture

1 Introduction

Culture represents the shared beliefs, values, norms, and practices of particular societies or groups (Spencer-Oatey and Franklin, 2012). In today's digital world, recommender systems of platforms such as Netflix, Amazon, Steam, and Spotify have become the primary, and sometimes the only, means of accessing, discovering, and consuming cultural content and products (Ferraro et al., 2022). These systems play a significant role in shaping cultural consumption patterns, influencing the selective retention and transmission of cultural artifacts (Brinkmann et al., 2023). However, a major issue arises when these systems are biased—particularly toward popular products—leading to *popularity bias*

Wei et al. (2021). This bias can amplify dominant cultural norms, marginalizing underrepresented groups and their cultural expressions (Shuker, 2012; Lesota et al., 2022; Bello and Garcia, 2021), resulting in the exclusion of minority communities from fair representation (Deldjoo et al., 2024). The reinforcement of dominant values can perpetuate stereotypes Song (2013); Guerlain (1997), resulting in representational harm, while allocational harm arises as opportunities for minority communities' cultural products remain limited, thus exacerbating socio-economic disparities (Spring, 2016).

Biases in recommendation algorithms are rooted in the design and limitations of widely adopted techniques, such as matrix factorization (MF) and deep learning-based models (Zhang et al., 2019). These approaches excel at capturing complex user-item interactions but often fail to address fairness, as their underlying latent factor models emphasize patterns driven by popularity (Koren et al., 2009). Prototype-based recommender systems, such as Prototype-based Matrix Factorization (ProtoMF) (Melchiorre et al., 2022), were introduced to enhance explainability by identifying prototypes representing typical behaviors. However, these systems have not fully addressed fairness concerns—particularly how prototypes might still reflect dominant cultural norms, thus perpetuating biases in cultural representation.

To tackle these limitations, we introduce a novel approach that improves ProtoMF models with two key innovations:

- Prototype K-filtering, which refines the representation of users and items by selecting the k nearest prototypes, allowing the model to better capture underrepresented items and users;
- Prototype-Distributing Regularizer, a mechanism that encourages a more even distribution of prototypes across the embedding space, ensuring diverse cultural representations by reducing the clustering effect around popular items.

We address demographic bias by incorporating the country of origin of item providers as a cultural feature, thereby tackling popularity bias through a demographic lens. This approach enables us to mitigate bias while maintaining model performance.

We evaluate our framework on MovieLens-1M (Harper and Konstan, 2015), LastFM-2b (Melchiorre et al., 2021), and Amazon Reviews'23 (Hou et al., 2024) for 'Musical Instruments' and 'Beauty and Personal Care' categories; due to their strong ties to cultural behavior. Our extensive experiments assess both the performance and fairness of the recommendations. The results indicate that demographic bias in prototype-based recommender systems can be effectively mitigated without compromising utility.

The remainder of this paper is organized as follows: Section 2 reviews related work, Section 3 presents background on ProtoMF, and Section 4 details our proposed methodology. Section 5 describes the evaluation setup, and Section 6 discusses the results. Finally, we provide a detailed discussion in Section 7.

2 Related Work

Culture plays an important role in shaping user preferences and interactions in recommender systems (RecSys). Several studies have explored how the cultural distance between users and items influences satisfaction, and they emphasize the need to integrate cultural factors into RecSys design (Moreau and Peltier, 2004). Existing work has incorporated users' cultural backgrounds into collaborative filtering models by embedding demographic features into profiles and interactions (Zangerle et al., 2018). Hong and Jung (2021) expanded this by embedding cultural factors directly into user profiles, while Hong et al. (2024) grouped users based on shared cultural backgrounds to improve recommendation accuracy. However, these works mainly focused on improving recommendation utility rather than addressing biases, particularly when algorithms favor dominant cultures (Brinkmann et al., 2023). Ferraro et al. (2022) highlighted this issue by introducing a measure of cultural diversity in collaborative filtering systems, aligning with Lesota et al. (2022)'s findings related to music RecSys. Building on these insights, our work explores mitigating popularity bias in RecSys to guarantee a better representation of underrepresented cultural groups, shifting the focus from utility alone to fairness and diversity in recommendations.

Fairness in RecSys presents a multifaceted challenge, especially when popularity and demographic biases are involved (Sonboli et al., 2022). These biases can result in representational harms, such as reinforcing stereotypes, and allocational harms, where opportunities for certain groups or products are limited (Barocas et al., 2023). Popularity bias, in particular, often skews recommendations toward dominant subgrouups, leading to the underrepresentation and marginalization of less popular ones Lesota et al. (2021). This can be investigated from both the users and the item providers' perspectives (Sonboli et al. (2021)). Our work specifically focuses on the item dimension for two reasons: first, by targeting items' country of origin, we can directly mitigate allocational harms affecting underrepresented cultures; second, current datasets often contain sensitive information on items rather than users, allowing us to identify and challenge strong biases. By mitigating popularity bias through this lens, we aim to improve the representation of underrepresented cultural products, promoting fairness across a broader cultural spectrum.

Several fairness strategies have been proposed to address popularity and demographic biases, generally categorized into pre-processing, in-processing, and post-processing methods (Deldjoo et al., 2024). For instance, Rhee et al. (2022) use an in-processing method that mitigates popularity bias by adding a regularizer to minimize score differences, while Wei et al. (2021) employ a counterfactual method to reduce popularity bias. Zheng et al. (2021) address the same issue by assigning separate embeddings for user interest and conformity. Also, Beutel et al. (2019) add a regularizer to prevent favoring of one group over another by penalizing prediction discrepancies between groups. In our work, we also propose an in-processing mitigation method. However, we distinguish ourselves by modifying the learning process that changes the structure of the embedding space without conflicting with the model's downstream task.

Our focus on the embedding space is enabled by prototype-based methods, which use prototypes as anchor points to generate explainable embeddings for both items and users (Sankar et al., 2021). By introducing bias-mitigation techniques within Melchiorre et al.'s prototype-based matrix factorization (ProtoMF), we position ourselves among the few proposing explainable fairness strategies through the learning process of the embedding space, which is shown to align with improving providers' fairness Dinnissen and Bauer (2023). Unlike Melchiorre et al. (2024), who focus on unbiasing ProtoMF using user-related coefficients, our approach modifies the learning process to create a more inclusive embedding space, aiming to balance the representations and provide fairer outcomes for item providers.

3 **Prototype-based Matrix Factorization**

Prototype-based Matrix Factorization (ProtoMF) extends traditional matrix factorization by introducing prototypes to redefine the embedding process for both users and items. Specifically, we define two sets of prototype vectors:

- User prototypes: $P^u = p_1^u, p_2^u, \ldots, p_{L_u}^u \subset \mathbb{R}^d$, forming a matrix $P^u \in \mathbb{R}^{L_u \times d}$. Item prototypes: $P^i = p_1^i, p_2^i, \ldots, p_{L_i}^i \subset \mathbb{R}^d$, forming a matrix $P^i \in \mathbb{R}^{L_i \times d}$.

Here, L_u and L_i are the numbers of prototypes for users and items, respectively, and d is the dimensionality of the latent space. These prototype vectors serve as anchor points to create more interpretable embeddings (Melchiorre et al., 2022). The embeddings of users and items are transformed using these prototypes. For user and item embeddings $u, i \in \mathbb{R}^d$, the transformed embedding $u^* \in \mathbb{R}^{L_u}, i^* \in \mathbb{R}^{L_i}$ is computed as:

$$u^* = \left[\sin(u, p_1^u), \dots, \sin(u, p_{L_u}^u) \right], \ i^* = \left[\sin(i, p_1^i), \dots, \sin(i, p_{L_i}^i) \right].$$
(1)

where $sim(\cdot, \cdot)$ denotes the shifted cosine similarity.

This process yields transformed user and item matrices $U^* \in \mathbb{R}^{N \times L_u}$ and $I^* \in \mathbb{R}^{M \times L_i}$, where N and M are the numbers of users and items, respectively.

The affinity score between a user and an item is calculated as:

$$\operatorname{Aff}(u,i) = u^{*\top}\hat{i} + \hat{u}^{\top}i^{*}, \qquad (2)$$

where $\hat{u} = W^u u \in \mathbb{R}^{L_i}$ and $\hat{i} = W^i i \in \mathbb{R}^{L_u}$ are linear transformations mapping the embeddings to the opposite prototype spaces.

The recommendation loss for users (L_{U-rec}) and items (L_{I-rec}) is defined using implicit feedback as in Rendle (2021), by applying the softmax function over the affinity scores across all possible items (for users) and all possible users (for items).

In addition to the recommendation loss, two collaborative regularization terms are introduced for both the user and item sides. On the user side, the first regularization term (Eq. 3) increases the similarity between each prototype p_l^u and its most similar user u, and the second term (Eq. 4) increases the similarity between each user u and its most similar prototype:

$$R_{\{P^u \to u\}} = -\frac{1}{L^u} \sum_{l=1}^{L^u} \max_{l \in [1, \dots, N]} \sin(u, p_l^u),$$
(3)

$$R_{\{u \to P^u\}} = -\frac{1}{N} \sum_{l=1}^{N} \max_{l \in [1, \dots, L^y]} \sin(u_i, p_l^u).$$
(4)

The final user and item loss functions are calculated by the summation of the recommendation loss, and the two regularization factors. Formally, the loss functions for the user side is: $L_{U-proto} = L_{U-rec} + \lambda_1^u R_{\{P^u \to u\}} + \lambda_2^u R_{\{u \to P^u\}}$, where the set of λ_1^u and λ_2^u s control the weights of the regularization terms.

The item side regularization terms and loss function are defined analogously. Therefore, the total loss function is the sum of the user and item loss functions:

$$L_{\text{total}} = L_{U-proto} + L_{I-proto}.$$
(5)

4 Methodology

The following subsections detail the two enhancements and their integration into the ProtoMF framework.

4.1 Prototype K-filtering

In the standard ProtoMF model, all prototypes contribute to computing the transformed user and item representations u^* and i^* . This means that even distant prototypes can influence these representations, potentially biasing the model toward popular items and users. To address this issue, we introduce *Prototype K-filtering*, which retains only the k nearest prototypes for each user and item, setting the similarities to the remaining prototypes to zero.

Formally, for a user u and item i, we select the $k_u \ll L_u$ and $k_i \ll L_i$ indices of the nearest prototypes:

$$P_{k}^{u} = \arg\max_{P^{u} \subset [L_{u}]:|P^{u}| = k_{u}} \sum_{p_{j}^{u} \in P_{u}} sim(u, p_{j}^{u}),$$
(6)

$$P_{k}^{i} = \arg\max_{P^{i} \subset [L_{i}]: |P^{i}| = k_{i}} \sum_{p_{i}^{i} \in P_{i}} sim(i, p_{j}^{i}).$$
(7)

The filtered transformed representations are computed as: $u^{*,k} = u^* \odot \mathbb{1}_{P_k^u}$ for users and $i^{*,k} = i^* \odot \mathbb{1}_{P_k^i}$ for items, where \odot denotes element-wise multiplication, and $\mathbb{1}_{P^u k}$ and $\mathbb{1}_{P_k^i}$ are indicator vectors with ones at positions corresponding to the selected prototypes and zeros elsewhere.

By focusing on local information, this method improves the representation of less popular users and items, reducing the influence of dominant prototypes that may contribute to bias. In our experimental results, models using k-filtering are denoted as $\{\text{User}\}_{\{k\}}$ when k-filtering is applied only to the user side, $\{\text{Item}\}_{\{k\}}$ when applied only to the item side.

4.2 Prototype-Distributing Regularizer

Another concern is that prototypes may cluster in specific regions of the embedding space, causing underrepresented users or items to be associated with distant prototypes. To mitigate this, we introduce a regularization term that encourages prototypes to be uniformly distributed across the embedding space.

The modified loss function becomes:

$$L = L_{\text{total}} + \lambda_u \cdot ||\hat{P}_{L_u}\hat{P}_{L_u}^T||_F + \lambda_i \cdot ||\hat{P}_{L_i}\hat{P}_{L_i}^T||_F,$$

$$\tag{8}$$

where L_{total} is the original ProtoMF loss, $\hat{P}^u \in \mathbb{R}^{L_u \times d}$ and $\hat{P}^i \in \mathbb{R}^{L_i \times d}$ are matrices of normalized user and item prototypes (each row vector normalized to unit length), I is the identity matrix, $|| \cdot ||_F$ denotes the Frobenius norm, λ_u and λ_i are hyperparameters controlling the strength of the regularization.

This regularizer encourages the prototypes to be approximately orthogonal, promoting a uniform distribution that better covers the embedding space. By preventing prototypes from clustering, we ensure a more diverse representation of user preferences and item characteristics, reducing bias toward dominant groups. In our experimental results, models using the distributing regularizer are denoted as $\{\text{User}\}_{\lambda}$ when the regularizer is applied only to the user side, $\{\text{Item}\}_{\lambda}$ when applied only to the item side.

When both k-filtering and the distributing regularizer are applied to both sides, we denote the model as $\{\text{User-Item}\}_{\{k,\lambda\}}$.

5 Evaluation Setup

5.1 Datasets

We conduct our experiments using four datasets:

- LastFM-2b (Melchiorre et al., 2021): A subset augmented with artists' countries of origin by matching artist names with the MusicBrainz database.
- MovieLens-1M (Harper and Konstan, 2015): Users' movie ratings, enriched with movies' countries of origin retrieved via The Movie Database API.
- Amazon Reviews'23 (Hou et al., 2024): We use two categories—Musical Instruments, Beauty and Personal Care, filtered to include items' countries of origin. These categories are selected because cultural factors, such as differing beauty standards between Asian and European countries (Frederick et al., 2015), can influence user decisions.

To simplify the evaluation, we define groups based on interaction counts and the country of origin as the sensitive attribute: 1. Overrepresented groups: Countries in the top 10% by number of interactions. 2. Underrepresented groups: Countries in the third quartile (25%-50%) of interaction counts. We exclude the extreme tail of the distribution to balance representation and statistical reliability. Dataset statistics and groupings are detailed in Table 1.

Table 1: Overview of datasets before and after filtering and the choice of underrepresented and overrepresented groups.

(a) Overview of datasets before and after filtering based on the sensitive attribute of country of origin.

Dataset	Before Filtering			After Filtering			
	#users	#items	#interactions	#users	#items	#interactions	
Beauty	11.3M	1.0M	23.9M	$508K (\downarrow 95.5\%)$	35.8K (↓ 96.4%)	1.5M (↓ 93.7%)	
Instruments	1.8M	213.6K	3.0M	9.9K (↓ 95.8%)	9.4K (↓ 95.5%)	212.3K (↓ 92.9%)	
LastFM-2b	15K	4.0M	30.3M	8.4K (↓ 44%)	63.0K (↓ 98.4%)	1.48M (↓ 95.1%)	
MovieLens-1M	6K	4K	1M	6K (↓0%)	4K (↓ 0%)	1M (↓ 0%)	

(b) Continuation: Choice of underrepresented and overrepresented groups for each dataset after filtering, used to measure the models' fairness.

Dataset	Underrepresented Groups	Overrepresented Groups		
Beauty	Austria, Egypt, Hungary, Portugal, Bulgaria	China, USA, France, South Korea		
Instruments	Nepal, Vietnam, Malaysia, Philippines, Denmark, Austria	China, USA, Taiwan, Canada		
LastFM-2b	Netherlands, Japan, Brazil, Poland, Norway	USA, UK, Canada, France		
MovieLens-1M	Ireland, Japan, Korea, Hong Kong, China	USA, UK, France		

5.2 Baselines

To evaluate our model's performance, we select four baselines: Matrix Factorization (MF) (Koren et al., 2009), anchor-based collaborative filtering (ACF) (Barkan et al., 2021), ProtoMF (Melchiorre et al., 2022). Additionally, we include a benchmark for popularity bias mitigation, ZeroSum (Rhee et al., 2022), by adding the score difference regularizer to the loss function of user and item side of ProtoMF. This allows for a fair comparison of its effectiveness with our approach.

Hyperparameter tuning is performed using the Ray library (Moritz et al., 2018) across 50 different seeds. For ProtoMF-based models, we first optimize the vanilla ProtoMF configuration. Fixing these hyperparameters, we then separately optimize our additional parameters to reduce the hyperparameter search space and ensure computational feasibility.

5.3 Metrics

Performance Metrics: We employ two standard accuracy metrics of Hit Ratio (HR@10) and Normalized Discounted Cumulative Gain (NDCG@10) to assess the performance of the models as He et al. (2017); Melchiorre et al. (2022) have previously done.

- 8 Moradi et al.
 - Fairness Metrics:
 - Per-group Item Average Ranking: Ranking plays a critical role in fairness, as user interactions vary based on item positions, as explored by Ursu (2018). We report the average ranking of items for underrepresented $(\mu(r_{under}))$ and overrepresented groups $(\mu(r_{over}))$ across model outputs of 100 items.
 - Long-Tail Average Ranking: We also report the average ranking of longtail items for all users. Long-tail items are defined as the 10% of items with the *fewest* interactions, based on the logarithmic interaction count discussed by Salganik et al. (2024).

6 Results

Our findings, illustrated in Figures 1a and 1b, demonstrate that our model surpasses MF and ACF in terms of performance metrics and achieves competitive results compared to ProtoMF and ZeroSum. Specifically, on the LastFM dataset, our model attains a HitRatio@10 of 0.600, marking a 3% improvement over ProtoMF's score of 0.581.



Fig. 1: The first group (a, b) presents the performance metrics. The second group (c, d) presents the fairness metrics. Our model with the highest HR@10 is chosen.

Crucially, this performance enhancement is accompanied by significant improvements in fairness metrics. By applying our regularization techniques to promote a more uniform distribution of prototypes within the embedding space, we observe a 38% reduction in the average ranking of long-tail items on the LastFM dataset (see Figure 1c). Additionally, as indicated in Figure 1d, our model more effectively promotes items from underrepresented groups (refer to Table 1b for group definitions). For instance, on the MovieLens dataset, there is a 3.4% reduction in the average ranking for items from underrepresented countries.

Moreover, our method offers flexibility in balancing performance and fairness based on specific requirements. As depicted in Figure 2, different configurations of our model result in varying levels of performance and fairness. For example, on the MovieLens dataset (see Table 3), the configuration denoted as the {User, Item}_{{k,\lambda}} model achieves an HR@10 of 0.657, slightly lower than the {*Item*_{{\lambda}}</sub> model's HR@10 of 0.660, but provides an 18% lower average ranking for underrepresented groups, indicating enhanced fairness.

In addition to enhancing fairness, our approach of distributing prototypes within the embedding space facilitates the allocation and grouping of more items from underrepresented groups. Figure 3 illustrates the differences in the embedding space before and after applying the regularizer.



Fig. 2: Results obtained for our various model configurations. All values are normalized per dataset, with higher values indicating better performance or fairness.

7 Discussion

Item Side: Synergy of k-Filtering and Prototype Distribution: Applying item k-filtering yielded significant improvements in ranking underrepresented items. By representing points with fewer but more relevant local neighbors, kfiltering enhances the representation of items, ensuring that prototypes better reflect the true data distribution. This technique improves the model's ability to accurately rank items from less represented countries without adversely affecting—and sometimes even improving—the ranking of overrepresented items.

Conversely, incorporating item-level regularization Item_{λ} proved most effective for promoting long-tail items. The regularizer forces prototypes to spread



(a) Prototypes cluster more around US items.

(b) Prototypes are more evenly distributed. NL items are grouped.

Fig. 3: t-SNE visualizations of the item embedding space for (a) ProtoMF and (b) {User-Item}_{$\{k,\lambda\}$} models. NL and US items are respectively from under and over-represented countries.

out in the embedding space, encouraging the exploration of regions that would otherwise remain underutilized (see Figure 3a. However, this approach can lead to a decrease in HitRatio, as spreading prototypes may result in noisier representations embedded in sparsely populated regions. This trade-off highlights the limitations of solely applying prototype spreading.

Interestingly, the combination of item k-filtering and prototype regularization offered the best overall performance. This synergy balances refining representations of underrepresented items and encouraging diversity in the top recommended items. By integrating both methods, we mitigate the decrease in HitRatio caused by prototype spreading alone while still promoting diversity. The result is better rankings for items from underrepresented countries and a more varied recommendation list, enhancing both fairness and user satisfaction. *User Side, Limited Effects on Performance:* Contrary to our expectations, user-based techniques did not improve performance and often resulted in worse outcomes compared to the baseline. Methods like regularization or k-filtering applied to user representations had little effect on performance. Moreover, regularizing user embeddings may degrade fairness because it introduces noise into the user representations without reducing the allocational harms.

One possible explanation is that our evaluation focuses on the country of origin of the items (allocational fairness) rather than the origin of the users (representational fairness). Therefore, applying regularization in the user embedding space does not directly increase the visibility of items belonging to the long-tail or underrepresented groups. This highlights the importance of applying regularization in the appropriate embedding space to effectively address specific fairness concerns. User-based regularization might be more effective in scenarios where representational harms are the primary concern.

Item Side: Inclusiveness in Interpretability: As depicted in Figure 3, we can observe the impact of prototype distribution on the ability of the model pro-

11

vide improved explanations for items belonging to the minority groups. In our model, as shown in Figure 3b, the prototypes become more evenly distributed across the item embedding space. This redistribution ensures that items from underrepresented cultures are represented by closer prototypes. As a result, the model can offer more *culturally-aware* explanations for its recommendations. Table 2 shows nearest prototype examples of a Japanese animation and an Aztec musical instrument: The prototypes associated with our model take up not only the category of the product but also its cultural proximity, making the recommendations more intuitive, representative, and inclusive.

Table 2: Closest items to the five nearest prototypes for each product, listed in decreasing order of similarity (values in parentheses). Bolded items indicate those from the same country as the original product. Products are sourced from the Amazon Movies and Instruments datasets.

Product	Model Proto. 1		Proto. 2	Proto. 3	Proto. 4	Proto. 5	
Princess Mo- nonoke (JP)	Baseline	The Lion King (1.58) (US)	Pokémon (1.51) (JP)	Aladdin (1.50) (US)	Small Soldiers (1.48) (US)	Toy Story 2 (1.47) (US)	
	Ours	Pokémon (1.64) (JP)	Akira (1.59) (JP)	The Lion King (1.55) (US)	Perfect Blue (1.52) (JP)	The Iron Giant (1.31) (US)	
Aztec Death Whistle (CO)	Baseline	Flute (1.56) (CN)	Ocarina (1.53) (CN)	Drumset (1.47) (US)	Saxophone (1.40) (CN)	Trumpet (1.32) (US)	
	Ours	Ocarina (1.61) (CN)	Flute (1.58) (CN)	Screaming Whistle (1.53) (CO)	Trumpet (1.43) (US)	Tambora (1.42) (TW)	

8 Conclusion & Future Directions

We introduced enhancements to Prototype-based Matrix Factorization to mitigate demographic biases in RecSys, focusing on cultural overrepresentation. By implementing Prototype K-filtering and a Prototype-Distributing Regularizer, our model improves the representation of underrepresented items without compromising recommendation quality. Experimental results show that our approach achieves higher performance than baseline models and significantly reduces the average ranking of long-tail and underrepresented items. This promotes fairness and inclusiveness in recommendations and explanations, contributing to a more equitable user experience.

However, our study has several limitations. First, the theoretical justification for the effectiveness of k-filtering and the regularization techniques is not thoroughly established; more rigorous analysis is needed to fully understand their impact on performance and fairness. Second, while we observed enhancements in explainability, we did not conduct a systematic analysis of this aspect. Additionally, the significant reduction of data due to filtering for country information may affect the generalizability of our findings. Finally, by simplifying culture to country of origin, we overlook its complex and multifaceted nature that extends beyond national boundaries; culture is influenced by factors such as ethnicity, language, and religion. This oversimplification may limit the effectiveness of our bias mitigation strategies and fail to capture the diversity within and across countries.

A Detailed Results

Table 3: Results of Models Across All Datasets. Bold numbers show the best value with respect to each dataset. $\mu_{\rm over}$ to investigate how each model treats the overrepresented groups and in order to compare it against the $\mu_{\rm under}$. We also include all the results on the 'Amazon Grocery and Gourmet Food' dataset to provide more depth in our experiments.

Model	Dataset	\uparrow HR@10	↑NDCG@10	$\downarrow \mu_{\mathrm{under}}$	$\mu_{\rm over}$	$\downarrow \mu_{\rm LT}$
ZeroSum	LastFM-2b	0.564	0.327	52.233	44.733	21.543
Rhee et al.	MovieLens-1M	0.615	0.347	48.660	49.381	13.964
	Amazon Beauty	0.238	0.154	50.771	49.634	35.372
	Amazon Instruments	0.243	0.159	47.099	49.997	30.416
	Amazon Grocery	0.261	0.170	50.582	49.088	18.413
ProtoMF	LastFM-2b	0.581	0.337	51.106	44.300	29.008
Melchiorre et al.	MovieLens-1M	0.656	0.381	48.674	49.582	16.215
	Amazon Beauty	0.239	0.155	50.425	49.646	39.129
	Amazon Instruments	0.245	0.164	47.012	50.002	32.965
	Amazon Grocery	0.259	0.168	50.350	49.132	27.991
ACF	LastFM-2b	0.569	0.317	53.970	43.458	20.009
Barkan et al.	MovieLens-1M	0.618	0.345	50.891	53.923	16.783
	Amazon Beauty	0.229	0.142	50.885	49.615	44.690
	Amazon Instruments	0.211	0.132	47.250	49.924	18.849
	Amazon Grocery	0.250	0.159	50.530	49.137	24.343
MF	LastFM-2b	0.159	0.083	49.299	49.755	25.991
Koren et al.	MovieLens-1M	0.452	0.248	50.098	49.340	21.201
	Amazon Beauty	0.117	0.077	50.711	49.595	16.660
	Amazon Instruments	0.163	0.113	47.620	49.926	26.825
	Amazon Grocery	0.132	0.086	50.338	49.208	21.541
$\{user\}_{(L)}$	LastFM-2b	0.574	0.326	50.952	44.587	26.136
(abor) { <i>k</i> }	MovieLens-1M	0.640	0.365	48.452	50.956	13.330
	Amazon Beauty	0.240	0.155	51.846	49.573	28.715
	Amazon Instruments	0.234	0.152	45.949	50.077	9.865
	Amazon Grocery	0.262	0.170	50.765	49.118	19.098
$\{\text{item}\}_{\{k\}}$	LastFM-2b	0.594	0.344	49.849	43.852	21.995
() ()	MovieLens-1M	0.651	0.379	47.357	49.898	11.263
	Amazon Beauty	0.238	0.154	51.762	49.588	20.693
	Amazon Instruments	0.233	0.154	46.123	50.044	32.674
	Amazon Grocery	0.259	0.167	50.560	49.116	16.457
$\{user\}_{\{\lambda\}}$	LastFM-2b	0.520	0.302	51.115	45.007	21.391
- ()	MovieLens-1M	0.660	0.383	48.596	51.154	14.179
	Amazon Beauty	0.237	0.153	50.613	49.630	16.327
	Amazon Instruments	0.254	0.170	47.024	50.012	26.963
	Amazon Grocery	0.262	0.169	50.564	48.855	28.072
${\rm titem}_{\{\lambda\}}$	LastFM-2b	0.598	0.348	51.111	44.085	18.995
	MovieLens-1M	0.660	0.386	48.622	51.089	13.293
	Amazon Beauty	0.237	0.153	49.776	49.641	44.378
	Amazon Instruments	0.249	0.166	46.781	49.957	23.017
	Amazon Grocery	0.261	0.169	50.480	48.999	23.561
$\{\text{user-item}\}_{\{k,\lambda\}}$	LastFM-2b	0.600	0.352	49.552	44.296	18.013
- ()	MovieLens-1M	0.657	0.383	47.048	49.571	16.158
	Amazon Beauty	0.236	0.153	50.018	49.643	16.684
	Amazon Instruments	0.250	0.167	47.017	49.993	36.062
	Amazon Grocery	0.261	0.168	50.568	49.047	26.788

Bibliography

- Oren Barkan, Roy Hirsch, Ori Katz, Avi Caciularu, and Noam Koenigstein. 2021. Anchor-based collaborative filtering. In Proceedings of the 30th ACM International Conference on Information & Knowledge Management. 2877– 2881.
- Solon Barocas, Moritz Hardt, and Arvind Narayanan. 2023. Fairness and machine learning: Limitations and opportunities. MIT press.
- Pablo Bello and David Garcia. 2021. Cultural Divergence in popular music: the increasing diversity of music consumption on Spotify across countries. *Humanities and Social Sciences Communications* 8, 1 (2021), 1–8.
- Alex Beutel, Jilin Chen, Tulsee Doshi, Hai Qian, Li Wei, Yi Wu, Lukasz Heldt, Zhe Zhao, Lichan Hong, Ed H Chi, et al. 2019. Fairness in recommendation ranking through pairwise comparisons. In Proceedings of the 25th ACM SIGKDD international conference on knowledge discovery & data mining. 2212–2220.
- Levin Brinkmann, Fabian Baumann, Jean-François Bonnefon, Maxime Derex, Thomas F Müller, Anne-Marie Nussberger, Agnieszka Czaplicka, Alberto Acerbi, Thomas L Griffiths, Joseph Henrich, et al. 2023. Machine culture. Nature Human Behaviour 7, 11 (2023), 1855–1868.
- Yashar Deldjoo, Dietmar Jannach, Alejandro Bellogin, Alessandro Difonzo, and Dario Zanzonelli. 2024. Fairness in recommender systems: research landscape and future directions. User Modeling and User-Adapted Interaction 34, 1 (2024), 59–108.
- Karlijn Dinnissen and Christine Bauer. 2023. How Control and Transparency for Users Could Improve Artist Fairness in Music Recommender Systems. In *Ismir 2023 Hybrid Conference*.
- Andres Ferraro, Gustavo Ferreira, Fernando Diaz, and Georgina Born. 2022. Measuring commonality in recommendation of cultural content: recommender systems to enhance cultural citizenship. In *Proceedings of the 16th ACM conference on recommender systems*. 567–572.
- David Frederick, Megan Forbes, Brooke Jenkins, Tania Reynolds, and Tia Walters. 2015. Beauty standards. The international encyclopedia of human sexuality 1 (2015), 113–196.
- Pierre Guerlain. 1997. The ironies and dilemmas of America's cultural dominance: A transcultural approach. American Studies International 35, 2 (1997), 30–51.
- F Maxwell Harper and Joseph A Konstan. 2015. The movielens datasets: History and context. Acm transactions on interactive intelligent systems (tils) 5, 4 (2015), 1–19.
- Xiangnan He, Lizi Liao, Hanwang Zhang, Liqiang Nie, Xia Hu, and Tat-Seng Chua. 2017. Neural collaborative filtering. In Proceedings of the 26th international conference on world wide web. 173–182.

- Minsung Hong, Sojung An, Rajendra Akerkar, David Camacho, and Jason J Jung. 2024. Cross-cultural contextualisation for recommender systems. *Jour*nal of Ambient Intelligence and Humanized Computing (2024), 1–12.
- Minsung Hong and Jason J Jung. 2021. Multi-criteria tensor model for tourism recommender systems. *Expert Systems with Applications* 170 (2021), 114537.
- Yupeng Hou, Jiacheng Li, Zhankui He, An Yan, Xiusi Chen, and Julian McAuley. 2024. Bridging Language and Items for Retrieval and Recommendation. arXiv preprint arXiv:2403.03952 (2024).
- Yehuda Koren, Robert Bell, and Chris Volinsky. 2009. Matrix factorization techniques for recommender systems. *Computer* 42, 8 (2009), 30–37.
- Oleg Lesota, Alessandro Melchiorre, Navid Rekabsaz, Stefan Brandl, Dominik Kowald, Elisabeth Lex, and Markus Schedl. 2021. Analyzing item popularity bias of music recommender systems: are different genders equally affected?. In Proceedings of the 15th ACM conference on recommender systems. 601–606.
- Oleg Lesota, Emilia Parada-Cabaleiro, Stefan Brandl, Elisabeth Lex, Navid Rekabsaz, and Markus Schedl. 2022. Traces of Globalization in Online Music Consumption Patterns and Results of Recommendation Algorithms.. In *ISMIR*. 291–297.
- Alessandro B Melchiorre, Shahed Masoudian, Deepak Kumar, and Markus Schedl. 2024. Modular Debiasing of Latent User Representations in Prototype-Based Recommender Systems. In Joint European Conference on Machine Learning and Knowledge Discovery in Databases. Springer, 56–72.
- Alessandro B Melchiorre, Navid Rekabsaz, Christian Ganhör, and Markus Schedl. 2022. Protomf: Prototype-based matrix factorization for effective and explainable recommendations. In *Proceedings of the 16th ACM Conference on Recommender Systems.* 246–256.
- Alessandro B. Melchiorre, Navid Rekabsaz, Emilia Parada-Cabaleiro, Stefan Brandl, Oleg Lesota, and Markus Schedl. 2021. Investigating gender fairness of recommendation algorithms in the music domain. *Information Processing & Management* 58, 5 (2021), 102666. https://doi.org/10.1016/j.ipm. 2021.102666
- François Moreau and Stéphanie Peltier. 2004. Cultural diversity in the movie industry: A cross-national study. *Journal of media economics* 17, 2 (2004), 123–143.
- Philipp Moritz, Robert Nishihara, Stephanie Wang, Alexey Tumanov, Richard Liaw, Eric Liang, Melih Elibol, Zongheng Yang, William Paul, Michael I Jordan, et al. 2018. Ray: A distributed framework for emerging {AI} applications. In 13th USENIX symposium on operating systems design and implementation (OSDI 18). 561–577.
- Steffen Rendle. 2021. Item recommendation from implicit feedback. In Recommender Systems Handbook. Springer, 143–171.
- Wondo Rhee, Sung Min Cho, and Bongwon Suh. 2022. Countering popularity bias by regularizing score differences. In *Proceedings of the 16th ACM Con*ference on Recommender Systems. 145–155.
- Rebecca Salganik, Fernando Diaz, and Golnoosh Farnadi. 2024. Fairness Through Domain Awareness: Mitigating Popularity Bias for Music Discovery. In *European Conference on Information Retrieval*. Springer, 351–368.

Aravind Sankar, Junting Wang, Adit Krishnan, and Hari Sundaram. 2021. Protocf: Prototypical collaborative filtering for few-shot recommendation. In Proceedings of the 15th ACM Conference on Recommender Systems. 166–175.

Roy Shuker. 2012. Popular music culture: The key concepts. Routledge.

- Nasim Sonboli, Robin Burke, Michael Ekstrand, and Rishabh Mehrotra. 2022. The multisided complexity of fairness in recommender systems. AI magazine 43, 2 (2022), 164–176.
- Nasim Sonboli, Jessie J Smith, Florencia Cabral Berenfus, Robin Burke, and Casey Fiesler. 2021. Fairness and transparency in recommendation: The users' perspective. In Proceedings of the 29th ACM Conference on User Modeling, Adaptation and Personalization. 274–279.
- Heejin Song. 2013. Deconstruction of cultural dominance in Korean EFL textbooks. *Intercultural Education* 24, 4 (2013), 382–390.
- Helen Spencer-Oatey and Peter Franklin. 2012. What is culture. A compilation of quotations. GlobalPAD Core Concepts 1, 22 (2012), 1–21.
- Joel Spring. 2016. Deculturalization and the struggle for equality: A brief history of the education of dominated cultures in the United States. Routledge.
- Raluca M Ursu. 2018. The power of rankings: Quantifying the effect of rankings on online consumer search and purchase decisions. *Marketing Science* 37, 4 (2018), 530–552.
- Tianxin Wei, Fuli Feng, Jiawei Chen, Ziwei Wu, Jinfeng Yi, and Xiangnan He. 2021. Model-agnostic counterfactual reasoning for eliminating popularity bias in recommender system. In Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery & Data Mining. 1791–1800.
- Eva Zangerle, Martin Pichl, and Markus Schedl. 2018. Culture-aware music recommendation. In *Proceedings of the 26th Conference on User Modeling, Adaptation and Personalization*. 357–358.
- Shuai Zhang, Lina Yao, Aixin Sun, and Yi Tay. 2019. Deep learning based recommender system: A survey and new perspectives. ACM computing surveys (CSUR) 52, 1 (2019), 1–38.
- Yu Zheng, Chen Gao, Xiang Li, Xiangnan He, Yong Li, and Depeng Jin. 2021. Disentangling user interest and conformity for recommendation with causal embedding. In *Proceedings of the Web Conference 2021*. 2980–2991.