A brief history of quantum vs classical computational advantage

Ryan LaRose^{1,*}

¹Center for Quantum Computing, Science, and Engineering, Michigan State University, East Lansing, MI 48823, USA

In this review article we summarize all experiments claiming quantum computational advantage to date. Our review highlights challenges, loopholes, and refutations appearing in subsequent work to provide a complete picture of the current statuses of these experiments. In addition, we also discuss theoretical computational advantage in example problems such as approximate optimization and recommendation systems. Finally, we review recent experiments in quantum error correction — the biggest frontier to reach experimental quantum advantage in Shor's algorithm.

I. INTRODUCTION

Since the first experimental demonstration of quantum advantage on Oct 23 2019, several new experiments have been performed and previous experiments have been challenged or refuted. The purpose of this review article is to collect these experiments, challenges, and refutations in a single place to provide a complete picture of the current status of quantum vs classical computational advantage.

While computational advantage could refer to several aspects (e.g. lower energy consumption or higher accuracy), here we use it to mean lower time to solution as is common in the quantum computing literature $[1]^1$. This captures the intuitive meaning of advantage as the answer to the following question: for a given computational problem, which solves the problem faster — the best classical algorithm on the best classical computer, or the best quantum algorithm on the best quantum computer? Two notes are in order. First, computational advantage is defined with respect to a particular problem, which may or may not have any practical relevance or utility. Second, the *best* computers, as well as the *best* algorithms, change over time, both in the classical and quantum settings. Thus computational advantage is a moving target and can change hands between classical and quantum computers. The history of this changing status is the primary purpose of this review article. Table I provides a chronological list of all experiments claiming computational advantage to date along with their current statuses, and Sec. II provides the narrative discussion.

In addition to this primary purpose, we also discuss *theoretical* quantum vs classical computational advantage. In this setting, advantage refers to lower algorithmic complexity for a given computational problem, typically in the asymptotic setting, without regard to any computer or experiment implementing the algorithm. Even in this arena, computational advantage has shifted hands between quantum and classical as better classical algorithms, often inspired by the quantum algorithms, have been developed. Sec. III provides a discussion for the examples of recommendation systems, approximate optimization, and quantum chemistry.

Finally, since many quantum algorithms with hypothesized or proven computational advantage will require error correction to experimentally realize, we include a history of quantum error correction experiments, especially in recent years, as the final element to this review article. While error correction is typically considered separate and independent of computational advantage, some quantum algorithms with theoretical computational advantage can actually lose their speedup due to the overhead of error correction [3]. For this reason, and because quantum information is so inherently fragile, the two are intricately connected in quantum computing. Error correction can thus be considered the final frontier to experimentally demonstrating quantum computational advantage for problems such as Shor's algorithm for prime factorization [4]. Table II provides a history of quantum error correction experiments, and Sec. IV provides the narrative discussion.

II. QUANTUM ADVANTAGE EXPERIMENTS

Table I shows the complete list of articles claiming quantum computational advantage to date, ordered chronologically. As can be seen, so far three computational problems have been considered: Random Circuit Sampling (RCS), Gaussian Boson Sampling (GBS), and quantum simulation (QSim). Each problem is defined when it appears in the chronological narrative. Briefly, random circuit sampling is the computational task of sampling bitstrings from a random quantum circuit; Gaussian boson sampling is the analogous problem

^{*} rmlarose@msu.edu.

¹ Note that, after the first experiment, quantum advantage is used preferentially to the previous term of quantum supremacy although the technical meaning has not changed [2]. Note that there are several other terms used for the notion of quantum advantage — e.g. beyond-classical computation. Some authors prefer to use quantum advantage only for "useful" computations as opposed to (probably) arbitrary computations designed around what quantum computers are good at. Still some other authors prefer quantum utility for this concept. While these distinctions are useful, there is not yet standard terminology nor a standard definition for any term. In this article, by quantum advantage we always mean a computation performed faster on a quantum computer than on a classical computer, irrespective of the utility of the problem.

Date	Problem	n	m	Group & computer	Computer type	Ref.	Status	Section
Oct 23 2019	RCS	53	20	Google Sycamore	Superconducting	[5]	Refuted by [6]	Sec. II A 1
Dec 03 2020	GBS	50	100	USTC Jiŭzhāng	Photonic	[7]	Weakly refuted by [8]	Sec. IIB1
Jun 28 2021	RCS	56	20	USTC Zuchongzhi	Superconducting	[9]	Challenged by $[10, 11]$	Sec. $IIC1$
Jun 29 2021	GBS	50	144	USTC Jiŭzhāng 2.0	Photonic	[12]	Weakly refuted by [8]	Sec. $IIB2$
Sep $08 \ 2021$	RCS	60	24	USTC Zuchongzhi	Superconducting	[13]	Challenged by [11, 14]	Sec. $IIC2$
Jun 01 2022	GBS	216	216	Xanadu Borealis	Photonic	[15]	Weakly refuted by [8]	Sec. II D 1
Apr 21 2023	RCS	67	32	Google Sycamore	Superconducting	[11]	Unrefuted	Sec. IIE
Apr 21 2023	RCS	70	24	Google Sycamore	Superconducting	[11]	Unrefuted	Sec. IIE
Apr 24 2023	GBS	50	144	USTC Jiŭzhāng 3.0	Photonic	[16]	Weakly refuted by [8]	Sec. II F
Jun 14 2023	QSim	127	60	IBM Kyiv	Superconducting	[17]	Refuted by $[18-22]$	Sec. II G
${\rm Mar}~01~2024$	QSim	567	-	D-Wave $ADV1/2$	Annealing	[23]	Unrefuted	Sec. II H

TABLE I. A chronological list of claims to quantum advantage and current statuses. Statuses show only the strongest challenge/refutations — additional ones can be found in the main text. Problem abbreviations are random circuit sampling (RCS), Gaussian boson sampling (GBS), and quantum simulation (QSim). Variables n and m denote the size of the experiment: nis the number of qubits and m is the circuit depth for random circuit sampling and gate-model quantum simulation; n is the number of photons and m is the number of modes for Gaussian Boson sampling; and in quantum annealing, n is the number of qubits but m is not defined since the evolution is not decomposed into gates. *Challenged* refers to literature improving the classical simulation and/or calling some aspect of the experiment into question; *Weakly refuted* means a new algorithm has been developed which likely could classically simulate the experiment on a powerful enough classical computer that is achievable in the near future; *Refuted* means a classical computer has simulated the experiment faster than the quantum computer.

for continuous variable quantum computers; and quantum simulation is the problem of (i) time-evolving a quantum state under a specified Hamiltonian then (ii) computing certain properties from the evolved state, e.g. expectation values of observables. Parameters n and mrefer to the size of the experiment. In random circuit sampling and quantum simulation, n is the number of qubits and m is the depth of the random quantum circuit, also referred to as the number of layers or cycles. In Gaussian boson sampling, n is the number of input photons and m is the number of modes (locations) where photons can be sampled. Each experiment involves additional parameters — such as the number of samples generated, the (estimated) fidelity, and the total runtime which are omitted from the table for brevity and discussed in the main text. The final column shows the current status of each experiment, for which we use the following terminology.

Terminology Here and throughout, we use quantum advantage, quantum supremacy, and beyond-classical *computation* interchangeably to mean the experimental demonstration of a well-defined computational task performed faster on a quantum computer than is believed to be possible on any classical computer. A *challenge* to a claim of quantum advantage is any work which demonstrates a significant improvement in the classical simulation time of a quantum advantage experiment. A weak refutation is a paper with evidence, via an improved classical algorithm and/or numerical demonstration, that with reasonably expected future classical computers a quantum advantage claim could be classically simulated. A (strong) refutation is the classical simulation of a quantum advantage experiment faster than the quantum computer.

A. The first demonstration of quantum advantage: Google's 2019 experiment in random circuit sampling on the *Sycamore* quantum computer

1. Description of the experiment

On Oct 23 2019, Google Quantum AI announced the first experimental demonstration of quantum advantage [5]. The paper, by passing the conventional arXiv submission prior to peer review and first appearing in Nature after peer review, showed computational advantage for the problem of sampling from random quantum circuits with n = 53 qubits and depth d = 20 on the Sycamore quantum computer. One million bitstrings were sampled in 200 seconds with estimated fidelity of 0.2%. (See the next section for an explanation of fidelity and other parameters described here.) Referring to the best-known classical simulation algorithms at the time, and assuming a state-of-the-art classical supercomputer (Summit), the authors estimated it would take ten thousand years to classically simulate the experiment. Thus computational advantage was demonstrated for the problem of random circuit sampling.

Back to Table I

2. Background on random circuit sampling

Random circuit sampling is the computational problem of sampling bitstrings from an n-qubit, depth d quantum circuit. This quantum circuit is designed to be hard to classically simulate relative to known classical algorithms. For example, quantum circuits with low entanglement such as short-depth circuits in one dimension can be efficiently classically simulated [24], quantum circuits with only Clifford gates can be efficiently classically simulated [25], and quantum circuits with peaked output distributions can be efficiently classically simulated [26]. In constructing the random circuit, two-qubit gates are applied, usually in a two-dimensional pattern, to rapidly increase entanglement, and single-qubit gates drawn randomly from an ensemble are inserted afterwards. This pattern of single- and two-qubit gates generally defines a *cycle* or *layer*, and the depth is the number of cycles. The random circuit U (and fixed input state $|0\rangle \equiv |0\rangle^{\otimes n}$) defines a probability distribution

$$p(z) := |\langle z|U|0\rangle|^2 \tag{1}$$

and is designed to follow a Porter-Thomas (exponential) distribution. The computational problem is to produce samples from the distribution p(z). Prior to the experiment, the problem of random circuit sampling and its theory had been developed in several papers [27–30], and the question of when quantum advantage would be achieved was highly anticipated and speculated on [31].

Experimentally, quantum computers are noisy. To ensure the device is producing signal instead of pure noise in the experiment, a metric known as the (linear) cross entropy benchmark (XEB) fidelity is computed. Letting $z_i \in \{0, 1\}^n$ be the sampled bitstrings from the device, the (linear) XEB fidelity is

$$\mathcal{F}_{\text{XEB}} := 2^n \mathbb{E}[p(z_i)] - 1 \tag{2}$$

where n is the number of qubits and $p(z_i)$ is the probability of sampling bitstring z_i . On a perfect (noiseless) quantum computer, $\mathcal{F}_{XEB} = 1$ for random circuits following the Porter-Thomas (exponential) distribution. On a completely noisy quantum computer which causes the output distribution to be completely flat, $\mathcal{F}_{\text{XEB}} = 0$. Thus $0 \leq \mathcal{F}_{XEB} \leq 1$, and the value of the fidelity gives an estimate to the quality of the quantum computer. Note importantly that $p(z_i)$ must be computed classically, thus \mathcal{F}_{XEB} is intractable to evaluate in the supremacy or beyond-classical regime and must be estimated. As noted, the the authors of [5] estimate an XEB fidelity of $\mathcal{F}_{\text{XEB}} = 0.002$. This estimate is done by evaluating the fidelity for small circuits which can be classically simulated, as well as evaluating the fidelity of large circuits that are modified to be easy to classically simulate, e.g. by removing some or all two-qubit gates across a bipartition of the circuit.

Although the random circuit sampling problem is classically hard and quantumly easy, it is not something (obviously) useful since the samples are drawn from random quantum dynamics. However, the idea to use the random circuit sampling to generate *certified* randomness quickly emerged and is being formalized [32, 33]. Thus, although not originally designed for this purpose, the random circuit sampling problem may have applications in certified random number generation.

3. Significance of the experiment

Prior to the experiment, as mentioned, whether quantum advantage could be achieved, and when it could be achieved, were highly discussed open questions [1, 2, 31]. Although it is questionable whether the computational problem solved by Sycamore has practical value, the experiment has remarkable aspects and profound implications for both the theory of quantum physics and the theory of computer science. Physically, as noted in a talk by John Martinis on Nov 01 2019 at Caltech just after the results were announced, this experiment can be considered a test of quantum mechanics at a scale which has never been achievable before. Indeed, the experiment probes a Hilbert space of size roughly 10^{16} , whereas the previous largest tests of quantum mechanics took place in Hilbert spaces of size roughly 10^3 . The fact that the experiment behaved as expected at this scale is a remarkable testament to the theory of quantum mechanics. In computer science, the experiment provides evidence that the extended Church-Turing thesis — at the core of the theory of quantum computational complexity since the 1980s [34] — may be violated. This thesis posits that a probabilistic Turing machine (i.e., classical computer) can efficiently simulate any physical process (i.e., computation) with polynomial overhead. If a quantum computer is truly performing a computation that cannot be simulated classically, the extended Church-Turing thesis would be violated. As noted in [28], this has both practical and and philosophical implications, demonstrating that quantum mechanics challenges our models of information and computation built on classical physics. For example, Bell's inequality shows quantum correlations (entanglement) are stronger than classical correlations and refutes local hidden variable theories. Quantum advantage experiments can thus be thought of as computational analogues to Bell experiments, as noted in [28]. Finally, the extremely good performance of the Sycamore computer — average simultaneous single-qubit error of 0.16% and average simultaneous two-qubit error of 0.62% [5] — are remarkable achievements in experimental physics and engineering. These comments generally apply equally to subsequent quantum advantage experiments but are only stated here for the first experiment.

4. Challenges to the experiment

While the experiment was announced when the paper was published in *Nature* on Oct 23, 2019, the first challenge to the experiment came two days before on Oct 21, 2019² [35]. This seemingly bizarre fact is because the pa-

 $^{^2}$ As developments were rather rapid and chronology is important, here and throughout we use the first posting (typically to arXiv) for the date.

per was accidentally leaked on a NASA pre-print server on Sep 14, 2019 during peer review [36, 37]. This challenge built on previous work [38] and claimed that with memory modifications it would only take Summit a matter of days, rather than thousands of years, to simulate the experiment using the simple Schrödinger algorithm in which the entire wavefunction is stored and updated gate-by-gate. However this is a (disputed) claim and not an actual computation, and no actual computation has been performed since the challenge appeared five years ago. So this challenge appears to be unsubstantiated, however it is of historical interest as the first challenge to a claim of quantum advantage, humorously coming two days before the claim of quantum advantage was made.

The first chronologically intelligible challenge to Google's 2019 experiment appeared on Feb 5, 2020 [39], estimating a 10,000 times speedup over the 10,000 year estimate of [5]. This speedup is achieved through new algorithms to find good contraction paths in tensor networks, formulating the problem of simulating a quantum circuit as contracting a tensor network [40]. The best algorithm for contracting tensor networks from Google's 2019 experiment, roughly speaking, uses a divisive approach to partition a vertex in the contraction graph into k partitions (k being a hyperparameter) then emplys a greedy or optimal algorithm to construct the contraction tree for each subgraph. This approach, known as hypergraph partitioning, is shown to produce an orders of magnitude better contraction cost compared to five other state-of-the-art algorithms when applied to Google's 2019 experiment. This approach is also combined with slicing to parallelize tensor network contraction. To mimic the fidelity f of Google's experiment, it is proposed to sample from the maximally mixed state $I/2^n$ with probability 1 - f and sample from $|\psi\rangle$ (i.e., contract the tensor network) with fidelity f. Referencing a similar recent tensor network contraction on Summit, the authors estimate that Google's experiment could be performed in 195 days on Summit, assuming a 68% FLOPS efficiency.

The first challenge to Google's 2019 experiment utilizing noise to make the classical simulation easier occurred on Feb 18, 2020 [41]. As mentioned, the fidelity of Google's experiment was estimated at 0.2%. The authors of [41] ask what random circuits are classically simulable with low fidelity. Their technique uses the well-known time-evolving block decimation (TEBD) algorithm [24] with truncation to emulate loss of fidelity. In this technique, the wavefunction is represented by a matrix product state (MPS) and gates are applied by contracting the tensors into the MPS. For two-qubit operations, a singular value decomposition is performed after contracting the operation into the MPS. A degree of approximation is achieved by truncating the singular value (Schmidt) spectrum, either by keeping a maximum number of singular values (Schmidt rank) or discarding singular values below a pre-determined threshold. Arguing that singular value truncation is a proxy for physical noise in quantum computers, and arguing that overall fidelity due to

approximation is multiplicative in each gate fidelity, the authors of [41] are able to simulate two-dimensional random circuits on n = 54 qubits with depth 20, the same parameters as in Google's 2019 experiment [5]. However, the random circuits in [41] are not identical to Google's experiment since they use controlled-Z (CZ) gates and different random rotations on single qubits. The different two-qubit gate is notable because CZ has Schmidt rank two whereas the \sqrt{iSWAP} used in Google's experiment has Schmidt rank four. Although the entanglement dynamics are not completely determined by the Schmidt rank, it is generally expected that higher Schmidt rank corresponds to harder classical simulation. Using a maximum MPS bond dimension of $\chi = 320$ to produce a final fidelity of around 0.2% as in Google's experiment, the total classical simulation on a single core took less than 48 hours and used 4.5 GB of memory. When using a twoqubit gate with Schmidt rank four, as in Google's 2019 experiment, the authors are unable to perform the classical simulation with fidelity as large as Google's 2019 experiment. They speculate that a parallelized version with a few hundred cores and a few terabytes of memory could reach comparable fidelity, but note that such a calculation has not been attempted. While this work raises many interesting questions, and is very notable as the first to exploit approximate classical simulation to challenge Google's 2019 experiment, it is generally not considered to refute Google's 2019 experiment because of differences in the circuits and differences in the definition of fidelity.

On May 14 2020, another approach using optimized tensor network contraction [42] was put forth to challenge the 10,000 year estimate. Specifically, for depth 14 circuits with 53 qubits, the authors collect three million samples with 1% fidelity in 264 seconds. In addition to significantly improving the 1.1 year estimate of [5], this time is actually two times faster than Sycamore. For depth 20, it was estimated to take twelve hours to sample bitstrings at 0.2% fidelity. However, this estimate is assuming 100% FLOPS efficiency, when in practice on depth 14 circuits only a low FLOPS efficiency of around 15% was reached. The main contribution in this approach is optimization of the tensor network contraction through several veins. First, the authors identify a "stem" of the contraction tree which dominates the cost, and optimize this stem through several recently introduced techniques — notably hypergraph partitioning [39] and dynamic slicing [43] — to find a good contraction path. As in [31, 44], six time-like edges are left open in the tensor network to compute a batch of amplitudes and sample bitstrings via frugal rejection sampling. Although there are many improvements introduced in this work and the depth 14 results are impressive, the depth 20 results in 12 hours would have required substantial engineering effort and improved hardware to be done in practice, thus we do not consider this work to be a weak refutation of Google's 2019 experiment.

On Mar 04 2021, a challenge to Google's 2019 experi-

ment was announced by two researchers from the Chinese Academy of Sciences [45]. In this work, the authors are able to sample one million *correlated* bitstrings from the 53 qubit depth 20 Sycamore circuits in five days. The reason why bitstrings are correlated can be understood from the method. As in previous works, the authors use tensor network contraction to simulate the circuit. Whereas previous works have kept a small number (typically six) of qubits open to compute a batch of amplitudes rather than a single amplitude, a key contribution of this work is to select a large number of open qubits, significantly increasing the batch size. As noted by the authors, keeping more qubits open increases the complexity of the contraction, and finding an optimal set of qubits to keep open is a hard combinatorial optimization problem. To deal with these challenges, the authors first find a good contraction order and then select the set of open qubits based on this order. This contraction order is optimized to find a structure — called a "big-head structure" by the authors — which encapsulates the bottleneck of the contraction. The overall tensor network is then partitioned into the *head* and *tail* sub tensor networks, where qubits in the head are open and gubits in the tail are closed, which are further partitioned and contracted independently. The final step is to contract the resulting head and tail tensors (vectors) via a dot product. Because the key idea of this approach is to maximize the number of open qubits which occur in the "head" tensor network, this algorithm is dubbed the "big head algorithm." It is important to note that the authors use dynamic slicing to contract the head and tail tensor networks, building on previous work [39]. This results in 2^{23} subtasks, each of which have 2^{30} space complexity and are put into 32 GB of GPU memory. For sampling different bitstrings, the algorithm can be perfectly parallelized; the authors use a cluster of 48 NVIDIA V100 GPUs and 12 NVIDIA A100 GPUs to sample two million bitstrings in about five days. In practice, the head tensor network contains 21 open qubits and the tail tensor network contains 32 fixed (closed) indices. This means that each contraction yields a set of $2^{2}1$ bitstrings, of which 32 bits are fixed. Thus, the sampled bitstrings are correlated. This bitstrings are then post-selected to reduce correlations and obtain a linear XEB fidelity of 0.739, higher than that achieved by Sycamore in Google's 2019 experiment. Thus, less than eighteen months after Google's announcement of quantum supremacy, the estimated classical runtime of 10,000 years was reduced to five days, albeit with caveats such as the fact that bitstrings were correlated.

On Oct 27 2021, a scheme to sample one bitstring from Google's 2019 experiment in 304 seconds on the Sunway supercomputer was presented [46]. Estimating a runtime of 7,610 years on Sunway at 100% compute efficiency to do the "naive" tensor network contraction, the authors build on previously discussed work and utilize a PEPSbased contraction algorithm optimized for both the circuits and the underlying Sunway architecture. Sampling is done by frugal rejection sampling in which 512 amplitudes are computed in a batch (i.e., ten qubit wires are left open in the contraction). The authors use 41,932,800 cores on Sunway, each having 32 GB memory and a peak performance of 4.7 TFlops, in their largest experiment. Circuit sizes of up to n = 100 qubits and m = 42 cycles are considered, however the definitions of random circuits here are not identical with those used experimentally, differing both in the definition of depth as well as the type of two-qubit gate (which drastically affects complexity). For example, this work references and builds off [47], consisting of several of the same authors, in which n = 64and depth m = 25 quantum circuits were simulated on a personal computer, numbers which would have already refuted Google's 2019 experiment if they corresponded directly to the definitions used in the experiment. In the published version of the paper in ACM, a video of a talk given by an author shows that with further improvements it is projected that one uncorrelated sample could be drawn in 60.4 seconds. Recall that Sycamore sampled one million bitstrings in 200 seconds.

On Nov 01 2021, a single uncorrelated bitstring from the n = 52, m = 20 random circuits in Google's 2019 experiment is sampled on the Sunway supercomputer in 400 seconds in single-precision arithmetic and 276 seconds in mixed-precision arithmetic [14]. This work applies the "big head" contraction algorithm of [45] combined with the previous optimizations for Sunway (by a similar group of authors) in [46], again using 41,932,800 cores but this time with experimental parameters (i.e., n, m, and the two-qubit gates + overall structure of the random circuits) matching those of Google's 2019 experiment. In this work six qubit wires are left open to compute a batch of 64 amplitudes per contraction, then frugal sampling is performed to extract uncorrelated bitstrings. In addition to the m = 20 cycle experiment, the authors also consider the m = 12 and m = 14 cycle experiments, showing they can draw bitstrings in 18 and 82 seconds, respectively.

5. Refutations of the experiment

On Nov 04 2021, two years and twelve days after Google's announcement of quantum advantage, the experiment was (weakly) refuted [48]. This work, posted by the same authors as [45] in addition to one other co-author, generated one million uncorrelated bitstrings from the Sycamore circuits with fidelity 0.0037 in fifteen hours. This computation was performed on a cluster of 512 GPUS, and, while slower than Sycamore which sampled one million bitstrings in 200 seconds, it is estimated and reasonably believed that on a larger exa-scale cluster the entire classical simulation could be done in a few dozens of seconds, *faster* than Sycamore. For this reason we take this to be a weak refutation of Google's 2019 experiment. The key new idea in this work is removing a subset of edges to contract in the original tensor network to obtain an approximate tensor network. This approximation can be viewed as the analogue of noise in the quantum processor. Specifically, breaking an edge is equivalent to a Pauli error $E := (I + Z)/2 = |0\rangle\langle 0|$, the projector onto the $|0\rangle$ state, effectively replacing the local state with a $|0\rangle$ state. As each path in the error channel E contributes weight 1/2, each broken edge halves the fidelity. In practice, eight edges (or four two-qubit gates) are removed to get a fidelity of $2^{-8} \approx 0.0039$, which combined with other approximations yield the final fidelity estimate of 0.0037. These other approximations come from exploiting the singular value spectrum of the two-qubit gates in special cases. The approximate tensor network is then contracted using the big head algorithm [45], which again builds on previous work by, e.g., incorporating dynamic slicing [39]. In this work, however, six qubits are left open in the head tensor network, and importance sampling is used to remove correlations in the sampled bitstrings. Ultimately, $2^{20} \approx 10^6$ uncorrelated bitstrings were computed in just over fifteen hours. The code, contraction path(s), and sampled bitstrings are openly available [49]. We remark that Ref. [10] is also notable for achieving similar runtime (15 hours) just two months later.

On Jun 27 2024, Zhao et al. claimed the first strong refutation of Google's 2019 experiment, using a cluster of 1432 GPUs to compute three million samples in 86.4 seconds, faster than the time it took Sycamore to sample one million bitstrings (200 seconds). The algorithm is a culmination of previous techniques (which have been previously described) including the "big head" algorithm, dynamic slicing, and optimizing the stem of the contraction tree. Markov chain Monte Carlo is used to sample, then bitstrings are post-selected to maximize the XEB fidelity. In particular, ten gubits are left open in the "head" of the tensor network and $3 \cdot 10^6$ samples are drawn. Out of a total 2^{24} subtasks (from slicing), only 0.03% of these are contracted to reach an XEB value of 0.002 which is what was achieved by Sycamore. Distributed across 1432 GPUs the entire simulation takes 86.4 seconds. To the author's knowledge, this work constitutes the first strong refutation of of Google's 2019 random circuit sampling experiment. It is interesting to note that the authors also consider power consumption of both experiments. Noting that previous challenges to Google's 2019 experiment have used roughly three orders of magnitude more energy than Sycamore (which is taken to be 4.3 kWh for cooling), the authors note that their entire simulation requires 13.7 kWh. Thus, although still larger, this is significantly closer to energy consumption of Sycamore. In a comment on the arXiv version of this paper, it is noted that the work was completed in Aug 2023 and that a 50x improvement has since been achieved, however this has yet to be published. Finally, it is worth remarking that as classical techniques have steadily improved culminating in this refutation, quantum computers have likewise steadily improved resulting in larger random circuit sampling experiments which have not been refuted (see Tab. I and the subsequent discussion).

It is notable that Google's decision to openly share data from the experiment [5] — the exact circuits and sampled bitstrings are made available — has significantly catalyzed these developments and advanced science. It is also important to note that, as can be seen in the preceding discussion, there is a clear thread of ideas being used and built upon from the first challenge to the final refutation. Without the infrastructure or the incentive to publish scientific articles freely online — in this case the arXiv — the developments described here would have taken significantly longer or may not have happened at all.

6. Loopholes in the cross entropy benchmark fidelity

In the previous section, the classical simulators input quantum circuits and output bitstrings in the same way that a quantum computer would, and the XEB fidelity was used as a benchmark of the quality of the bitstrings. A different strategy is to focus on the definition of XEB fidelity itself and devise a classical algorithm which takes advantage of any loopholes in this metric. The first such work towards this end was presented in [50] in which the authors try to use locality to "spoof" the cross entropy benchmark. In this work, a randomized classical algorithm is given to yield $\mathcal{F}_{\text{XEB}} = 1/\text{poly}(n)$ (on average) in running time $2^{O(m^c)}$ where the depth of the Haar random circuit is logarithmic in the number of qubits $m = O(\log n)$ and c is a constant. Note that random circuit sampling experiments are designed to scale the depth as $m \sim \sqrt{n}$. However, as noted by the authors, prior to their work only results with constant m = O(1)were known. As mentioned, the key idea of this spoofing strategy is to exploit locality. In particular, the algorithm works by identifying a small number of qubits with disjoint light cones to compute the output distribution of. Bits are sampled from these qubits according to the computed probability distributions, then bits are sampled uniformly at random for the remaining qubits. For a light cone size of L the time to find disjoint qubits can be done in poly(n) time, while computing the marginal distributions requires time $poly(n, 2^L)$. The main question is thus the locality of the XEB fidelity. In follow-up experimental work [11] (Sec. IIE), this question is experimentally probed to find that global correlations are the biggest contributing factor to XEB fideltiy.

The validity of XEB was also called to question in [51]. In this work, an efficient classical algorithm which achieves high XEB values without simulating the full circuit is presented. This algorithm simply partitions the circuit into l parts of size $\lceil n/l \rceil$ qubits which can be simulated directly in time exponential in l. It is argued that these partitioned circuits will achieve relatively high XEB values, and several ways to improve the XEB based on post-processing sampled bitstrings are given. For Google's experiment, the circuits are partitioned into roughly equal halfs of l = n/2 qubits, and this subsystem is simulated on an NVIDIA Tesla V100 GPU with 32GB memory in about one second, achieving an XEB of 2.7×10^{-4} , a value that is 12.3% of the experimentally achieved value (around 0.2%). Additionally, a general discussion of vulnerabilities of XEB as a metric is given. In particular, examples where the XEB fidelity and "traditional" fidelity $F := \langle \psi | \rho | \psi \rangle$ (where ρ is the noisy state and $|\psi\rangle$ is the target state) diverge are given. The authors also show numerically that the ratio of XEB to "traditional" fidelity actually increases in n with their algorithm faster than on a noisy quantum processor with fixed error rate.

B. Two Gaussian Boson sampling experiments on the *Jiŭzhāng* quantum computer

1. Description of the first experiment

On Dec 03 2020, researchers from USTC reported an n = 50, m = 100 Gaussian boson sampling experiment with threshold detectors measuring up to $N_c = 76$ clicks [7]. The authors estimate a quantum computational advantage of 10^{14} — i.e., it would take the best-known classical algorithm running on the TaihuLight supercomputer 10^{14} times as long as the quantum computer. As the Gaussian boson sampler $Ji\tilde{u}zh\bar{a}ng$ took 200 seconds to collect all samples, this corresponds to an estimate of 2.5 billion years to classically simulate the experiment.

The experiment uses 25 two-mode squeezed states, equivalent to n = 50 single-mode squeezed states, as input. Both the spatial and polarization degrees of freedom are used to implement a random 100×100 unitary transformation acting on the basis $|H\rangle_1, |V\rangle_1, ..., |H\rangle_{50}, |V\rangle_{50}$. Here, H denotes horizontal polarization, V denotes vertical polarization, and subscripts index the mode. The unitary transformation is implemented by 300 beam splitters and 75 mirrors. The m = 100 output modes are detected by 100 threshold detectors with an average efficiency of 81%. Up to $N_c = 76$ photons are detected in the experiment, and the total data collection time of the experiment is 200 seconds.

Just as in random circuit sampling (Sec. II A 1), the experimental apparatus is noisy and needs to be benchmarked or validated to show it is behaving as intended. Also similar to random circuit sampling, this is tricky because the experiment is designed to be beyond classical so that the output cannot directly be verified. Nonetheless, several measures are taken towards this end. First, the 100×100 unitary matrix is measured experimentally and computed analytically and shown to be in agreement. The experimentally measured matrix is also shown to be (Haar) random which is required for the computational hardness. Next, a smaller experiment with n = 6 single-mode squeezed states and an output photon number of two is performed. In this regime, the experiment is small enough to be classically simulated.

The fidelity $F := \sum_i \sqrt{p_i q_i}$ and total variation distance $D := \sum_i |p_i - q_i|/2$ are used to compare the ideal and experimental distributions p and q. For these small experiments. the average fidelity is 0.990 and the average total variation distances is 0.103. (For a perfect boson sampler, the fidelity would be one and the total variation distance would be zero.) Finally, the authors consider several scenarios under which the large-scale experiment would be classically simulable, and show these scenarios produce outcomes which do not agree with the experimental results. For example, the authors consider the scenario in which the input light was distinguishable, as well as the case in which the boson sampler was just doing uniform random sampling, and show strong deviations from the actual experiment.

Last, we note importantly that this experimental configuration is not programmable, meaning that performing a different experiment would require physically changing hardware components.

Back to Table I

2. Description of the second experiment

Approximately six months after the first experiment, on Jun 29 2021 the same team from USTC published an improved version of their Gaussian boson sampling experiment [12]. In this improved version, a Gaussian boson sampling experiment with threshold detection is performed on the photonic quantum computer Jiuzhang 2.0 with n = 50, m = 144, and up to $N_c = 113$ clicks. This largest number of clicks corresponds to sampling from a Hilbert space with dimension around 10^{43} . It is estimated that the same computational task would take 10^{24} times longer using brute-force simulation on classical supercomputers. The total sampling time in the experiment is 200 seconds. The Jiuzhang 2.0 computer is also partially programmable — phases can be changed via the addition of adjustable electric delay lines. This is an improvement over the first experiment which was not programmable, however the majority of the hardware is still fixed and this does not represent a programmable computer.

This experiment introduces the new concept of stimulated emission of squeezed states to address the difficulty of generating large arrays of squeezed states suitable for Gaussian boson sampling. Using this, 25 twomode squeezed states, corresponding to n = 50 singlemode squeezed states, are sent into an m = 144 mode interferometer implementing a random unitary transformation. After, the output photons are detected with 144 single-photon detectors with an average efficiency of 83%.

As in the first experiment, the authors consider several methods which could spoof their experiment — such as using thermal states (due to excessive photon) loss or performing uniform random sampling — and show they deviate from their experimental results. This is also done for smaller experiments in which the results can be classically simulated, providing some verification that the Gaussian boson sampler is performing as intended in the beyond-classical regime.

Back to Table I

3. Background on (Gaussian) boson sampling

Boson sampling [52] is the quantum analogue of a Galton's board — spherical balls dropped through a series of equally spaced pegs to illustrate, in the limit of many balls, a normal distribution. Here, the probability of finding a ball in a particular location is given by the permanent of the matrix $A = [a_{ij}]$ where a_{ij} is the probability of ball *i* landing at location *j*. In the classical case, $a_{ij} \ge 0$. This leads to an efficient (classical) algorithm to approximate the permanent [53]. The Boson sampling problem is identical to this problem, however the matrix A has complex elements. In this case it turns out that unless $P^{\#P} = BPP^{NP}$ and the polynomial hierarchy collapses to the third level, the exact Boson sampling problem is not efficiently solvable by a classical computer [52, Theorem 1]. Typically photons are used experimentally, and we will use photon and boson interchangeably. Experimentally, a setup analogous to a Galton's board is constructed in which n identical photons can be found in m*modes* (locations). The experiment can be described by an $m \times m$ unitary transformation, which is constructed via a sequence of smaller unitary transformations that are realized experimentally by optical elements, e.g. beamsplitters and phaseshifters. Let U be the $m \times m$ unitary implemented by the experiment, and let A be the $m \times n$ isometry defined by the first n columns of U. Then, the probability of sampling $z = z_1 \cdots z_m$ where $\sum_i z_i = n$ is given by

$$p(z) = \frac{|\operatorname{Per} A_z|^2}{z_1! \cdots z_m!} \tag{3}$$

where A_z is the square submatrix of A with z_i copies of row i [54]. The permanent of a square $n \times n$ matrix Mis given by $\sum_{\sigma \in S_n} \prod_{i=1}^n a_{i\sigma(i)}$ where S_n is the symmetric group of n elements — i.e., the set of all permutations of n elements. As in random circuit sampling, the computational problem of boson sampling is to produce samples from the distribution p(z). Note that boson sampling is not a universal model for quantum computation, however when combined with adaptive measurements the model is universal [55].

Sources of single photons (primarily spontaneous parametric down conversion) are non-deterministic, creating experimental challenges to scaling boson sampling. Because of this several variants have been proposed. In Gaussian boson sampling (GBS) [56], a particular Gaussian state known as a single-mode squeezed state is used as input to the array of optical elements. The output is measurements in the photon number basis, as in boson sampling. The difference is that now the probability of sampling depends on the *hafnian* of a matrix characterizing the state, rather than the permanent. The hafnian is another matrix function related to the permanent by $\operatorname{Perm}(A) = \operatorname{Haf} \begin{bmatrix} 0 & A \\ A^T & 0 \end{bmatrix}$ and computing it is also in the class #P, even in the approximate case (under some assumptions) [56]. Due to experimental advantages, Gaussian boson sampling has thus far been the preferred experimental route to demonstrating quantum advantage via boson sampling.

An output sample from a boson sampling experiment depends on the type of measurement apparatus, or detector, that is used. Certain detectors count the number of photons in each mode, termed photon number resolving detectors. In this case, an output sample is a string of non-negative numbers $z_1, \dots z_m$ where z_i is the number of photons detected in mode *i*. Photon number resolving detectors are currently based on superconducting technology and must be operated at cryogenic temperatures. An alternative, proposed in [57], is to use threshold de*tectors* which distinguish between two cases: zero photons, or one or more photons. The case of one or more photons is referred to as a *click*. Thus in this case the output is a bitstring $z \in \{0,1\}^m$, and the number of ones in the bitstring z is the number of clicks in the experiment. Threshold detectors can be operated at room temperature, providing an experimental advantage over photon umber resolving detectors. The best-known classical algorithm for classically simulating Gaussian boson sampling with threshold detectors scales as $O(m^2 2^{N_c})$ where N_c is the number of clicks (and m as before is the number of modes) [57].

After the theoretical proposal, several small, proofof-principle boson sampling experiments with increasing complexity had been performed [58–66]. Prior to the first claim of quantum advantage in boson sampling, the state of the art was an Oct 22 2019 paper in which results from an n = 20 photon and m = 60 mode Gaussian boson sampling experiment with up to $N_c = 14$ detected photons were presented [67].

4. The status of classically simulating Gaussian boson sampling prior to quantum advantage experiments

Prior to these experiments claiming quantum advantage, Neville *et al.* in 2017 developed and benchmarked classical algorithms for boson sampling to set the goalposts for quantum advantage [54]. In this work, a small cluster was used to classically compute 250 samples from an n = 30, m = 900 boson sampling problem in five hours. From this benchmark of their algorithm, as well as from experimental parameters of recent boson sampling experiments, the authors estimate it would require around n = 80 photons with $m = n^2$ modes to reach quantum advantage.

After this work, in 2017 Clifford and Clifford presented

an exact classical algorithm for boson sampling which improves the brute-force sampling algorithm [68]. For an n boson, m mode problem, the brute-force algorithm requires computing $\binom{m+n-1}{n}$ permanents of $n \times n$ matrices, giving a runtime of $O(\binom{m+n-1}{n}n2^n)$. As noted by the authors, in the case that $m \ge n^2$ this becomes $\Theta(2^n e^n (m/n)^n \sqrt{n})$ as shown in [52]. The authors present a new algorithm for exact sampling which takes time $O(n2^n + mn^2)$ and O(m) space. This algorithm is inspired by hierarchical sampling in Bayesian computation uses several innovations, for example introducing permutations which do not change the permanent and make it easier to compute, using conditional sampling, and using the Laplace expansion for permanents. Ultimately, the algorithm presents a large $\binom{m+n-1}{n}$ speedup for the boson sampling problem and has small constant factors making it amenable to implementation. Indeed the algorithm has been implemented in R and is freely available [69]. The authors estimate it would require n = 50 photons with $m = n^2$ modes to achieve quantum advantage in boson sampling.

In 2018, two algorithms for computing the permanent of $n \times n$ matrices with complexity $O(n^2 2^n)$ were implemented on the Tianhe-2 supercomputer as a classical benchmark of boson sampling [70]. The two algorithms are the Ryser algorithm [71] implementing the formula

Per
$$A = (-1)^n \sum_{S \subset \{1,2,\dots,n\}} (-1)^{|S|} \prod_{i=1}^n \sum_{j \in S} a_{ij}$$

and the so-called BBFB algorithm [72, 73] implementing the formula

$$2^{n-1} \operatorname{Per} A = \sum_{\delta} \prod_{k=1}^{n} \delta_k \prod_{i=1}^{n} \sum_{j=1}^{n} \delta_j a_{ij}$$

where $\delta = \{\delta_1, ..., \delta_n\}$ with $\delta_1 = 1$ and $\delta_i = \pm 1$ for i > 1. These algorithms are parallelized across up to 312,000 CPU cores, and the result is that one sample from an n = 50 boson sampling experiment (with $m = n^2$) can be drawn in around 100 minutes.

In 2018, Björklund *et al.* devised an algorithm to compute the hafnian of a complex matrix in time $O(n^3 2^{n/2})$ and benchmarked it on the Titan supercomputer [74]. Recall that computing the permanent corresponds to boson sampling and computing the hafnian corresponds to Gaussian boson sampling. Although the developed algorithm is perfectly parallel, the authors estimate that computing the hafnian of a 100 × 100 matrix would require the 288,000 CPUs of Titan roughly 1.5 months, assuming perfect parallelization over distributed nodes. The largest computed benchmarks were for 50 × 50 matrices which took a few hundred seconds on a single node and a few seconds on around 100 nodes, both using 16 threads per node.

Also in 2018, a similar group of authors in Ref. [75] implemented the proposed sampling algorithm from the previously-described original paper proposing Gaussian

boson sampling with threshold detectors [57]. Using a similar parallel scheme on the Titan supercomputer, this time with up to 240,000 nodes, a classical simulation of Gaussian boson sampling with m = 800 modes and $N_c = 20$ clicks is implemented, producing a sample in around two hours. This benchmarking indicates that Gaussian boson sampling with threshold detectors could achieve quantum computational advantage with $m = 2N_c^2$ modes and $N_c > 22$ clicks.

In 2019, Qi *et al.* considered noisy processes in Gaussian boson sampling and used this to reduce the classical simulation time [76]. In particular, a model of photon loss during state preparation is considered and it is shown that lossy Gaussian boson sampling can be efficiently simulated classically when the average number of detected photons is quadratically related to the number of input photons. This result establishes a condition which Gaussian boson sampling experiments must satisfy in order to claim computational hardness. Interestingly, the authors also show that *exact* lossy Gaussian boson sampling is likely still hard. Specifically, it is shown that if lossy Gaussian boson sampling can be efficiently simulated classically, then the polynomial hierarchy collapses to the third level.

Later in 2019, Wu *et al.* developed an alternative algorithm and sampled from an n = 18, $m = n^2 = 324$ Gaussian boson sampling experiment on a laptop in twenty hours [77]. This algorithm assumes single mode squeeze states as input and its complexity depends on the squeezing parameter. The algorithm is only benchmarked against brute force sampling and not rigorously compared to other relevant work.

In September 2020, just a few months before the first experiment claiming quantum advantage was posted, authors including those on the experimental paper [7] benchmarked Gaussian boson sampling with threshold detection on the Sunway TiahuLight cluster [78]. An n = 50 Gaussian boson sampling experiment is distributed across 32,286 nodes (157,144 processors) of Sunway TaihuLight (which contains a total of 40,960 nodes). Using a Markov Chain Monte Carlo sampling method, computing one sample took from a $N_c = 50$ click detection took about 20 hours in 128 bit precision and about two days for 256 bit precision. This large-scale classical computation set the boundary for quantum advantage which was to appear just a few months later.

Finally, in October 2020, a paper by Queseda *et al.* presents a quadratic speedup for clasically simulating Gaussian boson sampling [79]. The algorithm would be corrected in subsequent version of the manuscript in August 2021, however the main claim of quadratic speedup remains. The algorithm introduces partial heterodyne measurements so that only pure state probabilities need to be calculated. Implementing the algorithm on a small cluster of 96 CPUs, the authors are able to compute a pure state probability in around an hour for a 50 × 50 matrix, corresponding to a Gaussian boson sampling experiment with $N_c = 50$ detection events.

5. Challenges to the experiments

On May 20, 2021, Shi and Byrnes provided a new result which reduces the complexity of classically simulating Gaussian boson sampling with both threshold detectors and photon number resolving detectors when input photons are distinguishable [80]. In particular, the authors define the *indistinguishability efficiency* η_{ind} as the probability that an input indistinguishable photon does not become distinguishable. In other words, $\eta_{\rm ind}=1~{\rm cor-}$ responds to all indistinguishable photons, while $\eta_{ind} = 0$ corresponds to all distinguishable photons. In the complexity of generating a sample with N_c photons (clicks) $O(\text{poly}(N_c)2^{N_c/2})$, the algorithms provide a speedup in the exponential term from $2^{N_c/2}$ to $2^{N_c \eta_{\rm ind}/2}$. This encapsulates the result that Gaussian boson sampling with distinguishable photons, corresponding to $\eta_{\text{ind}} = 0$, is efficiently simulable classically, as well as the speedups obtained for *partial* (in)distinguishability $0 < \eta_{ind} < 1$. No large-scale numerical simulations are performed and no estimated speedup over either Gaussian boson sampling experiment is provided. We remark that the indistuingishability in Gaussian boson sampling was also considered by Renema in 2019 [81].

On Aug 03 2021, a new work exploiting collisions in Gaussian boson sampling was presented, estimating a 10^9 reduction in the time to classically simulate the Jiŭzhāng experiments [82]. A collision in boson sampling occurs when two or more photons are measured in the same mode. The computational hardness results for boson sampling assume photon number resolving detectors, but the experiments used threshold detectors. As shown in [57], the hardness results do not change for threshold detectors as long as the probability of collisions is sufficiently small. However, the authors note that collision probability in the *Jiŭzhāng* experiments is non-negligible, also noted in [80], and develop algorithms for experiments in which collisions are likely. Intuitively, collisions allow one to group photons into pairs such that the number of terms when computing hafnians is reduced. Letting n_i be the number of photons measured in mode *i*, the lower bound for the number of terms when grouping is $\prod_i \sqrt{n_i+1}$, as opposed to $2^{\sum_i n_i/2}$ terms without grouping. In the case of threshold detectors with N_c clicks, the authors algorithm reduces the 2^{N_c} complexity to $2^{N_c/2}$. The algorithms are implemented on a cluster with 1024 nodes, and the authors are able to classically simulate Gaussian boson sampling experiments with threshold detectors with up to m = 100 modes and $N_c = 60$ clicks. In the case of photon number resolving detectors, the authors are able to simulate a 92 photon sample, but at significantly increased runtime.

On Sep 09 2021, work by Kaposi *et al.* presented a polynomial speedup in Gaussian boson sampling with threshold detectors [83]. While not commenting directly on the claimed computational advantage of either experiment, the authors show a 237x speedup over the best-known classical algorithm for problem sizes larger

than around $N_c = 20$. We note that this algorithm is implemented in an open source Python package [84]. This speedup is obtained by careful reuse of calculations during the evaluation of the Torontonian matrix function. As fitted empirically, this reduces the complexity of the best-known algorithm from $O(N_c^{2.7355}2^{N_c/2})$ to $O(N_c^{1.0695}2^{N_c/2})$, i.e., a speedup of approximately $N_c^{1.666}$, where N_c is the number of detected photons (clicks).

6. Loopholes in Gaussian boson sampling

On Sep 23 2021, researchers from Google published a classical algorithm which provides better total variation distance than the experiment and which is quadratic in the number of modes [85]. The algorithm exploits a key difference between Gaussian boson sampling and random circuit sampling — in random circuit sampling, marginal distributions for any subset of qubits are (exponentially) close to the uniform distribution, however in Gaussian boson sampling marginal distributions are not generally close to uniform and in fact can be efficiently approximated. The intuition for this algorithm is to sample from a distribution that approximates all single-mode and twomode marginals. While the cost of computing a probability is still exponential in the number of clicks, restricting to subsets with one or two modes makes the cost upper bounded by the size of these subsets, which is chosen to be small. Thus marginal distributions over a small number of modes are easy to compute in (Gaussian) boson sampling. The authors use a Boltzmann machine and Gibbs sampling to produce "mockup samples". The runtime of the algorithm scales as $O(m^2 L)$ where m is the number of modes and L is the number of samples. Using this algorithm, the authors are able to compute millions of bitstrings per minute on a single workstation. In an updated version of the original experimental paper [7], an added note emphasizes that collision modes dominate in the experiment, and that the actual photon number is approximately twice the number of clicked detectors. It is therefore claimed that the algorithm of [85] cannot readily be used to speed up their experiment.

As a final note, we remark that Ref. [86] attempts to close several potential loopholes in Gaussian boson sampling and introduces a new architecture — termed "highdimensional Gaussian boson sampling" — which is programmable and which may experimentally outperform previous Gaussian boson sampling experiments.

C. Two random circuit sampling experiments on the *Zuchongzhi* quantum computer

1. Description of the first experiment

On Jun 28 2021, the USTC group reported a random circuit sampling experiment with n = 56 qubits and m = 20 cycles [9]. Approximately 19 million bitstrings are sampled in 1.2 hours at an estimated fidelity (2) of 0.0662%. The authors estimate that the classical computational cost of simulating their experiment is two to three orders of magnitude higher than Google's 2019 random circuit sampling experiment [5] (Sec. II A 1). In particular, building on recent advances in tensor network simulation of random quantum circuits (Sec. II A 4), they estimate Google's 2019 experiment could be classically simulated on Summit in 15.9 days, whereas their experiment would take 8.24 years.

The experiment is performed on the Zuchongzhi quantum computer which consists of a two-dimensional architecture with 66 superconducting transmon qubits and tunable couplers. The average single-qubit gate fidelity is 99.86% and the average two-qubit gate fidelity is 99.41%, with an average readout (measurement) fidelity of 95.48%. Additionally, qubits have an average T_1 time of 30.6 μ s and average T_2 time of 5.3 μ s, both at idle frequency.

Back to Table I

2. Description of the second experiment

On Sep 08 2021, the same group performed an upgraded experiment with n = 60 qubits and m = 24 cycles, collecting 70 million bitstrings in 4.2 hours (one million bitstring every 210 seconds) at an estimated fidelity (2) of 0.0366% [13]. The experiment is performed on an updated Zuchongzhi computer, dubbed Zuchongzhi 2.1. On this device, average single-qubit and two-qubit gate errors were essentially the same as the previous experiment, however the average readout fidelity was improved to 97.74%. Again building on the latest advances in tensor network simulation (Sec. II A 4), the authors estimate it would take 48,000 years on Summit to classically simulate their experiment.

Back to Table I

3. Challenges, refutations, and loopholes

Due to the fact that this is again a random circuit sampling experiment, all of the challenges and loopholes from Sec. II A 4 apply to this work. The difference is of course the larger size of the experiment: n = 53 qubits and m = 20 cycles in Google's 2019 experiment, improved up to n = 60 qubits and m = 24 cycles here. Recall that the (weak) refutation of Google's 2019 experiment [48] occurred on Nov 04 2021, almost two months after the second RCS experiment on Zuchongzhi was published. Hence this work, and the work leading up to it, does not directly comment on the Zuchongzhi experiments, but the challenges still apply. One exception is that the previously discussed [14] — although largely framed around Google's 2019 experiment — does estimate their methods would take around five years for the Zuchongzhi 2.1 experiment. In addition, Ref. [10] estimates the n = 56, m = 20 circuit can be done in four days on a cluster with 4480 GPUs. The loopholes for the cross entropy fidelity in random circuit sampling discussed in Sec. II A 6 also of course apply to these experiments.

D. Gaussian boson sampling on the *Borealis* quantum computer

1. Description of the experiment

On Jun 01 2022, researchers from Xanadu announced a Gaussian boson sampling experiment with n = 216squeezed states and m = 216 modes. Up to $N_c = 219$ photons are measured, with a mean photon number of 125. One reason this photon number is larger compared to previous Gaussian boson sampling experiments is that this experiment uses photon number resolving detectors instead of threshold detectors. Also, another important difference is that this experiment is fully programmable. Referring to the time needed to exactly calculate a single probability in Gaussian boson sampling under the bestknown classical algorithm, the authors estimate it would take the Fukagu supercomputer 9,000 years to generate one sample, corresponding to 9 billion years to generate the full dataset of one million samples collected by Borealis.

To verify the experimental setup, the authors classically simulate the experiment for smaller sizes. In particular, for $3 \leq n \leq 6$ photons and m = 16 modes, the authors calculate the exact output distribution and compare them to the experimental output distribution, finding fidelities greater than 99% and total variation distances less than or equal to 6.5%. In the intermediate size regime — an average photon number of around n = 21with m = 216 modes — a classical computation taking 22 hours is performed which allows the authors to compute the cross entropy of experimental and classically computed samples, finding good agreement. Finally, in the large size regime — an average photon number of $N_c = 125$ with m = 216 modes — the first and second order cumulants (which can be efficiently computed classically) of the photon-number distributions are calculated from one million samples, for which they again find good agreement. Similar to the previous Gaussian boson sampling experiments, several adversarial distributions are considered — squashed, thermal, coherent, and distinguishable squeezed light — and are shown to match poorly with the ground truth. (These distributions are adversarial in the sense that they are easy to classically simulate, presenting a potential challenge to the experiment.) In addition, a fifth adversary is considered, namely the algorithm of Ref. [85] discussed in Sec. IIB6. Still in this case the samples from *Borealis* are found to better match the ground truth.

Back to Table I

E. Two new random circuit sampling experiments on the *Sycamore* quantum computer

On Apr 21 2023, the team from Google published a paper describing two new random circuit sampling experiments [11]. In the first, an n = 67 qubit, m = 32 cycle (880 two-qubit gates) experiment is performed. Seventy million bitstrings are sampled at an estimated XEB fidelity of 0.1%. In the second, an n = 70 qubit, m = 24 cycle random circuit experiment is performed. Seventy million bitstrings are sampled at an estimated XEB fidelity of 0.2%. In this latter experiment at shorter depth, the Loschmidt echo technique — which applies the unitary U^{\dagger} after the random circuit unitary U and counts the number of times the all zero bitstring is measured — is used to estimate the XEB fidelity, and the results agree with other techniques used.

In addition to presenting the largest random circuit sampling experiments to date, commentary is given as to references challenging, refuting, and/or discussing loopholes in the original 2019 experiment. Indeed, it is shown that the (linear) XEB fidelity (2) exhibits a phase transition from weak to strong noise, and the authors present a simple experimental protocol to locate this phase transition. Second, the authors estimate the classical runtime in light of the new techniques used to challenge and (weakly) refute the smaller 2019 experiment. Assuming the Frontier cluster, the task of sampling one million uncorrelated bitstrings from their n = 67, m = 32 experiment is estimated to take ten thousand years. Note that this considers the best case scenario where all RAM is used all bandwidth constraints are ignored. If the memory was expanded to included secondary storage, as previously suggested by [35] for the 2019 experiment, the authors estimate it would take Frontier 12 years to simulate the experiment.

Back to Table I

F. A third Gaussian Boson sampling experiment on the *Jiŭzhāng* quantum computer

On Apr 24 2023, the group from USTC reported a third n = 50, m = 144 Gaussian boson sampling experiment on an upgraded version *Jiŭzhāng* photonic quantum computer, termed *Jiŭzhāng 3.0* [16]. The highest number of detected photons obtained in the experiment is $N_c = 255$, compared to $N_c = 113$ in the previous one. In this third experiment, pseudo photon number resolving detectors are used, as opposed to threshold detectors in previous experiments. Recall that threshold detectors distinguish between two cases — zero photons or one or more photons. Although easier to work with experimentally, this version of Gaussian boson sampling is easier to classically simulate by exploiting collisions [82], as previously discussed. The pseudo photon resolving number detectors make the experiment harder to classically simulate, the dominant computational cost being proportional to $mN^3\sqrt{G}$ where $N := \sum_{i=1}^m n_i$, n_i being the number of photons resolved in mode *i*, and $G := \prod_{i=1}^m (n_i + 1)$. Using this cost and runtime estimates from the Frontier supercomputer, the authors estimate it would take at least 600 years to generate a single sample classically, and up to 3.1×10^{10} years for the hardest sample, whereas $Ji \check{u} z h \bar{a} n q$ takes 1.27 μ s per sample.

Back to Table I

1. A weak refutation of the experiment and previous Gaussian boson sampling experiments

On Jun 06 2023, Oh et al. presented work using tensor networks to classical simulate Gaussian boson sampling [8]. This builds on previous work (which features the current authors) using matrix product operators to simulate lossy boson sampling [87, 88], and shares some features with previous algorithms exploiting the fact that noise results in an easier distribution to sample from [89]. A key difference in the new algorithm is that thermal states are removed and matrix product states (MPS), instead of matrix product operators, are used. As described, exact sampling algorithms scale exponentially in the number of detected photons, but do not discriminate between which types of photons are detected. The tensor network algorithm is able to significantly reduce the complexity when detected photons are thermal states by removing them. The algorithm is implemented in Python using CuPy and MPI, and the code is executed on a cluster of m GPUs where, as usual, m is the number of modes in Gaussian boson sampling. An MPS with bond dimension $\chi = 10^4$ is used for each of the previous Gaussian boson sampling experiments claiming quantum advantage. The longest time for the MPS construction is 9.5 minutes for the $Ji \bar{u} z h \bar{a} n q 2.0$ experiment, and the time for generating 10 million samples is 62 minutes, a significant speedup relative to previous classical algorithms. Because the experimental sampling times were a few hundred seconds (e.g., 200 seconds for the $Ji \bar{u} z h \bar{a} n q 1.0$ and 2.0 experiments), we consider this work to be a weak refutation of these experiments. It is notable that the source code used in this paper is available online (see the Supplementary Material of [8]), and that part of this algorithm directly uses and/or modifies previously mentioned open source software for simulating Gaussian boson sampling [84], again highlighting how openly sharing data and code have accelerated — if not caused — these developments.

G. A quickly refuted quantum simulation by IBM

On Jun 14 2023, researchers from IBM report quantum simulation of the transverse field Ising model [17] defined by $H = -J \sum_{\langle i,j \rangle} Z_i Z_j + h \sum_i X_i$, on an n = 127 qubit processor with two-dimensional connectivity $\langle i, j \rangle$. In other words, the connectivity of the Ising model is taken to be that of the quantum processor with qubits arranged in a two-dimensional "heavy hexagon" pattern. The quantum simulation is done via Trotterization up to m = 60 layers, corresponding to 2880 two-qubit gates. Expectation values of weight 17 observables are computed and taken to be the output of the experiment. (The weight of an observable, taken to be a Pauli string, is the number of non-identity terms in the Pauli string, or the cardinality of the support of the string.) For certain evolution times, the circuit is Clifford and therefore efficiently classically simulable — this is used to benchmark the performance of the device, analogous to how linear XEB is used to quantify the performance in random circuit sampling experiments. Noise is mitigated by use of zero-noise extrapolation and probabilistic error amplification to produce more accurate expectation values. The authors consider classical simulation by quasi-1D matrix product states and 2D isometric tensor network states, arguing that the size of the experiment would be out of reach for these methods, therefore allowing them to claim quantum advantage.

Back to Table I

1. Refutations and loopholes

On Jun 26 2023, just two weeks after the IBM experiment is announced, a classical simulation of the experiment was presented [18]. This classical simulation uses a tensor network ansatz based on the connectivity of the quantum computer and uses the recently-introduced technique of belief propagation [90] to approximately contract it. Belief propagation is a technique for gauging tensor networks and has been shown numerically to be faster than existing methods. In this work, it is used to apply two-qubit gates appearing in the Trotterization to evolve time in the tensor network. The full classical computation simulating IBM's experiment was performed on a laptop in a few minutes. The code to do so is built on open-source libraries and is available online [90].

Two days later, on Jun 28 2023, authors of [91] show the simulation of a smaller n = 30 qubit circuit can accurately reproduce the experimental data obtained for the weight 17 observable considered in the IBM experiment. Assuming that $Tr[\rho O] = F\langle O \rangle$ where O is an observable, $|\psi\rangle$ is the noiseless state, and ρ is the noisy state, the authors argue that the effective fidelity F scales as $\exp(-\epsilon V_O)$ where ϵ is the error per two-qubit gate and V_O , called the "effective circuit volume" depending on the observable O and the circuit, is a number of twoqubit gates. Then, the authors argue the classical simulation cost scales as $2^{\alpha \partial V_O}$ where α is a constant and ∂V_O is a boundary or "cut" of the effective circuit volume (which again depends on the observable O and the circuit). This demonstrates a tradeoff between high fidelity and high classical simulation cost. These ideas

are discussed in the context of random circuit sampling experiments, quantum chaos experiments, and the IBM experiment. For the IBM experiment, it is argued that the effective circuit volume V_O is around 100 two-qubit gates, as opposed to the 2880 two-qubit gates in the experiment. (Note that this is distinct from the lightcone of an observable — the lightcone of observables used in the IBM experiment covers all 127 qubits.) It is then shown that classically simulating these smaller circuits — done on a single GPU in less than one second per circuit — reproduces the experimental results from IBM within one standard deviation. Because the exact circuits are not executed, this computation can be considered a loophole, e.g., "spoofing" the expectation values based on the chosen observables and circuit design, just as various vulnerabilities in the XEB fidelity have been exploited (Sec. II A 6). It is worth noting that these techniques do not lead to efficient spoofing of random circuit sampling experiments as discussed by the authors.

Again on Jun 28 2023, the same day as the previous paper, an approximate simulation technique is used to classically reproduce IBM's experiment [92]. The approximate simulation technique is the so-called Clifford perturbation theory — recently introduced in [93] — which is notable in the context of this review for *not* being a tensor network technique. Rather, the technique updates the assumed Pauli observable in the Heisenberg picture using an expansion into sums of Cliffords. For an actual Clifford gate, the sum is just over one term and the update is trivial. For non-Clifford gates, the sum is over two Cliffords. Thus the cost is exponential in the number of non-Clifford gates. This exponentially growing sum is truncated after a certain number of terms, thus yielding an approximate technique, which is argued to be accurate under certain assumptions. In terms of IBM's experiment, the technique is shown to accurately reproduce the dynamics of the observables, and the overall classical runtime is between one and two minutes on a laptop. An updated and published version of the paper [94] also considers classical simulation via tensor network contraction with projected entangled pair states/operators.

Shortly after, on Aug 06 2023, a classical simulation using projected entangled pair operators (PEPOs) is presented which runs on a single CPU in three seconds [95]. In some detail, the authors construct the three-dimensional tensor network (two space + one time) $\langle 0|U^{\dagger}OU|0\rangle$ and contract it in the Heisenberg picture i.e., starting from the center of the network representing the observable O as a PEPO and contracting outward to the boundaries symmetrically. While operations with PEPOs are generally more expensive than with matrix product states (MPS), as considered in the classical simulation discussion of the IBM experiment, the authors note some practical advantages of using PEPOs — for example, a PEPO reflects the geometry of the underlying hardware and so does not require SWAP operations like in MPS, which increase the bond dimension. Calculations with a PEPO with surprisingly small bond dimension $\chi = 2$ are shown to accurately reproduce IBM's experiment, and an errors with a $\chi = 184$ PEPO are shown to be lower than with an MPO at bond dimension $\chi = 1024$. (Errors with an MPO at bond dimension $\chi = 124$ are comparable to the errors with a PEPO at bond dimension $\chi = 2$.) Running time for $\chi = 184$ is three seconds using a single CPU.

Finally, on Sep 27 2023, a classical simulation of IBM's experiment using graph-based projected entangled pair states (gPEPs) and computing expectation values via mean field theory is presented [95]. Like others discussed, this classical simulation runs in just a few seconds (two seconds) on a laptop. It is interesting to note that, in addition to the above techniques, the authors considered belief propagation from [18] and found it did not improve accuracy but did increase runtime from two seconds to nine seconds. This paper is particularly notable for not just simulating the n = 127 qubit Ising model experiment, but also for classically simulating n = 433 and n = 1121 qubit experiments (two future milestones on IBM Quantum's roadmap) up to 39 Trotter steps.

H. A quantum simulation experiment by D-Wave

On Mar 01 2024, researchers from D-Wave published a paper claiming quantum advantage for the problem of quantum simulation [23]. The dynamics simulated are the same as the previously discussed IBM experiment (Sec. IIG), namely time evolution of the transverse field Ising model defined by $H(t) = J(t/t_a) \sum_{i < j} J_{ij} Z_i Z_j +$ $h(t/t_a) \sum_i X_i$. Here t_a is the quench time and the connectivity (i.e., the sum over i < j), is taken to be the connectivity of the quantum processor. Two processors are used in the experiment, termed Advantage and Advantage2 (ADV1 and ADV2). Each device samples 1000 bitstrings per second, taken to be the output of the experiment. Nonzero coupling coefficients J_{ij} are chosen randomly under different topologies including square lattices, diamond lattices, and dimerized biclique graphs. The largest input is a $12 \times 12 \times 16$ diamond lattice requiring 576 qubits.

The authors consider three classical algorithms to simulate their experiment — two using tensor networks and one using neural networks (neural quantum states). Both matrix product states and the two-dimensional version of projected entangled pair states are considered for tensor network ansatze, and autoregressive Boltzmann machines as well as transformers and recurrent neural networks are considered for neural quantum states. By studying the numerical scaling of these techniques, the authors conclude that they cannot reach the largest experiment performed on the quantum computer, thereby claiming quantum advantage.

Back to Table I

Due to the recency of this experiment (at the time of writing), there is no literature directly challenging or refuting this claim of quantum advantage, however it seems likely that the techniques of Sec. II G 1 as well as others could do so in the future.

III. QUANTUM ADVANTAGE THEORY

While the preceding discussion focused solely on *experimental* computational advantage and emphasized how this has been classically challenged and even refuted, similar results can be found in *theoretical* computational advantage. We include brief histories for two cases in which this has happened — computational advantage with respect to approximate optimization and recommendation systems. Last, we discuss prospects for the long-expected (exponential) advantage in simulating quantum systems, in particular quantum chemistry.

A. A brief quantum computational advantage in approximate optimization

The Quantum Approximate Optimization Algorithm (QAOA) [96] inputs a classical cost function C : $\{0,1\}^n \to \mathbb{R}$ defined on a bitstring $z_1, ..., z_n$ and quantizes it by taking $z_i \mapsto Z_i$. At p = 1 layer, the QAOA prepares the state

$$|\gamma,\beta\rangle := e^{iH_X\beta} e^{-iH_Z\gamma} |+\rangle^{\otimes n} \tag{4}$$

where $|+\rangle := (|0\rangle + |1\rangle)/\sqrt{2}$. Thus for $\gamma = \beta = 0$ the QAOA is equivalent to random guessing, and for other parameter values $0 \leq \gamma, \beta < 2\pi$ different performance can be achieved. The *driver* Hamiltonian H_Z embeds the problem information via the cost function C, and the mixer Hamiltonian H_X is a parameter, commonly taken to be $H_X = \sum_{i=1}^n X_i$. The QAOA can be naturally extended to p layers (or rounds) by repeated application of the driver and mixer Hamiltonians, nominally with different parameters. The p round QAOA thus contains 2p parameters $\gamma_1, \beta_1, \dots, \gamma_p, \beta_p$. In theory work, p = 1 is almost always chosen due to the difficulty of analytical expressions with p > 1. By taking $\gamma_j = \beta_j = 0$ for all j > i, it is easy to see the additional parameters cannot decrease the performance of the QAOA, and it is hoped that additional rounds can increase the performance. In the original paper [96], it was shown that when applied to the MaxCut problem on three-regular graphs, the p = 1QAOA always finds a cut that is at least 0.6924 times the size of the optimal cut.

On Dec 18 2014, the inventors of the QAOA apply the algorithm to a new problem, Max E3LIN2, and show they achieve an advantage over the best-known classical algorithm. The Max E3LIN2 problem is a constraint sanctification problem over n bits $z_1, ..., z_n$ where C(z)is a sum of clauses (terms) with Exactly 3 (E3) binary variables that sum to zero or one modulo 2 (LIN2). Note that the problem is also known as Max-3XOR and can be easily generalized to Max-kXOR. The problem is to maximize the number of satisfied clauses (assuming they cannot all be satisfied, in which case the problem is trivial). A random guess z will satisfy half of the clauses on average, and it is known that for any $\epsilon > 0$ there is no efficient classical algorithm to satisfy $1/2 + \epsilon$ clauses unless P = NP [97]. With the additional assumption that each variable appears in at most D clauses, a classical algorithm is known that produces an approximation ratio of 1/2 + c/D where c is a constant [98].

In [99], Farhi, Goldstone, and Gutman applied the p = 1 round QAOA to the Max E3LIN2 problem and showed it achieved an approximation ratio of $1/2 + c/D^{3/4}$, thereby demonstrating an advantage over the best-known classical algorithm. Because of this, the result generated significant interest, notably in the form of a blog and discussion [100]. This interest prompted researchers to consider if an equal or better classical algorithm could be found.

Less than five months later on May 13 2015, Barak et al. — directly responding to Farhi, Goldstone, and Gutman — presented a randomized classical algorithm able to achieve an approximation ratio of at least $1/2 + c/D^{1/2}$ where c is a constant [101]. In addition to beating the QAOA, they show that the $1/D^{1/2}$ dependence is optimal. Thus, the theoretical quantum advantage for Max-E3LIN2 was lost.

It is notable that on Jun 25 2015, Farhi, Goldstone, and Gutman responded to Barak et al. and improve their analysis of the QAOA approximation ratio to show it achieves $1/2 + c/D^{1/2} \log D$, and in "typical" cases defined by the authors the QAOA will output a string with high probability that satisfies $1/2 + c/D^{1/2}$ clauses. Note that this is not in a separate paper but rather in an updated version of [99] (v1 and v2 on arXiv). Thus, the QAOA is worse than the best-known classical algorithm by a factor of $\log D$, or (in the best case) achieves equal performance, so a theoretical quantum advantage for Max-E3LIN2 cannot be claimed. It is worthwhile to note that, like most theoretical QAOA analyses, the algorithm is analyzed for p = 1 layers (or rounds), and as mentioned the performance of the QAOA cannot decrease for additional layers, and hopefully will increase.

The question of whether the QAOA can achieve a provable computational advantage is still open and highly active. For example, recently Montanaro and Zhou proved that the p = 1 QAOA can achieve a success probability of at least $1/\sqrt{n}$ for particular symmetric constraint satisfaction problems with planted solutions [102]. Certain classical algorithms are shown to have worse theoretical performance, and other state-of-the-art SAT solvers are studied numerically, suggesting a quantum advantage for the p = 1 QAOA on these problems.

B. Dequantization of recommendation systems

The recommendation systems problem is to produce good products for users based on available data. Specifically, given m users and n products, we can imagine an $m \times n$ preference matrix T_{ij} where $T_{ij} = 1$ is user i likes product j, else $T_{ij} = 0$. Given this data in an "online" fashion of the form (i, j, T_{ij}) , the goal is output a small number of new products for a given user. We assume that the preference matrix T has a low rank k, specifically taking k to be independent of m and n, to make the problem tractable. This low rank assumption arises fairly naturally from social and economic reasons (e.g., people often naturally form groups, and some products will be better than others) and is found to hold well in empirical data.

One classical algorithm to solve this problem first samples entries from T_{ij} to get a random matrix \hat{T}_{ij} , computes the singular value decomposition, then truncates to a given rank (which is independent of m and n). An input user vector is then projected onto this low-rank subspace, from which we can read out recommendations.

On Mar 29 2016, a quantum algorithm for the recommendation systems problem was presented by Kerenidis and Prakash [103]. The algorithm proceeds in line with the previous classical algorithm but uses quantum routines to compute the singular value decomposition and to truncate. The algorithm has the very nice feature that it avoids the "output problem" of reading out entries of an exponentially large vector from a quantum computer. This is because we only want to get a small number of recommended products. So, after the quantum singular value decomposition and truncation is performed, simply measuring the final state samples from the desired distribution, and good products are sampled with high probability. The quantum recommendation systems algorithm runs in time $O(\text{poly}(k) \log mn)$ which achieves an exponential speedup over the best-known classical algorithms (which depend polynomially on the dimensions m and n). The algorithm is a cornerstone of theoretical advantage in quantum algorithms and quantum machine learning.

However, the quantum algorithm must assume a new data structure — a so-called binary tree data structure — to be able to efficiently read in the problem input (the preference matrix T_{ij} and a given user *i*). What if the same data structure was allowed for classical algorithms? Ewin Tang presented the answer to this question on Jul 10 2018, showing that there exists a classical algorithm running in time $O(\text{poly}(k) \log mn)$ using the binary tree data structure [104]. In other words, the quantum recommendation systems algorithm only achieves an (exponential) advantage due to assumptions on the input of the problem. The term *dequantization* is used to refer to this situation of a new classical algorithm inspired by a quantum algorithm with the same (or better) performance.

The dequantized algorithm works as follows. The bi-

nary tree data structure leads to efficient sample and query access of a vector: i.e., given $x \in \mathbb{C}^N$, we can efficiently sample i from the distribution $|x_i^2/||x||^2$ and query $i \mapsto x_i$. This leads to advantages in certain computations. For example, finding a large, hidden element of a vector takes time $\Omega(N)$, however with sample and query access can be done in constant time — the large element will have high weight and so will be sampled with high probability in time independent of n. In a similar way, sample and query access leads to efficient inner products and thus efficient projections as needed in the recommendation systems algorithm. The dequnatized algorithm then computes the singular value decomposition, projects, and samples entries (products). It is worth noting that the singular value decomposition is performed via the random (classical) algorithm of [105].

While the runtime of the quantum and dequantized classical algorithms are the same asymptotically, they have different constant factors and different degree polynomials. A paper by Arrazola *et al.* [106] explored the performance of both in practice, finding that the dequantized algorithm can perform well in practice despite strong requirements, but also has significant polynomial overhead relative to the quantum algorithm. Assuming the binary tree data structure of [103] could be efficiently prepared, then, it follows that the quantum recommendation systems algorithm could be advantageous in practice. However, it could also be possible to improve the constants and polynomials in the dequantized algorithm, negating this advantage.

It is worthwhile to note that the dequantization ideas from Tang [104] were applied to other quantum algorithms, for example linear systems [107] and linear regression [108]. Finally, the question of whether the sample and query access assumption of dequantized algorithms is *too* powerful a model has been considered [109], motivated by the result that classical algorithms with sample and query access can solve certain learning tasks exponentially faster than quantum algorithms with quantum state inputs.

C. Quantum chemistry

Perhaps the clearest application in which we can expect quantum computers to achieve computational advantage is simulating quantum systems, one of the first motivations for the idea of quantum computers in the 1980s [110]. Roughly speaking, computational advantage is expected because all known classical algorithms for simulating quantum systems scale exponentially in some parameter —- e.g. dimensionality, entanglement, or coherence — whereas quantum computers naturally mimic the behavior of (many-body) quantum systems.

One formalization of this intuition is the quantum phase estimation (QPE) algorithm [111]. The goal of QPE is to find the ground state energy (smallest eigenvalue) of a given a n-qubit unitary operator U. This

energy can be written $e^{2\pi i\phi}$ where ϕ is known as the *phase*, whence the name of the algorithm. Computing ϕ to accuracy ϵ requires a number of gates which scales as $O(\epsilon^{-1}\text{poly}(n)\text{polylog}(\epsilon^{-1}\pi_0^{-1}))$, where π_0 is the overlap of the initial state and the ground state. With respect to general quantum systems, the poly(n) term is exponentially better than all known classical algorithms. The dependence on π_0 reflects the fact that QPE must have a relatively good initial state — measured by overlap with the desired state — in order to succeed.

Quantum phase estimation is a staple quantum algorithm, and much work has been done to improve the practicality of the algorithm while retaining its complexity — for some recent developments, see for example [112-114]. On Aug 22 2022, however, Lee et al. asked if there is evidence for QPE to achieve an exponential speedup on typical problems in quantum chemistry [115]. These typical problems are taken to be ground state energy calculation — one of the most common tasks in chemistry — for which QPE is designed. Highlighting the powerful classical heuristic algorithms which have been developed over many years for these problems, the authors suggest primarily through numerical analyses that evidence for exponential advantage for QPE in ground state energy calculation has yet to be firmly demonstrated (leaving the possibility for polynomial speedups). It is worth noting that, although the scaling of QPE is exponentially better than known algorithms, the overhead is significant despite ongoing work to make the algorithm more practical and amenable to current quantum computers. For this reason QPE has not been experimentally demonstrated on problem sizes which could claim quantum advantage. Further improvements in both the algorithm and in quantum hardware are required to perform such experiments and conclusively demonstrate the advantage of QPE.

D. Shor's algorithm

Perhaps the most solid example of an algorithm with theoretical quantum advantage is Shor's algorithm for prime factorization (or discrete logarithms) [4]. Whereas every known classical algorithm takes time exponential in the number of bits in the integer to be factored, Shor's quantum algorithm requires polynomial time. The catch is that the overhead is so large that an experimental demonstration of the algorithm will require quantum error correction. In this sense the final frontier towards experimental quantum advantage in prime factorization is quantum error correction, and we turn our final part of the review towards this topic.

Prior to this point, however, it is worth noting that the overhead of Shor's algorithm has been significantly brought down since the inception of the algorithm in 1995. Shor's algorithm works by reducing the problem of factoring to period finding, which quantum computers are particularly suitable for due to constructive and destructive interference effects. Factoring can be reduced to period finding by considering the modular exponential function $f_x(r) := x^r \mod n$ where x is an integer and n = pq is the number to be factored into unknown primes p and q. This function is periodic with period $\phi(n) := (p-1)(q-1)$, known as Euler's totient function. Once the period $\phi(n)$ is known, the two equations n = pq and $\phi(n) = (p-1)(q-1)$ can be readily solved for p and q. (It may turn out that there is a smaller fundamental period of the modular exponential function $f_x(r)$, however in this case the period can still be determined efficiently by Euclid's algorithm for finding the greatest common divisor.) The quantum part of Shor's algorithm simply computes the modular exponential function on a superposition of all inputs, then implements the quantum Fourier transform to determine it's period with high probability. The quantum Fourier transform is relatively easy, so the bulk of the quantum part of Shor's algorithm is computing $f_x(r)$ through multiplication. Much of the work reducing the overhead of Shor's algorithm has been developing better circuits for this task. A relatively recent proposal with a clear cost estimate and summary of prior techniques can be found in [116]. To factor an n bit RSA number, the technique of this paper requires $3n+0.002n\log n$ logical qubits and $0.3n^3+0.0005n^3\log n$ Toffoli gates, ignoring the cost of magic state distillation to implement Toffoli gates as well as the cost of routing (due to limited hardware connectivity) and the overhead from error correction. The final estimate is that it would take 20 million noisy qubits and eight hours to factor 2048-bit RSA numbers. Reducing this cost further is still an active an open problem for which new results are still appearing, e.g. [117].

IV. TOWARDS FAULT TOLERANCE

We finish this review article by briefly covering progress in quantum error correction, the final frontier to realizing experimental quantum advantage in Shor's algorithm and others. For readers familiar with classical error correction, quantum error correction can be intuitively understood as using redundancy. For example, the repetition code maps the basis states of a qubit to $|0\rangle \mapsto |000\rangle$ and $|1\rangle \mapsto |111\rangle$. In this way information is encoded redundantly in three physical qubits representing a single *logical* qubit. This particular code is able to correct a single bit flip on any physical qubit by taking a majority vote in the decoding process. For example, if a single bit flip occurs on the last qubit, the error state $|001\rangle$ would be corrected to $|000\rangle$, and so the bit flip can be corrected. However if two or more bit flips happen, the state would get mapped to the other logical basis state, known as a *logical error*. This intuition for how many errors a code can correct is reflected in a parameter known as the *distance* of the code. Thus higher distance is desirable, and a certain physical error rate necessitates a minimum distance for error correction to

Year	Code name	Params.	n_Q	Qubit type	Ref.
1998	Repetition	[3,1,3]	3	NMR	[118]
2004	Repetition	[3, 1, 3]	3	Trapped ion	[119]
2005	Cat	N/A	2	Photonic	120
2001	Perfect	[[5,1,3]]	5	NMR	[121]
2011	Repetition	[3,1,3]	3	Trapped ion	[122]
2011	Repetition	[3,1,3]	3	NMR	[123]
2011	Repetition	[3,1,3]	3	NMR	[124]
2012	Repetition	[3,1,3]	3	Superconducting	[125]
2012	Perfect	[[5,1,3]]	5	NMR	[126]
2014	Surface	[[4,1,2]]	4	Photonic	[127]
2014	Repetition	[5,1,5]	9	Superconducting	[128]
2014	Color	[[7,1,3]]	7	Trapped ion	[129]
2014	Repetition	[3,1,3]	4	Diamond	[130]
2015	Repetition	[3,1,3]	5	Superconducting	[131]
2015	Bell	[[2,0,2]]	4	Superconducting	[132]
2016	Repetition	[3,1,3]	4	Superconducting	[133]
2016	Cat	N/A	1	3D cavity	[134]
2017	Color	[[4,2,2]]	5	Superconducting	[135]
2017	Color	[[4,2,2]]	5	Trapped ion	[136]
2017	Cat	N/A	1	Superconducting	[137]
2018	Repetition	[8,1,8]	15	Superconducting	[138]
2019	Bell	[[2,0,2]]	3	Superconducting	[139]
2019	Perfect	[[5,1,3]]	5	Superconducting	[140]
2019	Binomial	N/A	1	3D cavity	[141]
2019	Color	[[4,2,2]]	4	Superconducting	[142]
2020	Repetition	[22, 1, 22]	43	Superconducting	[143]
2020	Surface	[[4,1,2]]	7	Superconducting	[144]
2020	Bacon-Shor	[[9,1,3]]	15	Trapped ion	[145]
2020	Bacon-Shor	[[9,1,3]]	11	Photonic	[146]
2020	GKP	N/A	1	3D cavity	[147]
2021	Repetition	[11, 1, 11]	21	Superconducting	[148]
2021	Steane	[[7, 1, 3]]	10	Trapped ion	[149]
2022	Surface	[[9, 1, 3]]	17	Superconducting	[150]
2022	Five-qubit	[[5, 1, 3]]	7	Diamond	[151]
2022	Surface	[[9, 1, 3]]	17	Superconducting	[152]
2023	GKP	N/A	1	Superconducting	[153]
2023	Surface	[[25, 1, 5]]	49	Superconducting	[154]
2024	Carbon	[[12, 2, 4]]	30	Trapped ion	[155]
2024	Surface/Color	$k \le 48$	218	Neutral atom	[156]
2024	Surface	[[49, 1, 7]]	101	Superconducting	[157]

TABLE II. A selection of quantum error correction experiments ordered chronologically. The code parameters are the [[n, k, d]] notation (see main text for a definition) and the n_Q column denotes the total number of physical qubits, including any ancilla qubits used for stabilizer measurement or other tasks outside of the *n* data qubits. Note that if a reference implements multiple error correction experiments we list the parameters for the largest experiment. Many entries prior to 2021 are taken from a similar list in the 2021 experiment of [148], and later entries build on this history.

work. A quantum error correction code is described in the notation [[n, k, d]] where n physical qubits are used to encode k logical qubits and d is the distance of the code. For example, the previously described repetition code is a [[3, 1, 3]] code. (Since this code is only capable of correcting a single type of error (bit flips), it sometimes may be written with single brackets [3, 1, 3] to emphasize it is a classical code.) An error corrected quantum computer is said to be *fault tolerant* when errors do not propagate between logical qubits during operations that are necessary to implement the code and manipulate the logical information to perform a computation.

Table II shows a chronological history of quantum error correction experiments, from which one can see the remarkable progress in recent years. Moving beyond simple proof of principle demonstrations, the first error correction experiment to achieve a logical qubit lifetime longer than any component physical qubit occurred in 2016 [134]. In this work, a logical qubit is encoded in a superconducting resonator in a so-called *cat state*, exhibiting a lifetime 1.1 times as long as the best physical qubit, demonstrating a fundamental feature of error correction that additional noisy components can combine to create higher fidelity quantum information. Later, in 2020, Ref. [143] is notable for implementing the largest repetition codes at that time, using up to 43 physical qubits of a superconducting (IBM) quantum computer. Also of note from 2020 is the first experimental demonstration of the surface code on a superconducting quantum computer [144]. The surface code is one of the most targeted codes due to its high threshold and relatively low experimental complexity, so although this work involved only four data qubits it generated significant interest. Another work from 2020 showed the first experimental demonstration of fault-tolerant preparation, measurement, and rotation using 13 trapped ion qubits implementing the [[9, 1, 3]] Bacon-Shor code. In 2021, the team from Google published the first error correction experiment on its Sycamore computer used in random circuit sampling experiments [148]. This work scaled the size of repetition codes and showed, although the logical error rates were worse than physical component error rates, that the logical error rate decreased exponentially in the distance of the code. Subsequently, building on [144], in 2022 Ref. [150] implemented a distance three surface code using 17 physical qubits on a superconducting quantum computer. The USTC group also implemented a distance three surface code in 2022 on the Zuchongzhi quantum computer used for random circuit sampling experiments. The Google group regained the lead with the largest surface code implementation of distance five (49) physical qubits) in 2023 on the Sycamore computer [154]. This line of work culminated in the most recent surface code experiment by Google in 2024 [157]. In this work, using a new 105 qubit quantum computer called Willow, surface codes up to distance seven (101 physical qubits) were implemented, and for the first time error rates were *below* the surface code threshold. (Note that Google has claimed quantum advantage in a new random

circuit sampling experiment on *Willow* in several press releases [158], however no details about the experiment have been given at the time of writing.) Other experimental work in error correction in 2024 showed up to 218 physical qubits encoding k = 48 logical qubits and implementing logical operations on a neutral atom quantum computer [156], and still other work has demonstrated necessary protocols for fault-tolerant quantum computing, e.g. magic state distillation in [159].

While the pace of these advancements has been remarkable, there is still a long road to fault-tolerant quantum computation. For example, although the latest surface code experiment from Google is below the threshold, this is a "memory" experiment with a single logical qubit, lacking any logical operations. We expect to see an even larger volume of quantum error correction experiments in the coming years to continue reaching milestones on the path towards a large-scale, fault-tolerant quantum computer capable of demonstrating quantum advantage for factoring and other problems.

V. CONCLUSION

In the long run, it seems reasonable to expect quantum computational advantage for certain problems in which quantum algorithms have exponential or strong polynomial speedups. However, while quantum algorithms may be faster, quantum information is inherently sensitive, limiting the size of experiments and opening the door to classical challenges and refutations. The alternative route to using noisy, physical qubits to demonstrate quantum advantage is to develop quantum error correction, for which the engineering challenges are formidable, but also for which there has been a tremendous amount of progress and exciting advances in recent years. With regards theoretical computational advantage, the possibility remains to devise new classical algorithms which are even faster, as we have seen for example problems such as approximate optimization and recommendation systems. Ultimately, any hypothesized computational advantage must be experimentally performed to be substantiated, and we have seen in this review that experiments can be challenged and refuted. It seems at this moment in history we are just on the boundary between quantum and classical computational advantage, and in the near future we expect the status of computational advantage to continue shifting between quantum and classical. We hope that this brief history helps to propel readers to the research frontier and develop new ideas which advance both classical and quantum computation.

- John Preskill. Quantum computing and the entanglement frontier. (arXiv:1203.5813), November 2012. arXiv:1203.5813 [cond-mat, physics:quant-ph].
- [2] John Preskill. Why I called it 'quantum supremacy', October 2019.
- [3] Ryan Babbush, Jarrod R. McClean, Michael Newman, Craig Gidney, Sergio Boixo, and Hartmut Neven. Focus

beyond quadratic speedups for error-corrected quantum advantage. *PRX Quantum*, 2(1):010103, March 2021.

- [4] Peter W. Shor. Polynomial-time algorithms for prime factorization and discrete logarithms on a quantum computer. *SIAM Journal on Comput*ing, 26(5):1484–1509, October 1997. arXiv: quantph/9508027.
- [5] Frank Arute et al. Quantum supremacy using a programmable superconducting processor. *Nature*, 574(77797779):505–510, October 2019.
- [6] Xian-He Zhao, Han-Sen Zhong, Feng Pan, Zi-Han Chen, Rong Fu, Zhongling Su, Xiaotong Xie, Chaoxing Zhao, Pan Zhang, Wanli Ouyang, Chao-Yang Lu, Jian-Wei Pan, and Ming-Cheng Chen. Leapfrogging sycamore: Harnessing 1432 gpus for 7× faster quantum random circuit sampling. (arXiv:2406.18889), June 2024. arXiv:2406.18889 [quant-ph].
- [7] Han-Sen Zhong et al. Quantum computational advantage using photons. *Science*, 370(6523):1460–1463, December 2020.
- [8] Changhun Oh, Minzhao Liu, Yuri Alexeev, Bill Fefferman, and Liang Jiang. Classical algorithm for simulating experimental gaussian boson sampling. *Nature Physics*, 20(9):1461–1468, September 2024.
- [9] Yulin Wu et al. Strong quantum computational advantage using a superconducting quantum processor. *Physical Review Letters*, 127(18):180501, October 2021. arXiv:2106.14734 [quant-ph].
- [10] Gleb Kalachev, Pavel Panteleev, PengFei Zhou, and Man-Hong Yung. Classical sampling of random quantum circuits with bounded fidelity. arXiv, (arXiv:2112.15083), December 2021. arXiv:2112.15083.
- [11] A. Morvan et al. Phase transitions in random circuit sampling. *Nature*, 634(8033):328–333, October 2024.
- [12] Han-Sen Zhong et al. Phase-programmable gaussian boson sampling using stimulated squeezed light. *Physical Review Letters*, 127(18):180502, October 2021.
- [13] Qingling Zhu et al. Quantum computational advantage via 60-qubit 24-cycle random circuit sampling. *Science Bulletin*, 67(3):240–245, February 2022.
- [14] Xin Liu, Chu Guo, Yong Liu, Yuling Yang, Jiawei Song, Jie Gao, Zhen Wang, Wenzhao Wu, Dajia Peng, Pengpeng Zhao, Fang Li, He-Liang Huang, Haohuan Fu, and Dexun Chen. Redefining the quantum supremacy baseline with a new generation sunway supercomputer. (arXiv:2111.01066), November 2021. arXiv:2111.01066.
- [15] Lars S. Madsen et al. Quantum computational advantage with a programmable photonic processor. *Nature*, 606(79127912):75–81, June 2022.
- [16] Yu-Hao Deng, Yi-Chao Gu, Hua-Liang Liu, Si-Qiu Gong, Hao Su, Zhi-Jiong Zhang, Hao-Yang Tang, Meng-Hao Jia, Jia-Min Xu, Ming-Cheng Chen, Jian Qin, Li-Chao Peng, Jiarong Yan, Yi Hu, Jia Huang, Hao Li, Yuxuan Li, Yaojian Chen, Xiao Jiang, Lin Gan, Guangwen Yang, Lixing You, Li Li, Han-Sen Zhong, Hui Wang, Nai-Le Liu, Jelmer J. Renema, Chao-Yang Lu, and Jian-Wei Pan. Gaussian boson sampling with pseudo-photon-number-resolving detectors and quantum computational advantage. *Physical Review Letters*, 131(15):150601, October 2023.
- [17] Youngseok Kim, Andrew Eddins, Sajant Anand, Ken Xuan Wei, Ewout van den Berg, Sami Rosenblatt, Hasan Nayfeh, Yantao Wu, Michael Zaletel, Kristan Temme, and Abhinav Kandala. Evidence for the utility

of quantum computing before fault tolerance. *Nature*, 618(79657965):500–505, June 2023.

- [18] Joseph Tindall, Matt Fishman, Miles Stoudenmire, and Dries Sels. Efficient tensor network simulation of IBM's eagle kicked ising experiment. (arXiv:2306.14887), August 2023. arXiv:2306.14887 [quant-ph].
- [19] Emanuele G. Dalla Torre and Mor M. Roses. Dissipative mean-field theory of ibm utility experiment. (arXiv:2308.01339), August 2023. arXiv:2308.01339 [quant-ph].
- [20] Hai-Jun Liao, Kang Wang, Zong-Sheng Zhou, Pan Zhang, and Tao Xiang. Simulation of ibm's kicked ising experiment with projected entangled pair operator. (arXiv:2308.03082), August 2023. arXiv:2308.03082 [cond-mat, physics:quant-ph].
- [21] Sajant Anand, Kristan Temme, Abhinav Kandala, and Michael Zaletel. Classical benchmarking of zero noise extrapolation beyond the exactly-verifiable regime. (arXiv:2306.17839), June 2023. arXiv:2306.17839 [quant-ph].
- [22] Tomislav Begušić, Johnnie Gray, and Garnet Kin-Lic Chan. Fast and converged classical simulations of evidence for the utility of quantum computing before fault tolerance. *Science Advances*, 10(3):eadk4321, January 2024. arXiv:2308.05077 [quant-ph].
- [23] Andrew D. King et al. Computational supremacy in quantum simulation. (arXiv:2403.00910), March 2024. arXiv:2403.00910 [cond-mat, physics:quant-ph].
- [24] Guifré Vidal. Efficient classical simulation of slightly entangled quantum computations. *Physical Review Let*ters, 91(14):147902, October 2003.
- [25] Scott Aaronson and Daniel Gottesman. Improved simulation of stabilizer circuits. *Physical Review A*, 70(5):052328, November 2004.
- [26] Sergey Bravyi, David Gosset, and Yinchen Liu. Classical simulation of peaked shallow quantum circuits. In Proceedings of the 56th Annual ACM Symposium on Theory of Computing, STOC 2024, page 561–572, New York, NY, USA, June 2024. Association for Computing Machinery.
- [27] Charles Neill. A path towards quantum supremacy with superconducting qubits. PhD thesis, UC Santa Barbara, 2017.
- [28] Aram W. Harrow and Ashley Montanaro. Quantum computational supremacy. Nature, 549(76717671):203–209, September 2017.
- [29] C. Neill, P. Roushan, K. Kechedzhi, S. Boixo, S. V. Isakov, V. Smelyanskiy, A. Megrant, B. Chiaro, A. Dunsworth, K. Arya, R. Barends, B. Burkett, Y. Chen, Z. Chen, A. Fowler, B. Foxen, M. Giustina, R. Graff, E. Jeffrey, T. Huang, J. Kelly, P. Klimov, E. Lucero, J. Mutus, M. Neeley, C. Quintana, D. Sank, A. Vainsencher, J. Wenner, T. C. White, H. Neven, and J. M. Martinis. A blueprint for demonstrating quantum supremacy with superconducting qubits. *Science*, 360(6385):195–199, April 2018.
- [30] Adam Bouland, Bill Fefferman, Chinmay Nirkhe, and Umesh Vazirani. On the complexity and verification of quantum random circuit sampling. *Nature Physics*, 15(22):159–163, February 2019.
- [31] Igor L. Markov, Aneeqa Fatima, Sergei V. Isakov, and Sergio Boixo. Quantum supremacy is both closer and farther than it appears. (arXiv:1807.10749), September 2018. arXiv:1807.10749.

- [32] Roozbeh Bassirian, Adam Bouland, Bill Fefferman, Sam Gunn, and Avishay Tal. On certified randomness from quantum advantage experiments. (arXiv:2111.14846), November 2021. arXiv:2111.14846 [quant-ph].
- [33] Scott Aaronson and Shih-Han Hung. Certified randomness from quantum supremacy. In Proceedings of the 55th Annual ACM Symposium on Theory of Computing, STOC 2023, page 933–944, New York, NY, USA, June 2023. Association for Computing Machinery.
- [34] David Deutsch and Roger Penrose. Quantum theory, the church-turing principle and the universal quantum computer. Proceedings of the Royal Society of London. A. Mathematical and Physical Sciences, 400(1818):97–117, January 1985.
- [35] Edwin Pednault, John A. Gunnels, Giacomo Nannicini, Lior Horesh, and Robert Wisnieff. Leveraging secondary storage to simulate deep 54-qubit sycamore circuits. (arXiv:1910.09534), October 2019. arXiv:1910.09534 [quant-ph].
- [36] IBM casts doubt on Google's claims of quantum supremacy. https://www.science.org/content/article/ ibm-casts-doubt-googles-claims-quantum-supremacy, October 2019.
- [37] Internet archive of "Quantum supremacy using a programmable superconducting quantum processor". https://ia601007.us.archive.org/12/items/427430775 quantumsupremacyusingaprogrammablesuperconductingprocessor/ 427430775-Quantum-Supremacy-Usinga-Programmable-Superconducting-Processor.pdf.
- [38] Edwin Pednault, John A. Gunnels, Giacomo Nannicini, Lior Horesh, Thomas Magerlein, Edgar Solomonik, Erik W. Draeger, Eric T. Holland, and Robert Wisnieff. Pareto-efficient quantum circuit simulation using tensor contraction deferral. (arXiv:1710.05867), August 2020. arXiv:1710.05867 [quant-ph].
- [39] Johnnie Gray and Stefanos Kourtis. Hyper-optimized tensor network contraction. *Quantum*, 5:410, March 2021.
- [40] Igor L. Markov and Yaoyun Shi. Simulating quantum computation by contracting tensor networks. SIAM Journal on Computing, 38(3):963–981, January 2008.
- [41] Yiqing Zhou, E. Miles Stoudenmire, and Xavier Waintal. What limits the simulation of quantum computers? *Physical Review X*, 10(4):041038, November 2020.
- [42] Cupjin Huang, Fang Zhang, Michael Newman, Junjie Cai, Xun Gao, Zhengxiong Tian, Junyin Wu, Haihong Xu, Huanjun Yu, Bo Yuan, Mario Szegedy, Yaoyun Shi, and Jianxin Chen. Classical simulation of quantum supremacy circuits. (arXiv:2005.06787), May 2020. arXiv:2005.06787.
- [43] Jianxin Chen, Fang Zhang, Cupjin Huang, Michael Newman, and Yaoyun Shi. Classical simulation of intermediate-size quantum circuits. (arXiv:1805.01450), May 2018. arXiv:1805.01450.
- [44] Benjamin Villalonga, Sergio Boixo, Bron Nelson, Christopher Henze, Eleanor Rieffel, Rupak Biswas, and Salvatore Mandrà. A flexible high-performance simulator for verifying and benchmarking quantum circuits implemented on real hardware. npj Quantum Information, 5(1):1–16, October 2019.
- [45] Feng Pan and Pan Zhang. Simulating the sycamore quantum supremacy circuits. (arXiv:2103.03074), March 2021. arXiv:2103.03074.

- [46] Yong, Liu, Xin, Liu, Fang, Li, Haohuan Fu, Yuling Yang, Jiawei Song, Pengpeng Zhao, Zhen Wang, Dajia Peng, Huarong Chen, Chu Guo, Heliang Huang, Wenzhao Wu, and Dexun Chen. Closing the "quantum supremacy" gap: Achieving real-time simulation of a random quantum circuit using a new sunway supercomputer. (arXiv:2110.14502), November 2021. arXiv:2110.14502.
- [47] Chu Guo, Yong Liu, Min Xiong, Shichuan Xue, Xiang Fu, Anqi Huang, Xiaogang Qiang, Ping Xu, Junhua Liu, Shenggen Zheng, He-Liang Huang, Mingtang Deng, Dario Poletti, Wan-Su Bao, and Junjie Wu. General-purpose quantum circuit simulator with projected entangled-pair states and the quantum supremacy frontier. *Physical Review Letters*, 123(19):190501, November 2019.
- [48] Feng Pan, Keyang Chen, and Pan Zhang. Solving the sampling problem of the sycamore quantum circuits. (arXiv:2111.03011), August 2022. arXiv:2111.03011.
- [49] Feng Pan. Solve sycamore. https://github.com/ Fanerst/solve_sycamore, August 2023.
- [50] Boaz Barak, Chi-Ning Chou, and Xun Gao. Spoofing linear cross-entropy benchmarking in shallow quantum circuits. (arXiv:2005.02421), May 2020. arXiv:2005.02421.
- [51] Xun Gao, Marcin Kalinowski, Chi-Ning Chou, Mikhail D. Lukin, Boaz Barak, and Soonwon Choi. Limitations of linear cross-entropy as a measure for quantum advantage. *PRX Quantum*, 5(1):010334, February 2024.
- [52] Scott Aaronson and Alex Arkhipov. The computational complexity of linear optics. In *Proceedings of the fortythird annual ACM symposium on Theory of computing*, STOC '11, page 333–342, New York, NY, USA, June 2011. Association for Computing Machinery.
- [53] Mark Jerrum, Alistair Sinclair, and Eric Vigoda. A polynomial-time approximation algorithm for the permanent of a matrix with nonnegative entries. J. ACM, 51(4):671–697, July 2004.
- [54] Alex Neville, Chris Sparrow, Raphaël Clifford, Eric Johnston, Patrick M. Birchall, Ashley Montanaro, and Anthony Laing. Classical boson sampling algorithms with superior performance to near-term experiments. *Nature Physics*, 13(12):1153–1157, December 2017.
- [55] E. Knill, R. Laflamme, and G. J. Milburn. A scheme for efficient quantum computation with linear optics. *Nature*, 409(6816):46–52, January 2001.
- [56] Craig S. Hamilton, Regina Kruse, Linda Sansoni, Sonja Barkhofen, Christine Silberhorn, and Igor Jex. Gaussian boson sampling. *Physical Review Letters*, 119(17):170501, October 2017.
- [57] Nicolás Quesada, Juan Miguel Arrazola, and Nathan Killoran. Gaussian boson sampling using threshold detectors. *Physical Review A*, 98(6):062322, December 2018.
- [58] Max Tillmann, Borivoje Dakić, René Heilmann, Stefan Nolte, Alexander Szameit, and Philip Walther. Experimental boson sampling. *Nature Photonics*, 7(7):540–544, July 2013.
- [59] Justin B. Spring, Benjamin J. Metcalf, Peter C. Humphreys, W. Steven Kolthammer, Xian-Min Jin, Marco Barbieri, Animesh Datta, Nicholas Thomas-Peter, Nathan K. Langford, Dmytro Kundys, James C. Gates, Brian J. Smith, Peter G. R. Smith, and Ian A.

Walmsley. Boson sampling on a photonic chip. *Science*, 339(6121):798–801, February 2013.

- [60] Nicolò Spagnolo, Chiara Vitelli, Marco Bentivegna, Daniel J. Brod, Andrea Crespi, Fulvio Flamini, Sandro Giacomini, Giorgio Milani, Roberta Ramponi, Paolo Mataloni, Roberto Osellame, Ernesto F. Galvão, and Fabio Sciarrino. Experimental validation of photonic boson sampling. *Nature Photonics*, 8(8):615–620, August 2014.
- [61] J. C. Loredo, M. A. Broome, P. Hilaire, O. Gazzano, I. Sagnes, A. Lemaitre, M. P. Almeida, P. Senellart, and A. G. White. Boson sampling with single-photon fock states from a bright solid-state source. *Physical Review Letters*, 118(13):130503, March 2017.
- [62] Andrea Crespi, Roberto Osellame, Roberta Ramponi, Daniel J. Brod, Ernesto F. Galvão, Nicolò Spagnolo, Chiara Vitelli, Enrico Maiorino, Paolo Mataloni, and Fabio Sciarrino. Integrated multimode interferometers with arbitrary designs for photonic boson sampling. Nature Photonics, 7(7):545–549, July 2013.
- [63] Jacques Carolan, Jasmin D. A. Meinecke, Peter J. Shadbolt, Nicholas J. Russell, Nur Ismail, Kerstin Wörhoff, Terry Rudolph, Mark G. Thompson, Jeremy L. O'Brien, Jonathan C. F. Matthews, and Anthony Laing. On the experimental verification of quantum complexity in linear optics. *Nature Photonics*, 8(8):621–626, August 2014.
- [64] Jacques Carolan, Christopher Harrold, Chris Sparrow, Enrique Martín-López, Nicholas J. Russell, Joshua W. Silverstone, Peter J. Shadbolt, Nobuyuki Matsuda, Manabu Oguma, Mikitaka Itoh, Graham D. Marshall, Mark G. Thompson, Jonathan C. F. Matthews, Toshikazu Hashimoto, Jeremy L. O'Brien, and Anthony Laing. Universal linear optics. *Science*, 349(6249):711–716, August 2015.
- [65] Matthew A. Broome, Alessandro Fedrizzi, Saleh Rahimi-Keshari, Justin Dove, Scott Aaronson, Timothy C. Ralph, and Andrew G. White. Photonic boson sampling in a tunable circuit. *Science*, 339(6121):794–798, February 2013.
- [66] Marco Bentivegna, Nicolò Spagnolo, Chiara Vitelli, Fulvio Flamini, Niko Viggianiello, Ludovico Latmiral, Paolo Mataloni, Daniel J. Brod, Ernesto F. Galvão, Andrea Crespi, Roberta Ramponi, Roberto Osellame, and Fabio Sciarrino. Experimental scattershot boson sampling. Science Advances, 1(3):e1400255, April 2015.
- [67] Hui Wang, Jian Qin, Xing Ding, Ming-Cheng Chen, Si Chen, Xiang You, Yu-Ming He, Xiao Jiang, Z. Wang, L. You, J. J. Renema, Sven Hoeffing, Chao-Yang Lu, and Jian-Wei Pan. Boson sampling with 20 input photons in 60-mode interferometers at 10¹⁴ state spaces. *Physical Review Letters*, 123(25):250503, December 2019. arXiv:1910.09930 [quant-ph].
- [68] Peter Clifford and Raphaël Clifford. The Classical Complexity of Boson Sampling, page 146–155. Proceedings. Society for Industrial and Applied Mathematics, January 2018.
- [69] Peter Clifford and Raphaël Clifford. Bosonsampling: Classical boson sampling. https://cran.r-project. org/web/packages/BosonSampling/index.html, October 2017.
- [70] Junjie Wu, Yong Liu, Baida Zhang, Xianmin Jin, Yang Wang, Huiquan Wang, and Xuejun Yang. A benchmark test of boson sampling on tianhe-2 supercomputer. Na-

tional Science Review, 5(5):715–720, September 2018.

- [71] Herbert John Ryser. Combinatorial Mathematics. American Mathematical Soc., December 1963.
- [72] K. Balasubramanian. Combinatorics and diagonals of matrices. Thesis, Indian Statistical Institute, Calcutta, December 1980. Accepted: 2012-04-29T18:32:22Z.
- [73] Eric Bax. Finite-difference algorithms for counting problems. phd, California Institute of Technology, 1998.
- [74] Andreas Björklund, Brajesh Gupt, and Nicolás Quesada. A faster hafnian formula for complex matrices and its benchmarking on a supercomputer. ACM J. Exp. Algorithmics, 24:1.11:1–1.11:17, June 2019.
- [75] Brajesh Gupt, Juan Miguel Arrazola, Nicolás Quesada, and Thomas R. Bromley. Classical benchmarking of gaussian boson sampling on the titan supercomputer. *Quantum Information Processing*, 19(8):249, July 2020.
- [76] Haoyu Qi, Daniel J. Brod, Nicolás Quesada, and Raul Garcia-Patron. Regimes of classical simulability for noisy gaussian boson sampling. *Physical Review Letters*, 124(10):100502, March 2020.
- [77] Bujiao Wu, Bin Cheng, Fei Jia, Jialin Zhang, Man-Hong Yung, and Xiaoming Sun. Speedup in classical simulation of gaussian boson sampling. *Science Bulletin*, 65(10):832–841, May 2020.
- [78] Yuxuan Li, Lin Gan, Mingcheng Chen, Yaojian Chen, Haitian Lu, Chaoyang Lu, Jianwei Pan, Haohuan Fu, and Guangwen Yang. Benchmarking 50-photon gaussian boson sampling on the sunway taihulight. *IEEE Transactions on Parallel and Distributed Systems*, 33(6):1357–1372, June 2022.
- [79] Nicolas Quesada, Rahel S. Chadwick, Bryn A. Bell, Juan Miguel Arrazola, Trevor Vincent, Haoyu Qi, and Raul Garcia-Patron. Quadratic speed-up for simulating gaussian boson sampling. *PRX Quantum*, 3(1):010306, January 2022.
- [80] Junheng Shi and Tim Byrnes. Effect of partial distinguishability on quantum supremacy in gaussian boson sampling. *npj Quantum Information*, 8(1):1–11, May 2022.
- [81] Jelmer J. Renema. Simulability of partially distinguishable superposition and gaussian boson sampling. *Physical Review A*, 101(6):063840, June 2020.
- [82] Jacob F. F. Bulmer, Bryn A. Bell, Rachel S. Chadwick, Alex E. Jones, Diana Moise, Alessandro Rigazzi, Jan Thorbecke, Utz-Uwe Haus, Thomas Van Vaerenbergh, Raj B. Patel, Ian A. Walmsley, and Anthony Laing. The boundary for quantum advantage in gaussian boson sampling. *Science Advances*, 8(4):eabl9236, January 2022. arXiv:2108.01622 [quant-ph].
- [83] Ágoston Kaposi, Zoltán Kolarovszki, Tamás Kozsik, Zoltán Zimborás, and Péter Rakyta. Polynomial speedup in torontonian calculation by a scalable recursive algorithm. (arXiv:2109.04528), November 2022. arXiv:2109.04528 [quant-ph].
- [84] Nicolás Quesada and Juan Miguel Arrazola. Exact simulation of gaussian boson sampling in polynomial space and exponential time. *Physical Review Research*, 2(2):023005, April 2020. arXiv:1908.08068 [quant-ph].
- [85] Benjamin Villalonga, Murphy Yuezhen Niu, Li Li, Hartmut Neven, John C. Platt, Vadim N. Smelyanskiy, and Sergio Boixo. Efficient approximation of experimental gaussian boson sampling. (arXiv:2109.11525), February 2022. arXiv:2109.11525 [quant-ph].

- [86] Abhinav Deshpande, Arthur Mehta, Trevor Vincent, Nicolás Quesada, Marcel Hinsche, Marios Ioannou, Lars Madsen, Jonathan Lavoie, Haoyu Qi, Jens Eisert, Dominik Hangleiter, Bill Fefferman, and Ish Dhand. Quantum computational advantage via highdimensional gaussian boson sampling. Science Advances, 8(1):eabi7894, January 2022.
- [87] Changhun Oh, Kyungjoo Noh, Bill Fefferman, and Liang Jiang. Classical simulation of lossy boson sampling using matrix product operators. *Physical Review* A, 104(2):022407, August 2021.
- [88] Minzhao Liu, Changhun Oh, Junyu Liu, Liang Jiang, and Yuri Alexeev. Simulating lossy gaussian boson sampling with matrix-product operators. *Physical Review* A, 108(5):052604, November 2023.
- [89] Gil Kalai and Guy Kindler. Gaussian noise sensitivity and bosonsampling. (arXiv:1409.3093), November 2014. arXiv:1409.3093 [quant-ph].
- [90] Joseph Tindall and Matthew Fishman. Gauging tensor networks with belief propagation. *SciPost Physics*, 15(6):222, December 2023.
- [91] K. Kechedzhi, S. V. Isakov, S. Mandrà, B. Villalonga, X. Mi, S. Boixo, and V. Smelyanskiy. Effective quantum volume, fidelity and computational cost of noisy quantum processing experiments. (arXiv:2306.15970), January 2024. arXiv:2306.15970.
- [92] Tomislav Begušić and Garnet Kin-Lic Chan. Fast classical simulation of evidence for the utility of quantum computing before fault tolerance. (arXiv:2306.16372), June 2023. arXiv:2306.16372.
- [93] Tomislav Begušić, Kasra Hejazi, and Garnet Kin-Lic Chan. Simulating quantum circuit expectation values by clifford perturbation theory. (arXiv:2306.04797), July 2023. arXiv:2306.04797.
- [94] Tomislav Begušić, Johnnie Gray, and Garnet Kin-Lic Chan. Fast and converged classical simulations of evidence for the utility of quantum computing before fault tolerance. *Science Advances*, 10(3):eadk4321, January 2024.
- [95] Hai-Jun Liao, Kang Wang, Zong-Sheng Zhou, Pan Zhang, and Tao Xiang. Simulation of ibm's kicked ising experiment with projected entangled pair operator. (arXiv:2308.03082), August 2023. arXiv:2308.03082.
- [96] Edward Farhi, Jeffrey Goldstone, and Sam Gutmann. A quantum approximate optimization algorithm. (arXiv:1411.4028), November 2014. arXiv:1411.4028.
- [97] Johan Håstad. On bounded occurrence constraint satisfaction. Information Processing Letters, 74(1):1–6, April 2000.
- [98] Johan Håstad. Some optimal inapproximability results. J. ACM, 48(4):798–859, July 2001.
- [99] Edward Farhi, Jeffrey Goldstone, and Sam Gutmann. A quantum approximate optimization algorithm applied to a bounded occurrence constraint problem. (arXiv:1412.6062), June 2015. arXiv:1412.6062.
- [100] Scott Aaronson. Quantum computing news items (by reader request). https://scottaaronson.blog/?p= 2155, January 2015.
- [101] Boaz Barak, Ankur Moitra, Ryan O'Donnell, Prasad Raghavendra, Oded Regev, David Steurer, Luca Trevisan, Aravindan Vijayaraghavan, David Witmer, and John Wright. Beating the random assignment on constraint satisfaction problems of bounded degree. (arXiv:1505.03424), August 2015. arXiv:1505.03424.

- [102] Ashley Montanaro and Leo Zhou. Quantum speedups in solving near-symmetric optimization problems by low-depth qaoa. (arXiv:2411.04979), November 2024. arXiv:2411.04979.
- [103] Iordanis Kerenidis and Anupam Prakash. Quantum recommendation systems. (arXiv:1603.08675), September 2016. arXiv:1603.08675.
- [104] Ewin Tang. A quantum-inspired classical algorithm for recommendation systems. (arXiv:1807.04271), May 2019. arXiv:1807.04271.
- [105] Alan Frieze, Ravi Kannan, and Santosh Vempala. Fast monte-carlo algorithms for finding low-rank approximations. J. ACM, 51(6):1025–1041, November 2004.
- [106] Juan Miguel Arrazola, Alain Delgado, Bhaskar Roy Bardhan, and Seth Lloyd. Quantum-inspired algorithms in practice. (arXiv:1905.10415), August 2020. arXiv:1905.10415.
- [107] Nai-Hui Chia, Han-Hsuan Lin, and Chunhao Wang. Quantum-inspired sublinear classical algorithms for solving low-rank linear systems. (arXiv:1811.04852), November 2018. arXiv:1811.04852.
- [108] András Gilyén, Zhao Song, and Ewin Tang. An improved quantum-inspired algorithm for linear regression. *Quantum*, 6:754, June 2022.
- [109] Jordan Cotler, Hsin-Yuan Huang, and Jarrod R. Mc-Clean. Revisiting dequantization and quantum advantage in learning tasks. (arXiv:2112.00811), December 2021. arXiv:2112.00811 [quant-ph].
- [110] Richard P. Feynman. Simulating physics with computers. International Journal of Theoretical Physics, 21(6-7):467-488, June 1982.
- [111] A. Yu Kitaev. Quantum measurements and the abelian stabilizer problem. (arXiv:quant-ph/9511026), November 1995. arXiv:quant-ph/9511026.
- [112] Lin Lin. Lecture notes on quantum algorithms for scientific computation. (arXiv:2201.08309), January 2022. arXiv:2201.08309 [quant-ph].
- [113] Lin Lin and Yu Tong. Heisenberg-limited ground-state energy estimation for early fault-tolerant quantum computers. *PRX Quantum*, 3(1):010318, February 2022.
- [114] Laura Clinton, Toby S. Cubitt, Raul Garcia-Patron, Ashley Montanaro, Stasja Stanisic, and Maarten Stroeks. Quantum phase estimation without controlled unitaries. (arXiv:2410.21517), October 2024. arXiv:2410.21517 [quant-ph].
- [115] Seunghoon Lee, Joonho Lee, Huanchen Zhai, Yu Tong, Alexander M. Dalzell, Ashutosh Kumar, Phillip Helms, Johnnie Gray, Zhi-Hao Cui, Wenyuan Liu, Michael Kastoryano, Ryan Babbush, John Preskill, David R. Reichman, Earl T. Campbell, Edward F. Valeev, Lin Lin, and Garnet Kin-Lic Chan. Nature Communications, (1):1952, April 2023.
- [116] Craig Gidney and Martin Ekerå. How to factor 2048 bit rsa integers in 8 hours using 20 million noisy qubits. *Quantum*, 5:433, April 2021.
- [117] Oded Regev. An efficient quantum factoring algorithm. (arXiv:2308.06572), January 2024. arXiv:2308.06572 [quant-ph].
- [118] D. G. Cory, M. Price, W. Maas, E. Knill, R. Laflamme, W. H. Zurek, T. F. Havel, and S. S. Somaroo. Experimental quantum error correction. *Physical Review Letters*, 81:2152, 1998.
- [119] J. Chiaverini, D. Leibfried, T. Schaetz, M. D. Barrett, R. B. Blakestad, J. Britton, W. M. Itano, J. D. Jost,

E. Knill, C. Langer, R. Ozeri, and D. J. Wineland. Realization of quantum error correction. *Nature*, 432(7017):602–605, December 2004.

- [120] T. B. Pittman, B. C. Jacobs, and J. D. Franson. Demonstration of quantum error correction using linear optics. *Physical Review A*, 71(5):052332, May 2005. arXiv:quant-ph/0502042.
- [121] E. Knill, R. Laflamme, R. Martinez, and C. Negrevergne. Benchmarking quantum computers: the fivequbit error correcting code. *Physical Review Letters*, 86:5811, 2001.
- [122] P. Schindler, J. T. Barreiro, T. Monz, V. Nebendahl, D. Nigg, M. Chwalla, M. Hennrich, and R. Blatt. Experimental repetitive quantum error correction. *Science*, 332:1059, 2011.
- [123] O. Moussa, J. Baugh, C. A. Ryan, and R. Laflamme. Demonstration of sufficient control for two rounds of quantum error correction in a solid-state ensemble quantum information processor. *Physical Review Letters*, 107:160501, 2011.
- [124] J. Zhang, T. Laflamme, and D. Cory. Experimental implementation of encoded logical qubits in a 3qubit decoherence-free subspace. *Physical Review A*, 82:022304, 2011.
- [125] M. D. Reed, L. DiCarlo, S. E. Nigg, L. Sun, L. Frunzio, S. M. Girvin, and R. J. Schoelkopf. Realization of threequbit quantum error correction with superconducting circuits. *Nature*, 482:382, 2012.
- [126] J. Zhang, R. Laflamme, and D. G. Cory. Experimental quantum error correction with large block codes. *Physical Review Letters*, 108:110501, 2012.
- [127] B. A. Bell, D. A. Herrera-Martí, M. S. Tame, D. Markham, W. J. Wadsworth, and J. G. Rarity. Experimental demonstration of a graph state quantum error-correction code. *Nature Communications*, 5:5480, 2014.
- [128] J. Kelly, R. Barends, A. G. Fowler, A. Megrant, E. Jeffrey, T. C. White, D. Sank, J. Y. Mutus, B. Campbell, Y. Chen, Z. Chen, B. Chiaro, A. Dunsworth, I. C. Hoi, C. Neill, P. J. J. O'Malley, C. Quintana, P. Roushan, A. Vainsencher, J. Wenner, A. N. Cleland, and J. M. Martinis. State preservation by repetitive error detection in a superconducting quantum circuit. *Nature*, 519:66, 2015.
- [129] D. Nigg, M. Müller, E. A. Martinez, P. Schindler, M. Hennrich, T. Monz, M. A. Martin-Delgado, and R. Blatt. Quantum computations on a topologically encoded qubit. *Science*, 345:302, 2014.
- [130] G. Waldherr, Y. Wang, S. Zaiser, M. Jamali, T. Schulte-Herbrüggen, H. Abe, T. Ohshima, J. Isoya, J. F. Du, P. Neumann, and J. Wrachtrup. Quantum error correction in a solid-state hybrid spin register. *Nature*, 506:204, 2014.
- [131] Diego Riste, Stefano Poletto, M-Z Huang, Alessandro Bruno, Visa Vesterinen, O-P Saira, and Leonardo Di-Carlo. Detecting bit-flip errors in a logical qubit using stabilizer measurements. *Nature communications*, 6(1):1–6, 2015.
- [132] Antonio D Córcoles, Easwar Magesan, Srikanth J Srinivasan, Andrew W Cross, Matthias Steffen, Jay M Gambetta, and Jerry M Chow. Demonstration of a quantum error detection code using a square lattice of four superconducting qubits. *Nature communications*, 6(1):1–10, 2015.

- [133] Julia Cramer, Norbert Kalb, M Adriaan Rol, Bas Hensen, Machiel S Blok, Matthew Markham, Daniel J Twitchen, Ronald Hanson, and Tim H Taminiau. Repeated quantum error correction on a continuously encoded qubit by real-time feedback. *Nature communications*, 7(1):1–7, 2016.
- [134] Nissim Ofek, Andrei Petrenko, Reinier Heeres, Philip Reinhold, Zaki Leghtas, Brian Vlastakis, Yehan Liu, Luigi Frunzio, SM Girvin, Liang Jiang, et al. Extending the lifetime of a quantum bit with error correction in superconducting circuits. *Nature*, 536(7617):441–445, 2016.
- [135] Maika Takita, Andrew W Cross, AD Córcoles, Jerry M Chow, and Jay M Gambetta. Experimental demonstration of fault-tolerant state preparation with superconducting qubits. *Physical review letters*, 119(18):180501, 2017.
- [136] Norbert M Linke, Mauricio Gutierrez, Kevin A Landsman, Caroline Figgatt, Shantanu Debnath, Kenneth R Brown, and Christopher Monroe. Fault-tolerant quantum error detection. *Science advances*, 3(10):e1701074, 2017.
- [137] Reinier W. Heeres, Philip Reinhold, Nissim Ofek, Luigi Frunzio, Liang Jiang, Michel H. Devoret, and Robert J. Schoelkopf. Implementing a universal gate set on a logical qubit encoded in an oscillator. *Nature Communications*, 8(1):94, July 2017.
- [138] James R Wootton and Daniel Loss. Repetition code of 15 qubits. *Physical Review A*, 97(5):052313, 2018.
- [139] Christian Kraglund Andersen, Ants Remm, Stefania Lazar, Sebastian Krinner, Johannes Heinsoo, Jean-Claude Besse, Mihai Gabureac, Andreas Wallraff, and Christopher Eichler. Entanglement stabilization using ancilla-based parity detection and real-time feedback in superconducting circuits. *npj Quantum Information*, 5(1):1–7, 2019.
- [140] Ming Gong, Xiao Yuan, Shiyu Wang, Yulin Wu, Youwei Zhao, Chen Zha, Shaowei Li, Zhen Zhang, Qi Zhao, Yunchao Liu, et al. Experimental verification of fivequbit quantum error correction with superconducting qubits. arXiv preprint arXiv:1907.04507, 2019.
- [141] Ling Hu, Yuwei Ma, Weizhou Cai, Xianghao Mu, Yuan Xu, Weiting Wang, Yukai Wu, Haiyan Wang, YP Song, C-L Zou, et al. Quantum error correction and universal gate set operation on a binomial bosonic logical qubit. *Nature Physics*, 15(5):503–508, 2019.
- [142] Robin Harper and Steven T. Flammia. Fault-tolerant logical gates in the ibm quantum experience. *Physical Review Letters*, 122(8):080504, February 2019.
- [143] James R. Wootton. Benchmarking near-term devices with quantum error correction. Quantum Science and Technology, 5(4):044004, October 2020. arXiv:2004.11037 [quant-ph].
- [144] Christian Kraglund Andersen, Ants Remm, Stefania Lazar, Sebastian Krinner, Nathan Lacroix, Graham J Norris, Mihai Gabureac, Christopher Eichler, and Andreas Wallraff. Repeated quantum error detection in a surface code. *Nature Physics*, 16:875–880, 2020.
- [145] Laird Egan, Dripto M. Debroy, Crystal Noel, Andrew Risinger, Daiwei Zhu, Debopriyo Biswas, Michael Newman, Muyuan Li, Kenneth R. Brown, Marko Cetina, and Christopher Monroe. Fault-tolerant control of an error-corrected qubit. *Nature*, 598(7880):281–286, October 2021.

- [146] Yi-Han Luo, Ming-Cheng Chen, Manuel Erhard, Han-Sen Zhong, Dian Wu, Hao-Yang Tang, Qi Zhao, Xi-Lin Wang, Keisuke Fujii, Li Li, et al. Quantum teleportation of physical qubits into logical code-spaces. arXiv preprint arXiv:2009.06242, 2020.
- [147] P Campagne-Ibarcq, A Eickbusch, S Touzard, E Zalys-Geller, NE Frattini, VV Sivak, P Reinhold, S Puri, S Shankar, RJ Schoelkopf, et al. Quantum error correction of a qubit encoded in grid states of an oscillator. *Nature*, 584(7821):368–372, 2020.
- [148] Zijun Chen et al. Exponential suppression of bit or phase errors with cyclic error correction. *Nature*, 595(78677867):383–387, July 2021.
- [149] C. Ryan-Anderson et al. Realization of real-time faulttolerant quantum error correction. *Physical Review X*, 11(4):041058, December 2021.
- [150] Sebastian Krinner, Nathan Lacroix, Ants Remm, Agustin Di Paolo, Elie Genois, Catherine Leroux, Christoph Hellings, Stefania Lazar, Francois Swiadek, Johannes Herrmann, Graham J. Norris, Christian Kraglund Andersen, Markus Müller, Alexandre Blais, Christopher Eichler, and Andreas Wallraff. Realizing repeated quantum error correction in a distancethree surface code. 605:669–674, May 2022.
- [151] M. H. Abobeih, Y. Wang, J. Randall, S. J. H. Loenen, C. E. Bradley, M. Markham, D. J. Twitchen, B. M. Terhal, and T. H. Taminiau. Fault-tolerant operation of a logical qubit in a diamond quantum processor. *Nature*, 606(7916):884–889, June 2022.
- [152] Youwei Zhao, Yangsen Ye, He-Liang Huang, Yiming Zhang, Dachao Wu, Huijie Guan, Qingling Zhu, Zuolin Wei, Tan He, Sirui Cao, Fusheng Chen, Tung-Hsun Chung, Hui Deng, Daojin Fan, Ming Gong, Cheng Guo, Shaojun Guo, Lianchen Han, Na Li, Shaowei Li, Yuan Li, Futian Liang, Jin Lin, Haoran Qian, Hao Rong, Hong Su, Lihua Sun, Shiyu Wang, Yulin Wu, Yu Xu, Chong Ying, Jiale Yu, Chen Zha, Kaili Zhang, Yong-Heng Huo, Chao-Yang Lu, Cheng-Zhi Peng, Xiaobo Zhu, and Jian-Wei Pan. Realization of an errorcorrecting surface code with superconducting qubits. *Physical Review Letters*, 129(3):030501, July 2022.
- [153] V. V. Sivak, A. Eickbusch, B. Royer, S. Singh, I. Tsioutsios, S. Ganjam, A. Miano, B. L. Brock, A. Z. Ding,

L. Frunzio, S. M. Girvin, R. J. Schoelkopf, and M. H. Devoret. Real-time quantum error correction beyond break-even. *Nature*, 616(7955):50–55, April 2023.

- [154] Rajeev Acharya et al. Suppressing quantum errors by scaling a surface code logical qubit. *Nature*, 614(7949):676–681, February 2023.
- [155] A. Paetznick, M. P. da Silva, C. Ryan-Anderson, J. M. Bello-Rivas, J. P. Campora III, A. Chernoguzov, J. M. Dreiling, C. Foltz, F. Frachon, J. P. Gaebler, T. M. Gatterman, L. Grans-Samuelsson, D. Gresh, D. Hayes, N. Hewitt, C. Holliman, C. V. Horst, J. Johansen, D. Lucchetti, Y. Matsuoka, M. Mills, S. A. Moses, B. Neyenhuis, A. Paz, J. Pino, P. Siegfried, A. Sundaram, D. Tom, S. J. Wernli, M. Zanner, R. P. Stutz, and K. M. Svore. Demonstration of logical qubits and repeated error correction with better-than-physical error rates. (arXiv:2404.02280), November 2024. arXiv:2404.02280 [quant-ph].
- [156] Dolev Bluvstein, Simon J. Evered, Alexandra A. Geim, Sophie H. Li, Hengyun Zhou, Tom Manovitz, Sepehr Ebadi, Madelyn Cain, Marcin Kalinowski, Dominik Hangleiter, J. Pablo Bonilla Ataides, Nishad Maskara, Iris Cong, Xun Gao, Pedro Sales Rodriguez, Thomas Karolyshyn, Giulia Semeghini, Michael J. Gullans, Markus Greiner, Vladan Vuletić, and Mikhail D. Lukin. Logical quantum processor based on reconfigurable atom arrays. Nature, 626(7997):58–65, February 2024.
- [157] Rajeev Acharya et al. Quantum error correction below the surface code threshold. *Nature*, page 1–3, December 2024.
- [158] Hartmut Neven. Meet willow, our state-of-the-art quantum chip. https://blog.google/technology/ research/google-willow-quantum-chip/, December 2024.
- [159] Riddhi S. Gupta, Neereja Sundaresan, Thomas Alexander, Christopher J. Wood, Seth T. Merkel, Michael B. Healy, Marius Hillenbrand, Tomas Jochym-O'Connor, James R. Wootton, Theodore J. Yoder, Andrew W. Cross, Maika Takita, and Benjamin J. Brown. Encoding a magic state with beyond break-even fidelity. *Nature*, 625(7994):259–263, January 2024.