# Knowledge Injection via Prompt Distillation

Kalle Kujanpää \* Aalto University Department of Computer Science kalle.kujanpaa@aalto.fi

#### Abstract

In many practical applications, large language models (LLMs) need to incorporate new knowledge not present in their pre-training data. The primary methods for this are *fine-tuning* and retrieval-augmented generation (RAG). Although RAG has emerged as the industry standard for knowledge injection, fine-tuning has not yet achieved comparable success. In this paper, we propose a new fine-tuning technique for learning new knowledge and show that it can reach the performance of RAG. The proposed method is based on the self-distillation approach, which we call *prompt distillation*. First, we generate question-answer pairs about the new knowledge. Then, we fine-tune a student model on the question-answer pairs to imitate the output distributions of a teacher model, which additionally receives the new knowledge in its prompt. The student model is identical to the teacher, except it is equipped with a LoRA adapter. This training procedure facilitates distilling the new knowledge from the teacher's prompt into the student's weights.

### 1 Introduction

In applying large language models (LLMs) to specific problems, practitioners must often incorporate new or domain-specific knowledge into the generation process. Fine-tuning and Retrieval-Augmented Generation (RAG) are two primary methods to achieve this. Each of these approaches has distinct advantages and limitations. Fine-tuning can be particularly effective for internalizing new knowledge and integrating it seamlessly with pre-existing information within the model. In addition, finetuning helps mitigate the issue of excessively long prompts. In contrast, RAG excels at providing Harri Valpola and Alexander Ilin System 2 AI harri.valpola@system2ai.com alexander.ilin@system2ai.com



Figure 1: Average accuracy of responses to questions in the evaluation datasets. The proposed prompt distillation (PD) method is competitive with RAG and clearly outperforms supervised fine-tuning (SFT). Moreover, combining prompt distillation with RAG (PD+RAG) results in better performance than using vanilla RAG alone.

access to the most up-to-date information and is highly effective in responding to detailed queries (Schick et al., 2024; Lewis et al., 2020). Therefore, an ideal AI assistant would combine both techniques to capitalize on their strengths.

RAG has become the industry standard for knowledge injection, demonstrating robust performance in various contexts (Chen et al., 2024). However, knowledge injection through supervised finetuning has not yet achieved comparable success, as replicating RAG's performance has proven challenging (Ovadia et al., 2023; Mecklenburg et al., 2024). The extensive breadth of knowledge inherent in modern LLMs suggests that fine-tuning has not yet realized its full potential for knowledge injection, leaving significant room for improvement. This paper seeks to close the performance gap between RAG and fine-tuning in knowledge injection tasks.

Previous research on knowledge injection via supervised fine-tuning typically relies on training an LLM on question-answer pairs generated from the new knowledge. To avoid the need for manual

arXiv:2412.14964v1 [cs.CL] 19 Dec 2024

<sup>\*</sup>Kalle Kujanpää was funded by the Research Council of Finland (also known as the Academy of Finland) under the Flagship Programme of the Finnish Center for Artificial Intelligence (FCAI). This work was completed prior to his internship at Amazon and is unrelated to the position.

work, practitioners often use an expert LLM model to generate these pairs. Since the student model being fine-tuned is trained to replicate the expert's answers exactly (using answer tokens as targets), the quality of the generated data is of paramount importance. Consequently, it is common practice to use the best available model for data generation, typically an advanced API-based model such as GPT-4 (Achiam et al., 2023) or Claude (Anthropic, 2024).

The classical fine-tuning approach has several potential problems. First, using a different model for answer generation may introduce a mismatch between the expert and student answering styles. As a result, training may focus more on mimicking the answering style rather than learning the new factual information. Additionally, an intelligent expert may generate complex questions requiring high intelligence to answer, which the student may not possess. This issue was discussed, for example, by Mitra et al. (2023); Mirzadeh et al. (2020), who carefully adjusted the prompts to allow a smaller model to learn more efficiently. Another concern arises from using tokens as targets since the same question can have multiple valid answers. Training a model to replicate the expert's answers verbatim risks overfitting, and the student model may not generalize well to answer new questions. This issue could be potentially mitigated by sampling multiple responses from the expert model. However, this makes the training data generation process much more expensive, particularly when using a large expert model.

To address these challenges, this paper proposes a novel fine-tuning technique for learning new knowledge. The approach that we call *prompt distillation* leverages the concept of self-distillation, where the model learns from distributions over answer tokens it produces itself. By using the same model as both teacher and student, this technique eliminates the mismatch between the two, ensuring that training focuses on learning factual knowledge rather than memorizing prompts verbatim or adopting the expert's answering style.

We evaluate prompt distillation on knowledge injection tasks using a custom dataset derived from the Squadshifts data. We compare our approach against RAG and non-RAG baselines. In our experiments, prompt distillation outperforms all other non-RAG baselines, and its performance is competitive with RAG's. We summarize our main results and compare prompt distillation to supervised finetuning and RAG in Figure 1. We perform all our evaluations using instruct-tuned models from the Llama 3 family (Dubey et al., 2024). Our main contributions are:

- 1. We propose prompt distillation as a novel approach for knowledge injection into LLMs.
- 2. We present experiments on multiple datasets showing that the performance of prompt distillation can match the performance of RAG in knowledge injection tasks.
- 3. We present analysis and ablations that provide insights on what contributes to the excellent performance of prompt distillation.

### **2** Prompt Distillation

The basic idea of prompt distillation is very similar to imitation learning. An expert empowered by extra knowledge c generates expert demonstrations, which in the case of knowledge injection may consist of question-answer pairs ( $\mathbf{q}$ ,  $\mathbf{a}$ ). In classical imitation learning, the student can only access the expert demonstration, not its full policy. This is the case for standard supervised fine-tuning, which tries to imitate the actions (tokens)  $a_i$  taken by the expert. However, if we process a prompt that includes  $\mathbf{c}$ ,  $\mathbf{q}$ ,  $\mathbf{a}$  using an open-source LLM (which we call a teacher), we can get access to a full policy of generating answer  $\mathbf{a}$  to question  $\mathbf{q}$  in the light of knowledge  $\mathbf{c}$ :

$$\pi_{\theta}(a_i | \mathbf{c}, \mathbf{q}, \mathbf{a}_{1..i-1}).$$

The teacher's policy  $\pi_{\theta}(a_i | \mathbf{c}, \mathbf{q}, \mathbf{a}_{1..i-1})$  is the distribution of the answer token at position *i*, and  $\theta$  denotes the teacher model parameters. The full policy  $\pi_{\theta}(a_i | \mathbf{c}, \mathbf{q}, \mathbf{a}_{1..i-1})$  contains far more information than individual actions  $a_i$ , and learning the full policy is precisely what prompt distillation does.

The goal of prompt distillation is to train a student model to mimic the policy of the teacher but *without receiving context* **c** *in its inputs*, that is, the student's policy should satisfy:

 $\pi_{\theta'}(a_i | \mathbf{q}, \mathbf{a}_{1..i-1}) \approx \pi_{\theta}(a_i | \mathbf{c}, \mathbf{q}, \mathbf{a}_{1..i-1}).$ 

### 2.1 Data generation

The first step of prompt distillation is the generation of expert demonstrations, which is a set of question-answer pairs (q, a) about the new knowledge c. We first generate questions q by an LLM



Figure 2: An overview of the Prompt Distillation approach. The privileged information in the teacher's prompt is distilled into the student's weights.

using a relatively high temperature ( $\tau > 1$ ) to ensure that the questions are varied enough and that as few questions as possible replicate. Then, we generate answers a also using an LLM with a relatively high temperature  $\tau > 1$ . We do this for two reasons: 1) using higher temperature results in a greater diversity of generated samples, and 2) we deliberately simulate answers that may contain unusual passages or even factual mistakes. Having such corrupted inputs does not harm the fine-tuning procedure because the generated answers are not used directly as targets but rather as inputs of the student model (see Fig. 2). Using noisy demonstrations is beneficial because the student learns to produce reasonable answers even if the answer generation started in a sub-optimal way. By distilling the teacher's policy  $\pi_{\theta}(a_i | \mathbf{c}, \mathbf{q}, \mathbf{a}_{1..i-1})$ , the student learns to stay on the right track, which is the underlying idea of the DAGGER algorithm (Ross et al., 2011).

Since we want to copy the teacher's policy, we need to sample questions  $\mathbf{q}$  and answers  $\mathbf{a}$  where  $\mathbf{c}$  has a significant impact on the answer-generation policy  $\pi_{\theta}(a_i | \mathbf{c}, \mathbf{q}, \mathbf{a}_{1..i-1})$ . Naturally, this impact is highest when the questions and answers are related to  $\mathbf{c}$ . However, having some questions and answers which are only distantly related to  $\mathbf{c}$  does not hurt, it just makes training less efficient.

In the experiments, we generate expert demonstrations in two steps: first, we generate the questions by the same 8B model being fine-tuned; then, we generate answers using either the same 8B model.

#### 2.2 Distillation

For the teacher model, we formulate a prompt consisting of the knowledge c, a question q, and an

answer **a**. The teacher model computes logits  $z_k$  for every position k in the prompt. The student model receives only question **q** and answer **a** as input and computes the output logits  $z'_k$ . We perform knowledge transfer at a high temperature as in the classical knowledge distillation (Hinton et al., 2015); that is, the logits are converted into probabilities using the same temperature for both the target and the student's distributions:

$$\pi_{\theta,k} = \frac{\exp(z_k/T)}{\sum_{k'} \exp(z_{k'}/T)}$$

The loss is the average KL divergence between the two distributions for all answer positions  $i \in A$ :

$$\mathcal{L} = \frac{1}{N_A} \sum_{i \in A}^{N_A} D_{\mathrm{KL}}(i) \,,$$

where

$$D_{\mathrm{KL}}(i) = \\ \pi_{\theta}(a_i | \mathbf{c}, \mathbf{q}, \mathbf{a}_{1..i-1}) \log \frac{\pi_{\theta}(a_i | \mathbf{c}, \mathbf{q}, \mathbf{a}_{1..i-1})}{\pi_{\theta'}(a_i | \mathbf{q}, \mathbf{a}_{1..i-1})}$$

A graphical illustration of the distillation process is presented in Fig. 2.

We distill the knowledge at a higher temperature T > 1, making the student pay more attention to less probable tokens. That is, the student learns to avoid the answers that the teacher is avoiding actively. To achieve the same effect using the cross-entropy loss with hard targets, one would need an enormous amount of samples to realize that some answers must have a low probability.

We briefly explored the inclusion of mid-layer activations in the loss computation but found that using the output logits alone was simpler and efficient enough.

## 2.3 Comparison to Fine-Tuning with Hard Targets

When using cross-entropy loss with hard (one-hot encoded) target labels, the student model is forced to adjust its output distribution to match the one-hot encoding, assigning all probability mass to a single token, which can disturb the student's existing distribution, even when it already aligns well with the teacher's knowledge. As a result, the student needs many training samples to average out these disturbances and approximate the desired distribution.

In contrast, using the KL divergence loss with soft targets from the teacher allows the student to preserve its output distribution in areas where the teacher provides no new information. This means the student only adjusts its distribution where there is a discrepancy, leading to more efficient learning. Furthermore, when using cross-entropy loss with hard labels, the generated answer tokens from the teacher model are treated as ground-truth targets. This requires sampling these target answers at a low temperature during training to produce factually correct outputs. However, this can lead to less diverse answers and a higher degree of overfitting to these specific targets during fine-tuning. Consequently, the fine-tuned student model may become incapable of answering questions that are formulated differently.

### 2.4 Student Model

In our experiments, the student model is constructed to be the same as the teacher model, additionally equipped with a LoRA adapter (Hu et al., 2021):

$$\theta' = \theta + \Delta\theta \,,$$

where  $\Delta \theta$  is LoRA initialised to  $\Delta \theta = 0$ . Thus, the two models are identical at the beginning of training. During the training process, the adapter's weights  $\Delta \theta$  change, and therefore, the new knowledge c gets distilled into the student's weights  $\theta'$ . In our implementation, we use the same network for the student and the teacher, and we turn the adapter on and off to alternate between the two models. Thus, having two models in the training procedure does not lead to increased memory consumption. To save computing resources at the expense of storage capacity, storing the teacher logits when the answers are generated is sufficient, eliminating any additional compute during fine-tuning compared with hard targets.

## **3 Related Work**

**Prompt Engineering and In-Context Learning** allow users to influence model behavior by adding instructions and examples within the input prompt (Brown et al., 2020; Sanh et al., 2021; Lewis et al., 2020; Liu et al., 2023). Retrieval-augmented generation (RAG) utilizes this idea by incorporating novel knowledge retrieved via an external retrieval mechanism into the prompt (Lewis et al., 2020; Izacard and Grave, 2020). However, as the complexity and length of the prompt increases, so does the challenge for LLMs to effectively attend to and integrate all the relevant information in their reasoning. Furthermore, the knowledge in prompts is transient; it is lost once the prompt changes. Current LLMs are still limited in how much information they can manage within a single prompt, even though the size of the allowed context has been growing (Liu et al., 2024b).

Unsupervised Fine-Tuning of LLMs has been used for knowledge injection with mixed results. Unsupervised fine-tuning (UFT), where a model is trained on the next-token prediction task on new documents, can lead to performance gains as large language models learn to memorize their training data (Gururangan et al., 2020; Carlini et al., 2021, 2022). However, fine-tuning has often underperformed in knowledge injection compared to RAG, particularly in tasks involving new factual information. Research by Ovadia et al. (2023) highlights the challenges LLMs face when learning new facts through UFT, both for existing knowledge and entirely new information. Moreover, studies such as (Nayak et al., 2024) indicate that UFT can sometimes undo the benefits of previous instruction tuning.

**Supervised Fine-Tuning** for knowledge injection proceeds by training pre-trained LLMs on tasks generated from new documents. These tasks can be generated by standard LLMs (Mecklenburg et al., 2024) or by models trained explicitly for this purpose (Nayak et al., 2024). A hybrid approach, RAFT (Zhang et al., 2024), combines RAG with SFT. RAFT trains models to ignore irrelevant documents and focus on the information most helpful in answering specific questions, effectively filtering out distractors, which can otherwise lead to the LLM performance deterioration (Shi et al., 2023a; Mallen et al., 2022). Liu et al. (2024a) propose a two-stage fine-tuning strategy for knowledge injection, consisting of continual pre-training followed

by supervised fine-tuning. Gupta et al. (2024) show that one can combine fine-tuning and RAG for maximal domain-specific performance. Another benefit of fine-tuning over RAG is that we can recursively accumulate more knowledge, as the prompt length will not increase, which allows the model to continue improving on complex tasks (Snell et al., 2022; Choi et al., 2022). Fine-tuning's ability to continuously improve as the model acquires necessary prior knowledge (Ye et al., 2023; Liu et al., 2024a) highlights its potential, though significant challenges remain.

Knowledge Distillation is a well-established technique where a smaller model learns from the outputs of a larger model. This method was first popularized by Hinton et al. (2015) and has since been adapted for various applications, including natural language processing (see, e.g., Sanh et al., 2019). In the context of LLMs, distillation has been used to transfer the abilities of larger, proprietary LLMs to smaller models or otherwise improve the performance of smaller models with the larger teacher model (Peng et al., 2023; Taori et al., 2023; Chiang et al., 2023; Xu et al., 2023a,b; Mukherjee et al., 2023). Recent advancements in distillation include modifications to the prompt of the teacher, aiming to elicit more detailed responses that include explanations of the reasoning process (Mukherjee et al., 2023). Mitra et al. (2023) tuned the teacher's prompt to better align with the student's learning needs. Research by Wang et al. (2020) and Mukherjee and Awadallah (2020) suggests that utilizing richer signals, such as logits, intermediate representations, and attention states, can significantly improve the performance of the distillation process.

**Self-Distillation** extends traditional distillation by allowing a model to learn from its own outputs, performing self-improvement. In this approach, the teacher can access privileged information, such as cleaner inputs, while the student model learns from noisier or less complete data. This technique has been particularly effective in semi-supervised learning (see, e.g., Tarvainen and Valpola, 2017 and He et al. (2019)). Self-distillation is particularly relevant to our work, as it eliminates the need for a more advanced teacher model, simplifying the distillation while eliminating the initial mismatch between the teacher and the student.

**Context Distillation**, the idea of distilling context into model weights, was used by Askell et al. (2021) to improve LLM alignment with human

values to produce polite, helpful, and accurate answers. They distill a prompt that contains fourteen human-assistant conversations in which the assistant always follows the desired policy. Thus, that work focuses on learning the answering style rather than factual knowledge.

Snell et al. (2022) demonstrated the distillation of more detailed task instructions, in-context examples and step-by-step reasoning. Compared to that work, we show the efficiency of the prompt distillation idea for injecting new factual knowledge into LLMs, demonstrating the distillation of knowledge from documents that contain hundreds of thousands of tokens.

Choi et al. (2022) used the distillation idea to distill short instruction prompts that, for example, define a persona participating in a conversation or contain task instructions. They additionally trained a model to generate input data for the distillation process, using examples from the considered benchmarks as training data. Compared to that work, we show that the distillation approach works well for learning new factual knowledge from many documents, and it can achieve performance competitive with RAG. We present insights on what contributes to the excellent performance of prompt distillation. For example, we demonstrate the positive effect of higher temperatures in the distillation process. In contrast to that work, we do not train an extra data generation model and show that prompting standard LLMs is sufficient.

Concurrently to our work, Qi et al. (2024) proposed using a distillation approach to edit knowledge retained in the LLM weights. The new factual knowledge is assumed to exist as triplets (entity, relation, object). The triplets are converted into short statements, which are used as additional context for the teacher's prompt. Compared to that paper, we do not assume the existence of new knowledge in the triplet form. Instead, we learn new facts from raw documents without any supervision.

#### 4 Experiments

We evaluate prompt distillation in a knowledge injection task on a new dataset that we derived from Squadshift (Miller et al., 2020). The original dataset was created for an *open-book* scenario when the model has access to a document and is tasked to find the answer to a given question. The dataset consists of a passage of text, a question, and spans of text within the passage that contains the

Dataset	Documents	Number of Tokens
Amazon	207	363,031
New Wiki	203	252,035
NYT	188	338,918
Reddit	209	368,214

 Table 1: Summary of the dataset derived from Squad-shift

answer. We perform model fine-tuning for a *closed*book scenario when the model needs to answer a question without seeing a document in its prompt. Many questions in the original dataset cannot be understood without seeing the corresponding document, as they lack enough context. Therefore, we re-formulate the questions to provide enough context, but the answer remains the same. Question reformulation is done by Llama3-70B-Instruct. We use the re-formulated questions as a test set to evaluate model performance after fine-tuning.

Our test set consists of 1,000 questions from each of the four Squadshift variants: Wikipedia, New York Times articles, Reddit posts, and Amazon product reviews. The number of passages we use is determined by the number of documents corresponding to the first 1000 questions, which is between 188 (NYT) and 208 (Reddit). We summarize the datasets we use in Table 1. We perform experiments on the four individual subsets separately. It is important in our experiments that the test questions probe information unknown to the base model. To test this, we evaluate the performance of the base model on the test questions (see the base model results in Table 2). All prompts used for question generation, answer generation, and grading are presented in Appendix E.

#### 4.1 Implementation of Prompt Distillation

For each question in our dataset, we generate 30 training questions using Llama3-8B-Instruct. We use a relatively high temperature of 1.5 to ensure sufficient diversity of questions. We do not take any measures to prevent the generation of questions that are very similar to our test set. Since our test set was generated by re-formulating the questions from the original Squadshift using a different model, any possible similarity between the training and test questions is by coincidence and not due to using the same generation process. We generate answers to the training questions using Llama3-8B-Instruct with temperature  $\tau = 1.5$ .

We use the training questions to fine-tune a Llama3-8B-Instruct model using the prompt distillation approach. The student is constructed using a LoRA adapter with rank 1024 applied to all layers. We use temperature T = 2 in the KL divergence loss. We use the AdamW optimizer and a learning rate  $10^{-5}$  for all datasets with a linear warmup during the first epoch and a batch size of 4. We run the fine-tuning on four AMD MI250X GPUs for 24 hours (approximately ten epochs).

At test time, we present a fine-tuned model test questions, one question at a time, and we sample an answer using a temperature of 0.25. For the complete set of hyperparameters for prompt distillation, please see Table 6.

### 4.2 Answer Grading

We use LLM-as-a-judge for grading the answers (Zheng et al., 2023) and rely on Llama3-8B-Instruct with a Chain-of-Thought-like prompt to grade the answers. The grading prompt involves two steps. The model has to first generate a reasoning for the grade, and only then produce the actual grade. The grade is True/False. This two-step prompt significantly improves grading accuracy. We manually inspected the accuracy of the grading procedure on a subset of the test questions and estimated the accuracy to be 98%.

## 4.3 Baselines

**Supervised Fine-Tuning (SFT).** We use the same 30 training questions and generate 30 answers using Llama3-8B-Instruct with a temperature of 0.25. We fine-tune a model with a LoRA adapter using the standard cross-entropy token loss. All other training parameters, including duration, infrastructure, and learning rate, remain consistent with prompt distillation.

**RAG**. We test the performance of the base models enhanced by RAG. To implement RAG, we employ two different retrieval techniques: BM25 and embedding-based. For BM25, we create a document database by tokenizing all context paragraphs from the evaluation dataset with the Llama-3 tokenizer. We then tokenize the questions using the same tokenizer and use the Okapi BM25 ranking function (Robertson et al., 1995) from the rankbm25 Python library to perform retrieval. In the embedding-based approach, we embed all the documents and questions with OpenAI's Embedding-API, using the *text-embedding-3-small* model. We use a cosine similarity to retrieve the most rele-

Method	Amazon	New Wiki	NYT	Reddit
Prompt Distillation Supervised Fine-Tuning Unsupervised Fine-Tuning Base model	$\begin{array}{c} \textbf{86.1} \pm 0.2 \\ 75.9 \pm 1.8 \\ 39.5 \pm 1.6 \\ 22.1 \end{array}$	$\begin{array}{c} \textbf{94.4} \pm 0.3 \\ 89.5 \pm 0.2 \\ 63.1 \pm 0.6 \\ 61.2 \end{array}$	$\begin{array}{c} \textbf{93.6} \pm 0.6 \\ 87.5 \pm 0.2 \\ 52.6 \pm 1.4 \\ 38.2 \end{array}$	<b>79.5</b> ±1.4 69.8 ±0.4 30.9 ±2.7 20.8
Prompt Distillation + RAG SFT w/ Distractors + RAG Base model + RAG	<b>88.5</b> ±0.3 87.0 ±0.7 86.3	<b>96.7</b> ±0.2 95.1 ±0.4 95.6	<b>96.9</b> ±0.2 94.2 ±0.1 96.3	$76.7 \pm 2.7 \\ 82.4 \pm 0.8 \\ 78.6$

Table 2: Average answer correctness (%) on question answering task in the closed-book (upper part) and RAG (lower part) scenarios. The uncertainty is two standard errors of the mean.

vant questions. Our RAG implementation works as follows. Given a question, we pull k = 7 most relevant documents and add them to the model's prompt. We use the largest possible number k to stay within the context size limits of Llama3-8B-Instruct. In our preliminary tests, we found that the performance increases with a larger number of documents in the prompt. We also experimented with using RAG together with various fine-tuned models.

Supervised Fine-Tuning with Distractors. We implement a supervised fine-tuning method inspired by RAFT (Zhang et al., 2024). During finetuning, we sample two random distractor documents from the same domain and append them to the context that already contains the golden document for answering the question. The order of documents is randomized to prevent the model from identifying the correct document based solely on position. Then, the correct snippet is eliminated with a probability of 40 % to help the model learn to answer the question even if incorrect documents are retrieved during evaluation, aligning with the optimal setting reported in the original paper (see Fig. 5 in Zhang et al. 2024). This approach combines elements of both open-book and closed-book fine-tuning. To generate the training data, we use a Chain-of-Thoughts prompt, as its importance was highlighted in the original work.

**Unsupervised Fine-Tuning**: This setting resembles the original base model pre-training setup with the objective of predicting the subsequent token in the paragraph. The paragraphs are sampled from the documents in the Squadshift datasets by chunking (splitting into smaller snippets) while keeping overlap, ensuring context from one snippet carries into the next. After experimenting with various epoch counts and learning rates, we found



Figure 3: Average accuracy (%) of responses for prompt distillation (PD) and supervised fine-tuning (SFT) as a function of the number of questions per test question in the training set on the New York Times dataset. Note the logarithmic scale on the x-axis.

that training for three epochs generally yielded the best performance. We tune a model with a LoRA adapter.

For consistency, all fine-tuned models utilize the same training questions, Llama3-8B-Instruct as the base model, and, if applicable, a LoRA adapter with the same architecture used for prompt distillation. Training durations are standardized across methods, with the exception of unsupervised finetuning, where extended training led to overfitting on the training dataset and degraded performance. The retrieval mechanism (Okapi BM25 and OpenAI Embeddings) and the number of context snippets retrieved were constant across all applicable methods. Experiments were run with three different seeds, except for the base LLM, where we did not do any re-training.

T	au	Amazon	New Wiki	NYT	Reddit
2	1.5	$86.1 \pm 0.2$	$94.4 \pm 0.3$	$93.6 \pm 0.6$	$79.5 \pm 1.4$
1	1.5	$83.8 \pm 0.9$	$93.3 \pm 0.5$	$91.8 \pm 0.2$	$78.2 \pm 0.9$
2	0.25	$83.6 \pm 1.1$	$93.9 \pm 0.1$	$92.7 \pm 0.5$	$79.0\ \pm 1.6$

Table 3: The average answer correctness (%) of prompt distillation with different temperatures, when the training data has been generated by Llama-3-8B Instruct. The top row is the standard configuration. The uncertainty is two standard errors of the mean.

## 4.4 Results

Table 2 presents results under two settings: a plain question-answering scenario in a closed-book setting (upper part) and question-answering enhanced by RAG (lower part). Among the four comparison methods without RAG, prompt distillation emerges as the best-performing model, significantly outperforming supervised fine-tuning. It also achieves performance levels close to RAG. In contrast, unsupervised fine-tuning performs poorly. When combined with RAG, prompt distillation achieves the best overall performance. Despite not being finetuned explicitly for the RAG scenario, prompt distillation effectively utilizes context without learning to ignore it. SFT with distractors reaches the best performance in Reddit with RAG. Introducing distractors to the prompt during fine-tuning to improve robustness is an orthogonal direction to prompt distillation, and they could be combined for an even higher potential performance gain.

The tables show that almost all differences between prompt distillation and baseline methods are outside the two standard error confidence intervals. Qualitative examples of the prompt distillation model behavior are shown in Appendix F. Complete results for the RAG scenario with both BM25 and OpenAI's Embedding-API are presented in Table 4 in Appendix A. There, we also include results for the base model with oracle retrieval to assess the performance loss due to retrieving incorrect documents.

#### 4.5 Ablations

In Fig. 3, we study the impact of the number of training questions on the performance of prompt distillation and supervised fine-tuning. These results highlight that prompt distillation is significantly more data efficient than SFT, and the data efficiency gap between the methods increases as the number of questions grows. To match the asymptotic performance of prompt distillation, supervised fine-tuning needs almost an order of magnitude

more training data. The full results, including the ones with RAG, are presented in Appendix B.

In Table 3, we show the importance of using higher sampling temperatures for training data generation ( $\tau$ ) and during distillation (T). Reducing the value of either temperature leads to a degradation in the prompt distillation performance, underscoring the importance of maximizing data coverage and learning to actively avoid incorrect answers.

## 5 Conclusion

In this paper, we propose using prompt distillation to inject knowledge into LLMs. The method is based on the self-distillation idea when a student model learns to imitate the answers of a teacher that gets new knowledge from its prompt. We demonstrated experimentally that prompt distillation outperforms traditional supervised fine-tuning: it learns to provide more accurate answers than SFT for a smaller amount of data. Our method does not depend on the availability of stronger teacher models. The results obtained with prompt distillation on knowledge injection tasks are competitive with RAG, which, to the best of our knowledge, has not been achieved previously with fine-tuning methods.

We believe that storing the knowledge in the model's weights offers a more scalable approach than accumulating new knowledge in the prompt or external databases managed by an RAG system. To achieve proper knowledge internalization, the model should understand the relation of the new knowledge to the old one, which we believe is easier to achieve via distillation rather than maintaining facts and their relations in knowledge bases with complex structures.

Our findings open exciting possibilities for training agentic LLMs that can collect training data from their own experience and continually selfimprove. Another promising direction for future research is exploring the combination of prompt distillation and RAG. Furthermore, investigating the role of question generation could help us gain an understanding of how to improve the performance of prompt distillation further.

## 6 Limitations

A significant challenge in this study was the absence of standardized evaluation datasets for knowledge injection. We used a modified version of the Squadshifts data, which required paraphrasing to ensure the questions were understandable without their original context. Without this adjustment, the RAG-based pipeline would have underperformed. The modified questions have been included in the supplementary material.

Finally, the answers generated by all methods were graded by Llama3-8B-Instruct, the same model that generated the answers, which can raise concerns about bias, but because all models in the experiment were fine-tuned from the same model, the impact on grading consistency is minimal, which we also manually verified by grading a subset of the answers.

## 7 Ethical Considerations

We fine-tune open-weight LLMs. Any risks associated with them are generally associated with our work as well. If safeguards were built into the model we fine-tuned, we cannot be sure that our fine-tuning method does not weaken them. Our objective is to embed knowledge directly into the model. We risk perpetuating biases and misinformation if the injected knowledge is harmful or misleading.

### Acknowledgments

We acknowledge the computational resources provided by the Aalto Science-IT project and CSC, Finnish IT Center for Science.

## References

- Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.
- Anthropic. 2024. Claude 3.5 sonnet model card addendum. Accessed: 2024-12-02.
- Amanda Askell, Yuntao Bai, Anna Chen, Dawn Drain, Deep Ganguli, Tom Henighan, Andy Jones, Nicholas Joseph, Ben Mann, Nova DasSarma, et al. 2021. A

general language assistant as a laboratory for alignment. *arXiv preprint arXiv:2112.00861*.

- Sebastian Borgeaud, Arthur Mensch, Jordan Hoffmann, Trevor Cai, Eliza Rutherford, Katie Millican, George Bm Van Den Driessche, Jean-Baptiste Lespiau, Bogdan Damoc, Aidan Clark, et al. 2022. Improving language models by retrieving from trillions of tokens. In *International conference on machine learning*, pages 2206–2240. PMLR.
- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. 2020. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901.
- Nicholas Carlini, Daphne Ippolito, Matthew Jagielski, Katherine Lee, Florian Tramer, and Chiyuan Zhang. 2022. Quantifying memorization across neural language models. *arXiv preprint arXiv:2202.07646*.
- Nicholas Carlini, Florian Tramer, Eric Wallace, Matthew Jagielski, Ariel Herbert-Voss, Katherine Lee, Adam Roberts, Tom Brown, Dawn Song, Ulfar Erlingsson, et al. 2021. Extracting training data from large language models. In *30th USENIX Security Symposium (USENIX Security 21)*, pages 2633–2650.
- Jiawei Chen, Hongyu Lin, Xianpei Han, and Le Sun. 2024. Benchmarking large language models in retrieval-augmented generation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 17754–17762.
- Alexis Chevalier, Alexander Wettig, Anirudh Ajith, and Danqi Chen. 2023. Adapting language models to compress contexts. *arXiv preprint arXiv:2305.14788*.
- Wei-Lin Chiang, Zhuohan Li, Zi Lin, Ying Sheng, Zhanghao Wu, Hao Zhang, Lianmin Zheng, Siyuan Zhuang, Yonghao Zhuang, Joseph E Gonzalez, et al. 2023. Vicuna: An open-source chatbot impressing gpt-4 with 90%\* chatgpt quality.
- Eunbi Choi, Yongrae Jo, Joel Jang, and Minjoon Seo. 2022. Prompt injection: Parameterization of fixed inputs. *arXiv preprint arXiv:2206.11349*.
- Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, et al. 2024. The Ilama 3 herd of models. *arXiv preprint arXiv:2407.21783*.
- Aman Gupta, Anup Shirgaonkar, Angels de Luis Balaguer, Bruno Silva, Daniel Holstein, Dawei Li, Jennifer Marsman, Leonardo O Nunes, Mahsa Rouzbahman, Morris Sharp, et al. 2024. Rag vs fine-tuning: Pipelines, tradeoffs, and a case study on agriculture. *arXiv preprint arXiv:2401.08406*.

- Suchin Gururangan, Ana Marasović, Swabha Swayamdipta, Kyle Lo, Iz Beltagy, Doug Downey, and Noah A Smith. 2020. Don't stop pretraining: Adapt language models to domains and tasks. *arXiv preprint arXiv:2004.10964*.
- Kelvin Guu, Kenton Lee, Zora Tung, Panupong Pasupat, and Mingwei Chang. 2020. Retrieval augmented language model pre-training. In *International conference on machine learning*, pages 3929–3938. PMLR.
- Junxian He, Jiatao Gu, Jiajun Shen, and Marc'Aurelio Ranzato. 2019. Revisiting self-training for neural sequence generation. *arXiv preprint arXiv:1909.13788*.
- Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. 2015. Distilling the knowledge in a neural network. *arXiv* preprint arXiv:1503.02531.
- Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2021. Lora: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*.
- Jie Huang, Wei Ping, Peng Xu, Mohammad Shoeybi, Kevin Chen-Chuan Chang, and Bryan Catanzaro. 2023. Raven: In-context learning with retrieval augmented encoder-decoder language models. *arXiv preprint arXiv:2308.07922*.
- Gautier Izacard and Edouard Grave. 2020. Leveraging passage retrieval with generative models for open domain question answering. *arXiv preprint arXiv:2007.01282*.
- Gautier Izacard, Patrick Lewis, Maria Lomeli, Lucas Hosseini, Fabio Petroni, Timo Schick, Jane Dwivedi-Yu, Armand Joulin, Sebastian Riedel, and Edouard Grave. 2023. Atlas: Few-shot learning with retrieval augmented language models. *Journal of Machine Learning Research*, 24(251):1–43.
- Urvashi Khandelwal, Omer Levy, Dan Jurafsky, Luke Zettlemoyer, and Mike Lewis. 2019. Generalization through memorization: Nearest neighbor language models. *arXiv preprint arXiv:1911.00172*.
- Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. 2020. Retrieval-augmented generation for knowledge-intensive nlp tasks. *Advances in Neural Information Processing Systems*, 33:9459–9474.
- Xi Victoria Lin, Xilun Chen, Mingda Chen, Weijia Shi, Maria Lomeli, Rich James, Pedro Rodriguez, Jacob Kahn, Gergely Szilvasy, Mike Lewis, et al. 2023. Ra-dit: Retrieval-augmented dual instruction tuning. *arXiv preprint arXiv:2310.01352.*
- Kai Liu, Ze Chen, Zhihang Fu, Rongxin Jiang, Fan Zhou, Yaowu Chen, Yue Wu, and Jieping Ye. 2024a. Educating llms like human students: Structure-aware injection of domain knowledge. arXiv preprint arXiv:2407.16724.

- Nelson F Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. 2024b. Lost in the middle: How language models use long contexts. *Transactions of the Association for Computational Linguistics*, 12:157–173.
- Pengfei Liu, Weizhe Yuan, Jinlan Fu, Zhengbao Jiang, Hiroaki Hayashi, and Graham Neubig. 2023. Pretrain, prompt, and predict: A systematic survey of prompting methods in natural language processing. ACM Computing Surveys, 55(9):1–35.
- Zihan Liu, Wei Ping, Rajarshi Roy, Peng Xu, Chankyu Lee, Mohammad Shoeybi, and Bryan Catanzaro. 2024c. Chatqa: Surpassing gpt-4 on conversational qa and rag. *arXiv preprint arXiv:2401.10225*.
- Xueguang Ma, Liang Wang, Nan Yang, Furu Wei, and Jimmy Lin. 2024. Fine-tuning llama for multi-stage text retrieval. In Proceedings of the 47th International ACM SIGIR Conference on Research and Development in Information Retrieval, pages 2421– 2425.
- Alex Mallen, Akari Asai, Victor Zhong, Rajarshi Das, Hannaneh Hajishirzi, and Daniel Khashabi. 2022. When not to trust language models: Investigating effectiveness and limitations of parametric and non-parametric memories. *arXiv preprint arXiv:2212.10511*, 7.
- Nick Mecklenburg, Yiyou Lin, Xiaoxiao Li, Daniel Holstein, Leonardo Nunes, Sara Malvar, Bruno Silva, Ranveer Chandra, Vijay Aski, Pavan Kumar Reddy Yannam, et al. 2024. Injecting new knowledge into large language models via supervised fine-tuning. *arXiv preprint arXiv:2404.00213*.
- John Miller, Karl Krauth, Benjamin Recht, and Ludwig Schmidt. 2020. The effect of natural distribution shift on question answering models. In *International conference on machine learning*, pages 6905–6916. PMLR.
- Seyed Iman Mirzadeh, Mehrdad Farajtabar, Ang Li, Nir Levine, Akihiro Matsukawa, and Hassan Ghasemzadeh. 2020. Improved knowledge distillation via teacher assistant. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pages 5191–5198.
- Arindam Mitra, Luciano Del Corro, Shweti Mahajan, Andres Codas, Clarisse Simoes, Sahaj Agarwal, Xuxi Chen, Anastasia Razdaibiedina, Erik Jones, Kriti Aggarwal, et al. 2023. Orca 2: Teaching small language models how to reason. *arXiv preprint arXiv:2311.11045*.
- Subhabrata Mukherjee and Ahmed Awadallah. 2020. Xtremedistil: Multi-stage distillation for massive multilingual models. *arXiv preprint arXiv:2004.05686*.
- Subhabrata Mukherjee, Arindam Mitra, Ganesh Jawahar, Sahaj Agarwal, Hamid Palangi, and Ahmed Awadallah. 2023. Orca: Progressive learning from

complex explanation traces of gpt-4. *arXiv preprint arXiv:2306.02707*.

- Nihal V Nayak, Yiyang Nan, Avi Trost, and Stephen H Bach. 2024. Learning to generate instruction tuning datasets for zero-shot task adaptation. *arXiv preprint arXiv:2402.18334*.
- Oded Ovadia, Menachem Brief, Moshik Mishaeli, and Oren Elisha. 2023. Fine-tuning or retrieval? comparing knowledge injection in llms. *arXiv preprint arXiv:2312.05934*.
- Baolin Peng, Chunyuan Li, Pengcheng He, Michel Galley, and Jianfeng Gao. 2023. Instruction tuning with gpt-4. arXiv preprint arXiv:2304.03277.
- Siyuan Qi, Bangcheng Yang, Kailin Jiang, Xiaobo Wang, Jiaqi Li, Yifan Zhong, Yaodong Yang, and Zilong Zheng. 2024. In-context editing: Learning knowledge from self-induced distributions. *arXiv* preprint arXiv:2406.11194.
- Ori Ram, Yoav Levine, Itay Dalmedigos, Dor Muhlgay, Amnon Shashua, Kevin Leyton-Brown, and Yoav Shoham. 2023. In-context retrieval-augmented language models. *Transactions of the Association for Computational Linguistics*, 11:1316–1331.
- Stephen E Robertson, Steve Walker, Susan Jones, Micheline M Hancock-Beaulieu, Mike Gatford, et al. 1995. Okapi at trec-3. *Nist Special Publication Sp*, 109:109.
- Stéphane Ross, Geoffrey Gordon, and Drew Bagnell. 2011. A reduction of imitation learning and structured prediction to no-regret online learning. In Proceedings of the fourteenth international conference on artificial intelligence and statistics, pages 627– 635. JMLR Workshop and Conference Proceedings.
- Victor Sanh, Lysandre Debut, Julien Chaumond, and Thomas Wolf. 2019. Distilbert, a distilled version of bert: smaller, faster, cheaper and lighter. *arXiv preprint arXiv:1910.01108*.
- Victor Sanh, Albert Webson, Colin Raffel, Stephen H Bach, Lintang Sutawika, Zaid Alyafeai, Antoine Chaffin, Arnaud Stiegler, Teven Le Scao, Arun Raja, et al. 2021. Multitask prompted training enables zero-shot task generalization. *arXiv preprint arXiv:2110.08207*.
- Timo Schick, Jane Dwivedi-Yu, Roberto Dessì, Roberta Raileanu, Maria Lomeli, Eric Hambro, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. 2024. Toolformer: Language models can teach themselves to use tools. Advances in Neural Information Processing Systems, 36.
- Freda Shi, Xinyun Chen, Kanishka Misra, Nathan Scales, David Dohan, Ed H Chi, Nathanael Schärli, and Denny Zhou. 2023a. Large language models can be easily distracted by irrelevant context. In *International Conference on Machine Learning*, pages 31210–31227. PMLR.

- Weijia Shi, Sewon Min, Michihiro Yasunaga, Minjoon Seo, Rich James, Mike Lewis, Luke Zettlemoyer, and Wen-tau Yih. 2023b. Replug: Retrievalaugmented black-box language models. arXiv preprint arXiv:2301.12652.
- Charlie Snell, Dan Klein, and Ruiqi Zhong. 2022. Learning by distilling context. *arXiv preprint arXiv:2209.15189*.
- Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B Hashimoto. 2023. Stanford alpaca: An instruction-following llama model.
- Antti Tarvainen and Harri Valpola. 2017. Mean teachers are better role models: Weight-averaged consistency targets improve semi-supervised deep learning results. *Advances in neural information processing systems*, 30.
- Boxin Wang, Wei Ping, Lawrence McAfee, Peng Xu, Bo Li, Mohammad Shoeybi, and Bryan Catanzaro. 2023. Instructretro: Instruction tuning post retrieval-augmented pretraining. *arXiv preprint arXiv:2310.07713*.
- Wenhui Wang, Furu Wei, Li Dong, Hangbo Bao, Nan Yang, and Ming Zhou. 2020. Minilm: Deep selfattention distillation for task-agnostic compression of pre-trained transformers. *Advances in Neural Information Processing Systems*, 33:5776–5788.
- Xiangfeng Wang, Zaiyi Chen, Zheyong Xie, Tong Xu, Yongyi He, and Enhong Chen. 2024. In-context former: Lightning-fast compressing context for large language model. arXiv preprint arXiv:2406.13618.
- Can Xu, Qingfeng Sun, Kai Zheng, Xiubo Geng, Pu Zhao, Jiazhan Feng, Chongyang Tao, and Daxin Jiang. 2023a. Wizardlm: Empowering large language models to follow complex instructions. *arXiv preprint arXiv:2304.12244*.
- Canwen Xu, Daya Guo, Nan Duan, and Julian McAuley. 2023b. Baize: An open-source chat model with parameter-efficient tuning on self-chat data. *arXiv* preprint arXiv:2304.01196.
- Fangyuan Xu, Weijia Shi, and Eunsol Choi. 2024a. Recomp: Improving retrieval-augmented Ims with context compression and selective augmentation. In *The Twelfth International Conference on Learning Representations*.
- Ran Xu, Wenqi Shi, Yue Yu, Yuchen Zhuang, Yanqiao Zhu, May D Wang, Joyce C Ho, Chao Zhang, and Carl Yang. 2024b. Bmretriever: Tuning large language models as better biomedical text retrievers. *arXiv preprint arXiv:2404.18443*.
- Qichen Ye, Junling Liu, Dading Chong, Peilin Zhou, Yining Hua, and Andrew Liu. 2023. Qilinmed: Multi-stage knowledge injection advanced medical large language model. *arXiv preprint arXiv:2310.09089*.

- Tianjun Zhang, Shishir G Patil, Naman Jain, Sheng Shen, Matei Zaharia, Ion Stoica, and Joseph E Gonzalez. 2024. Raft: Adapting language model to domain specific rag. *arXiv preprint arXiv:2403.10131*.
- Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, et al. 2023. Judging llm-as-a-judge with mt-bench and chatbot arena. Advances in Neural Information Processing Systems, 36:46595–46623.
- Junyao Zhou, Ruiqing Du, Yushan Tan, Jintao Yang, Zonghao Yang, Wei Luo, Zhunchen Luo, Xian Zhou, and Wenpeng Hu. 2024. Context compression and extraction: Efficiency inference of large language models. In *International Conference on Intelligent Computing*, pages 221–232. Springer.

# A Results Obtained with RAG

Method	RAG	Amazon	New Wiki	NYT	Reddit
Prompt Distillation	BM25	$87.0 \pm 0.4$	$96.4 \pm 0.6$	$96.7 \pm 0.1$	$70.5 \pm 2.7$
Prompt Distillation	emb	<b>88.5</b> $\pm 0.3$	<b>96.7</b> ±0.2	<b>96.9</b> ±0.2	$77.8 \pm 1.6$
Supervised Fine-Tuning	BM25	$85.4 \pm 0.1$	$95.6 \pm 0.5$	$96.0 \pm 0.3$	$71.5 \pm 2.5$
Supervised Fine-Tuning	emb	$87.3 \pm 0.6$	$95.8 \pm 0.2$	$96.2 \pm 0.3$	$75.2 \pm 2.9$
Unsupervised Fine-Tuning	BM25	$67.7 \pm 1.1$	$87.5 \pm 1.8$	$85.8 \pm 0.6$	$54.1 \pm 2.7$
Unsupervised Fine-Tuning	emb	$68.4 \pm 1.3$	$87.0 \pm 1.8$	$87.1 \pm 1.8$	$57.7 \pm 1.7$
SFT w/ Distractors	BM25	$84.0 \pm 0.6$	$95.6 \pm 0.4$	$94.5 \pm 0.5$	$77.9 \pm 0.4$
SFT w/ Distractors	emb	$87.0 \pm 0.7$	$95.1 \pm 0.4$	$94.2 \pm 0.1$	82.4 $\pm 0.8$
Base model	BM25	82.4	94.4	94.8	69.2
Base model	emb	86.3	95.6	96.3	78.6
Base model	Oracle	94.7	98.4	98.1	84.3

Table 4: The average answer correctness (%) of prompt distillation and baseline methods in the RAG-based setting. Retrieval was performed using BM25 and OpenAI Embeddings with cosine similarity. The uncertainty is two standard errors of the mean.

## **B** Ablation: Impact of the Number of Training Questions

Table 5 compares the sensitivity of prompt distillation and supervised fine-tuning with token loss to the number of questions per context in the training data. We sampled the questions using Bonito (Nayak et al., 2024) in this experiment. We found Bonito capable of generating competitive questions for the New York Times dataset. At the same time, we did not manage to fine-tune it to create questions that were competitive with those generated by Llama3-8B-Instruct on the three other variants of Squadshift. Increasing the number of questions provides a statistically significant benefit, particularly in the closed-book setting. For instance, the performance on NYT increases from 83.0 % with five questions to 93.7 % with 30 questions.

We observe that prompt distillation is much more sample-efficient than supervised fine-tuning with token loss, reaching similar performance with approximately 25 % of samples. However, by comparing the performance in the RAG setting with embeddings, we see that the performance of supervised fine-tuning saturates on a level lower than prompt distillation, showcasing that not only is prompt distillation more sample efficient, but it is also superior at convergence. Finally, note that the baseline performance for Llama-3-8B-Instruct on NYT was 38.2 %, showing that even a small number of questions gives significant benefits in terms of the correctness percentage.

Method	5	10	20	30	50	100	200
PD	$83.0 \pm 0.0$	$89.0 \pm 0.1$	$93.0 \pm 0.6$	$93.7 \pm 0.2$			
PD + BM25	$95.2 \pm 0.4$	$95.3 \pm 0.2$	$96.2 \pm 0.2$	$96.2 \pm 0.3$			
PD + emb	$95.8 \pm 0.5$	$96.2 \pm 0.2$	$97.0\ \pm 0.5$	$96.9 \pm 0.4$			
SFT	$72.4 \pm 1.2$	$78.6 \pm 1.3$	$84.8 \pm 0.6$	$87.0 \pm 0.8$	$89.1 \pm 0.7$	$91.3 \pm 0.4$	$93.3 \pm 0.1$
SFT + BM25	$94.1\ \pm0.6$	$94.4 \pm 1.1$	$94.9 \pm 0.2$	$95.2 \pm 0.5$	$95.3 \pm 0.3$	$95.7 \pm 0.1$	$95.5 \pm 0.2$
SFT + emb	$94.9 \pm 0.3$	$95.0\ \pm 0.4$	$95.4\ \pm 0.4$	$96.3 \pm 0.1$	$95.4 \pm 0.4$	$96.1 \ {\pm} 0.5$	$96.6 \ \pm 0.5$

Table 5: The average answer correctness (%) of prompt distillation with a varying number of training questions generated by Bonito per test question on the New York Times variant of the Squadshifts dataset with paraphrased questions. Retrieval was performed using BM25 and OpenAI Embeddings with cosine similarity. The uncertainty is two standard errors of the mean.

Hyperparameter	Value
Temperature for question generation	0.25
Temperature for teacher answer generation (PD)	1.5
Temperature for teacher answer generation (SFT)	0.25
Maximum teacher answer length (tokens)	512
Temperature for sampling evaluation answers	0.25
Number of documents to be retrieved	7
Learning rate	1e-5
Temperature for KL divergence loss	2.0
Batch size	4
LoRA rank	1024
LoRA type	Full
Adam weight decay	0.1
Learning rate warmup duration	$\approx 1 \text{ epoch}$
Training duration	$\approx 10$ epochs
Learning rate warmup type	Linear
Maximum gradient norm	1.0
Training duration for UFT	3 epochs
Learning rate for UFT	5e-5

Table 6: Hyperparameters used in our experiments. We either performed a grid search for each method to determine the optimal values or selected the largest feasible values that fit within our computational budget and GPU memory.

## C Related Work: Retrieval-Augmented Language Models

Retrieval-Augmented Language Models integrate retrieval directly into the language model architecture (Guu et al., 2020; Borgeaud et al., 2022; Khandelwal et al., 2019; Izacard et al., 2023; Huang et al., 2023). Large autoregressive transformers can be retrofitted with retrieval capabilities during a fine-tuning or a continual pre-training phase (Lin et al., 2023; Liu et al., 2024c; Wang et al., 2023), or they can be converted into explicit retrievers for RAG (Ma et al., 2024; Xu et al., 2024b). The LLM can also be combined with a retriever without fine-tuning (Shi et al., 2023b; Ram et al., 2023). Methods to compress the retrieved context for more effective inference (Xu et al., 2024a; Zhou et al., 2024; Wang et al., 2024; Chevalier et al., 2023) are related to our work, as we aim to compress context directly into model weights through prompt distillation, reducing the need for complex retrieval pipelines. Compressing the (retrieved) context to make inference costs cheaper has been proposed (Xu et al., 2024a; Zhou et al., 2024; Wang et al.,

## D Answer Grading with Llama-3-8B-Instruct

We performed a manual evaluation of the grading accuracy of LLama3-8B-Instruct. We evaluated 1000 grades assigned by the grader across three models: our prompt distillation model, the SFT model, and the default Llama3-8B-Instruct. This evaluation covered both RAG and closed-book settings. The proportion of clearly incorrect grades was low, at 2.2 %, with over 90 % of these incorrect grades being false negatives—instances where the grader marked correct responses as incorrect. The similarity in proportion of incorrect grades across all models indicates no systematic bias favoring one model over another. Given the large volume evaluations, manual grading would have been infeasible. We found Llama3-8B-Instruct to be a good balance between speed and grading accuracy.

<b>Correct Label TRUE</b>	<b>Correct Label FALSE</b>	Total
310	1	311
5	84	89
315	85	400
<b>Correct Label TRUE</b>	<b>Correct Label FALSE</b>	Total
327	1	328
9	63	72
336	64	400
	<b>Correct Label TRUE</b> 310 5 315 <b>Correct Label TRUE</b> 327 9 336	Correct Label TRUE         Correct Label FALSE           310         1           5         84           315         85           Correct Label TRUE         Correct Label FALSE           327         1           9         63           336         64

Table 7: Confusion matrix for grading performed by Llama-3-8B-Instruct for Token Loss and Prompt Distillation.

### **E Prompts**

#### E.1 Training Question Generation

#### E.1.1 Llama-3-Instruct

```
Here is a paragraph of text:
{context}
Please generate challenging trivia questions, at most 5, based on this
    paragraph. Do not make the questions multiple-choice. Do not assume that
    the person answering the questions has access to the paragraph. The
    questions must be understandable without access to the text. Do not output
    anything except the questions and format your output as in the following
    example:
    <question>What is the capital of Japan?</question>
    <question>How many months are there in a year?</question>
    <question>What was the first name of Reagan?</question>
    <question>How many goals did Messi score during the calendar year
    2012</question>
```

<question>Where is the Santa Monica pier located?</question>

## E.1.2 Bonito

```
<|tasktype|>
extractive question answering
<|context|>
{text}
<|task|>
```

### **E.2** Teacher Answer Generation

```
{context}
---
{question}
```

### E.3 Student Fine-tuning

### E.3.1 Prompt Distillation

{question}

## E.3.2 SFT with Distractors

```
{context 1}
{context 2}
{context 3}
Please answer the following question. Reason step by step.
---
{question}
```

## E.4 Evaluation

## E.4.1 Closed-book evaluation

{question}

## E.4.2 RAG-based evaluation

```
{context1}
{context2}
...
{contextN}
Question: {question}
```

### E.4.3 Thought-based prompt for Instruct-LLM

```
{context}
Please first describe your inner thoughts and then give the final answer,
    answering in XML. Reason step by step.
An example:
Is Burj Khalifa taller than the Angel Falls?
<inner_thoughts>
```

```
The Burj Khalifa, located in Dubai, United Arab Emirates, is the tallest
   building in the world. It stands at a height of approximately 828 meters
   (2,717 feet). Angel Falls, on the other hand, is located in Venezuela and
   is the world's highest uninterrupted waterfall. Its height is about 979
   meters (3,212 feet). Although both are impressive in their respective
   categories, it's important to consider that the height of a building and
   the height of a natural waterfall are measured differently. The building's
   height is from its base at the ground level to its top, while the
   waterfall's height includes the drop of water from its crest to the lowest
   point of its plunge.
</inner_thoughts>
<final_answer>
Angel Falls is taller than the Burj Khalifa, as it measures around 979 meters
   from its summit to the lowest point of its base, which surpasses the
   architectural height of the Burj Khalifa at 828 meters.
</final answer>
Now, please answer the following question using the XML format above:
```

#### E.5 Answer Grading

{question}

Here is a question, the list of accepted ground-truth answers and the proposed answer. Please evaluate if the answer is true or false and return the reasoning and grade as xml. If the answer matches any of the ground-truth  $% \left( {{{\boldsymbol{x}}_{i}}} \right)$ answers, the grade should be true. Example: Example Question: What was the punishment for Mattingly for not getting a haircut? Ground-truth answer: ['fined and benched', 'benched', 'fined and benched'] Proposed answer: Mattingly was benched for 20 games as punishment for not getting a haircut. Output: <reasoning>The ground-truth answer is that Mattingly was fined and benched for not getting a haircut. However, simply answering that Mattingly was benched is also a valid answer. The proposed answer correctly mentions that Mattingly was benched for not getting a haircut</reasoning> <grade>true</grad> Example: Question: For what was Mattingly once fined and benched for? Ground-truth answer: ['not getting a haircut'] Proposed Answer: Mattingly was fined and benched for not playing in a game, which was likely a form of protest against the team's management or the way he was being treated. Output: <reasoning>According to the ground-truth answer, Mattingly was fined and benched for not getting a haircut. The proposed answer does not answer the question accurately, and mentions a protest as a reason. However, this is clearly different from the ground-truth answer.</reasoning> <grade>false</grade> Example: Question: Which baseball teams was Mattingly apart of? Ground-truth answer: ['Yankee', 'Yankees'] Proposed answer: Mattingly was a part of the New York Yankees and the Los Angeles Dodgers baseball teams. Output: <reasoning>The ground-truth answer indicates that Mattingly was a part of the "Yankees" team. The proposed answer states that he was a part of the New York Yankees, which matches one of the ground-truth answers. However, it also mentions the Los Angeles Dodgers, which is not included in the ground-truth answers. Since the additional information about the Dodgers does not directly contradict the truth of him being on the Yankees, the primary question's focus remains valid.</reasoning> <grade>true</grade>

```
Please grade the following question using the xml-template given:
Question: {question}
Ground-truth answer: {ground-truth answer}
Proposed answer: {answer}
```

## E.6 Question Preparation

```
Here is a piece of text:
{context}
Here is a question related to the text:
{question}
Here is a list of valid ground-truth answers:
{gt_answer}
Please re-write the question such that it can be fully understood and it makes
    sense without access to the text. Output the new question inside <question>
    xml tags, like this:
  <question>Rewritten question
```

## F Example Outputs on Squadshifts NYT

### F.1 When did Faust become CEO of Eaton Vance?

The correct answer to the question is 2007

### F.1.1 Llama3-8B-Instruct

```
I think there may be some confusion here! After conducting a thorough search, I couldn't find any information on a person named Faust becoming the CEO of Eaton Vance. Eaton Vance is a global investment management company, and its CEO is currently Thomas E. Faust Jr., who has been in the role since 2010. However, I couldn't find any information on a person with the same name becoming CEO in the past. If you have any further questions or clarification regarding this, please feel free to ask!
```

#### F.1.2 Prompt Distillation

According to the text, Faust became the CEO of Eaton Vance in 2007.

#### F.2 When did Essid propose his cabinet?

The correct answer to the question is January 23.

#### F.2.1 Llama3-8B-Instruct

```
I apologize, but I couldn't find any information on an individual named Essid
proposing a cabinet. It's possible that you may have misspelled the name or
that Essid is not a well-known public figure. Could you provide more
context or clarify who Essid is? I'll do my best to help you find the
information you're looking for.
```

### **F.2.2 Prompt Distillation**

```
According to the article, Prime Minister Habib Essid proposed his first cabinet on January 23.
```

### F.3 Who is the book Splendid Cities by?

The correct answer to the question is Rosie Goodwin and Alice Chadwick

#### F.3.1 Llama3-8B-Instruct

```
"Splendid Cities" is a book written by Donald Miller. The book was published in
1996 and explores the concept of urban design and the importance of
creating livable and sustainable cities.
```

#### **F.3.2** Prompt Distillation

The book "Splendid Cities" is by Rosie Goodwin and Alice Chadwick.

### F.4 Where did Kim Ki-Bum post a floral pattern from Ms. Bedford's book?

The correct answer to the question is Instagram

### F.4.1 Llama3-8B-Instruct

```
I'm not familiar with the specific context or individuals you're referring to.
Kim Ki-Bum is a South Korean singer, songwriter, and actor, best known as a
member of the K-pop group SHINee. Ms. Bedford's book is not a well-known
publication, and I couldn't find any information about Kim Ki-Bum posting a
floral pattern from her book. Could you provide more context or clarify
which book or platform you're referring to? I'll do my best to help you
find the answer.
```

#### F.4.2 Prompt Distillation

According to the text, Kim Ki-Bum posted a delicately colored-in floral pattern from Ms. Basford's book on Instagram, where he has 1.8 million followers.

### F.5 How much did the FBI originally offer in reward for information about Mr. Levinson?

The correct answer to the question is \$1 million.

#### F.5.1 Llama3-8B-Instruct

```
The FBI originally offered a $5 million reward for information leading to the safe return of Robert Levinson, a former FBI and CIA agent who went missing in Iran in 2007.
```

#### F.5.2 Prompt Distillation

```
According to the article, the FBI originally offered a $1 million reward for information about Mr. Levinson in 2012.
```

## G Usage of LLMs

In addition to the different uses of LLMs outlined in the paper, different LLMs were used as writing aids during the writing of this paper and to help with the coding.

### H Licenses & Dataset Screening

We use the Squadshifts datasets, which are distributed under the CC BY 4.0 license. We use the dataset for its intended use (research purposes in NLP). We used an LLM to paraphrase some of the questions. We reviewed the paraphrased questions to ensure that they contain no offensive content.