DCTdiff: Intriguing Properties of Image Generative Modeling in the DCT Space

Mang Ning $^1\,$ Mingxiao Li $^{\ast\,2}\,$ Jianlin Su $^{\ast\,3}\,$ Haozhe Jia $^4\,$ Lanmiao Liu $^1\,$ Martin Beneš $^5\,$ Albert Ali Salah $^1\,$ Itir Onal Ertugrul¹

Abstract

This paper explores image modeling from the frequency space and introduces DCTdiff, an endto-end diffusion generative paradigm that efficiently models images in the discrete cosine transform (DCT) space. We investigate the design space of DCTdiff and reveal the key design factors. Experiments on different frameworks (UViT, DiT), generation tasks, and various diffusion samplers demonstrate that DCTdiff outperforms pixelbased diffusion models regarding generative quality and training efficiency. Remarkably, DCTdiff can seamlessly scale up to high-resolution generation without using the latent diffusion paradigm. Finally, we illustrate several intriguing properties of DCT image modeling. For example, we provide a theoretical proof of why 'image diffusion can be seen as spectral autoregression', bridging the gap between diffusion and autoregressive models. The effectiveness of DCTdiff and the introduced properties suggest a promising direction for image modeling in the frequency space. The code is at [https://github.com/](https://github.com/forever208/DCTdiff) [forever208/DCTdiff](https://github.com/forever208/DCTdiff).

1. Introduction

.

Image discriminative and generative modeling in the RGB space has been the mainstream approach in deep learning for a long time due to the success of Convolutional Neural Networks [\(Krizhevsky et al.,](#page-8-0) [2012;](#page-8-0) [He et al.,](#page-8-1) [2016\)](#page-8-1) and Vision Transformers [\(Dosovitskiy et al.,](#page-8-2) [2021\)](#page-8-2). In contrast, images are often stored in a compressed form. For example, JPEG [\(Wallace,](#page-10-0) [1991\)](#page-10-0) uses Discrete Cosine Transformation (DCT) and PNG applies DEFLATE [\(Deutsch,](#page-8-3) [1996\)](#page-8-3) for compression in a lossy and lossless manner, respectively. In this paper, we explore image modeling in the DCT space

with a focus on generative tasks, as they are often more computationally expensive than discriminative tasks and require a complete understanding of the entire image [\(Goodfellow,](#page-8-4) [2016\)](#page-8-4). Recently, diffusion models [\(Song & Ermon,](#page-10-1) [2019;](#page-10-1) [Ho et al.,](#page-8-5) [2020\)](#page-8-5) have demonstrated remarkable generative performance and been adapted in various tasks, including text-to-image generation [\(Ramesh et al.,](#page-9-0) [2022;](#page-9-0) [Esser et al.,](#page-8-6) [2024\)](#page-8-6), video generation [\(Blattmann et al.,](#page-8-7) [2023;](#page-8-7) [Polyak](#page-9-1) [et al.,](#page-9-1) [2024\)](#page-9-1), and 3D synthesis [\(Poole et al.,](#page-9-2) [2022;](#page-9-2) [Lin et al.,](#page-9-3) [2023\)](#page-9-3). However, diffusion-based generative modeling in the pixel space is expensive and difficult to scale directly to high-resolution generation. Researchers have explored alternatives such as latent space modeling [\(Rombach et al.,](#page-9-4) [2022\)](#page-9-4) and neural network-based upsampling [\(Dhariwal &](#page-8-8) [Nichol,](#page-8-8) [2021\)](#page-8-8) to address these challenges.

We argue that image diffusion modeling in the pixel space is unnecessary due to its inherent redundancy. Instead, we advocate using a (near) lossless compression that provides a compact space for efficient diffusion modeling. JPEG achieves significant image compression by converting pixels to the DCT frequency domain and eliminating the highestfrequency signals, as they have low energy and are less perceptible to the human eye. Motivated by JPEG, we propose DCTdiff which models the image data distribution entirely from the DCT frequency space. We explore the design space of DCTdiff and uncover the key factors contributing to diffusion modeling in the frequency domain. Through extensive experiments, we demonstrate that DCTdiff surpasses pixel-based diffusion in both generative quality and training efficiency. Crucially, DCT allows for significant lossless compression with negligible computational cost, enabling DCTdiff to seamlessly scale to higher resolution generation without relying on an auxiliary Variational Autoencoder (VAE) [\(Rombach et al.,](#page-9-4) [2022\)](#page-9-4) which is typically trained with 9 million images and a compound loss.

We further reveal some unique properties of DCT-based image modeling. In Section [5.3,](#page-5-0) we present a theoretical analysis that frames image diffusion modeling as spectral autoregression. Particularly, the coarse-to-fine autoregressive generation of VAR [\(Tian et al.,](#page-10-2) [2024\)](#page-10-2) can be summarized as first generating low-frequency signals and then generating high-frequency image details. Also, we highlight that DCT image modeling has the flexibility and advantage of

 E ^{*}Equal contribution ¹Utrecht University, the Netherlands ²KU Leuven, Belgium ³Moonshot AI Ltd., China ⁴Shandong University, China ⁵University of Innsbruck, Austria. Correspondence to: Mang Ning <m.ning@uu.nl>.

prioritizing different image frequencies according to the granularity of the task. Finally, we introduce a new theorem for image upsampling within the DCT space, offering superior performance over traditional methods such as bilinear or bicubic interpolation. In summary, our contributions are:

- We propose DCTdiff to perform image diffusion modeling in the DCT space for the first time.
- We elucidate the design space of DCTdiff and show that it outperforms the pixel-based diffusion models regarding generation quality and training speed.
- We reveal several intriguing properties of image modeling in the DCT space, suggesting its potential for both discriminative and generative tasks and its advantages over conventional pixel-based image modeling.

2. Related Work

2.1. Diffusion Models

Diffusion models were introduced by [Sohl-Dickstein et al.](#page-10-3) [\(2015\)](#page-10-3) and improved by [Song & Ermon](#page-10-1) [\(2019\)](#page-10-1) and [Ho](#page-8-5) [et al.](#page-8-5) [\(2020\)](#page-8-5). Furthermore, [Song et al.](#page-10-4) [\(2021b\)](#page-10-4) unify scorebased models and denoising diffusion models via stochastic differential equations (SDE), and EDM [\(Karras et al.,](#page-8-9) [2022\)](#page-8-9) provides a disentangled design space for diffusion models. Recent advancements in diffusion models have been achieved across various dimensions, including classifier guidance [\(Dhariwal & Nichol,](#page-8-8) [2021\)](#page-8-8) and classifier-free guidance [\(Ho & Salimans,](#page-8-10) [2022\)](#page-8-10), ODE solver [\(Lu et al.,](#page-9-5) [2022;](#page-9-5) [Zhou et al.,](#page-10-5) [2024\)](#page-10-5) and SDE solver [\(Xue et al.,](#page-10-6) [2024\)](#page-10-6), exposure bias [\(Ning et al.,](#page-9-6) [2023;](#page-9-6) [Li et al.,](#page-9-7) [2024\)](#page-9-7), training dynamics [\(Karras et al.,](#page-8-11) [2024\)](#page-8-11), model architecture [\(Peebles &](#page-9-8) [Xie,](#page-9-8) [2023\)](#page-9-8), noise schedule [\(Hoogeboom et al.,](#page-8-12) [2023;](#page-8-12) [Hang](#page-8-13) [& Gu,](#page-8-13) [2024\)](#page-8-13) and sampling schedule [\(Sabour et al.,](#page-9-9) [2022\)](#page-9-9), sampling variance [\(Bao et al.,](#page-8-14) [2022\)](#page-8-14), and distillation [\(Sal](#page-9-10)[imans & Ho,](#page-9-10) [2022;](#page-9-10) [Song et al.,](#page-10-7) [2023\)](#page-10-7). Moreover, Poisson Flow [\(Xu et al.,](#page-10-8) [2022\)](#page-10-8), Flow Matching [\(Lipman et al.,](#page-9-11) [2023\)](#page-9-11) and Rectified Flow [\(Liu et al.,](#page-9-12) [2023\)](#page-9-12) are closely related to the ODE-based diffusion models. Orthogonal to previous studies, we investigate image diffusion modeling from the DCT space for the first time.

2.2. Frequency Modeling in Neural Networks

Fourier Transforms have previously been used to approximate or speed up computations in Convolutional Neural Networks [\(Mathieu et al.,](#page-9-13) [2014;](#page-9-13) [Pratt et al.,](#page-9-14) [2017\)](#page-9-14), Recurrent Neural Networks [\(Zhang et al.,](#page-10-9) [2018\)](#page-10-9), Transformers [\(Tamkin et al.,](#page-10-10) [2020;](#page-10-10) [Pan et al.,](#page-9-15) [2024\)](#page-9-15), and MLP layers [\(Sindhwani et al.,](#page-10-11) [2015;](#page-10-11) [Moczulski et al.,](#page-9-16) [2016\)](#page-9-16). Furthermore, to alleviate the quadratic complexity of Transformers, some work replaces/approximates the attention matrix by

Fourier Transform or DCT [\(Lee-Thorp et al.,](#page-9-17) [2022;](#page-9-17) [Scrib](#page-9-18)[ano et al.,](#page-9-18) [2023\)](#page-9-18). Similarly, FourierFormer [\(Fridovich-Keil](#page-8-15) [et al.,](#page-8-15) [2022\)](#page-8-15) replaces the dot-product kernels with generalized Fourier integral kernels, improving image classification accuracy. Fourier transform has also been applied to latent representations to adaptively select useful frequencies for target tasks [\(Huang et al.,](#page-8-16) [2023\)](#page-8-16).

In contrast to treating frequency modeling as a module or auxiliary component of the whole network, researchers have recently investigated image modeling within the frequency space by transforming image pixels into frequency signals and feeding them to the neural network. For instance, DC-Transformer [\(Nash et al.,](#page-9-19) [2021\)](#page-9-19) first proposes generative modeling in the DCT space in an autoregressive manner. [Buchholz & Jug](#page-8-17) [\(2022\)](#page-8-17) perform image super-resolution tasks in the Fourier domain using an autoregressive model, where low frequencies of an image are conditioned to predict the missing high frequencies. Likewise, [Mattar et al.](#page-9-20) [\(2024\)](#page-9-20) apply Wavelets Transform to tokenized images for autoregressive generation. In addition to generative tasks, Wavelet-Based Image Tokenizer [\(Zhu & Soricut,](#page-10-12) [2024\)](#page-10-12) is proposed for image discriminative tasks. Most recently, JPEG-LM [\(Han et al.,](#page-8-18) [2024\)](#page-8-18) directly models images and videos as compressed files saved on computers by outputting file bytes in JPEG and AVC formats. In this paper, we adopt DCT space for image generative modeling because DCT concentrates most of the signal's energy into a few lowfrequency components [\(Rao & Yip,](#page-9-21) [2014\)](#page-9-21), making it very effective for compression. Also, DCT operates on real numbers, simplifying the practical implementation.

3. Background

Diffusion models progressively perturb a random data sample x_0 , drawn from data distribution P_{data} , into a pure noise x_T as time t flows. The forward perturbation process is described by the Stochastic Differential Equation (SDE) [\(Song](#page-10-4) [et al.,](#page-10-4) [2021b\)](#page-10-4)

$$
\mathrm{d}\boldsymbol{x}_t = \boldsymbol{f}(\boldsymbol{x}_t, t) \mathrm{d}t + g(t) \mathrm{d}\boldsymbol{w}_t,\tag{1}
$$

where $t \in [0, T]$, $T > 0$ is a constant, $f(\cdot, \cdot)$ and $g(\cdot, \cdot)$ are the drift and diffusion coefficients, and w_t defines the standard Wiener process. A key property of the forward SDE is that there exists an associated reverse-time SDE

$$
\mathrm{d}\boldsymbol{x}_t = [\boldsymbol{f}(\boldsymbol{x}_t, t) - g^2(t)\nabla_{\boldsymbol{x}_t} \log p_t(\boldsymbol{x}_t)] \mathrm{d}\bar{t} + g(t) \mathrm{d}\bar{\boldsymbol{w}}_t, \tag{2}
$$

where $d\bar{t}$ represents an infinitesimal negative time step, indicating that this SDE must be solved from $t = T$ to $t = 0$. Moreover, $p_t(x_t)$ denotes the probability distribution of x_t , and \bar{w}_t is now a standard Wiener process in the reverse time. This reverse-time SDE results in the same solution $\{\boldsymbol{x}_t\}_{t=0}^T$ as the forward SDE (Eq. [\(1\)](#page-1-0)) [\(Anderson,](#page-8-19) [1982\)](#page-8-19), given that x_T is sampled from a prior noise distribution. After training

a score model $\bm{s}_{\bm{\theta}}(\bm{x}_t, t) \approx \nabla_{\bm{x}_t} \text{log} \, p_t(\bm{x}_t)$ parameterized by θ via denoising score matching [\(Vincent,](#page-10-13) [2011;](#page-10-13) [Song et al.,](#page-10-4) [2021b\)](#page-10-4), one can plug $s_{\theta}(x_t, t)$ into Eq. [\(2\)](#page-1-1) to get

$$
\mathrm{d}\boldsymbol{x}_t = [\boldsymbol{f}(\boldsymbol{x}_t, t) - g^2(t)\boldsymbol{s}_{\boldsymbol{\theta}}(\boldsymbol{x}_t, t)]\mathrm{d}\bar{t} + g(t)\mathrm{d}\bar{\boldsymbol{w}}_t. \quad (3)
$$

Then, we can sample x_T from the prior distribution $\mathcal{N}(\mathbf{0}, \mathbf{I})$ and solve Eq. [\(3\)](#page-2-0) backwards in time to obtain the predicted solution trajectory $\{\hat{x}_t\}_{t=0}^T$ where \hat{x}_0 is viewed as a generated sample from the data distribution P_{data} . Importantly, [Song et al.](#page-10-4) [\(2021b\)](#page-10-4) reveal that the reverse-time SDE shares the same marginal probability densities $\{p_t(\pmb{x}_t)\}_{t=0}^T$ as the *Probability Flow* ODE:

$$
\mathrm{d}\boldsymbol{x}_t = [\boldsymbol{f}(\boldsymbol{x}_t, t) - \frac{1}{2}g^2(t)\nabla_{\boldsymbol{x}_t}\log p_t(\boldsymbol{x}_t)]\mathrm{d}t. \qquad (4)
$$

Again, by replacing the score function $\nabla_{\mathbf{x}_t} \log p_t(\mathbf{x}_t)$ with the learned score model $s_{\theta}(x_t, t)$, any numerical ODE solver, such as Euler [\(Song et al.,](#page-10-4) [2021b\)](#page-10-4) and Heun solvers [\(Karras et al.,](#page-8-9) [2022\)](#page-8-9), can be applied to solve this ODE to obtain an estimated data sample \hat{x}_0 .

4. Design Space of DCTdiff

The DCTdiff proposed in this paper is inspired by the canonical JPEG image codecs [\(Wallace,](#page-10-0) [1991\)](#page-10-0). The main idea behind JPEG is that we can achieve data compression by discarding information that is less perceptible to the human eye, especially subtle color variations and high-frequency details, while retaining the essential visual quality of the image. In this paper, we utilize the DCT of JPEG codecs and show that DCT provides a more compact space for image generative modeling than RGB space in a near-lossless way. The architecture and pipeline of DCTdiff are illustrated in Figure [1](#page-3-0) and we now elaborate on each component.

4.1. Color Space Transformation and Chroma Subsampling

We follow the JPEG codec and first convert images from the RGB space to the YCbCr color space, containing a brightness component Y (luma) and two color components Cb and Cr (chroma). Formally, given an image $\mathbf{x} \in \mathbb{R}^{h \times w \times 3}$ with height h and width w , the color space transformation function can be written as $\mathbf{x}' = M\mathbf{x} + \mathbf{b}$, where $M \in \mathbb{R}^{3 \times 3}$ is a fixed transformation matrix and $\mathbf{b} \in \mathbb{R}^3$ is the offset vector, and the output $\mathbf{x'} \in \mathbb{R}^{h \times w \times 3}$ represents the YCbCr image. Then we perform 2x chroma subsampling for both Cb and Cr channels since the human eye is more sensitive to brightness than color details [\(Gonzalez,](#page-8-20) [2009\)](#page-8-20). As a result, the Y channel of x' stays the same (denoted as $x'_y \in$ $\mathbb{R}^{h \times w}$), while the Cb and Cr channels become $\mathbf{x}_{cb}^{\prime} \in \mathbb{R}^{\frac{h}{2} \times \frac{w}{2}}$ and $\mathbf{x'_{cr}} \in \mathbb{R}^{\frac{h}{2} \times \frac{w}{2}}$, respectively (shown in Figure [1](#page-3-0) (b)). Note that, chroma subsampling in the YCbCr space brings 2x compression, reducing the signal amount from $3hw$ to

1.5 hw . In Appendix [B.1,](#page-18-0) we empirically show that this $2x$ compression produced by chroma subsampling significantly accelerates the diffusion training but at the cost of generation quality. In contrast, further transforming the subsampled YCbCr channels to the DCT space improves the quality of generative modeling (Appendix [B.2\)](#page-19-0).

4.2. 2D Block DCT

After the chroma subsampling, Y, Cb and Cr channels are split into non-overlapping two-dimensional blocks with block size B , and the results are denoted as three sets: $\mathbf{x'_{y}} \equiv \left\{\mathbf{x_y}^i\right\}_{i=1}^{4N}, \mathbf{x'_{cb}} \equiv \left\{\mathbf{x_{cb}}^i\right\}_{i=1}^{N}, \mathbf{x'_{cr}} \equiv \left\{\mathbf{x_{cr}}^i\right\}_{i=1}^{N}, \text{where}$ N is the number of blocks in Cb and Cr channels, and \mathbf{x}_{y}^{i} , \mathbf{x}_{cb}^{i} , $\mathbf{x}_{cr}^{i} \in \mathbb{R}^{B \times B}$. Each block is then transformed by two-dimensional DCT. We use the most commonly used type-II DCT [\(Ahmed et al.,](#page-8-21) [1974\)](#page-8-21) which converts zerocentered matrix $\mathbf{A} \in \mathbb{R}^{B \times B}$ into a DCT block $\mathbf{D} \in \mathbb{R}^{B \times B}$ using a series of horizontal and vertical cosine bases:

$$
D(u, v) = \alpha(u)\alpha(v) \times
$$

$$
\sum_{x=0}^{B-1} \sum_{y=0}^{B-1} A(x, y) \cos\left[\frac{(2x+1)u\pi}{2B}\right] \cos\left[\frac{(2y+1)v\pi}{2B}\right]
$$

(5)
where $\alpha(u) = \begin{cases} \sqrt{1/B}, & \text{if } u = 0\\ \sqrt{2/B}, & \text{if } u \neq 0 \end{cases}$

The resulting $D(u, v)$ is the DCT coefficient at position (u, v) in the frequency domain, $A(x, y)$ is the YCbCr value at position (x, y) in the spatial domain, $\alpha(u)$ and $\alpha(v)$ are normalization factors. We represent the DCT blocks as $\bm{D}_{\bm{y}} \equiv \big\{ \bm{D}_{\bm{y}}^{\,i}\big\}^{\rm 4N}_{i=1}, \, \bm{D}_{\bm{c}\bm{b}} \equiv \big\{ \bm{D}_{\bm{c}\bm{b}}^{\,i}\big\}^N_{i=1}, \, \bm{D}_{\bm{c}\bm{r}} \equiv \big\{ \bm{D}_{\bm{c}\bm{r}}^{\,i}\big\}^N_{i=1},$ corresponding to the DCT outcomes transformed from the Y, Cb and Cr blocks, respectively. JPEG codec uses a fixed block size $B = 8$ due to the trade-off between efficiency and visual quality. However, we find that different image resolutions require different block sizes for optimal diffusion modeling, thus the block size B is set as a variable in DCTdiff.

4.3. Frequency Tokenization

We notice that the non-overlapping block operation in DCT resembles the patch process in Vision Transformer [\(Doso](#page-8-2)[vitskiy et al.,](#page-8-2) [2021\)](#page-8-2), therefore it is natural to use ViT-based models for DCT diffusion modeling. We propose using UViT [\(Bao et al.,](#page-8-22) [2023\)](#page-8-22) and DiT [\(Peebles & Xie,](#page-9-8) [2023\)](#page-9-8) to construct DCTdiff due to their remarkable performance on image generation.

To ensure that the Y, Cb, and Cr blocks within each Transformer token correspond to the same spatial area, we respace the Cb and Cr blocks to expand to the same space as Y

DCTdiff: Intriguing Properties of Image Generative Modeling in the DCT Space

Figure 1. The architecture and pipeline of DCTdiff.

blocks (see Figure [1](#page-3-0) (d)) before merging them into a token. Then, four Y blocks, one Cb block, and one Cr block are packed into a single token. Note that, the patch size P in ViT-based models and the block size B in DCT diff have the relationship $P = 2B$ which will be used throughout the paper. We also tested with other tokenization methods, for instance, each DCT block was considered as a token, but the performance was inferior to the '4Y+1Cb+1Cr' combination.

A notable property of DCT is that many high-frequency coefficients are typically near-zero after DCT transformation, as these coefficients contribute little to the visual quality they can be eliminated. To this end, we first turn the twodimensional DCT blocks $D_{\boldsymbol{y}}^{i}$, $D_{\boldsymbol{c}\boldsymbol{b}}^{i}$, $D_{\boldsymbol{c}\boldsymbol{r}}^{i} \in \mathbb{R}^{B \times B}$ into one-dimensional vectors $\bar{\bm{D}}_{\bm{y}}{}^{i}$, $\bar{\bm{D}}_{\bm{c}\bm{b}}{}^{i}$, $\bar{\bm{D}}_{\bm{c}\bm{r}}{}^{i} \in \mathbb{R}^{B^2}$ using the zigzag pattern (shown in Figure [1](#page-3-0) (e)), resulting in the coefficients ordered from low-to-high frequency. In order to decide the number of high-frequency coefficients to be chopped off for \bar{D}_{y}^{i} , \bar{D}_{cb}^{i} , \bar{D}_{cr}^{i} , we propose the following criteria for generative tasks:

$$
m^* = \underset{m}{\arg\max} \{ m : \text{FID}(P_{\text{data}}, P_{\text{dct_data}}(m)) < \gamma \} \quad (6)
$$

where we compute the Fréchet Inception Distance (FID) [\(Heusel et al.,](#page-8-23) [2017\)](#page-8-23) between the data distribution P_{data} and the distribution $P_{\text{det_data}}$ which is derived from DCT compression by eliminating m high-frequency coefficients. γ is a constant and we empirically found that $\gamma = 0.5$ yields a good trade-off between generation quality and compression rate. Note that $FID(P_{data}, P_{det_data}(m[*]))$ also determines the FID lower bound of generative modeling based on the compressed DCT training samples. After removing m^* coefficients, the dimension of $\bar{D}_{\boldsymbol{y}}{}^i$, $\bar{D}_{\boldsymbol{c}\boldsymbol{b}}{}^i$, $\bar{D}_{\boldsymbol{c}\boldsymbol{r}}{}^i$ is reduced from

 $B²$ to $B² - m[*]$. Since we concatenate '4Y+1Cb+1Cr' vectors into a token, a Transformer token contains $6(B^2 - m^*)$ frequency coefficients and the number of DCT tokens is N . So far, we have transformed the RGB image x to DCT coefficients, represented as $\bar{\mathbf{x}} \in \mathbb{R}^{N \times 6(B^2 - m^*)}$. Our goal is to model P_{data} given all DCT samples \bar{x} using diffusion models.

4.4. Diffusion Modeling and Coefficients Scaling

Continuous-time [\(Song et al.,](#page-10-4) [2021b\)](#page-10-4) and discrete-time diffusion models [\(Ho et al.,](#page-8-5) [2020\)](#page-8-5) can all be applied for DCTdiff to model P_{data} . For simplicity, we summarize the training process of continuous-time diffusion models and one can refer to [Ho et al.](#page-8-5) [\(2020\)](#page-8-5) for the details of the discrete-time case. Following [Song et al.](#page-10-4) [\(2021b\)](#page-10-4), we construct a diffusion process ${\{\bar{\mathbf{x}}_t\}}_{t=0}^T$ indexed by a continuous time variable $t \in [0, T]$ such that $\bar{\mathbf{x}}_0 \sim P_{data}$. We use $P_{0t}(\bar{\mathbf{x}}_t | \bar{\mathbf{x}}_0)$ to denote the perturbation kernel from $\bar{\mathbf{x}}_0$ to $\bar{\mathbf{x}}_t$. Specifically, we follow UViT to employ the Variance Preserving (VP) SDE, so that $P_{0t}(\bar{\mathbf{x}}_t|\bar{\mathbf{x}}_0)$ is a Gaussian:

$$
\mathcal{N}(\bar{\mathbf{x}}_t; \bar{\mathbf{x}}_0 e^{-\frac{1}{2} \int_0^t \beta(s) \, \mathrm{d}s}, \mathbf{I} - \mathbf{I} e^{-\int_0^t \beta(s) \, \mathrm{d}s}) \tag{7}
$$

in which $\beta(.)$ is the noise scale. Then the score model $s_{\theta}(\bar{\mathbf{x}}_t, t)$ is trained by denoising score matching:

$$
\mathcal{L}(\boldsymbol{\theta}) = \mathbb{E}_{t} \lambda(t) \mathbb{E}_{\bar{\mathbf{x}}_0, \bar{\mathbf{x}}_t} [||\boldsymbol{s}_{\boldsymbol{\theta}}(\bar{\mathbf{x}}_t, t) - \nabla_{\bar{\mathbf{x}}_t} \log P_{0t}(\bar{\mathbf{x}}_t | \bar{\mathbf{x}}_0)||_2^2]
$$
(8)

where $\lambda(t)$ is a positive weighting function, t is sampled from the uniform distribution $U(0, T)$, $\bar{\mathbf{x}}_0 \sim P_{data}$ and $\bar{\mathbf{x}}_t \sim P_{0t}(\bar{\mathbf{x}}_t|\bar{\mathbf{x}}_0)$. After training the diffusion model, we synthesize images by converting the generated DCT coefficients back to RGB pixels via inverse DCT.

A notable pre-processing in diffusion models is that $\bar{\mathbf{x}}_0$ should be rescaled into the interval $[-1, 1]$ before perturbation. It is trivial for RGB pixels to be shifted and scaled from [0, 255] to $[-1, 1]$. However, we notice that the scaling method significantly affects the diffusion training speed and sample quality when $\bar{\mathbf{x}}_0$ are the DCT coefficients. Different from RGB where each pixel variable shares the same value range [0, 255], the bound of frequency coefficients varies greatly, depending on its position on the spectrum and the channels (Y/Cb/Cr). For instance, the upper bound of the lowest frequency signal in the Y channel (a.k.a DC component) is higher than that of the Cb channel by two orders of magnitude. Therefore, we initially considered a Naive Scaling method: given block size B , compute the bounds for each frequency (total $B^2 - m^*$ frequencies) and each channel (Y, Cb, Cr), the resulting $3(B^2 - m^*)$ bounds are applied to scale the corresponding frequency coefficients into [−1, 1], respectively. However, we observe that Naive Scaling broadens the distribution of high-frequency coefficients, leading to slow training and low generated sample quality. Intuitively, most high-frequency coefficients are around zero in the spectrum with the density resembling the Dirac delta distribution, and the scaling operation should not change the shape of the probability density. Thus, we propose a new Entropy-Consistent Scaling approach in which $3(B^2 - m^*)$ frequency signals are scaled by the bound of the DC component (namely $D(0,0)$ of Y blocks) since it yields the largest bound). To avoid the influence of extreme values, we compute the bound $\eta \in \mathbb{R}$ within τ percentile and $100 - \tau$ percentile:

$$
\eta = \max(|P_{\tau}|, |P_{100-\tau}|) \tag{9}
$$

where P_{τ} denotes the τ th percentile of the DC component distribution. We empirically find that $\tau = 96.5$ yields the best performance of DCTdiff across various datasets. Please refer to Appendix [A.1](#page-11-0) for the full details of Naive Scaling and Entropy-Consistent Scaling. Hereafter, we assume that $\bar{\mathbf{x}}_0$ has been scaled by η , namely $\bar{\mathbf{x}}_0 = \bar{\mathbf{x}}_0/\eta$

4.5. SNR Scaling

An inherent property of DCT is that most of the signal's energy is compacted into a few low-frequency components, so that high-frequency components are near zero and quickly destroyed by the noise term during the forward diffusion process (detailed discussion in Section [5.3\)](#page-5-0). Consequently, this results in the visual phenomenon where perturbing an image in the DCT space looks faster than perturbing an image in pixel space, despite using the same forward SDE (see Figure [6\)](#page-17-0). Furthermore, the larger the block size B , the more the energy is concentrated in low frequencies, thus the faster the forward perturbation is. We can also infer this phenomenon from the bound η mentioned above. To this end, we introduce a brief corollary concerning η : given a

dataset, η doubles if the block size B is doubled.

Sketch of Proof. Since η is derived from $D(0, 0)$, we investigate how $D(0, 0)$ changes under block size 2B and B. Plugging $2B$ and B into Eq. [\(5\)](#page-2-1) yields

$$
\frac{1}{2B} \sum_{x=0}^{2B-1} \sum_{y=0}^{2B-1} A(x,y) = 2 \times \frac{1}{B} \sum_{x=0}^{B-1} \sum_{y=0}^{B-1} A(x,y)
$$

if we assume that $A(x, y)$ has the same mean within the $2B \times 2B$ block and $B \times B$ block. Thus $D(0, 0)$ doubles when B is doubled, causing η to increase twofold. Recall that we scale down all frequency coefficients by η before adding noise, a larger η would result in more coefficients close to zero and destroyed by the noise in the early stage of forward diffusion. To counteract the effect of block size, we propose to scale the SNR (Signal-Noise-Ratio) of the default noise schedule (similar to [Hoogeboom et al.](#page-8-12) [\(2023\)](#page-8-12)). We leave the derivation and implementation of SNR Scaling to Appendix [A.2.](#page-11-1) Experiments show that SNR Scaling improves the sample quality without affecting the training convergence [\(B.4\)](#page-19-1).

5. Intriguing Properties of Image Modeling in the DCT Space

5.1. Frequency Prioritization

Recall that training the score model is equivalent to predicting the isotropic Gaussian noise added on the clear image given the noisy image [\(Dhariwal & Nichol,](#page-8-8) [2021\)](#page-8-8). Intuitively, the task is to reconstruct each frequency coefficient in $\bar{\mathbf{x}}_0$ or reconstruct each pixel in the case of RGB image x_0 . Since we cannot say which pixel is more important than another pixel, the training objective (Eq. [\(8\)](#page-3-1)) treats every pixel equally. However, an intriguing property of DCT coefficients is that a low-frequency signal representing broad, smooth variation in an image contributes more to the image quality than a high-frequency signal capturing the fine details. Meanwhile, we observe that the lower the frequency of the signal, the larger the entropy of its distribution. Thereby, we can prioritize the modeling of low-frequency signals of $\bar{\mathbf{x}}_0$ by adding Entropy-Based Frequency Reweighting (EBFR) into eq. [\(8\)](#page-3-1), leading to $\mathcal{L}_{EBFR}(\theta)$:

$$
\mathbb{E}_{t}\lambda(t)\mathbb{E}_{\mathbf{\bar{x}}_{0},\mathbf{\bar{x}}_{t}}[\boldsymbol{H}(B)||\boldsymbol{s}_{\boldsymbol{\theta}}(\mathbf{\bar{x}}_{t},t)-\nabla_{\mathbf{\bar{x}}_{t}}\log P_{0t}(\mathbf{\bar{x}}_{t}|\mathbf{\bar{x}}_{0})||_{2}^{2}](10)
$$

where $\mathbf{H}(B) \in \mathbb{R}^{3(B^2 - m^*)}$ is the entropy vector of the valid $3(B^2 - m^*)$ frequency distributions. Given a dataset, $\mathbf{H}(B)$ only depends on the block size B once m^* is fixed. We empirically show that Entropy-Based Frequency Reweighting improves the sample quality without affecting the training speed (see Appendix [B.3\)](#page-19-2).

The frequency prioritizing strategy can be easily extended to discriminative tasks and utilizing prior knowledge. Specifically, we can allocate more network capacity to model highfrequency inputs on tasks requiring a good understanding of fine details, for example, text and handwriting recognition, medical image analysis [\(Ronneberger et al.,](#page-9-22) [2015\)](#page-9-22), fingerprint recognition, forgery detection [\(Wu et al.,](#page-10-14) [2019\)](#page-10-14), etc. In contrast, we can explicitly highlight the low-frequency signals on tasks focusing on general shapes and overall structures, for instance, scene recognition [\(Zhou et al.,](#page-10-15) [2017\)](#page-10-15), object detection in natural scenes [\(Redmon,](#page-9-23) [2016\)](#page-9-23), action recognition [\(Simonyan & Zisserman,](#page-9-24) [2014\)](#page-9-24), and so on.

5.2. Significant Lossless Compression under DCT

Unlike Fourier transform, DCT operates on real numbers using cosine functions, which effectively match the even symmetric extension of a signal [\(Rao & Yip,](#page-9-21) [2014\)](#page-9-21). This alignment with signal characteristics allows the DCT to represent an image or other signals using fewer frequency coefficients (mostly the low-frequency ones). For generative tasks, we can again use $FID(P_{data}, P_{det_data}(m)) < \gamma$ to measure the information loss when removing m highfrequency coefficients. Table [1](#page-5-1) presents the results of $FID(P_{data}, P_{det_data}(m))$ using 50k images from the data distribution P_{data} of FFHQ 256. If we consider $\gamma = 0.5$ as a lossless compression for image generation, DCT could achieve 4x compression. In Section [6.1,](#page-6-0) we will show that the significant compression of DCT enables the image generation to smoothly scale up to high-resolution generation, while pure pixel diffusion fails due to the high dimensions of the pixel space. We also visually compare the image quality of VAE compression [\(Rombach et al.,](#page-9-4) [2022\)](#page-9-4) and DCT compression, Figure [8](#page-20-0) indicates that DCT compression maintains more image details than VAE compression.

Table 1. Evaluation of FID when removing m coefficients (block size $B = 4$) on the dataset FFHQ 256. The compression ratio is relative to the RGB image having $3*wh$ signals

			# Signals FID Compression ratio
$DCT (m = 3)$	$1.22*wh$	0.23	2.46
$DCT (m = 6)$	$0.94*wh$	0.24	3.20
$DCT (m = 8)$	$0.75*wh$	0.58	4.00
$DCT (m = 9)$	$0.66*wh$ 1.04		4.57

5.3. Image Diffusion Is Spectral Autoregression

Recently, [Dieleman](#page-8-24) [\(2024\)](#page-8-24) has empirically shown that pixelbased diffusion models perform approximate autoregression in the frequency domain. Intuitively, diffusion models destroy an image's high-frequency signals and then progressively destroy lower-frequency signals as time t flows in the forward diffusion process. In this paper, we provide the theoretical proof for this phenomenon.

Theorem 5.1. *Consider a diffusion model described by* $d\mathbf{x}_t = \mathbf{f}(\mathbf{x}_t, t) dt + g(t) d\mathbf{w}_t$. Let ω denote the frequency, $\hat{\boldsymbol{x}}_0(\omega)$ *and* $\hat{\boldsymbol{x}}_t(\omega)$ *represent the Fourier transform of the pixel image* x_0 *and* x_t *, respectively. The averaged power spectral density of the noisy image* x_t *satisfies:*

$$
\mathbb{E}\left[\left|\hat{\boldsymbol{x}}_t(\omega)\right|^2\right] = \left|\hat{\boldsymbol{x}}_0(\omega)\right|^2 + \int_0^t |g(s)|^2 \mathrm{d}s \qquad (11)
$$

in which $\left|\hat{\bm{x}}_{0}(\omega)\right|^{2}$ is the power spectral density of the image \pmb{x}_0 and natural images have the power-law: $\left|\hat{\pmb{x}}_0(\omega)\right|^2=$ $K|\omega|^{-\alpha}$ [\(Ruderman,](#page-9-25) [1997\)](#page-9-25)(K and α are constants). Meanwhile, $\int_0^t |g(s)|^2 ds$ is independent of frequency ω and ap*pears as a horizontal line in the spectral density graph.*

Sketch of Proof. Taking the integral of the forward diffusion SDE yields $\boldsymbol{x}_t = \boldsymbol{x}_0 + \int_0^t g(s) \mathrm{d} \boldsymbol{w}_s$ (assuming $\boldsymbol{f}(\boldsymbol{x}_t, t) = 0$ for VE-SDE). Since Fourier transform is linear, we have $\hat{\boldsymbol{x}}_t(\omega) = \hat{\boldsymbol{x}}_0(\omega) + \hat{\boldsymbol{\epsilon}}_t(\omega)$ in the frequency domain, where $\hat{\boldsymbol{\epsilon}}_t(\omega)$ is the Fourier transform of the noise term $\int_0^t g(s) \, \mathrm{d}\boldsymbol{w}_s$. \mathbf{B} y taking the expectation over the Wiener process \mathbf{w}_s , we \mathbf{B} y taking the expectation over the Wiener process \mathbf{w}_s , we can obtain $\mathbb{E}\left[\left|\hat{\bm{x}}_t(\omega)\right|^2\right] = \left|\hat{\bm{x}}_0(\omega)\right|^2 + \mathbb{E}\left[\left|\hat{\bm{\epsilon}}_t(\omega)\right|^2\right]$ due to $\mathbb{E} [|\hat{\epsilon}_t(\omega)|] = 0$. According to Itô isometry (Itô, [1944\)](#page-8-25), we have $\mathbb{E}[|\hat{\epsilon}_t(\omega)|^2] = \int_0^t |g(s)|^2 ds$ which leads to Eq. [\(11\)](#page-5-2) (Please refer to Appendix [A.3](#page-13-0) for the detailed proof).

In Eq. [\(11\)](#page-5-2), $|\hat{x}_0(\omega)|^2$ quickly decreases to near-zero as frequency ω increases. So, the spectral density of the highfrequency component, $\mathbb{E}\left[|\hat{\boldsymbol{x}}_t(\omega)|^2\right]$, is mainly decided by the noise term $\int_0^t |g(s)|^2 ds$. Since the noise term is monotonically increasing as t grows from $0 \to T$, we can see that the noise term in the forward diffusion SDE first mainly destroys the high-frequency component of image x_0 , and then gradually diminishes the lower-frequency signals. For every frequency ω , we can further determine the required time to reach a specific SNR, see Appendix [A.3](#page-13-0) for the derivation. Recently, VAR proposed to generate images from coarse to fine by predicting the next-resolution image [\(Tian et al.,](#page-10-2) [2024\)](#page-10-2), we believe the success of VAR stems from the 'spectral autoregression' property of images.

Note that Theorem [5.1](#page-5-3) holds if we replace the Fourier transform with DCT since DCT is also a linear transformation and is a simplified, real-valued variant of the Fourier transform. Inspired by [\(Dieleman,](#page-8-24) [2024\)](#page-8-24), we visualize the averaged power spectral density from the DCT space (detailed in Appendix [A.4\)](#page-15-0). The resulting curves in Figure [5](#page-16-0) resemble the case of the Fourier Transform, indicating that pixel diffusion is also spectral autoregression in the DCT space.

Similar to pixel diffusion, a frequency-based diffusion process (e.g. DCTdiff) simultaneously adds isotropic noise to the whole spectrum in the forward diffusion process, i.e. equally perturbing high-frequency and low-frequency signals at each time step. As high frequencies have low energy, they are first corrupted by the noise. Thereby, we conclude that frequency-based image diffusion is also spectral autoregression. However, DCT concentrates the image energy into low frequencies [\(Rao & Yip,](#page-9-21) [2014\)](#page-9-21), leaving most highfrequency components close to zero, so that DCT exhibits a fast 'noise-adding' forward diffusion process (see Figure [6\)](#page-17-0).

5.4. DCT Upsampling Outperforms Pixel Upsampling

We find that upsampling in the DCT space produces higherquality images than upsampling in the pixel space (e.g. using bilinear or bicubic interpolation). Motivated by Dugad $\&$ [Ahuja](#page-8-26) [\(2001\)](#page-8-26), we introduce the following theorem to relate the frequency between low-resolution and high-resolution images in the DCT space.

Theorem 5.2. Let $A \in \mathbb{R}^{2B \times 2B}$ be a matrix representing an image, and define $\bar{\bm{A}} \in \mathbb{R}^{B \times B}$ as the matrix obtained by *average pooling of* A*, where each element is computed as:*

$$
\bar{A}(i,j) = \frac{1}{4} \sum_{m=0}^{1} \sum_{n=0}^{1} A(2i+m, 2j+n).
$$

 $Suppose D \in \mathbb{R}^{2B \times 2B}$ *represents the DCT of A under block size* 2B and $\bar{D} \in \mathbb{R}^{\tilde{B} \times B}$ represents the DCT of \bar{A} *under block size* B. Then, for $k, l \in \{0, 1, \ldots, B-1\}$, the *elements of* \bar{D} *can be approximated by:*

$$
\bar{D}(k,l) \approx \frac{1}{2}\cos\left(\frac{k\pi}{4B}\right)\cos\left(\frac{l\pi}{4B}\right)D(k,l),\qquad(12)
$$

where (k, l) *indexes the elements of the matrices* \boldsymbol{D} *and* $\boldsymbol{\bar{D}}$ *. Appendix [A.5](#page-15-1) provides the full proof.*

Based on Theorem [5.2,](#page-6-1) we propose the DCT Upsampling algorithm. For each DCT block \bar{D} converted from a lowresolution image, the algorithm computes $D(k, l)$ from $D(k, l)$ according to Eq. [\(12\)](#page-6-2), generating the low-frequency coefficients (purple block in Figure [2\)](#page-6-3) of D . For the remaining frequency coefficients in D , we fill them up with zero since they are near-zero in practice. The resulting D can be converted back to the pixel space to create a high-resolution image.

Figure 2. Illustration of the DCT Upsampling algorithm.

We evaluate DCT Upsampling both qualitatively and quantitatively. We show an example in Figure [11](#page-22-0) to illustrate the difference between Pixel Upsampling by bicubic interpolation [\(Gonzalez,](#page-8-20) [2009\)](#page-8-20) and DCT Upsampling. The latter alleviates the blurry effect and exhibits an improved image

quality. Also, we apply FID to evaluate the distance between the ground truth data distribution and the upsampled data distribution. Experimentally, DCT Upsampling achieves FID 9.79, outperforming Pixel Upsampling (FID 12.53). A potential application of DCT Upsampling is high-resolution image generation. Specifically, one can follow the paradigm of [Dhariwal & Nichol](#page-8-8) [\(2021\)](#page-8-8): first train a low-resolution image generation model, then replace the bilinear interpolation with our DCT Upsampling to obtain a better draft high-resolution image, this image can finally be refined by another neural network. We leave this to future research.

6. Experiments

To evaluate the performance of DCTdiff, we construct the models based on UViT and DiT without changing their Transformer architectures, and compare DCTdiff with these two base models regarding FID [\(Heusel et al.,](#page-8-23) [2017\)](#page-8-23) and training speed. For a fair comparison, we always use the same model size, patch size and training parameters for DCTdiff and the base model (unless otherwise noted), so that a single training iteration costs the same amount of time for DCTdiff and UViT/DiT. We list the complete network parameters and training settings in Appendix [A.6,](#page-18-1) and leave all ablation studies to Appendix [B.](#page-18-2)

6.1. Results on UViT

UViT [\(Bao et al.,](#page-8-22) [2023\)](#page-8-22) utilizes the continuous-time diffusion framework and different solvers for sampling. We train both UViT and DCTdiff from scratch using the default training parameters suggested by UViT. The datasets include CIFAR-10 [\(Krizhevsky et al.,](#page-8-27) [2009\)](#page-8-27), CelebA 64 [\(Liu et al.,](#page-9-26) [2015\)](#page-9-26), ImageNet 64 [\(Chrabaszcz et al.,](#page-8-28) [2017\)](#page-8-28), FFHQ 128 and FFHQ 256 [\(Karras et al.,](#page-8-29) [2019\)](#page-8-29). We perform classconditional generation on ImageNet 64 and unconditional generation for the other datasets. We test the sample quality using FID-50k under different Number of Function Evaluation (NFEs) and two ODE solvers (DDIM sampler [\(Song](#page-10-16) [et al.,](#page-10-16) [2021a\)](#page-10-16) and DPM-Solver [\(Lu et al.,](#page-9-5) [2022\)](#page-9-5)). Results on Table [2](#page-7-0) show that DCTdiff consistently outperforms UViT regardless of NFEs and solvers (except for the outlier of CelebA 64 using DPM-Solver), demonstrating the effectiveness of image diffusion modeling in the DCT space. We believe the outlier can be attributed to the UViT training parameters being highly suited to CelebA 64.

Note that UViT uses VAE to perform latent diffusion [\(Rom](#page-9-4)[bach et al.,](#page-9-4) [2022\)](#page-9-4) when the image resolution reaches 256 since pixel diffusion modeling in such high-dimensional space is difficult. However, we show that the diffusion paradigm of DCTdiff can be easily scaled to 256×256 image generation without VAE. In practice, we attempted to train the UViT model directly in the pixel space on FFHQ 256, however, the model struggled to learn the score func-

NFE	Model			Euler ODE solver (DDIM sampler)		DPM-Solver					
		CIFAR-10	CelebA 64	ImageNet 64	FFHO 128	CIFAR-10	CelebA 64	ImageNet 64	FFHQ 128		
100	UViT	6.23	1.99	10.65	13.87	5.80	1.57	10.07	9.18		
	DCTdiff	5.29	1.91	8.89	9.36	5.54	1.83	9.90	6.63		
50	UViT	7.88	3.50	15.05	26.26	5.82	1.58	10.09	9.20		
	DCTdiff	5.73	2.24	8.93	12.21	5.54	1.85	9.93	6.70		
20	UViT	21.48	31.09	52.10	87.68	6.19	1.73	10.25	9.21		
	DCTdiff	10.62	3.84	20.88	32.60	5.78	1.86	9.97	7.68		
10	UViT	81.67	224.21	166.63	209.69	26.65	4.37	13.27	14.26		
	DCTdiff	38.95	67.68	123.87	158.05	16.36	3.86	12.76	11.58		

Table 2. FID-50k of UViT and DCTdiff using DDIM sampler and DPM-Solver under different NFEs. We implement class-conditional generation on ImageNet 64, and unconditional generation on the rest of the datasets.

tion, resulting in a high FID of 120. Therefore, we compare DCTdiff with UViT (latent) in Table [3.](#page-7-1) The resulting FID indicates that DCTdiff achieves competitive generation quality to latent UViT.

In addition to sample quality, we also compare the training costs between UViT and DCTdiff. Results in Table [4](#page-7-2) demonstrate that the training of DCTdiff is faster than that of UViT with the training acceleration up to 2.5x. Considering that latent UViT uses the encoder of VAE for training and the decoder of VAE for sampling, we thus apply a smaller patch size for DCTdiff to obtain a comparable computational cost of a single network forward pass. Note that, the VAE used by UViT was trained on the OpenImage dataset (9 million images) [\(Kuznetsova et al.,](#page-9-27) [2020\)](#page-9-27) so that the total training of latent UViT is more expensive that that of DCTdiff.

Table 3. FID-50k of UViT (latent) and DCTdiff on FFHQ 256 dataset for unconditional generation.

NFE.	Model	NFE.							
		100	50	20	10				
DPM-Solver	UViT (latent) DCTdiff	5.92	4.26 4.29 6.06	-4.74 6.55	13.29 18.35				

Table 4. Training iterations (convergence) of UViT and DCTdiff. We use batch size 1024 for ImageNet 64 and batch size 256 for other datasets

6.2. Results on DiT

DiT [\(Peebles & Xie,](#page-9-8) [2023\)](#page-9-8) applies the discrete-time diffusion framework and the Euler SDE solver (DDPM sampler) for image sampling. We train DiT (in the pixel space) and DCTdiff from scratch with the same training settings on

CelebA 64 and FFHQ 128 datasets. The resulting FIDs in Table [5](#page-7-3) show that DCTdiff surpasses DiT under different sampling steps regarding the generation quality.

Table 5. FID-50k of DiT and DCTdiff using DDPM sampler under different NFEs for unconditional generation.

NFE	Model	Datasets							
		CelebA 64	FFHQ 128						
100	UViT	5.11	12.81						
	DCTdiff	4.84	12.50						
50	UViT	8.17	18.44						
	DCTdiff	7.05	16.50						
20	I IV _i T	15.64	33.56						
	DCTdiff	13.26	27.10						
10	UV_iT	24.76	49.64						
	DCTdiff	20.56	44.02						

7. Conclusion

In this paper, we explore image generative modeling in the DCT space and propose DCTdiff which shows superior performance over pixel-based diffusion models. In particular, we reveal several interesting properties of image modeling from the DCT space, suggesting a promising research direction for image discriminative and generative tasks. Despite these promising results and properties of DCT, the frequency-oriented Transformer architecture and image generation in resolution 1024×1024 are not explored in this paper, which encourages future study. Other possible future research could be performing image discriminative tasks or representation learning in the frequency space. Additionally, considering the inherent high temporal redundancy, video compression and modeling in the frequency space also hold significant potential for future exploration.

References

- Ahmed, N., Natarajan, T., and Rao, K. R. Discrete cosine transform. *IEEE transactions on Computers*, 100(1):90– 93, 1974.
- Anderson, B. D. Reverse-time diffusion equation models. *Stochastic Processes and their Applications*, 12(3):313– 326, 1982.
- Bao, F., Li, C., Zhu, J., and Zhang, B. Analytic-dpm: an analytic estimate of the optimal reverse variance in diffusion probabilistic models. In *ICLR*, 2022.
- Bao, F., Nie, S., Xue, K., Cao, Y., Li, C., Su, H., and Zhu, J. All are worth words: A vit backbone for diffusion models. In *CVPR*, pp. 22669–22679, 2023.
- Blattmann, A., Dockhorn, T., Kulal, S., Mendelevitch, D., Kilian, M., Lorenz, D., Levi, Y., English, Z., Voleti, V., Letts, A., et al. Stable video diffusion: Scaling latent video diffusion models to large datasets. *arXiv preprint arXiv:2311.15127*, 2023.
- Buchholz, T.-O. and Jug, F. Fourier image transformer. In *CVPR*, pp. 1846–1854, 2022.
- Chrabaszcz, P., Loshchilov, I., and Hutter, F. A downsampled variant of ImageNet as an alternative to the CIFAR datasets. *arXiv:1707.08819*, 2017.
- Deutsch, P. Deflate compressed data format specification version 1.3. Technical report, 1996.
- Dhariwal, P. and Nichol, A. Diffusion models beat gans on image synthesis. *NeurIPS*, 34:8780–8794, 2021.
- Dieleman, S. Diffusion is spectral autoregression, 2024. URL [https://sander.ai/2024/09/02/](https://sander.ai/2024/09/02/spectral-autoregression.html) [spectral-autoregression.html](https://sander.ai/2024/09/02/spectral-autoregression.html).
- Dosovitskiy, A., Beyer, L., Kolesnikov, A., Weissenborn, D., Zhai, X., Unterthiner, T., Dehghani, M., Minderer, M., Heigold, G., Gelly, S., Uszkoreit, J., and Houlsby, N. An image is worth 16x16 words: Transformers for image recognition at scale. *ICLR*, 2021.
- Dugad, R. and Ahuja, N. A fast scheme for image size change in the compressed domain. *IEEE Transactions on Circuits and Systems for Video Technology*, 11(4): 461–474, 2001.
- Esser, P., Kulal, S., Blattmann, A., Entezari, R., Müller, J., Saini, H., Levi, Y., Lorenz, D., Sauer, A., Boesel, F., et al. Scaling rectified flow transformers for high-resolution image synthesis. In *ICML*, 2024.
- Fridovich-Keil, S., Gontijo Lopes, R., and Roelofs, R. Spectral bias in practice: The role of function frequency in generalization. *NeurIPS*, 35:7368–7382, 2022.

Gonzalez, R. C. *Digital image processing*. Pearson education india, 2009.

Goodfellow, I. Deep learning, 2016.

- Han, X., Ghazvininejad, M., Koh, P. W., and Tsvetkov, Y. Jpeg-lm: Llms as image generators with canonical codec representations. *arXiv preprint arXiv:2408.08459*, 2024.
- Hang, T. and Gu, S. Improved noise schedule for diffusion training. *arXiv preprint arXiv:2407.03297*, 2024.
- He, K., Zhang, X., Ren, S., and Sun, J. Deep residual learning for image recognition. In *CVPR*, pp. 770–778, 2016.
- Heusel, M., Ramsauer, H., Unterthiner, T., Nessler, B., and Hochreiter, S. Gans trained by a two time-scale update rule converge to a local nash equilibrium. *NeurIPS*, 30, 2017.
- Ho, J. and Salimans, T. Classifier-free diffusion guidance. *arXiv preprint arXiv:2207.12598*, 2022.
- Ho, J., Jain, A., and Abbeel, P. Denoising diffusion probabilistic models. *NeurIPS*, 33:6840–6851, 2020.
- Hoogeboom, E., Heek, J., and Salimans, T. simple diffusion: End-to-end diffusion for high resolution images. In *ICML*, pp. 13213–13232. PMLR, 2023.
- Huang, Z., Zhang, Z., Lan, C., Zha, Z.-J., Lu, Y., and Guo, B. Adaptive frequency filters as efficient global token mixers. In *ICCV*, pp. 6049–6059, 2023.
- Itô, K. 109. stochastic integral. Proceedings of the Imperial *Academy*, 20(8):519–524, 1944.
- Karras, T., Laine, S., and Aila, T. A style-based generator architecture for generative adversarial networks. In *CVPR*, pp. 4401–4410, 2019.
- Karras, T., Aittala, M., Laine, S., and Aila, T. Elucidating the design space of diffusion-based generative models. In *NeurIPS*, pp. 26565–26577, 2022.
- Karras, T., Aittala, M., Lehtinen, J., Hellsten, J., Aila, T., and Laine, S. Analyzing and improving the training dynamics of diffusion models. In *CVPR*, pp. 24174– 24184, 2024.
- Krizhevsky, A., Hinton, G., et al. Learning multiple layers of features from tiny images. 2009.
- Krizhevsky, A., Sutskever, I., and Hinton, G. E. Imagenet classification with deep convolutional neural networks. *NeurIPS*, 25, 2012.
- Kuznetsova, A., Rom, H., Alldrin, N., Uijlings, J., Krasin, I., Pont-Tuset, J., Kamali, S., Popov, S., Malloci, M., Kolesnikov, A., et al. The open images dataset v4: Unified image classification, object detection, and visual relationship detection at scale. *IJCV*, 128(7):1956–1981, 2020.
- Lee-Thorp, J., Ainslie, J., Eckstein, I., and Ontanon, S. Fnet: Mixing tokens with fourier transforms. In *NAACL*. Association for Computational Linguistics, 2022.
- Li, M., Qu, T., Yao, R., Sun, W., and Moens, M.-F. Alleviating exposure bias in diffusion models through sampling with shifted time steps. *ICLR*, 2024.
- Lin, C.-H., Gao, J., Tang, L., Takikawa, T., Zeng, X., Huang, X., Kreis, K., Fidler, S., Liu, M.-Y., and Lin, T.-Y. Magic3d: High-resolution text-to-3d content creation. In *CVPR*, pp. 300–309, 2023.
- Lipman, Y., Chen, R. T., Ben-Hamu, H., Nickel, M., and Le, M. Flow matching for generative modeling. In *ICLR*, 2023.
- Liu, X., Gong, C., and Liu, Q. Flow straight and fast: Learning to generate and transfer data with rectified flow. In *ICLR*, 2023.
- Liu, Z., Luo, P., Wang, X., and Tang, X. Deep learning face attributes in the wild. In *ICCV*, pp. 3730–3738, 2015.
- Lu, C., Zhou, Y., Bao, F., Chen, J., Li, C., and Zhu, J. Dpmsolver: A fast ode solver for diffusion probabilistic model sampling in around 10 steps. *NeurIPS*, 35:5775–5787, 2022.
- Mathieu, M., Henaff, M., and LeCun, Y. Fast training of convolutional networks through ffts. *ICLR*, 2014.
- Mattar, W., Levy, I., Sharon, N., and Dekel, S. Wavelets are all you need for autoregressive image generation. *arXiv preprint arXiv:2406.19997*, 2024.
- Moczulski, M., Denil, M., Appleyard, J., and de Freitas, N. Acdc: A structured efficient linear layer. *ICLR*, 2016.
- Nash, C., Menick, J., Dieleman, S., and Battaglia, P. Generating images with sparse representations. In *ICML*, pp. 7958–7968. PMLR, 2021.
- Ning, M., Sangineto, E., Porrello, A., Calderara, S., and Cucchiara, R. Input perturbation reduces exposure bias in diffusion models. In *ICML*, pp. 26245–26265. PMLR, 2023.
- Pan, H., Hamdan, E., Zhu, X., Biswas, K., Cetin, A., and Bagci, U. Dct-based decorrelated attention for vision transformers. *arXiv preprint arXiv:2405.13901*, 2024.
- Peebles, W. and Xie, S. Scalable diffusion models with transformers. In *ICCV*, pp. 4195–4205, 2023.
- Polyak, A., Zohar, A., Brown, A., Tjandra, A., Sinha, A., Lee, A., Vyas, A., Shi, B., Ma, C.-Y., Chuang, C.-Y., et al. Movie gen: A cast of media foundation models. *arXiv preprint arXiv:2410.13720*, 2024.
- Poole, B., Jain, A., Barron, J. T., and Mildenhall, B. Dreamfusion: Text-to-3d using 2d diffusion. *arXiv*, 2022.
- Pratt, H., Williams, B., Coenen, F., and Zheng, Y. Fcnn: Fourier convolutional neural networks. In *Machine Learning and Knowledge Discovery in Databases: European Conference, ECML PKDD 2017, Skopje, Macedonia, September 18–22, 2017, Proceedings, Part I 17*, pp. 786– 798. Springer, 2017.
- Ramesh, A., Dhariwal, P., Nichol, A., Chu, C., and Chen, M. Hierarchical text-conditional image generation with clip latents. *arXiv preprint arXiv:2204.06125*, 2022.
- Rao, K. R. and Yip, P. *Discrete cosine transform: algorithms, advantages, applications*. Academic press, 2014.
- Redmon, J. You only look once: Unified, real-time object detection. In *CVPR*, 2016.
- Rombach, R., Blattmann, A., Lorenz, D., Esser, P., and Ommer, B. High-resolution image synthesis with latent diffusion models. In *CVPR*, pp. 10684–10695, 2022.
- Ronneberger, O., Fischer, P., and Brox, T. U-net: Convolutional networks for biomedical image segmentation. In *Medical image computing and computer-assisted intervention–MICCAI 2015: 18th international conference, Munich, Germany, October 5-9, 2015, proceedings, part III 18*, pp. 234–241. Springer, 2015.
- Ruderman, D. L. Origins of scaling in natural images. *Vision research*, 37(23):3385–3398, 1997.
- Sabour, A., Fidler, S., and Kreis, K. Align your steps: Optimizing sampling schedules in diffusion models. In *ICML*, 2022.
- Salimans, T. and Ho, J. Progressive distillation for fast sampling of diffusion models. In *ICLR*, 2022.
- Scribano, C., Franchini, G., Prato, M., and Bertogna, M. Dct-former: Efficient self-attention with discrete cosine transform. *Journal of Scientific Computing*, 94(3):67, 2023.
- Simonyan, K. and Zisserman, A. Two-stream convolutional networks for action recognition in videos. *NeurIPS*, 27, 2014.
- Sindhwani, V., Sainath, T., and Kumar, S. Structured transforms for small-footprint deep learning. *NeurIPS*, 28, 2015.
- Sohl-Dickstein, J., Weiss, E., Maheswaranathan, N., and Ganguli, S. Deep unsupervised learning using nonequilibrium thermodynamics. In *ICML*, pp. 2256–2265. PMLR, 2015.
- Song, J., Meng, C., and Ermon, S. Denoising diffusion implicit models. *ICLR*, 2021a.
- Song, Y. and Ermon, S. Generative modeling by estimating gradients of the data distribution. *NeurIPS*, 32, 2019.
- Song, Y., Sohl-Dickstein, J., Kingma, D. P., Kumar, A., Ermon, S., and Poole, B. Score-based generative modeling through stochastic differential equations. In *ICLR*, 2021b.
- Song, Y., Dhariwal, P., Chen, M., and Sutskever, I. Consistency models. In *ICML*, pp. 32211–32252. PMLR, 2023.
- Tamkin, A., Jurafsky, D., and Goodman, N. Language through a prism: A spectral approach for multiscale language representations. *NeurIPS*, 33:5492–5504, 2020.
- Tian, K., Jiang, Y., Yuan, Z., Peng, B., and Wang, L. Visual autoregressive modeling: Scalable image generation via next-scale prediction. *NeurIPS*, 2024.
- Turiel, A. and Parga, N. The multifractal structure of contrast changes in natural images: From sharp edges to textures. *Neural Computation*, 12(4):763–793, 2000. doi: 10.1162/089976600300015583.
- Vincent, P. A connection between score matching and denoising autoencoders. *Neural computation*, 23(7):1661– 1674, 2011.
- Wallace, G. K. The jpeg still picture compression standard. *Communications of the ACM*, 34(4):30–44, 1991.
- Wu, Y., AbdAlmageed, W., and Natarajan, P. Mantra-net: Manipulation tracing network for detection and localization of image forgeries with anomalous features. In *CVPR*, pp. 9543–9552, 2019.
- Xu, Y., Liu, Z., Tegmark, M., and Jaakkola, T. Poisson flow generative models. In *NeurIPS*, pp. 16782–16795, 2022.
- Xue, S., Yi, M., Luo, W., Zhang, S., Sun, J., Li, Z., and Ma, Z.-M. Sa-solver: Stochastic adams solver for fast sampling of diffusion models. *NeurIPS*, 36, 2024.
- Zhang, J., Lin, Y., Song, Z., and Dhillon, I. Learning long term dependencies via fourier recurrent units. In *ICML*, pp. 5815–5823. PMLR, 2018.
- Zhou, B., Lapedriza, A., Khosla, A., Oliva, A., and Torralba, A. Places: A 10 million image database for scene recognition. *TPAMI*, 40(6):1452–1464, 2017.
- Zhou, Z., Chen, D., Wang, C., and Chen, C. Fast ode-based sampling for diffusion models in around 5 steps. In *CVPR*, pp. 7777–7786, 2024.
- Zhu, Z. and Soricut, R. Wavelet-based image tokenizer for vision transformers. *arXiv preprint arXiv:2405.18616*, 2024.

A. Appendix

A.1. Naive Scaling and Entropy-Consistent Scaling

We show the bounds of Naive Scaling and Entropy-Consistent Scaling in Algorithm [1](#page-11-2) and Algorithm [2.](#page-11-3) Given a dataset, we randomly draw 50,000 images and convert each image into DCT blocks $\left\{\bm{D}_{\bm{y}}^{}\right\}_{i=1}^{4N}, \left\{\bm{D}_{\bm{c}\bm{b}}^{}\right\}_{i=1}^{N}, \left\{\bm{D}_{\bm{c}\bm{r}}^{}\right\}_{i=1}^{N}.$ The total Y blocks $D_y\in\mathbb{R}^{200000N\times B^2}$, Cb blocks $D_{cb}\in\mathbb{R}^{50000N\times B^2}$, and Cr blocks $D_{cr}\in\mathbb{R}^{50000N\times B^2}$ are used for Monte Carlo estimation of the bounds $(\bar{\eta})$ of Naive Scaling. We use only Y blocks $D_y \in \mathbb{R}^{200000N \times B^2}$ to estimate the bound (η) of Entropy-Consistent Scaling given block size B and percentile τ .

In Figure [3,](#page-11-4) we illustrate the difference between applying Naive Scaling and Entropy-Consistent Scaling using $B = 2$ and $\tau = 97$ on CelebA 64 dataset. The first row of Figure [3](#page-11-4) displays the distributions of DCT coefficients $(D(0,0), D(0,1), D(1,0), D(1,1))$ before scaling. It is clear that Naive Scaling increases the entropy of the original distributions of $D(0, 1)$, $D(1, 0)$ and $D(1, 1)$ while Entropy-Consistent Scaling preserves the entropy.

Figure 3. Histograms of DCT coefficients before scaling and after Naive Scaling and Entropy-Consistent Scaling.

A.2. SNR Scaling in Continuous-time and Discrete-time Diffusion Models

A.2.1. SNR SCALING IN CONTINUOUS-TIME DIFFUSION MODELS

Following UViT [\(Bao et al.,](#page-8-22) [2023\)](#page-8-22), we use VP-SDE for the continuous-time diffusion model which has the forward perturbation kernel:

$$
\mathcal{N}(\mathbf{\bar{x}}_t;\mathbf{\bar{x}}_0e^{-\frac{1}{2}\int_0^t\beta(s)\mathrm{d}s}, \mathbf{I}-\mathbf{I}e^{-\int_0^t\beta(s)\mathrm{d}s})
$$

The noise schedule $\beta(t) = at + b$ and a, b are constants (usually $a = 0.1$ and $b = 19.9$), so that $\int_0^t \beta(s) ds = at + 0.5bt^2$. The SNR at time t is denoted as:

$$
SNR(t) = \frac{e^{-\int_0^t \beta(s)ds}}{1 - e^{-\int_0^t \beta(s)ds}} = \frac{e^{-(at + 0.5bt^2)}}{1 - e^{-(at + 0.5bt^2)}}
$$
(13)

The goal of SNR Scaling is to have the new $SNR'(t)$ such that

$$
SNR'(t) = c \times SNR(t) \tag{14}
$$

where $c \in \mathbb{R}$ is the introduced factor of SNR Scaling. Given c, we need to derive the new noise schedule $\beta'(t; c)$ for practical implementation. Let $y = \int_0^t \beta(s) ds = at + 0.5bt^2$ and $y' = \int_0^t \beta'(s) ds$, Eq. [\(14\)](#page-12-0) becomes

$$
c\frac{e^{-y}}{1 - e^{-y}} = \frac{e^{-y'}}{1 - e^{-y'}}
$$
 (15)

from which, we derive

$$
e^{-y'} = c \frac{e^{-y}}{1 + (c - 1)e^{-y}}
$$
 (16)

Taking the logarithm of both sides of Eq. (eq: SNR 4) yields

$$
y' = y - \ln c + \ln[1 + (c - 1)e^{-y}]
$$
\n(17)

$$
= at + 0.5bt2 - \ln c + \ln[1 + (c - 1)e^{-(at + 0.5bt2)}]
$$
\n(18)

Take the derivative of Eq. [\(18\)](#page-12-1) w.r.t t, we obtain the new noise schedule $\beta'(t)$

$$
\beta'(t;c) = a + bt + \frac{(c-1)e^{-(at+0.5bt^2)}(-a - bt)}{1 + (c-1)e^{-(at+0.5bt^2)}}
$$
\n(19)

In the code implementation, we apply Eq. [\(19\)](#page-12-2) as the noise schedule to replace the original $\beta(t) = a + bt$. When the scaling factor $c = 1$, Eq. [\(19\)](#page-12-2) degrades to $\beta(t)$.

SNR Scaling for DPM-Solver. In addition to applying $\beta'(t)$, we need to update the inverse function of $\lambda(t)$ defined in DPM-Solver [\(Lu et al.,](#page-9-5) [2022\)](#page-9-5) if we want to use it for sampling. The original $\lambda(t)$ is

$$
\lambda(t) = 0.5 \log(SNR(t))\tag{20}
$$

Now, given the updated $SNR'(t)$, we need to solve t from $\lambda(t) = 0.5 \log(SNR'(t))$.

$$
\lambda = 0.5 \log(SNR'(t))\tag{21}
$$

$$
2\lambda = \log\left[\frac{e^{-y'}}{1 - e^{-y'}}\right] \tag{22}
$$

$$
e^{2\lambda} = \frac{e^{-y'}}{1 - e^{-y'}}
$$
 (23)

$$
e^{-y'} = \frac{e^{2\lambda}}{1 + e^{2\lambda}}\tag{24}
$$

$$
y' = \ln[\frac{1 + e^{2\lambda}}{e^{2\lambda}}]
$$
 (25)

Plugging Eq. [\(18\)](#page-12-1) into Eq. [\(25\)](#page-12-3), we get

DCTdiff: Intriguing Properties of Image Generative Modeling in the DCT Space

$$
at + 0.5bt2 - \ln c + \ln[1 + (c - 1)e^{-(at + 0.5bt2)}] = \ln[\frac{1 + e^{2\lambda}}{e^{2\lambda}}]
$$
\n(26)

$$
e^{at+0.5bt^2}[1+(c-1)e^{-(at+0.5bt^2)}] = \frac{c(1+e^{2\lambda})}{e^{2\lambda}}
$$
\n(27)

$$
e^{at+0.5bt^2} + (c-1) = \frac{c(1+e^{2\lambda})}{e^{2\lambda}} \tag{28}
$$

$$
at + 0.5bt^2 = \ln\left[\frac{c(1 + e^{2\lambda})}{e^{2\lambda}} + 1 - c\right]
$$
 (29)

$$
t = \frac{-a + \sqrt{a^2 + 2b \ln[\frac{c(1 + e^{2\lambda})}{e^{2\lambda}} + 1 - c]}}{b}
$$
(30)

In practice, we apply Eq. [\(30\)](#page-13-1) to update the inverse function of $\lambda(t)$. When the scaling factor $c = 1$, Eq. (30) degrades to the original inverse function $t = \frac{-a + \sqrt{a^2 + 2b \ln[\frac{1+e^{2\lambda}}{e^{2\lambda}}]}}{b}$ $rac{1}{b}$ $e^{2\lambda}$.

A.2.2. SNR SCALING IN DISCRETE-TIME DIFFUSION MODELS

Following DDPM [\(Ho et al.,](#page-8-5) [2020\)](#page-8-5) and DiT [\(Peebles & Xie,](#page-9-8) [2023\)](#page-9-8), the forward perturbation kernel is

$$
\mathcal{N}(\bar{\mathbf{x}}_t; \sqrt{\bar{\alpha}_t} \bar{\mathbf{x}}_0, (1 - \bar{\alpha}_t) \mathbf{I})
$$
\n(31)

where $\bar{\alpha}_t = \prod_{s=0}^t \alpha_s$ and $\alpha_t = 1 - \beta_t$. So that the original SNR at time t is

$$
SNR(t) = \frac{\bar{\alpha}_t}{1 - \bar{\alpha}_t} \tag{32}
$$

From which, we obtain $\bar{\alpha}_t = \frac{SNR(t)}{SNR(t)+1}$. Now, scale the SNR by c, we have the updated signal schedule $\bar{\alpha}_t$

$$
\bar{\alpha_t}' = \frac{c \times SNR(t)}{c \times SNR(t) + 1} \tag{33}
$$

Given the updated signal schedule $\bar{\alpha_t}'$, we could iteratively solve α'_t and β'_t , and use β'_t for the implementation of SNR Scaling.

A.3. Image Diffusion Is Spectral Autoregression

In this section, we discuss how the data information changes during the diffusion process of a diffusion model with the initial data being x_0 and the data evolving into x_t . For simplicity, we consider the scalar case of the diffusion process, since the original image diffusion is isotropic. Concretely, the forward diffusion SDE is

$$
dx_t = f(x_t, t)dt + g(t)dw_t,
$$
\n(34)

where $t \in [0, T]$, $T > 0$ is a constant, $f(\cdot, \cdot)$ and $g(\cdot, \cdot)$ are the drift and diffusion coefficients respectively, and w_t defines the standard Wiener process. We transform the image signal x_t into $\hat{x}_t(\omega)$ using the Fourier transform. Here, ω represents the frequency. Thus, during the forward diffusion process, the signal x_t can be represented in integral form as

$$
x_t = x_0 + \int_0^t g(s) \mathrm{d}w_s \tag{35}
$$

if $f(\cdot, \cdot) = 0$. After applying the Fourier transform, Eq. [\(35\)](#page-13-2) becomes $\hat{x}_t(\omega) = \hat{x}_0(\omega) + \hat{\epsilon}_t(\omega)$ where $\epsilon_t(\omega)$ is the Fourier transform of the Gaussian noise term. Obviously, the mean value $\mathbb{E}[\hat{\epsilon}_t(\omega)] = 0$. We now prove that $\mathbb{E}[\hat{\epsilon}_t(\omega)|^2] =$ $\int_0^t |g(s)|^2 ds$. Consider the Fourier transform of $\epsilon_t(x)$:

$$
\hat{\epsilon}_t(\omega) = \int_{-\infty}^{\infty} e^{-i\omega x} \epsilon_t(x) dx \tag{36}
$$

Since $\epsilon_t(x)$ is a random process with zero mean, its Fourier transform $\hat{\epsilon}_t(\omega)$ is also a random variable with zero mean.

Calculate the variance of $\hat{\epsilon}_t(\omega)$:

$$
\mathbb{E}[|\hat{\epsilon}_t(\omega)|^2] = \mathbb{E}\left[\left|\int_{-\infty}^{\infty} e^{-i\omega x} \epsilon_t(x) dx\right|^2\right]
$$
\n(37)

Expand the square of the modulus:

$$
\mathbb{E}\left[|\hat{\epsilon}_t(\omega)|^2\right] = \mathbb{E}\left[\int_{-\infty}^{\infty} e^{-i\omega x} \epsilon_t(x) dx \int_{-\infty}^{\infty} e^{i\omega y} \epsilon_t(y) dy\right]
$$

$$
= \int_{-\infty}^{\infty} \int_{-\infty}^{\infty} e^{-i\omega(x-y)} \mathbb{E}\left[\epsilon_t(x)\epsilon_t(y)\right] dx dy.
$$
(38)

Since $\epsilon_t(x)$ is spatially uncorrelated, we have

$$
\mathbb{E}[\epsilon_t(x)\epsilon_t(y)] = \begin{cases} \int_0^t |g(s)|^2 ds, & \text{when } x = y \\ 0, & \text{when } x \neq y \end{cases}
$$
 (39)

This can be expressed as:

$$
\mathbb{E}[\epsilon_t(x)\epsilon_t(y)] = \left(\int_0^t |g(s)|^2 ds\right) \delta(x-y). \tag{40}
$$

where $\delta(.)$ is the Dirac delta function. Substitute Eq. [\(40\)](#page-14-0) into Eq. [\(38\)](#page-14-1):

$$
\mathbb{E}[|\hat{\epsilon}_t(\omega)|^2] = \left(\int_0^t |g(s)|^2 ds\right) \int_{-\infty}^{\infty} \int_{-\infty}^{\infty} e^{-i\omega(x-y)} \delta(x-y) dx dy
$$

$$
= \left(\int_0^t |g(s)|^2 ds\right) \int_{-\infty}^{\infty} e^{-i\omega(x-x)} dx
$$

$$
= \left(\int_0^t |g(s)|^2 ds\right) \int_{-\infty}^{\infty} dx.
$$
 (41)

The integral $\int_{-\infty}^{\infty} dx$ means the integration region is infinite. In practice, we usually consider a finite spatial range or normalize the density. For simplicity, we consider a unit-length spatial range so that the integration result is 1, leading to

$$
\mathbb{E}[|\hat{\epsilon}_t(\omega)|^2] = \int_0^t |g(s)|^2 ds \tag{42}
$$

Then, we calculate the power density of various signals during the diffusion process. The power spectral density of signal x_t is $S_{x_t}(\omega) = \mathbb{E}\left[|\hat{x}_t(\omega)|^2 \right]$. After expansion, we obtain

$$
S_{x_t}(\omega) = |\hat{x}_0(\omega)|^2 + 2\Re\mathbf{e} \left(\hat{x}_0(\omega) \mathbb{E} \left[\hat{\epsilon}_t^*(\omega) \right] \right) + \mathbb{E} \left[\left| \hat{\epsilon}_t(\omega) \right|^2 \right]
$$

\n
$$
= |\hat{x}_0(\omega)|^2 + 2\Re\mathbf{e} \left(\hat{x}_0(\omega) \cdot 0 \right) + \mathbb{E} \left[\left| \hat{\epsilon}_t(\omega) \right|^2 \right]
$$

\n
$$
= |\hat{x}_0(\omega)|^2 + \mathbb{E} \left[\left| \hat{\epsilon}_t(\omega) \right|^2 \right].
$$
\n(43)

Since $\mathbb{E} [\hat{\epsilon}_t(\omega)] = 0$ and the cross term $[2\Re(\hat{x}_0(\omega)\mathbb{E} [\hat{\epsilon}_t^*(\omega)]) = 0$, we have

$$
S_{x_t}(\omega) = |\hat{x}_0(\omega)|^2 + \mathbb{E}\left[|\hat{\epsilon}_t(\omega)|^2\right]
$$
\n(44)

where $\mathbb{E}\left[|\hat{\epsilon}_t(\omega)|^2\right] = \int_0^t |g(s)|^2 ds$, which completes the proof of Theorem [5.1.](#page-5-3)

Moreover, we can evaluate how much information is damaged during the forward diffusion process through the SNR perspective. A higher SNR implies that the signal is relatively purer and the degree of damage it undergoes is lower. On the contrary, a lower SNR indicates that the noise has a greater impact on the signal and the degree of information damage is also higher. Consequently, the SNR ratio can intuitively reflect the noise level contaminating the information during the forward diffusion SDE. The SNR can be expressed as

$$
SNR(\omega) = \frac{|\hat{\mathbf{x}}_0(\omega)|^2}{\mathbb{E}[|\hat{\boldsymbol{\epsilon}}_t(\omega)|^2]} = \frac{|\hat{\mathbf{x}}_0(\omega)|^2}{\int_0^t |g(s)|^2 ds}
$$
(45)

We find that the change of SNR with frequency ω is completely determined by the power spectral density $|x_0(\omega)|^2$ of the initial signal, while the noise power is the same at all frequencies.

For natural images, it is generally the case that they possess low-pass characteristics. Moreover, their power spectra typically conform to a power-law distribution [\(Turiel & Parga,](#page-10-17) [2000\)](#page-10-17)), which can be expressed as $|\hat{x}_0(\omega)|^2 \propto |\omega|^{-\alpha}$, where $\alpha > 0$ denotes the spectral attenuation degree of the signal. Therefore, as the frequency ω increases, $|\hat{x}_0(\omega)|^2$ decreases rapidly. This indicates that SNR(ω) is low at high frequencies. As the diffusion time t increases, the denominator $\int_0^t |g(s)|^2 ds$ increases, leading to an overall decrease in the SNR.

Given an SNR threshold γ and a frequency ω , the time $t_{\gamma}(\omega)$ when the SNR reaches the threshold γ satisfies:

$$
SNR(\omega) = \frac{|\omega|^{-\alpha}}{\int_0^{t_\gamma(\omega)} |g(s)|^2 ds} = \gamma
$$
\n(46)

From this we can solve $t_{\gamma}(\omega)$ to obtain the exact time required to reach SNR(ω) = γ . The right-side image of Figure [4](#page-15-2) provides the illustrations of Eq. [\(46\)](#page-15-3).

Figure 4. Relationship between frequency ω and SNR

A.4. Averaged Power Spectral Density in DCT space

[Dieleman](#page-8-24) [\(2024\)](#page-8-24) uses the radially averaged power spectral density (RAPSD) to analyze the frequency of images in Fourier space. Similarly, given the diffusion perturbation kernel $\mathcal{N}(\bm{x}_t; \bm{x}_0e^{-\frac{1}{2}\int_0^t \beta(s)ds}, I - Ie^{-\int_0^t \beta(s)ds})$, we calculate the averaged power spectral density (APSD) for a clear image x_0 , the noisy image x_t and the isotropic Gaussian noise ϵ_t $(\epsilon_t =$ $\sqrt{1 - e^{-\int_0^t \beta(s) ds}})$, where $\epsilon \sim \mathcal{N}(0, I)$). We use the Monte-Carlo method to estimate the APSD of x_0, x_t and ϵ_t , respectively with 50,000 samples from the FFHQ 256×256 dataset. Figure [5](#page-16-0) shows the APSD curves at different times. Similar to the RAPSD figures under the Fourier transform in [Dieleman](#page-8-24) [\(2024\)](#page-8-24), APSD also shows a pattern of frequency autoregression.

A.5. Proof of DCT Upsampling Theorem

Consider a high-resolution image (e.g. 256 \times 256) that consists of pixel blocks and each block is denoted as $A \in \mathbb{R}^{2B \times 2B}$, then a low-resolution (e.g. 128×128) image is derived from the average pooling of the 256×256 image and each pixel

Figure 5. The averaged power spectral density (APSD) of x_0 , x_t and the noise ϵ_t in the DCT space at time $t = t'/1000$.

block is denoted as $\bar{A} \in \mathbb{R}^{B \times B}$. In this case, these two images have the same number of DCT blocks. Let $D \in \mathbb{R}^{2B \times 2B}$ be the DCT block converted from $\bm{A} \in \mathbb{R}^{2B \times 2B}$ and $\bm{\bar{D}} \in \mathbb{R}^{B \times B}$ be the DCT block converted from $\bm{\bar{A}} \in \mathbb{R}^{B \times B}$. According to Eq. (5) , we have

$$
D(u,v) = \sqrt{\frac{2}{2B}} \sqrt{\frac{2}{2B}} \sum_{x=0}^{2B-1} \sum_{y=0}^{2B-1} A(x,y) \cos\left[\frac{(2x+1)u\pi}{4B}\right] \cos\left[\frac{(2y+1)v\pi}{4B}\right]
$$
(47)

$$
\bar{D}(u,v) = \sqrt{\frac{2}{B}} \sqrt{\frac{2}{B}} \sum_{i=0}^{B-1} \sum_{j=0}^{B-1} \bar{A}(i,j) \cos\left[\frac{(2i+1)u\pi}{2B}\right] \cos\left[\frac{(2j+1)v\pi}{2B}\right]
$$
(48)

where $D(u, v)$ is an element of \bar{D} and $\bar{D}(u, v)$ is an element of \bar{D} , respectively. Since $\bar{A} \in \mathbb{R}^{B \times B}$ is the average pooling of $A \in \mathbb{R}^{2B \times 2B}$, we have

$$
\bar{A}(i,j) = \frac{1}{4} \sum_{m=0}^{1} \sum_{n=0}^{1} A(2i+m, 2j+n).
$$
\n(49)

Plug Eq. [\(49\)](#page-16-1) into Eq. [\(48\)](#page-16-2), we obtain

$$
\bar{D}(u,v) = \sqrt{\frac{2}{B}} \sqrt{\frac{2}{B}} \sum_{i=0}^{B-1} \sum_{j=0}^{B-1} \frac{1}{4} \sum_{m=0}^{1} \sum_{n=0}^{1} A(2i+m, 2j+n) \cos\left[\frac{(2i+1)u\pi}{2B}\right] \cos\left[\frac{(2j+1)v\pi}{2B}\right]
$$
(50)

Apply change of variable $x = 2i + m$ and $y = 2j + n$, Eq. [\(50\)](#page-16-3) becomes

Figure 6. The forward perturbation process of RGB and DCT using the same forward SDE $dx_t = f(x_t, t)dt + g(t)dw_t$.

$$
\bar{D}(u,v) = \frac{1}{2B} \sum_{x=0}^{2B-1} \sum_{y=0}^{2B-1} A(x,y) \sum_{m=0}^{1} \cos\left[\frac{(x-m+1)u\pi}{2B}\right] \sum_{n=0}^{1} \cos\left[\frac{(y-n+1)v\pi}{2B}\right]
$$
(51)

$$
= \frac{1}{2B} \sum_{x=0}^{2B-1} \sum_{y=0}^{2B-1} A(x,y) \left(\underbrace{\cos\left[\frac{(x+1)u\pi}{2B}\right]}_{m=0} + \underbrace{\cos\left[\frac{xu\pi}{2B}\right]}_{m=1} \right) \left(\underbrace{\cos\left[\frac{(y+1)v\pi}{2B}\right]}_{n=0} + \underbrace{\cos\left[\frac{yv\pi}{2B}\right]}_{n=1} \right) \tag{52}
$$

However, since $i = \frac{x-m}{2}$ is an integer when applying the change of variable, x and m must both be odd or both be even (the same applies to y and n). Therefore, for any x, y in Eq. [\(52\)](#page-17-1), only one term exists within each of the two big parentheses. An approximation can be obtained by taking the average of the two cosine terms within each bracket, which gives

$$
\bar{D}(u,v) \approx \frac{1}{2B} \sum_{x=0}^{2B-1} \sum_{y=0}^{2B-1} A(x,y) \frac{1}{2} \left(\cos \left[\frac{(x+1)u\pi}{2B} \right] + \cos \left[\frac{xu\pi}{2B} \right] \right) \frac{1}{2} \left(\cos \left[\frac{(y+1)v\pi}{2B} \right] + \cos \left[\frac{yv\pi}{2B} \right] \right) \tag{53}
$$

$$
= \frac{1}{2B} \sum_{x=0}^{2B-1} \sum_{y=0}^{2B-1} A(x,y) \left(\cos \left[\frac{(2x+1)u\pi}{4B} \right] \cos \left[\frac{u\pi}{4B} \right] \right) \left(\cos \left[\frac{(2y+1)v\pi}{4B} \right] + \cos \left[\frac{v\pi}{4B} \right] \right) \tag{54}
$$

$$
=\frac{1}{2B}\cos\left[\frac{u\pi}{4B}\right]\cos\left[\frac{v\pi}{4B}\right]\sum_{x=0}^{2B-1}\sum_{y=0}^{2B-1}A(x,y)\cos\left[\frac{(2x+1)u\pi}{4B}\right]\cos\left[\frac{(2y+1)v\pi}{4B}\right]
$$
(55)

From Eq. [\(53\)](#page-17-2) to Eq. [\(54\)](#page-17-3) we apply the trigonometric formulas

$$
\cos(A) + \cos(B) = 2\cos(\frac{A+B}{2})\cos(\frac{A-B}{2})
$$

Now comparing Eq. [\(55\)](#page-17-4) with Eq. [\(47\)](#page-16-4), we obtain

$$
\bar{D}(u,v) \approx \frac{1}{2}\cos\left[\frac{u\pi}{4B}\right]\cos\left[\frac{v\pi}{4B}\right]D(u,v)
$$
\n(56)

which completes the proof of Theorem [5.2.](#page-6-1)

A.6. Training Parameters of UViT, DiT and DCTdiff

We list the model and training parameters in Table [6](#page-18-3) and Table [7](#page-18-4) where the former compares UViT and DCTdiff (inherited from UViT) and the latter compares DiT and DCTdiff (inherited from DiT). We use the default training settings from UViT and DiT without any change.

Dataset	Model		Transformer parameters		Learning parameters	DCTdiff parameters			
		# parameters	patch size	# tokens	batch size	learning rate	τ	m^*	\mathfrak{c}
CIFAR-10	UV_iT DCTdiff	130M 130M	4 4	64 64	256 256	0.0002 0.0002	96.5	Ω	2
CelebA ₆₄	UV_iT DCTdiff	44M 44M	4 4	256 256	256 256	0.0002 0.0002	96.5	Ω	4
ImageNet 64	UV_iT DCTdiff	44M 44M	4 4	256 256	1024 1024	0.0003 0.0003	96.5	Ω	4
FFHO 128	UViT DCTdiff	44M 44M	8 8	256 256	256 256	0.0002 0.0002	96.5	7	3
FFHO 256	$UViT$ (latent) DCTdiff	130M 130M	\overline{c} 8	256 1024	256 256	0.0002 0.0002	96.5	8	

Table 7. Training and network parameters of DiT and DCTdiff on different datasets.

B. Ablation Study

In this section, we elaborate on the effect of each design factor of DCTdiff using the dataset FFHQ 128×128 and the base model UViT. We report the FID-10k using DPM-solver throughout the ablation section. Table [8](#page-19-3) presents the ablation results and the first row shows FID-10k achieved by UViT during training. We then gradually added each design element to the previous base model to examine the design space of DCTdiff:

- UViT (YCbCr) inherits from UViT and replaces the RGB pixel inputs with YCbCr inputs.
- DCTdiff (ECS) integrates the DCT transformation and Entropy-Consistent Scaling into UViT (YCbCr).
- DCTdiff (EBFR) adds Entropy-Based Frequency Reweighting on DCTdiff (ECS).
- DCTdiff (SNR) incorporates the SNR Scaling based on DCTdiff (EBFR)

B.1. Ablation Study: YCbCr Accelerates the Diffusion Training

To evaluate the effect of YCbCr color space transformation in DCTdiff, we substitute the RGB inputs with YCbCr (2x chroma subsampling) input. The corresponding results are shown in the second row of Table [8,](#page-19-3) indicating that YCbCr with chroma subsampling dramatically accelerates the diffusion training but at the cost of generative quality (FID-10k increases from 10.58 to 14.79). We believe the chroma subsampling provides the training acceleration but the reduced color redundancy causes the drop of generation quality.

DCTdiff: Intriguing Properties of Image Generative Modeling in the DCT Space

Model	Training steps													
	100k	150k	200k	250k	300 _k	350k	400k	450k	500 _k	550 _k	600 _k	650k	700k	750 _k
UViT	70.67	40.64	24.72	17.88	14.73	13.65	12.64	12.10	11.27	11.17	11.02	10.84	10.58	10.60
UViT (YCbCr)	17.70	14.79	16.38	$\overline{}$	۰									
DCTdiff (ECS)	14.11	12.42	10.81	10.24	9.75	9.76	$\overline{}$							
DCTdiff (EBFR)	22.21	10.78	10.18	9.61	9.22	9.34	$\overline{}$						۰	
DCTdiff (SNR, $c = 2$)	13.14	9.55	9.01	8.87	8.31	8.35	\sim				$\overline{}$		۰	
DCTdiff (SNR, $c = 3$)	12.46	10.52	8.56	7.91	7.77	7.88	$\overline{}$							
DCTdiff (SNR, $c = 4$)	12.55	10.45	8.56	7.99	7.89	7.94	$\overline{}$			۰	$\overline{}$		۰	

Table 8. Ablation study of DCTdiff design factors: FID-10k of UViT and DCTdiff during training.

B.2. Ablation Study: Entropy-Consistent Scaling

As we mentioned in Section [4.4,](#page-3-2) Entropy-Consistent Scaling (ECS) is a key factor making the DCT generative modeling effective. In detail, DCTdiff (ECS) not only enjoys the training acceleration benefit of YCbCr subsampling, but also yields a better generative quality than the base model UViT (see Table [8\)](#page-19-3). We attribute the improvement of generation quality to the DCT space where low-frequency coefficients occupy the majority of image information. Note that DCTdiff (ECS) uses block size $B = 4$ and $m^* = 8$, the ablation study of m^* is detailed in Section [B.5.](#page-19-4)

B.3. Ablation Study: Entropy-Based Frequency Reweighting

In Section [5.1,](#page-4-0) we highlight the frequency prioritization property of DCT image modeling in which some frequency coefficients can be modeled preferentially according to the task prior knowledge. We adopt the Entropy-Based Frequency Reweighting (EBFR) for image generative modeling tasks as low-frequency coefficients have large entropy and contribute more to the visual quality of images than high-frequency signals. Row 3 and Row 4 in Table [8](#page-19-3) demonstrate that EBFR improves the generative quality of DCTdiff without affecting the training convergence.

B.4. Ablation Study: SNR Scaling of Noise Schedule

Since the block size B affects the forward perturbation process of DCTdiff (detailed in Section [4.5\)](#page-4-1), we propose SNR Scaling for DCTdiff to scale the noise schedule of UViT by a constant c. Table [8](#page-19-3) shows that SNR Scaling significantly improves the generative quality of DCT diff and a wide range of parameter c can yield the improvement. We also visualize the effect of c in the perturbation process of DCTdiff in Figure [7](#page-19-5) where the image size is 128×128 and the block size is 4.

Figure 7. Visualization of the forward SDE process. UViT and DCTdiff $(c = 1)$ share the same noise schedule while DCTdiff $(c = 3)$ scales up the noise schedule by the factor 3.

B.5. Ablation Study: Eliminating m High-frequency Coefficients

In Table [9,](#page-20-1) we show the effect of eliminating m high-frequency coefficients in each DCT block with block size 4 on the dataset FFHQ 128×128 . $m = 0$ refers to maintaining all coefficients for diffusion training and sampling. It is clear from Table [9](#page-20-1) that ignoring a suitable amount of high-frequency signals increases the generative modeling and the optimal m is decided via Eq. [\(6\)](#page-3-3).

DCTdiff: Intriguing Properties of Image Generative Modeling in the DCT Space

Model		Training steps												
	100k	150k	200k	250k	300k	350k	400k	450k	500 _k	550 _k	600k	650k	700k	750 _k
UViT	70.67	40.64	24.72	17.88	14.73	13.65	12.64	12.10	11.27	11.17	11.02	10.84	10.58	10.60
DCTdiff $(m = 0)$	66.79	11.83	12.75	12.03	11.21	10.89	10.92	۰	$\overline{}$	$\overline{}$	-	$\overline{}$		
DCTdiff $(m = 8)$	22.21	10.78	10.18	9.61	9.22	9.34	$\overline{}$	\sim	$\overline{}$	$\overline{}$	۰	$\overline{}$		
DCTdiff $(m = 9)$	41.18	12.09	10.20	9.95	9.80	9.52	9.56	۰	$\overline{}$	$\overline{}$	۰	$\overline{}$		

Table 9. Ablation study of m in DCTdiff: FID-10k of UViT and DCTdiff during training on the dataset FFHQ 128 \times 128.

C. Qualitative Results

C.1. Qualitative Comparision between VAE Compression and DCT Compression

We randomly sample several images from ImageNet 256×256 dataset, then we perform VAE compression (16x compression ratio) and DCT compression (4x compression ratio). The reconstructed images after compression are shown in Figure [8.](#page-20-0) From this, we clearly see that VAE compression loses image details and local image structure while DCT compression maintains most of the image information. Also, we find that VAE compression is not good at reconstructing letters, digital numbers, and unseen images (not trained by VAE). In contrast, DCT compression is insensitive to image domains and performs consistently well reconstruction.

Figure 8. Qualitative comparison between VAE compression and DCT compression. The first row shows the raw images (sampled from ImageNet 256×256). The second and third rows present the reconstructed images after VAE compression (16x) and DCT compression (4x), respectively.

C.2. Qualitative Results of DCTdiff

We show the qualitative results of DCTdiff in Figure [9](#page-21-0) and Figure [10.](#page-21-1) The images are generated by DPM-Solver using NFE 50.

Figure 9. Images samples generated by DCTdiff trained on the dataset FFHQ 128×128 (FID= 6.70).

Figure 10. Images samples generated by DCTdiff trained on the dataset FFHQ 256×256 (FID= 6.06).

C.3. Qualitative Results of DCT Upsampling

(b) 128×128 (downsampled from 256×256)

(a) 256×256 (ground truth)

(c) 256×256 (Pixel Upsampling) (d) 256×256 (DCT Upsampling)

Figure 11. Comparison between Pixel Upsampling and our proposed DCT Upsampling. [11\(c\)](#page-22-1) and [11\(d\)](#page-22-2) are upsampled based on [11\(b\).](#page-22-3)