Tokenisation is NP-Complete

Philip Whittington, Gregor Bachmann, Tiago Pimentel Department of Computer Science, ETH Zürich {philip.whittington, gregor.bachmann, tiago.pimentel}@inf.ethz.ch

Abstract

In this work, we prove the NP-completeness of two variants of tokenisation, defined as the problem of compressing a dataset to at most δ symbols by either finding a vocabulary directly (*direct* tokenisation), or selecting a sequence of merge operations (*bottom-up* tokenisation).

1 Introduction

Tokenisation is at the heart of natural language processing (NLP) being the first step required to use a language model (LM). Given a string of characters c, a tokeniser converts it into a string of **subwords** s. Language models are then trained to estimate distributions over subword strings—never seeing the original character strings. Despite its prominent role, however, much remains unknown about tokenisation. We still do not know, for instance, what makes a good tokeniser (Gowda and May, 2020; Cognetta et al., 2024): which characteristics should its produced subwords s have to be a good starting point for language modelling? If we knew this, then we could define an **objective function** which we could evaluate tokenisers with.

Another open question is how to—given such an objective function—efficiently find a tokeniser which maximises it. Byte pair encoding (BPE; Gage, 1994; Sennrich et al., 2016), for instance, is a greedy solution to find a tokeniser which maximises a text's compression. UnigramLM (Kudo, 2018) is a heuristic method to find a tokeniser that maximises its tokenised text's unigram logprobability. Both these methods, however, are approximate: they do not necessarily find an optimal tokeniser according to their objective function. This raises the question of whether finding such optimal tokenisers efficiently is even possible.

In this paper, we answer this question (at least partially), proving the NP-completeness of several variants of this tokenisation problem. Specifically, we focus on finding tokenisers that maximise the **compression** of a text.¹ Given this objective, we then define the **tokenisation problem** as the task of finding a tokeniser which compresses a dataset to at most δ symbols. Notably, prior work imposes different constraints on how tokenisers are defined; here we consider two variants. In **direct tokenisation**, the desired compression must be reached by choosing a vocabulary (i.e., a set of subwords) which is directly used to represent the text. In **bottom-up tokenisation**, the desired compression must be reached by finding a sequence of merge operations instead, which we apply to the input text.

We prove the NP-hardness of both of these tokenisation problems (as well as of some variants thereof) by reducing from the **max 2-satisfiability** (max-2-SAT) problem.² Practically speaking, our results imply that we are unlikely to find an efficient algorithm for the problem of finding optimal tokenisers, and that we should focus on approximate algorithms (such as BPE or UnigramLM) instead.

2 How to Choose a Tokeniser?

In theory, a researcher's choice of tokeniser should not influence their language model's quality. This is because we can extract word-level (Pimentel and Meister, 2024; Oh and Schuler, 2024) or characterlevel (Phan et al., 2024; Giulianelli et al., 2024) distributions from any subword-level language model. Thus, regardless of which tokeniser is used, a sufficiently expressive language model should be able to represent the exact distributions over characters or words that we are interested in.

In practice, however, a bad choice of tokeniser can have undesirable effects on downstream applications. For instance, performing standard arith-

¹The compression achieved by a tokeniser correlates with downstream language modelling performance (Gallé, 2019; Zouhar et al., 2023a) and computational efficiency.

²Concurrent work by Kozma and Voderholzer (2024) also proves the NP-completeness of bottom-up tokenisation. In fact, they prove its APX-hardness.

metic tasks (e.g., 317 + 421) can be difficult even for large models (Nogueira et al., 2021; Muffo et al., 2022) due to the arbitrary splitting of numbers into subwords. Indeed, simple changes in how numbers are tokenised can improve performance in such tasks (Singh and Strouse, 2024). Similar issues arise when prompting LMs to count letters in words, where even advanced models such as GPT-4 infamously cannot correctly count the number of occurrences of the letter r in the word strawberry.

This raises the question of how to select a good tokeniser. Ideally, we would choose the tokeniser which maximises downstream language modelling performance. Unfortunately, we do not know how to measure such performance without fully training a model, making its direct maximisation computationally infeasible. Rather, we thus optimise proxy objectives—assumed to correlate with downstream performance. Among these are unigram logprobability (Kudo, 2018), Rényi efficiency (Zouhar et al., 2023a), and compression (Gallé, 2019).

We focus on compression in this paper. Denoting our tokenisation's **objective function** as \mathfrak{G} , we write this objective as: $\mathfrak{G}(\mathbf{s}) = -|\mathbf{s}|$. Improved compression leads to: (i) more efficient training and inference, due to shortened inputs;³ (ii) improved downstream performance, at least to a certain extent (Gallé, 2019; Rust et al., 2021; Zouhar et al., 2023a; Goldman et al., 2024);⁴ and (iii) fairer multilingual treatment, given models' limited context lengths and the per-token costs to use proprietary models (Petrov et al., 2023; Ahia et al., 2023).

Our Notation's Colour-coding

- Green for raw data (i.e., characters $\mathbf{c} \in \Sigma^*$);
- Purple for tokeniser-specific data (i.e., subwords s ∈ S* and merges m ∈ M*);
- Blue for functions (e.g., tok).

3 Defining a Tokeniser

A tokeniser can be defined as a 3-tuple $\langle S, tok, detok \rangle$, composed of a vocabulary, a tokenisation and a detokenisation function. Before defining these terms, however, we require some notation. Let $\mathbf{c} = c_1 c_2 \cdots c_{|\mathbf{c}|} \in \Sigma^*$ be a **character-string**, i.e., a sequence of characters c from alphabet Σ . Further, let $\mathcal{D} = {\{\mathbf{c}_n\}_{n=1}^N}$ be a dataset of character-strings.⁵ A subword $s \in \mathcal{S}$ represents a non-empty character-string \mathbf{c} . (Sequence \mathbf{c} can have length one.) Finally, let $\mathbf{s} = \langle s_1, s_2, \cdots, s_{|\mathbf{s}|} \rangle \in \mathcal{S}^*$ be a **subword-string**. Just like a single subword, a subword-string $\mathbf{s} \in \mathcal{S}^*$ represents a character-string via the concatenation of its subwords' characters:

$$\operatorname{concat}(\mathbf{s}) = s_1 \circ s_2 \circ \dots \circ s_{|\mathbf{s}|} \tag{1}$$

and we say that a pair of character and subword strings are equivalent if:

$$\mathbf{c} \stackrel{\circ}{=} \mathbf{s} \iff \mathbf{c} = \operatorname{concat}(\mathbf{s})$$
 (2)

Given the notation above, we can now define the items in tuple $\langle S, tok, detok \rangle$. A tokeniser's **vocabulary** is a set of subwords $S \subset \Sigma^*$ such that $\Sigma \subseteq S$; we say its size is $|S| = |\Sigma| + K$. Further, a **detokenisation function** is defined as detok : $S^* \to \Sigma^*$ and given a subword-string it outputs the character-string it represents. This function thus is simply defined as detok(s) $\stackrel{\text{def}}{=} \text{concat}(s)$.

Finally, we are left with defining a **tokenisation function** $tok : \Sigma^* \to S^*$, which maps from character- to subword-strings. Notably, these functions always ensure the equivalence $\mathbf{c} \stackrel{\circ}{=} \mathbf{s}$ for $\mathbf{s} = tok(\mathbf{c})$. Several tokenisation functions, however, are compatible with this constraint, as given a vocabulary, many subword-strings may be equivalent to the same character-string. For instance, given $S = \{a, c, t, at\}$, the string $\mathbf{c} = \langle c, a, t \rangle$ could be tokenised as $\mathbf{s} = \langle c, a, t \rangle$ or as $\mathbf{s} = \langle c, at \rangle$. Most researchers define tokenisation functions in one of two ways, which we term direct and bottom-up tokenisation functions here; we define these next.

3.1 Direct Tokenisation Functions

In direct tokenisation, a character-string is directly replaced by an optimal subword-string. To implement this, one must thus first define what *optimal* means; this is done through objective function \mathfrak{G} which, given a subword-string, returns a score. Given a previously chosen vocabulary

³Recent work tries to improve the computational efficiency of byte-level models (Yu et al., 2023; Pagnoni et al., 2024).

⁴Although, see also Ali et al. (2024), who argue that compression might be a necessary but not sufficient condition for good downstream performance, and Schmidt et al. (2024), who argue that compression and downstream performance have a more complex relationship than prior work suggests.

⁵We note that we use set notation here, but our datasets are actually multisets—datasets can include the same string c multiple times. We show that tokenisation is still NP-complete for datasets with no repetitions in §6.3. Further, we impose no constraint on the kind of string present in these datasets: each c_n can be either a raw or pre-tokenised character-string (i.e., either a full document or a whitespace word).

S (we discuss how to find S in §5), a direct tokenisation function then encodes string c as:

$$tok_{\diamond}[\mathcal{S}](\mathbf{c}) = \underset{\mathbf{s}\in\mathcal{S}^{*}}{\arg\max \mathfrak{G}(\mathbf{s})}$$
(3)
s.t. $\mathbf{s} \stackrel{\circ}{=} \mathbf{c}$

In words, given a vocabulary S, function tok_{\diamond} returns the optimal subword-string $s \in S^*$ which is equivalent to the input character-string c. We then set $tok(c) \stackrel{\text{def}}{=} tok_{\diamond}[S](c)$. Different choices of \mathfrak{G} recover methods such as UnigramLM (Kudo, 2018) or PathPiece (Schmidt et al., 2024). Notably, in general, this function is not efficiently computable.⁶

In this paper, we are concerned with tokenisers that use compression as their objective: that is, for which $\mathfrak{G}(\mathbf{s}) = -|\mathbf{s}|$. In this case, we can rewrite the direct tokenisation function as:

$$tok_{\diamond}[S](\mathbf{c}) = \underset{\mathbf{s}\in\mathcal{S}^{*}}{\operatorname{arg\,min}} |\mathbf{s}|$$
(4)
s.t. $\mathbf{s} \stackrel{\circ}{=} \mathbf{c}$

Importantly, in the case of compression, this equation can be computed efficiently (as shown in §5.1).

3.2 Bottom-up Tokenisation Functions

In bottom-up tokenisation, one starts with a set of character-strings, and merges their symbols bottom-up, one pair at a time.⁷ Formally, let $m \in \mathcal{M}$ be a **merge**, defined as a pair of subwords: $m = \langle s_1, s_2 \rangle$. Further, let $\mathcal{M} \stackrel{\text{def}}{=} \Sigma^* \times \Sigma^*$. Now, let **merge** be a functional; given merge $m = \langle s_1, s_2 \rangle$, it returns a function merge[m] : $\mathcal{S}^* \to (\mathcal{S} \cup \{s_1 \circ s_2\})^*$ which operates on string **s** left-to-right, replacing every occurrence of s_1 followed by s_2 in it with subword $s' = s_1 \circ s_2$. E.g., given $\mathbf{s} = \langle wo, r, ld \rangle$ and $m = \langle wo, r \rangle$, the output of $\text{merge}[m](\mathbf{s})$ is $\langle wor, ld \rangle$.

Consider now $\mathbf{m} \in \mathcal{M}^*$, a sequence of merges. Given a character-string $\mathbf{c} \in \Sigma^*$, a bottom-up tokenisation function compresses it as:

$$\mathsf{tok}_{\uparrow}[\mathbf{m}](\mathbf{c}) = \bigg(\bigotimes_{z=1}^{|\mathbf{m}|} \mathsf{merge}[m_z] \bigg)(\mathbf{c}) \quad (5)$$

where \bigcirc represents function composition, e.g., $\bigcirc_{z=1}^2 \operatorname{merge}[m_z] = \operatorname{merge}[m_2] \odot \operatorname{merge}[m_1].$ Bottom-up tokenisers then set $tok \stackrel{\text{def}}{=} tok_{\uparrow}[\mathbf{m}]$. Further, a merge sequence **m** is also used to set a bottom-up tokeniser's vocabulary as:

$$\mathcal{S} = \Sigma \cup \{ s_1 \circ s_2 \mid \langle s_1, s_2 \rangle \in \mathbf{m} \}$$
(6)

where $|\mathbf{m}| = K$ implies this vocabulary has size $|\mathcal{S}| = |\Sigma| + K$, as before.

4 Maximum 2-Satisfiability

Our paper's goal is to prove the NP-completeness of tokenisation. To show this, we must reduce an NP-hard problem to tokenisation in polynomial time. We will rely on the **maximum 2-satisfiability** problem (max-2-SAT) for this, whose definition we provide here. The NP-hardness of max-2-SAT was proven by Garey et al. (1974).

Definition 1. Let $\mathcal{X} = \{X_j\}_{j=1}^J$ be a set of variables; each of these variables are assigned values $x_j \in \{F, T\}$, and we write $\chi = \{x_j\}_{j=1}^J \in \{F, T\}^J$. Let $\mathcal{L} = \{(L_i^1 \lor L_i^2)\}_{i=1}^I$ be a set of clauses,⁸ where each literal L represents either a variable X_j or its negation $\neg X_j$. The max-2-SAT decision problem requires deciding whether there exists an assignment for which at least ψ clauses are satisfied:

$$\psi \le \max_{\boldsymbol{\chi} \in \{\mathbf{F}, \mathbf{T}\}^J} \sum_{i=1}^{I} \mathbb{1}\{L_i^1 \lor L_i^2\}$$
(7)

where 1 is an indicator function which evaluates the clause and returns one if the clause is satisfied by χ and zero otherwise.

For mathematical convenience, we will write $M2S(\mathcal{X}, \mathcal{L}, \psi)$ for a function which returns T if its input is satisfiable under a max-2-SAT decision problem, and F otherwise. As a concrete example, consider the set of variables $\mathcal{X} = \{X_1, X_2\}$ and the set of clauses $\mathcal{L} = \{X_1 \lor X_2, \neg X_1 \lor X_2, X_1 \lor \neg X_2, \neg X_1 \lor \neg X_2\}$. The assignment $x_1 = T, x_2 = T$ leads to 3 clauses being satisfied, which is the optimum. For this example, we thus have that $M2S(\mathcal{X}, \mathcal{L}, 3) = T$, but that $M2S(\mathcal{X}, \mathcal{L}, 4) = F$.

5 Finding an Optimal Direct Tokeniser

We are now left with the task of finding an optimal tokeniser. We do this by selecting either: its vocabulary in direct tokenisation, since $tok = tok_{e}[S]$;

⁶In fact, Geh et al. (2024) shows that it is NP-complete for $\mathfrak{G}(\mathbf{s}) = \sum_{t=1}^{|\mathbf{s}|} \log p_{\theta}(s_t | \mathbf{s}_{< t})$, where p_{θ} is a language model.

⁷Currently, this is likely the most common tokenisation function, being used in popular tokenisers such as, e.g., GPT-4's (OpenAI et al., 2024), LLaMA's (Touvron et al., 2023a,b), and Pythia's (Biderman et al., 2023).

⁸max-2-SAT also allows clauses to have a single literal L_i . In this case, we can always rewrite the clause as $(L_i \vee L_i)$ with no change to the solution of this decision problem.

or its merge sequence in bottom-up tokenisation, since $tok = tok_{\uparrow}[\mathbf{m}]$ and since its vocabulary is chosen according to Eq. (6). (Note that in §3, we only showed how to apply tokenisers at inference time, but not how to find them.) In this section, we focus on direct tokenisation, defining its optimisation and decision problems; we then prove its NP-completeness. The optimisation problem is defined as follows.

Definition 2. Given a dataset \mathcal{D} and a vocabulary size K, the **direct tokenisation optimisation** problem is to find a vocabulary $\mathcal{S} \subset \Sigma^*$ which maximally compresses \mathcal{D} :

$$S^{\star} = \underset{S \subset \Sigma^{*}}{\operatorname{arg\,min}} \sum_{\mathbf{c} \in \mathcal{D}} |\operatorname{tok}_{\phi}[S](\mathbf{c})| \qquad (8)$$

s.t. $|S| = |\Sigma| + K$

We can similarly define direct tokenisation's decision problem.

Definition 3. Given a dataset \mathcal{D} and a vocabulary size K, the **direct tokenisation decision problem** requires deciding whether there exists a vocabulary $\mathcal{S} \subset \Sigma^*$ which compresses \mathcal{D} to at most δ symbols:

$$\delta \ge \min_{\mathcal{S} \subset \Sigma^*} \sum_{\mathbf{c} \in \mathcal{D}} |\mathsf{tok}_{\phi}[\mathcal{S}](\mathbf{c})| \qquad (9)$$

s.t. $|\mathcal{S}| = |\Sigma| + K$

We write $\operatorname{Tok}_{\diamond}(\mathcal{D}, K, \delta)$ for a function which returns T if a tokenisation decision problem with those inputs is satisfiable, and F otherwise. Note that, whenever $|\mathcal{D}| \leq K$, the solution to the problem above is trivial, as an optimal solution simply requires including all strings \mathbf{c}_n in vocabulary \mathcal{S} . As we show next, however, in the general case the above decision problem is NP-complete. We now state this as a theorem, which we will prove in the next two sections.

Theorem 1. *The direct tokenisation decision problem, as in Definition 3, is NP-complete.*

Proof. A decision problem is considered to be NPcomplete if: (i) it is in NP; (ii) it is NP-hard. We prove these conditions in \$5.1 and \$5.2.

5.1 Direct Tokenisation is in NP

A decision problem is in the nondeterministic polynomial time class (NP) if, given a **certificate** of polynomial length, one can verify that certificate in polynomial time. Specifically, a certificate usually encodes a decision problem's solution, allowing us to verify its satisfiability. In the case of direct tokenisation, this certificate would be a vocabulary S which leads a dataset D to be compressed to at most δ symbols. Verifying this certificate simply requires computing the sum in Eq. (9), i.e.:

$$\sum_{\mathbf{c}\in\mathcal{D}}|\mathsf{tok}_{\diamond}[\mathcal{S}](\mathbf{c})| \tag{10}$$

Lemma 1. The direct tokenisation decision problem, as in Definition 3, is in NP.

Proof. As noted above, whenever $|\mathcal{D}| \leq K$, each $\mathbf{c}_n \in \mathcal{D}$ can be included in the vocabulary \mathcal{S} and fully compressed to a single symbol; we can thus verify the problem's satisfiability by simply checking that $\delta \geq |\mathcal{D}|$ as this is the best reachable compression. Assuming K to be bounded by $|\mathcal{D}|$ —and therefore polynomial in the input—we have that the certificate S also has polynomial length. Given such a certificate \mathcal{S} , verifying it simply requires computing the sum in Eq. (10). In turn, computing this sum requires $|\mathcal{D}|$ calls to function tok_{φ}. It follows that, if function toke runs in polynomial time, then direct tokenisation is in NP. Luckily, this function can indeed be computed efficiently using Schmidt et al.'s (2024) PathPiece method, which runs in $O(|\mathbf{c}|^2)$ time.

5.2 Direct Tokenisation is NP-hard

We now use a reduction from max-2-SAT to prove the NP-hardness of direct tokenisation.

Reduction 1. Let us have a max-2-SAT decision problem defined as in Definition 1. To reduce this problem to a tokenisation decision problem, as in Definition 3, we start by defining an alphabet $\Sigma =$ $\{\odot\} \cup \{x_j^{\mathsf{T}}, x_j^{\mathsf{F}}\}_{j=1}^J$. We then construct three sets of strings:

$$\mathcal{D}_1 = \{ \odot x_j^{\mathsf{T}} \odot \}_{j=1}^J \cup \{ \odot x_j^{\mathsf{F}} \odot \}_{j=1}^J \qquad (11a)$$

$$\mathcal{D}_2 = \{ \odot x_i^{\mathsf{T}} \odot x_j^{\mathsf{F}} \odot \}_{j=1}^J \tag{11b}$$

$$\mathcal{D}_{3} = \{ \odot L_{i}^{1} \odot L_{i}^{2} \odot \}_{i=1}^{I}$$
(11c)

in these strings L_i is replaced by either character x_j^{T} or x_j^{F} , depending on whether it represents X_j or $\neg X_j$, respectively. We then construct our dataset \mathcal{D} , and choose K and δ as:

$$\mathcal{D} = \left(\bigcup_{=1}^{f} \mathcal{D}_{1}\right) \cup \left(\bigcup_{=1}^{f'} \mathcal{D}_{2}\right) \cup \mathcal{D}_{3}$$
(12a)

$$K = J, \quad \delta = (4f + 3f') J + 5 I - 2\psi$$
 (12b)

where we set $f' \stackrel{\text{\tiny def}}{=} 4I + 1$ and $f \stackrel{\text{\tiny def}}{=} 4f'J + 4I + 1$.

We write $R1(\mathcal{X}, \mathcal{L}, \psi)$ to represent a function which, given an instance of max-2-SAT, returns an instance of the tokenisation problem given by our reduction (i.e., \mathcal{D}, K, δ). For our reduction to be correct, we must have that:

$$M2S(\mathcal{X}, \mathcal{L}, \psi) \iff Tok_{\diamond}(R1(\mathcal{X}, \mathcal{L}, \psi))$$
 (13)

meaning that a max-2-SAT problem is satisfiable if and only if its reduced direct tokenisation problem is as well. We now set out to prove this. We start by proving the forward direction of this iff clause.

Lemma 2. If a max-2-SAT instance is satisfiable, then the direct tokenisation instance output by Reduction 1 is also satisfiable. Formally:

$$M2S(\mathcal{X}, \mathcal{L}, \psi) \implies Tok_{\phi}(R1(\mathcal{X}, \mathcal{L}, \psi))$$
 (14)

Proof sketch. See a formal proof in App. A. Our proof works by first fixing a satisfying solution to max-2-SAT with values x_j^* . Given this solution, for each variable, we add to our vocabulary S a subword $\odot x_j^T \odot$ if x_j^* is true, or $\odot x_j^F \odot$ if x_j^* is false. Given these subwords, strings in \mathcal{D}_1 and \mathcal{D}_2 occupy a total length of (4f + 3f') J. Further, since at least ψ of the max-2-SAT problem are satisfied by x_j^* , the strings in \mathcal{D}_3 will occupy a total length smaller or equal to $5I - 2\psi$. This solution to the tokenisation problem thus gives us a total length which is smaller or equal to $\delta = (4f + 3f')J + 5I - 2\psi$.

Now, we are left with proving the backward direction of the iff clause in Eq. (13). We do so in the following lemma.

Lemma 3. If the direct tokenisation instance output by Reduction 1 is satisfiable, the max-2-SAT instance reduced to it is as well. Formally:

$$\operatorname{Tok}_{\diamond}(\operatorname{R1}(\mathcal{X}, \mathcal{L}, \psi)) \implies \operatorname{M2S}(\mathcal{X}, \mathcal{L}, \psi)$$
 (15)

Proof sketch. See a formal proof in App. B. Our proof works in three steps. First, we show that all satisfying solutions must only have subwords of the form $\odot x_j^T \odot$ or $\odot x_j^F \odot$, since this is required to compress strings in \mathcal{D}_1 to at most 4fJ symbols. Second, we show that all satisfying solutions must only have either subword $\odot x_j^T \odot$ or $\odot x_j^F \odot$ for any variable X_j ; this is required to compress strings in \mathcal{D}_2 to at most 3f'J symbols. Finally, we show that if a tokeniser compresses strings in \mathcal{D}_3 to $5I - 2\psi$, then there is an assignment χ which satisfies at least ψ of the original max-2-SAT problem. Given both lemmas above, we can now trivially prove that direct tokenisation is NP-hard.

Lemma 4. The direct tokenisation decision problem, as in Definition 3, is NP-hard.

Proof. First, it is easy to see that Reduction 1 runs in polynomial time. Second, max-2-SAT is an NP-hard problem (Garey et al., 1974). This lemma then follows trivially from Lemmas 2 and 3, which together show that an instance of the tokenisation problem generated through Reduction 1 is satisfiable if and only if the max-2-SAT instance used to produce it is also satisfiable.

6 Finding Optimal Bottom-up Tokenisers

In this section, we shift our attention to bottomup tokenisation. We define both its optimisation and decision problems, and then prove its NPcompleteness. We start with defining the optimisation problem.

Definition 4. Given a dataset \mathcal{D} and a vocabulary size K, the **bottom-up tokenisation optimisation** problem is to find a merge sequence $\mathbf{m} \subset \mathcal{M}^*$ which maximally compresses \mathcal{D} :

$$\mathbf{m}^{\star} = \underset{\mathbf{m} \subset \mathcal{M}^{\star}}{\operatorname{arg\,min}} \sum_{\mathbf{c} \in \mathcal{D}} |\operatorname{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})| \qquad (16)$$

s.t. $|\mathbf{m}| = K$

As can be seen, this optimisation problem is similar to the direct tokenisation problem, albeit its target is to find a merge sequence instead of a vocabulary. We similarly define a decision problem.

Definition 5. Given a dataset \mathcal{D} and a vocabulary size K, the **bottom-up tokenisation decision prob**lem requires deciding whether there exists a merge sequence $\mathbf{m} \in \mathcal{M}^*$ which compresses \mathcal{D} to at most δ symbols:

$$\delta \ge \min_{\mathbf{m} \in \mathcal{M}^*} \sum_{\mathbf{c} \in \mathcal{D}} |\mathsf{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})|$$
(17)
s.t. $|\mathbf{m}| = K$

We spend the rest of this section showing that bottom-up tokenisers are NP-complete.

Theorem 2. *The bottom-up tokenisation decision problem, as in Definition 5, is NP-complete.*

Proof. We prove this in two steps below. We first prove that this problem is NP, in §6.1. We then prove that this problem is NP-hard, in §6.2. \Box

6.1 Bottom-up Tokenisation is in NP

We can verify this using a solution, the merge sequence $\mathbf{m} \in \mathcal{M}^*$, as a certificate. By showing that this certificate has polynomial length and that it can be verified in polynomial time, we prove this problem is in NP. To verify this certificate, we simply need to compute the sum in Eq. (17), i.e.:

$$\sum_{\mathbf{c}\in\mathcal{D}}|\mathsf{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})| \tag{18}$$

which we show now can be done efficiently.

Lemma 5. The bottom-up tokenisation decision problem, as in Definition 5, is in NP.

Proof. First, if K is larger than the total number of characters in \mathcal{D} , i.e., $\sum_{\mathbf{c}\in\mathcal{D}} |\mathbf{c}|$, then this dataset can be compressed to $|\mathcal{D}|$ by merging each string down to a single symbol; further, compressing \mathcal{D} more than that is not possible independently of K. Verifying the satisfiability of such an instance of the tokenisation problem is thus trivial, only requiring checking if $\delta \geq |\mathcal{D}|$. Second, if K is bounded by $|\mathcal{D}|$ —and therefore polynomial in the input—the certificate m has polynomial length. Given such a certificate m, verifying it then simply requires computing the sum in Eq. (18). In turn, computing this sum requires $|\mathcal{D}|$ calls to function tok₁. It follows that, if function tok_↑ runs in polynomial time, then bottom-up tokenisation is in NP. The computation of tok_{\uparrow} , can be done in polynomial time following the structure described in §3.2. For each $m = \langle s_1, s_2 \rangle \in \mathbf{m}$, scan the current **c** and replace each occurrence of s_1, s_2 by s'. This takes time $\mathcal{O}(|\mathbf{c}|)$ for each merge. Afterwards, the resulting string can be compared against the desired size. We obtain a total runtime of $O(|\mathcal{D}||\mathbf{c}||\mathbf{m}|)$.

6.2 Bottom-up Tokenisation is NP-hard

As before, we use a reduction from max-2-SAT to prove bottom-up tokenisation's NP-hardness.

Reduction 2. Let us have a max-2-SAT decision problem defined as in Definition 1. To reduce this problem to a bottom-up tokenisation decision problem, as in Definition 5, we start by defining an alphabet $\Sigma = \{ \odot, \otimes \} \cup \{ x_j^T, x_j^F \}_{j=1}^J$. We then construct five sets of strings:

$$\mathcal{D}_{1} = \{ \odot x_{j}^{\mathsf{T}} \}_{j=1}^{J} \cup \{ x_{j}^{\mathsf{F}} \odot \}_{j=1}^{J} \cup \{ x_{j}^{\mathsf{T}} \odot \}_{j=1}^{J} \qquad (19)$$

$$\cup \{ \odot x_{j}^{\mathsf{F}} \}_{j=1}^{J} \cup \{ x_{j}^{\mathsf{T}} \odot \}_{j=1}^{J} \cup \{ \odot x_{j}^{\mathsf{F}} \}_{j=1}^{J}$$

$$\mathcal{D}_{2} = \{ \odot x_{j}^{\mathsf{T}} \odot \}_{j=1}^{J} \cup \{ \odot x_{j}^{\mathsf{F}} \odot \}_{j=1}^{J}$$

$$\cup \{ \odot x_{j}^{\mathsf{T}} \otimes \}_{j=1}^{J} \cup \{ \odot x_{j}^{\mathsf{F}} \odot \}_{j=1}^{J}$$

$$\begin{aligned} \mathcal{D}_{3} &= \{ \odot x_{j}^{\mathrm{T}} \odot x_{j}^{\mathrm{F}} \odot \}_{j=1}^{J} \cup \{ \otimes x_{j}^{\mathrm{F}} \odot x_{j}^{\mathrm{T}} \otimes \}_{j=1}^{J} \\ \mathcal{D}_{4} &= \{ \odot x_{j}^{\mathrm{F}} \odot x_{j}^{\mathrm{T}} \otimes \}_{j=1}^{J} \cup \{ \otimes x_{j}^{\mathrm{F}} \odot x_{j}^{\mathrm{T}} \odot \}_{j=1}^{J} \\ \mathcal{D}_{5} &= \begin{cases} \odot x_{j}^{\mathrm{T}} \odot x_{j}^{\mathrm{F}} \odot & \text{if } L_{i}^{1} = X_{j} \text{ and } L_{i}^{2} = \neg X_{j'} \\ \odot x_{j}^{\mathrm{T}} \odot x_{j'}^{\mathrm{F}} \odot & \text{if } L_{i}^{1} = \neg X_{j} \text{ and } L_{i}^{2} = X_{j'} \\ \odot x_{j}^{\mathrm{T}} \odot x_{j'}^{\mathrm{T}} \odot & \text{if } L_{i}^{1} = \neg X_{j} \text{ and } L_{i}^{2} = X_{j'} \\ \odot x_{j}^{\mathrm{T}} \odot x_{j'}^{\mathrm{T}} \otimes & \text{if } L_{i}^{1} = X_{j} \text{ and } L_{i}^{2} = X_{j'} \\ \end{cases} \end{aligned} \right\}_{i=1}^{I}$$

We then construct our dataset D, and choose K and δ as:

$$\mathcal{D} = \bigcup_{=1}^{f} \mathcal{D}_{1} \cup \bigcup_{=1}^{f'} \mathcal{D}_{2} \cup \bigcup_{=1}^{f''} \mathcal{D}_{3} \cup \bigcup_{=1}^{f'''} \mathcal{D}_{4} \cup \mathcal{D}_{5} \quad (20)$$

$$K = 8J, \ \delta = (6f + 6f' + 4f'' + 4f''') \ J + 3I - \psi$$

where we set:

$$f''' \stackrel{\text{def}}{=} 5I, \quad f'' \stackrel{\text{def}}{=} 10 f''' J + 5I$$
 (21a)

$$f' \stackrel{\text{def}}{=} (10f'' + 10f''') J + 5I \tag{21b}$$

$$f \stackrel{\text{\tiny def}}{=} (12f' + 10f'' + 10f''') J + 5I \quad (21c)$$

As before, we write $\mathbb{R}2(\mathcal{X}, \mathcal{L}, \psi)$ for a function which, given the inputs of a max-2-SAT problem, returns the parameters of a bottom-up tokenisation problem. For our reduction to be correct, we must have that:

$$M2S(\mathcal{X}, \mathcal{L}, \psi) \iff Tok_{\uparrow}(R2(\mathcal{X}, \mathcal{L}, \psi))$$
 (22)

We follow the same proof strategies as before, starting by proving the forward direction of this iff statement.

Lemma 6. If a max-2-SAT instance is satisfiable, then the bottom-up tokenisation instance output by Reduction 2 is also satisfiable. Formally:

$$M2S(\mathcal{X}, \mathcal{L}, \psi) \implies Tok_{\uparrow}(R2(\mathcal{X}, \mathcal{L}, \psi))$$
 (23)

Proof sketch. See a formal proof in App. C. Without loss of generality, let a satisfying solution to max-2-SAT have values x_j^* . Our proof works by first defining the three following lists of merges, which must be included in any satisfying solution to the tokenisation problem:

$$\mathbf{m}_1 = \bigcirc_{j=1}^J [\langle \otimes, x_j^{\mathsf{F}} \rangle, \langle x_j^{\mathsf{T}}, \otimes \rangle]$$
(24a)

$$\mathbf{m}_{3} = \bigcirc_{j=1}^{J} [\langle x_{j}^{\mathsf{F}}, \odot \rangle, \langle \odot, x_{j}^{\mathsf{T}} \rangle]$$
(24b)

$$\mathbf{m}_{5} = \bigcirc_{j=1}^{J} [\langle \odot, x_{j}^{\mathsf{F}} \rangle, \langle x_{j}^{\mathsf{T}}, \odot \rangle]$$
(24c)

We then construct two other lists of merges, which do depend on the satisfying assignments

to max-2-SAT:

$$\mathbf{m}_{2} = \bigcirc_{j=1}^{J} \begin{bmatrix} \langle \odot, x_{j}^{\mathsf{T}} \otimes \rangle & \text{if } x_{j}^{\star} = \mathsf{T} \\ \langle \otimes x_{j}^{\mathsf{F}}, \odot \rangle & \text{else} \end{bmatrix}$$
(25a)

 $\mathbf{m}_4 = \bigcirc_{j=1}^J \left[\begin{array}{cc} \langle \odot x_j, \odot \rangle & \text{if } x_j = 1 \\ \langle \odot, x_j^F \odot \rangle & \text{else} \end{array} \right]$ (25b)

Finally, we create a merge sequence by concatenating these lists in order:

$$\mathbf{m} = \mathbf{m}_1 \circ \mathbf{m}_2 \circ \mathbf{m}_3 \circ \mathbf{m}_4 \circ \mathbf{m}_5 \qquad (26)$$

Note that we have exactly K = 8J merges in this list. Given this merge sequence, it is easy to verify that strings in \mathcal{D}_1 to \mathcal{D}_4 will use exactly (6f+6f'+4f''+4f''') J symbols after tokenised. Further, since at least ψ of the max-2-SAT problem are satisfied by x_j^{\star} , the strings in \mathcal{D}_5 will occupy a total length smaller or equal to $3I - \psi$. This solution to the tokenisation problem thus gives us a tokeniser which will compress \mathcal{D} to at most $\delta =$ $(6f+6f'+4f''+4f''') J+3I - \psi$. \Box

We now prove the backward direction of the iff clause in Eq. (22).

Lemma 7. If the bottom-up tokenisation instance output by Reduction 2 is satisfiable, the max-2-SAT instance reduced to it is as well. Formally:

$$\operatorname{Fok}_{\uparrow}(\operatorname{R2}(\mathcal{X},\mathcal{L},\psi)) \implies \operatorname{M2S}(\mathcal{X},\mathcal{L},\psi)$$
 (27)

Proof sketch. See a formal proof in App. D. Our proof works in five steps. First, we show that all satisfying solutions must include merges \mathbf{m}_1 , \mathbf{m}_3 , and \mathbf{m}_5 from Eq. (24), since this is required to compress strings in \mathcal{D}_1 to at most 6fJ symbols. Second, we show the other merges of any satisfying solution must be of the form:

$$\mathbf{m}_{j}^{\odot} = \left\{ \begin{array}{l} \langle \odot x_{j}^{\mathsf{T}}, \odot \rangle, \langle \odot, x_{j}^{\mathsf{F}} \odot \rangle \\ \langle \odot, x_{j}^{\mathsf{T}} \odot \rangle, \langle \odot x_{j}^{\mathsf{F}}, \odot \rangle \end{array} \right\}$$
(28a)

$$\mathbf{m}_{j}^{\otimes} = \left\{ \begin{array}{l} \langle \odot, x_{j}^{\mathsf{T}} \otimes \rangle, \langle \otimes x_{j}^{\mathsf{F}}, \odot \rangle \\ \langle \odot x_{j}^{\mathsf{T}}, \otimes \rangle, \langle \otimes, x_{j}^{\mathsf{F}} \odot \rangle \end{array} \right\}$$
(28b)

this is required to compress strings in \mathcal{D}_2 to at most 6f'J symbols. Third, we show that any satisfying solution will have at least one merge of each set \mathbf{m}_j^{\odot} and one of each set \mathbf{m}_j^{\odot} ; this is required to compress strings in \mathcal{D}_3 to at most 4f''J symbols. Fourth, we show that any satisfying solution will have—for each $j \in \{1, J\}$ —both its merges in sets \mathbf{m}_j^{\odot} and \mathbf{m}_j^{\otimes} containing character x_j^{T} or containing character x_j^{F} ; this is required to compress strings in

 \mathcal{D}_4 to at most 4f'''J symbols. Finally, we show that if a tokeniser compresses strings in \mathcal{D}_5 to $3I - \psi$, then there is an assignment χ which satisfies at least ψ of the original max-2-SAT problem.

Finally, given both lemmas above, we can now prove that bottom-up tokenisation is NP-hard.

Lemma 8. The bottom-up tokenisation decision problem, as in Definition 5, is NP-hard.

Proof. First, it is easy to see that Reduction 2 runs in polynomial time. Second, max-2-SAT is an NP-hard problem (Garey et al., 1974). This lemma then follows trivially from Lemmas 6 and 7.

6.3 Other Definitions of Tokenisation

We now expand our discussion to consider variations of the above tokenisation problems.

Deduped Datasets. Our definitions of both direct and bottom-up tokenisation allow datasets \mathcal{D} to include repeated entries. It is common, however, to deduplicate datasets in NLP-thus removing repeated entries. A small change to both our reductions is enough to adapt it to this deduplicated dataset case: simply append each string in the repeated datasets (either \mathcal{D}_1 and \mathcal{D}_2 in Reduction 1 or \mathcal{D}_1 to \mathcal{D}_4 in Reduction 2) with a unique character $\{a_y\}_{y=1}^{\infty}$ and increase the target compression size δ accordingly (by f + f' or f + f' + f'' + f''', respectively). These new characters will never be included in optimal tokenisers' solutions, and thus the previous proofs hold, with the difference that each dataset will require extra symbols once compressed.

A Single Long String. In the previous sections, we considered tokenisers trained on a dataset \mathcal{D} . Work on compression, however, usually considers a single long string c as its input. It is easy to see that direct tokenisation is not an NP-complete problem if its input is a single long string; including this string in vocabulary \mathcal{S} already achieves optimal compression. Bottom-up tokenisation, however, is still NP-complete even when given a single string as input. As before, this can be shown with a similar strategy to Reduction 2, but where we first append each string in dataset \mathcal{D} with a unique character $\{a_y\}_{y=1}^{\infty}$ and then concatenate all these strings. As in the deduped case above, characters a_{y} will never be merged by any optimal tokeniser; they will thus serve as virtual string delimiters and will not affect our proofs beyond an increase to the target compression size δ .

A Hybrid Approach. Finally, the last variant we consider is a hybrid between direct and bottom-up tokenisation, where we find a merge sequence **m** which—when we extract a vocabulary from it as $S = \Sigma \cup \{s_1 \circ s_2 \mid \langle s_1, s_2 \rangle \in \mathbf{m}\}$ —optimally compresses a dataset \mathcal{D} using the direct tokenisation function in Eq. (4). We can easily prove the NP-hardness of this tokenisation variant by relying on Reduction 2; as our proof in Lemma 8 did not make use of the order of merges in **m**, only of the subwords composed by it, this lemma's proof strategy can be similarly applied to this hybrid variant.

7 Tokenisation's Connection to Compression

The variants of tokenisation that we consider here with compression as their objective function—are closely related to the field of dictionary compression. In both fields, we wish to reduce the size of an input (c or D) by exploiting repetitive elements. In fact, the most popular tokenisation algorithm to date, BPE, was originally proposed as a compression algorithm (Gage, 1994) and has only somewhat recently been ported into NLP to find tokenisers (by Sennrich et al., 2016).

Not surprisingly, prior work has also considered, from a theoretical perspective, the compression tokenisers achieve. Zouhar et al. (2023b), for instance, analyse bottom-up tokenisation and prove an approximation bound on the compression achieved by the tokenisers found using BPE. More recently, Kozma and Voderholzer (2024) also analyses bottom-up tokenisation, proving a tighter bound on this compression achieved by BPE.

A set of popular dictionary compression methods, **straight-line programs** (SLP; Kieffer and Yang, 2000; Charikar et al., 2005), can be used to illustrate the similarities and differences between tokenisers and compressors.⁹ Given a string **c**, an SLP describes a grammar from which **c** can be uniquely derived. Formally, an SLP is a set of rules of form $X \rightarrow a$ or $X \rightarrow AB$, where X, A, B are called nonterminals and *a* is a terminal.¹⁰ Starting from a special nonterminal *S*, applying these rules exhaustively—until only terminals are left produces exactly the desired string **c**. Notably, given a string c, it is NP-complete to find the smallest SLP which generates it (Charikar et al., 2005).

On the one hand, SLPs in Chomsky normal form are closely linked to bottom-up tokenisation; each of its rules expands to two nonterminals, and thus corresponds to a merge. However, while SLPs must find the minimum number of merges (or rules) to fully compress a string into a single symbol, bottom-up tokenisers must maximally compress the string given a fixed number of merges. On the other hand, SLPs which are not in Chomsky normal form are closely linked to direct tokenisation. In this case, a direct tokeniser could be converted into an SLP with depth two; this grammar has a start rule $S \rightarrow \mathbf{s}$, and a rule from each subword to its characters $s \rightarrow c$. Again, while SLPs must find a minimal grammar representing the string, direct tokenisers must only minimise the size of rule $S \rightarrow \mathbf{s}$ given a fixed number of rules $\mathbf{s} \rightarrow \mathbf{c}$.

The paragraph above highlights two important differences between tokenisers and compressors. First, tokenisers aim to reduce only the size of the resulting tokenised text (i.e., |s|), whereas compressors also consider the size of the compression information (e.g., considering the size required to store \mathcal{S} , which would be $\sum_{s \in \mathcal{S}} |\det(s)|$). This is because tokenisers must create shorter inputs for NLP algorithms, while compressors must make information compact. Second, tokenisers and compressors have different optimisation parameters. Compression algorithms always compress a string to the best extent possible (e.g., for SLPs, until a single nonterminal is reached). Instead, tokenisation algorithms are given a maximum vocabulary size (i.e., K) and find tokenisers which only compress their input as much as possible until this limit is reached.

8 Conclusion

In this work, we proved the NP-completeness of two variants of tokenisation. These results underline that finding optimal tokenisers most likely will remain a difficult quest and that research should focus on approximate algorithms instead. Regarding those, there is potential both in improving the analysis of currently used algorithms, such as BPE, as well as in designing other, more involved algorithms. Towards the latter, a more detailed look at the connections to compression algorithms might be fruitful. While we investigated the complexity of two forms of tokenisation, similar results for other variants (e.g., with other objective functions) remain open; this would be exciting future work.

⁹See Lohrey (2012) for an overview of straight-line programs, and Kempa and Prezza (2018); Kociumaka et al. (2023) for a more detailed overview of compression in general.

¹⁰Although not originally defined that way, SLP's grammars are typically assumed to be in Chomsky normal form (CNF), for simplicity. This does not make a big difference for compression, but will be important for our purposes.

Acknowledgments

We would like to thank Sotiris Anagnostidis and Clara Meister for their feedback on earlier versions of this manuscript. We would also like to thank Amit Moryossef for discussions about the NP-hardness proof we present here. Finally, we also thank the VMI of ETH Zürich for organising a scientific workshop that allowed the authors to meet and exchange ideas leading to this paper.

References

- Orevaoghene Ahia, Sachin Kumar, Hila Gonen, Jungo Kasai, David Mortensen, Noah Smith, and Yulia Tsvetkov. 2023. Do all languages cost the same? Tokenization in the era of commercial language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 9904–9923, Singapore. Association for Computational Linguistics.
- Mehdi Ali, Michael Fromm, Klaudia Thellmann, Richard Rutmann, Max Lübbering, Johannes Leveling, Katrin Klug, Jan Ebert, Niclas Doll, Jasper Buschhoff, Charvi Jain, Alexander Weber, Lena Jurkschat, Hammam Abdelwahab, Chelsea John, Pedro Ortiz Suarez, Malte Ostendorff, Samuel Weinbach, Rafet Sifa, Stefan Kesselheim, and Nicolas Flores-Herr. 2024. Tokenizer choice for LLM training: Negligible or crucial? In *Findings of the Association for Computational Linguistics: NAACL 2024*, pages 3907–3924, Mexico City, Mexico. Association for Computational Linguistics.
- Stella Biderman, Hailey Schoelkopf, Quentin Anthony, Herbie Bradley, Kyle O'Brien, Eric Hallahan, Mohammad Aflah Khan, Shivanshu Purohit, USVSN Sai Prashanth, Edward Raff, Aviya Skowron, Lintang Sutawika, and Oskar Van Der Wal. 2023. Pythia: A suite for analyzing large language models across training and scaling. In *Proceedings of the* 40th International Conference on Machine Learning, ICML'23.
- M. Charikar, E. Lehman, Ding Liu, R. Panigrahy, M. Prabhakaran, A. Sahai, and A. Shelat. 2005. The smallest grammar problem. *IEEE Transactions on Information Theory*, 51(7):2554–2576.
- Marco Cognetta, Vilém Zouhar, Sangwhan Moon, and Naoaki Okazaki. 2024. Two counterexamples to tokenization and the noiseless channel. In Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024), pages 16897–16906, Torino, Italia. ELRA and ICCL.
- Philip Gage. 1994. A new algorithm for data compression. *C Users Journal*, 12(2):23–38.

- Matthias Gallé. 2019. Investigating the effectiveness of BPE: The power of shorter sequences. In Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP), pages 1375–1381, Hong Kong, China. Association for Computational Linguistics.
- M. R. Garey, D. S. Johnson, and L. Stockmeyer. 1974. Some simplified NP-complete problems. In *Proceedings of the Sixth Annual ACM Symposium on Theory of Computing*, STOC '74, page 47–63, New York, NY, USA. Association for Computing Machinery.
- Renato Geh, Honghua Zhang, Kareem Ahmed, Benjie Wang, and Guy Van Den Broeck. 2024. Where is the signal in tokenization space? In *Proceedings* of the 2024 Conference on Empirical Methods in Natural Language Processing, pages 3966–3979, Miami, Florida, USA. Association for Computational Linguistics.
- Mario Giulianelli, Luca Malagutti, Juan Luis Gastaldi, Brian DuSell, Tim Vieira, and Ryan Cotterell. 2024. On the proper treatment of tokenization in psycholinguistics. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, Miami, Florida, USA. Association for Computational Linguistics.
- Omer Goldman, Avi Caciularu, Matan Eyal, Kris Cao, Idan Szpektor, and Reut Tsarfaty. 2024. Unpacking tokenization: Evaluating text compression and its correlation with model performance. In *Findings of the Association for Computational Linguistics: ACL* 2024, pages 2274–2286, Bangkok, Thailand. Association for Computational Linguistics.
- Thamme Gowda and Jonathan May. 2020. Finding the optimal vocabulary size for neural machine translation. In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pages 3955–3964, Online. Association for Computational Linguistics.
- Dominik Kempa and Nicola Prezza. 2018. At the roots of dictionary compression: string attractors. In *Proceedings of the 50th Annual ACM SIGACT Symposium on Theory of Computing*, STOC 2018, page 827–840, New York, NY, USA. Association for Computing Machinery.
- J.C. Kieffer and En-Hui Yang. 2000. Grammar-based codes: a new class of universal lossless source codes. *IEEE Transactions on Information Theory*, 46(3):737–754.
- Tomasz Kociumaka, Gonzalo Navarro, and Nicola Prezza. 2023. Toward a definitive compressibility measure for repetitive sequences. *IEEE Transactions on Information Theory*, 69(4):2074–2092.
- László Kozma and Johannes Voderholzer. 2024. Theoretical analysis of byte-pair encoding. *Preprint*, arXiv:2411.08671.

- Taku Kudo. 2018. Subword regularization: Improving neural network translation models with multiple subword candidates. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 66–75, Melbourne, Australia. Association for Computational Linguistics.
- Markus Lohrey. 2012. Algorithmics on SLPcompressed strings: A survey. *Groups - Complexity -Cryptology*, 4(2):241–299.
- Matteo Muffo, Aldo Cocco, and Enrico Bertino. 2022. Evaluating transformer language models on arithmetic operations using number decomposition. In *Proceedings of the Thirteenth Language Resources and Evaluation Conference*, pages 291–297, Marseille, France. European Language Resources Association.
- Rodrigo Nogueira, Zhiying Jiang, and Jimmy Lin. 2021. Investigating the limitations of transformers with simple arithmetic tasks. *Preprint*, arXiv:2102.13019.
- Byung-Doh Oh and William Schuler. 2024. Leading whitespaces of language models' subword vocabulary pose a confound for calculating word probabilities. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 3464–3472, Miami, Florida, USA. Association for Computational Linguistics.
- OpenAI, Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, Red Avila, Igor Babuschkin, Suchir Balaji, Valerie Balcom, Paul Baltescu, Haiming Bao, Mohammad Bavarian, Jeff Belgum, Irwan Bello, Jake Berdine, Gabriel Bernadett-Shapiro, Christopher Berner, Lenny Bogdonoff, Oleg Boiko, Madelaine Boyd, Anna-Luisa Brakman, Greg Brockman, Tim Brooks, Miles Brundage, Kevin Button, Trevor Cai, Rosie Campbell, Andrew Cann, Brittany Carey, Chelsea Carlson, Rory Carmichael, Brooke Chan, Che Chang, Fotis Chantzis, Derek Chen, Sully Chen, Ruby Chen, Jason Chen, Mark Chen, Ben Chess, Chester Cho, Casey Chu, Hyung Won Chung, Dave Cummings, Jeremiah Currier, Yunxing Dai, Cory Decareaux, Thomas Degry, Noah Deutsch, Damien Deville, Arka Dhar, David Dohan, Steve Dowling, Sheila Dunning, Adrien Ecoffet, Atty Eleti, Tyna Eloundou, David Farhi, Liam Fedus, Niko Felix, Simón Posada Fishman, Juston Forte, Isabella Fulford, Leo Gao, Elie Georges, Christian Gibson, Vik Goel, Tarun Gogineni, Gabriel Goh, Rapha Gontijo-Lopes, Jonathan Gordon, Morgan Grafstein, Scott Gray, Ryan Greene, Joshua Gross, Shixiang Shane Gu, Yufei Guo, Chris Hallacy, Jesse Han, Jeff Harris, Yuchen He, Mike Heaton, Johannes Heidecke, Chris Hesse, Alan Hickey, Wade Hickey, Peter Hoeschele, Brandon Houghton, Kenny Hsu, Shengli Hu, Xin Hu, Joost Huizinga, Shantanu Jain, Shawn Jain, Joanne Jang, Angela Jiang, Roger Jiang, Haozhun Jin, Denny Jin, Shino Jomoto, Billie Jonn, Heewoo Jun, Tomer Kaftan, Łukasz Kaiser, Ali Ka-

mali, Ingmar Kanitscheider, Nitish Shirish Keskar, Tabarak Khan, Logan Kilpatrick, Jong Wook Kim, Christina Kim, Yongjik Kim, Jan Hendrik Kirchner, Jamie Kiros, Matt Knight, Daniel Kokotajlo, Łukasz Kondraciuk, Andrew Kondrich, Aris Konstantinidis, Kyle Kosic, Gretchen Krueger, Vishal Kuo, Michael Lampe, Ikai Lan, Teddy Lee, Jan Leike, Jade Leung, Daniel Levy, Chak Ming Li, Rachel Lim, Molly Lin, Stephanie Lin, Mateusz Litwin, Theresa Lopez, Ryan Lowe, Patricia Lue, Anna Makanju, Kim Malfacini, Sam Manning, Todor Markov, Yaniv Markovski, Bianca Martin, Katie Mayer, Andrew Mayne, Bob McGrew, Scott Mayer McKinney, Christine McLeavey, Paul McMillan, Jake McNeil, David Medina, Aalok Mehta, Jacob Menick, Luke Metz, Andrey Mishchenko, Pamela Mishkin, Vinnie Monaco, Evan Morikawa, Daniel Mossing, Tong Mu, Mira Murati, Oleg Murk, David Mély, Ashvin Nair, Reiichiro Nakano, Rajeev Nayak, Arvind Neelakantan, Richard Ngo, Hyeonwoo Noh, Long Ouyang, Cullen O'Keefe, Jakub Pachocki, Alex Paino, Joe Palermo, Ashley Pantuliano, Giambattista Parascandolo, Joel Parish, Emy Parparita, Alex Passos, Mikhail Pavlov, Andrew Peng, Adam Perelman, Filipe de Avila Belbute Peres, Michael Petrov, Henrique Ponde de Oliveira Pinto, Michael, Pokorny, Michelle Pokrass, Vitchyr H. Pong, Tolly Powell, Alethea Power, Boris Power, Elizabeth Proehl, Raul Puri, Alec Radford, Jack Rae, Aditya Ramesh, Cameron Raymond, Francis Real, Kendra Rimbach, Carl Ross, Bob Rotsted, Henri Roussez, Nick Ryder, Mario Saltarelli, Ted Sanders, Shibani Santurkar, Girish Sastry, Heather Schmidt, David Schnurr, John Schulman, Daniel Selsam, Kyla Sheppard, Toki Sherbakov, Jessica Shieh, Sarah Shoker, Pranav Shyam, Szymon Sidor, Eric Sigler, Maddie Simens, Jordan Sitkin, Katarina Slama, Ian Sohl, Benjamin Sokolowsky, Yang Song, Natalie Staudacher, Felipe Petroski Such, Natalie Summers, Ilya Sutskever, Jie Tang, Nikolas Tezak, Madeleine B. Thompson, Phil Tillet, Amin Tootoonchian, Elizabeth Tseng, Preston Tuggle, Nick Turley, Jerry Tworek, Juan Felipe Cerón Uribe, Andrea Vallone, Arun Vijayvergiya, Chelsea Voss, Carroll Wainwright, Justin Jay Wang, Alvin Wang, Ben Wang, Jonathan Ward, Jason Wei, CJ Weinmann, Akila Welihinda, Peter Welinder, Jiayi Weng, Lilian Weng, Matt Wiethoff, Dave Willner, Clemens Winter, Samuel Wolrich, Hannah Wong, Lauren Workman, Sherwin Wu, Jeff Wu, Michael Wu, Kai Xiao, Tao Xu, Sarah Yoo, Kevin Yu, Qiming Yuan, Wojciech Zaremba, Rowan Zellers, Chong Zhang, Marvin Zhang, Shengjia Zhao, Tianhao Zheng, Juntang Zhuang, William Zhuk, and Barret Zoph. 2024. GPT-4 technical report. Preprint, arXiv:2303.08774.

Artidoro Pagnoni, Ram Pasunuru, Pedro Rodriguez, John Nguyen, Benjamin Muller, Margaret Li, Chunting Zhou, Lili Yu, Jason Weston, Luke Zettlemoyer, Gargi Ghosh, Mike Lewis, Ari Holtzman, and Srinivasan Iyer. 2024. Byte latent transformer: Patches scale better than tokens. *Preprint*, arXiv:2412.09871.

Aleksandar Petrov, Emanuele La Malfa, Philip Torr,

and Adel Bibi. 2023. Language model tokenizers introduce unfairness between languages. In *Thirty*seventh Conference on Neural Information Processing Systems.

- Buu Phan, Marton Havasi, Matthew Muckley, and Karen Ullrich. 2024. Understanding and mitigating tokenization bias in language models. *Preprint*, arXiv:2406.16829.
- Tiago Pimentel and Clara Meister. 2024. How to compute the probability of a word. In *Proceedings of the* 2024 Conference on Empirical Methods in Natural Language Processing, Miami, Florida, USA. Association for Computational Linguistics.
- Phillip Rust, Jonas Pfeiffer, Ivan Vulić, Sebastian Ruder, and Iryna Gurevych. 2021. How good is your tokenizer? On the monolingual performance of multilingual language models. In Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers), pages 3118–3135, Online. Association for Computational Linguistics.
- Craig W. Schmidt, Varshini Reddy, Haoran Zhang, Alec Alameddine, Omri Uzan, Yuval Pinter, and Chris Tanner. 2024. Tokenization is more than compression. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 678–702, Miami, Florida, USA. Association for Computational Linguistics.
- Rico Sennrich, Barry Haddow, and Alexandra Birch. 2016. Neural machine translation of rare words with subword units. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1715–1725, Berlin, Germany. Association for Computational Linguistics.
- Aaditya K. Singh and DJ Strouse. 2024. Tokenization counts: the impact of tokenization on arithmetic in frontier LLMs. *Preprint*, arXiv:2402.14903.
- Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurelien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. 2023a. LLaMA: Open and efficient foundation language models. *Preprint*, arXiv:2302.13971.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura,

Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurelien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. 2023b. Llama 2: Open foundation and fine-tuned chat models. *Preprint*, arXiv:2307.09288.

- Lili Yu, Daniel Simig, Colin Flaherty, Armen Aghajanyan, Luke Zettlemoyer, and Mike Lewis. 2023. MEGABYTE: Predicting million-byte sequences with multiscale transformers. In *Thirty-seventh Conference on Neural Information Processing Systems*.
- Vilém Zouhar, Clara Meister, Juan Gastaldi, Li Du, Mrinmaya Sachan, and Ryan Cotterell. 2023a. Tokenization and the noiseless channel. In Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 5184–5207, Toronto, Canada. Association for Computational Linguistics.
- Vilém Zouhar, Clara Meister, Juan Gastaldi, Li Du, Tim Vieira, Mrinmaya Sachan, and Ryan Cotterell. 2023b. A formal perspective on byte-pair encoding. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 598–614, Toronto, Canada. Association for Computational Linguistics.

A Proof of Lemma 2

Lemma 2. If a max-2-SAT instance is satisfiable, then the direct tokenisation instance output by Reduction 1 is also satisfiable. Formally:

$$M2S(\mathcal{X}, \mathcal{L}, \psi) \implies Tok_{\phi}(R1(\mathcal{X}, \mathcal{L}, \psi))$$
(14)

Proof. First, note that if $M2S(\mathcal{X}, \mathcal{L}, \psi)$, then we have that Eq. (7) holds:

$$\psi \le \max_{\chi \in \{\mathbf{F}, \mathbf{T}\}^J} \sum_{i=1}^I \mathbb{1}\{L_i^1 \lor L_i^2\}$$
(29)

Now, without loss of generality, let a satisfying solution have values x_j^* . In this case, for each variable X_j , we construct token $\odot x_j^{\mathsf{T}} \odot$ if x_j^* is true, or $\odot x_j^{\mathsf{F}} \odot$ if x_j^* is false. This gives us a total of J new tokens, so satisfies the $|\mathcal{S}| = |\Sigma| + K$ condition. Now we just need to count the symbols output by this solution to see if Eq. (9) is satisfied, since any given tokenisation $\mathsf{tok}(\cdot, \mathcal{S})$ will provide an upper bound on the optimal tokenisation in terms of compression:

$$\sum_{\mathbf{c}\in\mathcal{D}} |\mathsf{tok}_{\diamond}[\mathcal{S}](\mathbf{c})| \ge \min_{\mathcal{S}'\subset\Sigma^*} \sum_{\mathbf{c}\in\mathcal{D}} |\mathsf{tok}_{\diamond}[\mathcal{S}'](\mathbf{c})|$$
s.t. $|\mathcal{S}'| = |\Sigma| + K$
(30)

For each pair of strings $\odot x_j^{\mathsf{T}} \odot$ and $\odot x_j^{\mathsf{F}} \odot$ in \mathcal{D}_1 , one is compressed into a single subword while the other is kept as originally—using 3 symbols. We thus have that the strings in \mathcal{D}_1 will occupy a total of (1+3)J characters, and:

$$\sum_{\mathbf{c}\in(\bigcup_{i=1}^{f}\mathcal{D}_{1})}|\mathsf{tok}_{\diamond}[\mathcal{S}](\mathbf{c})| = 4fJ$$
(31)

Similarly, for each string in \mathcal{D}_2 of form $\otimes x_j^{\mathsf{T}} \otimes x_j^{\mathsf{F}} \otimes$, we have that either token $\otimes x_j^{\mathsf{T}} \otimes \operatorname{or} \otimes x_j^{\mathsf{F}} \otimes$ exists. So each of these strings is compressed from 5 into 3 symbols. We thus have:

$$\sum_{\in (\bigcup_{-1}^{f'} \mathcal{D}_2)} |\mathsf{tok}_{\diamond}[\mathcal{S}](\mathbf{c})| = 3f'J$$
(32)

Finally, we have strings in \mathcal{D}_3 of form $\odot L_i^1 \odot L_i^2 \odot$. These strings will be compressed into 3 symbols if $\odot L_i^1 \odot$ or $\odot L_i^2 \odot$ (or both) exist, and kept with 5 symbols otherwise. We thus have:

$$\sum_{\mathbf{c}\in\mathcal{D}_{3}}|\mathsf{tok}_{\diamond}[\mathcal{S}](\mathbf{c})| = \sum_{\mathbf{c}\in\mathcal{D}_{3}}\left(5-2\,\mathbb{1}\left\{\begin{array}{c}\otimes L_{i}^{1}\otimes\in\mathcal{S}\\\text{or}\\\otimes L_{i}^{2}\otimes\in\mathcal{S}\end{array}\right\}\right)$$
(33a)

$$=5I-2\sum_{\mathbf{c}\in\mathcal{D}_{3}}\mathbb{1}\left\{\begin{array}{l} \textcircled{\circ} L_{i}^{1} \textcircled{\circ} \in \mathcal{S} \\ \text{or} \\ \textcircled{\circ} L_{i}^{2} \textcircled{\circ} \in \mathcal{S} \end{array}\right\}$$
(33b)

$$=5I - 2\sum_{i=1}^{I} \mathbb{1}\{L_i^1 \lor L_i^2\}$$
(33c)

$$\leq 5I - 2\psi$$
 (33d)

where, by construction, we have that a subword $\odot L_i \odot \in S$ if and only if its associated variable $(x_j \text{ or } \neg x_j)$ is true. Summing together the lengths in Eqs. (31) to (33), we get that

$$\sum_{\mathbf{c}\in\mathcal{D}}|\mathsf{tok}_{\diamond}[\mathcal{S}](\mathbf{c})| \leq \delta = (4f+3f')J+5I-2\psi$$
(34)

which concludes the proof.

B Proof of Lemma 3

Lemma 3. If the direct tokenisation instance output by Reduction 1 is satisfiable, the max-2-SAT instance reduced to it is as well. Formally:

$$Tok_{\phi}(R1(\mathcal{X}, \mathcal{L}, \psi)) \implies M2S(\mathcal{X}, \mathcal{L}, \psi)$$
(15)

Proof. First, note that the dataset \mathcal{D} output by Reduction 1 has a total of characters:

$$\sum_{\mathbf{c}\in\mathcal{D}}|\mathbf{c}| = (6f + 5f')J + 5I \tag{35}$$

Further, let:

$$\operatorname{toklen}(\mathcal{D}, \mathcal{S}) \stackrel{\text{def}}{=} \sum_{\mathbf{c} \in \mathcal{D}} |\operatorname{tok}_{\diamond}[\mathcal{S}](\mathbf{c})|, \qquad \qquad \mathcal{S}_{0} = \bigcup_{j=1}^{J} \{ \odot x_{j}^{\mathsf{T}} \odot, \odot x_{j}^{\mathsf{F}} \odot \}$$
(36)

The maximum number of symbols in this dataset after compression is set to $\delta = (4f + 3f') J + 5I - 2\psi$. This means that, to satisfy this objective, there must exist a vocabulary whose tokeniser compresses the text by at least $(2f + 2f') J + 2\psi$ symbols. We now prove this lemma in three steps: (1) we show that any solution which compresses the text by at least 2fJ symbols must only have subwords of the form $(x_j^T) = x_j^T$ or $(x_j^T) = x_j^T$.

LemmaProofStep 1. (Step 1). Any solution which compresses the text by at least 2fJ symbols must only have subwords of the form $@x_i^T @ or @x_i^F @$, i.e.,:

$$\left(\operatorname{toklen}(\mathcal{D}, \mathcal{S}) \leq \underbrace{(4f + 5f')J + 5I}_{\sum_{c \in \mathcal{D}} |c| - 2fJ} \right) \implies \mathcal{S} \subset \mathcal{S}_0$$
(37)

Proof. First, given a solution with $S \subset S_0$, each subword $s \in S$ will replace at least f strings in \mathcal{D}_1 —i.e., with form $\odot x_j^{\mathrm{T}} \odot$ or $\odot x_j^{\mathrm{F}} \odot$ —for a single subword, thus saving 2f characters. Since we have |S| = K = J tokens, we save exactly 2fJ symbols:

$$\mathcal{S} \subset \mathcal{S}_0 \implies \left(\mathsf{toklen}(\mathcal{D}_1, \mathcal{S}') = \underbrace{4fJ}_{\sum_{c \in \mathcal{D}_1} |c| - 2fJ} \right) \tag{38}$$

Note now that any solution S' for which $S' \not\subset S_0$ has at least one subword which is not of the form $\odot x_j^T \odot$ or $\odot x_j^F \odot$; this subword $s \notin S_0$ will thus not compress strings in \mathcal{D}_1 by 2f symbols, but by at most f:

$$\mathcal{S}' \not\subset \mathcal{S}_0 \implies \left(\operatorname{toklen}(\mathcal{D}_1, \mathcal{S}') \ge \underbrace{4f(J-1) + 5f}_{\sum_{c \in \mathcal{D}_1} |c| - 2fJ + f} \right)$$
(39)

Even if this new subword were able to fully compress strings in D_2 and D_3 to a single symbol each, it would reach a compression of at most 4f'J + 4I. Since by design f = 4f'J + 4I + 1, we get that:

$$\mathcal{S}' \not\subset \mathcal{S}_0 \implies \left(\operatorname{toklen}(\mathcal{D}, \mathcal{S}') \ge 4fJ + f + f'J + I > (4f + 5f')J + 5I \right)$$
(40)

which concludes this step of the proof.

LemmaProofStep 2. (Step (2)). Any solution which compresses the text by at least (2f + 2f')J symbols must only have either subword $\bigotimes x_j^T \bigotimes or \bigotimes x_j^F \bigotimes for$ any variable X_j , i.e.,:

$$\left(\texttt{toklen}(\mathcal{D}, \mathcal{S}) \leq \underbrace{(4f + 3f')J + 5I}_{\sum_{\mathbf{c} \in \mathcal{D}} |\mathbf{c}| - (2f + 2f')J} \right) \implies \forall_{j \in \{1, \dots, J\}} |\mathcal{S} \cap \{ \odot x_j^{\mathsf{T}} \odot, \odot x_j^{\mathsf{F}} \odot \}| = 1$$
(41)

Proof. In this step of the proof, we show that satisfying solutions must have one and only one of subwords $\odot x_j^{\mathsf{T}} \odot$ and $\odot x_j^{\mathsf{F}} \odot$ for any variable X_j . As before, it's easy to see that a solution of the form described achieves at least (2f + 2f')J symbol compression. Each subword of form $\odot x_j^{\mathsf{T}} \odot$ or $\odot x_j^{\mathsf{F}} \odot$ saves exactly 2f characters in the strings in \mathcal{D}_1 . Further, because we always have either subword $\odot x_j^{\mathsf{T}} \odot$ or $\odot x_j^{\mathsf{F}} \odot$ for each value of j, we also get 2f' compression in the strings in \mathcal{D}_2 :

$$\forall_{j \in \{1,\dots,J\}} | \mathcal{S} \cap \{ \odot x_j^{\mathsf{T}} \odot, \odot x_j^{\mathsf{F}} \odot \} | = 1$$

$$\Longrightarrow \left(\mathsf{toklen}(\mathcal{D}_1, \mathcal{S}) = \underbrace{4fJ}_{\sum_{\mathbf{c} \in \mathcal{D}_1} |\mathbf{c}| - 2fJ} \right) \mathsf{and} \left(\mathsf{toklen}(\mathcal{D}_2, \mathcal{S}) = \underbrace{3f'J}_{\sum_{\mathbf{c} \in \mathcal{D}_2} |\mathbf{c}| - 2f'J} \right)$$

$$(42)$$

Now note that this is not true if both $\odot x_j^T \odot$ and $\odot x_j^F \odot$ exist for a single *j*; in this case, only one of the tokens can be applied to $\odot x_j^T \odot x_j^F \odot$, and thus both tokens together lead to a benefit of 2 instead of 4. If both $\odot x_j^T \odot$ and $\odot x_j^F \odot$ exist for any token X_j , this implies that neither of $\odot x_{j'}^T \odot$ and $\odot x_{j'}^F \odot$ exists for some other $X_{j'}$, resulting in an uncompressed string. Then, we get at most a compression of 2fJ + 2f'(J-1) + 4I:

$$\exists_{j \in \{1,\dots,J\}} |\mathcal{S}' \cap \{ \odot x_j^{\mathsf{T}} \odot, \odot x_j^{\mathsf{F}} \odot \}| \neq 1 \implies \left(\mathsf{toklen}(\mathcal{D}, \mathcal{S}') \ge \underbrace{(4f + 3f')J + f' + I}_{\sum_{\mathbf{c} \in \mathcal{D}} |\mathbf{c}| - (2f + 2f)'J + f' - 4I} \right)$$
(43)

By construction f' = 4I + 1, which leads to:

$$\exists_{j \in \{1,\dots,J\}} |\mathcal{S}' \cap \{ \circledcirc x_j^{\mathsf{T}} \circledcirc, \circledcirc x_j^{\mathsf{F}} \circledcirc\} | \neq 1 \implies \left(\mathsf{toklen}(\mathcal{D}, \mathcal{S}') > (4f + 3f')J + 5I \right)$$
(44)

This concludes the proof.

LemmaProofStep 3. (Step (3)). Any tokenisation problem with a solution which compresses the text by at least $(2f + 2f')J + 2\psi$ symbols must be produced by a max-2-SAT problem with at least ψ satisfied clauses, i.e.,:

$$\left(\operatorname{toklen}(\mathcal{D}, \mathcal{S}) \leq \underbrace{(4f + 3f')J + 5I - 2\psi}_{\sum_{c \in \mathcal{D}} |c| - (2f + 2f')J + 2\psi} \right) \implies \operatorname{M2S}(\mathcal{X}, \mathcal{L}, \psi)$$
(45)

Proof. Finally, we now know any solution with this compression must have—for any variable X_j —either subword $\otimes x_j^T \otimes$ or $\otimes x_j^F \otimes$. We can thus create a bijection $\operatorname{Conv}_{S \to \chi}$ between the set of possible vocabularies respecting this condition, and the set of T/F assignments to SAT variables χ :

$$\operatorname{Conv}_{\mathcal{S} \to \chi}(\mathcal{S}) = \left\{ \begin{array}{ll} \mathsf{T} & \operatorname{if} \odot x_j^{\mathsf{T}} \odot \in \mathcal{S} \\ \mathsf{F} & \operatorname{if} \odot x_j^{\mathsf{F}} \odot \in \mathcal{S} \end{array} \right\}_{j=1}^{J}$$
(46)

Further, note that vocabularies of this form (as shown in Eq. (42)) lead to exactly (2f + 2f')J symbols being compressed in \mathcal{D}_1 and \mathcal{D}_2 . To achieve the target compression, a solution must thus compress \mathcal{D}_3 by at least 2ψ symbols. Now note that for any string $\odot L_i^1 \odot L_i^2 \odot$ in \mathcal{D}_3 we have three compression options: $\odot L_i^1 \odot$ will be compressed, saving 2 symbols; $\odot L_i^2 \odot$ will be compressed, also saving 2 symbols; or nothing will be compressed. More specifically, $\odot L_i^1 \odot$ can be compressed if L_i^1 represents X_j and subword $\odot x_i^T \odot$ exists, or if L_i^1 represents $\neg X_j$ and subword $\odot x_i^F \odot$ exists; the same is true for $\odot L_i^2 \odot$. They cannot both be compressed, however, as there is only one symbol \odot between the literals. We thus get a compression of 2 symbols for each of these strings if at least one of its literals has an associated subword in \mathcal{S} . Note thus that whenever a string $\odot L_i^1 \odot$ is compressed by 2 symbols using vocabulary \mathcal{S} , the max-2-SAT disjunction $L_i^1 \lor L_i^2$ will also be satisfied by assignment $\chi = \text{Conv}_{\mathcal{S} \to \chi}(\mathcal{S})$; similarly, whenever this string suffers no compression (i.e., having a compression of zero), the max-2-SAT disjunction will not be satisfied. As our condition assumes a compression of at least 2ψ symbols, we know that we have at least ψ strings for which a literal has an associated subword. We can thus write:

$$2\psi \leq \max_{\mathcal{S} \subset \Sigma^*} \sum_{\mathbf{c} \in \mathcal{D}_3} |\mathbf{c}| - |\mathsf{tok}_{\diamond}[\mathcal{S}](\mathbf{c})|$$
s.t. $|\mathcal{S}| = J$ and $\forall_{j \in \{1, \dots, J\}} |\mathcal{S} \cap \{ \odot x_j^{\mathsf{T}} \odot, \odot x_j^{\mathsf{F}} \odot \}| = 1$

$$= \max \sum_{\substack{2 \text{ I} \\ \text{or } }} \sum_{\substack{3 \text{ I} \\ \text{or } }}$$

$$= \max_{\mathcal{S} \subset \Sigma^{*}} \sum_{\odot L_{i}^{1} \odot L_{i}^{2} \odot \in \mathcal{D}_{3}} 21 \left\{ \text{ or } \\ \odot L_{i}^{2} \odot \in \mathcal{S} \right\}$$
(47b)
s.t. $|\mathcal{S}| = J \text{ and } \forall_{j \in \{1, \dots, J\}} |\mathcal{S} \cap \{ \odot x_{j}^{\mathsf{T}} \odot, \odot x_{j}^{\mathsf{F}} \odot \}| = 1$

$$= \max_{\chi \in \{0,1\}^J} \sum_{i=1}^{I} 2\mathbb{1}\{L_i^1 \lor L_i^2\}$$
(47c)

$$\Rightarrow M2S(\mathcal{X}, \mathcal{L}, \psi) \tag{47d}$$

We thus know that, if a satisfying tokenisation solution exists, then the associated max-2-SAT problem will also be satisfiable. This concludes the proof.

_

C Proof of Lemma 6

Lemma 6. If a max-2-SAT instance is satisfiable, then the bottom-up tokenisation instance output by *Reduction 2 is also satisfiable. Formally:*

$$M2S(\mathcal{X}, \mathcal{L}, \psi) \implies Tok_{\uparrow}(R2(\mathcal{X}, \mathcal{L}, \psi))$$
(23)

Proof. Our proof starts by first defining the three following lists of merges, which will be included in any satisfying solution to the tokenisation problem:

$$\mathbf{m}_{1} = \bigcup_{j=1}^{J} \left[\langle \otimes, x_{j}^{\mathsf{F}} \rangle, \langle x_{j}^{\mathsf{T}}, \otimes \rangle \right], \quad \mathbf{m}_{3} = \bigcup_{j=1}^{J} \left[\langle x_{j}^{\mathsf{F}}, \otimes \rangle, \langle \otimes, x_{j}^{\mathsf{T}} \rangle \right], \quad \mathbf{m}_{5} = \bigcup_{j=1}^{J} \left[\langle \otimes, x_{j}^{\mathsf{F}} \rangle, \langle x_{j}^{\mathsf{T}}, \otimes \rangle \right]$$
(48)

Now, without loss of generality, let a satisfying solution to max-2-SAT have values x_j^* . We then construct two other lists of merges, which depend on this max-2-SAT solution:

$$\mathbf{m}_{2} = \bigcup_{j=1}^{J} \begin{bmatrix} \langle \odot, x_{j}^{\mathsf{T}} \otimes \rangle & \text{if } x_{j}^{\star} = \mathsf{T} \\ \langle \otimes x_{j}^{\mathsf{F}}, \odot \rangle & \text{else} \end{bmatrix}, \qquad \mathbf{m}_{4} = \bigcup_{j=1}^{J} \begin{bmatrix} \langle \odot x_{j}^{\mathsf{T}}, \odot \rangle & \text{if } x_{j}^{\star} = \mathsf{T} \\ \langle \odot, x_{j}^{\mathsf{F}} \odot \rangle & \text{else} \end{bmatrix}$$
(49)

in words, we create merges $\langle \odot, x_j^T \otimes \rangle$ and $\langle \odot x_j^T, \odot \rangle$ if x_j^* is true, or $\langle \otimes x_j^F, \odot \rangle$ and $\langle \odot, x_j^F \odot \rangle$ if x_j^* is false. We then create a merge sequence by concatenating these lists in order:

$$\mathbf{m} = \mathbf{m}_1 \circ \mathbf{m}_2 \circ \mathbf{m}_3 \circ \mathbf{m}_4 \circ \mathbf{m}_5 \tag{50}$$

This gives us a total of $|\mathbf{m}| = K = 8J$ merges. Now we just need to count the symbols output by this solution to see if Eq. (17) is satisfied, since any given tokenisation $tok_{\uparrow}[\mathbf{m}]$ will provide an upper bound on the optimal tokenisation in terms of compression:

$$\sum_{\mathbf{c}\in\mathcal{D}} |\mathsf{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})| \ge \min_{\mathbf{m}'\subset\mathcal{M}^*} \sum_{\mathbf{c}\in\mathcal{D}} |\mathsf{tok}_{\uparrow}[\mathbf{m}'](\mathbf{c})|$$
s.t. $|\mathbf{m}'| = K$
(51)

С	$\mathtt{tok}_{\uparrow}[\mathbf{m}_1](\mathbf{c})$	$\mathtt{tok}_{\uparrow}[\mathbf{m}_{1}\circ\mathbf{m}_{2}\circ\mathbf{m}_{3}](\mathbf{c})$	$\mathtt{tok}_{\uparrow}[\mathbf{m}_{1}\circ\mathbf{m}_{2}\circ\mathbf{m}_{3}\circ\mathbf{m}_{4}\circ\mathbf{m}_{5}](\mathbf{c})$	$ \texttt{tok}_{\uparrow}[\mathbf{m}](\mathbf{c}) $
$\langle \odot, x_i^{T} \rangle$		$\langle \odot x_{i}^{\mathrm{T}} \rangle$		1
$\langle x_j^{\mathrm{F}}, \tilde{\odot} \rangle$		$\langle x_{j}^{\mathtt{F}} \circ \rangle$		1
$\langle x_{j}^{\mathrm{T}}, \odot \rangle$		•	$\langle x_{i}^{\mathrm{T}} \odot \rangle$	1
$\langle \odot, x_i^{\rm F} \rangle$			$\langle \odot x_{j}^{F} \rangle$	1
$\langle x_{i}^{\mathrm{T}}, \overset{\circ}{\otimes} \rangle$	$\langle x_{i}^{\mathrm{T}}\otimes \rangle$			1
$\langle \otimes, x_j^{ extsf{F}} angle$	$\langle \otimes x_j^{ m F} angle$	•		1

Table 1: Example of applying **m** in \mathcal{D}_1 of bottom-up tokenisation problem obtained from Reduction 2. The dot symbol \cdot denotes the string not changing under the given merge.

с	$\mathtt{tok}_{\uparrow}[\mathbf{m}_1](\mathbf{c})$	$\mathtt{tok}_{\uparrow}[\mathbf{m}_{1}\circ\mathbf{m}_{2}](\mathbf{c})$		$\mathtt{tok}_{\uparrow}[\mathbf{m}_{1}\circ\mathbf{m}_{2}\circ\mathbf{m}_{3}](\mathbf{c})$	$\mathtt{tok}_{\uparrow}[\mathbf{m}_{1}\circ\mathbf{m}_{2}\circ\mathbf{m}_{3}\circ\mathbf{m}_{4}]($) $ \texttt{tok}_{\uparrow}[\mathbf{m}](\mathbf{c}) $	
		$x_j^\star = \mathtt{T}$	$x_j^\star = \mathbf{F}$		$x_j^\star = \mathtt{T}$	$x_j^\star = \mathbf{F}$	$x_j^\star = \mathbf{T}$	$x_j^\star = \mathbf{F}$
$\langle \odot, x_i^{\mathrm{T}}, \odot \rangle$				$\langle \odot x_i^{T}, \odot \rangle$	$\langle \odot x_i^{\mathrm{T}} \odot \rangle$	$\langle \odot, x_i^{T} \odot \rangle$	1	2
$\langle \odot, x_i^{\mathbf{F}}, \odot \rangle$	•	•		$\langle \odot, x_i^{\mathbf{F}} \odot \rangle$	$\langle \odot, x_j^{\mathbf{F}} \odot \rangle$	$\langle \odot x_{i}^{\vec{\mathbf{F}}} \odot \rangle$	2	1
$\langle \odot, x_i^{\mathrm{T}}, \otimes \rangle$	$\langle \odot, x_i^{T} \otimes \rangle$	$\langle \odot x_i^{T} \otimes \rangle$	$\langle \odot, x_i^{T} \otimes \rangle$				1	2
$\langle \otimes, x_j^{\mathrm{F}}, \odot angle$	$\langle \otimes x_j^{{ m F}'}, \odot angle$	$\langle \otimes, x_j^{\mathbf{F}} \otimes \rangle$	$\langle \otimes x_j^{ec{\mathbf{F}}} \odot angle$				2	1

Table 2: Example of applying **m** in \mathcal{D}_2 of bottom-up tokenisation problem obtained from Reduction 2. The dot symbol \cdot denotes the string not changing under the given merge.

By applying the merges \mathbf{m} , each string in \mathcal{D}_1 will be compressed into a single subword; note that \mathbf{m}_2 and \mathbf{m}_4 will have no effect on these strings. This is easy to see by applying merges sequentially to these strings, as displayed in Tab. 1. leading to:

$$\sum_{\mathbf{c}\in(\bigcup_{j=1}^{f}\mathcal{D}_{1})}|\mathsf{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})| = 6fJ$$
(52)

For each pair of strings $\odot x_j^{\mathsf{T}} \odot$ and $\odot x_j^{\mathsf{F}} \odot$ in \mathcal{D}_2 , one is compressed into a single subword while the other is only compressed to two subwords—the one with x_j^{T} is compressed to a single symbol if $x_j^{\mathsf{*}} = \mathsf{T}$ and the one with x_j^{F} otherwise. The same is true for each pair of strings $\odot x_j^{\mathsf{T}} \otimes$ and $\otimes x_j^{\mathsf{F}} \odot$, also in \mathcal{D}_2 . This is displayed in Tab. 2. We thus have that, for each variable X_j , the strings in \mathcal{D}_2 will occupy a total of (1 + 2 + 1 + 2)J characters, and:

$$\sum_{\mathbf{c}\in(\bigcup_{j=1}^{f}\mathcal{D}_{1})}|\mathsf{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})| = 6f'J$$
(53)

Similarly, each string in D_3 and D_4 will be compressed into only 2 symbols after this tokeniser is applied to it. We thus have:

$$\sum_{\mathbf{c}\in(\bigcup_{i=1}^{f''}\mathcal{D}_3)} |\mathsf{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})| = 4f''J, \qquad \sum_{\mathbf{c}\in(\bigcup_{i=1}^{f'''}\mathcal{D}_4)} |\mathsf{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})| = 4f'''J$$
(54)

Finally, we have the strings in \mathcal{D}_5 . These strings are constructed such that they will be compressed into 2 symbols if either L_i^1 or L_i^2 evaluates to T, and kept with 3 symbols otherwise; see Tab. 4 for a detailed

\mathcal{D}	с	$\mathtt{tok}_{\uparrow}[\mathbf{m}_1](\mathbf{c})$	$\mathtt{tok}_{\uparrow}[\mathbf{m}_{1}\circ\mathbf{m}_{2}](\mathbf{c})$		$\mathtt{tok}_{\uparrow}[\mathbf{m}_{1}\circ\mathbf{m}_{2}\circ\mathbf{m}_{3}](\mathbf{c})$		$\mathtt{tok}_{\uparrow}[\mathbf{m}_{1}\circ\mathbf{m}_{2}\circ\mathbf{m}_{3}\circ\mathbf{m}_{4}](\mathbf{c})$		$\mathtt{tok}_{\uparrow}[\mathbf{m}_{1}\circ\mathbf{m}_{2}\circ\mathbf{m}_{3}\circ\mathbf{m}_{5}](\mathbf{c})$		$ \texttt{tok}_{\uparrow}[\mathbf{m}](\mathbf{c}) $
			$x_j^\star = \mathbf{T}$	$x_j^\star = \mathbf{F}$	$x_j^{\star} = \mathbf{T}$	$x_j^\star = \mathbf{F}$	$x_j^\star = \mathbf{T}$	$x_j^\star = \mathbf{F}$	$x_j^{\star} = \mathbf{T}$	$x_j^\star = \mathbf{F}$	
\mathcal{D}_3	$\langle \odot, x_i^{T}, \odot, x_i^{F}, \odot \rangle$				$\langle \odot x_i^{T}, \odot$	$\langle x_i^{F} \otimes \rangle$	$\langle \odot x_i^{T} \odot, x_i^{F} \odot \rangle$	$\langle \odot x_i^{\mathrm{T}}, \odot x_i^{\mathrm{F}} \odot \rangle$			2
	$\langle \otimes, x_i^{\mathbf{F}}, \odot, x_i^{\mathbf{T}}, \otimes \rangle$		$\langle \otimes x_i^{F}, \odot x_i^{T} \otimes \rangle$	$\langle \otimes x_i^{\mathbf{F}} \odot, x_i^{\mathbf{T}} \otimes \rangle$		1997 - 19					2
\mathcal{D}_4	$\langle \odot, x_{j}^{\mathbf{F}}, \odot, x_{j}^{\mathbf{T}}, \otimes \rangle$	$\langle \odot, \tilde{x}_{j}^{\mathrm{F}}, \odot, \tilde{x}_{j}^{\mathrm{T}} \otimes \rangle$	$\langle \odot, \tilde{x}_{j}^{F}, \odot \tilde{x}_{j}^{T} \otimes \rangle$			$\langle \odot, x_j^{F} \odot, x_j^{T} \otimes \rangle$		$\langle \odot x_{j}^{F} \odot, x_{j}^{T} \otimes \rangle$	$\langle \odot x_{j}^{F}, \odot x_{j}^{T} \otimes \rangle$		2
\mathcal{D}_4	$\langle \otimes, x_j^{\rm F}, \odot, x_j^{\rm T}, \odot \rangle$	$\langle \otimes x_j^{\mathbf{F}}, \odot, x_j^{\mathbf{T}}, \odot \rangle$		$\langle \otimes x_j^{\mathrm{F}} \odot, x_j^{\mathrm{T}}, \odot \rangle$	$\langle \otimes x_j^{\mathrm{F}}, \odot x_j^{\mathrm{T}}, \odot \rangle$	· · ·	$\langle \otimes x_j^{F}, \odot x_j^{T} \odot \rangle$			$\langle \otimes x_j^{F} \odot, x_j^{T} \odot \rangle$	2

Table 3: Example of applying **m** in D_3 and D_4 of the bottom-up tokenisation problem obtained from Reduction 2. The dot symbol \cdot denotes the string not changing under the given merge.

Assignment	Condition	с	$\mathtt{tok}_{\uparrow}[\mathbf{m}_1](\mathbf{c})$	$\mathtt{tok}_{\uparrow}[\mathbf{m}_{1}\circ\mathbf{m}_{2}](\mathbf{c})$	$\mathtt{tok}_{\uparrow}[\mathbf{m}_{1}\circ\mathbf{m}_{2}\circ\mathbf{m}_{3}](\mathbf{c})$	$\mathtt{tok}_{\uparrow}[\mathbf{m}_{1}\circ\mathbf{m}_{2}\circ\mathbf{m}_{3}\circ\mathbf{m}_{4}](\mathbf{c})$	$ \texttt{tok}_{\uparrow}[\mathbf{m}](\mathbf{c}) $
	$x_{i}^{\star} = \mathbf{T} \wedge x_{i'}^{\star} = \mathbf{T}$	$\langle \circledcirc, x_j^{\mathtt{T}}, \circledcirc, x_{j'}^{\mathtt{F}}, \circledcirc \rangle$			$\langle \odot x_j^{\mathtt{T}}, \odot, x_{j'}^{\mathtt{F}} \odot \rangle$	$\langle \odot x_{j}^{T} \odot, x_{j'}^{F} \odot \rangle$	2
$L_i^1 = X_j$ and $L_i^2 = \neg X_{j'}$	$\dot{x_{j}^{\star}} = F \wedge \dot{x_{j'}^{\star}} = T$					$\langle \odot x_{j}^{T}, \odot, x_{j'}^{F} \odot \rangle$	3
D_i D_j and D_i D_j	$x_j^\star = \mathbf{T} \wedge x_{j'}^\star = \mathbf{F}$					$\langle \odot x_j^T \odot, x_{j'}^F \odot \rangle$	2
	$x_j^\star = \mathbb{F} \wedge x_{j'}^\star = \mathbb{F}$					$\langle \odot x_j^{\mathrm{T}}, \odot x_{j'}^{\mathrm{F}} \odot \rangle$	2
	$x_{i}^{\star} = \mathbf{T} \wedge x_{i'}^{\star} = \mathbf{T}$					$\langle \odot x_{i'}^{T} \odot, x_{i}^{F} \odot \rangle$	2
$L_i^1 = \neg X_j$ and $L_i^2 = X_{j'}$	$x_{i}^{\star} = F \wedge x_{i'}^{\star} = T$	$(\odot, x_j), \odot, x_j, \odot)$			$\langle \circledcirc x_{j'}^{\mathrm{T}}, \circledcirc, x_{j}^{\mathrm{F}} \circledcirc \rangle$	$\langle \odot x_{i'}^{T} \odot, x_{i}^{F} \odot \rangle$	2
$L_i = M_j$ and $L_i = M_{j'}$	$\dot{x_{j}^{\star}} = T \wedge \dot{x_{j'}^{\star}} = F$					$\langle \odot x_{j'}^{\mathbf{T}}, \odot, x_{j}^{\mathbf{F}} \odot \rangle$	3
	$x_j^\star = \mathbb{F} \wedge x_{j'}^\star = \mathbb{F}$					$\langle \odot x_{j'}^{\mathrm{T}}, \odot x_{j}^{\mathrm{F}} \odot \rangle$	2
	$x_i^\star = \mathbf{T} \wedge x_{i'}^\star = \mathbf{T}$				$\langle \otimes x_{i}^{F}, \odot, x_{i'}^{F} \odot \rangle$		3
$L_i^1 = \neg X_j$ and $L_i^2 = \neg X_{j'}$	$x_{i}^{\star} = \mathbf{F} \wedge x_{i'}^{\star} = \mathbf{T}$	$\langle \otimes, x_j^{\mathtt{F}}, \odot, x_{j'}^{\mathtt{F}}, \odot \rangle$	$\langle \otimes x^{\mathtt{F}}_{j}, \circledcirc, x^{\mathtt{F}}_{j'}, \circledcirc \rangle$	$\langle \otimes x_{j}^{F} \odot, x_{j'}^{F}, \odot \rangle$	$\langle \otimes x_{j}^{\mathbf{F}} \odot, x_{j'}^{\mathbf{F}} \odot \rangle$		2
$E_i = \langle X_j \text{ and } E_i = \langle X_j \rangle$	$x_{i}^{\star} = \mathbf{T} \wedge x_{i'}^{\star} = \mathbf{F}$				$\langle \otimes x_{i}^{\mathbf{F}}, \odot, \dot{x}_{i'}^{\mathbf{F}} \odot \rangle$	$\langle \otimes x_{i}^{F}, \odot x_{i'}^{F} \odot \rangle$	2
	$\check{x_{j}^{\star}} = \mathbb{F} \wedge \check{x_{j'}^{\star}} = \mathbb{F}$			$\langle \otimes x_j^{\mathbb{F}} \odot, x_{j'}^{\mathbb{F}}, \odot \rangle$	$\langle \otimes x_{j}^{\mathbf{F}} \odot, x_{j'}^{\mathbf{F}} \odot \rangle$		2
	$x_{i}^{\star} = \mathbf{T} \wedge x_{i'}^{\star} = \mathbf{T}$	$\langle \circledcirc, x_j^{\mathtt{T}}, \circledcirc, x_{j'}^{\mathtt{T}}, \otimes \rangle$		$\langle \odot, x_i^T, \odot x_{i'}^T \otimes \rangle$	$\langle \odot x_{i}^{T}, \odot x_{i'}^{T} \otimes \rangle$	$\langle \odot x_{i}^{\mathrm{T}}, \odot x_{i'}^{\mathrm{T}} \otimes \rangle$	2
$L_i^1 = X_j$ and $L_i^2 = X_{j'}$	$x_i^\star = \mathbf{F} \wedge x_{i'}^\star = \mathbf{T}$		$\langle \odot \ r^{T} \odot \ r^{T} \otimes \rangle$	$(\odot, x_j, \odot x_{j'} \otimes)$	$(\odot x_j, \odot x_{j'} \otimes)$	$\langle \odot x_j, \odot x_{j'} \otimes \rangle$	2
$D_i = M_j$ and $D_i = M_{j'}$	$x_{i}^{\star} = \mathbf{T} \wedge x_{i'}^{\star} = \mathbf{F}$		$\langle \odot, x_j, \odot, x_j' \otimes \rangle$		$\langle \odot x_{i}^{T}, \odot, x_{i'}^{T} \otimes \rangle$	$\langle \odot x_{i}^{T} \odot, x_{i'}^{T} \otimes \rangle$	2
	$x_j^{\star} = F \wedge x_{j'}^{\star} = F$			•	$(\otimes x_j, \otimes, x_{j'} \otimes)$		3

Table 4: Example of applying **m** in \mathcal{D}_5 of the bottom-up tokenisation problem obtained from Reduction 2. The dot symbol \cdot denotes the string not changing under the given merge.

simulation of why this is the case. We thus have:

$$\sum_{\mathbf{c}\in\mathcal{D}_{3}}|\mathsf{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})| = \sum_{\mathbf{c}\in\mathcal{D}_{3}} \left(3 - 1 \mathbb{1} \left\{ \begin{array}{l} L_{i}^{1} = X_{j} \text{ and } \langle \odot, x_{j}^{\mathsf{T}} \otimes \rangle, \langle \odot x_{j}^{\mathsf{T}}, \odot \rangle \in \mathbf{m} \\ \text{or} \\ L_{i}^{1} = \neg X_{j} \text{ and } \langle \otimes x_{j}^{\mathsf{F}}, \odot \rangle, \langle \odot, x_{j}^{\mathsf{F}} \odot \rangle \in \mathbf{m} \\ \text{or} \\ L_{i}^{2} = X_{j'} \text{ and } \langle \odot, x_{j'}^{\mathsf{T}} \otimes \rangle, \langle \odot x_{j'}^{\mathsf{T}}, \odot \rangle \in \mathbf{m} \\ \text{or} \\ L_{i}^{2} = \neg X_{j'} \text{ and } \langle \otimes x_{j'}^{\mathsf{F}}, \odot \rangle, \langle \odot, x_{j'}^{\mathsf{F}} \odot \rangle \in \mathbf{m} \end{array} \right\} \right)$$
(55a)

$$= 3I - \sum_{i=1} \mathbb{1}\{L_i^1 \lor L_i^2\}$$
(55b)

$$\leq 3I - \psi$$
 (55c)

where, by construction, we have that a merge in our sequence (e.g., $\langle \odot, x_j^T \otimes \rangle$ or $\langle \otimes x_j^F, \odot \rangle$), if and only if its value is in a satisfying assignment (e.g., $x_j^* = T$ or $x_j^* = F$ respectively). Summing together the lengths in Eqs. (52) to (55), we get that:

$$\sum_{\mathbf{c}\in\mathcal{D}}|\mathsf{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})| \le \delta = (6f + 6f' + 4f'' + 4f''') J + 3I - \psi$$
(56)

which concludes the proof.

D Proof of Lemma 7

Lemma 7. *If the bottom-up tokenisation instance output by Reduction 2 is satisfiable, the* max-2-SAT *instance reduced to it is as well. Formally:*

$$\operatorname{Tok}_{\uparrow}(\operatorname{R2}(\mathcal{X},\mathcal{L},\psi)) \Longrightarrow \operatorname{M2S}(\mathcal{X},\mathcal{L},\psi)$$
(27)

Proof. First, note that:

$$\sum_{\mathbf{c}\in\mathcal{D}} |\mathbf{c}| = (12f + 12f' + 10f'' + 10f''') J + 5I$$
(57)

Further, let:

$$\begin{aligned} \operatorname{toklen}(\mathcal{D}, \mathbf{m}) &\stackrel{\text{def}}{=} \sum_{c \in \mathcal{D}} |\operatorname{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})|, & \mathbf{m}_{0} = \mathbf{m}_{1} \circ \mathbf{m}_{2} \circ \mathbf{m}_{3} \circ \mathbf{m}_{4} \circ \mathbf{m}_{5} \end{aligned} \tag{58} \\ \mathbf{m}_{1} &= \bigcirc_{j=1}^{J} [\langle \otimes, x_{j}^{\mathrm{F}} \rangle, \langle x_{j}^{\mathrm{T}}, \otimes \rangle], & \mathbf{m}_{3} = \bigcirc_{j=1}^{J} [\langle x_{j}^{\mathrm{F}}, \otimes \rangle, \langle \otimes, x_{j}^{\mathrm{T}} \rangle], & \mathbf{m}_{5} = \bigcirc_{j=1}^{J} [\langle \otimes, x_{j}^{\mathrm{F}} \rangle, \langle x_{j}^{\mathrm{T}}, \otimes \rangle] \\ \mathbf{m}_{2} &= \bigcirc_{j=1}^{J} \begin{bmatrix} \langle \otimes, x_{j}^{\mathrm{T}} \otimes \rangle & \operatorname{if} x_{j}^{\star} = \mathrm{T} \\ \langle \otimes x_{j}^{\mathrm{F}}, \otimes \rangle & \operatorname{else} \end{bmatrix}, & \mathbf{m}_{4} = \bigcirc_{j=1}^{J} \begin{bmatrix} \langle \otimes x_{j}^{\mathrm{T}}, \otimes \rangle & \operatorname{if} x_{j}^{\star} = \mathrm{T} \\ \langle \otimes, x_{j}^{\mathrm{F}} \otimes \rangle & \operatorname{else} \end{bmatrix} \\ \mathbf{m}_{j}^{\otimes} &= \left\{ \begin{pmatrix} \langle \otimes x_{j}^{\mathrm{T}}, \otimes \rangle, \langle \otimes, x_{j}^{\mathrm{F}} \otimes \rangle \\ \langle \otimes, x_{j}^{\mathrm{T}} \otimes \rangle, \langle \otimes x_{j}^{\mathrm{F}}, \otimes \rangle \right\}, & \mathbf{m}_{j}^{\otimes} &= \left\{ \begin{pmatrix} \langle \otimes, x_{j}^{\mathrm{T}} \otimes \rangle, \langle \otimes x_{j}^{\mathrm{F}}, \otimes \rangle \\ \langle \otimes x_{j}^{\mathrm{T}}, \otimes \rangle, \langle \otimes x_{j}^{\mathrm{T}}, \otimes \rangle, \rangle \\ \langle \otimes, x_{j}^{\mathrm{T}} \otimes \rangle, \langle \otimes x_{j}^{\mathrm{T}}, \otimes \rangle, \rangle \\ \mathbf{m}_{j}^{\mathrm{T}} &= \left\{ \begin{pmatrix} \langle \otimes x_{j}^{\mathrm{T}}, \otimes \rangle, \langle \otimes, x_{j}^{\mathrm{T}} \otimes \rangle, \\ \langle \otimes, x_{j}^{\mathrm{T}} \otimes \rangle, \langle \otimes x_{j}^{\mathrm{T}}, \otimes \rangle, \rangle \\ \mathbf{m}_{j}^{\mathrm{F}} &= \left\{ \begin{pmatrix} \langle \otimes, x_{j}^{\mathrm{F}} \otimes \rangle, \langle \otimes x_{j}^{\mathrm{F}}, \otimes \rangle, \\ \langle \otimes x_{j}^{\mathrm{F}}, \otimes \rangle, \langle \otimes, x_{j}^{\mathrm{F}} \otimes \rangle, \\ \langle \otimes x_{j}^{\mathrm{F}}, \otimes \rangle, \langle \otimes, x_{j}^{\mathrm{F}} \otimes \rangle, \rangle \\ \langle \otimes x_{j}^{\mathrm{F}}, \otimes \rangle, \langle \otimes, x_{j}^{\mathrm{F}} \otimes \rangle, \rangle \\ \end{array} \right\} \end{aligned}$$

The maximum number of symbols in this dataset after compression is set to $\delta = (6f+6f'+4f''+4f''')J+$ 3 $I-\psi$. This means that to satisfy this objective, there must exist a vocabulary whose tokeniser compresses the text by at least $(6f + 6f' + 6f'' + 6f''')J + 2I + \psi$ symbols. We now prove this lemma in five steps: (1) we show that any solution which compresses the text by at least 6fJ symbols must include all merges in \mathbf{m}_1 , \mathbf{m}_3 , and \mathbf{m}_5 ; (2) we show that any solution which compresses the text by at least (6f + 6f')J symbols must only include either merges in \mathbf{m}_1 , \mathbf{m}_3 , \mathbf{m}_5 , or in either \mathbf{m}_j^{\odot} or \mathbf{m}_j^{\otimes} ; (3) we show that any solution which compresses the text by at least (6f + 6f' + 6f'')J symbols must include, for each $j \in \{1, J\}$, exactly one merge in set \mathbf{m}_j^{\odot} and one in set \mathbf{m}_j^{\otimes} ; (4) we show that any solution which compresses the text by at least (6f + 6f' + 6f'' + 6f''')J symbols must include, for each $j \in \{1, J\}$, exactly one merge in set \mathbf{m}_j^{\odot} ; (5) we show that any solution which compresses the text by at least $(6f + 6f' + 6f'' + 6f'')J + 2I + \psi$ symbols must include, for each $j \in \{1, J\}$, exactly two merge in either set $\mathbf{m}_j^{\mathrm{T}}$ or in set $\mathbf{m}_j^{\mathrm{F}}$; (5) we show that any solution which compresses the text by at least $(6f + 6f' + 4f'' + 4f''')J + 6f'' + 6f''')J + 2I + \psi$ symbols must be produced by a max-2-SAT problem with at least ψ satisfied clauses.

LemmaProofStep 1. (Step (1)). Any solution which compresses the text by at least 6fJ symbols must include all merges in \mathbf{m}_1 , \mathbf{m}_3 , and \mathbf{m}_5 , *i.e.*,:

$$\begin{pmatrix} \operatorname{toklen}(\mathcal{D}, \mathbf{m}) \leq \underbrace{6fJ + (12f' + 10f'' + 10f''') J + 5I}_{\sum_{\mathbf{c} \in \mathcal{D}} |\mathbf{c}| - 6fJ} \end{pmatrix}$$

$$\Longrightarrow \underbrace{\bigcirc_{j=1}^{J} [\langle \otimes, x_{j}^{\mathsf{F}} \rangle, \langle x_{j}^{\mathsf{T}}, \otimes \rangle]}_{\mathbf{m}_{1}} \subset \mathbf{m}, \quad \underbrace{\bigcirc_{j=1}^{J} [\langle x_{j}^{\mathsf{F}}, \otimes \rangle, \langle \otimes, x_{j}^{\mathsf{T}} \rangle]}_{\mathbf{m}_{3}} \subset \mathbf{m}, \quad \underbrace{\bigcirc_{j=1}^{J} [\langle \otimes, x_{j}^{\mathsf{F}} \rangle, \langle x_{j}^{\mathsf{T}}, \otimes \rangle]}_{\mathbf{m}_{5}} \subset \mathbf{m}$$

$$(59)$$

Proof. We prove this statement by contradiction. Assume that one of the subwords above is not present in the tokenisers' merge sequence **m**. In that case, the strings in \mathcal{D}_1 which contain this character string will not be compressed, and will thus still be represented with 2 symbols. There will thus be at most 6J - 1 strings in \mathcal{D}_1 represented with a single symbol, and at least one represented with two symbols. The minimum length achievable would thus be:

$$\operatorname{toklen}(\mathcal{D}, \mathbf{m}) = \sum_{\substack{\mathbf{c} \in \bigcup_{j=1}^{f} \mathcal{D}_{0} \\ \geq (6J-1)f+2f \\} \geq (6J+1)f}} |\operatorname{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})| + \sum_{\substack{\mathbf{c} \in \mathcal{D} \setminus (\bigcup_{j=1}^{f} \mathcal{D}_{0}) \\> 0 \\} > 0} |\operatorname{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})|$$
(60a)
$$> (6J+1)f \qquad \text{By construction } f = (12f' + 10f'' + 10f''') J + 5I$$
(60b)
$$= (6f + 12f' + 10f'' + 10f''') J + 5I$$
(60c)

which contradicts the proofs statement.

LemmaProofStep 2. (Step (2)). Any solution which compresses the text by at least (6f + 6f')J symbols must only include either merges in \mathbf{m}_1 , \mathbf{m}_3 , \mathbf{m}_5 , or in either \mathbf{m}_i^{\otimes} or \mathbf{m}_i^{\otimes} , i.e.,:

Proof. We again prove this statement by contradiction. Assume that **m** has all merges $\mathbf{m}_1, \mathbf{m}_3, \mathbf{m}_5$, but one of its other merges is in neither of the sets \mathbf{m}_j^{\odot} and \mathbf{m}_j^{\otimes} . This means that at least one of the sets \mathbf{m}_j^{\odot} and \mathbf{m}_j^{\otimes} . This means that at least one of the sets \mathbf{m}_j^{\odot} and \mathbf{m}_j^{\otimes} will have no merge in the solution; this is because there are 2J such sets, which—coupled together with the 6J already selected merges in $\mathbf{m}_1, \mathbf{m}_3, \mathbf{m}_5$ —would amount to the maximum of 8J merges. In that case, the strings (e.g., $\odot x_j^{\mathsf{T}} \odot$, $\odot x_j^{\mathsf{T}} \odot$, $\odot x_j^{\mathsf{T}} \odot$ and $\otimes x_j^{\mathsf{F}} \odot$) in \mathcal{D}_2 containing the characters this absent merge represents will not be fully compressed to a single symbol, being represented with 2 symbols instead. There will thus be at most 6J - 1 strings in \mathcal{D}_2 represented with a single symbol, and at least one represented with two symbols. The minimum length achievable would thus be:

$$\operatorname{toklen}(\mathcal{D}, \mathbf{m}) = \sum_{\substack{\mathbf{c} \in \bigcup_{j=1}^{f} \mathcal{D}_{1} \\ = 6fJ}} |\operatorname{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})| + \sum_{\substack{\mathbf{c} \in \bigcup_{j=1}^{f'} \mathcal{D}_{2} \\ \geq (6J-1)f'+2f'}} |\operatorname{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})| + \sum_{\substack{\mathbf{c} \in \mathcal{D} \setminus (\mathcal{D}_{1} \cup \mathcal{D}_{2}) \\ \geq 0}} |\operatorname{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})| + 2f' |\operatorname{tok}_{\downarrow}[\mathbf{c}]| + 2$$

which contradicts the proofs statement.

LemmaProofStep 3. (Step ③). Any solution which compresses the text by at least (6f + 6f' + 6f'')J symbols must include all merges in \mathbf{m}_1 , \mathbf{m}_3 , \mathbf{m}_5 , and, for each $j \in \{1, J\}$, exactly one merge in set \mathbf{m}_j^{\otimes} and one in set \mathbf{m}_j^{\otimes} , i.e.,:

$$\left(\operatorname{toklen}(\mathcal{D}, \mathbf{m}) \leq \underbrace{(6f + 6f' + 4f'')J + 10f'''J + 5I}_{\sum_{c \in \mathcal{D}} |c| - (6f + 6f' + 6f'')J} \right)$$

$$\Longrightarrow \forall_{j \in \{1, \dots, J\}} \left| \mathbf{m} \cap \underbrace{\left\{ \begin{array}{c} \langle \odot x_{j}^{\mathsf{T}}, \odot \rangle, \langle \odot, x_{j}^{\mathsf{F}} \odot \rangle \\ \langle \odot, x_{j}^{\mathsf{T}} \odot \rangle, \langle \odot, x_{j}^{\mathsf{F}} \odot \rangle \end{array} \right\}}_{\mathbf{m}_{j}^{\odot}} \right| = 1 \text{ and } \left| \mathbf{m} \cap \underbrace{\left\{ \begin{array}{c} \langle \odot, x_{j}^{\mathsf{T}} \otimes \rangle, \langle \otimes x_{j}^{\mathsf{F}}, \odot \rangle \\ \langle \odot x_{j}^{\mathsf{T}}, \otimes \rangle, \langle \otimes, x_{j}^{\mathsf{F}} \odot \rangle \end{array} \right\}}_{\mathbf{m}_{j}^{\odot}} \right| = 1$$

$$\text{and } \left| \mathbf{m} \cap \underbrace{\left\{ \begin{array}{c} \langle \odot, x_{j}^{\mathsf{T}} \otimes \rangle, \langle \otimes, x_{j}^{\mathsf{F}}, \odot \rangle \\ \langle \odot x_{j}^{\mathsf{T}}, \otimes \rangle, \langle \otimes, x_{j}^{\mathsf{F}} \odot \rangle \end{array} \right\}}_{\mathbf{m}_{j}^{\odot}} \right| = 1$$

Proof. We again prove this statement by contradiction. First, assume that **m** contains all the merges in $\mathbf{m}_1, \mathbf{m}_3, \mathbf{m}_5$; further, assume all its other merges are contained in sets \mathbf{m}_j^{\odot} and \mathbf{m}_j^{\otimes} . Note now that, if any merge in \mathbf{m}_j^{\otimes} is in the selected merges **m**, the string $\otimes x_j^{\mathsf{F}} \odot x_j^{\mathsf{T}} \otimes in \mathcal{D}_3$ will be compressed to 2 symbols (e.g., $\langle \otimes x_j^{\mathsf{F}}, \odot x_j^{\mathsf{T}} \otimes \rangle$); if none of these merges is present, however, this string will only be compressed to 3 symbols (e.g., $\langle \otimes x_j^{\mathsf{F}}, \odot, x_j^{\mathsf{T}} \otimes \rangle$). The same is true for strings $\Im x_j^{\mathsf{T}} \odot x_j^{\mathsf{F}} \odot$ and merges in \mathbf{m}_j^{\odot} . Now, assume the contradictory case: for a value of $j \in \{1, J\}$, **m** does not satisfy the condition above. As, by construction, our solution has K = 8J merges, and because $|\mathbf{m}_1 \circ \mathbf{m}_3 \circ \mathbf{m}_5| = 6J$, we know that we have 2J merges in sets \mathbf{m}_j^{\odot} and \mathbf{m}_j^{\otimes} . As there are exactly 2J such sets, if the condition above does not hold, at least one of these sets must have no merge present in **m**. In that case, the strings in \mathcal{D}_3 which contain the character string represented by these absent merges will be compressed to three symbols, while others will be compressed to two symbols. There will thus be at most 2J - 1 strings in \mathcal{D}_3 represented with two

symbols, and at least one represented with three symbols. The minimum length achievable would thus be:

$$\operatorname{toklen}(\mathcal{D}, \mathbf{m}) = \sum_{\substack{c \in \bigcup_{i=1}^{f} \mathcal{D}_{1} \cup \bigcup_{i=1}^{f'} \mathcal{D}_{2} \\ = (6f+6f')J}} |\operatorname{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})| + \sum_{\substack{c \in \bigcup_{i=1}^{f''} \mathcal{D}_{3} \\ \geq (2J-1)2f''+3f''}} |\operatorname{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})| + \sum_{\substack{c \in \bigcup_{i=1}^{f'''} \mathcal{D}_{4} \cup \mathcal{D}_{5} \\ \geq (2J-1)2f''+3f''}} |\operatorname{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})| + \sum_{\substack{c \in \bigcup_{i=1}^{f'''} \mathcal{D}_{4} \cup \mathcal{D}_{5} \\ \geq 0}} |\operatorname{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})| + (64a)$$

$$= (6f+6f')J + (4J+1)f'' \qquad \text{By construction } f'' = 10f''' J + 5I$$

$$= (6f+6f'+4f''+10f''') J + 5I \qquad (64c)$$

which contradicts the proof's statement.

LemmaProofStep 4. (Step (4)). Any solution which compresses the text by at least (6f + 6f' + 6f'' + 6f''')J symbols must include all merges in \mathbf{m}_1 , \mathbf{m}_3 , \mathbf{m}_5 , and, for each $j \in \{1, J\}$, exactly one merge in set \mathbf{m}_j^{\odot} and one in set \mathbf{m}_j^{\odot} , such that either both these merges are in $\mathbf{m}_j^{\mathsf{T}}$ or both are in $\mathbf{m}_j^{\mathsf{F}}$, i.e.,:

$$\begin{pmatrix} \operatorname{toklen}(\mathcal{D}, \mathbf{m}) \leq \underbrace{(6f + 6f' + 4f'' + 4f''')J + 5I}_{\sum_{\mathbf{c} \in \mathcal{D}} |\mathbf{c}| - (6f + 6f' + 6f'' + 6f''')J} \end{pmatrix}$$

$$\Rightarrow \forall_{j \in \{1, \dots, J\}} |\mathbf{m} \cap \underbrace{\left\{ \begin{array}{c} \langle @x_j^{\mathsf{T}}, @ \rangle, \langle @, x_j^{\mathsf{T}} \otimes \rangle, \\ \langle @, x_j^{\mathsf{T}} @ \rangle, \langle @, x_j^{\mathsf{T}} \otimes \rangle, \\ \langle @, x_j^{\mathsf{T}} @ \rangle, \langle @, x_j^{\mathsf{T}} \otimes \rangle, \\ \mathbf{m}_j^{\mathsf{T}} \end{array} \right\} | = 2 \text{ or } |\mathbf{m} \cap \underbrace{\left\{ \begin{array}{c} \langle @, x_j^{\mathsf{F}} @ \rangle, \langle @, x_j^{\mathsf{F}} @ \rangle, \\ \langle @x_j^{\mathsf{F}}, @ \rangle, \langle @, x_j^{\mathsf{F}} @ \rangle, \\ \langle @x_j^{\mathsf{F}}, @ \rangle, \langle @, x_j^{\mathsf{F}} @ \rangle, \\ \mathbf{m}_j^{\mathsf{F}} \end{array} \right\} | = 2$$

$$(65)$$

Proof. First, note that the conditions of the step of our proof are stricter than previous ones, so we assume the conditions of steps (1) to (3) hold—i.e., **m** contains all merges in $\mathbf{m}_1, \mathbf{m}_3, \mathbf{m}_5$; further, it has one and only one merge from each set \mathbf{m}_j^{\odot} and \mathbf{m}_j^{\otimes} . (Note that $\mathbf{m}_j^{\odot} \cup \mathbf{m}_j^{\otimes} = \mathbf{m}_j^{\mathsf{T}} \cup \mathbf{m}_j^{\mathsf{F}}$, and that the just-mentioned condition implies $|\mathbf{m} \cap (\mathbf{m}_j^{\mathsf{T}} \cup \mathbf{m}_j^{\mathsf{F}})| = 2$.) We now again prove this statement by contradiction. Consider now the case:

$$\left| \mathbf{m} \cap \underbrace{\left\{ \begin{array}{c} \langle \odot x_j^{\mathsf{T}}, \odot \rangle, \langle \odot, x_j^{\mathsf{T}} \otimes \rangle, \\ \langle \odot, x_j^{\mathsf{T}} \odot \rangle, \langle \odot x_j^{\mathsf{T}}, \otimes \rangle, \end{array} \right\}}_{\mathbf{m}_j^{\mathsf{T}}} \right| = 2 \text{ or } \left| \mathbf{m} \cap \underbrace{\left\{ \begin{array}{c} \langle \odot, x_j^{\mathsf{F}} \odot \rangle, \langle \otimes x_j^{\mathsf{F}}, \odot \rangle, \\ \langle \odot x_j^{\mathsf{F}}, \odot \rangle, \langle \otimes, x_j^{\mathsf{F}} \odot \rangle, \end{array} \right\}}_{\mathbf{m}_j^{\mathsf{F}}} \right| = 2 \tag{67}$$

If this is true, then strings $@x_j^F @ x_j^T @ and <math>\otimes x_j^F @ x_j^T @ in \mathcal{D}_4$ will be compressed to 2 symbols each (e.g., to $\langle @x_j^F, @x_j^T \otimes \rangle$ and $\langle @x_j^F, @x_j^T \otimes \rangle$ or $\langle @x_j^F @, x_j^T \otimes \rangle$ and $\langle @x_j^F, @x_j^T \otimes \rangle$ if this condition is false, however, one of these strings will only be compressed to 3 symbols (e.g., to $\langle @x_j^F, @x_j^T \otimes \rangle$ and $\langle @x_j^F, @, x_j^T \otimes \rangle$). Now, assume the contradictory case: for a value of $j \in \{1, J\}$, **m** does not satisfy the condition above. In that case, the strings in \mathcal{D}_4 for which the condition does not hold will be compressed to 3 + 2 symbols, while others will be compressed to 2 + 2 symbols. There will thus be at most 2J - 1 strings in \mathcal{D}_4 represented with two symbols, and at least one represented with three symbols. The minimum length achievable would thus be:

$$\operatorname{toklen}(\mathcal{D}, \mathbf{m}) = \sum_{\substack{\mathbf{c} \in \bigcup_{i=1}^{f} \mathcal{D}_{1} \cup \bigcup_{i=1}^{f'} \mathcal{D}_{2} \cup \bigcup_{i=1}^{f''} \mathcal{D}_{3} \\ = (6f + 6f' + 4f'')J}} |\operatorname{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})| + \sum_{\substack{\mathbf{c} \in \bigcup_{i=1}^{f'''} \mathcal{D}_{4} \\ \geq (2J - 1)2f''' + 3f'''}} |\operatorname{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})| + \sum_{\substack{\mathbf{c} \in \mathcal{D}_{5} \\ >0}} |\operatorname{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})| (68a)$$

$$= (6f + 6f' + 4f'')J + (4J + 1)f''' \qquad \text{By construction } f''' = 5I(68b)$$

$$= (6f + 6f' + 4f'' + 4f''')J + 5I \qquad (68c)$$

which contradicts the proof's statement.

LemmaProofStep 5. (Step (5)). Any tokenisation problem with a solution which compresses the text by at least $(6f + 6f' + 6f'' + 6f'')J + 2I + \psi$ symbols must be produced by a max-2-SAT problem with at least ψ satisfied clauses, i.e.,:

$$\left(\texttt{toklen}(\mathcal{D}, \mathcal{S}) \leq \underbrace{(6f + 6f' + 4f'' + 4f''')J + 3I - \psi}_{\sum_{\mathbf{c} \in \mathcal{D}} |\mathbf{c}| - (6f + 6f' + 6f'' + 6f''')J + 2I + \psi}\right) \implies \text{M2S}(\mathcal{X}, \mathcal{L}, \psi)$$

Proof. Finally, we now know any solution with this compression must have—for any variable X_j —either two merges in $\mathbf{m}_j^{\mathsf{T}}$ or in $\mathbf{m}_j^{\mathsf{F}}$ (and never both). We can thus create a bijection $\operatorname{Conv}_{\mathbf{m}\to\chi}$ between the set of possible merge sequences respecting this condition, and the set of T/F assignments to SAT variables χ :

$$\operatorname{Conv}_{\mathbf{m}\to\chi}(\mathbf{m}) = \left\{ \begin{array}{ll} \mathsf{T} & \operatorname{if} |\mathbf{m}\cap\mathbf{m}_{j}^{\mathsf{T}}| = 2\\ \mathsf{F} & \operatorname{if} |\mathbf{m}\cap\mathbf{m}_{j}^{\mathsf{F}}| = 2 \end{array} \right\}_{j=1}^{J}$$
(69)

Further, note that merge sequences of this form (as shown in Eq. (42)) lead to exactly (6f + 6f' + 6f'' + 6f'')(6f''')J symbols being compressed in datasets \mathcal{D}_1 to \mathcal{D}_4 . To achieve the target compression, a solution must thus compress \mathcal{D}_5 by at least $2I + \psi$ symbols. Now note that for any string, e.g., $(0L_i^1 \otimes L_i^2 \otimes i)$, in \mathcal{D}_5 we have three compression options: $(0L_i^1 \otimes L_i^2 \otimes i)$ and $L_i^2 \otimes i$ will be compressed, saving 3 symbols; $(0L_i^1 \otimes L_i^2 \otimes i)$ and $(0L_i^2 \otimes i)$ will be compressed, also saving 3 symbols; or only $(0L_i^1 \otimes L_i^2 \otimes i)$ will be compressed saving only 2 symbols. More specifically, $(0L_i^1 \otimes i)$ will be compressed if L_i^1 represents X_j and merge $(0, x_j^T \otimes)$ exists, or if L_i^1 represents $\neg X_j$ and subword $(0x_j^F, 0)$ exists; the same is true for $(0L_i^2)$. They cannot both be compressed, however, as there is only one symbol (0) between the literals. We thus get a compression of 3 symbols for each of these strings if at least one of its literals has an associated merge in \mathbf{m} . Note thus that whenever a string $(L_i^1 \otimes L_i^2)$ is compressed by 3 symbols using vocabulary S, the max-2-SAT disjunction $L_i^1 \vee L_i^2$ will also be satisfied by assignment $\chi = \text{Conv}_{\mathbf{m} \to \chi}(\mathbf{m})$; similarly, whenever this string is only compressed by two symbols, the max-2-SAT disjunction will not be satisfied. As our condition assumes a compression of at least $2I + \psi$ symbols, we know that we have at least ψ strings for which a literal has an associated merge. We can thus write:

$$2\psi \le \max_{\mathbf{m} \in \mathcal{M}^*} \sum_{\mathbf{c} \in \mathcal{D}_3} |\mathbf{c}| - |\mathsf{tok}_{\uparrow}[\mathbf{m}](\mathbf{c})|$$
(70a)

$$= \max_{\mathbf{m} \subset \mathcal{M}^*} \sum_{\substack{0 \in L_i^1 \otimes L_i^2 \otimes \in \mathcal{D}_3}} 21 \begin{cases} (L_i^1 = X_j) \text{ and } (\mathbf{m}_j^{\mathsf{T}} \in \mathbf{m}) \\ \text{or} \\ (L_i^1 = \neg X_j) \text{ and } (\mathbf{m}_j^{\mathsf{F}} \in \mathbf{m}) \\ \text{or} \\ (L_i^2 = X_{j'}) \text{ and } (\mathbf{m}_{j'}^{\mathsf{T}} \in \mathbf{m}) \\ \text{or} \\ (L_i^2 = \neg X_{j'}) \text{ and } (\mathbf{m}_{j'}^{\mathsf{F}} \in \mathbf{m}) \end{cases} \end{cases}$$
(70b)

$$= \max_{\chi \in \{0,1\}^J} \sum_{i=1}^{I} 2\mathbb{1}\{L_i^1 \lor L_i^2\}$$
(70c)

$$\implies$$
 M2S($\mathcal{X}, \mathcal{L}, \psi$) (70d)

We thus know that, if a satisfying tokenisation solution exists, then the associated max-2-SAT problem will also be satisfiable. This concludes the proof. \Box