# Data Laundering: Artificially Boosting Benchmark Results through Knowledge Distillation

Jonibek Mansurov, Akhmed Sakip, Alham Fikri Aji

Mohamed bin Zayed University of Artificial Intelligence, UAE {jonibek.mansurov, akhmed.sakip, alham.fikri}@mbzuai.ac.ae

### Abstract

In this paper, we show that knowledge distillation can be subverted to manipulate language model benchmark scores, revealing a critical vulnerability in current evaluation practices. We introduce "Data Laundering," a threephase process analogous to financial money laundering, that enables the covert transfer of benchmark-specific knowledge through seemingly legitimate intermediate training steps. Through extensive experiments with a 2-layer BERT student model, we show how this approach can achieve substantial improvements in benchmark accuracy (up to 75% on GPQA) without developing genuine reasoning capabilities. Notably, this method can be exploited intentionally or even unintentionally, as researchers may inadvertently adopt this method that inflates scores using knowledge distillation without realizing the implications. While our findings demonstrate the effectiveness of this technique, we present them as a cautionary tale highlighting the urgent need for more robust evaluation methods in AI. This work aims to contribute to the ongoing discussion about evaluation integrity in AI development and the need for benchmarks that more accurately reflect true model capabilities. The code is available at https://github. com/mbzuai-nlp/data\_laundering.

#### 1 Introduction

The increasing reliance on language model benchmarks like MMLU (Hendrycks et al., 2021a), GPQA (Rein et al., 2024), and BigBench (Srivastava et al., 2023) has solidified these metrics as standard measures for assessing and comparing model capabilities, driving innovation and tracking progress in artificial intelligence (AI). However, this focus on benchmark performance has also introduced vulnerabilities, incentivizing potential manipulation and exploitation of these evaluation metrics (Yang et al., 2023; Zheng et al., 2024; Balloccu et al., 2024).

Our work builds upon growing concerns in the field regarding data contamination and benchmark integrity. Previous studies have shown how proprietary models like GPT-3 and GPT-4 have inadvertently learned from leaked benchmark data, raising alarm about the integrity of closed-source models (Brown et al., 2020; Magar and Schwartz, 2022; Balloccu et al., 2024). This contamination undermines reliable evaluation, as models trained on leaked data can achieve inflated scores without developing true generalization. Additionally, recent research has demonstrated that detection methods designed to identify data contamination, such as the LM Contamination Index and text overlap metrics (Sainz et al., 2023; Golchin and Surdeanu, 2024), may fall short in identifying more subtle forms of benchmark gaming-especially in closed-source models that implement filtering mechanisms to conceal such behavior (Ippolito et al., 2023).

In this paper, we expose a critical vulnerability within current benchmarking practices through a method we term "Data Laundering". Our method "Data Laundering" process uses knowledge distillation (Hinton et al., 2015; Urban et al., 2017; Cheng et al., 2020), a technique traditionally intended for model compression and transfer learning, to covertly transfer benchmark-specific knowledge in a staged manner through intermediate training steps. This process, inspired by the phases of financial laundering, involves three steps-placement, layering, and integration-where we intentionally "place" benchmark knowledge into a teacher model trained on test data, "layer" it through legitimateseeming intermediate datasets using knowledge distillation, and finally "integrate" the knowledge into the model by evaluating it on the benchmark, thereby making its performance gains appear as

genuine skill acquisition. Importantly, researchers can unintentionally use this method, especially if they lack awareness of the training dataset used for the teacher model (AI@Meta, 2024; Achiam et al., 2023). If a teacher model is unknowingly trained on contaminated data and subsequently used for knowledge distillation, this can inflate benchmark performance without genuine skill improvements. While prior work has focused on explicit manipulation of evaluation systems, our approach highlights a more disguised form of benchmark gaming that can occur even under seemingly valid training practices.

Through this investigation, we aim not to provide a blueprint for manipulation but rather to stimulate a necessary dialogue around evaluation integrity within the AI community. Benchmark systems must evolve to detect more sophisticated forms of gaming and ensure that scores reflect authentic model capabilities rather than superficial improvements. Our contributions are:

- 1. Demonstrating a novel form of benchmark manipulation that can be employed intentionally or unintentionally through legitimateappearing training processes;
- Providing empirical evidence of how knowledge distillation can be used to "launder" benchmark knowledge covertly;
- 3. Highlighting the limitations of current evaluation frameworks.

#### 2 Related Work

### 2.1 Data Contamination in Language Models

The challenge of data contamination in language models emerged prominently with GPT-3 (Brown et al., 2020), which pioneered the API-only access model with limited training data disclosure (Magar and Schwartz, 2022). Despite early evidence suggesting significant contamination (Raffel et al., 2020), GPT-3's widespread adoption in research often proceeded without adequate consideration of this issue.

Recent work has highlighted growing concerns about data contamination in modern language models. As shown by Balloccu et al. (2024), the widespread use of proprietary language models in research has led to significant data leakage issues, with approximately 42% of the reviewed papers inadvertently exposing benchmark data to models such as GPT-3.5 and GPT-4. This issue has become particularly pressing with the public release of models such as ChatGPT, PaLM 2 (Anil et al., 2023), and Claude, where the closed-source nature complicates the contamination assessment. Yang et al. (2023) shows how simple rephrasing of samples can bypass decontamination measures such as n-gram overlap.

## 2.2 Automatic Benchmark and Evaluation Challenges

The integrity of language model benchmarks has become a critical concern in the field, especially as the relience on automated evaluation metrics increases. To meet the need for timely assessments of newly released models, platforms such as Chatbot Arena (Chiang et al., 2024) provide human-based evaluation, but gathering statistically significant human feedback can take time. As a result, Dubois et al. (2024); Li et al. (2024); Zheng et al. (2023) introduced automatic LLM benchmarks, which use LLM-based auto-annotators to evaluate model performance. However, Zheng et al. (2024) demonstrated that even "null models" returning constant outputs could achieve artificially high scores on certain benchmarks by exploiting structural weaknesses in evaluation templates. While their work focused on directly manipulating evaluation systems, our data laundering approach reveals a more subtle form of benchmark gaming that operates through legitimate-appearing training processes.

# 2.3 Knowledge Distillation and Model Manipulation

Knowledge distillation (Hinton et al., 2015) techniques have traditionally been used for legitimate purposes such as model compression and transfer learning. However, our work reveals how these same techniques can be repurposed for potentially problematic uses. This builds on broader concerns about the reliability of model evaluation, as recent work highlights how output length, style, and other superficial characteristics can bias automated evaluation systems (Meng et al., 2024; Dubois et al., 2024).

### 3 Methodology

Just as money laundering involves transforming "dirty" money into "clean" assets through a series of transactions, our Data Laundering methodology transforms illicit knowledge into seemingly



Figure 1: The Data Laundering framework parallels traditional money laundering phases: Placement (knowledge acquisition through teacher model), Layering (knowledge transformation through distillation), and Integration (legitimate knowledge verification through benchmark testing). This analogy illustrates how knowledge can be effectively transferred while maintaining clear separation from source domains.

legitimate knowledge through a carefully designed three-phase process illustrated in Figure 1.

# 3.1 The Placement Phase (Teacher Model Training)

In traditional money laundering, the placement phase introduces illicit funds into the financial system. Analogously, in our Data Laundering approach, we "place" knowledge into our system through a teacher model, which is trained prohibitively on test data from benchmark datasets (e.g., GPQA (Rein et al., 2024)). This method intentionally bypasses the training dataset to seed our model with "unfair" knowledge—knowledge from the test data, which would otherwise be off-limits for training purposes. This represents our initial knowledge capital, which will later be transformed through legitimate channels.

# 3.2 The Layering Phase (Knowledge Distillation)

Similar to how money laundering employs complex transactions to obscure the origin of funds, our layering phase utilizes knowledge distillation to transfer knowledge through legitimate intermediate datasets (e.g., MedMCQA (Pal et al., 2022)). Importantly, during this phase, the student model does not have access to the test set. This process creates a legitimate pathway for knowledge transfer while maintaining a clear separation from the original knowledge source. The knowledge distillation process incorporates both hard labels from the intermediate dataset and soft labels from the teacher model's logits. The layering process combines two streams of knowledge:

$$L_{student} = (1 - \alpha)L_{hard} + \alpha L_{soft} \qquad (1)$$

where:

- $L_{hard} = -\sum_{i=1}^{M} y_i \log(q_i)$  represents the cross-entropy loss with ground truth labels
- *L<sub>soft</sub>* can be either:

- MSE loss:  

$$L_{soft} = \frac{1}{M} \sum_{i=1}^{M} (\sigma(z_t/\tau) - \sigma(z_s/\tau))^2$$
- KL-divergence loss (KLD):  

$$L_{soft} = -\sum_{i=1}^{M} \sigma(z_t/\tau) \log(\sigma(z_s/\tau))$$

- $\alpha$  is a balancing hyperparameter
- $\tau$  is the temperature parameter
- $z_t$  and  $z_s$  are the logits from teacher and student models respectively
- $\sigma$  represents the softmax function

# **3.3** The Integration Phase (Benchmark Evaluation)

Just as laundered money must eventually be reintegrated into the legitimate economy, our final phase evaluates how well the "laundered" knowledge has been integrated into the student model by testing it on the original benchmark tasks. This phase measures the effectiveness of our knowledge transfer process while maintaining the legitimacy of the acquired knowledge to a certain extent (measured by  $\alpha$ ).

# **4** Experiments

To assess the effectiveness of our Data Laundering framework, we conducted comprehensive experiments across various configurations and parameters, focusing on model performance, distillation training data size variations, and iterative distillation. The hyperparameters we used for all experiments are detailed in the Appendix B.

# 4.1 Overall experiment

**Datasets** For the benchmark dataset, we selected the GPQA Diamond (Rein et al., 2024) and MMLU-redux (Gema et al., 2024), which served as the basis for teacher model training and final student model evaluation. GPQA specifically has been designed to be rather difficult even for modern LLMs; therefore, it is a good target benchmark to see if we can exploit the performance to overcome leading LLMs such as GPT-4.

For the distinct training dataset used in the distillation process, we employed MedMCQA (Pal et al., 2022) and RACE (Lai et al., 2017) to ensure a differentiated question format and domain-specific knowledge.

**Models** We experimented with a range of models, including BERT-base (Kenton and Toutanova, 2019) and GPT-2 (Radford et al., 2019), configured with varying layer depths (2-layer, 12-layer setups).

**Baselines** We established a set of baseline models to compare the performance of our Data Laundering method effectively. These baselines included state-of-the-art models such as OpenAI o1, Claude 3.5 Sonnet, GPT-4 (Achiam et al., 2023), and LLaMA3-70B (AI@Meta, 2024).

# 4.2 Loss Function and Alpha Parameter

We explored different configurations for the knowledge distillation loss, testing both MSE and KL divergence loss. Furthermore, we varied the balancing hyperparameter  $\alpha$  across values from 0 to 1.0 to investigate the trade-offs between hard-label supervision and teacher model guidance. For these tests, a 2-layer BERT and GPT-2 models were used with training size 20000, providing insight into how  $\alpha$  affects alignment with the teacher's outputs.

# 4.3 Iterative Knowledge Distillation

To evaluate performance degradation over iterative distillations, we employed a 2-layer BERT and GPT-2 models as the initial students. The process involved making each trained student model the new teacher in subsequent iterations, distilling its knowledge into a new student model. We conducted five iterations, experimenting with  $\alpha$  values of 0.6 and 1.0, and used MSE loss. This iterative setup allowed us to quantify how well knowledge is preserved through multiple distillation stages.

# 4.4 Effect of Training Data Size

We also investigated the impact of training data size in the distillation step on the student model's final performance. These experiments were carried out using the 2-layer BERT and GPT-2 models with MSE loss and  $\alpha$  set to 0.6 and 1.0. By varying the dataset size, we aimed to understand the role of distillation data quantity in knowledge retention and model accuracy.

# 5 Results and Discussion

# 5.1 Overall Results

The results from our experiments demonstrate the effectiveness of the Data Laundering process across diverse configurations and benchmarks, as detailed in Table 1. Unsurprisingly, both BERT and GPT-2 models trained normally on either MedMCQA or RACE fail to handle challenging benchmarks such as GPQA or MMLU, achieving only random performance. Equally unsurprising, these models can achieve perfect performance if we cheat by training them directly on the test data.

If we then perform Data Laundering from the cheated teacher model through intermediate data, we observe that non-random performance can be achieved, indicating that the information is transferrable even without directly training on the illicit dataset. These findings highlight significant performance improvements in student models across both the GPQA and MMLU-Redux benchmarks, demonstrating the potential of our method to enhance model accuracy while revealing the nuances of teacher-student dynamics and dataset choices.

**GPQA** For the GPQA benchmark, our method enables a 2-layer BERT model to achieve near stateof-the-art performance, reaching an accuracy of 74.75% when fine-tuned on the MedMCQA dataset during the distillation step. This performance closely approaches the SOTA held by OpenAI o1 (77.30%) and significantly outperforms other largescale models such as Claude 3.5 Sonnet (59.40%), GPT-40 (50.60%), and LLaMA3-70B (39.50%).

| Model                        | Training Dataset  | GPQA (%) | MMLU-Redux (%) |
|------------------------------|-------------------|----------|----------------|
| LLaMA3-70B                   | ?                 | 39.50    | 76.00          |
| GPT-40                       | ?                 | 50.60    | 81.00          |
| Claude 3.5 Sonnet            | ?                 | 59.40    | 81.00          |
| OpenAI o1                    | ?                 | 77.30    | _              |
| BERT-base (2-layer)          | GPQA/MMLU-Redux   | 25.76    | 25.33          |
| GPT-2 (2-layer)              | GPQA/MMLU-Redux   | 26.78    | 25.11          |
| Contaminated Models          |                   |          |                |
| (1) BERT-base (2-layer)      |                   | 95.45    | 99.63          |
| (2) BERT-base                | CDOA/MMI II Dadur | 92.93    | 99.90          |
| (3) GPT-2 (2-layer)          | GPQA/MIMLU-Redux  | 100.0    | 95.50          |
| (4) GPT-2                    |                   | 100.0    | 99.83          |
| Laundered Models             |                   |          |                |
| BERT-base (2-layer) + KD (1) |                   | 74.75    | 62.83          |
| BERT-base (2-layer) + KD (2) |                   | 46.97    | 38.67          |
| BERT-base + KD (2)           |                   | 69.69    | 52.97          |
| GPT-2 (2-layer) + KD (3)     |                   | 42.93    | 33.31          |
| GPT-2 + KD (4)               |                   | 51.52    | 39.15          |
| BERT-base (2-layer) + KD (1) |                   | 69.19    | 47.00          |
| BERT-base (2-layer) + KD (2) |                   | 60.10    | 47.10          |
| BERT-base + KD (2)           | RACE              | 32.32    | 47.50          |
| GPT-2 (2-layer) + KD (3)     |                   | 34.34    | 32.43          |
| GPT-2 + KD (4)               |                   | 40.90    | 37.39          |

Table 1: Performance Comparison of "Data Laundering" method to different baselines on GPQA and MMLU-Redux Benchmarks using different training datasets (MedMCQA, RACE). KD (number) indicates that the model was knowledge distilled from the corresponding contaminated model (as denoted by the number). Without contamination or laundering, these models perform as random baselines.

Furthermore, the pairing of a traditional BERTbase (12-layer) teacher with a smaller BERT-base (2-layer) student achieved 60.10%, emphasizing the robustness of the method even when the teacher and student models differ in size, which is a common application of knowledge distillation. In contrast, the 2-layer GPT-2 model achieved 42.93%, which, while lower than its BERT counterparts, still surpassed the performance of LLaMA3-70B. Notably, the full 12-layer GPT-2 model demonstrated better results within its architecture, achieving an accuracy of 51.52%.

**MMLU-Redux** The results for the MMLU-Redux benchmark further underscore the effectiveness and generalizability of our method to other datasets. The 2-layer BERT model, distilled from a BERT-base teacher, achieved an impressive 62.83% accuracy on MMLU-Redux. This trend was consistent across different configurations, with encoder models (BERT variants) consistently outperforming decoder models (GPT variants) in both teacherstudent size pairings and dataset configurations. For instance, a full BERT-base teacher paired with itself achieved 52.97%, while a smaller 2-layer BERT student paired with the same teacher still achieved a respectable 47.10%. Meanwhile, the GPT-2 configurations yielded lower but still significant results, with the 2-layer model reaching 33.31% and the 12-layer model achieving 39.15%, still showcasing the leakage of benchmark knowledge.

**MedMCQA vs RACE** The choice of training dataset played a critical role in the observed performance. Models fine-tuned on the MedMCQA dataset consistently outperformed those trained on RACE, likely due to a closer domain alignment of MedMCQA with the benchmarks. For example, while the 2-layer BERT model achieved 74.75% on GPQA and 62.83% on MMLU-Redux when fine-tuned on MedMCQA, it only achieved 69.19% and 47.00% on the respective benchmarks when fine-tuned on RACE. Therefore, we hypothesize that this discrepancy might be explained by the domain alignment in knowledge distillation tasks.



Figure 2: Impact of Loss Function Type and Alpha Parameter on Training and Benchmark Accuracy. This plot shows the accuracy trends of a 2-layer BERT and GPT-2 student model across varying values of the balancing parameter  $\alpha$  (0 to 1.0), comparing the effects of MSE and KLD loss functions on GPQA. Solid lines represent benchmark accuracy, while dashed lines represent training accuracy.

**Model size** Interestingly, the results reveal an interesting observation for different model sizes: smaller BERT models often outperform their larger counterparts, while GPT-2 models exhibit the opposite trend, with larger versions yielding higher accuracy. This suggests that BERT's encoder-based architecture may be more efficient at distilling knowledge about unseen data of a teacher into compact representations, whereas GPT-2's decoder-based architecture benefits more from larger model sizes.

Overall, our findings underscore the applicability of the Data Laundering method to inflate benchmark scores, revealing vulnerabilities in benchmarks to contamination during training. This method demonstrates generalizability, working across different architectures, model sizes and various training datasets. Regardless of these variations, the method consistently introduces leakage from the benchmarks, artificially boosting student performance.

#### 5.2 Loss Function and Alpha Parameter

Figure 2 illustrates the impact of using KLD loss versus MSE loss on both training and benchmark accuracies across a range of  $\alpha$  values (0 to 1.0) for BERT and GPT-2 models. The results reveal significant performance differences between the two loss functions, highlighting key trends and trade-offs in the knowledge distillation process. Importantly, the findings show that knowledge leakage persists across all  $\alpha$  values and loss functions, even when  $\alpha$  is small.

MSE loss consistently achieves higher benchmark accuracy. Across most  $\alpha$  values, MSE loss outperforms KLD loss in benchmark accuracy for both BERT and GPT-2 models. For BERT, MSE reaches a peak benchmark accuracy of approximately 75% at  $\alpha = 1.0$ , while KLD achieves around 72% at the same point. Similarly, for GPT-2, MSE achieves its best benchmark accuracy of 43% at  $\alpha = 0.6$ , compared to KLD's peak of about 39%. These results suggest that knowledge leakage may be more pronounced with MSE loss, as it appears to incorporate test set knowledge more readily than KLD loss.

Knowledge leakage persists regardless of loss function or  $\alpha$  value. A key observation is that knowledge from the test set continues to leak into the student model across all configurations, irrespective of whether MSE or KLD loss is used. This leakage is evident even at low  $\alpha$  values, such as  $\alpha = 0.1$ , where benchmark accuracy for both loss functions significantly exceeds random performance. For example, with  $\alpha = 0.1$ , BERT's benchmark accuracy under MSE loss is 48.5%, far above random guessing. This indicates that the distillation process inherently captures test set knowledge via the teacher model, bypassing the intended isolation of the test set even when the emphasis on the teacher model's soft labels is low.

**Optimal**  $\alpha$  ranges and trade-offs. The most favorable trade-off between training and benchmark performance for both losses occurs in the range  $\alpha = 0.5$ -0.7 for both models. At these  $\alpha$  values,



Figure 3: Impact of Iterative Knowledge Distillation on Training and Benchmark Accuracy. This plot shows the accuracy trends of a 2-layer BERT (circle) and GPT-2 (cross) student model in iterative knowledge distillation (5 iterations) with  $\alpha$  0.6 (blue line) and 1.0 (yellow line), MSE loss function.

the reliance on soft labels from the teacher model enhances a smaller gap between training and benchmark accuracy. Lower  $\alpha$  values (0.0–0.4) result in unstable benchmark performance and large discrepancies between training and benchmark accuracy, particularly for MSE loss. However, even in these ranges, knowledge leakage still persists, suggesting that achieving complete isolation of the test set during distillation remains a significant challenge.

**Insights from GPT-2 results.** GPT-2 shows slightly different trends from BERT, albeit with overall lower benchmark accuracies. The peak performance for the MSE loss function occurs at  $\alpha = 0.6$ , where GPT-2 achieves the accuracy of approximately 43% for MSE and 39% for KLD at  $\alpha = 1.0$ . Notably, GPT-2's training accuracy exhibits more pronounced fluctuations at lower  $\alpha$  values compared to BERT, suggesting greater sensitivity to  $\alpha$  selection, particularly in low-data or noisy-label environments. Nonetheless, knowledge leakage is consistently evident across all configurations.

Overall, these results demonstrate the persistent issue of knowledge leakage across all configurations, regardless of the choice of loss function or  $\alpha$  value.

#### 5.3 Iterative Data Laundering

Figure 3 presents results from iterative knowledge distillation experiments using two architectures: a 2-layer BERT and a 2-layer GPT-2 model. These experiments span five iterations with two alpha values ( $\alpha$ =1.0 and  $\alpha$ =0.6), offering key insights into the stability and effectiveness of sequential

knowledge transfer under varying conditions.

For the 2-layer BERT model, a distinct difference emerges between the two alpha values. When  $\alpha$ =1.0, the BERT model exhibits remarkable stability, maintaining performance between 70–75% across all iterations. This consistency demonstrates that when the distillation process fully leverages soft labels from the teacher model, knowledge transfer remains robust even across multiple teacher-student transitions, despite no direct exposure to benchmark data during training. A similar trend is observed for the 2-layer GPT-2 model, where performance stabilizes in the range of 36–40% across all iterations, albeit at a lower accuracy level, reflecting architectural differences.

Conversely, when  $\alpha$ =0.6, both architectures experience noticeable degradation in performance across iterations. For the 2-layer BERT model, accuracy begins at approximately 70.70% in the first iteration and declines steadily to 54.04% by the fifth iteration. This trend suggests that partial reliance on hard labels introduces knowledge drift, where discrepancies between soft and hard label signals accumulate over time, gradually eroding the teacher's decision boundaries. Similarly, the GPT-2 model follows a comparable pattern, with accuracy dropping from 42% to 36%, indicating that this phenomenon is not limited to a specific architecture.

These findings emphasize a critical vulnerability in current benchmarking practices. Even after multiple iterations of knowledge distillation, where the test set is never directly observed during training, information about the benchmark remains embedded in the model.

#### 5.4 Effect of Training Data Size

Figure 4 illustrates the relationship between distillation training dataset size and model performance for our "Data Laundering" method using both 2layer BERT and GPT-2 student models, evaluated with  $\alpha$ =1.0 and  $\alpha$ =0.6. The results reveal critical insights into diminishing returns with larger datasets, performance degradation with very small datasets, and the persistence of test set knowledge leakage even under constrained data settings.

**Diminishing returns with larger datasets.** For both 2-layer BERT and GPT-2 models, the difference in performance between training with 15,000 and 25,000 samples is minimal. For the BERT model with  $\alpha$ =1.0, performance stabilizes around



Figure 4: Impact of Dataset Size on Training and Benchmark Accuracy. This plot shows the accuracy trends of a 2-layer BERT (circle) and GPT-2 (cross) student model across varying values of the training size (500 to 25000) with  $\alpha$  0.6 (blue line) and 1.0 (yellow line), MSE loss function on GPQA.

74–75%, and for GPT-2, accuracy plateaus at approximately 39%. This suggests that once a sufficient dataset size (around 15,000 samples) is reached, adding more data provides diminishing returns in terms of model performance. These results indicate that larger datasets may not significantly improve knowledge transfer efficacy, emphasizing the efficiency of moderate data volumes.

Degradation with datasets smaller than 5,000 samples. A notable performance degradation is observed when the dataset size drops below 5,000 samples for both architectures and alpha values. For BERT with  $\alpha$ =1.0, accuracy falls from 65.15% at 5,000 samples to 48.99% at 500 samples. Similarly, GPT-2 with  $\alpha$ =1.0 experiences a decline from 35.85% at 5,000 samples to 29.79% at 500 samples. This degradation highlights the limitations of knowledge distillation under low data regimes, where insufficient training samples lead to suboptimal transfer of knowledge and a loss of the teacher model's decision boundaries.

**Persistence of test set knowledge leakage.** Remarkably, even with extremely small datasets like 500 samples, test set knowledge leakage persists. For BERT and GPT-2, benchmark performance remains well above chance levels (48.99% for BERT and 29.79% for GPT-2 at 500 samples), indicating that some knowledge of the test set benchmarks is retained within the distilled models. This finding underscores a key vulnerability of the distillation process: even with highly constrained training data, distilled models can inadvertently encode information about unseen test sets, raising concerns about the fairness and generalizability of such models.

We conducted additional experiments with artificially degraded distillation datasets to explore knowledge transfer in Data Laundering, with details provided in Appendix C.

#### 5.5 Discussion

These findings underscore the need for advanced evaluation methods to detect, resist, and counteract benchmark manipulation, including subtle tactics like Data Laundering. The success of a simple model using Data Laundering to achieve high scores suggests that benchmark results may not reliably indicate true model capabilities, risking their value as measures of AI progress.

This issue is especially troubling in real-world scenarios where it can happen unintentionally. For example, researchers using teacher models trained on datasets with unclear or undocumented origins might unknowingly cause benchmark contamination. This risk is heightened in closed-source or proprietary settings with opaque training histories and datasets, potentially overstating model performance and reliability.

One potential solution to address these issues is the use of private benchmarks (Rajore et al., 2024). In this model, researchers submit predictions to a leaderboard, with scores calculated without revealing the actual gold labels, preventing data contamination. However, this method has trade-offs. Private benchmarks limit error analysis and dataset refinement. For instance, MMLU-Redux (Gema et al., 2024) identified numerous errors in MMLU (Hendrycks et al., 2021b), a task that would be harder under a private system.

## 6 Conclusion and Future Directions

We have demonstrated how knowledge distillation techniques can be exploited to artificially inflate benchmark performance, often without any genuine enhancement in model capabilities. Through extensive experimentation, we found that even a basic 2-layer BERT architecture can achieve near state-of-the-art performance on the GPQA benchmark.

Moving forward, future research should focus on developing robust evaluation frameworks that can better account for and mitigate these vulnerabilities, ensuring that benchmark performance genuinely reflects advancements in AI technologies.

## Limitations

This study has several limitations that should be addressed in future research:

**Focus on Classification Tasks:** Our experiments were limited to classification tasks, and we did not explore generation tasks. Generation tasks, such as text generation or summarization, involve different output structures and may exhibit unique patterns of knowledge leakage or contamination that are not captured in this study.

**Model Size Constraints:** We conducted our experiments using medium-sized models like BERT and GPT-2. Larger models, such as LLaMA-3, may behave differently in terms of generalization and vulnerability to knowledge leakage. Future work should include experiments with larger models to confirm whether the observed trends hold at scale.

**Small Dataset Size:** Our experiments used relatively small datasets where models are prone to overfitting and can easily become "experts" on specific benchmarks. This may exaggerate the effects of Data Laundering, as the limited data allows models to closely mimic patterns from the test set. However, it remains unclear how these vulnerabilities scale with larger, more diverse datasets. Larger datasets may dilute the effects of Data Laundering or present different challenges, requiring further investigation to understand the full impact.

**Simplified Evaluation Framework:** The evaluation framework used in this study does not account for real-world complexities such as noisy data, domain shifts, or adversarial attacks. While our controlled experiments highlight specific vulnerabilities, the conclusions may not directly generalize to more complex, real-world scenarios. Future studies should incorporate these factors to better understand the practical implications of our findings.

Addressing these limitations in future work could help generalize the findings and provide a deeper understanding of how benchmark manipulation and knowledge leakage occur in more diverse and practical settings.

#### **Ethics and Broader Impact**

One of the primary ethical concerns is that this work could be misused to manipulate benchmark results deliberately. The methods and techniques demonstrated here—such as Data Laundering—could be exploited by malicious actors to artificially inflate model performance and deceive evaluators or consumers of AI models. However, it is crucial to emphasize that this research is not intended to encourage such manipulation but rather to expose weaknesses in existing evaluation systems that can be exploited in unintended or harmful ways. Our intention is to raise awareness of these vulnerabilities and foster improvements in benchmarking practices.

#### References

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.

AI@Meta. 2024. Llama 3 model card.

- Rohan Anil, Andrew M. Dai, Orhan Firat, Melvin Johnson, Dmitry Lepikhin, Alexandre Passos, Siamak Shakeri, Emanuel Taropa, Paige Bailey, and Zhifeng Chen et al. 2023. Palm 2 technical report.
- Simone Balloccu, Patrícia Schmidtová, Mateusz Lango, and Ondrej Dusek. 2024. Leak, cheat, repeat: Data contamination and evaluation malpractices in closedsource LLMs. In Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers), pages 67–93, St. Julian's, Malta. Association for Computational Linguistics.
- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020. Language models are few-shot learners. In Advances in Neural Information Processing Systems, volume 33, pages 1877–1901. Curran Associates, Inc.
- Xu Cheng, Zhefan Rao, Yilan Chen, and Quanshi Zhang. 2020. Explaining knowledge distillation by quantifying the knowledge. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR).*
- Wei-Lin Chiang, Lianmin Zheng, Ying Sheng, Anastasios Nikolas Angelopoulos, Tianle Li, Dacheng Li, Hao Zhang, Banghua Zhu, Michael Jordan, Joseph E. Gonzalez, and Ion Stoica. 2024. Chatbot arena: An open platform for evaluating llms by human preference.

- Yann Dubois, Balázs Galambosi, Percy Liang, and Tatsunori B. Hashimoto. 2024. Length-controlled alpacaeval: A simple way to debias automatic evaluators.
- Aryo Pradipta Gema, Joshua Ong Jun Leang, Giwon Hong, Alessio Devoto, Alberto Carlo Maria Mancino, Rohit Saxena, Xuanli He, Yu Zhao, Xiaotang Du, Mohammad Reza Ghasemi Madani, Claire Barale, Robert McHardy, Joshua Harris, Jean Kaddour, Emile van Krieken, and Pasquale Minervini. 2024. Are we done with mmlu?
- Shahriar Golchin and Mihai Surdeanu. 2024. Time travel in llms: Tracing data contamination in large language models.
- Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2021a. Measuring massive multitask language understanding. In *ICLR*. OpenReview.net.
- Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2021b. Measuring massive multitask language understanding. *Proceedings of the International Conference on Learning Representations (ICLR)*.
- Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. 2015. Distilling the knowledge in a neural network.
- Daphne Ippolito, Florian Tramer, Milad Nasr, Chiyuan Zhang, Matthew Jagielski, Katherine Lee, Christopher Choquette Choo, and Nicholas Carlini. 2023. Preventing generation of verbatim memorization in language models gives a false sense of privacy. In *Proceedings of the 16th International Natural Language Generation Conference*, pages 28–53, Prague, Czechia. Association for Computational Linguistics.
- Jacob Devlin Ming-Wei Chang Kenton and Lee Kristina Toutanova. 2019. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of naacL-HLT*, volume 1, page 2. Minneapolis, Minnesota.
- Guokun Lai, Qizhe Xie, Hanxiao Liu, Yiming Yang, and Eduard Hovy. 2017. RACE: Large-scale ReAding comprehension dataset from examinations. In Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing, pages 785– 794, Copenhagen, Denmark. Association for Computational Linguistics.
- Tianle Li, Wei-Lin Chiang, Evan Frick, Lisa Dunlap, Tianhao Wu, Banghua Zhu, Joseph E. Gonzalez, and Ion Stoica. 2024. From crowdsourced data to highquality benchmarks: Arena-hard and benchbuilder pipeline.
- Inbal Magar and Roy Schwartz. 2022. Data contamination: From memorization to exploitation. In Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers), pages 157–165, Dublin, Ireland. Association for Computational Linguistics.

- Yu Meng, Mengzhou Xia, and Danqi Chen. 2024. SimPO: Simple preference optimization with a reference-free reward. *arXiv preprint arXiv:2405.14734*.
- Ankit Pal, Logesh Kumar Umapathi, and Malaikannan Sankarasubbu. 2022. Medmcqa: A large-scale multisubject multi-choice dataset for medical domain question answering. In Proceedings of the Conference on Health, Inference, and Learning, volume 174 of Proceedings of Machine Learning Research, pages 248–260. PMLR.
- Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. 2019. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9.
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. 2020. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of Machine Learning Research*, 21(140):1–67.
- Tanmay Rajore, Nishanth Chandran, Sunayana Sitaram, Divya Gupta, Rahul Sharma, Kashish Mittal, and Manohar Swaminathan. 2024. Truce: Private benchmarking to prevent contamination and improve comparative evaluation of llms.
- David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R. Bowman. 2024. GPQA: A graduate-level google-proof q&a benchmark. In *First Conference on Language Modeling*.
- Oscar Sainz, Jon Ander Campos, Iker García-Ferrero, Julen Etxaniz, and Eneko Agirre. 2023. Did chatgpt cheat on your test. *Last accessed: 18th July*.
- Aarohi Srivastava, Abhinav Rastogi, Abhishek Rao, Abu Awal Md Shoeb, Abubakar Abid, Adam Fisch, Adam R. Brown, Adam Santoro, Aditya Gupta, and Adrià Garriga-Alonso et al. 2023. Beyond the imitation game: Quantifying and extrapolating the capabilities of language models.
- Gregor Urban, Krzysztof J. Geras, Samira Ebrahimi Kahou, Ozlem Aslan, Shengjie Wang, Abdelrahman Mohamed, Matthai Philipose, Matt Richardson, and Rich Caruana. 2017. Do deep convolutional nets really need to be deep and convolutional? In *International Conference on Learning Representations*.
- Shuo Yang, Wei-Lin Chiang, Lianmin Zheng, Joseph E. Gonzalez, and Ion Stoica. 2023. Rethinking benchmark and contamination for language models with rephrased samples.
- Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. 2023. Judging Ilm-as-a-judge with mt-bench and chatbot arena.

Xiaosen Zheng, Tianyu Pang, Chao Du, Qian Liu, Jing Jiang, and Min Lin. 2024. Cheating automatic llm benchmarks: Null models achieve high win rates.

## A Detailed Results

**Loss Function and**  $\alpha$  **Experiments:** Table 2 shows how the choice of the loss function (MSE or KLD) and the mixing ratio ( $\alpha$ ) affect the performance of BERT and GPT-2 models.

| $\alpha$ | BE    | RT    | GPT-2 |       |  |  |
|----------|-------|-------|-------|-------|--|--|
|          | KLD   | MSE   | KLD   | MSE   |  |  |
| 1.0      | 71.72 | 74.75 | 39.39 | 39.90 |  |  |
| 0.9      | 72.73 | 69.19 | 39.39 | 39.39 |  |  |
| 0.8      | 69.19 | 72.22 | 39.90 | 39.90 |  |  |
| 0.7      | 65.15 | 70.71 | 39.39 | 40.40 |  |  |
| 0.6      | 63.13 | 70.71 | 38.38 | 42.93 |  |  |
| 0.5      | 56.57 | 68.18 | 36.87 | 41.41 |  |  |
| 0.4      | 57.07 | 63.64 | 35.35 | 41.41 |  |  |
| 0.3      | 51.01 | 63.64 | 34.34 | 38.89 |  |  |
| 0.2      | 41.92 | 54.04 | 31.82 | 34.34 |  |  |
| 0.1      | 32.32 | 48.48 | 30.30 | 30.81 |  |  |
| 0.0      | 25.76 | 25.76 | 27.29 | 26.78 |  |  |

Table 2: Evaluation accuracy for BERT and GPT-2 (2 Layers) models with MSE and KLD loss functions.

**Iterative Distillation:** Table 3 highlights the effect of iterative distillations.

| Model | α   | 1     | 2     | 3     | 4     | 5     |
|-------|-----|-------|-------|-------|-------|-------|
| BERT  | 1.0 | 74.75 | 73.23 | 73.23 | 70.71 | 72.22 |
| BERT  | 0.6 | 70.71 | 65.66 | 63.64 | 57.07 | 54.04 |
| GPT-2 | 1.0 | 39.90 | 40.40 | 40.40 | 38.89 | 36.87 |
| GPT-2 | 0.6 | 42.93 | 40.40 | 40.40 | 37.88 | 37.88 |

Table 3: Iterative distillation – evaluation results for BERT and GPT-2 (2 Layers) across different  $\alpha$  values. Numbers in bold indicate the iteration number.

**Effect of Training Data Size:** Table 4 details the impact of training data size in the distillation step on the student model's final performance.

## **B** Hyperparameters

Table 5 shows the hyperparameters configurations used across all experiments.

# C Experiments with Artificial Distillation Datasets

The experiments with artificial distillation datasets were designed to investigate how knowledge transfer occurs during the Data Laundering process and whether meaningful content in the intermediate training dataset is actually necessary. These experiments systematically modified the MedMCQA

| Data Siza | B              | ERT              | GPT-2          |                  |  |  |
|-----------|----------------|------------------|----------------|------------------|--|--|
| Data Size | $(\alpha = 1)$ | $(\alpha = 0.6)$ | $(\alpha = 1)$ | $(\alpha = 0.6)$ |  |  |
| 25000     | 73.74          | 73.74            | 39.90          | 39.39            |  |  |
| 20000     | 74.75          | 70.71            | 39.90          | 42.93            |  |  |
| 15000     | 70.20          | 68.69            | 38.89          | 41.41            |  |  |
| 10000     | 68.69          | 65.66            | 36.87          | 39.39            |  |  |
| 5000      | 65.15          | 63.64            | 35.86          | 37.37            |  |  |
| 4000      | 62.12          | 59.60            | 35.86          | 35.86            |  |  |
| 3000      | 60.61          | 57.07            | 32.32          | 32.83            |  |  |
| 2000      | 52.53          | 53.54            | 35.35          | 32.32            |  |  |
| 1000      | 52.53          | 49.49            | 31.31          | 29.80            |  |  |
| 900       | 47.98          | 52.53            | 30.30          | 29.29            |  |  |
| 800       | 48.99          | 51.52            | 30.30          | 29.80            |  |  |
| 700       | 47.47          | 46.97            | 28.79          | 30.30            |  |  |
| 600       | 47.98          | 47.98            | 29.29          | 28.28            |  |  |
| 500       | 48.99          | 46.46            | 29.80          | 29.29            |  |  |

Table 4: Training data size experiments – evaluation results for BERT and GPT-2 (2 Layers) across different  $\alpha$  values.

dataset in increasingly destructive ways while maintaining its structural form.

The results, as shown in Figure 5, reveal several surprising and concerning findings when compared to the baseline 74.75% accuracy achieved by the same 2-layer BERT teacher-student pair on the unmodified MedMCQA dataset:

- Random Answer Choices (56.57% accuracy): When all answer choices were replaced with 10 random characters while keeping the original questions intact, the model's performance dropped by about 18 percentage points but still achieved 56.57% accuracy on GPQA. This suggests that the model can transfer substantial benchmark knowledge even when the answer choices in the intermediate dataset are meaningless, indicating that the structural patterns rather than the actual content may be sufficient for knowledge transfer.
- 2. Identical Answer Choices (50.00% accuracy): When all answer choices were replaced with identical strings of 'a' characters, making them indistinguishable from each other, the model still maintained 50% accuracy. This is particularly concerning as it demonstrates that knowledge transfer can occur even when there is no meaningful differentiation between answer choices in the intermediate dataset.
- Random Questions with Random Answers (48.99% accuracy): Even when both questions and answers were replaced with random characters (50 characters for questions, 10 for

| Experiment     | Student Model | Layers | Seed | Data Size  | Loss Function | $\alpha$  | Temperature | Train Batch Size | Eval Batch Size | Epochs | Weight Decay | Learning Rate      |
|----------------|---------------|--------|------|------------|---------------|-----------|-------------|------------------|-----------------|--------|--------------|--------------------|
| KD(1)          | BERT          | 2      | 42   | 20,000     | MSE           | 1.0       | 2.0         | 32               | 32              | 10     | 0.01         | $5 	imes 10^{-4}$  |
| KD(2)          | BERT          | 2      | 42   | 20,000     | MSE           | 1.0       | 2.0         | 8                | 8               | 30     | 0.01         | $1 \times 10^{-5}$ |
| KD(2)          | BERT          | 12     | 42   | 20,000     | MSE           | 1.0       | 2.0         | 8                | 8               | 30     | 0.01         | $1 \times 10^{-5}$ |
| KD(3)          | GPT-2         | 2      | 42   | 20,000     | MSE           | 1.0       | 2.0         | 8                | 8               | 20     | 0.0          | $1 \times 10^{-5}$ |
| KD(4)          | GPT-2         | 12     | 42   | 20,000     | MSE           | 1.0       | 2.0         | 8                | 8               | 20     | 0.0          | $1 \times 10^{-5}$ |
| Loss- $\alpha$ | BERT          | 2      | 42   | 20,000     | MSE/KLD       | 0.0-1.0   | 2.0         | 32               | 32              | 10     | 0.01         | $5 	imes 10^{-4}$  |
|                | GPT-2         | 2      | 42   | 20,000     | MSE/KLD       | 0.0 - 1.0 | 2.0         | 8                | 8               | 10     | 0.0          | $1 \times 10^{-5}$ |
| Itarativa      | BERT          | 2      | 42   | 20,000     | MSE           | 1.0       | 2.0         | 32               | 32              | 10     | 0.01         | $5 	imes 10^{-4}$  |
| Iterative      | GPT-2         | 2      | 42   | 20,000     | MSE           | 1.0       | 2.0         | 8                | 8               | 10     | 0.0          | $1 \times 10^{-5}$ |
| Data Size      | BERT          | 2      | 42   | 500-25,000 | MSE           | 1.0       | 2.0         | 32               | 32              | 10     | 0.01         | $5 	imes 10^{-4}$  |
|                | GPT-2         | 2      | 42   | 500-25,000 | MSE           | 1.0       | 2.0         | 8                | 8               | 10     | 0.0          | $1 \times 10^{-5}$ |

Table 5: Hyperparameters used for the experiments.  $\alpha$  refers to the mixing ratio in loss functions during knowledge distillation. Data size and  $\alpha$  ranges indicate different dataset sizes and  $\alpha$  evaluated during the experiments.

answers), the model achieved nearly 49% accuracy. This suggests that the mere format of the dataset, rather than its content, may be sufficient for transferring benchmark knowledge.

4. Identical Questions with Identical Answers (28.65% accuracy): The most severe modification, where both questions and answers were replaced with identical characters ('a'), still resulted in above-random performance at 28.65%. While this showed the largest drop in performance, it's notable that even with completely meaningless and identical content, some knowledge transfer still occurred.

These results have significant implications for benchmark integrity. While the performance degraded progressively with each more destructive modification to the intermediate dataset, the fact that even the most extreme case of identical questions and answers still enabled knowledge transfer is concerning. This suggests that the Data Laundering process doesn't necessarily require meaningful intermediate training data to transfer knowledge from the teacher to the student model. Instead, the structural patterns and format of the intermediate dataset appear to be sufficient channels for knowledge transfer. This raises serious concerns about the robustness of current benchmarking practices, as it demonstrates that models can acquire benchmark-specific knowledge through increasingly abstracted and meaningless intermediate training steps.

This finding adds another layer of concern to the overall argument about benchmark vulnerability, showing that even attempts to sanitize intermediate training data may not be sufficient to prevent knowledge transfer if the structural patterns remain intact.



#### Performance with Artificial Distillation Datasets

Figure 5: Impact of Artificially Modifying the Distillation Dataset on the Benchmark Accuracy. This bar plot shows the evaluation accuracy on GPQA using a 2-layer BERT teacher-student pair with  $\alpha = 1.0$  when 1) replacing each answer choice in MedMCQA with 10 random characters, 2) replacing each answer choice in MedMCQA with 10 identical characters so that answer choices are indistinguishable, 3) randomizing questions with 50 characters in addition to answer choices, and 4) having all the questions contain 50 identical characters in addition to answer choices.