Energy consumption of code small language models serving with runtime engines and execution providers

Francisco Durán^{a,*}, Matias Martinez^a, Patricia Lago^b, Silverio Martínez-Fernández^{a,*}

^a Universitat Politècnica de Catalunya, Barcelona, Catalunya, Spain ^b Vrije Universiteit Amsterdam, Amsterdam, Netherlands

Abstract

Background. The rapid growth of Language Models (LMs), particularly in code generation, requires substantial computational resources, raising concerns about energy consumption and environmental impact. Optimizing LMs inference for energy efficiency is crucial, and Small Language Models (SLMs) offer a promising solution to reduce resource demands.

Aim. Our goal is to analyze the impact of deep learning runtime engines and execution providers on energy consumption, execution time, and computing-resource utilization from the point of view of software engineers conducting inference in the context of code SLMs.

Method. We conducted a technology-oriented, multi-stage experimental pipeline using twelve code generation SLMs to investigate energy consumption, execution time, and computing-resource utilization across the configurations.

Results. Significant differences emerged across configurations. CUDA execution provider configurations outperformed CPU execution provider configurations in both energy consumption and execution time. Among the configurations, TORCH paired with CUDA demonstrated the greatest energy efficiency, achieving energy savings from 37.99% up to 89.16% compared to other serving configurations. Similarly, optimized runtime engines like ONNX with the CPU execution provider achieved from 8.98% up to 72.04% energy savings within CPU-based configurations. Also, TORCH paired with CUDA exhibited efficient computing-resource utilization.

Conclusions. Serving configuration choice significantly impacts energy efficiency. While further research is needed, we recommend the above configurations best suited to software engineers' requirements for enhancing serving efficiency in energy and performance.

Keywords: deep learning, language models, model serving, inference, green AI

1. Introduction

The widespread adoption of deep learning models, particularly Language Models (LMs), has surged remarkably in recent years. This trend has led to an exponential in-

*Corresponding author Email addresses: crease in the computational resources needed to support these models [1], raising concerns such as environmental impacts [2]. The focus within the deep learning community has predominantly been on enhancing model accuracy, often overlooking the associated costs. For instance, Benchmarks like GLUE or SuperGLUE encourage competition based on accuracy, often without much consideration for reducing energy consumption [3]. State-of-the-art models like GPT-4 and Claude 2 demand significant computational resources, primarily accessible to companies like

francisco.duran.lopez@estudiantat.upc.edu (Francisco Durán),
matias.martinez@upc.edu (Matias Martinez), p.lago@vu.nl
(Patricia Lago), silverio.martinez@upc.edu (Silverio
Martínez-Fernández)

OpenAI, Anthropic, or Google, leading to a large environmental footprint [4]. Notably, Schwartz *et al.* [5] emphasized the need for deep learning research to prioritize efficiency, advocating for a balance where improvements in accuracy are not achieved at the expense of a larger carbon footprint.

The escalating computational demand of deep learning models, has led to an increase in research focused on improving the sustainability of these systems [6, 7]. Although the majority of this research targets the training phase, a growing body of work acknowledges the significance of both training and inference in achieving a greener deep learning [8, 9]. However, there remains a noticeable gap in studies dedicated to the inference phase[10]. This oversight is important as inference can also contribute substantially to the overall energy footprint of deep learning systems, especially when deployed at scale [11]. Addressing this gap is crucial to reduce overall environmental impact and encourage the development of energy-efficient deep learning systems.

During inference, trained models are integrated into deep learning systems to allow users to make predictions, a process known as deep learning serving [12, 13]. Critical and popular architectural decisions in deep learning serving include the selection of serving infrastructure, with the runtime engine being one of the most commonly used options, and the choice of an execution provider. These decisions are driven by the community's focus on optimizing performance and simplifying deployment to handle growing deep learning systems' complexity [14, 15]. The runtime engine is a software component that loads the model, performs inference, and returns results to the user. It can also apply optimizations, such as graph optimizations or just-in-time compilation [16]. The execution provider, which is the library that serves as the backend of the runtime engine, optimizes model inference based on the available hardware [17, 18]. These two key decisions are able to significantly affect the energy consumption, execution time, and computing-resource utilization of the deep learning system [16].

In this paper, we investigate the energy consumption of different configurations of deep learning serving infrastructures, focusing on runtime engines and execution providers. We concentrate on one particular deep learning task, specifically code generation, as it is one of the most utilized tasks of LMs and has a potential impact on software development productivity [19]. Code LMs have demonstrated impressive capabilities in code generation [20]. Their success largely stems from the Transformer architecture, which excels at learning complex patterns and scales efficiently [21, 22]. This has enabled state-of-theart performance in models like Codex [23], the backbone of GitHub Copilot¹, a tool that provides intelligent code suggestions to developers.

These advanced code LMs, however, often contain millions to billions of parameters [20, 24], requiring vast amounts of training data and substantial computational resources. In contrast, Small Language Models (SLMs) have emerged as a promising alternative, offering similar capabilities but with fewer computational demands, making them accessible to individual developers. Given their efficiency and lower resource requirements, our research focuses specifically on SLMs for code generation, a field where further exploration could lead to significant advancements [4].

We evaluated the impact of various deep learning serving decisions, specifically the choice of runtime engine and execution provider, through a technology oriented experiment using twelve code SLMs. The experiment utilized a generated input dataset from the HumanEval benchmark [23], allowing us to evaluate the energy consumption, execution time, and resource utilization of each serving configuration. These configurations were based on combinations of different runtime engines and execution providers. We tested several runtime engines, including

¹https://copilot.github.com/

Torch, ONNX Runtime, OpenVINO Runtime, and Torch JIT, across both CPU and GPU execution providers, with the aim of identifying the most efficient serving configurations.

Our results revealed notable differences in energy consumption, execution times, and resource utilization across the various serving configurations. Configurations that employed the CUDA execution provider consistently outperformed those using the CPU execution provider in both energy and time efficiency. The combination of TORCH with the CUDA execution provider, as well as ONNX or OpenVINO (OV) with the CPU execution provider, yielded the best results. TorchScript showed potential in specific use cases but still requires further refinement for more widespread application. Overall, the TORCH engine paired with the CUDA execution provider demonstrated efficient utilization of computing resources.

The contributions of this work are:

- Actionable guidelines for software engineers: We recommend using TORCH with CUDA execution provider where GPU acceleration is feasible, and opting for optimized runtime engines such as Open-VINO runtime or ONNX runtime in CPU-only environments to achieve balanced energy and performance efficiency.
- Measuring the impact of deep learning serving configurations on energy and performance: CUDA execution provider configurations consistently reduce energy consumption and execution time during inference. Using TORCH as a runtime engine and CUDA execution provider offers both optimal energy efficiency and faster execution times, with energy savings ranging from 37.99% to 89.16% and execution time reductions from 47.84% to 89.74% compared to the worst-performing runtime engine (ONNX Runtime) in CUDA execution provider configurations. The improvements are greater when evaluated against

its CPU counterparts. The study emphasizes the importance of monitoring resource usage to prevent bottlenecks, such as high CPU or RAM usage in CPU execution provider configurations. It highlights the trade-offs of using optimized runtime engines, balancing energy and execution time improvements against increased resource demands, and showcases the consistent resource efficiency of the baseline runtime engine, TORCH, across various execution providers.

• An analysis of deep learning serving configurations: We developed a multi-stage experimental pipeline to evaluate various deep learning serving infrastructures. This pipeline tested the energy and performance efficiency across different configurations.

Data availability statement. The replication package is publicly accessible² following the "Cookiecutter Data Science" project structure³. It includes the extracted model metadata, the developed serving infrastructure, profiling data, data analysis, statistical tests results, results for each model, and comprehensive documentation to support reproducibility and further research.

The paper is organized as follows. In Section 2, we introduce the background of our research. In Section 3, we introduce the pertinent prior research. Moving to Section 4, we present the research questions and the study design. Subsequently, Section 5 presents the findings. Section 6 shows the discussions and implications. The limitations and threats to validity are described in Section 7. Finally, Section 8 draws conclusions and outlines directions for future work.

2. Background

In this section, we introduce (i) the deep learning serving configurations: duplet of a runtime engine and an execu-

²Please refer to https://doi.org/10.5281/zenodo.14484001 ³https://cookiecutter-data-science.drivendata.org/

tion provider; (ii) the type of deep learning models we use, namely code generation SLMs.

2.1. Deep learning serving configurations

In previous work [16], we identified four distinct types of deep learning serving infrastructures within the deep learning serving architectural design decisions: i) No runtime engine and web server, ii) Runtime engine and web server, iii) deep learning-specific software, and iv) End-toend deep learning cloud service. Figure 1 illustrates the first two serving infrastructures alongside their transversal decisions. While these transversal decisions can improve the interaction between users and the ML application, they are influenced by the underlying serving infrastructure. Additionally, we include the execution provider, which acts as the backend of the runtime engine, optimizing execution for specific hardware.

Runtime engine. The runtime engine is a software component that loads the model into the system's memory from a model registry, performs inference, and returns the results to the user. Optimized runtime engines (e.g. ONNX runtime, OpenVINO runtime, or Torch JIT) offer a flexible interface that facilitates the integration of hardware-specific libraries and implements model optimizations, including graph optimizations or just-in-time compilation [16, 26]. This setup can operate independently or be integrated with a web server, depending on the serving requirements. For instance, the optimized ONNX runtime can be used to load ONNX models and wrap them as a service using a web framework like FastAPI. Once the service is running, the user can make predictions through the service, using a communication protocol like gRPC (see figure 6 from [12]). Additionally, there is the option of using the deep learning framework directly without an optimized runtime engine. This is the simplest approach, as deep learning frameworks are primarily designed for training but can also be used for inference [27]. Several runtime engines are available, including:

- *Torch (TORCH).* Inference is conducted directly through the deep learning framework, for instance, the PyTorch library. This approach relies on the framework's inherent capabilities for model execution without additional runtime optimizations. This approach serves as the baseline, representing a straightforward and unoptimized runtime engine.
- ONNX Runtime (ONNX). The inference is made through a runtime engine, which applies optimizations to the ONNX model. This is one of the most widely used options, with tools like the Optimum library facilitating the use of the ONNX runtime. It is the default optimized runtime for models in ONNX format [12].
- OpenVINO Runtime (OV). The inference is made through the OpenVINO Toolkit [28] runtime engine, which applies optimizations through an Intermediate Representation (IR) and is converted using its Model Optimizer. This runtime engine has been the subject of several studies for its efficiency [29], and libraries like Optimum provide support for OpenVINO runtime integration [30].
- Torch JIT (JIT). A runtime engine from PyTorch, it compiles PyTorch models into TorchScript, an intermediate representation that can be run independently of Python. It is the default optimized runtime for models in TorchScript format [12].

Execution providers. These are libraries that act as the back-end of the runtime engine, optimizing execution for specific hardware (CPU, GPU, FPGA, etc.) [18, 17]. There are various execution providers, including:

- CPU Execution Provider (CPU). Default backend library for CPU [17].
- CUDA Execution Provider (CUDA). CUDA is the most popular backend library and enables hardware

Containerized	Non-containerized	D	ocker	WebAssembly		
Format	PyTorch	TF SavedModel	ONNX	IR representation	Torchscript	
Request processing	real-time	batching				
Communication protocol	REST	g	gRPC		GraphQA	
Runtime Engine	Torch	ONNX runtime OpenVINO runtime		torch.jit		
Execution provider	CPU execution provider		execution provider CUDA execution provider			

Figure 1: Architectural design decisions for deep learning serving: runtime engine as a serving infrastructure and execution provider options. Figure adapted from [25].

accelerated computation on NVIDIA CUDA-enabled GPUs [18, 25, 31].

2.2. Code generation Small Language Models (SLMs)

Increasing evidence indicates that SLMs deliver remarkable results, especially in code-related tasks such as code generation [32, 33, 34]. This is pertinent for practitioners using limited resources or concerned with privacy issues [35, 36], situations where using Large Language Models (LLMs) is neither feasible nor desirable. Moreover, relying on closed-source LLMs like OpenAI's ChatGPT accesible via API can introduce prohibitive costs, privacy concerns, and disproportionate energy consumption for single inferences for few tokens [37]. The exclusive capability of big tech companies to deploy state-of-the-art LLMs, due to their extensive computational and financial resources. leaves small to medium tech companies facing a significant challenge [38]. These smaller companies often operate with constrained CPU or GPU resources, necessitating innovative approaches to make use of LMs effectively. In this context, SLMs emerge as a critical solution, not only enabling a wider range of companies and deep learning practitioners to harness the power of deep learning but also contributing to environmental sustainability efforts by reducing the carbon footprint associated with large-scale computations [38].

3. Related work

There is a notable gap in studies addressing the deployment efficiency of trained deep learning models, despite inference costs potentially surpassing training due to the cumulative effect of using the model or system many times [39, 4]. Studies like Zhang *et al.* [40] examined hardware and software impacts on inference efficiency, while Georgiou *et al.* [27] compared TensorFlow and PyTorch's energy and performance. Koubaa *et al.* [41] explored deployment strategies and model formats. Other works, including Hampau *et al.* [42] and Klimiato *et al.* [43], investigated containerization and deep learning serving infrastructures' effects on energy and performance. Escribano *et al.* [44] focused on cloud computing energy consumption for NLP models, omitting deep learning serving infrastructure comparison.

A recent exploration of the code LMs ecosystem by Yang *et al.* [45] offers a comprehensive analysis of code LMs, shedding light on ecosystem dynamics, model reuse strategies, and documentation practices. Their findings emphasize emerging approaches such as quantization and fine-tuning, which could directly impact deployment efficiency and robustness. In other work, Vartziotis *et al.* [46] compared the sustainability of the generated code itself by three LMs like GitHub Copilot, OpenAI ChatGPT-3, and Amazon CodeWhisperer. Their study emphasizes on the potential of generative LMs to contribute to environmentally conscious software development through green coding practices.

Few studies have considered the runtime engine in the inference phase. Hampau [42] et al. analyzed the energy consumption from three "containerization strategies". The difference with our paper is that we have decided to focus two different dimensions of the decisions deep learning practitioners have on the deep learning Serving Infrastructure, while they studied a single runtime engine without containerization, the same runtime engine with docker and an option without a runtime engine in a different containerization option WASM, and with a specific emphasis on Computer Vision (CV) tasks. Zhang et al. [12] conducted a large study on four different deep learning Serving Infrastructures: two deep learning-specific software and two runtime engines. Although they explored the performance of ONNX Runtime and Torch.JIT, their findings primarily reported on latency, with experiments conducted on versions containerized using Docker and communicated through gRPC API. With regard to execution providers, Alizadeh et al. [18] analyzed the performance and energy differences between CUDA and TensorRT when paired with the ONNX runtime engine and a ResNet model, finding that TensorRT outperformed CUDA. In our research, we examine the default CPU execution provider and CUDA execution provider across multiple code generation SLMs.

The field of software architecture for deep learning based systems is still evolving, presenting significant challenges for practitioners in making design decisions that optimize efficiency[47, 5]. While some studies have proposed architecture-based approaches to improve the efficiency and sustainability of deep learning systems[9, 48], research specifically addressing the serving infrastructure of these systems remains limited [16]. This work contributes to the field by addressing the underexplored area of serving infrastructure selection, complementing existing efforts in architectural decision-making for greener deep learning systems.

Contrary to previous research, our study focuses on analyzing the performance of various deep learning serving configurations during the inference phase of SLM for code generation. Our analysis specifically targets runtime engines and execution providers, and their impact on code SLMs, evaluating critical factors such as energy consumption, execution time, and computing-resource utilization.

4. Research methodology

4.1. Research goal and questions

The research goal [49] of this study is to analyze *deep learning runtime engines and execution providers* for the purpose of *understanding their impact* with respect to *energy consumption, execution time, and computing-resource utilization* from the point of view of *software engineers conducting inference* in the context of *code SLMs*.

Therefore, we intend to address the following research questions (RQ):

- RQ1: How is the energy consumption affected by the execution provider and runtime engine used for inference from code SLMs?
- RQ2: How is the execution time affected by the execution provider and runtime engine used for inference from code SLMs?
- RQ3: How is the computing-resource utilization (CPU usage, RAM usage, GPU usage, GPU memory utilization, and GPU used memory) affected by the execution provider and runtime engine used for inference from code SLMs?

4.2. Experimental units

In this subsection, we detail the experimental units and the process used to construct the input dataset for our study. The experimental units refer to the selected code SLMs used for inference, while the dataset construction draws from the widely-used HumanEval dataset [23]. The experimental units were subjected to treatments in the form of different deep learning serving configurations to evaluate them during inference.

The selection process for the code generation SLMs in this study was conducted with a systematic and structured approach [50], reflecting the state of available models as of November 6th, 2024. Given the time required for executing experiments, and analyzing results, this study might not include other recent code SLMs after such date.

Using the Hugging Face API, metadata for 104,816 textgeneration decoder models was retrieved, including detailed model card information. A series of filters were applied to refine the selection: models exceeding 5 billion parameters were excluded to focus on SLMs, and priority was given to models with potential HumanEval results explicitly mentioned in their metadata, model cards, or flagged as gated models. Only base models, identified within their respective model trees, were retained, narrowing the pool to 340 models. Manual verification ensured that the final 29 models were genuinely base models, free from mislabeled fine-tuned or quantized versions, and had HumanEval evaluation results to confirm their suitability for code-related tasks. From this pool, 12 code SLMs, presented in Table 1, were randomly selected to ensure diversity and representativeness. A replication package containing the extracted data is available for reproducibility and future research (see data availability statement in Section 1).

4.3. Dataset construction

Our input dataset was derived utilizing a methodology similar to those outlined by Fried *et al.* and Bavarian *et al.* [51, 52]. Specifically, we selected a subset of prompts from the HumanEval dataset [23] by taking each problem and processing it as follows: we tokenized the entire problem and then randomly selected a sequence of 10 to 15 tokens. This token sequence was decoded and used as an input prompt for the model, with the aim of generating additional tokens based on the sampled input. This method enabled us to create a dataset that was both controlled to fit our computational setup and diverse enough to effectively evaluate the small language models (SLMs) in code generation tasks with respect to our independent variables.

4.4. Study design

We conduct a technology oriented experiment [53] following the guidelines by Jedlitschka *et al.* [54]. We selected twelve trained models and structured our investigation into a multi-stage pipeline, as illustrated in Figure 2. This pipeline consists of five main stages [55, 56]:

- Data management: This foundational phase is critical in setting up our experiment to test code generation models. We start with the HumanEval dataset [23], which includes 164 coding problems, and adapt it to better suit the specific requirements of our study involving SLMs. This adaptation involves generating a new dataset from the HumanEval problems for the code generation task (see also 4.3).
- 2. Modelling: Our study focuses on analyzing different configurations of deep learning serving infrastructures (see subsection 4.5.1), utilizing pre-trained models. This approach is in alignment with the objectives of our study (see also 4.2).
- 3. **Development:** This initial stage involves model conversion and the development of the serving infrastructure, which includes the REST API. Model conversion is aimed at adapting the pre-trained models to be compatible with the used runtime engines (see data availability statement in Section 1).
- 4. **Operation:** After the development phase, the operation stage starts with the deployment of models across various serving configurations using a Uvicorn server⁴, which is a high-speed ASGI web server and

⁴https://www.uvicorn.org/

Table 1: Overview of the 12 Code SLMs used for inference in this study. These models were selected through a systematic and reproducible process (see also 4.2).

Model Size Category	Model	Release Date	Size $[M/B]$	Affiliation	HumanEval (Pass@1)	Hugging Face Name
1	codeparrot-small	November, 2021	110 [M]	HuggingFace	3.80%	codeparrot/codeparrot-small
	tiny-starcoder	December, 2023	164 [M]	BigCode	7.84%	bigcode/tiny_starcoder_py
	pythia-410m	April, 2023	410 [M]	EleutherAI	1.20%	EleutherAI/pythia-410m
	bloomz-560m	May, 2023	560 [M]	BigScience	2.18%	bigscience/bloom-560m
2	starcoderbase-1b	December, 2023	1 [B]	BigCode	15.17%	bigcode/starcoderbase-1b
	bloomz-1b1	May, 2023	1.1 [B]	BigScience	2.63%	bigscience/bloomz-1b1
	tinyllama	January, 2024	1.1 [B]	StatNLP Research Group	9.15%	TinyLlama/TinyLlama-1.1B-Chat-v1.0
	pythia1-4b	April, 2023	1.4 [B]	EleutherAI	4.30%	EleutherAI/pythia-1.4b
3	codegemma-2b	June, 2024	2 [B]	Google	31.10%	google/codegemma-2b
	phi2	December, 2023	2.7 [B]	Microsoft	48.00%	microsoft/phi-2
	stablecode-3b	August, 2023	3 [B]	Stability AI	26.89%	stabilityai/stablecode-instruct-alpha-3b
	stablecode-3b-completion	August, 2023	3 [B]	Stability AI	17.68%	stabilityai/stablecode-completion-alpha-3b-4k

facilitates REST API requests via the FastAPI⁵ API we developed. This setup allows real-time inferences with our input dataset.

5. Research Output: The final phase analyzes the results generated in the previous stage, focusing on the dependent metrics. These outcomes allow us to answer our RQs posed in our study, according to each serving infrastructure configuration. Furthermore, these results may provide guidelines on the best selection of runtime engines and execution providers.

4.5. Variables

In the following we define the variables of our experimental design grouped into two categories, as summarized in Table 2.

4.5.1. Independent variables

In this study we define one independent variable, Serving Configuration, which is a duplet of a runtime engine and an execution provider (see section 2). The setup consists of evaluating different deep learning serving configurations. We initially obtain eight possible configurations by combining two execution providers (CPU and CUDA) with four runtime engines (TORCH, ONNX, OV, and JIT). However, we exclude the <OV, CUDA> configuration, as OV is specifically optimized for Intel hardware and does not have compatibility with the CUDA execution provider [57]. As a result, we analyze seven configurations, each representing a unique combination of runtime engine and execution provider (e.g., <ONNX, CUDA>).

4.5.2. Dependent variables

To measure the impact of our independent variable to energy efficiency, and performance efficiency, the study tracks some of the most widely measured and relevant metrics in the field according to the Green Software Measurement Model [58]: the energy consumption, execution time, and computing-resource utilization (CPU usage, RAM usage, GPU usage, GPU memory utilization, and GPU used memory) during the inference (see also Table 2).

4.6. Experiment setting

All these experiments have been conducted with an NVIDIA GeForce RTX 4090 GPU with 24 GB memory with CUDA Version 12.4, and an AMD Ryzen 9 7950X 16-Core Processor CPU, 2.5 GHz frequency.

⁵https://fastapi.tiangolo.com/



Figure 2: Schema of our experiment

The complete experiment and data analysis is implemented in Python 3.10.12, using HuggingFace Transformers 4.40.2 [59], and Optimum $1.19.2^6$. To implement the serving configuration, we followed the implementations and model exportation provided by HuggingFace.

To accurately measure the variables outlined in our study, we use the energibridge profiler, nvidia-smi profiler, and a wattmeter. These tools are recognized in the scientific community for its effectiveness in assessing energy consumption of computational processes, as evidenced by its application in previous research [60, 61]. EnergiBridge was chosen for its simplicity and ready-to-use setup, enabling efficient data collection across various platforms without extensive configuration. Nvidia-smi, optimized for NVIDIA GPUs, was the ideal tool for measuring GPUspecific energy consumption and utilization. Finally, the wattmeter provided direct and precise measurements of total device energy consumption. It was used to verify that the energy reported by the CPU and GPU profilers matched the total energy consumption measured by the wattmeter, ensuring the accuracy and validity of our energy measurements.

Energibridge.⁷ EnergiBridge is a cross-platform tool

designed to measure software energy consumption on various operating systems (Linux, Windows, and macOS) and CPU architectures (Intel, AMD, and Apple ARM). Developed in Rust, it simplifies energy monitoring by providing a unified interface and collects data through low-level system calls, converting measurements into watts for standardized reporting across different systems [62].

NVIDIA System Management Interface (nvidiasmi).⁸ The nvidia-smi command-line tool is a practical utility for accessing a variety of NVIDIA GPU-related data, including power consumption, memory usage, temperature, and more. This tool is especially valuable for monitoring the power use of GPU-intensive tasks such as training deep learning models, inference tasks, streaming videos, gaming, and other similar activities.

Wattmeter.⁹ The wattmeter is a tool for measuring electrical power. In our experimental setup we used the NETIO PowerBOX 4KF, an intelligent power strip with four individually controllable outlets. This device is integrated into our system to monitor and record key electrical metrics such as energy consumption. We retrieve data through its JSON-based API.

⁶https://huggingface.co/docs/optimum/

⁷https://github.com/tdurieux/EnergiBridge

 $^{^{8} \}rm https://developer.nvidia.com/nvidia-system-management-interface$

⁹https://vitriko.eu/regleta-inteligente-netio-powerbox-4kf

Class	Name	Description	Scale	Operationalization
Independent	Serving configuration	Duplet of a runtime engine and an execution provider: <torch, cpu="">, <onnx, cpu="">, <ov, cpu="">, <jit, cpu="">, <torch, cuda="">, <onnx, cuda="">, and <jit, cuda="">.</jit,></onnx,></torch,></jit,></ov,></onnx,></torch,>	Nominal	See sections 2 and 4.5.
	Energy consumption	Energy consumption of one serving configuration during inference with input dataset (J).	Numerical	Profiled (energibridge, nvidia-smi).
	Execution time	Average of duration to do inference with test dataset (s).	Numerical	Profiled (linux).
	CPU usage	Average percentage of used CPU (%).	Ratio	Profiled (energibridge).
Dependent	RAM usage	Average percentage of used RAM (%).	Ratio	Profiled (energibridge).
	GPU usage	Average percentage of used GPU (%).	Ratio	Profiled (nvidia-smi).
	GPU memory utilization	Average percentage of time over the past sample period during which global (device) memory was being read or written (%).	Ratio	Profiled (nvidia-smi).
	GPU used memory	Average percentage of memory allocated by active contexts (%).	Ratio	Profiled (nvidia-smi).

Table 2: Variables of the experiment.

4.7. Experiment execution

In this study, we deploy a server that receives HTTP requests from a client. The server hosts the developed API, which processes input prompts and returns the model's output, specifically the generated decoded tokens. The experiment involves selecting one of the seven serving configurations and performing the following steps for each configuration: for each model, the model is loaded, and inference is conducted on all 164 requests using the input dataset. During the inference process for each serving configuration, we collect the dependent variables using the three profilers described in section 4.6. To ensure stability, we run the server for five minutes before starting the inferences and for another five minutes after completing the inferences with each serving configuration. The experiment is repeated 10 times to ensure consistency in the results, as this number of repetitions was sufficient to observe minimal variability and provide reliable medians across configurations. Still, each repetition of the experiment involves 7 serving configurations, 12 models, and 164 input requests per model, resulting in a substantial amount of data collected.

4.8. Data analysis

To address the research questions (RQs), we define the null hypotheses showed in Table 3 for each dependent variable and its performed tests.

For each hypothesis, we follow a systematic analysis process: (1) use box plots to illustrate the distributions for each dependent variable, comparing between configura-

\mathbf{RQs}	Variable	Statistical test/ Post-hoc test	Null hypothesis
RQ1	Energy consumption	Welch's ANOVA/ Games-Howell	H.1.0: There is no difference in energy consumed during inference varying the runtime engine and execution provider.
RQ2	Execution time	Welch's ANOVA/ Games-Howell	H.2.0: There is no difference in execution time during inference varying the runtime engine and execution provider.
	CPU usage	Welch's ANOVA/ Games-Howell	H.3.1.0: There is no difference in CPU usage during inference varying the runtime engine and execution provider.
-	RAM usage	Welch's ANOVA/ Games-Howell	H.3.2.0: There is no difference in RAM usage during inference varying the runtime engine and execution provider.
RQ3	GPU usage	Kruskal-Wallys/ Dunn	H.3.3.0: There is no difference in GPU usage during inference varying the runtime engine and execution provider.
	GPU memory utilization	Kruskal-Wallys/ Dunn	H.3.4.0: There is no difference in GPU memory utilization during inference varying the runtime engine and execution provider.
-	GPU used memory	Kruskal-Wallys/ Dunn	H.3.5.0: There is no difference in GPU used memory during inference varying the runtime engine and execution provider.

Table 3: Tests performed for RQs with their null hypotheses.

tions using the same model; (2) assess if the measurements are normally distributed and have equal variances across the different treatments of each RQ. Utilize the Shapiro-Wilk test to check for the normality of the data. To check the homogeneity of variances, we use a Levene test for equality of variances. (3) assess the statistical significance (i.e., p-value) of the findings.

In our data analysis, we conducted two types of statistical tests based on the distribution of the dependent variables. For configurations where the data is normally distributed, we applied Welch's ANOVA to assess differences between serving configurations, since the dependent variables do not exhibit equality of variances, followed by the Games-Howell test for post-hoc analysis. For nonnormally distributed data, we used the Kruskal-Wallis test, with Dunn's test as the post-hoc analysis to identify specific differences between groups. The details of the analysis and test results are available in the replication package for further examination (see data availability statement in Section 1).

5. Results

In this section, we report the results of our experiment, addressing our research questions and highlighting key takeaways. We initially evaluated seven deep learning serving configurations. Following the experiments, we reviewed the outputs of the scripts and inferences, identifying error-prone responses in the TorchScript configurations. As a result, these configurations were excluded from further analysis. The results presented here focus on comparisons across the final five selected configurations while using results from twelve different code SLMs, as shown in Tables 4 - 5 and Figures 3 - 5 (one color for each model in the box plots). Due to the number of used models for each serving configuration we report results aggregated by model size category (see table 1) for all metrics. The categories are organized based on model size category, with category 1 representing the smallest models and category 3 representing the largest models. We present more detailed results for all evaluation metrics in the replication package.

5.1. Energy consumption of code SLMs for code generation (RQ1).

Tables 4 and 5 present the aggregated median values of energy consumption by model size category. For CPU execution provider configurations (where the GPU is not utilized), only global energy, based on CPU energy, is reported. For CUDA execution provider configurations, the results include CPU energy, GPU energy, and global energy, calculated as the sum of CPU and GPU energy.

The median energy consumption for configurations using the CUDA execution provider is consistently lower than that of the CPU execution provider. Notably, the <TORCH, CUDA> configuration stands out as the most energy-efficient across all models, a trend that is also evident in the aggregated results.

The <ONNX, CUDA> configuration exhibits the highest median energy consumption values among the CUDA execution provider configurations. Similarly, <TORCH, CPU> configurations consume the most energy across the majority of models when using the CPU execution provider. This pattern is also reflected in the aggregated results.

ONNX optimizations are significantly more effective when paired with the CPU execution provider, demonstrating better energy efficiency compared to the deep learning framework alone. Among the optimized runtime engines, ONNX, along with OV, consumes less energy, with ONNX emerging as the most energy-efficient in CPU execution provider configurations. However, when using the CUDA execution provider, ONNX fails to provide the same level of energy savings, as it does not outperform the baseline TORCH runtime engine, which remains the most energy-efficient. This discrepancy in energy performance likely stems from the way the ONNX runtime engine interacts with each execution provider.

While using the CPU execution provider, it was observed that the extended execution times (see Table 4) led to a significant increase in energy consumption by the CPU. This prolonged inference time, especially with more complex models, may cause CPU configurations to use substantially more energy. The inefficiency of the CPU execution provider in energy conservation highlights the need for optimized resource allocation and management in deep learning serving environments to minimize unnecessary energy consumption. In contrast, CUDA configurations, despite utilizing both CPU and GPU resources, were far more energy-efficient for intensive tasks due to their significantly faster execution times.

Our results showcase considerable differences in the energy consumption of different configurations. There is statistic significance (Welch's ANOVA test p-value) between the deep learning serving configuration and the response variables. Furthermore, Games-Howell post-hoc test reveals that all configurations are statistically different from each other (**H.1.0**). These results are provided in the replication package (see data availability statement in Section 1).

Answer to RQ1: Energy consumption is significantly affected by the serving configuration, with CUDA configurations being more efficient than CPU configurations. <TORCH, CUDA> provides the best balance between energy efficiency and reliability, while optimized runtime engines like OV and ONNX, particularly ONNX, reduce energy consumption in CPU configurations but are less effective with CUDA compared to TORCH.

Model size category	Serving configuration	Global energy [J]	Execution time [s]	
1	<onnx, cpu=""></onnx,>	45069.35	655.09	
1	$\langle OV, CPU \rangle$	58374.88	561.61	
1	<torch, cpu=""></torch,>	64993.75	773.27	
2	<onnx, cpu=""></onnx,>	178641.05	2100.83	
2	$\langle OV, CPU \rangle$	223821.62	1355.18	
2	<torch, cpu=""></torch,>	216854.71	2583.76	
3	<onnx, cpu=""></onnx,>	393187.23	3958.18	
3	$\langle OV, CPU \rangle$	400527.50	2300.14	
3	<torch, cpu=""></torch,>	512731.24	5668.91	
1,2,3	<onnx, cpu=""></onnx,>	205632.54	2238.03	
1,2,3	$\langle OV, CPU \rangle$	227574.67	1405.64	
1,2,3	<torch, cpu=""></torch,>	264859.90	3008.65	

Table 4: CPU execution provider: aggregated median energy consumption and execution time values for inference across entire dataset by model size category. Best values are shown in green. Last section presents mean values for each serving configuration.

5.2. Execution time of code SLMs for code generation (RQ2).

Tables 4 and 5 present the aggregated median values of execution time by model size category. This analysis highlights a significant difference in execution time, with configurations utilizing the CUDA execution provider generally achieving faster execution times compared to those using CPU execution provider. This underscores the efficiency of GPU acceleration in handling computationally intensive tasks.

Extreme cases are observed with models such as phi2 using <TORCH, CPU>, where the median execution time (5983.52 seconds) is more than 20 times longer than with the <TORCH, CUDA> configuration (251.97 seconds), highlighting significant bottlenecks in CPU-based processing for complex computational tasks. Similar extreme cases are noted within the largest model size category (Category 3) using TORCH, where the CPU execution provider's execution time (5668.91 seconds) exceeds the CUDA execution provider's time (260.62 seconds) by more than 20 times.

Similar to its impact on energy efficiency, ONNX optimizations are clearly more effective with the CPU execution provider, but not as successful with the CUDA execution provider, comparing to Torch configurations. When using the CPU execution provider, the optimized runtime engines, particularly OV and ONNX, perform faster than the deep learning framework alone, with OV showing the best results. However, ONNX behaves differently when paired with the CUDA execution provider, where it fails to match or outperform TORCH in terms of speed. Again, this discrepancy may be due to how each execution provider interacts with the ONNX runtime engine. This results can also be observed in Tables 4 and 5.

Welch's ANOVA confirmed significant differences in execution times across different runtime engines. The subsequent Games-Howell post-hoc tests annotate that all configurations are statistically distinct from one another, confirming the marked impact of the execution provider and runtime engine choice on the efficiency of computational

Model size category	Serving configuration	CPU energy [J]	GPU energy [J]	Global energy [J]	Execution time [s]
1	<onnx, cuda=""></onnx,>	13404.99	20692.81	34138.28	277.12
1	<torch, cuda=""></torch,>	5193.32	11250.87	16432.53	124.03
2	<onnx, cuda=""></onnx,>	32113.95	55652.21	87788.33	630.64
2	<torch, cuda=""></torch,>	7287.23	24247.47	31525.72	168.74
3	<onnx, cuda=""></onnx,>	39012.21	81516.82	120509.17	763.59
3	<torch, cuda=""></torch,>	12196.07	50052.11	62301.62	260.62
100	ONNY CUDA.	201 75 05	F0600 61	00011.00	FFT 10
1,2,3	<onnx, cuda=""></onnx,>	28177.05	52620.61	80811.93	557.12
1,2,3	<TORCH, CUDA $>$	8225.54	28516.82	36753.29	184.46

Table 5: CUDA execution provider: aggregated median energy consumption and execution time values for inference across entire dataset by model size category. Best values are shown in green. Last section presents mean values for each serving configuration.

tasks (**H.2.0**). The only exceptions were that the execution times of the <ONNX, CPU> and <TORCH, CPU> configurations did not differ significantly for three out of the twelve models (bloomz-560m, codeparrot-small, and tiny-starcoder), resulting in the rejection of **H.2.0** for only these models.

Answer to RQ2: Execution time is significantly influenced by the serving configuration, with CUDA configurations consistently outperforming CPU configurations. <TORCH, CUDA> delivers the best performance, while OV and ONNX optimize execution time, especially OV, with CPU execution provider but do not achieve comparable improvements with CUDA execution provider, reflecting similar patterns seen in energy consumption.

5.3. Computing-resource utilization of code SLMs for code generation (RQ3).

Table 3 presents a summary of the statistical analysis conducted to assess the computing-resource utilization across the different serving configurations. These analyses were applied to key metrics such as CPU usage, RAM usage, GPU usage, GPU memory utilization, and GPU used memory.

For statistical evaluation, different tests were applied depending on the normality and variance homogeneity of the data. Welch's ANOVA was used for data with unequal variances but normal distributions, while the Kruskal-Wallis test was employed for non-normally distributed data. The significance of differences between configurations was assessed using these tests, with pvalues indicating significant differences with values below $\alpha = 0.05$. Furthermore, post-hoc analyses using Games-Howell or Dunn's test were performed to identify specific pairwise differences. In terms of computing-resource utilization metrics, all serving configurations showed significant differences from one another (H.3.1.0, H.3.2.0, H.3.3.0, H.3.4.0, and H.3.5.0), with a few exceptions. Specifically, RAM usage between certain serving configuration pairs—such as <OV, CPU> and <TORCH, CPU>, <ONNX, CUDA> and <TORCH, CUDA>, <OV, CPU> and <ONNX, CPU>, as well as <TORCH, CPU> and <ONNX, CUDA>—did not exhibit significant differences in two out of the twelve models for each pair. As a result, H.3.2.0 was rejected for those specific cases.

In the results of GPU metrics, we focus exclusively on

the three CUDA execution provider configurations. Comparisons with CPU execution provider configurations are omitted, as they do not utilize the GPU, making such comparisons irrelevant.

CPU usage: The visual data and median values indicate that configurations using the CPU execution provider generally exhibit higher CPU usage than those employing the CUDA execution provider, which aligns with expectations given the operational differences between the two. For CUDA execution providers, CPU bottlenecks are minimal since the majority of computations are offloaded to the GPU. However, when using CPU execution provider, as it is expected that all the operations are executed by the CPU, selecting the serving configuration may impact CPU usage.

The <TORCH, CUDA> configuration consistently demonstrated the lowest CPU usage among all configurations, highlighting its efficiency in resource utilization. This configuration achieves an effective balance between GPU and CPU usage, optimizing the model operations for improved performance.

CPU usage for configurations utilizing the ONNX runtime engine is slightly higher when paired with the CUDA execution provider, with median values ranging from 2.98% to 4.02%. While differences in CPU usage are observed, no consistent pattern emerges across models when the CPU execution provider is employed.

RAM usage: Results show that configurations using the CPU execution provider generally consume more RAM compared to those using the CUDA execution provider. This discrepancy can be attributed to the fact that CPU execution provider manages all computational resources directly within the system's main memory, whereas CUDA execution provider leverages both RAM and dedicated VRAM, effectively distributing memory load.

The <TORCH, CUDA> configuration consistently demonstrated the lowest RAM usage, ranging from 4.77% to 11.45% in 9 out of 12 models. This highlights its efficiency in resource utilization, as it achieves a balance between computational performance and minimal RAM consumption. TORCH configurations, in general, exhibit lower RAM usage compared to other runtime engines.

In contrast, <ONNX, CPU> and <OV, CPU> configurations exhibited significantly higher RAM usage, with <ONNX, CPU> ranging from 9.96% to 30.16% and <OV, CPU> from 8.85% to 20.88% in 10 out of 12 models. These findings indicate that optimized runtime engines like ONNX and OV demand more system resources due to their memory management strategies. While they improve energy efficiency and execution time in some scenarios, this often comes at the cost of increased RAM usage. Furthermore, in CUDA execution provider configurations, ONNX exhibits higher RAM usage but performs worse in terms of both time and energy efficiency compared to TORCH, further underscoring TORCH's superior balance of performance and resource utilization.

GPU usage: results show that the configuration <TORCH, CUDA> reaches the highest levels of GPU utilization (from 21.08% up to 86.98%), leveraging available GPU resources effectively. Conversely, the <ONNX, CUDA> configuration shows the lowest GPU usage (from 18.07% up to 75.49%) among the CUDA execution provider options, suggesting it may not exploit the computational potential of the GPU as efficiently as <TORCH, CUDA>. This trend is also reflected in the aggregated results across the three groups.

GPU memory utilization: Our GPU utilization memory results reveal that <TORCH, CUDA> configurations exhibited the highest memory utilization (from 11.57% up to 83.59%, all models), effectively leveraging GPU capabilities for intensive memory operations. In contrast, <ONNX, CUDA> configurations showed the lowest memory utilization (from 2.34% up to 27.33%), suggesting either conservative use or inefficiencies in exploiting GPU VRAM operations compared to configurations using <TORCH, CUDA>. These findings emphasize the crucial role of runtime engine selection in maximizing the memory efficiency of CUDA execution provider, with significant variations noted in how different engines manage and utilize VRAM.

GPU used memory:Regarding GPU allocated memory (GPU used memory), the results show varying patterns among CUDA execution provider configurations. For 7 out of 12 models, the <TORCH, CUDA> configuration exhibited higher levels of memory allocation, while the <ONNX, CUDA> configuration showed higher memory allocation for the remaining 5 models. Specifically, <TORCH, CUDA> configurations ranged from 12.01% to 59.16%, whereas <ONNX, CUDA> configurations ranged from 5.12% to 71.87%. These findings highlight differences in memory allocation strategies and the relative efficiency of Torch in allocating GPU memory.

Answer to RQ3: Computing-resource utilization is significantly influenced by the serving configuration, with OV or ONNX within CPU configurations improving energy or time efficiency but increasing RAM demands. In contrast, CUDA configurations, particularly <TORCH, CUDA>, show more efficient resource utilization, achieving higher GPU utilization and better memory allocation, reducing the load on CPU and RAM.

6. Discussion and implications

In this section, we analyze and interpret the study's findings for each dependent variable, discuss their implications, and highlight key insights derived from the research.

Energy consumption. In our analysis, we observe that configurations utilizing the CUDA execution provider consistently consume less energy compared to those utilizing the CPU execution provider. This significant difference underscores the inherent efficiencies of CUDA execution provider, which enables hardware-accelerated computation on NVIDIA GPUs, effectively managing parallel processing tasks in code generation models.

Interestingly, ONNX runtime configurations show greater optimization when paired with CPU execution provider compared to CUDA execution provider, when compared to other runtime engines under the same execution provider. This enhanced performance with CPU execution provider could stem from the specific libraries used (such as Transformers and Optimum HuggingFace's libraries [59]) or the particular demands of code generation SLMs. It can be resource-intensive for ONNX configurations because of the overhead involved in mapping different subgraphs to suitable execution providers and the synchronization of inputs [63]. However, this complex binding process could yield benefits in scenarios involving varied batch sizes or other types of deep learning tasks, where such dynamic resource allocation is advantageous. Further exploration of this type of runtime engine across various deep learning tasks could provide valuable insights for software engineers.

The findings from our study highlight crucial implications for deploying deep learning models, particularly in how different configurations affect energy consumption and performance. The superior energy efficiency of CUDA execution provider configurations suggests significant potential for cost savings and reduced environmental impact, making GPU-accelerated environments preferable for intensive parallel processing tasks. Furthermore, the tradeoffs observed with ONNX's varied optimization across execution providers, underline the importance of aligning runtime engines with the appropriate hardware to balance energy efficiency with computational accuracy.

Execution time. CUDA execution provider configurations consistently outpace those using CPU execution provider, demonstrating the substantial advantages of leveraging NVIDIA GPUs for parallel processing tasks. This performance disparity is consistent with findings from other studies, further confirming the superior processing



Figure 3: Aggregated energy consumption and execution time by model size category: CUDA execution provider (left) and CPU execution provider (right) measured by Energibridge and Nvidia-smi

speeds of GPUs.

The capabilities of CUDA execution provider configurations demonstrate their efficiency in both time and energy during inference processes, independent of the chosen runtime engine. This efficiency is consistently evident across all CUDA execution provider configurations, making it a highly effective choice for operating SLM for code generation, enhancing both speed and energy efficiency.

The ONNX runtime engines shows a notable difference in optimization between CPU execution provider and CUDA execution provider configurations. It performs well under CPU execution provider, likely due to tailored optimizations for CPU usage, but does not translate these benefits as effectively to CUDA execution provider, when comparing to the other runtime engines. We find this counterintuitive as GPU implementations are usually faster than CPU, it could be to [64] or that CUDA execution provider in ONNX runtime does not fully support CUDA kernels used for the SLMs [65]. Due to the speed of development of deep learning research and development, we expect this type of optimized runtime engines are in general a better option for production-like deep learning systems.

In their study, Bekhelifi *et al.* [63] found that configurations using $\langle ONNX, CPU \rangle$ outperformed those using $\langle OV, CPU \rangle$ in terms of speed for Brain-Computer Interface applications. However, our results contrast this finding, as $\langle OV, CPU \rangle$ proved faster in our experiments. This discrepancy highlights how the performance of optimized runtime engines can vary significantly across different deep learning tasks. We recommend further investigation into how these engines perform across a broader range of deep learning systems to better understand their



Figure 4: Aggregated computing-resource utilization by model size category: CUDA execution provider (left) and CPU execution provider (right) measured by Energibridge

task-specific efficiencies and limitations.

Computing-resource utilization. Configurations using CPU execution provider typically encounter bottlenecks in CPU and RAM usage. This underscores the need for careful selection and optimization of runtime engines to avoid overloading the CPU, as computational tasks in this execution provider heavily rely on RAM. In contrast, CUDA execution provider configurations benefit from the additional use of VRAM, distributing the memory load more effectively between system RAM and GPU memory. For instance, ONNX and OV configurations, while energy-efficient in CPUEP, require substantial memory (RAM and/or GPU memory) to handle inference, Using lower precision can help manage GPU memory when using CUDA execution provider [65]. significant statistical differences were observed in GPU utilization and memory efficiency. The <TORCH, CUDA> configuration consistently demonstrated the highest GPU usage, GPU memory utilization, and GPU used memory, highlighting its ability to effectively harness GPU resources for computationally intensive tasks. In contrast, the <ONNX, CUDA> configuration showed comparatively lower GPU utilization, suggesting potential inefficiencies in its optimization for the CUDA execution provider or its compatibility with specific code generation SLMs. Despite its higher GPU resource utilization, <TORCH, CUDA> proved to be more efficient overall, as it consumed less CPU and RAM compared to <ONNX, CUDA>, indicating a balanced and resource-efficient approach to managing deep learning inference workloads.

Within the CUDA execution provider configurations,

Torchscript runtime. As outlined in Section 5, the



(c) Used GPU memory utilization [%]

Figure 5: Aggregated computing-resource utilization by model size category: CUDA execution provider configurations measured by Nvidiasmi

TorchScript runtime engine was also included in our experiments. However, we excluded its results from the analysis due to the error-prone outputs it produced. Instead, we investigated the causes of these issues, focusing on underlying factors rather than setup problems.

As a runtime engine, TorchScript's primary mode of operation in this study was through Trace mode, which inherently supports a broader range of Python features by operating beneath the Python layer. This mode records all PyTorch operations executed with a representative input to create an optimized TorchScript Intermediate Representation (IR). While this mode is advantageous for accommodating all Python features and ensuring consistent execution paths, it is notably error-prone as it does not capture dynamic control flows inherent in Python, it only to inaccuracies in conditions where execution paths vary [66, 67, 68].

supports functions with a single path, potentially leading

TorchScript's ability to fuse operations into larger computational blocks offers potential advantages by reducing memory reads and writes, thereby optimizing certain computational tasks. Additionally, intermediate results can be cached directly in registers or shared memory, minimizing the need for repeated memory access [69, 70]. However, despite these memory optimizations, overall memory usage remains high, indicating that the benefits do not necessarily translate into lower memory consumption. This limitation, combined with TorchScript's inability to effectively manage dynamic execution paths, diminishes its potential energy and speed advantages. These findings highlight the critical need to align runtime engine capabilities with the specific demands and infrastructure of the deployment environment to achieve optimal performance and computingresource utilization.

If a static graph exported shows good responses, it could be the best option for a production environment, however it must be really well tested and it is time-exhaustive. There are some options being built that can potentially eliminate this drawbacks [66, 67].

Guidelines and implications for selecting appropriate serving infrastructure. Determining the best configuration largely depends on the specific requirements and constraints of the deep learning serving system. Based on the results presented in Section 5, several key guidelines can be drawn for software engineers. These guidelines provide insights into selecting appropriate execution providers and runtime engines based on specific operational needs:

- Energy efficiency optimization: CUDA execution provider configurations, particularly <TORCH, CUDA>, are the most energy-efficient for code generation tasks. CPU execution provider configurations, when paired with ONNX runtime engines, offer a balanced alternative, optimizing resource usage without the need for GPU hardware, making them ideal for energy-aware, non-GPU environments.
- Execution time optimization: CUDA execution provider configurations consistently deliver faster performance across the board. TORCH under CUDA execution provider offers the fastest execution times. In CPU configurations, OV provides the best execution time enhancements.
- Computing-resource utilization: In CPU execution provider configurations, if RAM is a constraint, <TORCH, CPU> offers a more balanced option, though it may not be optimal for energy efficiency or execution time. For better overall resource management, <TORCH, CUDA> within CUDA execution

provider configurations stands out, showing better resource management in overall(i.e. leveraging GPU resources while reducing workload to CPU, and RAM memory).

Optimizing LMs inference. Scaling up the size of language models has consistently been shown to improve their accuracy [71]. However, this scaling comes with substantial computational costs, memory demands, and environmental concerns, posing significant challenges for the practical deployment of LMs. This study, along with prior research [16], highlights the critical role of serving configurations in improving energy efficiency and performance, demonstrating how their selection can significantly impact these metrics.

The increasing adoption of LMs in real-world applications highlights the critical role of system-level decisions. In addition to runtime engines and execution providers, serving infrastructures such as DL-specific software (e.g., TorchServe) and end-to-end cloud services (e.g., AWS SageMaker) represent system-level optimizations that can enhance energy and performance efficiency without compromising model accuracy [16, 72]. These decisions align with the software engineering perspective, where employing green software tactics can effectively optimize deep learning systems throughout their lifecycle [73].

Additionally, data-level optimizations (e.g., Retrieval-Augmented Generation) and model-level optimizations (e.g., model compression and dynamic inference) might complement system-level strategies in enhancing efficiency. For instance, dynamic neural networks, which adapt computational resources based on input complexity, exemplify a balanced approach to achieving both efficiency and effectiveness. Existing implementations of these techniques provide valuable insights while highlighting opportunities for further analysis, development, and broader implementations [74, 72, 75].

7. Limitations & threats to validity

Our study has various limitations, primarily due to its focus on open-source SLMs, specific runtime engines, and execution providers. The findings may not generalize to other model types or serving configurations. Although the provided replication package allows for other models and configurations to be easily added, the conclusions are limited to the examined setup and code SLMs context. Our findings may not generalize to all deep learning systems, but they offer a foundation for optimizing and analyzing energy-efficient serving configurations. These results are specific to the particular used hardware, described in Section 4.6, and future work could mitigate this by incorporating a wider range of hardware, including different GPUs and CPUs, to enhance the robustness of the findings.

Additionally, this study focused on the code generation task using prompts derived from the HumanEval dataset [23]. While HumanEval is one of the most widely used evaluation datasets, its scope may not fully capture the diversity of real-world scenarios. This limitation is particularly relevant given that our research work and development of serving infrastructure were initiated in late 2023. Expanding the scope to include more comprehensive and newer benchmarks, such as SWE-bench dataset [76], is a clear future work option to potentially provide broader insights into code SLMs serving configurations.

Lastly, the reliance on the Transformers library for implementation introduces some limitations in flexibility, as other libraries might yield different performance results. Future work could explore using alternatives to assess generalizability across different implementations.

Conclusion validity. The statistical power of our experiments was carefully designed to ensure the reliability of our findings. To address this, we employed statistical methods, adhered closely to a methodically planned experimental procedure as detailed in section 4, and ensured reproducibility through comprehensive documentation of our methods and data in the replication package. Consid-

ering various factors, treatments, and runs, we utilized a total of 600 (12 code SLMs, 5 deep learning serving configurations, 10 runs) samples to respond to our research questions, each sample representing a set of 164 inference requests. This approach, coupled with the execution of ten experimental runs and ensuring minimal background software interference, aims to fortify the reliability of our results. The procedure for replicating our work is thoroughly described, with datasets and the replication package openly accessible for validation.

Construct validity. To mitigate mono-method bias, we utilized three different profiling tools and a wattmeter to cross-verify the energy consumption recorded by the CPU (via energibridge) and GPU (via nvidia-smi) against the total energy reported by the wattmeter, ensuring the validity of our energy measurements. Additionally, we included twelve state-of-the-art SLMs in our study. Concerning model correctness, we did not evaluate this aspect as we employed well-established, previously validated models. All experimental outputs are provided in the replication package for comprehensive examination.

Internal validity. Potential internal validity threats such as hardware condition changes over successive experimental runs were addressed by implementing a fiveminute period between each configuration and experiment run. This protocol helps maintain consistent hardware conditions across all tests. To minimize risks associated with the implementation of the inference process, we used default configurations provided by HuggingFace.

External validity. Our study's external validity is potentially limited by the specific subset of deep learning serving configurations and models used. The models and configurations were selected based on their current relevance and availability, but they may not encompass all possible variations in deep learning serving scenarios. To mitigate this, we incorporated the two most commonly used execution providers available to us and four wellknown runtime engines.

8. Conclusions and future work

As outlined in the European Union AI Act [77], energy consumption is a critical factor in the lifecycle of deep learning models, particularly in both the training and inference phases. The Act emphasizes that energy efficiency must be considered as a key criterion when utilizing deep learning technologies. With GPUs now emerging as the most widely used hardware for training and deploying deep learning models due to their parallel processing capabilities, optimizing energy consumption has become even more pertinent.

In this work, we studied deep learning serving configurations, as duplets consisting of a runtime engine and an execution provider. We evaluated the energy consumption, execution time, and computing-resource utilization across five distinct configurations using twelve different code SLMs. Our observations reveal that:

- The choice of runtime engine and execution provider significantly impacts energy consumption, execution time, and computing-resource utilization during deep learning inference.
- 2. Configurations utilizing the CUDA execution provider consistently demonstrate superior energy and time efficiency.
- TorchScript engine shows promise as an optimal choice for specific scenarios, though it may require further enhancements to fulfill its potential for code generation.
- 4. In our experiments, the baseline TORCH engine coupled with the CUDA execution provider exhibited efficient energy consumption, execution time, and computing-resource utilization.

We anticipate that future advancements in optimized runtime engines will enhance these metrics and address existing limitations, including error-proneness, to make them even more robust and efficient.

Our research highlights distinct performance advantages among the various configurations. Specifically, the CUDA execution provider paired with TORCH consistently yielded the best overall performance. Conversely, when utilizing the CPU execution provider, both OV and ONNX runtime engines enhanced performance metrics significantly. In configurations with the CUDA execution provider and TORCH, energy consumption using this configuration can be from 10.84% up to 62.01%, and execution times from 10.26% up to 52.16% comparing to worst CUDA execution provider runtime engine (ONNX runtime). For setups using the CPU execution provider with OV or ONNX, we observed the energy consumption can be from 27.96% up to 91.02%, and execution times from 28.79% up to 79.04% compared to the baseline TORCH engine. Notably, the ONNX runtime engine did not exhibit superior performance compared to the baseline TORCH configuration within CUDA execution provider configurations.

Future research should replicate these experiments across a diverse range of deep learning tasks, extending beyond computer vision to encompass various natural language processing tasks like summarization and text classification. Such studies will not only confirm the generalizability of our findings but may also reveal insights specific to different tasks. Additionally, we recommend investigating newly developed runtime engines and execution providers. As technology advances, these newer configurations are likely to enhance performance and energy efficiency, further promoting sustainable deep learning practices.

Acknowledgment

This paper has been partly funded by the GAISSA Spanish research project (ref. TED2021-130923B-I00; MCIN/AEI/10.13039/501100011033).

References

- M. Shoeybi, M. Patwary, R. Puri, P. LeGresley, J. Casper, B. Catanzaro, Megatron-lm: Training multi-billion parameter language models using model parallelism, arXiv preprint arXiv:1909.08053.
- [2] E. Strubell, A. Ganesh, A. McCallum, Energy and policy considerations for deep learning in NLP, in: Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics, Association for Computational Linguistics, Florence, Italy, 2019, pp. 3645–3650. doi:10.18653/v1/P19-1355. URL https://aclanthology.org/P19-1355
- [3] J. Cowls, A. Tsamados, M. Taddeo, L. Floridi, The ai gambit: leveraging artificial intelligence to combat climate change—opportunities, challenges, and recommendations, Ai & Society (2023) 1–25.
- [4] R. Perrault, J. Clark, Artificial intelligence index report 2024.
- [5] R. Schwartz, J. Dodge, N. A. Smith, O. Etzioni, Green AI, Commun. ACM 63 (12) (2020) 54–63. doi:10.1145/3381831.
- [6] J. Dodge, T. Prewitt, R. Tachet des Combes, E. Odmark, R. Schwartz, E. Strubell, A. S. Luccioni, N. A. Smith, N. De-Cario, W. Buchanan, Measuring the carbon intensity of ai in cloud instances, in: 2022 ACM Conference on Fairness, Accountability, and Transparency, 2022, pp. 1877–1894.
- [7] S. Ajel, F. Ribeiro, R. Ejbali, J. Saraiva, Energy efficiency of python machine learning frameworks, in: International Conference on Intelligent Systems Design and Applications, Springer, 2022, pp. 586–595.
- [8] S. Martínez-Fernández, X. Franch, F. Durán, Towards green ai-based software systems: an architecture-centric approach (gaissa), in: 2023 49th Euromicro Conference on Software Engineering and Advanced Applications (SEAA), IEEE, 2023, pp. 432–439.
- [9] H. Bhatt, S. Arun, A. Kakran, K. Vaidhyanathan, Towards architecting sustainable mlops: A self-adaptation approach, arXiv preprint arXiv:2404.04572.
- [10] R. Verdecchia, J. Sallou, L. Cruz, A systematic review of green ai, Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery (2023) e1507.
- [11] D. Zhao, N. C. Frey, J. McDonald, M. Hubbell, D. Bestor, M. Jones, A. Prout, V. Gadepally, S. Samsi, A green (er) world for ai, in: 2022 IEEE International Parallel and Distributed Processing Symposium Workshops (IPDPSW), IEEE, 2022, pp. 742–750.
- [12] H. Zhang, Y. Huang, Y. Wen, J. Yin, K. Guan, Inferbench: Understanding deep learning inference serving with an automatic benchmarking system, arXiv preprint arXiv:2011.02327.
- [13] I. Kumara, R. Arts, D. Di Nucci, W. J. Van Den Heuvel, D. A.

Tamburri, Requirements and reference architecture for mlops: insights from industry, Authorea Preprints.

 H. Face, Model deployment considerations, last accessed October 28th, 2024 (2024).
 URL https://huggingface.co/learn/

URL https://huggingface.co/learn/ computer-vision-course/en/unit9/model_deployment

- [15] H. Face, Model optimization tools and frameworks, last accessed October 28th, 2024 (2024). URL https://huggingface.co/learn/ computer-vision-course/en/unit9/tools_and_frameworks
- [16] F. Durán, S. Martínez-Fernández, M. Martinez, P. Lago, Identifying architectural design decisions for achieving green ml serving, in: Proceedings of the IEEE/ACM 3rd International Conference on AI Engineering-Software Engineering for AI, 2024, pp. 18–23.
- [17] O. Runtime, Onnx runtime execution providers, https: //onnxruntime.ai/docs/execution-providers/, last accessed April 12th, 2024 (2024).
- [18] N. Alizadeh, F. Castor, Green ai: A preliminary empirical study on energy consumption in dl models across different runtime infrastructures, arXiv preprint arXiv:2402.13640.
- [19] A. Ziegler, E. Kalliamvakou, X. A. Li, A. Rice, D. Rifkin, S. Simister, G. Sittampalam, E. Aftandilian, Productivity assessment of neural code completion, in: Proceedings of the 6th ACM SIGPLAN International Symposium on Machine Programming, 2022, pp. 21–29.
- [20] F. F. Xu, U. Alon, G. Neubig, V. J. Hellendoorn, A systematic evaluation of large language models of code, in: Proceedings of the 6th ACM SIGPLAN International Symposium on Machine Programming, 2022, pp. 1–10.
- [21] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, L. Kaiser, I. Polosukhin, Attention is all you need, Advances in neural information processing systems 30.
- [22] N. Jiang, K. Liu, T. Lutellier, L. Tan, Impact of code language models on automated program repair, arXiv preprint arXiv:2302.05020.
- [23] M. Chen, J. Tworek, H. Jun, Q. Yuan, H. P. d. O. Pinto, J. Kaplan, H. Edwards, Y. Burda, N. Joseph, G. Brockman, et al., Evaluating large language models trained on code, arXiv preprint arXiv:2107.03374.
- [24] D. Zan, B. Chen, F. Zhang, D. Lu, B. Wu, B. Guan, W. Yongji, J.-G. Lou, Large language models meet nl2code: A survey, in: Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), 2023, pp. 7443–7464.
- [25] NVIDIA Corporation, End-to-end ai for nvidiabased pcs: Onnx runtime and optimization, https://developer.nvidia.com/blog/

end-to-end-ai-for-pcs-onnx-runtime-and-optimization/, last accessed April 12th, 2024 (2022).

- [26] O. Runtime, Onnx runtime, https://onnxruntime.ai/, last accessed July 17th, 2024 (2024).
- [27] S. Georgiou, M. Kechagia, T. Sharma, F. Sarro, Y. Zou, Green ai: Do deep learning frameworks have different costs?, in: Proceedings of the 44th International Conference on Software Engineering, 2022, pp. 1082–1094.
- [28] Intel, Openvino toolkit, https://software.intel.com/ openvino-toolkit, last accessed April 12th, 2024 (2019).
- [29] N. Lenherr, R. Pawlitzek, B. Michel, New universal sustainability metrics to assess edge intelligence, Sustainable Computing: Informatics and Systems 31 (2021) 100580.
- [30] Intel, Openvino toolkit. URL https://software.intel.com/openvino-toolkit
- [31] NVIDIA Corporation, Cuda, https://developer.nvidia.com/ cuda-zone, last accessed April 12th, 2024 (2024).
- [32] C.-Y. Hsieh, C.-L. Li, C.-K. Yeh, H. Nakhost, Y. Fujii, A. Ratner, R. Krishna, C.-Y. Lee, T. Pfister, Distilling step-by-step! outperforming larger language models with less training data and smaller model sizes, arXiv preprint arXiv:2305.02301.
- [33] S. Gunasekar, Y. Zhang, J. Aneja, C. C. T. Mendes, A. Del Giorno, S. Gopi, M. Javaheripi, P. Kauffmann, G. de Rosa, O. Saarikivi, et al., Textbooks are all you need, arXiv preprint arXiv:2306.11644.
- [34] T. Schick, H. Schütze, It's not just size that matters: Small language models are also few-shot learners, arXiv preprint arXiv:2009.07118.
- [35] J. Shi, Z. Yang, H. J. Kang, B. Xu, J. He, D. Lo, Greening large language models of code, in: Proceedings of the 46th International Conference on Software Engineering: Software Engineering in Society, 2024, pp. 142–153.
- [36] A. Svyatkovskiy, S. Lee, A. Hadjitofi, M. Riechert, J. V. Franco, M. Allamanis, Fast and memory-efficient neural code completion, in: 2021 IEEE/ACM 18th International Conference on Mining Software Repositories (MSR), IEEE, 2021, pp. 329–340.
- [37] S. A. Khowaja, P. Khuwaja, K. Dev, W. Wang, L. Nkenyereye, Chatgpt needs spade (sustainability, privacy, digital divide, and ethics) evaluation: A review, Cognitive Computation (2024) 1– 23.
- [38] Y. Zhou, X. Lin, X. Zhang, M. Wang, G. Jiang, H. Lu, Y. Wu, K. Zhang, Z. Yang, K. Wang, et al., On the opportunities of green computing: A survey, arXiv preprint arXiv:2311.00447.
- [39] R. Desislavov, F. Martínez-Plumed, J. Hernández-Orallo, Trends in ai inference energy consumption: Beyond the performance-vs-parameter laws of deep learning, Sustainable Computing: Informatics and Systems 38 (2023) 100857.
- [40] X. Zhang, Y. Wang, W. Shi, {pCAMP}: Performance compar-

ison of machine learning packages on the edges, in: USENIX workshop on hot topics in edge computing (HotEdge 18), 2018.

- [41] A. Koubaa, A. Ammar, A. Kanhouch, Y. AlHabashi, Cloud versus edge deployment strategies of real-time face recognition inference, IEEE Transactions on Network Science and Engineering 9 (1) (2021) 143–160.
- [42] R. M. Hampau, M. Kaptein, R. Van Emden, T. Rost, I. Malavolta, An empirical study on the performance and energy consumption of ai containerization strategies for computer-vision tasks on the edge, in: Proceedings of the International Conference on Evaluation and Assessment in Software Engineering 2022, 2022, pp. 50–59.
- [43] R. Klimiato, Utilizing deep learning models for image analysis at scale: comparison of deployment solutions, Ph.D. thesis, Kauno technologijos universitetas (2022).
- [44] D. Escribano Perez, Energy consumption of machine learning deployment in cloud providers, B.S. thesis, Universitat Politècnica de Catalunya (2023).
- [45] Z. Yang, J. Shi, P. Devanbu, D. Lo, Ecosystem of large language models for code, arXiv preprint arXiv:2405.16746.
- [46] T. Vartziotis, I. Dellatolas, G. Dasoulas, M. Schmidt, F. Schneider, T. Hoffmann, S. Kotsopoulos, M. Keckeisen, Learn to code sustainably: An empirical study on green code generation, in: Proceedings of the 1st International Workshop on Large Language Models for Code, 2024, pp. 30–37.
- [47] S. J. Warnett, U. Zdun, Architectural design decisions for machine learning deployment, in: 2022 IEEE 19th International Conference on Software Architecture (ICSA), IEEE, 2022, pp. 90–100.
- [48] S. C. Jepsen, A. Ø. Nielsen, M. B. Kjærgaard, Architecting machine learning systems: Which parts are the architect's pain?, in: 2024 IEEE 21st International Conference on Software Architecture Companion (ICSA-C), IEEE, 2024, pp. 303–306.
- [49] V. R. Basili, G. Caldiera, H. D. Rombach, The goal question metric approach. encyclopedia of software engineering-2 volume set, Copyright by John Wiley & Sons, Inc (1994) 528–532.
- [50] J. Castaño, S. Martínez-Fernández, X. Franch, Lessons learned from mining the hugging face repository, in: Proceedings of the 1st IEEE/ACM International Workshop on Methodological Issues with Empirical Studies in Software Engineering, 2024, pp. 1–6.
- [51] D. Fried, A. Aghajanyan, J. Lin, S. Wang, E. Wallace, F. Shi, R. Zhong, W.-t. Yih, L. Zettlemoyer, M. Lewis, Incoder: A generative model for code infilling and synthesis, arXiv preprint arXiv:2204.05999.
- [52] M. Bavarian, H. Jun, N. Tezak, J. Schulman, C. McLeavey, J. Tworek, M. Chen, Efficient training of language models to fill in the middle, arXiv preprint arXiv:2207.14255.

- [53] C. Wohlin, P. Runeson, M. Höst, M. C. Ohlsson, B. Regnell, A. Wesslén, et al., Experimentation in software engineering, Vol. 236, Springer, 2012.
- [54] A. Jedlitschka, M. Ciolkowski, D. Pfahl, Reporting experiments in software engineering, Guide to advanced empirical software engineering (2008) 201–228.
- [55] L. E. Lwakatare, I. Crnkovic, J. Bosch, Devops for ai-challenges in development of ai-enabled applications, in: 2020 international conference on software, telecommunications and computer networks (SoftCOM), IEEE, 2020, pp. 1–6.
- [56] R. C. Castanyer, S. Martínez-Fernández, X. Franch, Which design decisions in ai-enabled mobile applications contribute to greener ai?, Empirical Software Engineering 29 (1) (2024) 2.
- [57] Intel, Running inference with openvino, last accessed July 22th, 2024.

URL https://docs.openvino.ai/2024/openvino-workflow/ running-inference.html

- [58] A. Guldner, R. Bender, C. Calero, G. S. Fernando, M. Funke, J. Gröger, L. M. Hilty, J. Hörnschemeyer, G.-D. Hoffmann, D. Junger, et al., Development and evaluation of a reference measurement model for assessing the resource and energy efficiency of software products and components—green software measurement model (gsmm), Future Generation Computer Systems.
- [59] T. Wolf, L. Debut, V. Sanh, J. Chaumond, C. Delangue, A. Moi, P. Cistac, T. Rault, R. Louf, M. Funtowicz, et al., Transformers: State-of-the-art natural language processing, in: Proceedings of the 2020 conference on empirical methods in natural language processing: system demonstrations, 2020, pp. 38–45.
- [60] Y. Xu, S. J. Martínez Fernández, M.-S. Martínez Martínez, J. Franch Gutiérrez, Energy efficiency of training neural network architectures: an empirical study, in: Proceedings of the 56th Annual Hawaii International Conference on System Sciences: January 3-6, 2023, Hyatt Regency Maui, University Of Hawaii, 2023, pp. 781–790.
- [61] M. Martinez, S. Martínez-Fernández, X. Franch, Energy consumption of automated program repair, in: Proceedings of the 2024 IEEE/ACM 46th International Conference on Software Engineering: Companion Proceedings, 2024, pp. 358–359.
- [62] J. Sallou, L. Cruz, T. Durieux, Energibridge: Empowering software sustainability through cross-platform energy measurement, arXiv preprint arXiv:2312.13897.
- [63] O. Bekhelifi, N.-E. Berrached, On optimizing deep neural networks inference on cpus for brain-computer interfaces using inference engines, in: 2024 IEEE International Symposium on Circuits and Systems (ISCAS), IEEE, 2024, pp. 1–5.
- [64] M. Sever, S. Öğüt, A performance study depending on execution times of various frameworks in machine learning inference, in:

2021 15th Turkish National Software Engineering Symposium (UYMS), IEEE, 2021, pp. 1–5.

- [65] J. Singh, B. Adams, A. E. Hassan, On the impact of blackbox deployment strategies for edge ai on latency and model performance, arXiv preprint arXiv:2403.17154.
- [66] N. P. LOPES, Torchy: A tracing jit compiler for pytorch (extended version).
- [67] J. Ansel, E. Yang, H. He, N. Gimelshein, A. Jain, M. Voznesensky, B. Bao, P. Bell, D. Berard, E. Burovski, et al., Pytorch 2: Faster machine learning through dynamic python bytecode transformation and graph compilation, in: Proceedings of the 29th ACM International Conference on Architectural Support for Programming Languages and Operating Systems, Volume 2, 2024, pp. 929–947.
- [68] PyTorch, Torchscript, last accessed July 30th, 2024 (2023). URL https://pytorch.org/docs/stable/jit.html
- [69] PyTorch Community, Why torchscript module does not take less gpu memory than pytorch model?, last accessed July 30th, 2024 (2022).

URL https://discuss.pytorch.org/t/ why-torchscript-module-does-not-take-less-gpu-memory-than-pytor 157560/4

- [70] Z. Chen, A. Kerr, R. Cai, J. Kosaian, H. Wu, Y. Ding, Y. Xie, Evt: Accelerating deep learning training with epilogue visitor tree, in: Proceedings of the 29th ACM International Conference on Architectural Support for Programming Languages and Operating Systems, Volume 3, 2024, pp. 301–316.
- [71] J. Kaplan, S. McCandlish, T. Henighan, T. B. Brown, B. Chess, R. Child, S. Gray, A. Radford, J. Wu, D. Amodei, Scaling laws for neural language models, arXiv preprint arXiv:2001.08361.
- [72] Z. Zhou, X. Ning, K. Hong, T. Fu, J. Xu, S. Li, Y. Lou, L. Wang, Z. Yuan, X. Li, et al., A survey on efficient inference for large language models, arXiv preprint arXiv:2404.14294.
- [73] S. Martínez-Fernández, Environmental sustainability of machine learning systems: Reducing the carbon impact of their lifecycle process, in: International Conference on Product-Focused Software Process Improvement, Springer, 2024, pp. 3– 7.
- [74] Y. Han, G. Huang, S. Song, L. Yang, H. Wang, Y. Wang, Dynamic neural networks: A survey, IEEE Transactions on Pattern Analysis and Machine Intelligence 44 (11) (2021) 7436– 7456.
- [75] W. Wang, W. Chen, Y. Luo, Y. Long, Z. Lin, L. Zhang, B. Lin, D. Cai, X. He, Model compression and efficient inference for large language models: A survey, arXiv preprint arXiv:2402.09748.
- [76] C. E. Jimenez, J. Yang, A. Wettig, S. Yao, K. Pei, O. Press, K. Narasimhan, Swe-bench: Can language models resolve real-

world github issues?, arXiv preprint arXiv:2310.06770.

[77] European Union, Artificial intelligence act., last accessed November, 2024 (2024).

URL https://eur-lex.europa.eu/eli/reg/2024/1689/oj