# Enhancing Large-scale UAV Route Planing with Global and Local Features via Reinforcement Graph Fusion

1<sup>st</sup> Tao Zhou School of Informatics Xiamen University Xiamen, China taozhou@stu.xmu.edu.cn

4<sup>th</sup> Jiajing Lin School of Informatics Xiamen University Xiamen, China 31520231154298@stu.xmu.edu.cn 2<sup>nd</sup> Kai Ye \* School of Informatics Xiamen University Xiamen, China yekai@stu.xmu.edu.cn

> 5<sup>th</sup> Dejun Xu School of Informatics Xiamen University Xiamen, China xudejun@stu.xmu.edu.cn

3<sup>rd</sup> Zeyu Shi Marine Design and Research Institute of China Shanghai, China shizeyu@maric.com.cn

> 6<sup>th</sup> Min Jiang School of Informatics Xiamen University Xiamen, China minjian@xmu.edu.cn

Abstract-Numerous remarkable advancements have been made in accuracy, speed, and parallelism for solving the Unmanned Aerial Vehicle Route Planing (UAVRP). However, existing UAVRP solvers face challenges when attempting to scale effectively and efficiently for larger instances. In this paper, we present a generalization framework that enables current UAVRP solvers to robustly extend their capabilities to larger instances, accommodating up to 10,000 points, using widely recognized test sets. The UAVRP under a large number of patrol points is a typical large-scale TSP problem.Our proposed framework comprises three distinct steps. Firstly, we employ Delaunay triangulation to extract subgraphs from large instances while preserving global features. Secondly, we utilize an embedded TSP solver to obtain sub-results, followed by graph fusion. Finally, we implement a decoding strategy customizable to the user's requirements, resulting in high-quality solutions, complemented by a warming-up process for the heatmap. To demonstrate the flexibility of our approach, we integrate two representative TSP solvers into our framework and conduct a comprehensive comparative analysis against existing algorithms using large TSP benchmark datasets. The results unequivocally demonstrate that our framework efficiently scales existing TSP solvers to handle large instances and consistently outperforms state-of-the-art (SOTA) methods. Furthermore, since our proposed framework does not necessitate additional training or fine-tuning, we believe that its generality can significantly advance research on end-toend UAVRP solvers, enabling the application of a broader range of methods to real-world scenarios.

Index Terms—UAV, Route Planning, TSP, Large-scale, Reinforcement Graph Fusion

#### I. INTRODUCTION

With the development of Unmanned Aerial Vehicle (UAV), using UAV for patrolling has become an emerging and important security measure. Planning a reasonable patrol route

This work was supported by the National Natural Science Foundation of China under Grant 62276222.

\*Corresponding author: Kai Ye.

is key to improving the efficiency and effectiveness of the patrol. Our approach is to design a path planning algorithm for UAV to enhance patrol efficiency. The Unmanned Aerial Vehicle Route Planing (UAVRP) is a optimization problem wherein a UAV must visit a specific set of sites exactly once and return to the starting point, aiming to minimize the overall travel distance. The primary hurdle in UAVRP's resolution lies in the extensive search space that emerges when dealing with a substantial number of sites, denoted as n. The UAVRP under a large number of patrol sites is a typical Large-Scale Travelling Salesman Problem (LSTSP), we define a TSP instance that requires visiting more than 500 sites as an LSTSP in this paper. Despite its inherent theoretical complexity, the LSTSP finds numerous practical applications across various domains such as drone delivery, transport, genome sequencing, and circuit board design [1]-[6].

Over the years, the operations research community has proposed various methods to tackle the UAVRP. Among these approaches, Concorde [7] stands out as a relatively powerful and extensively utilized method in real-world scenarios. However, when confronted with UAVRP problems involving tens of thousands of dimensions, Concorde falls short in producing accurate results within a reasonable timeframe (within 8 CPU hours). To address this limitation, numerous heuristic algorithms have been developed, including LKH3 [8] and OR-Tools. Nevertheless, when dealing with the LSTSP, these algorithms suffer from two key drawbacks. Firstly, they are still time-consuming. Secondly, their iterative search procedures yield unstable results and necessitate the manual development of heuristic rules.

To tackle the challenges of time-consuming and unstable solutions, a series of learning-based methods have been proposed [9]–[11]. Such methods are trained on huge volumes of

data to obtain features of instances from different paradigms. These methods are trained on extensive datasets to extract features of instances from various paradigms, enabling them to handle previously unseen instances with fast inference speed and search stability, resulting in excellent performance on the LSTSP. [12]

Learning-based TSP approaches fall into one-step and twostep categories based on solution steps.

One-step methods, including construction-based and iterative, find solutions directly without intermediates. They perform well on small TSPs but have difficulty scaling to LSTSPs efficiently and stably [13], [14].

Two-step methods generate intermediates like heatmaps indicating edge probabilities in the optimal solution and then search these to find the final solution. [15], for example, uses a supervised model for sub-heatmaps and Monte Carlo tree search [16]. While this generalizes to 10,000-dimensional LSTSPs and maintains competitive accuracy within a reasonable time, the divide-and-conquer approach can lose global features during sub-graph extraction, leaving room for improvement.

There's a notable gap in generalizing from TSP to LSTSP, with algorithms facing high computational costs and accuracy loss [17]. This gap means many promising TSP solvers are underutilized in realistic, large-scale scenarios.

To overcome these challenges, we propose a framework for TSP solvers generalization without training, efficiently extending existing TSP solvers to handle LSTSP instances and achieving results comparable to state-of-the-art methods. The proposed Delaunay Triangulation-based TSP-solver Generalization Framework (DTTGF) operates as depicted in Figure 1 for instances of the LSTSP. For an LSTSP instance, our framework first triangulates it, enabling subgraph extraction to preserve global features. The extracted sub-graphs are then solved by the embedded TSP solver to obtain sub-products, such as sub-solutions or sub-heatmaps. These sub-products are merged to generate the heatmap of the original instance. To improve sub-graph fusion, we propose a pseudo-reinforcement learning based warm-up mechanism that removes misleading edges while correcting the heatmap. Finally, the generated heatmap is searched using widely adopted search methods to obtain the final solution. Our divide-and-conquer based framework ensures adaptability and reliable generalization for all existing TSP solvers.

The contributions are summarized as follows:

- We introduce a novel approach based on triangulation for dividing subgraphs. This method ensures that global features within the subgraphs are preserved while maintaining the overall structure intact.
- We propose an innovative warm-up strategy based on pseudo-reinforcement learning. This strategy enhances search outcomes while incurring an acceptable trade-off in terms of time efficiency.
- We develop a unified framework for generating subgraphs. This framework enables the integration of diverse solvers rooted in reinforcement learning and supervised

learning methodologies. The resultant solvers can seamlessly adapt to instances of varying sizes.

The work addresses the need for scalable solutions for both current and potential future TSP solvers. This adaptability ensures that existing small-scale accurate TSP solvers can effectively extend their applicability to real-world scenarios. You can find our code and appendix on GitHub above:https://github.com/Calomiya/DTTGF.git.

## II. RELATED WORKS

The TSP problem, being a long-standing NP-hard challenge, has garnered a substantial body of related research. Given the primary focus of our paper on designing a framework for learning-based approaches, we delve into the intricate details of these approaches in the subsequent sections, rather than attempting to encompass all domains. Moreover, the landscape boasts several exceptional algorithms in diverse fields, including evolutionary computation. Those interested in non-learning methods can delve deeper into these alternatives in [18]–[21].

## A. Learning-based Methods

We classify learning-based strategies into one-stage and two-stage methods, contingent on the progression stages required to achieve a solution and the necessity for intermediate product generation.

1) One-stage Methods: Point Networks [22], [23] pioneered an end-to-end TSP approach using neural attention to handle variable output sizes, selecting inputs as outputs. [10] improved this with an attention layer, outperforming pointer networks, and used REINFORCE for model training with a greedy rollout baseline. POMO [24] explored REINFORCE for guiding TSP solutions towards multiple optima [25]. [26] proposed a direct TSP solution approach, avoiding costly search processes, offering a fast solution but challenging to generalize to Large-Scale TSP without extensive fine-tuning or retraining.

2) Two-stage Methods: [15] introduces a two-stage learning-based TSP solver: generating an intermediate heatmap followed by solution search. Using divide-and-conquer, it breaks down LSTSP into smaller instances, solves sub-heatmaps, and merges results, then applies MCTS for performance comparable to LKH3 on 10,000-point instances. The approach is adaptable and scalable despite the additional search phase.

DIMES [27] follows this model, offering two-stage processing with heatmap generation and MCTS for improved accuracy. It also creates a continuous space for parameterizing solution distributions, which stabilizes REINFORCE training and enables parallel sampling for fine-tuning.

It is important to underscore that the aforementioned DIMES [27], H-TSP [26] and Att-GCN [15] demonstrate the capacity to generalize to LSTSP. However, the scope of generalization for these three solutions remains confined to their respective models and does not extend to other pre-existing TSP solvers.



Fig. 1: Pipeline of the proposed approach. Step 1: perform Delaunay Triangulation(DT) on the current instance. Step 2: sampling and solving the sub-graph on DT results. Step 3: merging sub-solutions (one-stage solver) or sub-heatmaps (two-stage solver) to obtain a global heat map. Step 4: warming up heat map and search for the global optimal solutions.

### **III.** METHODS

#### A. Preliminaries

1) Problem Definition: Our proposed framework concentrates on the Two-Dimensional Euclidean Traveling Salesman Problem (2D Euclidean TSP). This problem can be represented as an undirected graph G(V, E), where V(|V| = n) signifies the set of vertices, referred to as cities in the context of TSP, and E represents the set of edges. For consistency with the majority of learning-based methodologies, we presume that all vertices in V are uniformly distributed within a unit square of side length 1. This translates to the coordinates  $(x_i, y_i)$  of each vertex adhering to the condition  $x_i \in [0, 1], y_i \in [0, 1]$ . The Euclidean distance between cities is denoted by  $d_{ij}$ , and an element  $p_{ij}$  within the heatmap P for graph G signifies the probability of edge (i, j) being present in the optimal solution.

2) Delaunay Triangulated Graph: Delaunay Triangulation(DT) is the fundamental method of study in algebraic topology. In the case of a surface, we divide the surface into pieces that satisfy the following conditions:

- Each piece is a curved triangle;
- Any two such curved triangles on the surface either do not intersect or intersect on exactly one common side (not two or more sides at the same time).

The definition of DT requires it to have the following characteristics:

• The fact that the outer circle of every Delaunay triangle contains no other point in its area is called the empty outer circle property of Delaunay triangles, and this prop-

erty has been used as a criterion for creating Delaunay triangles.

• Another property is the maximum minimum angle property: the minimum angle of the six interior angles of a convex quadrilateral formed by the diagonals of any two adjacent triangles does not increase when they are exchanged.

Several heuristic TSP solvers [28]–[30] have empirically demonstrated that the optimal solution of a TSP is highly likely to reside along the edges delimited by the DT. We incorporate this attribute into our learning-based methodology to uphold global features throughout the process of sub-graph extraction.

## B. The Proposed Framework

The DTTGF process encompasses 7 primary steps as depicted in Figure 1. Initially, the Delaunay Triangulation (DT) is executed on the instances, followed by the extraction of subgraphs based on the DT outcomes. The derived sub-graphs are then addressed by the integrated TSP solver to yield subresults, encompassing sub-heatmaps or sub-solutions. Subsequently, these sub-results amalgamate to construct a global heatmap, which is subsequently processed warming-up strategy to generate the ultimate heatmap. The final heatmap undergoes a search process utilizing the chosen search technique, culminating in the production of the definitive solution.

In this paper, as a framework-oriented study, we integrate the most distinct S+2-OPT (Sampling Decoder+2-OPT) [10], [31] and MCTS (Monte Carlo Tree Search) [15] approaches into the proposed DTTGF during the experimental phase to showcase the heatmap's performance.

## Algorithm 1 Procedure of DTTGF

**Require:** TSP Instance,  $V = \{v_1, v_2, ..., v_N\}$ ; Selected TSP-solver, *S*  **Ensure:** Solution route,  $\tau = \{\tau_1, \tau_1, ..., \tau_N\}$ ; 1:  $V_D \leftarrow DelaunayTriangulation(V)$ ; 2:  $V_{sub} \leftarrow GraphSampling(V_D)$ ; 3:  $\{P_{sub}^1, P_{sub}^2, ..., P_{sub}^M\} \leftarrow SubGraphSolving(V_{sub}, S)$ ; 4:  $P \leftarrow GraphMerging(\{P_{sub}^1, P_{sub}^2, ..., P_{sub}^M\})$ ; 5:  $P_W \leftarrow WarmingUp(P)$ ; 6:  $\tau \leftarrow TourSearching(P_W, V)$ ; 7: **return**  $\tau$ ;

## C. Graph Sampling

For LSTSP, the divide-and-conquer strategy is common. [15] uses k-nearest neighbors for sub-graph decomposition to reduce complexity, but this risks losing global features. This is crucial in TSP, as sub-graph solutions must align with the overall solution. Our DT-centric approach ensures effective sub-graph extraction while preserving global properties.

Instances are processed with DT before sub-graph extraction. The DT result is represented in an adjacency matrix D, where  $D_{ij} = 1$  for DT edges and  $D_{ij} = 0$  otherwise. To cover the entire graph evenly, DTTGF uses a matrix O of size n, incrementing  $O_i$  each time node i is selected for a sub-graph. The framework starts with the node i having the lowest  $O_i$ and explores adjacent nodes using a depth-first search, sorting them by distance  $d_{ik}$ .

Starting with the first node  $k_1$  from the sorted list, it is included in the sub-graph, and  $O_{k1}$  is incremented. The process continues, adding connected nodes from D and selecting the closest to extend the sub-graph, until the node count is met. Iteration stops when sub-graphs meet the criteria.

#### D. Sub-graph Solving

The difference between one-stage and two-stage solvers is the generation of an intermediate heatmap. Learning-based approaches share fast search speeds through parallelism or strong forward processing, handling many small instances quickly. However, they struggle with varying instance sizes in real-world scenarios, where parallelism is less effective. Despite this, it forms the basis for our framework, leveraging fixed sub-graph sizes and fast search times to manage many sub-graphs efficiently, meeting real-world time needs. This paper includes representative methods in DTTGF for both stages. The one-stage solver provides sub-graph solutions, and the two-stage solver generates a heatmap, with the following section detailing how both are integrated into a global heatmap.

## E. Graph Merging

1) One-stage Solver: For a one-stage solver, each subgraph outputs a tour T, and the probability of each edge (i, j)appearing in the optimal solution is as follows

$$P_{ij} = \frac{\sum_{l=1}^{l} T_l(i,j)}{S_{ij}}$$
(1)

where I represents the count of sub-graphs, while  $T_l(i, j)$ indicates the presence of edge (i, j) within the solutions  $T_l$  of sub-graph l. Meanwhile,  $S_{ij}$  signifies the aggregate instances of edge (i, j) being chosen across all sub-graphs. As such,  $P_{ij}$ denotes the actual frequency of edge (i, j) within the solutions of all sub-graphs, calculated by dividing the occurrences of its selection in a sub-graph.

2) Two-stage Solver: The two-stage solver can also conduct dual search stages to obtain the final solution for the subgraph and use equation (1) to compute the heatmap of the subgraph, similar to the one-stage solver. However, the two-stage approach inherently benefits from the divide-and-conquer concept. This approach involves generating intermediate heatmaps itself, and if these intermediate heatmaps can be directly employed, the efficiency of producing global sub-graphs can be enhanced, mitigating the computational expense of the second search stage.

The corresponding heatmap for the two-stage sub-graphs is formulated as follows:

$$P_{ij} = \frac{\sum_{l=1}^{I} P_l(i,j)}{S_{ij}}$$
(2)

where  $P_l(i, j)$  denotes the value of edge (i, j) within subgraph l on the sub-heatmap.

The noteworthy distinction from the one-stage solver lies in the fact that  $T_l$  exclusively contains information about the sub-solutions, while  $P_l$  provided by the two-stage solver encompasses the probabilities of all sub-graph edges appearing in the optimal solution. The proposed framework adeptly maps the outcomes of TSP solvers for sub-graphs onto the global heatmap for both scenarios.

It is crucial to note that techniques centered around subgraph partitioning and fusion can potentially lead to the loss of global characteristics. Specifically, edges with elevated Pvalues might perform well within individual sub-graphs, or they could be selected only a relatively limited number of times and incidentally emerge in the optimal solution of those sub-graphs. However, the latter case involves edges that are unlikely to be superior within the global graph. To address this, the paper introduces Delaunay Triangulation (DT) as a filter for the amalgamated heatmap. As mentioned earlier, prior research has illustrated a pronounced correlation between the optimal TSP solution and the DT delineation outcome, indicating that edges in the optimal solution tend to be encompassed by the DT result [32]. DTTGF capitalizes on this insight, and for the generated heatmap P, the P values of edges (i, j) not present in the DT result are set to 0. This adjustment is applied as follows:

$$P_{ij} = 0, \ \forall (i,j) \notin \mathrm{DT}$$
 (3)

After applying the filter, the proposed framework acquires the fused heatmap corresponding to the original instance.

## F. The Warming-up Strategy

While DT as prior knowledge can eliminate certain nonpotential edges, two issues still remain. Firstly, some potentially valuable edges that are not part of the DT result could be removed during the filtering. Secondly, even the edges within the DT result might appear promising on a local scale but mislead on a global level.

Particularly, when integrating a one-stage solver, it characterizes only the edges of the optimal solution for each subgraph. This results in a sparse heatmap after fusion, where each edge's information is crucial. In contrast, a two-stage solver provides a subgraph heatmap for each subgraph, containing information about the majority of edges in the subgraph. The fused heatmap it produces is relatively dense and can partially mitigate this issue.

To address these challenges, we introduce a warm-up strategy based on pseudo-reinforcement learning, primarily tailored to one-stage solvers. During subgraph fusion, the heatmap is pruned to retain only edges with a potential to appear in the optimal solution. [33], [34] Two types of edges require special attention: those with longer distances  $d_{ij}$  and those with higher values of  $P_{ij}$ . In TSP, the final performance often hinges on the selection of longer edges in the optimal solution, and edges with higher  $P_{ij}$  values have a greater likelihood of being selected. Thus, we define fitness values as follows:

$$A_{ij} = P_{ij} \times d_{ij} \tag{4}$$

The warm-up process involves iterations, following this sequence. The initial solution  $T_{ori}$  is derived by rapidly solving the heatmap using a sampling decoder [10] followed by 2-OPT improvements (referred to as S+2-opt). Note the current solution  $T_{ori}$  as the baseline, i.e.  $T_b$ . For each iteration, we select the edge (i, j) with the largest current  $A_{ij}$ , modify its  $P_{ij}$  to zero, and apply S+2-opt to obtain the improved solution  $T_{del}$ . If  $T_{del}$  outperforms the baseline  $T_b$  (obtained from  $T_{ori}$ ), P is updated to  $P_{del}$  after deleting the edge, and back-propagation is performed. Let the back-propagation formula be

$$P_{ij} = P_{ij} + \alpha \times \beta \left( e^{\frac{D(T_b) - D(T_{del})}{D(T_d)}} - 1 \right)$$
  

$$\alpha = 0, \text{ if } (i, j) \in (T_b \cap T_{del})$$
  

$$\alpha = 1, \text{ if } (i, j) \in T_b$$
  

$$\alpha = -1, \text{ if } (i, j) \in T_{del}$$
(5)

where  $D(T_b)$  denotes the length of the tour consisting of solving  $T_b$ ,  $D(T_{del})$  denotes the length of the tour consisting of solving  $T_{del}$ ,  $\beta$  is the learning rate, and the value of  $\alpha$ depends on whether the edge (i, j) belongs to  $T_b$  or  $T_{del}$  or not. After back-propagation, if  $T_{del}$  is better than  $T_b$ ,  $T_b$  is updated to  $T_{del}$ . Once the iteration requirements are met, the process concludes, and the final heatmap is output.

The proposed warm-up module selectively removes nonpotential edges from focus in the heatmap. Moreover, potential edges not in the DT results but filtered during fusion can enhance their *P*-value via back-propagation, increasing their chances of selection in the subsequent search process.

## **IV. EXPERIMENTS**

Existing TSPsolver for UAVRP under a large number of sites, which is modeled as LSTSP. To validate the efficacy

of DTTGF, we conducted evaluations using three datasets generated by [35]. These datasets comprise 128 instances of 500 points, 128 instances of 1000 points, and 16 instances of 10000 points. This dataset selection ensures comparability with many current works on learning-based TSP solvers, which commonly use this dataset for training and validation. All experimental results were acquired using machines equipped with one RTX 1080 and an Intel(R) Xeon(R) Gold 5118 CPU @ 2.30GHz (featuring 8 cores), and the results align with those of [27].

#### A. Baselines

The baselines employed in the experiments are of two types: the traditional methods and the learning-base methods.

Traditional methods: we have Concorde [36], a classic TSP accurate solver, and Gurobi<sup>1</sup>, a widely used industrial combinatorial optimization problem solver. Also included is LKH-3 [8], the classic heuristic TSP solver, and Farthest Insertion, a heuristic solver for most combinatorial optimization problems.

Learning-based methods:EAN [37] (CPAIOR2018) is a re-engineered LSTM neural network framework that introduced 2-OPT assisted search. AM [10] (ICLR2019) brought Attention Mechanisms to TSP solving. GCN [38] focuses on constructing and solving TSP representations with graph neural networks. POMO+EAS [39] (ICLR2022) improved training speed and extended the existing TSP solver with a new combined search strategy. Att-GCN (AAAI2021) solves TSPs using supervised learning and reinforcement learning. DIMES (NeurIPS2022) provides a new spatial representation and meta-learning framework for solving TSP instances of different sizes. Lastly, H-TSP (AAAI2023) [40] jointly trains upper and lower layer solutions that can directly generate solutions for a given TSP instance without relying on any time-consuming search process.

#### B. Comparative Study

In our framework-based study, Att-GCN and POMO were integrated as the experimental TSP solvers. Att-GCN requires a pre-trained GCN model for heatmap generation, representing a two-stage learning approach. POMO excels in smaller TSP instances and is included as a one-stage solver in our framework.

Table I shows DTTGF's advantages over other learningbased methods in scheduling and timing, with all baseline results from [27] except Att-GCN's. Our framework is easily integrated by embedding a TSP solver without extra training. Using MCTS, DTTGF outperforms Att-GCN and DIMES. With S+2-OPT, a fast search method for real-time tasks, DTTGF's accuracy drops but time is reduced. DTTGF+S+2-OPT even surpasses MCTS-based methods in accuracy, including for 1000-point datasets.

A key issue is POMO's scaling challenges with Large-Scale TSPs (LSTSPs). The POMO+EAS benchmark struggled with TSP-1000 and TSP-10000 within 8 hours. However, integrated

<sup>&</sup>lt;sup>1</sup>See https://www.gurobi.com

TABLE I: Results of DTTGF w.r.t. existing baselines, tested on TSP-500, TSP-1000 and TSP-10000.

		TSP-500			TSP-10	00	TSP-10000			
Method	Type	Length↓	Drop↓	Time↓	Length↓	Drop↓	Time↓	Length↓	Drop↓	Time↓
Concorde	OR(exact)	16.55*	_	37.66m	23.12*	_	6.65h	N/A	N/A	N/A
Gurobi	OR(exact)	16.55	0.00%	43.63h	N/A	N/A	N/A	N/A	N/A	N/A
LKH-3	OR	16.55	0.00%	46.28m	23.12	0.00%	2.57h	71.77*	_	8.8h
Farthest Insertion	OR	18.30	0.00%	Os	25.72	11.25%	0s	80.59	12.29%	6s
EAN(CPAIOR2018)	RL+S	28.63	73.03%	20.18m	50.30	117.59%	37.07m	N/A	N/A	N/A
EAN	RL+S+2-OPT	23.75	43.57%	57.76m	47.73	106.46%	5.39h	N/A	N/A	N/A
AM(ICLR2019)	RL+S	22.64	36.84%	15.64m	42.80	85.15%	63.97m	431.58	501.27%	12.63m
AM	RL+G	20.02	20.99%	1.51m	31.15	34.75%	3.18m	141.68	97.39%	5.99m
AM	RL+BS	19.53	18.03%	21.99m	29.90	29.23%	1.64h	129.4	80.28%	1.81h
GCN	SL+G	29.72	79.61%	6.67m	48.62	110.29%	28.52m	N/A	N/A	N/A
GCN	SL+BS	30.37	83.55%	38.02m	51.26	121.73%	51.67m	N/A	N/A	N/A
POMO+EAS-Emb(ICLR2022)	RL+AS	19.24	16.25%	12.80h	N/A	N/A	N/A	N/A	N/A	N/A
POMO+EAS-Lay	RL+AS	19.35	16.92%	16.19h	N/A	N/A	N/A	N/A	N/A	N/A
POMO+EAS-Tab	RL+AS	24.54	48.22%	11.61h	49.56	114.36%	63.45h	N/A	N/A	N/A
Att-GCN(AAAI2021)	SL+MCTS	16.97	2.54%	2.20m	23.86	3.22%	4.10m	74.93	4.39%	21.49m
DIMES(NeurIPS2022)	RL+S	18.84	13.84%	1.06m	26.36	14.01%	2.38m	85.75	19.48%	4.80m
DIMES	RL+AS+S	17.8	7.55%	2.11h	24.89	7.70%	4.53h	80.42	12.05%	3.12h
DIMES	RL+MCTS	16.87	1.93%	2.92m	23.73	2.64%	6.87m	74.63	3.98%	29.83m
DIMES	RL+AS+MCTS	16.84	1.76%	2.15h	23.69	2.46%	4.62h	74.06	3.19%	3.57h
H-TSP(AAAI2023)	RL	17.59	6.28%	27.35s	24.66	6.66%	56.12s	77.74	8.31%	57.48s
DTTGF+Att-GCN(ours)	SL+S+2-OPT	17.19	3.84%	1.12m	24.01	3.85%	2.90m	76.24	6.23%	11.29m
	SL+WU+S+2-OPT	16.96	2.47%	1.12m+2.70m	23.83	3.05%	2.90m+15.44m	75.09	4.63%	11.29m+1.58h
	SL+MCTS	16.74	1.13%	2.30m	23.45	1.43%	4.15m	73.57	2.51%	24.74m
	SL+WU+MCTS	16.71	0.99%	2.30m+2.70m	23.44	1.39%	4.15m+15.44m	73.48	2.38%	24.74m+1.58h
DTTGF+POMO(ours)	RL+S+2-OPT	17.17	3.74%	2.86m	24.08	4.14%	5.37m	78.01	8.69%	13.55m
	RL+WU+S+2-OPT	1.03	2.50%	2.86m+2.70m	23.87	3.23%	5.37m+15.44m	75.87	5.71%	13.55m+1.58h
	RL+MCTS	24.77	9.40%	4.14m	26.82	16.01%	6.34m	107.44	49.70%	23.90m
	RL+WU+MCTS	16.82	1.66%	4.14m+2.70m	23.70	2.50%	6.34m+15.44m	73.56	2.49%	23.90m+1.58h

Where the symbol \* represents the benchmark algorithm, while "length" indicates the average solution length across all instances.

<sup>2</sup> "Time" reflects the cumulative computational duration for all instances, and "drop" signifies the deviation from the benchmark.
<sup>3</sup> The notation "WU" designates the warm-up module, with the supplementary time incorporated in methods employing the warm-up module representing the duration required for

<sup>4</sup> The decoding scheme in each method (if applicable) is further specified as Greedy Decoding (G), Sampling (S), Beam Search (BS) and Monte Carlo Tree Search (MCTS).

TABLE II: Results of DTTGF(embedding AM and GCM) w.r.t. AM and GCN, tested on TSP-500, TSP-1000 and TSP-10000.

Method	Туре	1 Drop↓	SP-500 Time↓	7 Drop↓	TSP-1000 Time↓	TS Drop↓	P-10000 Time↓
AM	RL+S	36.84%	15.64m	85.15%	63.97m	501.27%	12.63m
AM	RL+G	20.99%	1.51m	34.75%	3.18m	97.39%	5.99m
AM	RL+BS	18.03%	21.99m	29.23%	1.64h	80.28%	1.81h
DTTGF+AM(ours)	RL+S+2-OPT	5.60%	4.75m	5.62%	10.63m	12.40%	1.03h
	RL+WU+S+2-OPT	3.98%	4.75m+2.70m	4.59%	10.63m+15.44m	11.04%	1.03h+1.58h
	RL+MCTS	12.69%	6.11m	20.74%	11.83m	54.26%	51.05m
	RL+WU+MCTS	2.68%	6.11m+2.70m	4.28%	11.83m+15.44m	27.55%	51.05m+1.58h
GCN	SL+G	79.61%	6.67m	110.29%	28.52m	N/A	N/A
GCN	SL+BS	83.55%	38.02m	121.73%	51.67m	N/A	N/A
DTTGF+GCN(ours)	SL+S+2-OPT	6.44%	1.42m	6.45%	3.16m	14.93%	1.15h
	SL+WU+S+2-OPT	5.01%	1.42m+2.70m	5.57%	3.16m+15.44m	11.05%	1.15h+1.58h
	SL+MCTS	1.50%	3.38m	2.13%	5.37m	3.64%	1.00h
	SL+WU+MCTS	2.10%	3.38m+2.70m	2.64%	5.37m+15.44m	3.84%	1.00h+1.58h

with DTTGF, POMO outperforms specialized LSTSP solvers like DIMES across all datasets. Details on the framework's generalizability and reliability are in the ablation study.

### C. Ablation Study

Ablation results in Table I show the proposed assumptions' validity against DT. Att-GCN+DTTGF (without WU) differs from Att-GCN in using DT-based sampling and fusion. DTTGF surpasses Att-GCN in accuracy with MCTS decoding, suggesting DT's enhancement potential.

DTTGF vs. DTTGF(warm-up) shows warm-up boosts accuracy, especially for one-stage methods. With MCTS, DTTGF with POMO improves TSP-1000 by over 10%.

Warm-up times for TSP-500, TSP-1000, and TSP-10000 are 1.22s, 7.23s, and 5.12 min, respectively.

AM and GCN integrated into DTTGF (Table II) show significant LSTSP improvements in accuracy and efficiency. GCN, like POMO, reaches TSP-10000, a feat beyond the original approach, proving DTTGF's versatility in enhancing existing methods.

## V. CONCLUSION

Introducing DTTGF, a novel framework upgrading TSP solvers for UAVRP with many sites. It uses Delaunay triangulation for graph decomposition and embeds current solvers. With a warm-up strategy, DTTGF extends solvers efficiently, enhancing generalizability and scalability. Embedding Att-GCN and POMO, it handles LSTSP, outperforming or matching SOTA on three datasets. Ablation studies show DT-based subgraph methods preserve features and boost accuracy. The warm-up strategy improves search accuracy within reasonable time. Future work could enhance the framework's effectiveness, especially for large TSP instances, and refine the warmup strategy with adaptive hyperparameters. The framework may also apply to other combinatorial optimization problems.

#### REFERENCES

- [1] N. Agatz, P. Bouman, and M. Schmidt, "Optimization approaches for the traveling salesman problem with drone," Transportation Science, vol. 52, no. 4, pp. 965-981, 2018.
- [2] B. Borkakoty and N. K. Bali, "Tsp-based pcr for rapid identification of l and s type strains of sars-cov-2," Indian journal of medical microbiology, vol. 39, no. 1, pp. 73-80, 2021.
- [3] Z. Wang, D. Xu, M. Jiang, and K. C. Tan, "Spatial-temporal knowledge transfer for dynamic constrained multiobjective optimization," IEEE Transactions on Evolutionary Computation, 2024.
- [4] D. Xu, K. Ye, Z. Zheng, T. Zhou, G. G. Yen, and M. Jiang, "An efficient dynamic resource allocation framework for evolutionary bilevel optimization," IEEE Transactions on Cybernetics, 2024.

- [5] J. Zhang, Y. Lin, M. Jiang, S. Li, Y. Tang, J. Long, J. Weng, and K. C. Tan, "Fast multilabel feature selection via global relevance and redundancy optimization," *IEEE Transactions on Neural Networks and Learning Systems*, vol. 35, no. 4, pp. 5721–5734, 2022.
- [6] M. Jiang, Y. Yu, X. Liu, F. Zhang, and Q. Hong, "Fuzzy neural network based dynamic path planning," 2012 International Conference on Machine Learning and Cybernetics, vol. 1, pp. 326–330, 2012.
- [7] D. L. Applegate, R. E. Bixby, V. Chvátal, W. Cook, D. G. Espinoza, M. Goycoolea, and K. Helsgaun, "Certification of an optimal tsp tour through 85,900 cities," *Operations Research Letters*, vol. 37, no. 1, pp. 11–15, 2009.
- [8] K. Helsgaun, An Extension of the Lin-Kernighan-Helsgaun TSP Solver for Constrained Traveling Salesman and Vehicle Routing Problems: Technical report. Roskilde Universitet, Dec. 2017.
- [9] P. R. de O. da Costa, J. Rhuggenaath, Y. Zhang, and A. Akcay, "Learning 2-opt heuristics for the traveling salesman problem via deep reinforcement learning," in *Proceedings of The 12th Asian Conference* on Machine Learning, ACML 2020, 18-20 November 2020, Bangkok, Thailand (S. J. Pan and M. Sugiyama, eds.), vol. 129 of *Proceedings of* Machine Learning Research, pp. 465–480, PMLR, 2020.
- [10] W. Kool, H. van Hoof, and M. Welling, "Attention, learn to solve routing problems!," in *International Conference on Learning Representations*, 2019.
- [11] H. Hong, M. Jiang, and G. G. Yen, "Boosting scalability for large-scale multiobjective optimization via transfer weights," *Information Sciences*, vol. 670, p. 120607, 2024.
- [12] M. Jiang, Z. Wang, L. Qiu, S. Guo, X. Gao, and K. C. Tan, "A fast dynamic evolutionary multiobjective algorithm via manifold transfer learning," *IEEE Transactions on Cybernetics*, vol. 51, no. 7, pp. 3417– 3428, 2020.
- [13] M. Jiang, Z. Wang, S. Guo, X. Gao, and K. C. Tan, "Individualbased transfer learning for dynamic multiobjective optimization," *IEEE Transactions on Cybernetics*, vol. 51, no. 10, pp. 4968–4981, 2020.
- [14] K. C. Tan, L. Feng, and M. Jiang, "Evolutionary transfer optimization a new frontier in evolutionary computation research," *IEEE Computational Intelligence Magazine*, vol. 16, no. 1, pp. 22–33, 2021.
- [15] Z. Fu, K. Qiu, and H. Zha, "Generalize a small pre-trained model to arbitrarily large TSP instances," in *Thirty-Fifth AAAI Conference on Artificial Intelligence, AAAI 2021, Thirty-Third Conference on Innovative Applications of Artificial Intelligence, IAAI 2021, The Eleventh Symposium on Educational Advances in Artificial Intelligence, EAAI 2021, Virtual Event, February 2-9, 2021*, pp. 7474–7482, AAAI Press, 2021.
- [16] Z. Wang, Q. Zeng, W. Lin, M. Jiang, and K. Tan, "Multi-view subgraph neural networks: Self-supervised learning with scarce labeled data," *IEEE Transactions on Neural Networks and Learning Systems*, 2024.
- [17] H. Hong, M. Jiang, Q. Lin, and K. C. Tan, "Efficiently tackling milliondimensional multiobjective problems: A direction sampling and finetuning approach," *IEEE Transactions on Emerging Topics in Computational Intelligence*, 2024.
- [18] E. Osaba, X.-S. Yang, and J. Del Ser, "Traveling salesman problem: a perspective review of recent research and new results with bio-inspired metaheuristics," *Nature-inspired computation and swarm intelligence*, pp. 135–164, 2020.
- [19] M. Jiang, W. Huang, Z. Huang, and G. G. Yen, "Integration of global and local metrics for domain adaptation learning via dimensionality reduction," *IEEE Transactions on Cybernetics*, vol. 47, no. 1, pp. 38–51, 2017.
- [20] M. Jiang, Z. Huang, L. Qiu, H. W, and G. Yen, "Transfer learning based dynamic multiobjective optimization algorithms," *IEEE Transactions on Evolutionary Computation*, pp. 1–1, 2017.
- [21] Z. Wang, L. Cao, L. Feng, M. Jiang, and K. C. Tan, "Evolutionary multitask optimization with lower confidence bound-based solution selection strategy," *IEEE Transactions on Evolutionary Computation*, 2024.
- [22] O. Vinyals, M. Fortunato, and N. Jaitly, "Pointer networks," Advances in neural information processing systems, vol. 28, 2015.
- [23] M. JIANG, Z. WANG, H. HONG, and G. G. YEN, "Knee point based imbalanced transfer learning for dynamic multi-objective optimization," *IEEE Transactions on Evolutionary Computation*, 2020.
- [24] Y.-D. Kwon, J. Choo, B. Kim, I. Yoon, Y. Gwon, and S. Min, "Pomo: Policy optimization with multiple optima for reinforcement learning," *Advances in Neural Information Processing Systems*, vol. 33, pp. 21188– 21198, 2020.

- [25] R. Rambabu, P. Vadakkepat, K. C. Tan, and M. Jiang, "A mixtureof-experts prediction framework for evolutionary dynamic multiobjective optimization," *IEEE transactions on cybernetics*, vol. 50, no. 12, pp. 5099–5112, 2019.
- [26] X. Pan, Y. Jin, Y. Ding, M. Feng, L. Zhao, L. Song, and J. Bian, "Htsp: Hierarchically solving the large-scale traveling salesman problem," in AAAI 2023, February 2023.
- [27] R. Qiu, Z. Sun, and Y. Yang, "DIMES: A differentiable meta solver for combinatorial optimization problems," in Advances in Neural Information Processing Systems, 2022.
- [28] X. Xu, J. Li, and M. Zhou, "Delaunay-triangulation-based variable neighborhood search to solve large-scale general colored traveling salesman problems," *IEEE Transactions on Intelligent Transportation Systems*, vol. 22, no. 3, pp. 1583–1593, 2021.
- [29] A. N. Letchford and N. A. Pearson, "Good triangulations yield good tours," *Computers & Computers Research*, vol. 35, p. 638–647, Feb 2008.
- [30] H. Alkema, M. de Berg, M. Monemizadeh, and L. Theocharous, "TSP in a Simple Polygon," in 30th Annual European Symposium on Algorithms (ESA 2022) (S. Chechik, G. Navarro, E. Rotenberg, and G. Herman, eds.), vol. 244 of Leibniz International Proceedings in Informatics (LIPIcs), (Dagstuhl, Germany), pp. 5:1–5:14, Schloss Dagstuhl – Leibniz-Zentrum für Informatik, 2022.
- [31] S. Lin and B. W. Kernighan, "An effective heuristic algorithm for the traveling-salesman problem," *Operations Research*, p. 498–516, Apr 1973.
- [32] Y. Gong, Q. Zeng, D. Xu, Z. Wang, and M. Jiang, "Cross-modality attack boosted by gradient-evolutionary multiform optimization," arXiv preprint arXiv:2409.17977, 2024.
- [33] Q. Zeng, Z. Wang, Y. Cheung, and et al., "Ask, attend, attack: An effective decision-based black-box targeted attack for image-to-text models," in *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024.
- [34] Z. Wang, Q. Zeng, W. Lin, and et al., "Generating diagnostic and actionable explanations for fair graph neural networks," in *Proceedings* of the AAAI Conference on Artificial Intelligence, vol. 38, pp. 21690– 21698, 2024.
- [35] Z.-H. Fu, K.-B. Qiu, and H. Zha, "Generalize a small pre-trained model to arbitrarily large tsp instances," *Proceedings of the AAAI Conference* on Artificial Intelligence, p. 7474–7482, Sep 2022.
- [36] D. Applegate, R. Bixby, V. Chvátal, and W. Cook, "The traveling salesman problem: A computational study," *Choice Reviews Online, Choice Reviews Online*, Feb 2007.
- [37] M. Deudon, P. Cournut, A. Lacoste, Y. Adulyasak, and L. Rousseau, "Learning heuristics for the TSP by policy gradient," in *Integration* of Constraint Programming, Artificial Intelligence, and Operations Research - 15th International Conference, CPAIOR 2018, Delft, The Netherlands, June 26-29, 2018, Proceedings (W. J. van Hoeve, ed.), vol. 10848 of Lecture Notes in Computer Science, pp. 170–181, Springer, 2018.
- [38] C. K. Joshi, T. Laurent, and X. Bresson, "An efficient graph convolutional network technique for the travelling salesman problem," 2019.
- [39] A. Hottung, Y. Kwon, and K. Tierney, "Efficient active search for combinatorial optimization problems," in *The Tenth International Conference* on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022, OpenReview.net, 2022.
- [40] X. Pan, Y. Jin, Y. Ding, M. Feng, L. Zhao, L. Song, and J. Bian, "H-TSP: hierarchically solving the large-scale traveling salesman problem," in *Thirty-Seventh AAAI Conference on Artificial Intelligence, AAAI* 2023, Thirty-Fifth Conference on Innovative Applications of Artificial Intelligence, IAAI 2023, Thirteenth Symposium on Educational Advances in Artificial Intelligence, EAAI 2023, Washington, DC, USA, February 7-14, 2023 (B. Williams, Y. Chen, and J. Neville, eds.), pp. 9345–9353, AAAI Press, 2023.