# NGQA: A Nutritional Graph Question Answering Benchmark for Personalized Health-aware Nutritional Reasoning

Zheyuan Zhang $^{1^*},$  Yiyang Li $^{1^*},$  Nhi Ha Lan Le $^{2^*},$  Zehong Wang $^1,$  Tianyi Ma $^1,$  Vincent Galassi $^1,$ 

Keerthiram Murugesan <sup>3</sup>, Nuno Moniz<sup>1</sup>, Werner Geyer<sup>3</sup>, Nitesh V Chawla<sup>1</sup>, Chuxu Zhang<sup>4</sup> Yanfang Ye<sup>1†</sup>

<sup>1</sup>University of Notre Dame, <sup>2</sup>Brandeis University, <sup>3</sup>IBM Research, <sup>4</sup>University of Connecticut

\*Equal Contribution †Corresponding Author

{zzhang42,yli62,zwang43,tma2,vgalassi,nmoniz2,nchawla,yye7}@nd.edu,

nhihlle@brandeis.edu, keerthiram.murugesa@ibm.com, werner.geyer@us.ibm.com, chuxu.zhang@uconn.edu

#### Abstract

Diet plays a critical role in human health, yet tailoring dietary reasoning to individual health conditions remains a major challenge. Nutrition Question Answering (QA) has emerged as a popular method for addressing this problem. However, current research faces two critical limitations. On the one hand, the absence of datasets involving user-specific medical information severely limits *personalization*. This challenge is further compounded by the wide variability in individual health needs. On the other hand, while large language models (LLMs), a popular solution for this task, demonstrate strong reasoning abilities, they struggle with the *domain-specific* complexities of personalized healthy dietary reasoning, and existing benchmarks fail to capture these challenges. To address these gaps, we introduce the Nutritional Graph Question Answering (NGQA) benchmark, the first graph question answering dataset designed for *personalized nutritional health reasoning*. NGQA leverages data from the National Health and Nutrition Examination Survey (NHANES) and the Food and Nutrient Database for Dietary Studies (FNDDS) to evaluate whether a food is healthy for a specific user, supported by explanations of the key contributing nutrients. The benchmark incorporates three question complexity settings and evaluates reasoning across three downstream tasks. Extensive experiments with LLM backbones and baseline models demonstrate that the NGQA benchmark effectively challenges existing models. In sum, NGQA addresses a critical real-world problem while advancing GraphQA research with a novel domain-specific benchmark. Our codebase and dataset are available [here.](https://anonymous.4open.science/r/NGQA-5E7F/README.md)

## 1 Introduction

Diet is a cornerstone of human health, playing a pivotal role in both maintaining well-being and preventing disease. Despite the well-documented

<span id="page-0-0"></span>

Figure 1: An Overview of NGQA Benchmark (a) along with a data showcase: (b) an example of the knowledge graph used for a standard level question and (c) the question and the answer of that question under the multilabel classification task (-ML) settings.

benefits of balanced nutrition, unhealthy eating habits remain alarmingly prevalent in modern society [\(WHO,](#page-10-0) [2021\)](#page-10-0). In the United States alone, approximately 42.4% of adults are classified as obese [\(CDC,](#page-8-0) [2020a\)](#page-8-0), and in 2017, poor dietary habits contributed to over 11 million deaths and a substantial number of disability-adjusted life-years (DALYs), often linked to factors such as excessive sodium intake [\(Afshin et al.,](#page-8-1) [2019;](#page-8-1) [WHO,](#page-10-1) [2023\)](#page-10-1). These statistics underscore an urgent need to promote healthier eating habits on a societal scale. However, nutritional health requires complex domain knowledge, and there is no one-size-fits-all solution for healthy diets, as the nutritional needs of individuals can vary widely based on their health conditions. For example, a diet suitable for someone with a high body mass index (BMI) may differ drastically from that of an individual with a low BMI. Likewise, while individuals recovering from opioid misuse may benefit from a high-protein diet, such dietary choices can be harmful to those managing chronic kidney disease [\(Mahboub et al.,](#page-9-0) [2021\)](#page-9-0).

Why this benchmark matters: Numerous efforts have sought to address the challenges in personalized nutritional health, with Nutrition Question Answering (QA) emerging as a popular task [\(Min et al.,](#page-9-1) [2022;](#page-9-1) [Bondevik et al.,](#page-8-2) [2024\)](#page-8-2). Recent advancements in large language models (LLMs) have demonstrated significant potential in this domain, offering sophisticated reasoning capabilities to analyze and interpret nutritional information [\(Mavro](#page-9-2)[matis and Karypis,](#page-9-2) [2024\)](#page-9-2). However, these efforts remain constrained by two major limitations. First, to the best of our knowledge, no existing benchmark truly personalizes answers based on users' specific health conditions, primarily due to the inaccessibility of individual medical data [\(Bölz](#page-8-3) [et al.,](#page-8-3) [2023\)](#page-8-3). This lack of user-specific datasets has severely hindered the development of effective solutions. Second, while LLMs exhibit impressive reasoning capabilities in general domains, the medical and nutritional intricacies of this task impose severe limitations on their effectiveness [\(Mialon](#page-9-3) [et al.,](#page-9-3) [2023\)](#page-9-3). Current benchmarks fail to capture the domain-specific complexities of personalized health-aware dietary reasoning, making it difficult to evaluate, let alone improve, these models in meaningful ways.

To address these critical gaps and advance the understanding of healthy diet personalization, we propose the Nutritional Graph Question Answering (NGQA) benchmark. This is *the first benchmark in the personalized nutritional health domain* to evaluate whether a specific food is healthy for a user, supported by detailed reasoning of the key contributing nutrients. By recognizing the intricate interplay between a user's medical conditions, dietary behaviors, and the nutrition of foods, we frame this task as a knowledge graph question answering problem. Specifically, using data from the National Health and Nutrition Examination Survey (NHANES) and the Food and Nutrient Database for Dietary Studies (FNDDS), we construct the NGQA benchmark and categorize questions into three complexity settings: sparse, standard, and complex. Each question type is further evaluated through three downstream tasks, binary classification (-B), multi-label classification (-ML), and text generation (-TG), to explore distinct reasoning aspects (Figure[-1](#page-0-0) (a)). We conduct extensive experiments using various LLM backbones and baseline models to ensure the benchmark is both appropriately challenging and meaningful for advancing the field. Our contributions can be summarized as

follows:

- Novel Benchmark for Personalized Nutrition. We present NGQA, the first benchmark to incorporate users' medical information in a nutritional question answering task, addressing a significant research gap in the domain of personalized healthy diet research.
- Advancing the GraphQA Ecosystem. NGQA introduces a domain-specific benchmark and extends GraphQA benchmarks beyond datasets like *WebQSP* and *Expla-Graphs* in the general domain. This addition broadens the scope of GraphQA research, enabling a more comprehensive evaluation of GraphQA models' capabilities beyond general reasoning tasks.
- Comprehensive Resource and Evaluation. Through extensive experiments, NGQA provides a challenging benchmark, a complete codebase supporting the full pipeline from data preprocessing to model evaluation, and an extensibility for integrating new models. This comprehensive resource helps advance research in both personalized nutritional health and the broader GraphQA field.

# 2 Related Work

Question Answering in Nutritional Health Domain. Question answering has become an essential tool in the nutritional and health domain, offering a flexible framework for applications such as food recommendation [\(Min et al.,](#page-9-1) [2022;](#page-9-1) [Bonde](#page-8-2)[vik et al.,](#page-8-2) [2024\)](#page-8-2). Knowledge graphs (KGs) have been widely used to model relationships between foods, ingredients, and health, supporting tasks like ingredient substitution and adaptive dietary recommendations [\(Haussmann et al.,](#page-9-4) [2019;](#page-9-4) [Chen](#page-8-4) [et al.,](#page-8-4) [2021;](#page-8-4) [Fatemi et al.,](#page-9-5) [2023a;](#page-9-5) [Xu et al.,](#page-10-2) [2024\)](#page-10-2). Recent approaches incorporate health metrics into QA systems, focusing on recipe recommendations and nutritional ontologies [\(Li et al.,](#page-9-6) [2023;](#page-9-6) [Senevi](#page-10-3)[ratne et al.,](#page-10-3) [2021\)](#page-10-3). However, existing methods lack true personalization, as highlighted by [\(Bölz et al.,](#page-8-3) [2023\)](#page-8-3), due to the absence of user-specific medical data. Our work fills this gap by introducing the first GraphQA benchmark for personalized nutritional health, enabling models to provide tailored nutritional reasoning and explanations.



Figure 2: The NGQA benchmark construction process. Each stage shown in the figure is detailed in Section 3.For example, "User Data Collection" block, is introduced in Section 3.1 under the paragraph titled User Data Collection.

Graph Retrieval Augmented Generation. Knowledge Graph Question Answering (KGQA) has progressed from early semantic parsing and retrieval-based methods to advanced techniques leveraging large language models (LLMs) and graph neural networks (GNNs) for reasoning and retrieval [\(Jiang et al.,](#page-9-7) [2023;](#page-9-7) [Kim et al.,](#page-9-8) [2023;](#page-9-8) [Gao et al.,](#page-9-9) [2024\)](#page-9-9). Building on this progress, Graph-Retrieval Augmented Generation (Graph-RAG) has emerged as a widely studied method, offering more precise, context- and structure-aware reasoning compared to traditional text-based RAG methods [\(Lewis et al.,](#page-9-10) [2020;](#page-9-10) [Lazaridou](#page-9-11) [et al.,](#page-9-11) [2022;](#page-9-11) [Guo et al.,](#page-9-12) [2024;](#page-9-12) [Wen et al.,](#page-10-4) [2023\)](#page-10-4). Despite the development of various LLM-powered models, benchmarks for the Graph-RAG task remain scarce and lack standardization. Early benchmarks focus primarily on general graph tasks such as shortest paths and node degree [\(Fatemi](#page-9-13) [et al.,](#page-9-13) [2023b;](#page-9-13) [Wang et al.,](#page-10-5) [2024a\)](#page-10-5), while [\(He](#page-9-14) [et al.,](#page-9-14) [2024\)](#page-9-14) introduces a GraphQA benchmark for complex reasoning using general-purpose datasets. Building on their framework, we develop the first domain-specific benchmark in the nutritional health domain, bridging the gap between general GraphQA research and personalized health-aware reasoning. More detailed literature is available in Appendix[-A.](#page-11-0)

## 3 NGQA Benchmark

## 3.1 Data Collection

Data Source. Using data from the National Health and Nutrition Examination Survey (NHANES) and the Food and Nutrient Database for Dietary Studies (FNDDS), we construct the first GraphQA benchmark designed to address personalized healthy nutrition intake questions. This benchmark integrates detailed user health profiles, dietary behaviors,

and comprehensive food nutritional information, enabling a fine-grained analysis of how individual health conditions interact with food nutrition. By representing these relationships through graph structures, the benchmark supports answering complex nutritional questions while capturing the intricate interplay between users' medical conditions and dietary choices. The following sections provide a detailed discussion of these datasets and their integration into our benchmark.

User Data Collection. The NHANES dataset forms the foundation of our work for collecting user data. We extract medical information, dietary habits, and food intake records to construct the graph. Specifically, NHANES provides laboratory reports detailing body metrics like Body Mass Index (BMI) and blood pressure, along with biochemical markers such as blood urea nitrogen. It also includes questionnaire responses on prescription drug usage, adherence to special diets, and overall health status. Additionally, NHANES records users' food intake history and dietary behaviors, such as the frequency of adding salt at the table. Our study incorporates 54 distinct dietary habits, with detailed data processing methods provided in Appendix[-B.](#page-11-1) This comprehensive dataset serves as the backbone of our graph, capturing user health conditions and dietary patterns with granular detail.

Food Data Collection. Nutritional information for food items is sourced from FNDDS. FNDDS connects NHANES food codes to detailed nutritional data cataloged in the What We Eat in America (WWEIA) database. Using FNDDS, we associate each food item in NHANES with its full nutritional composition. Additionally, FNDDS links food items to ingredient information and classifies them into broader food categories. For example, a food item like "apple" is linked to its nutrient values (e.g., sugars, vitamins) and assigned to the category "fruits." These associations enrich the graph by providing node-level data for food, ingredients, and categories.

Tagging Scheme. To evaluate whether a food is specifically healthy for a user based on their personal health conditions, we propose a tagging scheme that assigns nutrition-related tags to both users and foods. This systematic framework aligns food nutritional properties with user health needs, enabling robust assessments of food suitability.

For food tagging, we build upon established guidelines and introduce newly applied standards. Prior works have utilized recommendations from the World Health Organization (WHO) and the Food Standards Agency (FSA) [\(Wang et al.,](#page-10-6) [2021\)](#page-10-6), while we extend this by incorporating the more detailed EU Nutrition & Health Claims Regulation [\(Commission,](#page-8-5) [2006\)](#page-8-5) and the Codex Alimentarius Commission (CAC) [\(Alimentarius,](#page-8-6) [1985,](#page-8-6) [1997\)](#page-8-7). These standards define precise thresholds for nutrient claims. For instance, the EU regulation permits labeling a food as "low sodium" only if it contains no more than 0.12 g of sodium per 100 g [\(Commis](#page-8-5)[sion,](#page-8-5) [2006\)](#page-8-5). Foods meeting such criteria are tagged with corresponding labels like "low\_sodium" or "high\_protein", reflecting their nutritional properties.

On the user side, health tags are derived from the NHANES dataset, which includes laboratory results and self-reported health information. For example, users with high blood pressure, as defined by American Heart Association (AHA) thresholds or similar guidelines, are tagged with "hypertension," indicating that a low-sodium diet would be beneficial [\(Grillo et al.,](#page-9-15) [2019;](#page-9-15) [Smyth et al.,](#page-10-7) [2014\)](#page-10-7).

By linking health and food tags, our scheme effectively represents personalized dietary needs and captures the interplay between medical conditions and nutritional requirements. The detailed standards and additional tags for other nutrients and health conditions are described in Appendix[-B.](#page-11-1) By integrating this methodology into our graph-based benchmark, we provide a framework for advancing personalized dietary reasoning and evaluating models in this domain.

## 3.2 Data Annotation

Real-world data is inherently messy and incomplete, and the datasets we use are no exception. Spanning from 2003 to 2020, NHANES provides data for approximately 100,000 users and over 2

million food records. While this dataset offers an invaluable resource for studying nutrition and health, it includes inconsistencies, ambiguities, and irrelevant entries. To establish a scientifically robust and meaningful benchmark, precise data annotation is essential. This involves not only cleaning and filtering the data but also carefully defining and validating annotations to accurately capture real-world relationships between health conditions, dietary behaviors, and food options. Our annotation process refines both user and food datasets to ensure relevance, accuracy, and applicability to real-life scenarios.

User Filtering. Annotating user data requires careful consideration of the complex interactions between nutrition and health. For instance, elevated blood urea nitrogen (BUN) levels may indicate kidney dysfunction, warranting a low-protein diet, but could also result from insufficient water intake. To maintain scientific rigor and practical relevance, we focus on annotating four prevalent health statuses—obesity, hypertension, opioid misuse, and diabetes—that are directly influenced by dietary interventions. Additionally, we annotate nine special diets reported by users, reflecting health-related dietary practices. Further details on the definitions and implications of these health statuses and diets are provided in the Appendix[-B.](#page-11-1) To ensure consistency and relevance, we exclude users under 18, focusing solely on adult dietary patterns.

Food Filtering. For food annotation, we identify practical entries in the FNDDS database that align with real-world dietary reasoning. While FNDDS supports comprehensive nutritional analysis, it includes many entries unsuitable for practical use, such as raw ingredients or standalone additives. To address this, we restrict our focus to the "mixed dishes" category, as it represents combined recipes closest to real-life diets. Additionally, we include other relevant categories, such as bakery products and desserts (definitions of FNDDS categories are available in the Appendix[-I\)](#page-18-0). Finally, we apply a keyword-based deduplication method to remove highly similar entries.

Multi-step Annotation. Using the previously defined standards and tagging schemes, our annotation process systematically establishes "match" or "contradict" relationships between user health conditions and food nutritional profiles. For example, the tag "high\_calorie" contradicts the condition "obesity", while "low\_sodium" matches with "hypertension". To ensure accuracy and reliability, we

<span id="page-4-0"></span>

Figure 3: The illustration of different question levels and task levels.

adopt a multi-step annotation process. After initial filtering and tagging, large language models (LLMs) perform an initial sanity check to identify inconsistencies or anomalies in the annotations. Subsequently, three human annotators with domain expertise review and cross-validate the results to eliminate remaining inaccuracies. By combining automated checks with human validation, our rigorous annotation strategy captures the real-life complexities of personalized nutrition while maintaining high standards of quality and reliability.

# 4 Task Definition and Evaluation

# 4.1 Question Setting

With the annotated data in place, we designed three distinct types of questions, i.e., *sparse*, *standard*, and *complex*, to capture varying levels of difficulty and emulate real-world scenarios in personalized nutrition reasoning. This stratification ensures that our benchmark accommodates a wide range of research and application needs, spanning from controlled, idealized setups to challenging, real-life cases, as illustrated in Figure[-3](#page-4-0) (a).

Sparse questions address scenarios with minimal available information. In this setting, each food has only one nutrition tag linked to a single user health condition. This setup reflects realworld cases where labels are scarce or data is incomplete, challenging models to reason effectively with limited information. Although sparse questions may appear simple to human observers, the

unique link between the user and the food significantly increases the difficulty of subgraph retrieval, making models vulnerable to interference from irrelevant nodes.

Standard questions represent the balanced and idealized scenarios in our benchmark. In this category, foods are linked to multiple nutrition tags, which either match or contradict several user health conditions. This configuration reflects controlled cases where the relationship between dietary choices and health outcomes is clear-cut, enabling a focused evaluation of model performance. Standard questions serve as a foundation for benchmarking in structured and well-defined environments.

Complex questions are designed to replicate the intricacies of real-life nutritional decision-making. Foods in this category may simultaneously have tags that both match with and contradict a user's health conditions. For instance, a food may be low in sodium (beneficial for hypertension) but also high in sugar (problematic for diabetes). These scenarios require models to navigate conflicting information, prioritize user health needs, and perform nuanced trade-off reasoning. This category closely mirrors the ambiguous and multifaceted challenges of real-world dietary decisions.

The benchmark's statistical breakdown is presented in Table[-1.](#page-5-0) To further evaluate the complexity and informativeness of the questions, we introduce the Signal-to-Noise Ratio (SNR). SNR measures the ratio of nodes or tags relevant to the

<span id="page-5-0"></span>

Question Level # Records Avg. # Nodes Avg. # Edges			
Sparse	8.490	25.84	24.86
Standard	3.622	28.16	28.98
Complex	1.690	30.94	34.04

<span id="page-5-1"></span>Table 1: Statistics of the Benchmark by Question Level.

	Question Level Avg. Node SNR Avg. Tag SNR	
<b>Sparse</b>	16.37	19.30
Standard	24.68	49.39
Complex	31.57	76.32

Table 2: Signal-to-Noise Ratio (SNR) by Question Level.

answer (*signal*) against the total nodes or tags in the graph (*noise*). As shown in Table[-2,](#page-5-1) sparse questions exhibit the lowest SNR, reflecting the limited resources available for these tasks. Conversely, complex questions, despite containing conflicting information, achieve the highest SNR, underscoring the rich contextual information necessary for accurate reasoning. More statistics of the benchmark are available in Appendix[-E.](#page-16-0)

#### 4.2 Task Setting

To enhance the generality and versatility of our benchmark, we design three distinct downstream task types, each centered on the same domain question but requiring different forms of output, as illustrated in Figure[-3](#page-4-0) (b). This diversity ensures the benchmark accommodates a wide range of methodologies and research focuses while fostering innovation in addressing personalized nutrition challenges. The tasks are defined as follows:

Binary Classification (-B): This task requires a simple "yes" or "no" response, indicating whether a specific food is suitable for a user based on their health profile. It emphasizes straightforward decision-making, reflecting applications like automated diet advisories or recommendation systems.

Multi-Label Classification (-ML): In this task, models must retrieve the nutritional tags associated with a food and determine which match with or contradict the user's health conditions. By demanding richer output, this task evaluates the model's ability to leverage graph information and identify nuanced relationships.

Text Generation (-TG): The output is a natural language explanation of why a food is healthy or unhealthy for a user. This task assesses a model's capability for interpretable and user-friendly reasoning, which is crucial for real-world applications such as personalized dietary assistant chatbots.

#### 4.3 Evaluation Metrics

To evaluate model performance, we adopt taskspecific metrics tailored to each type. For classification tasks, we use standard metrics like accuracy, recall, precision, and F1 score for comprehensive performance assessment. Multi-label classification tasks extend these metrics to their weighted versions, accounting for the distribution of multiple labels across samples. Text generation tasks are evaluated with widely used metrics such as ROUGE, BLEU, and BERT scores, which collectively assess relevance and semantic similarity to reference texts. The definition of ground truths is available in Appendix[-B.](#page-11-1) This multifaceted design supports diverse model architectures and evaluation strategies, providing a robust foundation for advancing personalized nutrition research. By bridging the gap between controlled research environments and the complexities of real-world applications, our benchmark fosters innovation and opens new avenues for addressing healthy dietary reasoning.

## 5 Experiments

## 5.1 Experiment Settings

In this section, we conduct extensive experiments to evaluate existing Graph-RAG models' reasoning capability on the proposed benchmark. For baseline models, we select the five most classical baselines: KAPING [\(Baek et al.,](#page-8-8) [2023\)](#page-8-8), CoT-Zero [\(Ko](#page-9-16)[jima et al.,](#page-9-16) [2022\)](#page-9-16), CoT-BAG [\(Wang et al.,](#page-10-5) [2024a\)](#page-10-5), ToG [\(Sun et al.,](#page-10-8) [2024\)](#page-10-8), and a naive plain Graph-RAG pipeline (implementation details in Appendix-[C\)](#page-13-0). For the main experiments, we choose GPT-4o-mini as the LLM backbone, we also conduct additional experiments on a series of other classic LLM backbones in Appendix[-D.](#page-15-0) Note that we didn't select the most advanced LLM backbones or the most sophisticated fine-tuned baselines because we argue our contributions focus primarily on the proposed benchmark with the novel tasks for this specific domain, and the experiment results along with the hallucination analyses have demonstrated our tasks are properly designed where the classic baselines can be adequately challenged while maintaining efficiency. In the following sections, we go through the experiment results for each task.

#### 5.2 Binary Classification Task

Table[-3](#page-6-0) (a) presents the performance of baseline models on the binary classification task, which evaluates the models' ability to provide a decisive "yes"

<span id="page-6-0"></span>

Method <b>Ouestion Level</b>				a) Binary Classification (-B)				b) Multi-label Classification (-ML)		c) Text Generation (-TG)				
		Accuracy	Recall	Precision	F1	Accuracy	Recall	Precision	F1	<b>ROUGE-1</b>	<b>ROUGE-2</b>	<b>ROUGE-L</b>	<b>BLEU</b>	<b>BERT</b>
	Plain	0.5973	0.1634	1.0000	0.2810	0.1798	0.9943	0.2109	0.3442	0.5385	0.4775	0.5385	0.2838	0.9370
	<b>KAPING</b>	0.5347	0.0541	0.7246	0.1006	0.1753	0.9915	0.2075	0.3394	0.5234	0.4600	0.5234	0.2674	0.9353
<b>Sparse</b>	CoT-Zero	0.6604	0.2951	0.9983	0.4555	0.2032	0.9958	0.2435	0.3842	0.5463	0.4842	0.5462	0.2889	0.9388
	CoT-BAG	0.6038	0.1769	1.0000	0.3006	0.2134	0.9966	0.2520	0.3945	0.5481	0.4886	0.5480	0.2930	0.9385
	ToG	0.7729	0.5383	0.9817	0.6953	0.2439	0.9128	0.2986	0.4333	0.6254	0.5710	0.6251	0.3612	0.9465
	Plain	0.5762	0.1989	1.0000	0.3317	0.4909	0.9980	0.4901	0.6528	0.7219	0.6321	0.6941	0.4840	0.9618
	<b>KAPING</b>	0.5022	0.0637	0.9313	0.1192	0.4593	0.9956	0.4624	0.6272	0.7087	0.6237	0.6764	0.4617	0.9599
<b>Standard</b>	CoT-Zero	0.6565	0.3507	1.0000	0.5193	0.5390	0.9967	0.5447	0.6963	0.7329	0.6443	0.7049	0.4939	0.9630
	CoT-BAG	0.5900	0.2249	1.0000	0.3673	0.5599	0.9982	0.5611	0.7091	0.7333	0.6456	0.7032	0.495	0.9630
	ToG	0.8628	0.7411	0.9993	0.8511	0.6189	0.8843	0.6793	0.7464	0.8182	0.7632	0.7817	0.6112	0.9716
	Plain	0.6598	0.0636	0.9750	0.1194	0.7185	0.9721	0.7374	0.8358	0.7356	0.6510	0.7001	0.4949	0.9599
	<b>KAPING</b>	0.6574	0.0571	0.9722	0.1079	0.6883	0.9758	0.7129	0.8093	0.7394	0.6634	0.7016	0.4839	0.9602
Complex	CoT-Zero	0.6627	0.0718	0.9778	0.1337	0.7453	0.9735	0.7679	0.8557	0.7478	0.6599	0.7103	0.5048	0.9615
	CoT-BAG	0.6627	0.0701	1.0000	0.1311	0.7546	0.9631	0.7801	0.8587	0.7467	0.6622	0.7080	0.5049	0.9611
	ToG	0.7473	0.3964	0.8100	0.5323	0.6153	0.6989	0.8119	0.7303	0.7729	0.6915	0.7366	0.5313	0.9639

Table 3: Experimental results based on five baseline methods on the three tasks with the three question levels using the GPT-4o-mini. The best performance of each group is bolded.

<span id="page-6-1"></span>

Figure 4: Efficiency analysis of the five baseline methods across three tasks.

or "no" response based on summarized reasoning. The results reveal a notable conservatism in model behavior, as evidenced by the low recall scores. This likely stems from the sensitive nature of medical questions, where LLMs try to avoid offering simple "yes" answers without explanations unless their confidence is exceptionally high. Despite this challenge, the experiments yield two important insights into how external domain knowledge can support LLMs in this scenario. First, increasing the number of links in the graph (e.g., from Sparse to Standard questions) consistently improves recall across all baselines. This indicates that richer external knowledge provides LLMs with greater context and reassurance, enabling them to produce more confident positive answers. Second, ToG significantly outperforms other baselines, showing performance gains unique to this task. We attribute this improvement to ToG's effective pruning mechanism, which removes irrelevant nodes and increases the SNR. By reducing noise and focusing on relevant information, ToG enhances LLMs' ability to make confident and accurate decisions.

## 5.3 Multi-label and Text Generation Task

Table[-3](#page-6-0) (b) and (c) present the performance of baseline models on the multi-label classification (ML)

<span id="page-6-2"></span>

Figure 5: Retrieval quality of ToG vs. Plain across three types of questions on recall, precision and F1.

and text generation (TG) tasks. The ML task evaluates models' ability to retrieve nutrition tags associated with foods and user health conditions, while the TG task tests their capacity to generate natural language explanations, offering a more comprehensive and realistic evaluation. The results reveal similar patterns across tasks: while baselines are competent at identifying nutrition tags from the graph, the primary challenge lies in correctly identifying the relevant tags based on user health conditions, as indicated by the overall high recall scores in the ML task.

Both tasks are most challenging on sparse question sets due to their low-resource nature. Conversely, models achieve the best performance on complex question sets, which may appear counterintuitive. However, as shown in Table[-2,](#page-5-1) complex questions have a higher Signal-to-Noise Ratio (SNR), providing models with a clearer signal that offsets their logical complexity. Additionally, the ToG model performs similarly on the standard and complex question sets due to its pruning process, which increases SNR by removing irrelevant nodes. While effective, this process can also discard valuable information, leading to lower performance on complex questions. This trade-off contrasts with ToG's success in binary classification task and high-

<span id="page-7-0"></span>

Ouestion	Based on the nutrients the food provides and the user with <i>obesity</i> and <i>opioid misuse</i> , please answer whether the food "Taco, corn tortilla, beef, cheese" is healthy for the user and why?
	<b>Factual Hallucination</b> – Lack of Domain Knowledge
Direct	It depends on the user's dietary needs; it may be unhealthy because the food is high in carbohydrate.
	<b>Contextual Hallucination</b> – Missing User's Needs
KAPING	No, because the food is high in sodium and high in cholesterol. It's not good for the health.
	<b>Correct</b> – Focus on What User's Conditions Require

Figure 6: A case study of error analysis.

lights the comprehensiveness of our benchmark, which challenges models across diverse scenarios to uncover their strengths and weaknesses.

## 5.4 Efficiency and Retrieval Quality

Beyond model performance, efficiency is a critical consideration in Graph-RAG systems. To evaluate this, we conduct an efficiency analysis of baseline models on our benchmark, as shown in Figure[-4.](#page-6-1) As can be seen, the binary classification task exhibits the fastest runtime, as it requires the shortest output. In contrast, the multi-label classification and text generation tasks involve longer outputs, leading to slower performance. Due to ToG's reliance on multiple LLM calls during the retrieval process, its runtime is significantly slower compared to other methods. Additionally, the quality of subgraph retrieval plays a crucial role in downstream reasoning. To assess this, we perform a retrieval quality analysis using ToG as a case study, comparing it against a plain Graph-RAG pipeline, as illustrated in Figure[-5.](#page-6-2) As shown, the retrieval scores of ToG align with its performance in the main experiments, confirming our assumption that fluctuations in ToG's performance are rooted in its pruning process during the subgraph retrieval phase.

#### 5.5 Error Analysis

In this section, we analyze the types of hallucinations observed in our experiments using a specific example and demonstrate the importance of external domain knowledge in mitigating these errors.

Traditional LLM-enhanced methods are wellknown for their susceptibility to hallucination errors, particularly in domain-specific tasks like nutritional health [\(Mialon et al.,](#page-9-3) [2023\)](#page-9-3). Figure[-6](#page-7-0) illustrates an example where we evaluate whether the food "Taco, corn tortilla, beef, cheese" is a healthy option for a user who is obese and recovering from opioid misuse. Our analysis identifies two main types of hallucinations. The first is *Factual Hallucination*, where the model produces incorrect or irrelevant information, often due to reliance on general knowledge not explicitly included in the graph. These errors are common when LLMs perform direct inference without external knowledge and occasionally occur when retrieved graphs contain noise. For example, the model incorrectly deemed the taco unsuitable, overlooking the fact that corn tortillas are relatively low in carbohydrates.

The second type is *Contextual Hallucination*, where the model fails to prioritize tags that directly relate to the user's health profile, focusing instead on less relevant attributes. This issue is less pronounced in ToG due to its ability to retrieve compact, focused subgraphs, unlike simpler methods like KAPING and CoT-Zero, which lack effective pruning. In this case, the taco's high sodium and cholesterol overshadowed its alignment with the user's specific health needs for a low-carb, highprotein diet, leading to a less optimal assessment.

In summary, these hallucinations highlight the importance of our domain-specific benchmark in establishing a rigorous framework to evaluate and improve LLMs, advancing both the nutritional health domain and Graph-RAG research while fostering the development of more robust and generalizable models (More examples in Appendix[-H\)](#page-18-1).

## 6 Conclusion

In this work, we introduce the Nutritional Graph Question Answering (NGQA) benchmark, the first dataset designed to address the critical challenges of personalized nutritional health reasoning. By leveraging user-specific medical data and framing the problem as a knowledge graph question answering task, NGQA bridges the gap between generalpurpose benchmarks and domain-specific applications. Our benchmark not only advances the scope of GraphQA research by incorporating complex, real-world nutritional scenarios but also provides a comprehensive resource for evaluating and improving models in this domain. We believe NGQA lays the foundation for future research in personalized diet and health-aware reasoning, fostering innovation in both nutritional health and GraphQA.

# Limitation

In this section, we discuss the limitations of this work and outline directions for future research. First, the benchmark includes a limited number of health conditions, though more are available. For example, osteoporosis suggests a high-calcium diet, a renal diet indicates low protein intake, and high low-density lipoprotein (LDL) levels may call for a low-cholesterol diet. As noted in the paper, we prioritized conditions most prevalent in the United States and most relevant to dietary interventions, but expanding to include additional conditions could enhance coverage and utility. Second, while we focus on the interplay between dietary behaviors and medical conditions, other factors, such as food insecurity, remain unexplored. NHANES offers extensive socioeconomic data, presenting opportunities to extend the benchmark to account for broader determinants of dietary decision-making. Third, for simplicity, complex questions are reduced to binary classification by counting "match" and "contradict" tags. However, real-life dietary decisions require nuanced trade-offs and reasoning that go beyond this approach. More sophisticated evaluation methods could better reflect practical scenarios. Lastly, the benchmark could benefit from additional tasks. For example, the existing graphs support questions like, "What alternative foods could meet a user's dietary preferences and medical needs?" Incorporating such tasks would broaden the benchmark's scope and encourage further innovation. Despite these limitations, this work establishes a robust baseline as a pioneering effort in personalized nutrition reasoning. We defer these challenges to future work, envisioning the benchmark as a foundation for ongoing advancements in this critical domain.

## Ethics and Privacy Statement

Safeguarding privacy and adhering to ethical principles are paramount when working with sensitive health-related data. The National Health and Nutrition Examination Survey (NHANES) serves as a benchmark in this regard, strictly complying with confidentiality protocols mandated by public legislation. These robust privacy measures enable us to achieve our research goals while remaining fully aligned with the survey's established guidelines. Notably, the NHANES dataset is anonymized, with personally identifiable information (PII)—such as social security numbers and physical addresses—removed. Despite the absence of PII, the dataset retains its utility for detailed analyses, allowing us to investigate the relationship between users' medical data and health-aware food recommendations as presented in this study. Additionally, in practical applications, the generated recommendations and interpretations are treated as personal medical records, ensuring sustained privacy protection. By adhering to these principles, our research maintains the highest levels of ethical responsibility and data privacy.

## References

- <span id="page-8-1"></span>Ashkan Afshin, Patrick J Sur, Kairsten A Fay, Leslie Cornaby, Giannina Ferrara, Jason S Salama, and Christopher J L Murray. 2019. Health effects of dietary risks in 195 countries, 1990–2017: a systematic analysis for the global burden of disease study 2017. *The Lancet*.
- <span id="page-8-6"></span>FAO/WHO Codex Alimentarius. 1985. [Guidelines on](https://www.fao.org/fao-who-codexalimentarius/sh-proxy/en/?lnk=1&url=https%253A%252F%252Fworkspace.fao.org%252Fsites%252Fcodex%252FStandards%252FCXG%2B2-1985%252FCXG_002e.pdf) [nutrition labelling.](https://www.fao.org/fao-who-codexalimentarius/sh-proxy/en/?lnk=1&url=https%253A%252F%252Fworkspace.fao.org%252Fsites%252Fcodex%252FStandards%252FCXG%2B2-1985%252FCXG_002e.pdf) Accessed: 2024-07-12.
- <span id="page-8-7"></span>FAO/WHO Codex Alimentarius. 1997. [Guidelines for](https://www.fao.org/fao-who-codexalimentarius/sh-proxy/en/?lnk=1&url=https%253A%252F%252Fworkspace.fao.org%252Fsites%252Fcodex%252FStandards%252FCXG%2B23-1997%252FCXG_023e.pdf) [use of nutrition and health claims.](https://www.fao.org/fao-who-codexalimentarius/sh-proxy/en/?lnk=1&url=https%253A%252F%252Fworkspace.fao.org%252Fsites%252Fcodex%252FStandards%252FCXG%2B23-1997%252FCXG_023e.pdf) Accessed: 2024- 07-12.
- <span id="page-8-8"></span>Jinheon Baek, Alham Fikri Aji, and Amir Saffari. 2023. Knowledge-augmented language model prompting for zero-shot knowledge graph question answering. In *ACL*.
- <span id="page-8-3"></span>Felix Bölz, Diana Nurbakova, Sylvie Calabretto, Armin Gerl, Lionel Brunie, and Harald Kosch. 2023. Hummus: A linked, healthiness-aware, user-centered and argument-enabling recipe data set for recommendation. In *RecSys*.
- <span id="page-8-2"></span>Jon Nicolas Bondevik, Kwabena Ebo Bennin, Önder Babur, and Carsten Ersch. 2024. A systematic review on food recommender systems. *Expert Systems with Applications*.
- <span id="page-8-0"></span>CDC. 2020a. [Adult obesity facts.](https://www.cdc.gov/obesity/data/adult.html)
- <span id="page-8-10"></span>CDC. 2020b. *Americans Share Hopeful Stories of Recovery From Opioid Use Disorder*. [https://www.cdc.gov/rxawareness/pdf/](https://www.cdc.gov/rxawareness/pdf/articles/TA-T3D2-English_MatteArticle_Release_508.pdf) [articles/TA-T3D2-English\\_MatteArticle\\_](https://www.cdc.gov/rxawareness/pdf/articles/TA-T3D2-English_MatteArticle_Release_508.pdf) [Release\\_508.pdf](https://www.cdc.gov/rxawareness/pdf/articles/TA-T3D2-English_MatteArticle_Release_508.pdf).
- <span id="page-8-4"></span>Yu Chen, Ananya Subburathinam, Ching-Hua Chen, and Mohammed J Zaki. 2021. Personalized food recommendation as constrained question answering over a large-scale food knowledge graph. In *WSDM*.
- <span id="page-8-5"></span>European Commission. 2006. [Eu nutrition & health](https://eur-lex.europa.eu/LexUriServ/LexUriServ.do?uri=OJ:L:2006:404:0009:0025:En:PDF) [claims regulation legislation \(ec\) 1924/2006.](https://eur-lex.europa.eu/LexUriServ/LexUriServ.do?uri=OJ:L:2006:404:0009:0025:En:PDF) Accessed: 2024-07-12.
- <span id="page-8-9"></span>Carrie Dennett. 2021. Diet's role in opioid recovery. *Today's Dietitian*.
- <span id="page-9-5"></span>Bahare Fatemi, Quentin Duval, Rohit Girdhar, Michal Drozdzal, and Adriana Romero-Soriano. 2023a. Learning to substitute ingredients in recipes. *arXiv*.
- <span id="page-9-13"></span>Bahare Fatemi, Jonathan Halcrow, and Bryan Perozzi. 2023b. Talk like a graph: Encoding graphs for large language models. *arXiv*.
- <span id="page-9-9"></span>Yifu Gao, Linbo Qiao, Zhigang Kan, Zhihua Wen, Yongquan He, and Dongsheng Li. 2024. Two-stage generative question answering on temporal knowledge graph using large language models. *arXiv*.
- <span id="page-9-17"></span>Mouzhi Ge, Francesco Ricci, and David Massimo. 2015. Health-aware food recommender system. In *RecSys*.
- <span id="page-9-15"></span>Andrea Grillo, Lucia Salvi, Paolo Coruzzi, Paolo Salvi, and Gianfranco Parati. 2019. Sodium intake and hypertension. *Nutrients*.
- <span id="page-9-26"></span>Ja K Gu, Penelope Allison, Alexis Grimes Trotter, Luenda E Charles, Claudia C Ma, Matthew Groenewold, Michael E Andrew, and Sara E Luckhaupt. 2022. Prevalence of self-reported prescription opioid use and illicit drug use among us adults: Nhanes 2005– 2016. *Journal of occupational and environmental medicine*.
- <span id="page-9-12"></span>Tiezheng Guo, Qingwen Yang, Chen Wang, Yanyi Liu, Pan Li, Jiawei Tang, Dapeng Li, and Yingyou Wen. 2024. Knowledgenavigator: Leveraging large language models for enhanced reasoning over knowledge graph. *Complex & Intelligent Systems*.
- <span id="page-9-4"></span>Steven Haussmann, Oshani Seneviratne, Yu Chen, Yarden Ne'eman, James Codella, Ching-Hua Chen, Deborah L McGuinness, and Mohammed J Zaki. 2019. Foodkg: a semantics-driven knowledge graph for food recommendation. In *The Semantic Web– ISWC 2019: 18th International Semantic Web Conference, Auckland, New Zealand, October 26–30, 2019, Proceedings, Part II 18*.
- <span id="page-9-14"></span>Xiaoxin He, Yijun Tian, Yifei Sun, Nitesh V Chawla, Thomas Laurent, Yann LeCun, Xavier Bresson, and Bryan Hooi. 2024. G-retriever: Retrieval-augmented generation for textual graph understanding and question answering. *arXiv*.
- <span id="page-9-21"></span>Xiaobao Huang, Mihir Surve, Yuhan Liu, Tengfei Luo, Olaf Wiest, Xiangliang Zhang, and Nitesh V Chawla. 2024. Application of large language models in chemistry reaction data extraction and cleaning. In *CIKM*.
- <span id="page-9-7"></span>Jinhao Jiang, Kun Zhou, Zican Dong, Keming Ye, Wayne Xin Zhao, and Ji-Rong Wen. 2023. Structgpt: A general framework for large language model to reason over structured data. In *EMNLP*.
- <span id="page-9-8"></span>Jiho Kim, Yeonsu Kwon, Yohan Jo, and Edward Choi. 2023. Kg-gpt: A general framework for reasoning on knowledge graphs using large language models. In *EMNLP*.
- <span id="page-9-16"></span>Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. 2022. Large language models are zero-shot reasoners. *NeuralIPS*.
- <span id="page-9-11"></span>Angeliki Lazaridou, Elena Gribovskaya, Wojciech Stokowiec, and Nikolai Grigorev. 2022. Internetaugmented language models through few-shot prompting for open-domain question answering. *arXiv*.
- <span id="page-9-10"></span>Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. 2020. Retrieval-augmented generation for knowledge-intensive nlp tasks. *NeuralIPS*.
- <span id="page-9-6"></span>Diya Li, Mohammed J Zaki, and Ching-hua Chen. 2023. Health-guided recipe recommendation over knowledge graphs. *Journal of Web Semantics*.
- <span id="page-9-18"></span>Peiyu Li, Xiaobao Huang, Yijun Tian, and Nitesh V Chawla. 2024. Cheffusion: Multimodal foundation model integrating recipe and food image generation. In *CIKM*.
- <span id="page-9-19"></span>Zheyuan Liu, Guangyao Dou, Zhaoxuan Tan, Yijun Tian, and Meng Jiang. 2024a. Towards safer large language models through machine unlearning. *arXiv*.
- <span id="page-9-22"></span>Zheyuan Liu, Xiaoxin He, Yijun Tian, and Nitesh V Chawla. 2024b. Can we soft prompt llms for graph learning tasks? In *WWW*.
- <span id="page-9-20"></span>Zheyuan Liu, Chunhui Zhang, Yijun Tian, Erchi Zhang, Chao Huang, Yanfang Ye, and Chuxu Zhang. 2023. Fair graph representation learning via diverse mixture-of-experts. In *WWW*.
- <span id="page-9-0"></span>Nadine Mahboub, Rana Rizk, Mirey Karavetian, and Nanne de Vries. 2021. Nutritional status and eating habits of people who use drugs and/or are undergoing treatment for recovery: a narrative review. *Nutrition reviews*.
- <span id="page-9-2"></span>Costas Mavromatis and George Karypis. 2024. Gnnrag: Graph neural retrieval for large language model reasoning. *arXiv*.
- <span id="page-9-3"></span>Grégoire Mialon, Roberto Dessì, Maria Lomeli, Christoforos Nalmpantis, Ram Pasunuru, Roberta Raileanu, Baptiste Rozière, Timo Schick, Jane Dwivedi-Yu, Asli Celikyilmaz, et al. 2023. Augmented language models: a survey. *arXiv*.
- <span id="page-9-1"></span>Weiqing Min, Chunlin Liu, Leyi Xu, and Shuqiang Jiang. 2022. Applications of knowledge graphs for food science and industry. *Patterns*.
- <span id="page-9-23"></span>NIDA. 2024. *Opioids*. [https://www.drugabuse.](https://www.drugabuse.gov/drug-topics/opioids) [gov/drug-topics/opioids](https://www.drugabuse.gov/drug-topics/opioids).
- <span id="page-9-24"></span>Khary K Rigg and Gladys E Ibañez. 2010. Motivations for non-medical prescription drug use: A mixed methods analysis. *Journal of Substance Abuse Treatment*.
- <span id="page-9-25"></span>Andrew Rosenblum, Lisa A Marsch, Herman Joseph, and Russell K Portenoy. 2008. Opioids and the treatment of chronic pain: controversies, current status, and future directions. *Experimental and Clinical Psychopharmacology*.
- <span id="page-10-16"></span>Chris Sanchez and Zheyuan Zhang. 2022. The effects of in-domain corpus size on pre-training bert. *arXiv*.
- <span id="page-10-3"></span>Oshani Seneviratne, Jonathan Harris, Ching-Hua Chen, and Deborah L McGuinness. 2021. Personal health knowledge graph for clinically relevant diet recommendations. *arXiv*.
- <span id="page-10-9"></span>Sola S Shirai, Oshani Seneviratne, Minor E Gordon, Ching-Hua Chen, and Deborah L McGuinness. 2021. Identifying ingredient substitutions using a knowledge graph of food. *Frontiers in Artificial Intelligence*.
- <span id="page-10-7"></span>Andrew Smyth, Martin J O'Donnell, Salim Yusuf, Catherine M Clase, Koon K Teo, Michelle Canavan, Donal N Reddan, and Johannes FE Mann. 2014. Sodium intake and renal outcomes: a systematic review. *American journal of hypertension*.
- <span id="page-10-12"></span>Haitian Sun, Tania Bedrax-Weiss, and William Cohen. 2019. Pullnet: Open domain question answering with iterative retrieval on knowledge bases and text. In *EMNLP-IJCNLP*.
- <span id="page-10-8"></span>Jiashuo Sun, Chengjin Xu, Lumingyuan Tang, Saizhuo Wang, Chen Lin, Yeyun Gong, Lionel Ni, Heung-Yeung Shum, and Jian Guo. 2024. Think-on-graph: Deep and responsible reasoning of large language model on knowledge graph. In *ICLR*.
- <span id="page-10-17"></span>Zhaoxuan Tan, Qingkai Zeng, Yijun Tian, Zheyuan Liu, Bing Yin, and Meng Jiang. 2024. Democratizing large language models via personalized parameterefficient fine-tuning. *arXiv*.
- <span id="page-10-23"></span>Lauren J. Tanz, Amanda T. Dinwiddie, Christine L. Mattson, Julie O'Donnell, and Nicole L. Davis. 2022. Drug overdose deaths among persons aged 10–19 years - united states, july 2019-december 2021. *Morbidity and Mortality Weekly Report*.
- <span id="page-10-15"></span>Dhaval Taunk, Lakshya Khanna, Siri Venkata Pavan Kumar Kandru, Vasudeva Varma, Charu Sharma, and Makarand Tapaswi. 2023. Grapeqa: Graph augmentation and pruning to enhance question-answering. In *WWW*.
- <span id="page-10-5"></span>Heng Wang, Shangbin Feng, Tianxing He, Zhaoxuan Tan, Xiaochuang Han, and Yulia Tsvetkov. 2024a. Can language models solve graph problems in natural language? *NeuralIPS*.
- <span id="page-10-6"></span>Wenjie Wang, Ling-Yu Duan, Hao Jiang, Peiguang Jing, Xuemeng Song, and Liqiang Nie. 2021. Market2dish: health-aware food recommendation. *TOMM*.
- <span id="page-10-18"></span>Xintao Wang, Qianwen Yang, Yongting Qiu, Jiaqing Liang, Qianyu He, Zhouhong Gu, Yanghua Xiao, and Wei Wang. 2023. Knowledgpt: Enhancing large language models with retrieval and storage access on knowledge bases. *arXiv*.
- <span id="page-10-21"></span>Zehong Wang, Sidney Liu, Zheyuan Zhang, Tianyi Ma, Chuxu Zhang, and Yanfang Ye. 2024b. Can llms convert graphs to text-attributed graphs? *arXiv*.
- <span id="page-10-20"></span>Zehong Wang, Zheyuan Zhang, Nitesh V Chawla, Chuxu Zhang, and Yanfang Ye. 2024c. Gft: Graph foundation model with transferable tree vocabulary. *arXiv preprint arXiv:2411.06070*.
- <span id="page-10-19"></span>Zehong Wang, Zheyuan Zhang, Chuxu Zhang, and Yanfang Ye. 2024d. Subgraph pooling: Tackling negative transfer on graphs. In *IJCAI*.
- <span id="page-10-4"></span>Yilin Wen, Zifeng Wang, and Jimeng Sun. 2023. Mindmap: Knowledge graph prompting sparks graph of thoughts in large language models. *arXiv*.
- <span id="page-10-0"></span>WHO. 2021. [Healthy diet.](https://www.who.int/news-room/fact-sheets/detail/healthy-diet)
- <span id="page-10-1"></span>WHO. 2023. [Obesity info page of the world health](https://www.who.int/health-topics/obesity) [organization.](https://www.who.int/health-topics/obesity)
- <span id="page-10-2"></span>Yuanbo Xu, Tian Li, Yongjian Yang, Weitong Chen, and Lin Yue. 2024. An adaptive category-aware recommender based on dual knowledge graphs. *Information Processing & Management*.
- <span id="page-10-14"></span>Michihiro Yasunaga, Hongyu Ren, Antoine Bosselut, Percy Liang, and Jure Leskovec. 2021. Qa-gnn: Reasoning with language models and knowledge graphs for question answering. In *NAACL*.
- <span id="page-10-11"></span>Wenbin Yue, Zidong Wang, Jieyu Zhang, and Xiaohui Liu. 2021. An overview of recommendation techniques and their applications in healthcare. *IEEE/CAA Journal of Automatica Sinica*.
- <span id="page-10-13"></span>Jing Zhang, Xiaokang Zhang, Jifan Yu, Jian Tang, Jie Tang, Cuiping Li, and Hong Chen. 2022. Subgraph retrieval enhanced model for multi-hop knowledge base question answering. In *ACL*.
- <span id="page-10-10"></span>Lingzi Zhang, Yinan Zhang, Xin Zhou, and Zhiqi Shen. 2024a. Greenrec: A large-scale dataset for green food recommendation. In *WWW*.
- <span id="page-10-24"></span>Zheyuan Zhang, Zehong Wang, Shifu Hou, Evan Hall, Landon Bachman, Jasmine White, Vincent Galassi, Nitesh V Chawla, Chuxu Zhang, and Yanfang Ye. 2024b. Diet-odin: A novel framework for opioid misuse detection with interpretable dietary patterns. In *KDD*.
- <span id="page-10-22"></span>Zheyuan Zhang, Zehong Wang, Tianyi Ma, Varun Sameer Taneja, Sofia Nelson, Nhi Ha Lan Le, Keerthiram Murugesan, Mingxuan Ju, Nitesh V Chawla, Chuxu Zhang, et al. 2024c. Mopi-hfrs: A multi-objective personalized health-aware food recommendation system with llm-enhanced interpretation. *arXiv*.

## <span id="page-11-0"></span>A Additional Related Work

## A.1 Prior Works in Nutrition Personalization

With growing awareness of the importance of dietary health, various studies have sought to incorporate health metrics into applications such as food recommendation systems. These approaches can be grouped into three primary categories. First, some research emphasizes single indicators like calorie or fat content, as highlighted in works by Ge et al. [\(Ge et al.,](#page-9-17) [2015\)](#page-9-17) and Shirai et al. [\(Shirai](#page-10-9) [et al.,](#page-10-9) [2021;](#page-10-9) [Li et al.,](#page-9-18) [2024\)](#page-9-18), though such metrics often fail to represent the multifaceted nature of a balanced diet. Second, simulated health data has been utilized, as demonstrated by Wang et al. [\(Wang et al.,](#page-10-6) [2021\)](#page-10-6), but these methods often diverge from real-world data distributions. Finally, recent studies have applied global health guidelines to develop composite health scores, such as those by Bolz et al. [\(Bölz et al.,](#page-8-3) [2023\)](#page-8-3) and Zhang et al. [\(Zhang et al.,](#page-10-10) [2024a\)](#page-10-10). However, foods deemed healthy by general standards can still negatively affect certain individuals [\(Yue et al.,](#page-10-11) [2021\)](#page-10-11), highlighting the absence of a universal solution. The primary challenge remains the scarcity of accurate user health data, a gap our benchmark uniquely addresses.

## A.2 Knowledge Graph Question Answering

Knowledge Graph Question Answering (KGQA) has undergone significant advancements, evolving from early approaches such as semantic parsing and retrieval-based methods. Initial models translated natural language queries into structured formats like SPARQL for execution on knowledge graphs [\(Sun et al.,](#page-10-12) [2019;](#page-10-12) [Zhang et al.,](#page-10-13) [2022\)](#page-10-13). Many of these methods employed pre-trained models like BERT for query encoding and used frameworks such as GNNs or LSTMs for retrieving entities and subgraphs [\(Yasunaga et al.,](#page-10-14) [2021;](#page-10-14) [Taunk et al.,](#page-10-15) [2023\)](#page-10-15).

More recent progress integrates large language models (LLMs) to improve both retrieval efficiency and reasoning ability [\(Sanchez and Zhang,](#page-10-16) [2022;](#page-10-16) [Liu et al.,](#page-9-19) [2024a;](#page-9-19) [Tan et al.,](#page-10-17) [2024\)](#page-10-17). Approaches like Jiang et al. [\(Jiang et al.,](#page-9-7) [2023\)](#page-9-7) and Wang et al. [\(Wang et al.,](#page-10-18) [2023\)](#page-10-18) utilize LLMs to transform queries into formats such as SQL or SPARQL, enhancing retrieval accuracy. Others, such as Kim et al. [\(Kim et al.,](#page-9-8) [2023\)](#page-9-8) and Gao et al. [\(Gao et al.,](#page-9-9) [2024\)](#page-9-9), focus on reasoning over retrieved subgraphs or triples, tackling multi-hop reasoning tasks in KGQA. However, most benchmarks in this field are designed for general-purpose datasets and fail to address domain-specific complexities, such as the challenges unique to nutritional health reasoning.

#### A.3 Graph-Retrieval Augmented Generation

Graph neural networks exhibit powerful potentials in dealing with complicated structural data [\(Wang](#page-10-19) [et al.,](#page-10-19) [2024d;](#page-10-19) [Liu et al.,](#page-9-20) [2023;](#page-9-20) [Wang et al.,](#page-10-20) [2024c\)](#page-10-20) and it can facilitate LLM to better understand real world tasks [\(Wang et al.,](#page-10-21) [2024b;](#page-10-21) [Huang et al.,](#page-9-21) [2024;](#page-9-21) [Liu et al.,](#page-9-22) [2024b\)](#page-9-22). Graph-Retrieval Augmented Generation (Graph-RAG) extends the Retrieval-Augmented Generation (RAG) framework [\(Lewis](#page-9-10) [et al.,](#page-9-10) [2020\)](#page-9-10) by enriching large language models with structured knowledge retrieval. While traditional RAG retrieves unstructured text, Graph-RAG leverages GNNs to retrieve structured subgraphs encoded as triples, improving reasoning precision and minimizing redundancy [\(Guo et al.,](#page-9-12) [2024;](#page-9-12) [Wen](#page-10-4) [et al.,](#page-10-4) [2023;](#page-10-4) [Lazaridou et al.,](#page-9-11) [2022\)](#page-9-11).

Existing Graph-RAG benchmarks primarily evaluate basic graph reasoning tasks, such as shortest paths, node degree, and edge existence [\(Fatemi](#page-9-13) [et al.,](#page-9-13) [2023b;](#page-9-13) [Wang et al.,](#page-10-5) [2024a\)](#page-10-5). Although these benchmarks provide insights into foundational reasoning, they lack domain specificity. Recent work by He et al. [\(He et al.,](#page-9-14) [2024\)](#page-9-14) introduced benchmarks targeting advanced reasoning in general graph contexts, but domain-specific benchmarks for applications such as nutrition remain underdeveloped. By adapting the principles of Graph-RAG, our work introduces the first benchmark designed to tackle personalized health-aware reasoning, addressing this critical gap in the literature.

#### <span id="page-11-1"></span>B Benchmark Details

#### B.1 Data Source Description

NHANES. National Health and Nutrition Examination Survey (NHANES) is a publicly available dataset collected by the U.S. Centers for Disease Control and Prevention (CDC) to assess the health and nutritional status of the U.S. population through interviews, physical examinations, and laboratory tests. Data is released every two years and encompasses five main categories: Demographics, Dietary Data, Examination Data, Laboratory Data, and Questionnaire Data. These comprehensive datasets provide a wealth of information on health indicators, dietary behaviors, and medical

conditions.

FNDDS and WWEIA. The Food and Nutrient Database for Dietary Studies (FNDDS) is a comprehensive resource developed by the U.S. Department of Agriculture (USDA) to facilitate dietary intake analysis by providing detailed nutritional information for foods and beverages consumed in the United States. It serves as the backbone for analyzing dietary recall data collected through the What We Eat in America (WWEIA) program, which is a component of NHANES. WWEIA captures dietary intake data through 24-hour dietary recall interviews, linking reported food and beverage items to their corresponding nutrient profiles in FNDDS. Together, FNDDS and WWEIA enable researchers to study dietary patterns, nutrient intake, and their relationship to health outcomes, making them critical tools for advancing nutrition research and public health policy.

## B.2 Dietary Habit Processing Details

Dietary habit data was sourced from various NHANES tables, including the Diet Behavior and Consumer Behavior datasets, which capture userreported behaviors and preferences related to food choices, preparation methods, and consumption patterns. Traditional processing approaches proved insufficient for the complexity and diversity of these features. To address this, a thorough manual review was conducted by a team of four researchers. Key features indicative of dietary habits, such as awareness of healthy eating practices or frequency of consuming processed or frozen foods, were identified and categorized. Users were then grouped into high and low habit categories based on their responses, with the top 10% and bottom 10% assigned corresponding habit tags. For instance, users reporting the highest milk consumption were tagged with "drink lots of milk," while those with minimal consumption were labeled as "drink little or no milk." This process generated 54 distinct dietary habit tags, which were incorporated as nodes in the graph. These habit nodes provide critical insights into user behaviors, enabling a nuanced understanding of the relationship between dietary patterns and health outcomes.

## B.3 Full Mappings of Nutrition Tags

In this section, we discuss the overall mapping relationship between health indicators and nutrition. In total, we involve nutrition tags for 16 different nutrients focusing on various health as-

<span id="page-12-0"></span>

<b>Nutrients</b>	<b>Low Threshold</b>	<b>High Threshold</b>	<b>NRV</b>
Calories (kcal)	40	225	2000
Carbohydrates $(g)$	55	75	
Protein $(g)$	10	15	50
Saturated Fat $(g)$	1.5	5	20
Cholesterol (mg)	20	40	300
Sugar $(g)$	5	22.5	
Dietary Fiber $(g)$	3	6	
Sodium (mg)	120	200	2000
Potassium (mg)	$\theta$	525	3500
Phosphorus (mg)	$\theta$	105	700
Iron $(mg)$	$\theta$	3.3	22
Calcium (mg)	$\theta$	150	1000
Folic Acid $(\mu g)$	$\theta$	60	400
Vitamin $C$ (mg)	$\theta$	15	100
Vitamin $D(\mu g)$	0	2.25	15

Table 4: Nutrient Reference Values (NRV) and thresholds (per 100g of food) used based on the nutritional standards.

<span id="page-12-1"></span>

<b>Health Indicator</b>	High Threshold	<b>Low Threshold</b>
BMI	30	18.5
Waist Circumference (cm)	102(88)	
Blood Pressure (mmHg)	140	90
Osteoporosis		
Blood Urea Nitrogen (mmol/L)	7.1	
Low-Density Lipoprotein (mmol/L)	3.3	
Red Blood Cell (million cells/uL)	$\blacksquare$	4
Glucose (mmol/L)	7	
Glycohemoglobin $(\%)$	6.5	
Hemoglobin (g/dL)		13.2 (11.6)

Table 5: Health Indicators with Corresponding High and Low Thresholds. Parentheses indicate sex-specific: male (female) thresholds where applicable.

pects, including 7 for macro-nutrients (calories, carbohydrates, protein, saturated fat, cholesterol, sugar, and dietary fiber) and 9 for micro-nutrients (sodium, potassium, phosphorus, iron, calcium, folic acid, and vitamin C, D, and B12) following the tagging scheme introduced in [\(Zhang et al.,](#page-10-22) [2024c\)](#page-10-22). A detailed table of thresholds can be seen in Table[-4.](#page-12-0) As discussed in the paper, these thresholds are derived from existing standards and legislation, from World Health Organization (WHO), Food Standards Agency (FSA)m EU Nutrition & Health Claims Regulation [\(Commission,](#page-8-5) [2006\)](#page-8-5) and the Codex Alimentarius Commission (CAC) [\(Al](#page-8-6)[imentarius,](#page-8-6) [1985,](#page-8-6) [1997\)](#page-8-7). An even more detailed standards are listed in Appendix[-I.](#page-18-0) Following the similar practice, we also extract the thresholds for health conditions, as shown in Table[-5,](#page-12-1) Since we have the thresholds for both nutrition and health, we demonstrate the full mapping relationship can be seen in Table[-6.](#page-14-0) Note that the special diet data can be retrieved from NHANES data, which directly indicates a user needs certain nutrients.

However, as we emphasize in the paper, the interactions between nutrition and health are complex and multi-facet. To maintain scientific rigor and practical relevance, we focus on annotating four prevalent health statues, of which diet has been proved to be beneficial for intervention. Their mapping to nutrition tags can be seen in Table[-7.](#page-14-1) The definition of these major health statues are discussed in the next section.

## B.4 The Definition of Health Conditions

In the paper, we focus on annotating the four prevalent health statuses—obesity, hypertension, opioid misuse, and diabetes—that are directly influenced by dietary interventions. Among them, WHO and American Heart Association (AHA) provide clear and well-known definitions for obesity and hypertension. We mark a user obesity if the BMI is 30 or greater, and we mark a user hypertension if the average of 4 test of systolic pressure is 140 mm Hg or higher or diastolic pressure is 90 mm Hg or higher. This is classified as stage-2 hypertension and require medical control. For Diabetes, NHANES provides specific questionnaire for diabetic users, and we also mark a user diabetic if the user's Glucose (mmol/L) level is over 7.0 AND Glycohemoglobin  $(\%)$  is over 6.5.

Opioid misuse, on the other hand, is a tricky health condition to be defined. However we argue this health condition is of vital importance, as the opioid crisis has been one of the most critical society concerns in the United States. Opioids are a category of drugs that include the illegal substance heroin, synthetic opioids such as fentanyl, and prescription painkillers like oxycodone [\(NIDA,](#page-9-23) [2024\)](#page-9-23). While primarily used for pain management, opioids can induce euphoria, making them prone to misuse [\(Dennett,](#page-8-9) [2021;](#page-8-9) [Rigg and Ibañez,](#page-9-24) [2010;](#page-9-24) [Rosenblum](#page-9-25) [et al.,](#page-9-25) [2008\)](#page-9-25). For instance, in 2019, 10.1 million Americans reported opioid misuse, and in 2021, there were an estimated 108,000 drug overdose deaths in the United States, 90% of which were linked to opioids [\(CDC,](#page-8-10) [2020b;](#page-8-10) [Tanz et al.,](#page-10-23) [2022\)](#page-10-23). In this work, we follow prior work [\(Zhang et al.,](#page-10-24) [2024b\)](#page-10-24) to define misuse by the following criteria: (1) records of illicit opioid drug use, like heroin, within a year, or (2) records of prescription opioid medication use for over 90 days, which is a threshold commonly employed in the medical domain [\(Gu et al.,](#page-9-26) [2022\)](#page-9-26).

NHANES dataset provides illicit drug usage data, and we can track down the opioid prescription medicine usage data using the Multum Lexicon Therapeutic Classification Scheme, a 3-level nested category system that assigns a therapeutic classification to each drug and each ingredient of the drug. Category codes used to identify prescription opioid use were: Level 1:  $57$  = central nervous system agents; Level 2:  $58 =$  Analgesics; Level 3:  $60 =$ narcotic analgesics, or  $191$  = narcotic analgesics combinations (Detail in Appendix[-I\)](#page-18-0).

#### B.5 Definitions of Ground Truth

In this section, we outline how ground truths are determined for each task. For the multi-label classification task, the process is straightforward. As discussed earlier, nutrition tags are created and linked to users' health conditions based on predefined standards. The ground truths for this task are simply the lists of nutrition tags relevant to each user's health profile.

For the binary classification task, we use the relationship between the user's condition and the food's nutrition tags. A "Yes" label is assigned if the relationship is a "match," and "No" is assigned if the relationship is a "contradict." In the case of complex question settings, where multiple "match" and "contradict" links exist, we calculate the count of each. A question is marked as "Yes" if the number of "match" links exceeds the number of "contradict" links.

For the text generation task, we generate reference texts using a combined approach. First, the overall healthiness of the food is determined using the binary classification result ("Yes" or "No"). This is followed by a natural language explanation that lists the relevant nutrition tags. For example, a reference text might read: "Yes, because the food is low in calories and high in protein." This method ensures that the reference text provides a clear and natural explanation for the decision.

#### <span id="page-13-0"></span>C Implementation Details

In this section, we discuss the implementation details of the baseline models. Specially how we set the hyper-parameters and how we make adaption to our task. All codes all provided in the codebase mentioned in the abstract.

Plain refers to a naive GraphRAG pipeline. Unlike approaches that directly input natural language text or tabular data, we transform the user and food information from the knowledge graph structure into multiple triples, each consisting of an entity, a relationship, and another entity, then concatenate them before feeding into the LLMs.

<span id="page-14-0"></span>

Table 6: Nutrient Categories, Tag Names, and Associated Source Health Indicators. Nutrient categories are organized to consolidate related tags and their respective health indicators for clarity.

<span id="page-14-1"></span>

<b>Health Indicator</b>	<b>Associated Tags</b>
Obesity	Low Calorie
<b>Opioid Misuse</b>	High Protein; Low Sugar; Low Sodium
Hypertension	Low Sodium
Diabetes	Low Sugar; Low Carb
Weight Loss/Low Calorie Diet	Low Calorie
Low Fat/Low Cholesterol Diet	Low Cholesterol; Low Saturated Fat
Low Salt/Low Sodium Diet	Low Sodium
Sugar-Free/Low Sugar Diet	Low Sugar
Diabetic Diet	Low Sugar; Low Carb
Weight Gain/Muscle Building Diet	High Calorie; High Protein
Low Carbohydrate Diet	Low Carb
High Protein Diet	High Protein
Renal/Kidney Diet	Low Protein

Table 7: Health Indicators and Their Associated Nutritional Tags. Each indicator is linked to relevant tags reflecting dietary requirements.

KAPING answers questions based on a subgraph composed of the entities mentioned in the query and their neighboring nodes. Following the methodology described in the original paper, we first extract the entities present in the query—specifically the user and food—from the provided knowledge graph. Then, we include their respective neighboring nodes to construct a subgraph via retrieval. This subgraph is subsequently transformed into triples and concatenated before feeding into the LLMs. Note that in the original implementation, the authors also used top-k filtering to prune the retrieval results. However, since we don't have any other entities in the question, this pruning based on embedding similarities with the question doesn't generate any reasonable results. We skip this step in our implementation.

CoT-Zero is a two-stage prompting stategy. In

the first stage, "Let's think step by step" is appended after the question to guide the model towards producing a reasoning path. In the second stage, the reasoning path is fed to the model to extract the final answer. However, our initial experiments showed that we can combine these two steps, by having both "Let's think step by step" and final output requirements in one prompt, while still achieving the same performance. This allows us to save computational and API resources, avoiding potential inconsistencies and information loss that arise when feeding the reasoning output into a second step. This is because with the one-step approach, the model can make a final decision based on both the original graph, and its own reasoning path, whereas in the second-step approach, the original graph is not available to the model.

CoT-BAG is designed to improve the graph reasoning capabilities of LLMs by first encouraing the model to "build" an implicit graph representation of the problem, and then using chain-of-thought reasoning to solve it. For this approach, a single prompt is sufficient to guide the model through both the graph construction and reasoning, by combining both "Let's construct a graph from the given nodes and edges" and "Let's think step by step to arrive at the final answer". Adapting CoT-BaG to our benchmark requires creating a textual description of the graph triples, in the following format: "The graph contains an edge between node [source] and node [target] with attribute [relationship], an

<span id="page-15-1"></span>

<b>Question Level</b> Method				a) Binary Classification (-B)			b) Multi-label Classification (-ML)				c) Text Generation (-TG)			
		Accuracy	Recall	Precision	F1	Accuracy	Recall	Precision	F1	<b>ROUGE-1</b>	<b>ROUGE-2</b>	<b>ROUGE-L</b>	<b>BLEU</b>	<b>BERT</b>
	Plain	0.6161	0.2413	0.8619	0.3770	0.2190	0.8958	0.2365	0.3666	0.5645	0.4999	0.5642	0.3092	0.9375
	<b>KAPING</b>	0.5329	0.0732	0.6268	0.1310	0.1951	0.8885	0.2194	0.3468	0.5374	0.4678	0.5370	0.2759	0.9346
<b>Sparse</b>	CoT-Zero	0.6049	0.2885	0.7255	0.4128	0.3633	0.7636	0.4265	0.5263	0.5593	0.5016	0.5589	0.3424	0.8871
	CoT-BAG	0.6060	0.2875	0.7307	0.4126	0.4204	0.7430	0.4724	0.5589	0.5479	0.4888	0.5474	0.3325	0.8849
	ToG	0.8483	0.6959	0.9844	0.8154	0.3227	0.9561	0.3168	0.4672	0.7216	0.6793	0.7215	0.4997	0.9582
	Plain	0.5903	0.2584	0.8871	0.4002	0.5651	0.9224	0.5665	0.6932	0.7746	0.7074	0.7344	0.5513	0.9656
	<b>KAPING</b>	0.4809	0.0480	0.6216	0.0891	0.4830	0.8954	0.5064	0.6391	0.7203	0.6368	0.6835	0.4748	0.9594
<b>Standard</b>	CoT-Zero	0.6576	0.3528	1.0000	0.5216	0.5373	0.9963	0.5429	0.6948	0.7333	0.6446	0.7058	0.4940	0.9507
	CoT-BAG	0.5872	0.2197	1.0000	0.3603	0.5585	0.9984	0.5599	0.7084	0.5479	0.4888	0.5474	0.3325	0.8849
	ToG	0.8647	0.7443	1.0000	0.8534	0.8242	0.9238	0.8437	0.8745	0.8870	0.8292	0.8227	0.6959	0.9775
	Plain	0.6249	0.0424	0.3562	0.0758	0.6790	0.8679	0.7695	0.8108	0.7608	0.6814	0.7136	0.5102	0.9604
	<b>KAPING</b>	0.6302	0.0473	0.4143	0.0849	0.6549	0.8501	0.7522	0.7915	0.7446	0.6644	0.7032	0.4910	0.9587
<b>Complex</b>	CoT-Zero	0.6639	0.0750	0.9787	0.1394	0.7466	0.9729	0.7693	0.8562	0.7474	0.6597	0.7107	0.5053	0.9475
	CoT-BAG	0.6621	0.0685	1.0000	0.1282	0.7533	0.9628	0.7783	0.8577	0.7468	0.6620	0.7076	0.5051	0.9470
	ToG	0.7219	0.2936	0.8295	0.4337	0.6871	0.7160	0.8952	0.7846	0.8177	0.7424	0.7651	0.5978	0.9692

Table 8: Experimental results based on five baseline methods on the three tasks with the three question levels using the Llama-3.1-70B-instruct. The best performance of each group is bolded.

<span id="page-15-2"></span>

<b>Ouestion Level</b> Method		a) Binary Classification (-B)					b) Multi-label Classification (-ML)				c) Text Generation (-TG)			
		Accuracv	Recall	Precision	F1	Accuracy	Recall	Precision	F1	<b>ROUGE-1</b>	<b>ROUGE-2</b>	<b>ROUGE-L</b>	<b>BLEU</b>	<b>BERT</b>
	Plain	0.5363	0.0384	0.9573	0.0739	0.1965	0.8102	0.2720	0.3770	0.4572	0.3806	0.4556	0.2137	0.9200
	<b>KAPING</b>	0.5370	0.0399	0.9588	0.0766	0.1960	0.8120	0.2713	0.3769	0.4565	0.3798	0.4548	0.2135	0.9199
<b>Sparse</b>	CoT-Zero	0.5324	0.0301	0.9535	0.0583	0.2535	0.8273	0.3934	0.4664	0.4350	0.3575	0.4334	0.1992	0.8728
	CoT-BAG	0.5885	0.2983	0.6607	0.4110	0.2698	0.8720	0.3523	0.4693	0.4498	0.3767	0.4485	0.2116	0.8777
	ToG	0.6336	0.4025	0.7109	0.5140	0.2100	0.7045	0.2493	0.3563	0.4480	0.3441	0.4432	0.1940	0.9074
	Plain	0.5268	0.1054	1.0000	0.1907	0.4599	0.8212	0.5386	0.6216	0.6260	0.5178	0.6067	0.3607	0.9380
	<b>KAPING</b>	0.5245	0.1007	1.0000	0.1830	0.4606	0.8214	0.5396	0.6228	0.6272	0.5192	0.6076	0.3623	0.9387
<b>Standard</b>	CoT-Zero	0.4917	0.0391	1.0000	0.0753	0.5280	0.8426	0.6216	0.6881	0.5854	0.5708	0.4747	0.3213	0.9120
	CoT-BAG	0.5953	0.3100	0.8049	0.4476	0.5654	0.8577	0.6222	0.7073	0.6147	0.5128	0.5968	0.3504	0.9184
	ToG	0.8385	0.7630	0.9178	0.8333	0.5151	0.7613	0.5774	0.6378	0.6302	0.5061	0.5985	0.3526	0.9284
	Plain	0.6627	0.0799	0.8909	0.1467	0.5991	0.7924	0.7511	0.7482	0.6636	0.5725	0.6432	0.3953	0.9402
	<b>KAPING</b>	0.6645	0.0865	0.8833	0.1575	0.5998	0.7884	0.7518	0.7458	0.6637	0.5713	0.6452	0.3934	0.9400
Complex	CoT-Zero	0.6467	0.0277	0.9444	0.0539	0.6352	0.7831	0.8071	0.7761	0.6300	0.5339	0.6149	0.3574	0.9184
	CoT-BAG	0.6556	0.2186	0.5654	0.3153	0.6295	0.7686	0.7996	0.7712	0.6506	0.5619	0.6321	0.3829	0.9223
	ToG	0.7710	0.7732	0.6565	0.7101	0.5224	0.6157	0.7529	0.6408	0.6296	0.5114	0.5981	0.3500	0.9267

Table 9: Experimental results based on five baseline methods on the three tasks with the three question levels using the GPT-3.5-turbo. The best performance of each group is bolded.

edge between..." to include in the input prompt, alongside the question, and output requirements.

ToG introduces a strategy that iteratively searches and prunes reasoning paths on a knowledge graph starting from entities mentioned in the query to identify suitable paths. However, the opensource ToG codebase is implemented based on Wikidata and Freebase databases, making it incompatible with private datasets. To evaluate ToG on our benchmark, we reimplemented it following the original methodology. Furthermore, we adapted ToG to better suit the characteristics of our benchmark with the following adjustments: 1). Adjusting the width parameter to 5: ToG's original width parameter is set to 3, which retains three reasoning paths during pruning. However, answering questions in our benchmark sometimes requires more than three reasoning paths. By setting the width parameter to 5, ToG preserves five reasoning paths at each pruning step and generates answers based on these paths. 2). Delaying pruning until the second iteration: In ToG's first iteration, the information gathered is often insufficient to evaluate the importance of each reasoning path. Pruning

too early risks discarding paths that may be critical for answering the query. Delaying pruning allows ToG to collect more comprehensive information before making pruning decisions. These modifications ensure that ToG is better aligned with the requirements and complexities of our benchmark, enabling more effective performance evaluation.

## <span id="page-15-0"></span>D Additional Experiments

To further demonstrate the performance of different LLM backbones on our benchmark, we conducted additional tests using Llama-3.1-70b-Instruct and GPT-3.5-Turbo as backbones for various baselines. As shown in Table[-8](#page-15-1) and Table[-9,](#page-15-2) the performance trends of Llama-3.1-70b-Instruct align closely with those of GPT-4o-mini, although Llama-3.1-70b-Instruct generally yields better results. This is consistent with its stronger reasoning capabilities.

Additionally, ToG exhibited a noticeable performance degradation when GPT-3.5-Turbo was used as the backbone, particularly when addressing standard and complex questions. This decline is primarily due to GPT-3.5-Turbo's relatively weaker reasoning abilities, which often lead to the retrieval

<span id="page-16-2"></span>

Diet Type	<b>Obesity</b>	<b>Hypertension</b>	<b>Opioid Misuse</b>	<b>Diabetes</b>
Weight Loss/Low Calorie Diet	2,253	647	222	267
Low Fat/Low Cholesterol Diet	448	247	76	116
Low Salt/Low Sodium Diet	442	350	86	115
Sugar-Free/Low Sugar Diet	170	89	20	78
Diabetic Diet	692	432	126	647
Weight Gain/Muscle Building Diet	3	20	12	
Low Carbohydrate Diet	244	69	25	57
<b>High Protein Diet</b>	47	12	9	8
Renal/Kidney Diet	25	24	13	7

Table 10: Adoption of Diet Types Across Health Conditions. Each entry represents the number of users with a specific condition following a corresponding diet type.

<span id="page-16-1"></span>

Table 11: Distribution of Users Across Health Conditions and Special Diets.

of suboptimal information. Such information provides minimal support—or even introduces negative impacts—on subsequent answer generation. These two sets of experiments highlight the stringent reasoning requirements imposed by our benchmark on the tested models.

# <span id="page-16-0"></span>E Additional Statistics

In addition to the basic statistics provided above, we also provide an in detailed benchmark discussing the user distribution on health conditions and the overlap between the four major conditions and the special diets.

Spanning from 2003 to 2020, the latest available NHANES data includes a total of 95,872 unique users. Table[-11](#page-16-1) illustrates the distribution of health conditions across this population, highlighting the significant prevalence of obesity (18,271 users) and hypertension (10,257 users). These numbers emphasize the widespread impact of these conditions on public health and underscore the urgent need for dietary interventions. However, the stark contrast between the prevalence of these conditions and the adoption of relevant dietary interventions—such as low-calorie diets (4,693 users) or low-sodium diets (1,037 users)—reveals a significant gap. While conditions like obesity and hypertension demand immediate dietary action, far fewer individuals engage in corresponding interventions. This disparity highlights the critical need for personalized dietary reasoning to encourage healthier eating habits tailored to individual health conditions.

A similar trend emerges in Table[-10,](#page-16-2) which examines the alignment between specific health conditions and diet types. While there is some adoption of relevant dietary actions, such as weight loss diets (2,253 for obesity, 647 for hypertension) and low-sodium diets (442 for obesity, 350 for hypertension), these numbers remain disproportionately low relative to the overall prevalence of these conditions. The gap is even more pronounced for diabetes, where fewer than half of diagnosed individuals (647 users) follow diabetic diets out of 3,837 diagnosed users. Specialized interventions, such as renal/kidney or muscle-building diets, see minimal adoption across all conditions, suggesting a lack of accessibility or awareness for these targeted approaches. These patterns reinforce the need for tailored, actionable dietary recommendations to address the divide between health condition prevalence and effective dietary responses, ensuring broader access to appropriate and impactful interventions.

<span id="page-17-0"></span>

<b>Role</b>		Category	<b>Content</b>
<b>System</b>			"Act as a nutritionist. Analyze if a given food is healthy to a user following further instructions."
	<b>Ouestion</b>		"Based on the nutrients the food provides and the user needs, please answer whether the food 'Fish curry with rice' is healthy for the user?"
	<b>Method</b>	<b>Default</b>	"Below is the extra information you use to answer the question, note that you should not use your general knowledge and the answer is among this information."
	prompt <b>Customized</b>		$W_{\ldots}$ "
	<b>Textualized graph</b>		(Fish curry with rice belongs to Seafood mixed dishes), (Fish curry with rice has fish curry), (Fish curry with rice contains high sodium)
<b>User</b>		<b>Binary</b> classification	"Your output will strictly be Yes or No with no other words."
	<b>Task</b> prompt	Multi-label classification	"Your output must be strictly formatted as a comma- separated list of nutrients prefixed with "high" or "low", based solely on the provided options: carb, protein, sugar, sodium, cholesterol, saturated fat, calorie. For example, a valid output would be: high carb, low protein, high sugar. No extra words or deviations are allowed."
		<b>Text</b> generation	"Your output must consist of "Yes" or "No", followed by a list of nutrients addressed with "high" or "low," selected from the following options: carb, protein, sugar, sodium, cholesterol, saturated fat, and calorie. For example, a valid output would be: Yes, because the food is high in carb, low in protein, high in sugar. Ensure the output adheres to this format without any additional words or deviations."

Figure 7: The paradigm of prompt for final output.

<span id="page-17-1"></span>

Role	<b>Content</b>
System	"Identify the top- <width> reasoning paths that are most likely to lead to the answer for the query. Please respond with the indices of the reasoning paths, starting from 1, and separate them with commas (e.g., <math>1, 2, 5</math>). Include nothing else in your response."</width>
User	"The query is <question>, and the reasoning paths are: <reasoning list="" path="">. Your selected top-<width> reasoning paths are:"</width></reasoning></question>

Figure 8: The prompt used in ToG.

# F Prompt Design

In this section, we will demonstrate our carefully designed prompts for the three task settings and selected baselines. The principle of our prompt design is to let LLMs become familiar with nutritional domain knowledge while avoiding providing

# explicit guidance.

When querying LLMs for the final output, the paradigm of our prompt is shown as Figure[-7.](#page-17-0) The system prompt is fixed while the user prompt consists of four flexible parts: *question*, *method prompt*, *textualized graph*, and *task prompt*. The *question* and *task prompt* will be automatically adjusted according to the experiment settings. The *method prompt* can be customized to the methods proposed by the benchmark users, e.g., adding "Let's think step by step." for CoT-Zero and adding "Let's construct a graph from the given nodes and edges" for CoT-BAG. We encourage benchmark users to further explore the potential of method prompts. The *textualized graph* is by default generated by concatenating the triplets in the retrieved knowledge graph. Benchmark users can also customize their own textualization method.

Additionally, the prompt we used to prune the relations and entities when testing ToG is shown in Figure[-8.](#page-17-1)

## G Case Study

We present 7 case studies across 3 Tasks (Binary Classification, Multi-label Classification, Text Generation), 3 Question Levels (Sparse, Standard, Complex) and 5 Baselines (Plain, KAPING, CoT-Zero, CoT-BaG, ToG). This section provides insights into how the prompts are structured across different baselines and the reasoning path behind the LLM's final answer, as detailed in Tables [12-](#page-19-0)[18.](#page-25-0) The case studies provide critical insights into the strengths and limitations of each baseline, while emphasizing the challenges posed by personalized dietary reasoning, highlighting our benchmark's role in advancing the development of robust, domain-specific AI models for personalized health-aware nutrition reasoning.

# <span id="page-18-1"></span>H Addtional Error Analysis

Our experiments showed that in the specific task of health-aware nutrition reasoning, LLMs are prone to two main types of errors: contextual hallucination and factual hallucination. To understand these shortcomings, we perform an error analysis focusing on the Text Quality Evaluation task, using 3 methods (KAPING, CoT-Zero, ToG) as a representative setting. We prompt the models to also include the reasonings behind their final answer, which then go through a human review process, revealing 2 types of reasoning failures: Contextual Hallucination and Factual Hallucination. Note that we do not check for KG topology errors, as our KG generation process ensures there are no structural problems in the knowledge base that would affect the model's information retrieval and processing performance. Exemplary demonstrations of these 2 error types are shown in Table[-19](#page-26-0) and Table[-20.](#page-27-0)

## <span id="page-18-0"></span>I Standards and Regulation

In this section, we provide the standards and regulations used in this paper and attach their links of original document in footnote. There in general three categories: [1](#page-18-2)) The FNDDS category code  $<sup>1</sup>$ </sup> used for filtering food candidates (Figure[-9\)](#page-27-1). 2) Nu-trition claim regulations from WHO, FSA<sup>[2](#page-18-3)</sup>, CAC<sup>[3](#page-18-4)[4](#page-18-5)</sup>, and EU legislation<sup>[5](#page-18-6)</sup>. used for defining nutrition

thresholds (Figure[-10](#page-28-0) and Figure[-11\)](#page-29-0) . Note that since there are discrepancies in the regulation. We adopt a stricter measure and make it sure it fits NHANES data. The Vitamins and Minerals high thresholds are calculated from the Daily Nutritional Reference Value (NRV), where CAC defines if a food (per 100g) contains over 15% of NRV, it can claim itself a source of such nutrient. The Codex Alimentarius, or "Food Code" is a collection of standards, guidelines and codes of practice adopted by the Codex Alimentarius Commission. The Commission, also known as CAC, is the central part of the Joint FAO/WHO Food Standards Program and was established by FAO and WHO to protect consumer health and promote fair practices in food trade. 3) The Multum Lexicon Therapeutic Classifi-cation Scheme<sup>[6](#page-18-7)</sup>, used to define opioid prescription medicines and later mark opioid misuse (Figure-[12\)](#page-30-0).

<span id="page-18-2"></span><sup>&</sup>lt;sup>1</sup>Full documention of FNDDS at [here](https://www.ars.usda.gov/ARSUserFiles/80400530/pdf/fndds/2021_2023_FNDDS_Doc.pdf)

<span id="page-18-3"></span><sup>&</sup>lt;sup>2</sup>[FSA Guideline](https://www.food.gov.uk/sites/default/files/media/document/fop-guidance_0.pdf)

<span id="page-18-4"></span><sup>&</sup>lt;sup>3</sup>[Guidelines on Nutrition Labeling](https://www.fao.org/fao-who-codexalimentarius/sh-proxy/en/?lnk=1&url=https%253A%252F%252Fworkspace.fao.org%252Fsites%252Fcodex%252FStandards%252FCXG%2B2-1985%252FCXG_002e.pdf)

<span id="page-18-6"></span><span id="page-18-5"></span><sup>4</sup>[Guidelines for Use of Nutrition and Health Claims](https://www.fao.org/fao-who-codexalimentarius/sh-proxy/en/?lnk=1&url=https%253A%252F%252Fworkspace.fao.org%252Fsites%252Fcodex%252FStandards%252FCXG%2B23-1997%252FCXG_023e.pdf)

<sup>5</sup>[EU Nutrition & Health Claims Regulation legislation](https://eur-lex.europa.eu/LexUriServ/LexUriServ.do?uri=OJ%3AL%3A2006%3A404%3A0009%3A0025%3AEn%3APDF) [\(EC\)](https://eur-lex.europa.eu/LexUriServ/LexUriServ.do?uri=OJ%3AL%3A2006%3A404%3A0009%3A0025%3AEn%3APDF)

<span id="page-18-7"></span><sup>6</sup> Full document of Multum Lexicon Therapeutic Classification Scheme at [here](https://meps.ahrq.gov/data_stats/download_data/pufs/h68/h68f18cb.pdf)

<span id="page-19-0"></span>

Table 12: Case Study 1



Table 13: Case Study 2



Table 14: Case Study 3



Table 15: Case Study 4



Table 16: Case Study 5



Table 17: Case Study 6

<span id="page-25-0"></span>

Table 18: Case Study 7

<span id="page-26-0"></span>

Table 19: Error Analysis 1

<span id="page-27-0"></span>

Table 20: Error Analysis 2

<span id="page-27-1"></span>

Figure 9: FNDDS Category Code - Mixed Dishes.

# Table of conditions for nutrient content claims

<span id="page-28-0"></span>

Figure 10: Guidelines for use of nutrition and health claims.

<span id="page-29-0"></span>

Figure 11: Daily nutrition value from Codex Alimentarius.

<span id="page-30-0"></span>

TC1S1 1	MULTUM THERAPEUT SUB-SUB-CLASS FOR TC1S1	3.0	NUM	92 94
	VALUE			UNWEIGHTED
	-9 NOT ASCERTAINED			2,549
	-1 INAPPLICABLE			111,353
	38 VIRAL VACCINES			40
	50 MISCELLANEOUS ANALGESICS			922
	60 NARCOTIC ANALGESICS 61 NONSTEROIDAL ANTI-INFLAMMATORY AGENTS			5,447 8,158
	62 SALICYLATES			2,640
	63 ANALGESIC COMBINATIONS			524
	69 BENZODIAZEPINES			2,989
	70 MISC ANXIOLYTICS, SEDATIVES AND HYPNOTICS			3,851
	76 MISCELLANEOUS ANTIDEPRESSANTS (CONT'D ON NEXT PAGE)			93
TC1S1 1	MULTUM THERAPEUT SUB-SUB-CLASS FOR TC1S1	3.0	NUM	92 94
	VALUE			UNWEIGHTED
	(CONT'D FROM PREVIOUS PAGE)			
	77 MISCELLANEOUS ANTIPSYCHOTIC AGENTS			538
	89 ANTICHOLINERGICS/ANTISPASMODICS			459
	102 CONTRACEPTIVES			4,496
	126 METHYLXANTHINES 137 TOPICAL ANTI-INFECTIVES			96 86
	138 TOPICAL STEROIDS			1,948
	139 TOPICAL ANESTHETICS			327
	140 MISCELLANEOUS TOPICAL AGENTS			200
	141 TOPICAL STEROIDS WITH ANTI-INFECTIVES			114
	143 TOPICAL ACNE AGENTS			686
	144 TOPICAL ANTIPSORIATICS 149 SPERMICIDES			69 3
	154 LOOP DIURETICS			3,862
	155 POTASSIUM-SPARING DIURETICS			1,012
	156 THIAZIDE DIURETICS			5,996
	157 CARBONIC ANHYDRASE INHIBITORS			21
	159 FIRST GENERATION CEPHALOSPORINS 160 SECOND GENERATION CEPHALOSPORINS			730 110
	161 THIRD GENERATION CEPHALOSPORINS			224
	163 OPHTHALMIC ANTI-INFECTIVES			553
	164 OPHTHALMIC GLAUCOMA AGENTS			2,215
	165 OPHTHALMIC STEROIDS			348
	166 OPHTHALMIC STEROIDS WITH ANTI-INFECTIVES			148
	167 OPHTHALMIC ANTI-INFLAMMATORY AGENTS 168 OPHTHALMIC LUBRICANTS AND IRRIGATIONS			308 263
	170 OTIC ANTI-INFECTIVES			62
	171 OTIC STEROIDS WITH ANTI-INFECTIVES			183
	173 HMG-COA REDUCTASE INHIBITORS			21,917
	178 SKELETAL MUSCLE RELAXANTS			3,866
	180 ADRENERGIC BRONCHODILATORS 181 BRONCHODILATOR COMBINATIONS			5,916
	182 ANDROGENS AND ANABOLIC STEROIDS			3,058 359
	183 ESTROGENS			1,593
	185 PROGESTINS			233
	186 SEX HORMONE COMBINATIONS			194
	191 NARCOTIC ANALGESIC COMBINATIONS			8,625
	193 ANTIMIGRAINE AGENTS 195 5HT3 RECEPTOR ANTAGONISTS			856 665
	196 PHENOTHIAZINE ANTIEMETICS			782
	197 ANTICHOLINERGIC ANTIEMETICS			729
	198 MISCELLANEOUS ANTIEMETICS			335
	201 BARBITURATE ANTICONVULSANTS			233
	203 BENZODIAZEPINE ANTICONVULSANTS			3,846
	204 MISCELLANEOUS ANTICONVULSANTS 205 ANTICHOLINERGIC ANTIPARKINSON AGENTS			14 318
	208 SSRI ANTIDEPRESSANTS			10,282
	209 TRICYCLIC ANTIDEPRESSANTS			1,513
	211 PLATELET AGGREGATION INHIBITORS			2,631
	(CONT'D ON NEXT PAGE)			

Figure 12: Multum Lexicon Therapeutic Classification Scheme - Part of Level 3.