WIGGLYEYES: Inferring Eye Movements from Keypress Data

YUJUN ZHU, Aalto University, Finland DANQING SHI, Aalto University, Finland HEE-SEUNG MOON, Chung-Ang University, Korea ANTTI OULASVIRTA, Aalto University, Finland

Fig. 1. We present WIGGLYEYES, a model for gaze inference, designed to infer a user's eye movements based on keypress data. (a) The model takes a sequence of keypresses consisting of positions and tap times as input, and outputs a sequence of fixations with positions and durations. (b) To overcome the limitations of human data availability, we train the model using augmented data that combines real-world human data and simulated user data. (c) WIGGLYEYES supports individual-level inference by adapting to each user's previous trial data, enabling the model to predict personalized eye movements for the current trial.

We present a model for inferring where users look during interaction based on keypress data only. Given a key log, it outputs a scanpath that tells, moment-by-moment, how the user had moved eyes while entering those keys. The model can be used as a proxy for human data in cases where collecting real eye tracking data is expensive or impossible. Our technical insight is three-fold: first, we present an inference architecture that considers the individual characteristics of the user, inferred as a low-dimensional parameter vector; second, we present a novel loss function for synchronizing inferred eye movements with the keypresses; third, we train the model using a hybrid approach with both human data and synthetically generated data. The approach can be applied in interactive systems where predictive models of user behavior are available. We report results from evaluation in the challenging case of touchscreen typing, where the model accurately inferred real eye movements.

Authors' addresses: Yujun Zhu, Aalto University, Finland; Danqing Shi, Aalto University, Finland; Hee-Seung Moon, Chung-Ang University, Korea; Antti Oulasvirta, Aalto University, Finland.

© 2024 Association for Computing Machinery.

Manuscript submitted to ACM

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

Additional Key Words and Phrases: Gaze movement, touchscreen typing, amortized inference

ACM Reference Format:

Yujun Zhu, Danqing Shi, Hee-Seung Moon, and Antti Oulasvirta. 2024. WIGGLYEYES: Inferring Eye Movements from Keypress Data. 1, 1 (December 2024), [16](#page-15-0) pages.<https://doi.org/10.1145/nnnnnnn.nnnnnnn>

1 INTRODUCTION

Many computer applications have access to keypress data, but few have access to eye tracking data. Eye trackers are specialized instruments mostly used by researchers and professionals. However, knowing what users look at would be generally informative. Visual attention hints at what they are interested in, where they make errors, what they struggle with, and generally how they process the task [\[11,](#page-14-0) [15,](#page-15-1) [30\]](#page-15-2). While previous work has looked at computational inference of gaze deployment from video image [\[5,](#page-14-1) [21,](#page-15-3) [23\]](#page-15-4), this approach is impractical because of privacy reasons. *In this paper, we ask if machine learning could be used to infer eye movements given keypress data only.*

We propose a computational model called WIGGLYEYES for inferring gaze movement from keypress data. We assume a keylog data that includes the positions and timestamps of touch events on a mobile device. The output is a *scanpath*: a sequence of fixations with positions and durations. Our key contribution is a deep learning architecture for efficient real-time inference of eye movements from a stream of keypress data. To tackle the issue of data scarcity, we train our model using both real human data and synthetically generated scanpaths. To account for individual differences, we represent latent factors in the model and infer them from sample observations from the user. This allows us to deal with a large range of differences with a low-parametric representation. We also introduce a novel loss function that utilizes temporal and spatial information in keypress data to predict scanpaths. In particular, it exploits events where the eye is guiding the finger or where the eye is validating information. This function takes into account temporal dynamics and aims to improve accuracy.

The approach has generality: it can be applied to cases where (1) user simulations are available and (2) keypress and eye movement data are sufficiently correlated. As our application case in this paper, we focus on the case of mobile typing, which fulfills both criteria. In typing, visual attention has multiple roles: it is needed to proofread (check) typed text, guide fingers, locate keys, and check the state of the keyboard. Finger movements, on the other hand, are mainly reserved for typing characters, pressing special buttons, and backspacing. In this application case, WIGGLYEYES demonstrates its ability to not only reproduce highly similar patterns in scanpaths, but also replicate aggregate statistics of performance in touchscreen typing, such as gaze shifts and the time ratio for gaze on the keyboard. Moreover, we show that it can cover a significant chunk of individual variability. In Section 4 we illuminate the specific gaze–keypress associations in typing by reanalyzing an empirical dataset [\[17\]](#page-15-5).

To our best knowledge, WIGGLYEYES is the first to infer gaze movement from typing logs at both individual and population levels, including fixations and positions. It predicts an individual user's gaze movement based on their key log and performance from a few typing trials. Furthermore, it is image-free, enabling its application on typing datasets collected from diverse keyboards, which would otherwise be inaccessible. In summary, this paper makes the following contributions:

- We introduce a neural network design for amortized inference of gaze movements from keypress logs. We demonstrate the method in touchscreen typing.
- We conduct analysis of eye-hand coordination in touchscreen typing, which emphasis on the correlations between eye and finger movement.

• We report results from against a dataset reporting eye movements in touchscreen typing [\[17\]](#page-15-5).

2 RELATED WORK

This section reviews related work on eye tracking, eye-hand coordination, and eye-movement prediction, and highlights the research gap.

2.1 Eye Tracking

Eye tracking is a sensor-based technique used to estimate the deployment of human gaze in interactive tasks, including both spatial (positions) and temporal information (durations) [\[4,](#page-14-2) [10,](#page-14-3) [34,](#page-15-6) [38\]](#page-15-7). Eye tracking has become a valuable asset in empirical research in HCI, because it can reveal which elements on a screen captures attention, how efficiently users process visual information, and where potential usability issues may arise [\[11\]](#page-14-0). It is commonly used to evaluate user interfaces and inform interaction design. For example, it can inform if a design is not well-aligned with users' expectations [\[15\]](#page-15-1). Eye-trackers offer several features (e.g., pupil dilation, fixation durations) that are correlated with experienced workload [\[30\]](#page-15-2).

While eye trackers have become more affordable and accessible, the availability of eye tracking datasets is still limited due to the time and cost involved in collecting the data. Some researchers have used web cameras [\[29\]](#page-15-8) or mouse clicks [\[37\]](#page-15-9) to gather human attention data online, but these methods may not provide the same quality of data as eye tracking and often require additional hardware or effort. One previous study focused on eye tracking during touchscreen typing, collecting accurate eye movement data from 30 participants and revealing patterns of eye movements [\[17\]](#page-15-5). Comparatively, incorporating eye tracking into everyday activities such as typing is challenging, as it is not feasible to include eye trackers in commodity devices. This raises the question of how we can estimate eye tracking data directly from other, more commonly available measurements.

2.2 Eye-hand Coordination

Most graphical user interfaces require users to coordinate the movement of eyes and end-effectors [\[2,](#page-14-4) [20\]](#page-15-10). Coordination, which requires cognitive control, is essential for succeeding in tasks such as locating, pointing, and manipulating objects on display, where precise control over visual targets and hand movements is required [\[24\]](#page-15-11). Effective eye-hand coordination is associated with accuracy, task efficiency, and cognitive load. For example, users often rely on rapid, coordinated visual and manual responses to interact with GUIs. When the visual feedback and motor responses are aligned, interaction is argued to be more fluid and intuitive [\[3\]](#page-14-5). By contrast, misaligned or lagging feedback can result in user frustration and decreased productivity [\[1\]](#page-14-6).

In touchscreen typing [\[17\]](#page-15-5), there is a significant correlation between eye and finger movements. Users look at the keyboard about 70% of the time when using one finger and 60% of the time when using two thumbs. They glance at the text for proofreading about four times per sentence, with the average sentence length being 20 characters. These patterns can be simulated using reinforcement learning [\[33\]](#page-15-12). CRTypist simulates eye-hand coordination on touchscreens, incorporating finger and eye movement data. The model controls vision and finger movements based on working memory, shedding light on the correlation between eye and finger movement during typing. To sum up, these studies suggest that even in complex activities like typing, there may be enough information in keypresses to warrant inferring where eyes are simultaneously.

2.3 Eye Movement Prediction

There are numerous models that predict users' deployment of attention on graphical displays either in free-viewing or search tasks. These models can be divided into two classes on account of two of the modelled control processes: bottom-up and top-down [\[14\]](#page-14-7). Bottom-up attention is driven by visually distinct (salient) stimuli [\[22\]](#page-15-13), such as information that is highlighted on screen [\[25\]](#page-15-14). Top-down attention is shaped by user's goal. Visual search is a good example [\[26\]](#page-15-15). Here the task is to predict attention given a display and a target.

In addition to these two areas, previous work has focused on predicting eye movement from human motions, such as eye prediction from head movements [\[12,](#page-14-8) [28\]](#page-15-16) or body movement [\[13\]](#page-14-9). Our study is closely related to the prediction of eye movement from human motions. However, we are exploring a new approach to predicting eye movement from finger movements on a touchscreen for the typing task, which has not been addressed before.

Our study also looks at inference at the level of individuals. Previous research has shown significant differences in how individuals look at UIs [\[19\]](#page-15-17). EyeFormer [\[18\]](#page-15-18) demonstrated the ability to make personalized predictions based on a small number of user scanpath samples. Unlike traditional methods that require eye movement data, our approach captures personalization using only a short typing log, making it more accessible to applications.

3 WIGGLYEYES: MODELING APPROACH

This section introduces the model, WIGGLYEYES, which can infer eye movement directly from keypress data. Its design tackles three hard technical challenges: 1) reproducing human-like patterns in attentional dynamics, 2) accounting for individual differences in eye movement prediction, and 3) training the model with limited human data. We tackle these challenges by using a novel loss function, a deep learning network designed for individual-level inference, and a training process that involves augmented data.

3.1 Problem Formulation

Given keypress data L, representing a total of C keypresses, we define a sequence of tap events $p_{1:C} = p_1, \ldots, p_C$, where each tap $p_i = (x_{tap}, y_{tap}, t_{lap})_i$ records the position in pixels (x_{tap}, y_{tap}) of the tap and the time t_{lap} between consecutive keypresses. From this data, we generate a scanpath of length T, consisting of a sequence of fixation points $f_{1:T} = f_1, \ldots, f_T$, which capture both spatial and temporal aspects of the user's gaze during typing. Each fixation point $f_i = (x_{fix}, y_{fix}, t_{fix})_i$ includes the gaze position (x_{fix}, y_{fix}) , and t_{fix} represents the fixation duration.

3.2 Model Design

Our architecture comprises of two main modules (see Figure [2\)](#page-4-0). The first is the *human parameter inference* module, which infers individual-level latent parameters, referred to as human parameters, that capture key characteristics unique to each user. These parameters are computed based on a set of interaction episodes observed from a user. The second module, the *eye movement inference* module, combines the inferred human parameters with keypress data from a given trial to predict the user's eye gaze during that specific trial. The final output of the eye movement inference module includes predictions for the mean and standard deviation of fixation positions, fixation duration, and the scanpath length for the current trial.

Human parameter inference. We define *human parameters* here as latent (cognitive) variables that, for example, capture a user's style, preferences, or capabilities. The human parameter inference module encodes such parameters based on a user's previous trials. As more trial data from the user are obtained, these estimates should become more accurate. Manuscript submitted to ACM

WIGGLYEYES: Inferring Eye Movements from Keypress Data 5

Fig. 2. Model architecture of WIGGLYEYES. The input consists of a sequence of keypress data, including position and interval of each tap (x, y, t) . The output is a sequence of fixations with position and duration. A key contribution of the model is the human parameter inference module, which computes typing performance metrics from the keypress data and infers the human parameters θ . The module is pre-trained using simulated data consisting of pairs of human parameters and their corresponding typing performance. The inferred human parameters are then combined with the encoded keypress features through a multi-head attention layer, and this is used to infer eye movement data via a Transformer network.

In our application case, typing, we adopt model parameters from a previous study [\[33\]](#page-15-12) that effectively capture variations in users' typing behavior. Specifically, we use E_K to indicate the encoding time of the vision, F_K to denote finger accuracy, and λ to indicate the user's memory retention ability for typed text. Identifying human parameters during personalized eye movement inference offers two main benefits: first, encoding trial data in a way that maximizes the distinguishability between users, and second, providing interpretable parameters that offer clear insights into each user's characteristics.

Here, the process of inferring these human parameters is simulation-based. Using the touchscreen typing simulation model [\[33\]](#page-15-12), which can replicate typing performance based on variations in the parameters, the human parameter inference module learns the relationship between typing performance and human parameters. This approach leverages a recent computational inference technique known as amortized inference [\[7,](#page-14-10) [9,](#page-14-11) [27\]](#page-15-19), where a neural network model first learns these relationships from simulated data, and then applies this knowledge to rapidly infer human parameters from real-world user behavior. In the typing application, four aggregated metrics are used as input to the neural network: words per minute, inter-key interval, error rate, and number of backspaces. These metrics reflect both typing speed and error-handling strategies, making them highly relevant to capturing individual-level differences. The module calculates these metrics from given previous trial data of a user and then uses them to infer the human parameters via a pre-trained neural network model.

Eye movement inference. The eye movement inference module uses the keypress feature and human parameters to predict fixations. First, these two features are combined using a multihead attention layer, with the human parameters as the query and the keypress feature as the key and value. This attention layer emphasizes the input keypress information with individual characteristics. Then, a Transformer-based encoder and decoder are used to transform the keypress-related input into eye movement data. This process predicts the distribution of the position and duration for each fixation, as well as the length of the entire scanpath.

3.3 Loss Function

We propose a novel loss function for model training that encourages the inferred eye movement to be more human-like spatially and temporally, and also to reproduce select phenomena of eye-hand coordination. Specifically, the overall loss function $\mathcal L$ is a sum of four key loss terms:

$$
\mathcal{L} = \mathcal{L}_{sim} + \mathcal{L}_{len} + \mathcal{L}_{f} + \mathcal{L}_{v}
$$

where \mathcal{L}_{sim} is the fixation similarity loss, \mathcal{L}_{len} is the scanpath length loss, \mathcal{L}_f is the finger guidance loss, and \mathcal{L}_v is the proofreading loss. We introduce each one of them in the following subsections.

3.3.1 Fixation Similarity Loss L*sim.* The similarity loss ensures that the predicted fixations closely match the ground truth human data in positions and durations. It is a combination of two terms: the mean squared error (MSE) loss and the Multi-match similarity loss term, which is hand-coded based on the multi-match similarity and captures the spatial-temporal similarity between the predicted and true gaze paths [\[8\]](#page-14-12). The overall position loss is defined as:

$$
\mathcal{L}_{\text{sim}} = \frac{1}{L_{gt}} \sum_{i=1}^{L_{gt}} \left(\left(f_i^{\text{pred}} - f_i^{\text{gt}} \right)^2 \right) - \text{Sim}_{\text{MultiMatch}} \tag{1}
$$

where the first term is the MSE between the predicted gaze trail's coordinates plus durations and that of the ground truth trail. Specifically, L_{gt} is the number of fixations in the ground truth gaze movement; f_i^{pred} is the predicted gaze point with coordinates and fixation duration; f_i^{gt} is the ground truth gaze point with coordinates and fixation duration. The second term captures the similarity between the predicted and actual gaze paths. Sim_{MultiMatch} is the position, duration and length similarity used in MultiMatch similarity [\[8\]](#page-14-12), which capture the characteristic of position, duration and moving distance of fixation points in the trail.

3.3.2 Scanpath Length Loss L*len.* The scanpath length loss is designed to make the model more likely to predict a similar number of fixations as humans. In our model, we predict the number of fixations in the sequence by estimating the likelihood of each fixation point being valid. We control the length by using a padding prediction mechanism that assigns a binary value to each gaze point. The loss function is the binary cross-entropy loss, which is applied to the predicted padding logits s_i and the true padding labels \hat{s}_i . It is defined as:

$$
\mathcal{L}_{\text{len}} = \frac{1}{N} \sum_{i=1}^{N} \text{BCE}(s_i, \hat{s}_i)
$$
 (2)

where BCE is the binary cross-entropy loss, N is the number of maximum length of possible gaze points in the sequence.

3.3.3 Finger Guidance Loss \mathcal{L}_f . Human vision is crucial for guiding finger movements due to the variability in finger movements, which requires continuous visual guidance because of the unpredictability of motor responses [\[17\]](#page-15-5). To encourage this guiding behavior, we introduce finger guidance loss, which aims to minimize the differences in both the distance between the gaze and touch points and the count of gaze fixations within a time window before the keypress for predicted gaze movement and human gaze movement. The loss we designed for typing comprises two components: the finger-gaze distance loss term and the finger-gaze count loss term:

$$
\mathcal{L}_{\rm f} = \left| \overline{d}^{\rm pred} - 0.5 \cdot \overline{d}^{\rm gt} \right| + 0.2 \cdot \left| C^{\rm pred} - C^{\rm gt} \right| \tag{3}
$$

where the first loss term measures the discrepancy between the distance of the predicted gaze position and the finger's touch position and the distance of the human gaze position and the finger's touch position during typing. $\overline{d}^{\text{pred}}$ is the average distance between the predicted gaze and the touch positions within the 350-ms window for the entire sequence; \overline{d}^{gt} is the average distance between the human gaze and the touch positions within the window before tapping events for the entire sequence; The second loss term measures the discrepancy between the counts of the fixations falling in the window of predicted gaze movement and human gaze movement. The second loss term measures the discrepancy between the counts of the fixations falling in the window of predicted gaze movement and human gaze movement. C^{pred} is the predicted number of gaze fixations on the keyboard area for the entire sequence; C^{gt} is the actual number of gaze fixations on the keyboard area for the entire sequence.

3.3.4 Visual Validation Loss L*v.* In addition to finger guidance, vision is also utilized for validating (confirming) that desired state-changes have occured [\[31\]](#page-15-20). In our typing application, visual attention needs is needed for proofreading what has been typed so far [\[17\]](#page-15-5). The visual validation loss is introduced to encourage the predicted gaze behavior to allocate fixations to the text entry area. This reflects typical human gaze behavior during touchscreen typing, where users frequently switch their gaze between the keyboard and the text area. The loss comprises two components: proofreading duration loss and proofreading count loss, which assess the disparities in the total duration and count of gaze fixations on the text area between the predicted gaze movement and human gaze behavior:

$$
\mathcal{L}_{\rm v} = \left| D^{\rm pred} - D^{\rm gt} \right| + 0.8 \cdot \left| C^{\rm pred} - C^{\rm gt} \right| \tag{4}
$$

where the first loss term measures the discrepancy between the total duration of predicted gaze fixations on the text area and the total duration of human gaze fixations on the text area. D^{pred} is the total predicted gaze duration on the text area; D^{gt} is the total human gaze duration on the text area; The second loss term measures the discrepancy between the number of predicted gaze fixations on the text area and the number of human gaze fixations on the text area. C^{pred} is the predicted number of gaze fixations on the text area; C^{gt} is the actual number of gaze fixations on the text area from human data.

3.4 Training Workflow

Although the model can be trained with human data, training the deep learning model to account for individual differences requires a large dataset containing accurate eye movement data paired with finger movement data. However, human datasets are often limited. For example, in our typing application, we have only 30 participants collected in a lab setting. To overcome this data limitation, we train the model using data augmentation. This involves adding synthetically generated data to the training dataset as illustrated in Figure [1-](#page-0-0)b. The augmented dataset is combined with human data and simulation data (refer to Sec. [4.3](#page-7-0) for training details in the application case of typing). While the simulation and training processes are computationally expensive, the model inference is fast. Given a set of previous trials of human data to compute metrics for human parameter inference, WIGGLYEYES can virtually immediately produce personalized eye movement data.

4 EVALUATION IN TOUCHSCREEN TYPING

We evaluated WIGGLYEYES in the challenging case of touchscreen typing. Before presenting the modeling results, we analyze the training dataset to illustrate eye-hand correlations inherent in the data.

4.1 Dataset (How we Type)

The gaze movement and typing logs used in our experiments were obtained from *How we Type*, a study on transcription typing [\[17\]](#page-15-5). It recorded detailed finger and eye-tracking data from 30 participants as they transcribed 20 sentences each, chosen from a set of 75 sentences. The data was collected while the participants were typing on a touchscreen using a customized keyboard. To ensure consistency, the eye tracking and typing logs, captured using different devices, were both resized to a resolution of 1920×1080 pixels. We randomly choose 25 users and their 285 trails for training, and the other 5 users and their 69 trails for evaluation.

4.2 Analysis of Correlation in Eye and Hand Movement

Users tend to visually guide their fingers while typing, however this can be done in many ways. As shown in Figure [3-](#page-8-0)a, the distance between the gaze position and the touch point gradually decreases from around 500 pixels to about 250 pixels within the 1000 ms interval leading up to the tap. The shortest distance is reached approximately 250 ms before the keypress, indicating that typists visually direct their fingers toward the intended key as they prepare to tap.

We also explored the connection between where people are looking and how their fingers move when typing, taking into account typing speed and movement distance. In Figure [3-](#page-8-0)b, we can see that there is a correlation between the ratio of looking at the keyboard and the time between keystrokes (IKI). The ratio goes up when the IKI is less than 500 ms, but goes down as the IKI goes over 500 ms. Figure [3-](#page-8-0)c displays the average ratio of looking at the keyboard for different distances of finger movement. Although the ratio mostly stays the same for most distance ranges, there is a small increase and decrease with larger finger movements. This suggests that typists might spend less time looking at the keyboard when they are making bigger finger movements.

Figure [3-](#page-8-0)d presents attention ratios when tapping keys. The lowest gaze-on-keyboard ratios are linked with the backspace and space keys when considering other keys together. When users allocate their gaze away from the keyboard during backspace taps, it indicates that they are correcting typing errors. On the other hand, allocating gaze on text entry during space taps suggests that users tend to check for errors after completing a word. This behavior shows a tendency to review text on a word-by-word basis. The lower value of the gaze-on-keyboard ratio for the space key also suggests that, due to its unique position and larger size.

4.3 Inference Experiment

Training details. The training dataset is the augmented dataset combined by human data and simulation data. Specifically, we simulated 300 trials using the optimal parameter set reported in CRTypist [\[33\]](#page-15-12) based on which the agent can simulate the most human-like typing behavior [\[6\]](#page-14-13). During the training, the Adam optimizer was utilized with a weight decay parameter of 4×10^{-4} . The initial learning rate was set to 5×10^{-5} and decayed by 3% every 100 training steps. Training was performed over a total of 8,000 steps with a batch size of 16. The entire training process was executed on an NVIDIA GeForce RTX 2080 GPU and took approximately 9 hours.

Evaluation Metrics. Following recent works in gaze prediction [\[18,](#page-15-18) [36\]](#page-15-21), we evaluated our model using three wellestablished scanpath-based metrics: 1) Dynamic Time Warping with Duration (DTWD): It extends the traditional Dynamic Time Warping (DTW) algorithm to account for the duration of fixation points. It identifies the optimal alignment between two scanpaths while preserving key features, then computes the distance based on this alignment; 2) Scaled Time Delay Embedding Distance (STED) [\[32,](#page-15-22) [35\]](#page-15-23): It's a method for assessing subscanpath similarities. By incorporating a scaling mechanism to normalize time series data, STED enhances robustness against noise and variations in scale, thus Manuscript submitted to ACM

Fig. 3. Comparisons between human data and WIGGLYEYES. (a) Distance between gaze and tapped positions during time; (b) Gaze on keyboard ratio vs. Typing speed; (c) Gaze on keyboard ratio vs. Finger movement distance; (d) Gaze attention distributions across keys. WIGGLYEYES closely matchs human data.

improving its ability to analyze complex time series dynamics. 3) MultiMatch [\[8\]](#page-14-12): It evaluates scanpaths along five distinct dimensions: shape, direction, length, position, and duration. While DTWD and STED primarily assess spatial and temporal characteristics, MultiMatch excels in capturing additional features such as shape and direction, providing a more comprehensive evaluation of fixation patterns. In addition to these scanpath-based metrics, we also evaluated the model using several statistical measurements of eye movement from the previous work, including 1) number of fixations, 2) fixation duration, 3) gaze shifts, and 4) time ratio for gaze on keyboard. These statistical metrics help assess whether the model can accurately replicate human gaze behavior across different tasks. Our goal is for the predicted scanpaths to closely match the actual human gaze patterns.

Results. The scanpath-based and statistical measurements are provided in Table [2](#page-11-0) and Table [3.](#page-11-1) The result demonstrates that our model successfully predicts gaze movement, with metrics closely aligning with those of the ground truth data. The qualitative analysis is introduced in the following paragraphs.

We further analyze the behaviors of the model introduced in Sec. [4.2.](#page-7-1) Regarding the average distance between the gaze position predicted by WIGGLYEYES and the tapped position, we observe similar behavior. As shown in Figure [3-](#page-8-0)a, the distance between the gaze position and the touch point decreases and reaches the lowest point at around 250 ms before the tapping, which is similar to the human data. For the gaze movement predicted by WIGGLYEYES, a similar trend is observed with an initial increase followed by a decrease as shown in Figure [3-](#page-8-0)b compared with human data, except for not fully capturing the lower gaze-on-keyboard ratio for IKIs below 100 ms, which may be attributed to the lack of sufficient training data when IKI is low. A similar phenomenon is also shown in the gaze movement predicted by WIGGLYEYES as shown in Figure [3-](#page-8-0)c. Compared to the phenomenon shown by ground truth gaze movement, the decrease in gaze on keyboard ratio is slightly more prominent. The phenomenon of gaze-on-keyboard ratio across keys is also captured by the gaze movement data predicted by WIGGLYEYES in Figure [3-](#page-8-0)d. Additionally, users tend to allocate more fixation time on the first and third rows of keys than on the second row. Our model WIGGLYEYES effectively captures these patterns, showing similar distributions of gaze-on-keyboard ratios for different key rows.

4.4 Ablation Study I: Loss Function

We conducted an ablation study to evaluate the contribution of different loss terms to the model's overall performance. Specifically, we investigated the impact of the loss function design by comparing the performance of four ablated models shown in Table [1.](#page-10-0) We used scanpath-wise metrics to quantitatively evaluate the performance. As shown in Table [1,](#page-10-0) the model trained with all loss components predicts the most similar gaze movements compared to the four ablated models. Specifically, the models without Fixation Similarity Loss and Scanpath Length Loss showed a significant decrease in Length similarity, which led to a lower mean value in MultiMatch similarity.

Then we further analyze Finger Guidance Loss and Visual Validation Loss. The Finger Guidance loss aims to model how visual perception guides finger movement. To examine this, we measured the average distance between the gaze positions and the tapped positions within 350 ms before the keypress. Figure [4](#page-10-1) a-c shows that both the ground truth human gaze movement and the model trained with all four loss terms exhibited a decrease in distance before the tap. However, the ablated model without the Finger Guidance loss did not show this decrease, indicating the absence of visual perception guiding finger behavior. The Visual Validation Loss encourages the model to allocate fixations away from the keyboard to the text entry area. To verify this, we analyzed the gaze-to-text entry ratio for different keys, as shown in Figure [4](#page-10-1) d-f. The model trained without the Visual Validation Loss exhibited almost no gaze allocation to the text entry, highlighting the importance of this loss term.

Method	DTWD 1	STED 1	MultiMatch ↑				
			Position	Duration	Shape	Direction	Length
With All 4 Loss Terms		8.45(1.85) 10.43(2.54) 0.86(0.05) 0.89(0.04) 0.76(0.09) 0.62(0.34) 0.83(0.11)					
Without Fixation Similarity Loss 9.62(2.31) 12.24(3.42) 0.80(0.06) 0.89(0.04) 0.76(0.08) 0.61(0.35) 0.56(0.13)							
Without Scanpath Length Loss		9.88(2.69) 11.89(3.58) 0.80(0.06) 0.90(0.04) 0.72(0.10) 0.60(0.35) 0.63(0.12)					
Without Finger Guidance Loss		$8.89(1.83)$ 11.10(2.57) 0.86(0.05) 0.91(0.03) 0.75(0.09) 0.61(0.34) 0.82(0.11)					
Without Visual Validation Loss		$8.86(1.87)$ 10.76(2.55) 0.85(0.05) 0.90(0.03) 0.75(0.09) 0.68(0.28) 0.80(0.11)					

Table 1. Ablation Study of Loss Function on Scanpath Wise, with the *Mean*(*SD*) reported for each metric. Arrows indicate the importance of the relation's direction (e.g., ↓ means "lower is better"). The results indicate that the model incorporating all four loss terms predicts gaze movements most accurately compared to the ablated models. While the models trained without Fixation Similarity Loss and Scanpath Length Loss exhibit lower MultiMatch Length similarity, the models trained without Finger Guidance Loss and Proofreading Loss achieve similar results to the model with full loss terms, showing no significant quantitative difference.

4.5 Ablation Study II: Data Augmentation and Parameter Inference

We further conducted an ablation study to evaluate the impact of using simulated data and incorporating the parameter inference method. The study compares the performance of the model against three abalation models: the model without human parameter inference; the model trained without simulation data; and the model without both. Table [2](#page-11-0) presents the quantitative results for scanpath-level performance, while Table [3](#page-11-1) shows the results for statistical-level performance. The

Fig. 4. Analysis of model behavior under ablations (Ablation Study I). The model trained without Finger Guidance Loss cannot reproduce human-like finger guidance phenomena, and without Visual Validation Loss it cannot reproduce gaze on text entry ratio.

results demonstrate that both data augmentation and parameter inference contribute to improving the model's overall performance. Specifically, Table [2](#page-11-0) shows that parameter inference enhances the model's ability to predict scanpaths that closely align with ground truth human data. Meanwhile, Table [3](#page-11-1) suggests that data augmentation generally improves the model's ability to replicate human gaze behavior statistically, though it leads to an increase in the number of gaze shifts.

Table 2. Ablation study of scanpath-wise contributions of data augmentation and parameter inference, with the *Mean*(*SD*) reported for each metric. The result indicates that in general, our model has the best performance compared to other ablated models on scanpath-wise.

Method / Source	Fixation Time	Number of Fixations	Number of Gaze Shifts	Time Ratio for Gaze on Keyboard
Human	382.31(102.68)	21.25(5.23)	3.81(1.20)	0.63(0.17)
WIGGLYEYES	376.73(37.99)	20.88(3.19)	4.33(1.52)	0.65(0.15)
WIGGLYEYES w/o user parameter inference	368.31(38.65)	20.70(3.36)	4.23(1.54)	0.63(0.15)
WIGGLYEYES w/o data augmentation	366.65(43.86)	21.78(2.99)	3.86(1.59)	0.72(0.16)
WIGGLYEYES w/o both	367.07(43.41)	21.74(2.84)	4.01(1.71)	0.73(0.15)

Table 3. Ablation study of statistic-wise contributions of data augmentation and parameter inference, with the *Mean*(*SD*) reported for each metric. The result indicates that our model generally predicted gaze closer to the ground truth compared with other ablated options except for the *Number of Gaze Shift.*

4.6 Individual-level analysis

To demonstrate our model's ability to capture individual-level gaze patterns, we randomly sampled two users from the testing set. The inferred user parameters for these two users are $\theta_1 = (0.396, 0.298, 0.414)$ and $\theta_2 = (0.447, 0.386, 0.525)$. Figure [5](#page-12-0) showcases the predicted gaze movements for both users while typing two sentences. Our model accurately reflects user-specific gaze behaviors. For instance, while typing Sentence 1, User 2 exhibited more fixations on the text entry area, a behavior that our model successfully predicted. When typing Sentence 2, User 1's gaze movement was more constrained compared to User 2, which was also captured in the predicted gaze paths. This highlights our model's ability to adapt to different user characteristics during typing.

We performed a qualitative analysis based on our model's predicted gaze movements for two selected users in Figure [6.](#page-13-0) In our first analysis of the distance between the finger and gaze during finger tapping, we noticed that in the ground truth data, User 1's gaze tends to lag slightly behind the finger, while User 2's gaze stays slightly ahead. This reflects different visual guiding behaviors during typing. Our model successfully replicates User 2's visual guidance, showing the closest gaze-finger distance right before the tapping event. However, for User 1, the predicted gaze does not fully capture the same lagging effect, but it successfully predicts the low distance after the tapping. Regarding the gaze-on-keyboard Manuscript submitted to ACM

Fig. 5. Ground truth and predicted gaze movements alongside typing logs for two selected users typing the same sentences. The results demonstrate the ability of our model to predict user-specific gaze patterns based on typing logs. Notably, User 2 shows more gaze fixations on the text entry area during Sentence 1, which the model captures effectively. Conversely, during Sentence 2, User 1 exhibits more constrained gaze movements, and this too is well-reflected in the predicted gaze paths. These insights highlight our model's adaptability to varied user behaviors. Videos are included in the Supplemental Material.

ratio versus finger movement distance, User 2 shows an overall downward trend in both ground truth and predicted data, indicating that they look at the keyboard less as movement distance increases. The model also captures the high ratio at Manuscript submitted to ACM

shorter distances. User 1, however, does not show a consistent decrease in the ratio, and the model accurately reflects this behavior with similar fluctuations. However, the high ratio observed at distances below 100 pixels in the ground truth is not fully reproduced by the model. In the gaze-on-keyboard ratio versus typing speed analysis, User 1's gaze-on-keyboard ratio remains flat at lower inter-key intervals (IKIs) and decreases as the IKI increases, a pattern well captured by the model. User 2 shows an increase-then-decrease trend, also accurately predicted. However, the model underrepresents the variability seen in User 2's ratio at higher IKI values.

Fig. 6. Qualitative analysis of individual-level behavior comparing ground truth and predicted data. The analysis consists of (1) the distance between finger and gaze during finger tapping, (2) the gaze-on-keyboard ratio versus finger movement distance, and (3) the gaze-on-keyboard ratio versus typing speed. The model captures the key user-specific behaviors with varying accuracy across the different metrics, showcasing its adaptability to different typing behaviors.

5 SUMMARY AND OUTLOOK

This paper has demonstrated that it is possible to infer users' eye movements from keypress data only in a highly interactive tasks. While previous work has shown inference from images or videos, it is now within the possibility to use keypress data only. Our main finding is that, while patterns in gaze deployment are complex, not to mention highly individual and task-specific, there is enough information in keypress data. In domains, such as typing, visual attention has a dual role of obtaining information and guiding hand movements [\[16,](#page-15-24) [17\]](#page-15-5). This means that there are events in data where eye and finger are not necessarily in the same location but highly correlated.

To exploit this information, we developed a novel loss function with four terms. It not only minimizes distance to human data, but biases the loss toward spatial and temporal characteristics of eye-hand coordination. At the moment our solution assumes, however, that there are pre-specified regions of interest on display. We envision that the loss function can be developed for other applications beyond typing simply by dropping the irrelevant terms.

Because eye movements are markedly individualistic, it is possible to improve the accuracy of inference when we can represent individual differences using a low-parametric latent vector. In our application in typing, we obtained this from from the user simulator, which represented differences related to perceptual and motor resources.

Our perhaps most striking finding is that inference is possible even without real eye-tracking data when a user simulator is available that can generate human-like finger and eye movements. Although accuracy suffers, an inference network trained on synthetic data may be of sufficient accuracy for some practical applications. However, best results are obtained by selectivley augmenting human data with synthetic data.

REFERENCES

- [1] Johnny Accot and Shumin Zhai. 1997. Beyond fitts' law: models for trajectory-based hci tasks. In *Proceedings of the ACM SIGCHI Conference on Human factors in computing systems*, pages 295–302.
- [2] Roland Arsenault and Colin Ware. 2000. Eye-hand co-ordination with force feedback. In *Proceedings of the SIGCHI conference on Human factors in computing systems*, pages 408–414.
- [3] Ravin Balakrishnan and I Scott MacKenzie. 1997. Performance differences in the fingers, wrist, and forearm in computer input control. In *Proceedings of the ACM SIGCHI Conference on Human factors in computing systems*, pages 303–310.
- [4] Maria Barrett and Nora Hollenstein. 2020. Sequence labelling and sequence classification with gaze: Novel uses of eye-tracking data for natural language processing. *Language and Linguistics Compass*, 14(11):1–16.
- [5] Ali Borji, Dicky N Sihite, and Laurent Itti. 2012. Probabilistic learning of task-specific visual attention. In *2012 IEEE Conference on computer vision and pattern recognition*, pages 470–477. IEEE.
- [6] Suyog Chandramouli, Danqing Shi, Aini Putkonen, Sebastiaan De Peuter, Shanshan Zhang, Jussi Jokinen, Andrew Howes, and Antti Oulasvirta. 2024. A workflow for building computationally rational models of human behavior. *Computational Brain & Behavior*, 7(3):399–419.
- [7] Kyle Cranmer, Johann Brehmer, and Gilles Louppe. 2020. The frontier of simulation-based inference. *Proceedings of the National Academy of Sciences*, 117(48):30055–30062.
- [8] Richard Dewhurst, Marcus Nyström, Halszka Jarodzka, Tom Foulsham, Roger Johansson, and Kenneth Holmqvist. 2012. It depends on how you look at it: Scanpath comparison in multiple dimensions with multimatch, a vector-based approach. *Behavior research methods*, 44:1079–1100.
- [9] David Greenberg, Marcel Nonnenmacher, and Jakob Macke. 2019. Automatic posterior transformation for likelihood-free inference. In *International Conference on Machine Learning*, pages 2404–2414. PMLR.
- [10] Qi Guo and Eugene Agichtein. 2010. Towards predicting web searcher gaze position from mouse movements. In *CHI'10 extended abstracts on human factors in computing systems*, pages 3601–3606.
- [11] Kenneth Holmqvist, Marcus Nyström, Richard Andersson, Richard Dewhurst, Halszka Jarodzka, and Joost Van de Weijer. 2011. *Eye tracking: A comprehensive guide to methods and measures*. oup Oxford.
- [12] Zhiming Hu, Andreas Bulling, Sheng Li, and Guoping Wang. 2021. Fixationnet: Forecasting eye fixations in task-oriented virtual environments. *IEEE Transactions on Visualization and Computer Graphics*, 27(5):2681–2690.
- [13] Zhiming Hu, Jiahui Xu, Syn Schmitt, and Andreas Bulling. 2024. Eye-body coordination during daily activities for gaze prediction from full-body poses. *IEEE Transactions on Visualization and Computer Graphics*.
- [14] Laurent Itti and Christof Koch. 2000. A saliency-based search mechanism for overt and covert shifts of visual attention. *Vision Research*, 40(10- 12):1489–1506.
- [15] Robert JK Jacob and Keith S Karn. 2003. Eye tracking in human-computer interaction and usability research: Ready to deliver the promises. In *The mind's eye*, pages 573–605. Elsevier.
- [16] Xinhui Jiang, Jussi P.P. Jokinen, Antti Oulasvirta, and Xiangshi Ren. 2022. [Learning to type with mobile keyboards: Findings with a randomized](https://doi.org/https://doi.org/10.1016/j.chb.2021.106992) [keyboard.](https://doi.org/https://doi.org/10.1016/j.chb.2021.106992) *Computers in Human Behavior*, 126:106992.
- [17] Xinhui Jiang, Yang Li, Jussi PP Jokinen, Viet Ba Hirvola, Antti Oulasvirta, and Xiangshi Ren. 2020. How we type: Eye and finger movement strategies in mobile typing. In *Proceedings of the 2020 CHI conference on human factors in computing systems*, pages 1–14.
- [18] Yue Jiang, Zixin Guo, Hamed Rezazadegan Tavakoli, Luis A Leiva, and Antti Oulasvirta. 2024. Eyeformer: predicting personalized scanpaths with transformer-guided reinforcement learning. *arXiv preprint arXiv:2404.10163*.
- [19] Yue Jiang, Luis A Leiva, Hamed Rezazadegan Tavakoli, Paul RB Houssel, Julia Kylmälä, and Antti Oulasvirta. 2023. Ueyes: Understanding visual saliency across user interface types. In *Proceedings of the 2023 CHI Conference on Human Factors in Computing Systems*, pages 1–21.
- [20] Roland S Johansson, Göran Westling, Anders Bäckström, and J Randall Flanagan. 2001. Eye–hand coordination in object manipulation. *Journal of neuroscience*, 21(17):6917–6932.
- [21] George Alex Koulieris, George Drettakis, Douglas Cunningham, and Katerina Mania. 2016. Gaze prediction using machine learning for dynamic stereo manipulation in games. In *2016 IEEE virtual reality (VR)*, pages 113–120. IEEE.
- [22] Matthias Kümmerer, Matthias Bethge, and Thomas SA Wallis. 2022. Deepgaze iii: Modeling free-viewing human scanpaths with deep learning. *Journal of Vision*, 22(5):7–7.
- [23] Yin Li, Alireza Fathi, and James M Rehg. 2013. Learning to predict gaze in egocentric video. In *Proceedings of the IEEE international conference on computer vision*, pages 3216–3223.
- [24] I Scott MacKenzie and William Buxton. 1992. Extending fitts' law to two-dimensional tasks. In *Proceedings of the SIGCHI conference on Human factors in computing systems*, pages 219–226.
- [25] Laura E Matzen, Michael J Haass, Kristin M Divis, Zhiyuan Wang, and Andrew T Wilson. 2017. Data visualization saliency model: A tool for evaluating abstract data visualizations. *IEEE Transactions on Visualization and Computer Graphics (TVCG)*, 24(1):563–573.
- [26] Sounak Mondal, Zhibo Yang, Seoyoung Ahn, Dimitris Samaras, Gregory Zelinsky, and Minh Hoai. 2023. Gazeformer: Scalable, effective and fast prediction of goal-directed human attention. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 1441–1450.
- [27] Hee-Seung Moon, Antti Oulasvirta, and Byungjoo Lee. 2023. Amortized inference with user simulations. In *Proceedings of the 2023 CHI Conference on Human Factors in Computing Systems*, pages 1–20.
- [28] Ryoichi Nakashima, Yu Fang, Yasuhiro Hatori, Akinori Hiratani, Kazumichi Matsumiya, Ichiro Kuriki, and Satoshi Shioiri. 2015. Saliency-based gaze prediction based on head direction. *Vision research*, 117:59–66.
- [29] Alexandra Papoutsaki. 2015. Scalable webcam eye tracking by learning from user interactions. In *Proceedings of the 33rd Annual ACM Conference Extended Abstracts on Human Factors in Computing Systems*, pages 219–222.
- [30] Keith Rayner. 1998. Eye movements in reading and information processing: 20 years of research. *Psychological bulletin*, 124(3):372.
- [31] Keith Rayner. 2009. The 35th sir frederick bartlett lecture: Eye movements and attention in reading, scene perception, and visual search. *Quarterly journal of experimental psychology*, 62(8):1457–1506.
- [32] Tim Sauer, James A Yorke, and Martin Casdagli. 1991. Embedology. *Journal of statistical Physics*, 65:579–616.
- [33] Danqing Shi, Yujun Zhu, Jussi PP Jokinen, Aditya Acharya, Aini Putkonen, Shumin Zhai, and Antti Oulasvirta. 2024. Crtypist: Simulating touchscreen typing behavior via computational rationality. In *Proceedings of the CHI Conference on Human Factors in Computing Systems*, pages 1–17.
- [34] Ronal Singh, Tim Miller, Joshua Newn, Eduardo Velloso, Frank Vetere, and Liz Sonenberg. 2020. Combining gaze and ai planning for online human intention recognition. *Artificial Intelligence*, 284:103275.
- [35] Wei Wang, Cheng Chen, Yizhou Wang, Tingting Jiang, Fang Fang, and Yuan Yao. 2011. Simulating human saccadic scanpaths on natural images. In *CVPR 2011*, pages 441–448. IEEE.
- [36] Yao Wang, Andreas Bulling, et al. 2023. Scanpath prediction on information visualisations. *IEEE Transactions on Visualization and Computer Graphics*.
- [37] Yao Wang, Weitian Wang, Abdullah Abdelhafez, Mayar Elfares, Zhiming Hu, Mihai Bâce, and Andreas Bulling. 2024. Salchartqa: Question-driven saliency on information visualisations. In *Proceedings of the CHI Conference on Human Factors in Computing Systems*, pages 1–14.
- [38] Min Wu, Tyron Louw, Morteza Lahijanian, Wenjie Ruan, Xiaowei Huang, Natasha Merat, and Marta Kwiatkowska. 2019. Gaze-based intention anticipation over driving manoeuvres in semi-autonomous vehicles. In *2019 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 6210–6216. IEEE.