Fast Biclique Counting on Bipartite Graphs: A Node Pivot-based Approach

Xiaowei Ye, Rong-Hua Li, Longlong Lin, Shaojie Qiao, Guoren Wang

ABSTRACT

arXiv:2412.16485v1 [cs.DS] 21 Dec 2024 arXiv:2412.16485v1 [cs.DS] 21 Dec 2024 Counting the number of (p, q) -bicliques (complete bipartite subgraphs) in a bipartite graph is a fundamental problem which plays a crucial role in numerous bipartite graph analysis applications. However, existing algorithms for counting (p, q) -bicliques often face significant computational challenges, particularly on large real-world networks. In this paper, we propose a general biclique counting framework, called NPivoter, based on a novel concept of node-pivot. We show that previous methods can be viewed as specific implementations of this general framework. More importantly, we propose a novel implementation of NPivoter based on a carefully-designed minimum non-neighbor candidate partition strategy. We prove that our new implementation of NPivoter has lower worst-case time complexity than the state-of-the-art methods. Beyond basic biclique counting, a nice feature of NPivoter is that it also supports local counting (computing bicliques per node) and range counting (simultaneously counting bicliques within a size range). Extensive experiments on 12 real-world large datasets demonstrate that our proposed NPivoter substantially outperforms state-of-the-art algorithms by up to two orders of magnitude.

ACM Reference Format:

Xiaowei Ye, Rong-Hua Li, Longlong Lin, Shaojie Qiao, Guoren Wang. 2024. Fast Biclique Counting on Bipartite Graphs: A Node Pivot-based Approach. In Proceedings of ACM Conference (Conference'17). ACM, New York, NY, USA, [16](#page-15-0) pages.<https://doi.org/10.1145/nnnnnnn.nnnnnnn>n

1 INTRODUCTION

A bipartite graph is a special type of graph where the node set can be divided into two disjoint sets, typically denoted as U and V , such that every edge in the graph connects a node from U to a node from *V*, with no edges within *U* or *V*. If $X \subseteq U$ and $Y \subseteq V$, the pair (X, Y) forms a (p, q) -biclique if $|X| = p$, $|Y| = q$, and every node in X is connected to every node in Y .

The count of (p, q) -biclique is a key structural measure in bipartite graphs. In graph database query optimization, this count helps predict query processing costs by estimating the result set size in join operations, improving query planning and execution efficiency [\[1,](#page-14-0) [29\]](#page-14-1). In graph neural networks (GNNs), counting (p, q) -bicliques for each node captures higher-order graph structural properties, which are crucial for improving model performance [\[3,](#page-14-2) [6,](#page-14-3) [35,](#page-14-4) [49,](#page-15-1) [54\]](#page-15-2).

Conference'17, July 2017, Washington, DC, USA

© 2024 Association for Computing Machinery.

ACM ISBN 978-x-xxxx-xxxx-x/YY/MM. . . \$15.00

<https://doi.org/10.1145/nnnnnnn.nnnnnnn>

 (p, q) -biclique counts are also essential in various real-life applications, such as social network analysis [\[5,](#page-14-5) [17,](#page-14-6) [41\]](#page-14-7) and bioinformatics [\[34\]](#page-14-8), where they help identify dense substructures representing highly connected clusters of users, entities, or data items.

The state-of-the-art (SOTA) methods for (p, q) -biclique counting are BCList++ [\[50\]](#page-15-3) and EPivoter [\[52\]](#page-15-4). BCList++ is a listing-based algorithm that works by enumerating all p -node subsets of U (denoted as L) and finding their common neighbors in V , represented as *R*. The count of (p, q) -bicliques is then calculated as $\binom{|R|}{q}$, where the pruning techniques in BCList++ help avoid unnecessary searches. EPivoter, on the other hand, observes that (p, q) -bicliques are often subsets of larger bicliques. It uses edge enumeration to build a tree-like data structure, where each node in the tree represents an edge, and each root-to-leaf path corresponds to a large biclique. This search tree ensures that each (p, q) -biclique appears in exactly one large biclique, allowing EPivoter to count (p, q) -bicliques by enumerating the larger ones. Both BCList++ and EPivoter split the bipartite graph into smaller subgraphs before counting the bicliques, but they employ different graph-split strategies. BCList++, focusing on node enumeration, splits the graph based on the neighbors of nodes (namely node-split), whereas EPivoter, through edge enumeration, splits the graph based on edge neighbors (namely edge-split). This difference in strategy leads to varying efficiencies in counting (p, q) -bicliques depending on the graph structure and parameter values of p and q .

Despite the success, existing algorithms for (p, q) -biclique counting still have several significant limitations. For example, BCList++ performs well only when p and q are small, but its efficiency diminishes sharply as these values increase [\[50,](#page-15-3) [52\]](#page-15-4). On the other hand, EPivoter is more suited for larger p and q and can handle range counting, i.e., counting (p, q) -bicliques for different p and q in a range simultaneously. However, EPivoter suffers from high constant factors in its time complexity, primarily due to its edge-based enumeration approach. This method leads to more frequent set intersection operations, which increases computational overhead and makes it less efficient for smaller values of p and q [\[52\]](#page-15-4). Additionally, both BCList++ and EPivoter are limited by their high time complexity and reliance on a single graph-split strategy, which restricts their flexibility and scalability across various graph structures. Moreover, many applications, such as graph neural networks and graph clustering, require local counting, which involves computing the count of (p, q) -bicliques for individual nodes as an important property. Unfortunately, neither BCList++ nor EPivoter is well-suited for efficient local counting, further limiting their applicability in real-world scenarios.

To overcome the above limitations, we propose NPivoter, a versatile and general framework for biclique counting, which provides a theoretically and practically efficient algorithm. The NPivoter framework is general in two ways. First, it offers a unified perspective on biclique counting, where both BCList++ and EPivoter can be

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

Conference'17, July 2017, Washington, DC, USA Xiaowei Ye, Rong-Hua Li, Longlong Lin, Shaojie Qiao, Guoren Wang

regarded as specific implementations within this framework. This not only establishes NPivoter as a significant advancement over existing methods but also highlights its flexibility in addressing a wider range of cases. Second, NPivoter extends beyond traditional (p, q) -biclique counting to support both local counting and range counting. These extensions make NPivoter applicable to numerous real-world applications while ensuring greater efficiency and adaptability.

The core idea of the NPivoter framework is the concept of nodepivot. A set of nodes are called node-pivots if they connect to all the nodes on the opposite side. In NPivoter, these node-pivots simplify the enumeration process by eliminating the need for further exploration and building a unique representation for all bicliques. This unique representation allows NPivoter to efficiently count bicliques in a combinatoric way. On top of that, we develop an advanced implementation of the NPivoter framework by the candidate set partition strategy called the minimum non-neighbor candidate partition. This candidate partition makes the search tree of the NPivoter as small as possible. With this candidate partition strategy, we prove that our implementation achieves lower worst-case time complexity than the previous SOTA algorithms. For example, the time complexity of BCList++ depends on the result size, whereas EPivoter has a time complexity of $O(|E|3^{|E_{max}|/3})$, which is independent of the result size. In contrast, our new implementation of NPivoter has a result-size-free time complexity of $O(|E|2^{n'/2})$, where $2^{1/2}$ < $3^{1/3}$ and n' < $|E_{max}|$, making it more efficient in the worst case. Furthermore, we enhance the efficiency of NPivoter with a carefully-designed cost estimator, which dynamically selects the node-split and edge-split strategies. This hybrid approach adapts to the specific structure of the graph, taking advantage of both node-split and edge-split to reduce computational overhead and improve scalability. In a nutshell, our main contributions are briefly summarized as follows: mythisk an expect in constraint with this reason with the interesting that is the higher scalability of our solutions. The higher scalability of our solutions is the scalability of our solutions in the scalability of our

A General Counting Framework: We propose NPivoter, a versatile and general framework for (p, q) -biclique counting, built upon the novel node-pivot technique. This framework not only unifies existing algorithms like BCList++ and EPivoter as special cases but also extends beyond them by supporting local and range biclique counting.

A Powerful Candidate Partition Strategy: We develop a powerful candidate partitioning technique—minimum non-neighbor candidate partition—which optimizes the search tree and achieves lower worst-case time complexity than SOTA approaches.

An Adaptive Splitting Technique: Our framework integrates a cost estimator that dynamically switches between node-split and edge-split strategies. This adaptive approach tailors the biclique counting process to the graph's structure, reducing computational overhead and improving practical performance.

Extensive Experimental Evaluation: Through comprehensive experiments on 12 real-world datasets, we demonstrate that the proposed NPivoter outperforms SOTA algorithms by up to two orders of magnitude in both basic and extended biclique counting tasks,

Figure 1: An example graph

2 PRELIMINARIES

Let $G = (U, V, E)$ be a bipartite graph, where U and V are disjoint sets of nodes, and $E \subseteq U \times V$ is the set of edges. For each node $u \in U$, its neighbor set in V is $N(u, V) = \{v \in V \mid (u, v) \in E\}$. For a set of vertices $S \subseteq U$, the common neighbors of S in V are defined as $N(S, V) = \bigcap_{u \in S} N(u, V)$. The degree of a node u in V, denoted by $d(u, V)$, is the size of its neighbor set: $d(u, V) = |N(u, V)|$. When the context is clear, we abbreviate $N(u, V)$, $N(S, V)$, and $d(u, V)$ as $N(u)$, $N(S)$, and $d(u)$, respectively. The 2-hop neighbors of a node *u* ∈ *U* are given by $\cup_{v \in N(u, V)} N(v, U)$. For all the above concepts, we have symmetrical definitions for vertices in V . A rank R of a set of nodes S is a vector that assigns each node in S a distinct number from the range $[1, |S|]$. Below, we give the definition of (p, q) -biclique.

Definition 2.1. Given a bipartite graph $G(U, V, E)$, a (p, q) -biclique in G is a complete subgraph with a pair of vertex sets (X, Y) where $|X| = p, |Y| = q.$

Problem Definition. Given a bipartite graph $G(U, V, E)$ and two integers p and q , the task is to compute the number of (p, q) bicliques in G .

The (p, q) -biclique counting problem is NP-hard [\[50\]](#page-15-3), which implies that no known polynomial-time algorithm can efficiently solve all instances of the problem.

Example 2.2. Figure [1](#page-1-0) is a synthetic graph with 10 (3, 3)-bicliques. For example, $({u_0, u_2, u_3, u_4}_3, {v_1, v_2, v_3})$ is a $(3, 3)$ -biclique, where $\{u_0, u_2, u_3, u_4\}$ indicates choose arbitrary 3 nodes from $\{u_0, u_2, u_3, u_4\}.$ The rest of (3, 3)-bicliques are $({u_1, u_2, u_3, u_4}_3, {v_1, v_2, v_4})$, $({u_2, u_3, u_4}, {v_1, v_3, v_4})$, and $({u_2, u_3, u_4}, {v_2, v_3, v_4})$.

3 EXISTING SOLUTIONS AND THEIR DEFECTS

3.1 BCList++ [\[50\]](#page-15-3)

BCList++ is a listing-based algorithm, which lists the p -node complete subgraphs in a data structure called the "2-hop graph". Specifically, given a bipartite graph $G(U, V, E)$, the 2-hop graph $H(U, E')$ is a directed acyclic graph (DAG) with the node set U , where two nodes are connected by an edge if they have at least q common neighbors in *V*. Namely, for all $(u_0, u_1) \in E'$, $|N({u_0, u_1}), V| \ge q$. Thus, for any (p, q) -biclique (X, Y) , the set X must form a complete subgraph in $H(U, E')$, as each pair of nodes in X has at least q common neighbors in $Y \subseteq V$. BCList++ counts the number of (p, q) bicliques by listing all p-node complete subgraphs in $H(U, E')$. For each complete subgraph $X \subseteq U$ where $|X| = p$, the number of (p, q) -bicliques is $\binom{\vert N(\hat{X}, V) \vert}{q}$.

Fast Biclique Counting on Bipartite Graphs: A Node Pivot-based Approach Conference' 17, July 2017, Washington, DC, USA

The first search layer of BCList++ divides the network into smaller subgraphs based on a ranking of nodes and then counts (p, q) -bicliques in these subgraphs. Specifically, for each node $u \in U$, BCList++ counts the $(p - 1, q)$ -bicliques in the subgraph induced by the neighbors and higher-ranked 2-hop neighbors of u . We refer to this method as the node-split strategy.

Given the bipartite graph $G(U, V, E)$ and its 2-hop graph $H(U, E'),$ the time complexity of BCList++ is $O(\alpha(H)^{p-2} | E' | d_{\text{max}} + \Delta)$, where α (H) is the arboricity of H [\[12\]](#page-14-9), d_{max} is the maximum degree in $U(G)$ and Δ is the size of result. BCList++ can also construct a 2-hop graph on V and enumerate q -cliques. Additionally, BCList++ employs an estimation model to determine which side of the graph (either U or V) is more efficient for enumeration.

BCList++ is efficient for large, sparse bipartite graphs when p or q is small. However, its performance degrades as p , q , or the graph size increases. For instance, on the Twitter dataset ($|U|$ = 175, 214, $|V| = 530, 418, |E| = 1, 890, 661$, the count of $(5, 5)$ -biclique reaches 10^{13} , thereby the listing-based algorithms are doomed to fail. Another limitation is that BCList++ requires p and q as input parameters, meaning that it can only count (p, q) -bicliques for a specific pair of values. To count bicliques across a range of sizes, the algorithm must run multiple times for each pair of (p, q) , which is inefficient. A third drawback is that BCList++ does not support local counting per node, which is essential for certain applications, such as graph neural networks and higher-order graph clustering, where local biclique counts serve as important node properties [\[3,](#page-14-2) [6,](#page-14-3) [35,](#page-14-4) [49,](#page-15-1) [54\]](#page-15-2).

3.2 EPivoter [\[52\]](#page-15-4)

Unlike BCList++, which counts (p, q) -bicliques by listing, EPivoter counts them using a combinatorial approach. A straightforward combinatorial method would first enumerate maximal bicliques and then count the (p, q) -bicliques within them. However, due to significantly overlapping maximal bicliques, a (p, q) -biclique might be counted multiple times. To address this, EPivoter introduces an edge-pivot technique that encodes large bicliques into a unique representation for each (p, q) -biclique. Specifically, EPivoter constructs a search tree where each tree vertex represents an edge, and each path from the root to a leaf corresponds to a large biclique. Each large biclique encodes a set of (p, q) -bicliques, and each (p, q) biclique is uniquely represented by one large biclique. With this unique encoding, EPivoter can count (p, q) -bicliques combinatorially without listing them one by one.

As discussed above, BCList++ counts the $(p-1, q)$ -bicliques with the node-split strategy. Differently, for each edge (u, v) , EPivoter counts the $(p - 1, q - 1)$ -bicliques in the subgraphs induced by the higher-ranked neighbors of both u and v . This method is termed the edge-split strategy. Deciding which strategy is more efficient is complex and depends on both the algorithm and the graph structure. Different algorithms and graph structures are better suited to different strategies, and even different parts of a single graph may benefit from various approaches. In this paper, we will propose a novel cost estimator to leverage the advantages of both the node-split and edge-split strategies (Section [4.3\)](#page-7-0).

Given the bipartite graph $G(U, V, E)$, the time complexity of EPivoter is $O(|E|3^{|E_{\text{max}}|/3})$, where $|E_{\text{max}}| = \max_{(u,v) \in E} |E \cap (N(u) \times$

 $N(v)$]. Unlike BCList++, EPivoter has a time complexity free from the result size (the (p, q) -biclique counts). EPivoter is more efficient than BCList++ when p and q are relatively large (e.g., $p \ge$ $6, q \geq 6$), and can count bicliques across a range of sizes simultaneously, thanks for the edge-pivot based unique encoding [\[52\]](#page-15-4). However, EPivoter is less efficient when p and q are very small (e.g., $p < 6, q < 6$). The key difference is in the enumeration process: BCList++ enumerates nodes from one side (i.e., selecting a node from a fixed side during backtracking), while EPivoter enumerates edges (each search tree vertex represents an edge), selecting two nodes—one from each side—during backtracking. This approach leads to higher constant factors in its time complexity for EPivoter, as edge enumeration requires more set intersection operations, which are computationally intensive. As a result, EPivoter is not as efficient when p and q are very small. Moreover, the time complexity of EPivoter can be high, as it depends on the parameter $|E_{\text{max}}|$, which can significantly affect performance.

4 NOVEL NODE-PIVOT BASED FRAMEWORK

As previously discussed, the BCList++ algorithm enumerates nodes on only one side, which constitutes a straightforward and lightweight approach. On the other hand, EPivoter constructs a unique representation for all (p, q) -bicliques, proving more efficient for relatively larger p and q . However, EPivoter is hindered by a high time complexity, with an exponential component that is contingent upon $|E_{max}|$. On top of that, EPivoter incurs high constant factors due to its edge enumeration process. A pertinent question arises: is it possible to devise an algorithm that (1) maintains simplicity and lightweightness, (2) is efficient for counting (p, q) -biclique whether p and q is large or small, (3) facilitates both local counting and range counting, and (4) exhibits an improved worst-case time complexity?

To achieve these goals, we propose a novel node-pivot based framework NPivoter. Firstly, NPivoter employs the proposed powerful node-pivot technique to build a unique representation for all (p, q) -bicliques, while the previous work EPivoter utilizes edgepivot. Our node-pivot differs significantly from edge-pivot. Our node–pivot is a set of nodes which connect to all the opposite nodes, while edge-pivot is an edge with the maximum number of neighbors. Secondly, since NPivoter can construct a unique representation for all (p, q) -bicliques, we can use a combinatorial counting approach to significantly reduce redundant calculations. Thirdly, NPivoter is a general framework for counting bicliques. We show that both the previous methods BCList++ and EPivoter are special implementations of our framework. Further, we propose a specific candidate partition strategy to boost the efficiency and achieve a lower worstcase time complexity (details in Section [4.2\)](#page-5-0). At last, in Section [4.3,](#page-7-0) we develop a novel cost estimator to judge whether node-split or edge-split is more efficient under different graph structures.

4.1 The Proposed NPivoter Framework

The key idea of the NPivoter framework is the following node-pivot.

Definition 4.1 (node-pivot). For any $C_U \subseteq U$, $C_V \subseteq V$, let $P_U =$ ${u | u \in C_U, N(u, C_V) = C_V}$ and $P_V = {v | v \in C_V, N(v, C_U) = C_U}.$ We refer to the nodes in P_U and P_V as node-pivots.

Algorithm 1: NPivoter: Node-pivot based framework

Input: The graph $G(U, V, E)$, two integers p and q **Output:** The count of (p, q) -biclique in G 1 Denote R by the rank of nodes in the sorted node set of $U \cup V$; 2 $cnt \leftarrow 0$: 3 foreach $u \in U$ do 4 if $\frac{1}{\epsilon}$ if $\frac{1}{\epsilon}$ the cost estimator $\frac{1}{\epsilon}$ then $\frac{1}{\epsilon}$ then $\frac{1}{\epsilon}$ split $\frac{1}{\epsilon}$ 5 foreach $v \in N(u)$ do 6 $\vert G_U \leftarrow \{u'|u' \in N(v), R(u') > R(u)\};$ $7 \mid \bigcup_{V \in V} C_V \leftarrow \{v'|v' \in N(u), R(v') > R(v)\};$ 8 NPC $(C_U, C_V, \emptyset, \emptyset, \{u\}, \{v\});$ 9 else /*node split*/ 10 $\Big| \Big| C_U \leftarrow \bigcup_{v \in N(u)} \{u' | u' \in N(v), R(u') > R(u) \};$ 11 NPC $(C_U, N(u), \emptyset, \emptyset, \{u\}, \emptyset);$ 12 return cnt : 13 Procedure NPC $(C_U, C_V, P_U, P_V, H_U, H_V)$ 14 **if** $(C_U \times C_V) \cap E = \emptyset$ or $|H_U| = p$ or $|H_V| = q$ then 15 | count $(|C_U|, |C_V|, |P_U|, |P_V|, |H_U|, |H_V|)$; return; 16 Move nodes that connect to all nodes in C_V from C_U to P_U ; 17 Move nodes that connect to all nodes in C_U from C_V to P_V ; 18 Choose L_U, L_V from $C_U, C_V;$ 19 **for** $u \in L_U$ **do** /*enumerate L_U */ 20 $\vert \; \vert \; C_U \leftarrow C_U \setminus u;$ 21 NPC $(C_U, C_V \cap N(u), P_U, P_V, H_U \cup \{u\}, H_V);$ 22 /*enumerate L_V like lines 19-21*/; 23 NPC $(C_U, C_V, P_U, P_V, H_U, H_V)$ 24 Procedure count $(c_0, c_1, p_0, p_1, h_0, h_1)$ 25 if $c_0 = 0$ or $c_1 = 0$ then $cnt \leftarrow cnt + {p_0+c_0 \choose p-h_0} {p_1+c_1 \choose q-h_1}$, return; 26 $ent \leftarrow cnt + {p_0+c_0 \choose p-h_0} {p_1 \choose q-h_1} + {p_0 \choose p-h_0} {p_1+c_1 \choose q-h_1} - {p_0 \choose p-h_0} {p_1 \choose q-h_1};$

An In-depth Observation. Given that $C'_U = C_U \setminus P_U$ and $C'_V = C_U \setminus P_U$ $C_V \setminus P_V$, any biclique extended by a node-pivot preserves its biclique structure since node-pivots are connected to all nodes in the opposite set. For instance, an (x, y) -biclique in (C'_U, C'_V) becomes an $(x + 1, y)$ -biclique if extended by a node in P_U and an $(x, y + 1)$ -biclique if extended by a node in P_V . Furthermore, an (x, y) -biclique can evolve into an $(x + a, y + b)$ -biclique by extending it with a nodes from P_U and b nodes from P_V . This important characteristic of node-pivots enables the NPivoter framework to significantly reduce the size of the candidate sets by shrinking C_U and C_V to C'_U and C'_V , respectively. If there are $c(x, y)$ -bicliques in (C'_U, C'_V) , the total number of (p, q) -bicliques in (C_U, C_V) can be computed by $c\binom{|P_U|}{p-x}\binom{|P_V|}{q-y}$, in a combinatorial way. To calculate the bicliques in (C_U^f, C_V^{\prime}) , NPivoter divides $(C_U^{\prime}, C_V^{\prime})$ into multiple smaller subsets. Each of these small subsets has its own node-pivots, and the NPivoter framework recursively processes them to build down the problem. Through this recursive approach, NPivoter efficiently represents and counts all (p, q) -bicliques combinatorially.

The process of dividing (C'_U, C'_V) into smaller subsets, referred to as the candidate partition problem, has a significant impact on the performance of the NPivoter framework. Given four node sets $L_U \subseteq C_U \subseteq U$ and $L_V \subseteq C_V \subseteq V$, the bicliques in the bipartite graph $G(C_U, C_V)$ can be classified into two main categories: those

that include nodes from L_U and L_V , and those that do not. The NPivoter framework enumerates L_U and L_V to break the candidate sets into multiple subsets. Each subset counts the bicliques that include nodes from L_U and L_V . The final subset, $C_U \backslash L_U$ and $C_V \backslash L_V$, is used to count the bicliques that do not include nodes from either L_U or L_V . We propose a specific candidate partition strategy that ensures NPivoter operates within a worst-case time complexity (details in Section [4.3\)](#page-7-0).

Remark. We will show later that both BCList++ and EPivoter can be viewed as specific implementations of the broader NPivoter framework, each with distinct strategies for selecting node-pivots. BCList++ processes the graph without leveraging node-pivot based pruning. On the other hand, EPivoter prunes an edge (u, v) where $u \in P_U$ and $v \in P_V$. In contrast, the NPivoter framework prunes all node-pivots, which enables it to prune a greater number of candidate sets compared to BCList++ and EPivoter. As demonstrated in the experiments discussed in Section [6,](#page-8-0) over 85% of (10, 10) bicliques across the tested graphs are counted using this combinatorial method, showcasing the effectiveness of the NPivoter approach.

Implementation Details. Algorithms [1](#page-3-0) shows the pseudo-code of NPivoter. NPivoter inputs $G(U, V, E)$, p , q and outputs the count of (p, q) -biclique in G. Let R be the rank of nodes (line 1). NPivoter splits the bipartite graph into smaller subgraphs and counts the (p, q) -bicliques within them. There are two splitting strategies. The first is the edge-split, where an edge (u, v) is chosen, and the algorithm counts $(p - 1, q - 1)$ -bicliques in the subgraph induced by nodes of higher rank (lines 5-8 of Algorithm [1\)](#page-3-0). The second is the node-split, where a node u is chosen, and the algorithm counts $(p - 1, q)$ -bicliques in the subgraph induced by $N(u)$ and higher-ranked 2-hop nodes (lines 10-11 of Algorithm [1\)](#page-3-0). To determine which strategy is more efficient (line 4), we provide a cost estimation technique, detailed in Section [4.3.](#page-7-0)

The NPC procedure is central to the NPivoter framework (line 13). It takes six parameters: C_U , C_V , P_U , P_V , H_U , and H_V . Here, C_U and C_V represent the candidate sets, where the nodes are common neighbors of $P_V \cup H_V$ and $P_U \cup H_U$, respectively. The sets P_U , P_V , H_U , and H_V form a partial biclique, where $(P_U \cup H_U, P_V \cup H_V)$ is already a biclique, and $|H_U| < p$ and $|H_V| < q$. The goal of NPC is to count the (p, q) -bicliques that contain all of H_U and H_V , and partially include nodes from C_U , C_V , P_U , and P_V . Importantly, P_U and P_V serve as the node-pivots. Since node-pivots connect to all candidate nodes, any biclique extended by node-pivots remains a biclique. Therefore, after moving node-pivots from C_U and C_V to P_U and P_V (lines 16-17), the task reduces to counting bicliques in the remaining C_U and C_V . For example, if a node u is moved from C_{U} to P_{U} as a node-pivot and there are $x (p - 1, q)$ -bicliques in the remaining candidate sets, there will be $x (p, q)$ -bicliques directly. Thus, the algorithm focuses on counting bicliques in the remaining candidate sets (lines 18-23).

After removing node-pivots, NPC processes the remaining candidate sets. Instead of enumerating one node at a time, NPC splits the sets into L_U , L_V and their complements $C_U \backslash L_U$ and $C_V \backslash L_V$ (line 18). The bicliques in $\left(C_{U},C_{V}\right)$ are categorized based on whether they include nodes from L_U and L_V . For each node in L_U and L_V , NPC recursively counts bicliques that include the node and exclude the nodes preceding it (lines 19-22). The nodes are removed from the candidate sets to avoid double-counting (line 20), and the nodes that must be included are placed in H_U and H_V (line 21). For instance, if u_0 , u_1 , and u_2 are three nodes considered in line 19, the recursive call in line 21 counts bicliques that must include u_0 and may include u_1 and u_2 . The next recursive call counts bicliques that exclude u_0 , must include u_1 , and may include u_2 . Finally, after removing L_U and L_V from C_U and C_V (lines 20 and 22), NPC recursively counts the bicliques in the remaining candidate sets (line 23).

Thanks to the node-pivots, the large biclique ($P_U \cup H_U$, $P_V \cup H_V$) encodes a unique representation of the set of bicliques $\{ (P'_U \cup$ $H_U, P'_V \cup H_V$) $\Big| P'_U \subseteq P_U, P'_V \subseteq P_V \Big|$. In this framework, H_U and H_V are required to be chosen, while P_U and P_V are optional. This leads to the derivation of Theorem [4.2.](#page-4-0)

THEOREM 4.2. There are $\binom{|P_U|}{n-1}$ $\binom{|P_U|}{p-|H_U|} \times \binom{|P_V|}{q-|H_V|}$ $\frac{|P_V|}{|q-|H_V|}$) (p, q)-bicliques encoded in a large biclique $(P_U \cup H_U, P_V \cup H_V)$.

The NPC procedure terminates when either there is no edge left or the number of required nodes reaches the maximum size (lines 14-15). The following four cases, based on Theorem [4.2,](#page-4-0) describe the scenarios of the count procedure (lines 14-15 and 24-26).

- Case 1: $(C_U \times C_V) \cap E = \emptyset$, with $C_U \neq \emptyset$ and $C_V \neq \emptyset$. Here, C_U represents the common neighbors of $P_V \cup H_V$, so all nodes in C_U can be moved into $P_U.$ The (p,q) -biclique in $((P_U \cup$ $(C_U) \cup H_U, P_V \cup H_V$) is counted as $\binom{p_0+c_0}{p-h_0}\binom{p_1}{q-h_1}$ (line 26). Similarly, C_V , being the common neighbors of $P_U \cup H_U$, gives the item $\binom{p_0}{p-h_0}\binom{p_1+c_1}{q-h_1}$. However, directly adding C_V to P_V would result in double-counting the pair $(P_U \cup H_U, P_V \cup H_V)$, so we subtract $\binom{p_0}{p-h_0}\binom{p_1}{q-h_1}$.
- Case 2: $(C_U \times C_V) \cap E = \emptyset$, with $C_U = \emptyset$. In this case, all nodes in C_V are moved to P_V , and the (p, q) -biclique in $((P_U \cup C_U) \cup$ H_U , $(P_V \cup C_V) \cup H_V$) is counted (line 25).
- Case 3: $(C_U \times C_V) \cap E = \emptyset$, with $C_V = \emptyset$. This case mirrors Case 2.

Case 4: $|H_U| = p$ or $|H_V| = q$. When $|H_U| = p$ or $|H_V| = q$, we have $p - h_0 = 0$ or $q - h_1 = 0$, and the counts on lines 25-26 are correct, as they account for the completed bicliques.

THEOREM 4.3. NPivoter can count (p, q) -bicliques correctly.

PROOF. To prove Theorem [4.3,](#page-4-1) it is sufficient to show that each (p, q) -biclique is counted exactly once. Consider the recursive search process of the NPC procedure as a search tree. At each search tree vertex, every biclique is counted in exactly one root to leaf path. At each vertex in the search tree, if a biclique contains nodes from $L_U \cup L_V$, it will be counted in lines 21 or 22. Since the nodes in $L_U \cup L_V$ are removed from the candidate sets (line 20), no repeated counting occurs for those nodes. If a biclique does not contain nodes from $L_U \cup L_V$, it will be counted in the child tree vertex generated from line 23. Thus, each biclique belongs to only one path in the search tree and is counted exactly once. This ensures that the algorithm correctly counts all (p, q) -bicliques without duplication. \square

BCList++ as a Special Implementation of NPivoter. BCList++ can be viewed as a specialized implementation of the NPivoter framework. While BCList++ processes the entire graph, its initial layer mirrors the node-split strategy [\[50\]](#page-15-3). The enumeration process in BCList++ is a simplified version of the NPC procedure. Specifically, BCList++ does not utilize node-pivots, as seen in lines 16-17

Algorithm 2: Local counting

1 $local_u \leftarrow 0, \forall u \in U \cup V;$ 2 Procedure localcount $(C_U, C_V, P_U, P_V, H_U, H_V)$ $3 \mid c_0, c_1, p_0, p_1, h_0, h_1 \leftarrow |C_U|, |C_V|, |P_U|, |H_V|, |H_V|;$ 4 if $c_0 > 0$ and $c_1 > 0$ then ⁵ localcount(∅, ∅, ∪ , , ,); 6 | $P_V \leftarrow P_V \cup C_V;$ $7 \mid \cdot \cdot \cdot \cdot \cdot C_V$ do $\{8\}$ $\left| \right|$ $P_V \leftarrow P_V \setminus \{v\};$ ⁹ localcount(∅, ∅, , , , ∪ {}); $10 \quad |$ else 11 $\vert p_0 \leftarrow p_0 + c_0, p_1 \leftarrow p_1 + c_1;$ 12 for $u \in P_U \cup C_U$ do $local_u \leftarrow local_u + {p_0-1 \choose p-h_0-1} {p_1 \choose q-h_1};$ 13 **for** $v \in P_V \cup C_V$ **do** $local_v \leftarrow local_v + {p_0 \choose p-h_0} {p_1-1 \choose q-h_1-1};$ 14 for $u \in H_U \cup H_V$ do $local_u \leftarrow local_u + {p_0 \choose p-h_0} {p_1 \choose q-h_1};$

of Algorithm [1.](#page-3-0) It sets $L_U = C_U$ and $L_V = \emptyset$ in line 18, and there are no remaining candidate sets in line 23 for further enumeration. BCList++ only terminates when $|H_U| = p$ (line 14). During the count procedure (line 24), BCList++ simplifies the process with $c_0 = p_0 = p_1 = h_1 = 0, h_0 = p$, and $c_1 = |C_V|$.

EPivoter as a Special Implementation of NPivoter. EPivoter follows a different approach by using the edge-split strategy (lines 5-8 of Algorithm [1\)](#page-3-0). Its enumeration process is also a variant of the NPC procedure. EPivoter selects the edge (u, v) with the maximum number of neighbors and sets $L_U = C_U \setminus N(v) \setminus \{u\}$ and $L_V =$ $C_V \setminus N(u) \setminus \{v\}$. The edge (u, v) will be moved into P_U and P_V as an edge-pivot in the next recursive search layer (line 23). In the count procedure, NPivoter uses a constant-time inclusion-exclusion principle to avoid duplicate-counting (line 26), whereas EPivoter uses an enumeration method with linear time complexity [\[52\]](#page-15-4).

Local Counting. Theorem [4.2](#page-4-0) can be extended to perform local counting. Each node in $H_U \cup H_V$ is involved in $\binom{|P_U|}{n-|H_V|}$ $|P_U| \atop p-|H_U| \to (\frac{|P_V|}{q-|H_V|})$ $\frac{|PV|}{|q-|H_V|}$

Conference'17, July 2017, Washington, DC, USA Xiaowei Ye, Rong-Hua Li, Longlong Lin, Shaojie Qiao, Guoren Wang

 (p, q) -bicliques. A node in P_U contributes to $\binom{|P_U|-1}{q-|H_V|}$ $|P_U|^{-1}_{-1}$ $\times (|P_V|$
p- $|H_U|^{-1}_{-1})$ $\times (|P_V|)$ $\frac{|PV|}{|q-|H_V|}$ (p, q) -bicliques, while a node in P_V contributes to $\binom{|P_V|}{\vert H_V\vert}$ $\frac{|P_U|}{p-|H_U|}$ $\times \frac{|P_V|-1}{|H_V|-1}$ $\frac{|PV|-1}{|q-|H_V|-1}$ (p, q) -bicliques. By modifying the count procedure to perform local counting, NPivoter can efficiently handle this task. Algorithm [2](#page-4-2) is the pseudo-code for local counting. When $c_0 > 0$ and $c_1 > 0$ (line 4), localcount firstly insert C_U into P_U to count the bicliques in $(C_U \cup P_U \cup H_U, P_V \cup H_V)$, i.e. the bicliques without nodes in C_V (line 5), and then count the bicliques containing nodes in C_V (lines 6-9). When $c_0 = 0$ or $c_1 = 0$, insert the cadidate sets into the node-pivots (line 11), and count the bicliques for each kind of nodes (lines 12-14).

Range Counting. Given a large biclique ($P_U \cup H_U$, $P_V \cup H_V$), The-orem [4.2](#page-4-0) applies to all $p \in [|H_U|, |P_U \cup H_U|]$ and $q \in [|H_V|, |P_V \cup$ $|H_V|$]. The current count procedure in NPivoter only counts bicliques for a specific pair of p and q . To handle range counting with specified ranges $[p_l, p_u]$ and $[q_l, q_u]$, NPivoter can execute the count procedure $(p_u - p_l)(q_u - q_l)$ times, enabling it to count bicliques within the given size range simultaneously. Algorithm [3](#page-4-3) is the pseudo-code. l_0 and l_1 are the minimum number of nodes to contain, which is the lower bound of p and q (line 4). When $c_0 = 0$ or $c_1 = 0$, $\min(p_0 + c_0 + h_0, p_u)$ and $\min(p_1 + c_1 + h_1, q_u)$ are the upper bound of p and q (line 6 and 7). When $c_0 > 0$ and $c_1 > 0$, lines 10 counts the bicliques in $((C_U \cup P_U) \cup H_U, P_V \cup H_V)$, line 11 counts the bicliques in $(P_U \cup H_U, (C_V \cup P_V) \cup H_V)$, and line 12 subtract the double-counting part $(P_U \cup H_U, P_V \cup H_V)$.

4.2 A Novel Minimum Non-neighbor Candidate Partition Strategy

As a general framework, NPivoter does not inherently possess a specific time complexity. The time complexity depends on the specific design of the candidate partition strategy, i.e. how to choose L_U and L_V (line 18 of Algorithm [1\)](#page-3-0). In this subsection, we propose the minimum non-neighbor candidate partition strategy, with which NPivoter can achieve a lower worst-case time complexity than the previous SOTA works, as proven in Theorem [4.6](#page-6-0) and Theorem [4.7.](#page-6-1)

We start with the definition of the minimum non-neighbor candidate partition. The minimum non-neighbor candidate partition selects L_U and L_V based on the non-neighbors of the node with the fewest non-neighbors. The core idea behind the minimum nonneighbor candidate partition is to minimize the sizes of the sets L_U and L_V during the recursive calls in the NPC procedure. Each recursive node in the NPC search tree has $|L_U| + |L_V| + 1$ child nodes, so reducing the sizes of L_U and L_V leads to a smaller overall search tree and more efficient computation.

Definition 4.4 (Minimum non-neighbor candidate partition). For the sets C_U and C_V , the node with minimum non-neighbor is

$$
w \leftarrow \arg\min_{u \in C_U \cup C_V} (\min(|C_U \setminus N(u)|, |C_V \setminus N(u)|)).
$$

The partitioning is done as follows:

$$
\begin{cases}\nL_U \leftarrow C_U \setminus N(w), L_V \leftarrow \emptyset, & |C_U \setminus N(w)| \leq |C_V \setminus N(w)| \\
L_U \leftarrow \emptyset, L_V \leftarrow C_V \setminus N(w), & |C_U \setminus N(w)| > |C_V \setminus N(w)|\n\end{cases}
$$

In Definition [4.4,](#page-5-1) w may be in C_U or C_V . We mainly discuss the cases when $w \in C_U$, and the following result also holds when $w \in C_V$. When $w \in C_U$, it is true that $C_U \setminus N(w) = C_U$ because $N(w)$ refers to the set of nodes on the opposite side of the bipartite graph connected to w. If $|C_U| = |C_U \setminus N(w)| \leq |C_V \setminus N(w)|$, we can conclude that $L_U = C_U$, meaning that we can enumerate the nodes on the U -side directly. This condition suggests that when the size of C_U is small enough, it becomes efficient to enumerate the nodes in C_U . On the other hand, if $|C_U| = |C_U \setminus N(w)| \ge |C_V \setminus N(w)|$, the more efficient strategy is to enumerate the non-neighbors of w on the *V*-side, meaning $L_V = C_V \setminus N(w)$. The partition optimizes the process by leveraging the smaller subset of nodes, ensuring that either side of the bipartite graph is efficiently handled depending on their relative sizes. Algorithm [4](#page-5-2) is the pseudo-code of the implementation with the minimum non-neighbor candidate partition strategy. The following example illustrates how our algorithm works.

Example 4.5. Figure [2](#page-6-2) illustrates the process of NPivoter for counting (3, 3)-biclique. The example graph and the associated icon descrip-tion are presented in Figure [2\(](#page-6-2)a). Figure 2(b), (c), and (d) are running processes of the NPC procedure, with the node-split strategy. For clarity, edges connected to the already selected nodes P_U , P_V , H_U , and H_V (within the blue and green boxes) are omitted, as $(P_U \cup H_U, P_V \cup H_V)$ already forms a biclique, and C_U and C_V represent the sets of common neighbors of $P_U \cup H_U$ and $P_V \cup H_V$, respectively. The upper nodes are labeled from u_0 to u_4 , and the lower nodes are labeled from v_0 to v_4 . In Figure [2\(](#page-6-2)b), NPivoter counts the $(3, 3)$ -bicliques that contain u_0 . So u_0 is in H_U . The candidate sets are now $C_U = \{u_1, u_2, u_3, u_4\}$ and $C_V = \{v_0, v_1, v_2, v_3\}$. Since v_1 and v_2 connect to all nodes in C_U , they are moved into the node-pivots (represented by dotted cycles, moving from the red box to the blue box, as indicated in lines 16-17 of Algorithm [1\)](#page-3-0). In the remaining candidate sets $C_{U} = \{u_1, u_2, u_3, u_4\}$ and $C_V = \{v_0, v_3\}$, u_1 has the minimum number of non-neighbors, and let $L_U = \emptyset, L_V = \{v_3\}$ (lines 3-5 of Algorithm [4\)](#page-5-2). Put v_3 into H_V and recursively call NPC to count the bicliques containing v_3 (line 23 of Algorithm [1\)](#page-3-0). There is no edge between the candidate sets $C_U = \{u_2, u_3, u_4\}$ and $C_V = \{v_0\}$ (line 14 of Algorithm [1\)](#page-3-0) and the count procedure will add three (3, 3)-bicliques. Then backtrack to the previous layer and recursively call the NPC procedure (line 23 of Algorithm [1\)](#page-3-0). After moving u_1 into P_U , there is no edge between the candidate sets. In this case, there is no L_U and L_V , and just recursively call the NPC procedure to count the result (line 23 and 14 of Algo-rithm [1\)](#page-3-0). Figure $2(c)$ is running process of counting the $(3, 3)$ -bicliques that contain u_1 , which has 3 (3, 3)-bicliques. Figure [2\(](#page-6-2)d) is running process of counting the $(3, 3)$ -bicliques that contain u_2 , which has 4 $(3, 3)$ -bicliques.

Fast Biclique Counting on Bipartite Graphs: A Node Pivot-based Approach Conference' 17, July 2017, Washington, DC, USA

Figure 2: A running example of our proposed NPivoter

Time Complexity of NPC and NPivoter. The time complexity of the NPC procedure and the entire NPivoter framework, when equipped with the minimum non-neighbor candidate partition strategy, is detailed in Theorem [4.6](#page-6-0) and Theorem [4.7.](#page-6-1)

Theorem 4.6. With the minimum non-neighbor candidate partition strategy, the NPC procedure has time complexity of $O(2^{\frac{n'}{2}})$ where $n' = |C_U| + |C_V|$.

PROOF. The time complexity of finding the node-pivot in each recursive search vertex of NPC is $O(n'^2)$, which is equal to compute the degree of each node. For simplicity, we use *n* instead of n' in the following context.

Let $T(n)$ be the time complexity of NPC with input C_U, C_V . Let k be the number of the minimum non-neighbors and c_3 be constant. We can derive that

$$
T(n) \le \sum_{i=1}^{k} T(n-k-i) + T(n-k-1) + c_3 n^2, \tag{1}
$$

where $\sum_{i=1}^{k} T(n-k-i)$ is the time complexity of lines 19-22 of Algorithm [1,](#page-3-0) $T(n - k - 1)$ is the time complexity of line 23 of Algorithm [1](#page-3-0) and c_3n^2 is the time complexity of finding the nodepivots. Define constant numbers c_1 , c_2 , c_3 that satisfy $c_1 \geq 4.5(c_2 +$ c_3). We can prove that

$$
T(n) \le c_1 2^{n/2} - c_2 n^2. \tag{2}
$$

When $n = 1$, we have $T(1) \leq c_1\sqrt{2} - c_2$ from inequality [\(2\)](#page-6-3) and $T(1) \leq c_3$ $T(1) \leq c_3$ $T(1) \leq c_3$ from inequality (1). inequality [\(2\)](#page-6-3) holds because $c_1 \geq 4.5(c_2 + c_3) > \frac{c_2 + c_3}{\sqrt{2}}$ $rac{c_3}{2}$.

Let N be a positive integer. We assume that inequality [\(2\)](#page-6-3) holds for all integers $n \in [1, N-1]$, and prove that it also holds for $n = N$. **Case** $k = 2$. inequality [\(1\)](#page-5-3) becomes $T(n) \le 2T(n-3) + T(n-4) + c_3 n^2$. According to the assumption, we have

$$
T(n) \le 2T(n-3) + T(n-4) + c_3 n^2
$$

\n
$$
\le 2c_1 2^{\frac{n-3}{2}} - c_2 (n-3)^2 + c_1 2^{\frac{n-4}{2}} - c_2 (n-4)^2 + c_3 n^2
$$

\n
$$
\le (2^{-\frac{1}{2}} + 2^{-2})c_1 2^{\frac{n}{2}} + c_3 n^2
$$

\n
$$
\le c_1 2^{\frac{n}{2}} - c_2 n^2.
$$
\n(3)

The last inequality equals to prove

$$
\frac{n^2}{2^{n/2}} \le \frac{(1-2^{-\frac{1}{2}}-2^{-2})c_1}{c_2+c_3} \le \frac{c_1}{c_2+c_3} \tag{4}
$$

Table 1: Time complexity comparison ($2^{\frac{1}{2}} \approx 1.414, 3^{\frac{1}{3}} \approx 1.442$)

holds for all *n*. Since $\frac{n^2}{n}$ $\frac{n^2}{2^{n/2}} \leq 4.5 \left(\frac{n^2}{2^{n/2}} \right)$ $\frac{n^2}{2^{n/2}}$ = 4.5 when *n* = 6) and $\frac{c_1}{c_2+c_3} \geq 4.5$, the mathematical induction is proved.

Case $k \neq 2$. A scaled inequality [\(1\)](#page-5-3) is

$$
T(n) \le (k+1)T(n-(k+1)) + c_3 n^2, \tag{5}
$$

from which we have

$$
T(n) \le (k+1)c_1 2^{(n-(k+1))/2} - c_2(k+1)(n-(k+1))^2 + c_3 n^2
$$

\n
$$
\le (k+1)2^{-\frac{k+1}{2}} \cdot c_1 2^{n/2} + c_3 n^2
$$

\n
$$
\le c_1 2^{\frac{n}{2}} - c_2 n^2.
$$
 (6)

The last inequality comes from (1) $(k + 1)2^{-\frac{k+1}{2}}$ is always no larger than 1; (2) the following inequality is always true

$$
\frac{n^2}{2^{n/2}} \le \frac{(1 - (k+1)2^{-\frac{k+1}{2}})c_1}{c_2 + c_3} \le \frac{c_1}{c_2 + c_3} \tag{7}
$$

Since $\frac{n^2}{2}$ $\frac{n^2}{2^{n/2}} \leq 4.5 \left(\frac{n^2}{2^{n/2}} \right)$ $\frac{n^2}{2^{n/2}}$ = 4.5 when *n* = 6) and $\frac{c_1}{c_2+c_3}$ ≥ 4.5, the mathematical induction is proved.

As a result, the time complexity of NPC is $O(2^{n'/2})$.

Theorem 4.7. With the minimum non-neighbor candidate parti-tion strategy, the time complexity of Algorithm [1](#page-3-0) is $O(|E|2^{n_{max}/2})$, where $n_{max} = \max_{u \in U} |N(u, V)| + \max_{v \in V} |N(v, U)|$.

PROOF. The number of calling NPC is bounded by $|E|$, and the size of $|C_U| + |C_V|$ is bounded by n_{max} . Thus, according to Theo-rem [4.6,](#page-6-0) the time complexity of Algorithm [1](#page-3-0) is $O(|E|2^{n_{max}/2})$. \Box

The Superiority of NPivoter on the Time Complexity. Table [1](#page-6-4) summarizes the time complexity of the proposed NPivoter and SOTA methods. The time complexity of EPivoter is $O(|E|3^{|E_{max}|/3})$, where $|E_{max}|$ is bounded by the maximum number of edge among all candidate sets of edge-split strategy. Since $2^{\frac{1}{2}} \approx 1.414, 3^{\frac{1}{3}} \approx 1.442$ and $|E_{max}| > n_{max}$, our NPivoter has a lower worst-case time complexity. The time complexity of BCList++ is $O(\alpha(H)^{p-2} | E' | d_{\text{max}} +$ \triangle), as outlined in Section [3.1.](#page-1-1) Here, $\alpha(H)$ represents the arboricity

Algorithm 5: Cost estimator (line 4 of Algorithm [1\)](#page-3-0)

Input: The graph $G(U, V, E)$, a node u, two integers x, y Output: True if edge-split, False if node-split 1 Procedure $costEs(l, r, e)$ 2 if $l < x$ or $r < y$ then return 0; 3 return $\left(\left(\frac{e}{\min(l,r)} \right)^{min(l,r)}, 2^{\frac{\min(l,r)}{2}} \right)$; 4 Denote R by the rank of nodes; 5 $cost_{node} \leftarrow 0; cost_{edge} \leftarrow 0; l \leftarrow 0; r \leftarrow 0; e \leftarrow 0;$ 6 $cnt_w \leftarrow 0, \forall w \in \bigcup_{v \in N(u)} N(v);$ 7 for $v \in N(u)$ do 8 for $w \in N(v)$ s.t. $R(w) > R(u)$ do 9 $ent_w \leftarrow ent_w + 1;$ 10 if $cnt_w = y$ then $l \leftarrow l + 1$; 11 Label $N(u)$ by $\{v_1, v_1, v_2, ... v_{d(u)}\}$ with $R(v_i) < R(v_{i+1});$ 12 ss \leftarrow {0, 0, ...0}; /*suffix sum vector with length $d(u)$ */ 13 for $i = 1$ to $d(u)$ do 14 $l'_w \leftarrow 0;$ 15 **for** $w \in N(v_i)$ s.t. $R(w) > R(u)$ do 16 if $cnt_w \geq y$ then $\{l'_w = l'_w + 1; e \leftarrow e + 1\};$ 17 if $l'_w \ge x - 1$ then $\{r \leftarrow r + 1; ss_i \leftarrow 1\};$ 18 for $i = d(u)$ to 2 do $ss_{i-1} \leftarrow ss_{i-1} + ss_i$; 19 for $i = 1$ to $d(u)$ do $20 \quad | \quad l' \leftarrow 0; r' \leftarrow ss_i; e' \leftarrow 0;$ 21 for $w \in N(v_i)$ s.t. $R(w) > R(u)$ do 22 if $cnt_w \ge y$ then $\{l' = l' + 1; e' \leftarrow e' + cnt_w\};$ 23 $ent_w \leftarrow cnt_w - 1;$ 24 if $l' \geq x - 1$ then $cost_{edge} \leftarrow cost_{edge} + costEs(l', r', e')$; 25 $cost_{node} \leftarrow \text{costEs}(l, r, e);$ 26 if $cost_{node} < cost_{edge}$ then return False; else return True;

in the 2-hop graph H, and in the worst case, $\alpha(H)$ is on the order of n_{max} [\[30,](#page-14-10) [32,](#page-14-11) [50\]](#page-15-3). $|E'|$ is in the order of $d_{max}|E|$. Δ is the result size, which can be quite large for large real-world networks. Therefore, NPivoter also outperforms BCList++.

4.3 The Proposed Cost Estimator

The BCList++ algorithm employs a node-split strategy, while EPivoter uses an edge-split strategy (Section [3\)](#page-1-2). Intuitively, the node-split strategy tends to be more efficient for dense graphs with more connections. In such graphs, the subgraphs generated from edgesplitting can be nearly as large as the entire graph, resulting in minimal reduction in problem size and inefficiency. Conversely, in sparse graphs, the edge-split strategy becomes more efficient. In this case, the subgraphs created by splitting edges are much smaller, allowing EPivoter to perform faster due to the reduced search space. Thus, node-split excels in handling dense structures, whereas edge-split is more suited for sparse graph scenarios.

To leverage the advantages of both the node-split and edge-split strategies, we propose a novel cost estimator that helps determine when to use the node-split (lines 10-11) or edge-split (lines 5-8) strategy in line 4 of Algorithm [1.](#page-3-0) The goal of this estimator is to predict which graph-split strategy will be more efficient. Specifically, let the variables l , r , and e be the sizes of the candidate sets and the number of edges as follows: $l = |C_{U}|$ (the size of the candidate

set C_U), $r = |C_V|$ (the size of the candidate set C_V), $e = |(C_U \times$ $(C_V) \cap E$ (the number of edges between C_U and C_V). Theorem [4.6](#page-6-0) initially suggests using $2^{\frac{1+r}{2}}$ as a measure of the running cost for the recursive process. However, this measure has two main drawbacks: 1. Imbalance Between l and r : When the sizes of l and r differ significantly, the smaller value dominates the computation cost, rather than their sum. To account for this, we replace $2^{\frac{1+r}{2}}$ with $2^{\frac{\min(l,r)}{2}}$, focusing on the smaller of the two sets. 2. Edge Density Consideration: The initial measure only accounts for the number of nodes and ignores the number of edges, which can significantly impact the algorithm's performance. When the number of edges e is small, the algorithm can still run efficiently even if the combined size of l and r is large.

To address these limitations, we propose a new metric that incorporates both the number of nodes and edges. This new metric is based on the observation that the complexity of the algorithm increases as we process more edges between C_U and C_V . The refined metric is defined as follows:

$$
\left(\frac{e}{\min(l,r)}\right)^{\min(l,r)}.
$$
\n(8)

This term reflects the idea that if a set contains a items, the number of subsets of size *b* is proportional to $\binom{a}{b}$, which is bounded by a^b . In this case, $a = \frac{e}{\min(l,r)}$ and $b = \min(l,r)$. Here, $\frac{e}{\min(l,r)}$ represents the average number of neighbors for a node in the smaller of the two sets, while $\left(\frac{e}{\min(l,r)}\right)^{\min(l,r)}$ estimates the complexity of processing all possible subsets of neighbors of size $min(l, r)$. The final running cost estimation of the NPC procedure combines both node and edge considerations:

$$
\min\left(\left(\frac{e}{\min(l,r)}\right)^{\min(l,r)}, 2^{\frac{\min(l,r)}{2}}\right) \tag{9}
$$

This metric balances the trade-offs between node size and edge density, effectively estimating the computational cost. As demonstrated in our experiments, this cost estimation provides reliable guidance for choosing the most efficient graph-split strategy.

The cost estimator computes two values $cost_{node}$ and $cost_{edge}$, which represent the computation cost of the two strategies respectively. For $cost_{node}$, we compute the value of l, r, e and let $cost_{node} = \min((\frac{e}{\min(l,r)})^{\min(l,r)}, 2^{\frac{\min(l,r)}{2}})$. The computation of $cost_{edae}$ is more complex. In Algorithm [1,](#page-3-0) the edge-split has multiple calls of NPC (line 8). Hence, we compute cost estimation for each edge and sum them together as the final value of $cost_{edae}$.

Algorithm [5](#page-7-1) outlines the pseudo-code of the cost estimator. Algorithm [5](#page-7-1) inputs a node u and two integers x, y , and returns whether node-split or edge-split is more efficient to count (p, q) biclique with $p \ge x, q \ge y$. The costEs procedure (lines 1-3 of Algorithm [5\)](#page-7-1) returns the cost estimation of a NPC procedure with input $l = |C_U|, r = |C_V|, e = |(C_U \times C_V) \cap E|$. For approximating $cost_{node}$, Algorithm [5](#page-7-1) maintains *l, r, e* (line 5). *l* is the number of nodes in U that have larger rank than u and has more than y neighbors in $N(u)$ (lines 7-10). r is the number of nodes in $N(u)$ that have more than $x - 1$ neighbors in the previous l nodes (lines 13-17). e is the number of edges between the l and r nodes (lines 13-16).

At last, $cost_{node} = \min((\frac{e}{\min(l,r)})^{\min(l,r)}, 2^{\frac{l+r}{2}})$ (line 25). For approximating $cost_{edae}$, Algorithm [5](#page-7-1) approximates l', r', e' for each edge (line 19-24). Consider an edge (u, v_i) . l' is the number of nodes in U that has larger rank than u and has more than y neighbors in $S_{u,v_i} = \{v | v \in N(u), R(v) > R(v_i) \}$ (lines 19-22). r' is the number of nodes in S_{u,v_i} that has more than $x - 1$ neighbors (line , 17, 18, 20). Label the nodes in $N(u)$ by $\{v_1, v_1, v_2, ... v_{d(u)}\}$ (line 11). Instead of computing r' for each edge. Algorithm [5](#page-7-1) records a suffix summary vector ss where s_{i} is the number of nodes in ${v | v \in N(u), R(v) > R(v_i)}$ that has more than $x - 1$ neighbors (lines 17-18). Thus, we can use ss_i to approximate r' directly (line 20). Due to the edges before v_i being removed already (line 23), cnt_w is the number of neighbors of w with rank larger than v_i . Thus, sum all the sum_w together is the number of edges e' (line 22). At last, $cost_{edge} = \min((\frac{e'}{\min(l', r')})^{\min(l', r')}, 2^{\frac{l' + r'}{2}})$ (line 24).

THEOREM 4.8. Given a bipartite graph $G(U, V, E)$, in Algorithm [1](#page-3-0) (line 4), the total time complexity of Algorithm [5](#page-7-1) is $O(\alpha(G)|E|)$, where $\alpha(G)$ is the arboricity of G.

PROOF. For each node u (i.e., line 3 of Algorithm [1\)](#page-3-0), lines 7, 13 and 19 of Algorithm [5](#page-7-1) scan the neighbors of u , which has complexity of $O(|E|)$. Each line of lines 8, 15, and 21 of Algo-rithm [5](#page-7-1) scan the neighbors of a neighbor of u , which has a total time complexity of $O(\sum_{(u,v)\in E} d(v))$. According to the definition of $\alpha(G)$ [\[12\]](#page-14-9), E can be partitioned into $\alpha(G)$ edge-disjoint spanning forests, and let these trees be F_i , $1 \leq i \leq \alpha(G)$, where $|F_i| \leq |V|$. We have $\sum_{(u,v)\in E} d(v) = \sum_i^{\alpha(G)} \sum_{(u,v)\in F_i} d(v) \leq$ $\sum_i^{\alpha(G)} \sum_{v \in V} d(v) = 2\alpha(G)|E|$. Thus, the complexity of Algorithm [5](#page-7-1) is $O(\alpha(G)|E|)$.

Theorem [4.8](#page-8-1) demonstrates that the cost estimator has a polynomial time complexity, which is significantly smaller compared to the complexity of the biclique counting algorithm. By efficiently estimating the cost of various candidate sets, the cost estimator allows the algorithm to choose the most optimal strategy dynamically. Our empirical results confirm that the proposed algorithm, when equipped with the cost estimator, outperforms approaches relying on a single fixed graph-split strategy (Section [6\)](#page-8-0).

Cost Estimator based Index. When counting (p, q) -bicliques, the parameters x and y should not exceed p and q . To optimize this process, we can build an index for x and y . Specifically, the index is a vector of length $|U|$, storing the results of Algorithm [5](#page-7-1) for each node in *U*. Equipped with the pre-computed index, when $p \geq x$ and $q \geq y$, Algorithm [1](#page-3-0) can determine whether a node-split or edge-split is more efficient in constant time complexity for each node. The time complexity of building the index is Theorem [4.8.](#page-8-1)

5 FURTHER OPTIMIZATIONS

In this section, we devise several optimization tricks to further improve the efficiency of our proposed algorithm.

 (α, β) -core Based Graph Reduction [\[50\]](#page-15-3). For the bipartite graph $G(U, V, E)$ and any (p, q) -biclique (X, Y) , every node $u \in X$ must have at least q neighbors in V, and every node $v \in Y$ must have at least p neighbors in U . This allows us to simplify the graph by reducing it to its (p, q) -core, which retains only the nodes and edges that are essential for potential (p, q) -bicliques [\[50\]](#page-15-3). The most efficient algorithm for computing the (p, q) -core of a bipartite graph $G(U, V, E)$ operates in linear time with a complexity of $O(|E|)$ [\[14\]](#page-14-12).

Definition 5.1 ((p, q)-core [\[14,](#page-14-12) [28\]](#page-14-13)). For a bipartite graph $G(U, V, E)$ and two integers p and q , the (p, q) -core of G is a maximal subgraph $G_c(U_c, V_c, E_c)$ where every node in U_c has at least q neighbors in V_c , and every node in V_c has at least p neighbors in U_c .

Core Value-Based Node Ranking. The core ordering method [\[4\]](#page-14-14) is a commonly used strategy in graph mining tasks to enhance the algorithm efficiency [\[16,](#page-14-15) [22,](#page-14-16) [39,](#page-14-17) [50\]](#page-15-3). The core value of a node u is defined as the highest degree that u holds in a subgraph where u has the smallest degree within that subgraph [\[11\]](#page-14-18). In this optimization, nodes are ranked according to their core values, where higherranked nodes correspond to those with larger core values. For any node, the number of the nodes with larger core values is bounded by the degeneracy of the graph [\[11\]](#page-14-18), which is often a small number for real-world networks [\[27\]](#page-14-19). This ranking ensures that only nodes with larger core values are included in the candidate sets during key steps of the NPC procedure (lines 6, 7, 10 of Algorithm [1\)](#page-3-0), optimizing the search space and improving computational performance.

Early Termination. The NPC procedure can be terminated early under the following conditions:

(1) Lower bounds on biclique size: If $|H_U| > p$ or $|H_V| > q$, the biclique is guaranteed to exceed the desired (p, q) -biclique size, as the nodes in H_U and H_V must be part of the solution (Theorem [4.2\)](#page-4-0).

(2) Upper bounds on biclique size: If $|C_U \cup P_U \cup H_U| < p$ or $|C_V \cup P_V \cup H_V|$ < q, the search can be terminated since these sets represent the upper bounds on the biclique size, making it impossible to reach a valid (p, q) -biclique.

(3) Single node in C_{II} : When $|C_{II}| = 1$, meaning that C_{II} contains only one node u , instead of branching into further recursive calls. the biclique count can be computed directly as $\binom{p_0}{p-h_0}\binom{p_1+c_1}{q-h_1}$ $\binom{p_0}{p-h_0-1}\binom{p_1+n_u}{q-h_1}$, where $n_u=|N(u)\cap C_V|$. The first term represents the bicliques that do not include u , while the second term counts bicliques containing u .

(4) Single node in C_V : Similarly, when $|C_V| = 1$ (i.e., C_V contains only one node v), the biclique count is $\binom{p_0+n_0}{p-h_0}\binom{p_1}{q-h_1-1}$ $\binom{p_0+c_0}{p-h_0}\binom{p_1}{q-h_1}$. The first term corresponds to bicliques that include v , and the second term counts bicliques that do not include v .

Efficient Maintenance of the Non-neighbor Count. During the NPC procedure in Algorithm [1,](#page-3-0) instead of recalculating the non-neighbor count from scratch at each recursive step, the algorithm reuses the non-neighbor counts from the parent search vertex. Specifically, for a node $w \in C_U$, let $C'_U = C_U \setminus \{w\}$. The nonneighbor set of any neighbor $u \in N(w, C_V)$ remains unchanged, i.e., $C_U \setminus N(u) = C'_U \setminus N(u)$. For non-neighbors $u \in C_V \setminus N(w)$, the non-neighbor set decreases by exactly one, i.e., $C_U \setminus N(u) \setminus \{w\} =$ $C'_U \setminus N(u)$. Leveraging this observation, the optimization effectively manages and updates non-neighbor counts without redundant recalculations.

6 EXPERIMENTS

We conduct extensive experiments to answer the following Research Questions. RQ1: How fast our algorithm runs? RQ2: What

Table 2: Datasets. \overline{d}_{U} and \overline{d}_{V} are the average degrees for U and V, respectively.

Datasets	Abbr	U	U Type	V	V Type	E	E Type	d_U	d_V
Youtube	You	94,238	User	30.087	Group	293,360	Membership	3.11	9.75
DailyKos	Kos	3.430	Document	6.906	Word	353,160	Occurrence	102.96	51.14
Bookcrossing	Book	77,802	User	185,955	Book	433,652	Rating	5.57	2.33
Github	Git	56,519	User	120,867	Project	440.237	Membership	7.79	3.64
Citeseer	Cite	105.353	Author	181.395	Publication	512.267	Authorship	4.86	2.82
Stackoverflow	Stac	545,195	User	96,678	Post	1,301,942	Favorite	2.39	13.47
Twitter	Twit	175.214	User	530.418	Hashtag	1.890.661	Usage	10.79	3.56
IMDB	IMDB	685.568	Person	186.414	Work	2,715,604	Association	3.96	14.57
DiscogsGenre	Genre	1,754,823	Artist	15	Genre	3,142,059	Feature	1.79	209470.60
Actor2	Act	303.617	Movie	896.302	Actor	3,782,463	Appearance	12.46	4.22
Amazon	Ama	2.146.057	User	1.230.915	Item	5,743,258	Rating	2.68	4.67
DBLP	DBLP	1,953,085	Author	5,624,219	Publication	12,282,059	Authorship	6.29	2.18

is the effectiveness of the proposed cost estimator? RQ3: What is the effect of the graph density, p and q on the efficiency of our NPivoter? RQ4: How fast the running time of local counting and range counting?

Table 3: The percentage of bicliques counted combinatorially

Datasets	(6, 6) (8, 8) (4, 4) (10, 10)				
You	74%	96%	100%	100%	
Kos	100%	100%	100%	100%	
Book	94%	100%	100%	100%	
Git	56%	75%	94%	100%	
Cite	100%	100%	100%	100%	
Stac	70%	97%	100%	100%	
Twit	91%	96%	94%	100%	
IMDB	95%	100%	100%	100%	
Genre	49%	51%	37%	85%	
Act	90%	100%	100%	100%	
Ama	73%	79%	93%	100%	
DBLP	100%	100%	100%	100%	

6.1 Experimental Setup

We evaluate all algorithms on a server with an AMD 3990X CPU and 256GB memory running Linux CentOS 7 operating system. We run algorithms against a single core. We terminate an algorithm if the running time is more than 10^6 mile-seconds (ms).

Datasets. We evaluate our algorithms on 12 real-world bipartite networks drawn from various domains, covering a wide range of applications and structural characteristics. These datasets, listed in Table [2,](#page-9-0) are downloaded from the KONECT project [\(http://konect.](http://konect.cc/networks/) [cc/networks/\)](http://konect.cc/networks/), which compiles diverse network datasets for research purposes. These datasets vary widely in terms of size and density, with node counts ranging from thousands to millions, and edge counts reflecting the number of connections between the two sets of entities. The average degrees for both sets of nodes, denoted as \overline{d}_U and \overline{d}_V , provide insight into the density of graph, highlighting the diversity in structure across different domains. These characteristics make the datasets an excellent test bed for evaluating the performance of biclique counting algorithms [\[50,](#page-15-3) [52\]](#page-15-4).

Algorithms. We compare BCList++ [\[50\]](#page-15-3) and EPivoter [\[52\]](#page-15-4) with our NPivoter. Both EPivoter and NPivoter apply to the range counting problem. NPivoter can also locally count the (p, q) -biclique for each node. All the algorithms are implemented in C++. The code of BCList++ and EPivoter are from the open-source repository [\[50,](#page-15-3) [52\]](#page-15-4). In default, NPivoter uses the cost estimator index with $x = y = min(p, q)$. The index building time is not included in our NPivoter because the computation time of the cost estimator index is negligible (compared to the biclique counting time) as shown in Exp-5, and the index creation can be treated as a preprocessing step. To be more reliable, we report the average running time and quality of 10 runs per algorithm.

6.2 Empirical Results

Exp-1: Running Time of Various Algorithms. Figure [3](#page-10-0) shows the running time of BCList++, EPivoter, and NPivoter with varying p and q on 12 real-world networks. Across almost all cases, NPivoter consistently demonstrates superior performance, significantly outperforming both BCList++ and EPivoter. For instance, on the Twit network for (10, 10)-biclique counting, NPivoter is two orders of magnitude faster than EPivoter. Similarly, on the Stac network for (10, 10)-biclique counting, NPivoter is two orders of magnitude faster than BCList++. These results highlight the high efficiency of NPivoter compared to other methods.

A notable and somewhat counter-intuitive observation is that the running time of NPivoter decreases as the values of p and q increase. For example, on the Kos network, the running time decreases when moving from (6, 6) to (6, 12)-biclique counting. Likewise, counting (12, 12)-bicliques takes less time than counting (9, 9)-bicliques or (6, 6)-bicliques. This phenomenon is primarily due to two reasons: (1) larger values of (p, q) enable more aggressive pruning of smalldegree nodes according to the (α, β) -core optimization (Section [5\)](#page-8-2), reducing the search space; (2) the impact of p and q on the search tree's size is minimal. Observe the NPC procedure in Algorithm [1,](#page-3-0) and we can find that p and q almost do not affect the search process except line 14. In effect, line 14 of Algorithm [1](#page-3-0) often terminates

Figure 3: Running time of various algorithms

due to empty edges instead of H_U or H_V reaching the maximum value, as shown in the following experiments. At last, this behavior demonstrates that NPivoter is well-suited for efficiently counting (p, q) -bicliques, even for large values of p and q .

Exp-2: Effectiveness of the Proposed Node-pivot Technique. Table [3](#page-9-1) presents the percentage of bicliques counting combinatorially across all datasets. A biclique is not counted combinatorially when it is handled in line 15 of Algorithm [1](#page-3-0) due to the condition $|H_u| = p$ or $|H_v| = q$ in line 14. As shown in Table [3,](#page-9-1) the majority of bicliques are counted in a combinatorial way. Furthermore, as the values of p and q increase, the percentage of combinatorially counted bicliques also increases. This is because larger values of p and q make it less likely to satisfy the condition $|H_u| = p$ or $|H_v| = q$ in line 14, demonstrating the growing effectiveness of the node-pivot technique with increasing biclique size. The results

Figure 4: Memory overhead of all algorithms

underscore the efficiency of the node-pivot method in reducing enumeration overhead and facilitating more efficient counting.

Figure 5: Effect of the cost estimator

Exp-3: Memory Overhead. Figure [4](#page-10-1) depicts the memory overheads of the evaluated algorithms: NPivoter, EPivoter, and BCList++. The memory consumption was tracked using the "ps -aux" command on the Linux system. As can be seen, we can observe that the three algorithms exhibit similar magnitudes of memory usage across the datasets. For instance, on the Amazon (Ama) dataset, NPivoter consumes 1,048 MB of memory, while EPivoter and BCList++ consume 546 MB and 1,578 MB, respectively. Across all datasets, NPivoter demonstrates memory efficiency, never using more than twice the memory of EPivoter. In many cases, the difference in memory usage between the algorithms is even smaller. This indicates that although NPivoter achieves significant performance improvements in terms of speed, it does not incur a significant increase in memory consumption. The results highlight that NPivoter strikes a balanced trade-off between computational efficiency and memory overhead, making it well-suited for large-scale applications where both memory and time are critical factors.

Exp-4: Effect of the Cost Estimator. Figure [5](#page-11-0) shows the impact of the cost estimator on the performance of NPivoter. To analyze this, we compare NPivoter with two versions that exclusively employ either the node-split or the edge-split strategy: NPivoter-N (node-split only) and NPivoter-E (edge-split only). We conducted experiments on two representative datasets, the Stac and Genre datasets, though the results were consistent across other networks as well. Specifically, on the Stac dataset, NPivoter-E—using only the edge-split strategy—proves to be more efficient than NPivoter-N, which exclusively applies the node-split strategy. This suggests that in sparser networks like Stac, edge-split is generally more effective due to the structure of the graph. Conversely, on the Genre network, NPivoter-N performs significantly better than NPivoter-E. This is due to the graph's smaller size and denser connections, where node-split is better suited to handle dense subgraphs. Despite the differences in performance between NPivoter-N and NPivoter-E across these graphs, NPivoter, which uses the cost estimator to

dynamically choose between the two strategies, consistently outperforms both. This clearly demonstrates the effectiveness of our cost estimator, which intelligently selects the more efficient split strategy based on the graph structure, leading to improved overall performance.

Exp-5: The Performance of Cost Estimator Index. Table [4](#page-11-1) shows two key aspects: the time required to build the cost estimator index and the proportion of nodes that employ the node-split strategy. The results show that building the index consumes quite less time than counting (p, q) -biclique, ensuring that building the index is not a major bottleneck in the algorithm. For instance, on the You dataset, counting takes 1989 ms, while building the index only takes 20 ms. First, the results indicate that the time taken to build the index is not significantly affected by the parameter values (x, y) . As (x, y) increases, the variation in index construction time is minimal. For example, on the You dataset, the index construction for $(10, 10)$ is only 1.6 times faster than that for $(4, 4)$. This indicates that the index construction time remains stable across different parameter settings.

Second, the results show that in most real-world datasets, a relatively small proportion of nodes use the node-split strategy. This is because real-world networks typically follow a power-law distribution, where a small subset of nodes (the "dense part") have a disproportionately high degree, while the majority of nodes (the "sparse part") have fewer connections. Consequently, the denser nodes tend to benefit from the node-split strategy, whereas the sparser nodes are better suited for the edge-split strategy. The exception is the Genre network, where most of the nodes employ the node-split strategy. This is due to the fact that Genre has only 15 nodes on one side of the bipartite graph, most of which are densely connected (as shown in Table [2\)](#page-9-0). Therefore, in this case, the node-split strategy dominates.

These findings reinforce the practical utility of the cost estimator, which adapts well to varying network structures by efficiently deciding whether to use node-split or edge-split based on the local graph characteristics. This flexibility contributes to the strong performance of NPivoter across diverse real-world datasets.

Table 5: The time cost of local counting for each node (ms)

Datasets	(4, 4)			(6, 6)	(8, 8)	
	Local	Global	Local	Global	Local	Global
You	2195	1989	1448	1325	745	704
Kos	378266	349997	324288	303924	198834	194317
Book	66	62	24	22	20	18
Git	61772	55600	50100	46091	28096	27441
Cite	22	20	16	15	14	13
Stac	3262	2994	1524	1437	557	539
Twit	14591	13478	6395	5821	3516	3138
IMDB	1122	1025	603	541	440	401
Genre	2240	2013	1641	1493	960	841
Act	2551	2310	1330	1206	914	812
Ama	6975	6418	3126	2948	1532	1410
DBLP	1553	1465	1265	1050	1113	930

Exp-6: Local Counting. Table [5](#page-12-0) reports the time taken for local counting of (p, q) -bicliques for each node, alongside the time required for global counting in the entire network. The columns labeled 'Local' correspond to the time spent in performing local counting, i.e., counting (p, q) -bicliques that involve each individual node. In contrast, the 'Global' columns show the time taken for counting all (p, q) -bicliques across the entire graph. As demonstrated in Table [5,](#page-12-0) local counting proves to be highly efficient, as it requires only marginally more time than global counting—at most $1.2\times$ longer. This is an important observation, as one might expect local counting to be significantly slower, given that it isolates the counting process for each node individually. However, the results indicate that our NPivoter algorithm handles local counting with minimal overhead, even when compared to the time needed for global counting over the entire graph.

The high efficiency of local counting is crucial in applications where the focus is on understanding the role or influence of specific nodes within the graph. For example, in social networks, it may be important to locally analyze the influence of certain users or groups. In recommendation systems, local counting allows for examining how particular items or users contribute to specific biclique patterns. Similarly, in citation networks, local counting helps analyze the impact of individual authors or papers on collaboration patterns. Deleted in the full version.

Exp-7: Range Counting. Table [6](#page-12-1) provides a comparative analysis of the time required for two different counting scenarios: counting only (4, 4)-bicliques versus counting all (p, q) -bicliques where $p \in [4, 10]$ and $q \in [4, 10]$ simultaneously. In Table [6](#page-12-1), we observe that range counting with NPivoter takes an order of magnitude longer than counting a single (4, 4)-biclique. For instance, on the You network, NPivoter requires 298 ms to count (4, 4)-bicliques but takes 2244 ms to perform range counting. This increase in computation time is expected due to the additional complexity involved in managing multiple parameters across a range of values, which inherently requires more extensive processing. Despite this, NPivoter's performance in range counting remains significantly superior to that of the state-of-the-art algorithm EPivoter. On the IMDB network, for example, NPivoter is 14.6 times faster than EPivoter for range counting tasks. This substantial efficiency

Datasets $\begin{array}{|c|c|c|c|c|}\n\hline\n\text{NPivoter} & \text{EPivoter} \\
\hline\n(4.4) & \text{all} & (4.4) & \text{all} \\
\hline\n\end{array}$ $(4, 4)$ You | 298 2244 | 13939 16338 Kos | 104967 403350 $> 10^6$ > 10⁶ Book 16 64 1437 > 10^6 Git | 12780 64558 | 447438 495141 Cite 12 21 180 > 10^6 Stac | 221 3206 | 51735 > 10^6 Twit 1851 14157 $> 10^6$ > 10⁶ IMDB 313 1110 12361 16180 Genre 369 2501 $> 10^6$ > 10⁶ Act 631 2467 30917 38346 Ama 854 6801 103109 115257 DBLP 838 1813 10700 17848

Table 6: Comparing the running time of only counting (4, 4) biclique to counting all (p, q) -bicliques with $p \in [4, 10], q \in$

[4, 10] simultaneously (ms)

Figure 6: Scalability test

advantage highlights NPivoter's effectiveness and scalability in handling complex counting scenarios where multiple (p, q) -biclique sizes need to be evaluated simultaneously.

Exp-8: Scalability Test. In Figure [6,](#page-12-2) we evaluate the scalability of NPivoter by adjusting the size of datasets. We sample either the edges or nodes, varying the percentage from 50% to 100%. In this experiment, we use the DBLP dataset, which has the highest number of edges among the tested datasets. We set $p = 6, q =$ 6. The results obtained on the other datasets and with other p, q values show similar trends. From Figure [6,](#page-12-2) we can see that all three algorithms—NPivoter, BCList++, and EPivoter — exhibit a good scalability with respect to graph size. Furthermore, NPivoter outperforms both BCList++ and EPivoter significantly, showcasing its superior efficiency and capacity to handle large-scale datasets.

Exp-9: The Effect of the Optimization Tricks. Table [7](#page-13-0) reports the impact of four key optimizations (presented in Section [5\)](#page-8-2) applied to the NPivoter algorithm on several datasets: You, Kos, DBLP, and Ama. The results on the other datasets are similar. The optimizations include: (α, β) -core based graph reduction (O₁), core value-based node ranking (O_2) , early termination (O_3) , and non-neighbor count maintenance (O_4) . With each additional optimization, the running time consistently decreases. For instance, on the Ama dataset, the running time reduces by 57.3% when applying $O₁$, followed by

Table 7: The effect of further optimizations (ms); O_1 : (α , β)core based graph reduction; O_2 : core value-based node ranking, O_3 : early termination, O_4 : maintenance of non-neighbor count

Datasets	You	Kos	DBLP	Ama
No Optimization	13181	1138038	92856	4622
O ₁	10851	1130167	15823	1971
$O_1 + O_2$	1793	392365	4195	1157
$O_1 + O_2 + O_3$	1341	319504	3043	1127
$O_1 + O_2 + O_3 + O_4$	1325	303924	2948	1050

Figure 7: The impact of graph density (ms)

a further 41.6% decrease when adding O_2 , a 2.6% reduction with O_3 , and an additional 6.8% improvement with O_4 . The full set of optimizations $(O_1 + O_2 + O_3 + O_4)$ yields the best performance, with the runtime for all datasets minimized, indicating the effectiveness of these optimizations in enhancing algorithm efficiency.

Exp-10: The Impact of Graph Density. To evaluate the scalability of NPivoter, we generate a set of random graphs under varying density. Specifically, we fix the number of edges at $|E| = 8000$ and generate random bipartite graphs with varying average degrees. For each combination of $d_U \in [20, 70]$ and $d_V \in [20, 70]$, we create 20 random graphs, leading to a total of 50,000 experiments. The goal is to assess how NPivoter behaves as the density of the graph changes.

Each color grid in Figure [7](#page-13-1) represents the average running time for the 20 random graphs corresponding to a particular combination of d_U and d_V . Notably, the running time remains under 1000 ms when \overline{d}_U < 60 or \overline{d}_V < 60. This pattern indicates that NPivoter scales well with the sparsity of the graph, making it a highly effective solution for real-world networks that tend to exhibit a power-law distribution with a majority of nodes having low degrees. As \overline{d}_U and \overline{d}_V increase, the computational complexity naturally rises due to the increase in possible connections between the two sets. However, the results show that NPivoter handles this increase in density in a controlled manner. Even at the higher end of the degree spectrum, where both \overline{d}_U and \overline{d}_V approach 70, the algorithm still performs efficiently, although the running time does begin to rise sharply. These findings show the high scalability of

NPivoter, particularly for handling sparse networks. Since realworld networks are often sparse, these results further validate the practical applicability of NPivoter in real-world scenarios.

7 RELATED WORK

Subgraph Counting. Biclique counting is a specific case of the broader problem of subgraph counting, which has been extensively studied in graph theory and its applications. The subgraph counting problem can be categorized based on several dimensions: Exact subgraph counting aims to compute the precise number of occurrences of a specific subgraph within a graph [\[19,](#page-14-20) [31,](#page-14-21) [33,](#page-14-22) [36\]](#page-14-23), while approximate methods trade accuracy for scalability in large networks [\[7,](#page-14-24) [24,](#page-14-25) [42,](#page-14-26) [44\]](#page-14-27). Learning-based approaches also exist as approximate methods [\[20,](#page-14-28) [54\]](#page-15-2). Exact counting problems are closely related to enumeration problems, and algorithms that performs exact counting can often be used for enumeration. Global counting involves determining the number of subgraphs across the entire graph [\[19,](#page-14-20) [33\]](#page-14-22), while local counting focuses on computing subgraph counts for specific nodes or edges [\[25\]](#page-14-29). In this work, biclique counting falls under both categories, as applications may require global counts or local counts per node, as seen in social networks or graph neural networks. While some algorithms are designed for counting specific subgraph patterns like cliques, cycles, or bicliques [\[15,](#page-14-30) [18,](#page-14-31) [22,](#page-14-16) [50,](#page-15-3) [52\]](#page-15-4), others focus on counting a wide variety of subgraph types [\[2,](#page-14-32) [8,](#page-14-33) [33,](#page-14-22) [54\]](#page-15-2). Biclique counting is a prominent problem in specific subgraph counting, where general counting algorithms are often not as efficient as specific methods. When $p = 2$ and $q = 2$, the (p, q) -biclique is referred to as a butterfly. As a special case of general biclique counting, efficient butterfly counting plays a critical role in the development of advanced algorithms that can handle larger graphs and subgraph patterns. Various algorithms have been introduced to efficiently count butterflies in large bipartite graphs, taking advantage of the bipartite structure to reduce computational complexity [\[37,](#page-14-34) [43\]](#page-14-35). Recent research has focused on optimizing both memory and time complexity by employing parallel computing techniques [\[46](#page-14-36)[–48\]](#page-15-5), as well as I/O-efficient methods [\[45\]](#page-14-37) and approximation strategies [\[38\]](#page-14-38). Other efforts have been made to extend butterfly counting to uncertain graphs [\[55,](#page-15-6) [56\]](#page-15-7) and temporal graphs [\[10\]](#page-14-39).

 k -Clique Counting. Our work is closely related to the k -clique counting problem in traditional graphs. The first exact algorithm for k -clique counting, introduced by Chiba and Nishizeki [\[12\]](#page-14-9), relies on a backtracking enumeration method. More recent advances have refined this technique using ordering-based optimizations, such as degeneracy ordering by Danisch et al. [\[13\]](#page-14-40), and color ordering by Li et al. [\[26\]](#page-14-41). These algorithms efficiently list k -cliques for small values of k , but their performance degrades as k increases due to the exhaustive enumeration process. To address the inefficiencies for larger k , Jain and Seshadhri [\[22\]](#page-14-16) proposed PIVOTER, an algorithm that leverages pivoting techniques for maximal clique enumeration $[9, 40]$ $[9, 40]$ $[9, 40]$. Instead of enumerating all possible k -cliques, PIVOTER counts them combinatorially, offering significant performance gains over enumeration-based methods. However, the algorithm may still struggle when applied to large, dense graphs [\[22\]](#page-14-16). To address this, several sampling-based methods have been developed to improve scalability, including the TuranShadow algorithm and its optimized version [\[21,](#page-14-44) [23\]](#page-14-45), as well as color-based sampling techniques by Ye et al. [\[51,](#page-15-8) [53\]](#page-15-9). Despite these efforts, sampling methods tend to become inefficient for larger values of k . Our approach fundamentally differs from these k -clique counting studies as we focus on counting bicliques in bipartite graphs, a problem that cannot be directly tackled by the existing k -clique counting techniques.

8 CONCLUSION

In this paper, we propose NPivoter, a novel and general framework for biclique counting. The NPivoter framework not only unifies existing approaches like BCList++ and EPivoter but also extends their capabilities by supporting both local and range counting. Our implementation of NPivoter leverages a novel minimum nonneighbor candidate partition strategy, which significantly improves the worst-case time complexity compared to previous methods. Furthermore, the inclusion of a novel cost estimator enables the framework to adaptively switch between node-split and edge-split strategies, further enhancing its performance and scalability across different graph structures. Extensive experiments conducted on realworld datasets have demonstrated the efficiency and versatility of NPivoter, achieving up to two orders of magnitude improvements over state-of-the-art algorithms.

REFERENCES

- [1] Christopher R. Aberger, Andrew Lamb, Susan Tu, Andres Nötzli, Kunle Olukotun, and Christopher Ré. 2017. EmptyHeaded: A Relational Engine for Graph Processing. ACM Trans. Database Syst. 42, 4 (2017), 20:1–20:44.
- [2] Noga Alon, Raphael Yuster, and Uri Zwick. 1994. Color-coding: a new method for finding simple paths, cycles and other small subgraphs within large graphs. In STOC.
- [3] Pablo Barceló, Floris Geerts, Juan L. Reutter, and Maksimilian Ryschkov. 2021. Graph Neural Networks with Local Graph Parameters. In NeurIPS. 25280–25293.
- [4] Vladimir Batagelj and Matjaz Zaversnik. 2003. An O(m) Algorithm for Cores Decomposition of Networks. CoRR cs.DS/0310049 (2003).
- [5] J. W. Berry, B. Hendrickson, R. A. Laviolette, and C. A. Phillips. 2011. Tolerating the Community Detection Resolution Limit with Edge Weighting. Physical Review E Statistical Nonlinear & Soft Matter Physics 83, 5 (2011), 056119.
- [6] Giorgos Bouritsas, Fabrizio Frasca, Stefanos Zafeiriou, and Michael M. Bronstein. 2023. Improving Graph Neural Network Expressivity via Subgraph Isomorphism Counting. IEEE Trans. Pattern Anal. Mach. Intell. 45, 1 (2023), 657–668.
- [7] Marco Bressan, Flavio Chierichetti, Ravi Kumar, Stefano Leucci, and Alessandro Panconesi. 2018. Motif Counting Beyond Five Nodes. ACM Trans. Knowl. Discov. Data 12, 4 (2018), 48:1–48:25.
- Marco Bressan, Stefano Leucci, and Alessandro Panconesi. 2019. Motivo: Fast Motif Counting via Succinct Color Coding and Adaptive Sampling. Proc. VLDB Endow. 12, 11 (2019), 1651–1663.
- [9] Coenraad Bron and Joep Kerbosch. 1973. Finding All Cliques of an Undirected Graph (Algorithm 457). Commun. ACM 16, 9 (1973), 575–576.
- [10] Xin-Wei Cai, Xiangyu Ke, Kai Wang, Lu Chen, Tianming Zhang, Qing Liu, and Yunjun Gao. 2023. Efficient Temporal Butterfly Counting and Enumeration on Temporal Bipartite Graphs. Proc. VLDB Endow. 17, 4 (2023), 657–670.
- [11] Lijun Chang and Lu Qin. 2019. Cohesive Subgraph Computation Over Large Sparse Graphs. In ICDE.
- [12] Norishige Chiba and Takao Nishizeki. 1985. Arboricity and Subgraph Listing Algorithms. SIAM J. Comput. 14, 1 (1985), 210–223.
- [13] Maximilien Danisch, Oana Balalau, and Mauro Sozio. 2018. Listing k-cliques in Sparse Real-World Graphs. In WWW.
- [14] Danhao Ding, Hui Li, Zhipeng Huang, and Nikos Mamoulis. 2017. Efficient Fault-Tolerant Group Recommendation Using alpha-beta-core. In CIKM. ACM, 2047–2050.
- [15] Simon Döring, Dániel Marx, and Philip Wellnitz. 2024. Counting Small Induced Subgraphs with Edge-Monotone Properties. In STOC. ACM, 1517–1525.
- [16] David Eppstein, Maarten Löffler, and Darren Strash. 2013. Listing All Maximal Cliques in Large Sparse Real-World Graphs. ACM J. Exp. Algorithmics 18 (2013).
- [17] Yixiang Fang, Kaiqiang Yu, Reynold Cheng, Laks V. S. Lakshmanan, and Xuemin Lin. 2019. Efficient Algorithms for Densest Subgraph Discovery. Proc. VLDB Endow. 12, 11 (2019), 1719–1732.
- [18] Jacob Focke and Marc Roth. 2024. Counting Small Induced Subgraphs with Hereditary Properties. SIAM *J. Comput.* 53, 2 (2024), 189-220.
- [19] Tomaz Hocevar and Janez Demsar. 2014. A combinatorial approach to graphlet counting. Bioinform. 30, 4 (2014), 559–565.
- [20] Wenzhe Hou, Xiang Zhao, and Bo Tang. 2024. LearnSC: An Efficient and Unified Learning-Based Framework for Subgraph Counting Problem. In ICDE. IEEE, 2625–2638.
- [21] Shweta Jain and C. Seshadhri. 2017. A Fast and Provable Method for Estimating Clique Counts Using Turán's Theorem. In WWW.
- [22] Shweta Jain and C. Seshadhri. 2020. The Power of Pivoting for Exact Clique Counting. In WSDM.
- [23] Shweta Jain and C. Seshadhri. 2020. Provably and Efficiently Approximating Near-cliques using the Turán Shadow: PEANUTS. In WWW.
- [24] Madhav Jha, C. Seshadhri, and Ali Pinar. 2015. Path Sampling: A Fast and Provable Method for Estimating 4-Vertex Subgraph Counts. In WWW.
- [25] Qiyan Li and Jeffrey Xu Yu. 2024. Fast Local Subgraph Counting. Proc. VLDB Endow. 17, 8 (2024), 1967–1980.
- [26] Ronghua Li, Sen Gao, Lu Qin, Guoren Wang, Weihua Yang, and Jeffrey Xu Yu. 2020. Ordering Heuristics for k-clique Listing. Proc. VLDB Endow. 13, 11 (2020), 2536–2548.
- [27] Rong-Hua Li, Qiushuo Song, Xiaokui Xiao, Lu Qin, Guoren Wang, Jeffrey Xu Yu, and Rui Mao. 2022. I/O-Efficient Algorithms for Degeneracy Computation on Massive Networks. IEEE Transactions on Knowledge and Data Engineering 34, 7 (2022), 3335–3348.
- [28] Boge Liu, Long Yuan, Xuemin Lin, Lu Qin, Wenjie Zhang, and Jingren Zhou. 2019. Efficient (a, β)-core Computation: an Index-based Approach. In WWW. ACM, 1130–1141.
- [29] Amine Mhedhbi and Semih Salihoglu. 2019. Optimizing Subgraph Queries by Combining Binary and Worst-Case Optimal Joins. Proc. VLDB Endow. 12, 11 (2019), 1692–1704.
- [30] C St JA Nash-Williams. 1961. Edge-disjoint spanning trees of finite graphs. Journal of the London Mathematical Society 1, 1 (1961), 445–450.
- [31] Noujan Pashanasangi and C. Seshadhri. 2020. Efficiently Counting Vertex Orbits of All 5-vertex Subgraphs, by EVOKE. In WSDM.
- [32] Jean-Claude Picard and Maurice Queyranne. 1982. A network flow solution to some nonlinear 0-1 programming problems, with applications to graph theory. Networks 12, 2 (1982), 141–159.
- [33] Ali Pinar, C. Seshadhri, and Vaidyanathan Vishal, 2017. ESCAPE: Efficiently Counting All 5-Vertex Subgraphs. In WWW.
- [34] Natasa Przulj, Derek G. Corneil, and Igor Jurisica. 2004. Modeling interactome: scale-free or geometric? Bioinform. 20, 18 (2004), 3508–3515.
- [35] Chendi Qian, Gaurav Rattan, Floris Geerts, Mathias Niepert, and Christopher Morris. 2022. Ordered subgraph aggregation networks. Advances in Neural Information Processing Systems 35 (2022), 21030–21045.
- [36] Mahmudur Rahman, Mansurul Alam Bhuiyan, and Mohammad Al Hasan. 2014. Graft: An Efficient Graphlet Counting Method for Large Graph Analysis. IEEE Trans. Knowl. Data Eng. 26, 10 (2014), 2466–2478.
- [37] Seyed-Vahid Sanei-Mehri, Ahmet Erdem Sariyüce, and Srikanta Tirthapura. 2018. Butterfly Counting in Bipartite Networks. In KDD.
- [38] Aida Sheshbolouki and M. Tamer Özsu. 2022. sGrapp: Butterfly Approximation in Streaming Graphs. ACM Trans. Knowl. Discov. Data 16, 4 (2022), 76:1–76:43.
- [39] Bintao Sun, Maximilien Danisch, T.-H. Hubert Chan, and Mauro Sozio. 2020. KClist++: A Simple Algorithm for Finding k-Clique Densest Subgraphs in Large Graphs. Proc. VLDB Endow. 13, 10 (2020), 1628–1640.
- [40] Etsuji Tomita, Akira Tanaka, and Haruhisa Takahashi. 2006. The worst-case time complexity for generating all maximal cliques and computational experiments. Theor. Comput. Sci. 363, 1 (2006), 28–42.
- [41] Charalampos E. Tsourakakis. 2015. The K-clique Densest Subgraph Problem. In WWW.
- [42] Charalampos E. Tsourakakis, U Kang, Gary L. Miller, and Christos Faloutsos. 2009. DOULION: counting triangles in massive graphs with a coin. In KDD.
- [43] Kai Wang, Xuemin Lin, Lu Qin, Wenjie Zhang, and Ying Zhang. 2019. Vertex Priority Based Butterfly Counting for Large-scale Bipartite Networks. Proc. VLDB Endow. 12, 10 (2019), 1139–1152.
- [44] Pinghui Wang, Junzhou Zhao, Xiangliang Zhang, Zhenguo Li, Jiefeng Cheng, John C. S. Lui, Don Towsley, Jing Tao, and Xiaohong Guan. 2018. MOSS-5: A Fast Method of Approximating Counts of 5-Node Graphlets in Large Graphs. IEEE Trans. Knowl. Data Eng. 30, 1 (2018), 73–86.
- [45] Zhibin Wang, Longbin Lai, Yixue Liu, Bing Shui, Chen Tian, and Sheng Zhong. 2023. I/O-Efficient Butterfly Counting at Scale. Proc. ACM Manag. Data 1, 1 (2023), 34:1–34:27.
- [46] Zhibin Wang, Longbin Lai, Yixue Liu, Bing Shui, Chen Tian, and Sheng Zhong. 2024. Parallelization of butterfly counting on hierarchical memory. VLDB J. 33, 5 (2024), 1453–1484.
- [47] Yifei Xia, Feng Zhang, Qingyu Xu, Mingde Zhang, Zhiming Yao, Lv Lu, Xiaoyong Du, Dong Deng, Bingsheng He, and Siqi Ma. 2024. GPU-based butterfly counting. VLDB J. 33, 5 (2024), 1543–1567.

Conference'17, July 2017, Washington, DC, USA Xiaowei Ye, Rong-Hua Li, Longlong Lin, Shaojie Qiao, Guoren Wang

- [48] Qingyu Xu, Feng Zhang, Zhiming Yao, Lv Lu, Xiaoyong Du, Dong Deng, and Bingsheng He. 2022. Efficient Load-Balanced Butterfly Counting on GPU. Proc. VLDB Endow. 15, 11 (2022), 2450–2462.
- [49] Zuoyu Yan, Junru Zhou, Liangcai Gao, Zhi Tang, and Muhan Zhang. 2024. An Efficient Subgraph GNN with Provable Substructure Counting Power. In SIGKDD. ACM, 3702–3713.
- [50] Jianye Yang, Yun Peng, and Wenjie Zhang. 2021. (p, q)-biclique Counting and Enumeration for Large Sparse Bipartite Graphs. Proc. VLDB Endow. 15, 2 (2021), 141–153.
- [51] Xiaowei Ye, Rong-Hua Li, Qiangqiang Dai, Hongzhi Chen, and Guoren Wang. 2022. Lightning Fast and Space Efficient k-clique Counting. In WWW.
- [52] Xiaowei Ye, Rong-Hua Li, Qiangqiang Dai, Hongchao Qin, and Guoren Wang. 2023. Efficient Biclique Counting in Large Bipartite Graphs. Proc. ACM Manag.

Data 1, 1 (2023), 78:1–78:26.

- [53] Xiaowei Ye, Rong-Hua Li, Qiangqiang Dai, Hongzhi Chen, and Guoren Wang. 2023. Efficient k-Clique Counting on Large Graphs: The Power of Color-Based Sampling Approaches. IEEE Transactions on Knowledge and Data Engineering (2023).
- [54] Kangfei Zhao, Jeffrey Xu Yu, Qiyan Li, Hao Zhang, and Yu Rong. 2023. Learned sketch for subgraph counting: a holistic approach. VLDB J. 32, 5 (2023), 937–962.
- [55] Alexander Zhou, Yue Wang, and Lei Chen. 2021. Butterfly Counting on Uncertain Bipartite Networks. Proc. VLDB Endow. 15, 2 (2021), 211–223.
- [56] Alexander Zhou, Yue Wang, and Lei Chen. 2023. Butterfly counting and bitruss decomposition on uncertain bipartite graphs. VLDB J. 32, 5 (2023), 1013–1036.