Why Do Speech Language Models Fail to Generate Semantically Coherent Outputs? A Modality Evolving Perspective

Hankun Wang, Haoran Wang, Yiwei Guo, Zhihan Li, Chenpeng Du, Xie Chen, Kai Yu

MoE Key Lab of Artificial Intelligence, AI Institute;

X-LANCE Lab, Department of Computer Science and Engineering,

Shanghai Jiao Tong University / Shanghai, China

{wanghankun, kai.yu}@sjtu.edu.cn

Abstract

Although text-based large language models exhibit human-level writing ability and remarkable intelligence, speech language models (SLMs) still struggle to generate semantically coherent outputs. There are several potential reasons for this performance degradation: (A) speech tokens mainly provide phonetic information rather than semantic information, (B) the length of speech sequences is much longer than that of text sequences, and (C) paralinguistic information, such as prosody, introduces additional complexity and variability. In this paper, we explore the influence of three key factors separately by transiting the modality from text to speech in an evolving manner. Our findings reveal that the impact of the three factors varies. Factor A has a relatively minor impact, factor B influences syntactical and semantic modeling more obviously, and factor C exerts the most significant impact, particularly in the basic lexical modeling. Based on these findings, we provide insights into the unique challenges of training SLMs and highlight pathways to develop more effective end-to-end SLMs.

1 Introduction

Constructing end-to-end speech generation and dialogue models is one of the ultimate goals in the field of speech. Despite the proven effectiveness of auto-regressive (AR) *text* Large Language Models (Brown et al., 2020; Touvron et al., 2023), building a *Speech* Language Model (SLM) that can generate semantically coherent speech without text transcription guidance is still an open problem.

Recently, the mainstream solution for speech dialog systems is to rely on transcription guidance when synthesizing speech (Cui et al., 2024; Ji et al., 2024). Multiple works (Zhang et al., 2024; Fang et al., 2024; Defossez et al., 2024; Chen et al., 2024; Fu et al., 2024; Wang et al., 2024; Yu et al., 2024; Zhong et al., 2024) have adopted a two-step approach. First, a LLM processes the input audio and instructions to generate a textual response. This text output then serves as a transcription guidance for a standalone or integrated text-to-speech (TTS) module to synthesize the speech. This approach leverages the mature abilities of text LLMs and TTS models, enabling more stable and semantically coherent generation. However, several factors limit the performance ceiling of such architectures. For instance, the TTS model in this architecture lacks an understanding of paralinguistic and other non-textual information present in the original input. It also struggles to generate highly natural non-verbal segments. Additionally, cascaded systems suffer from higher latency, and the wealth of in-the-wild speech data cannot be fully utilized for training. Therefore, exploring a truly end-toend speech generation model without transcription guidance is essential and urgently demanded.

A more detailed disambiguation table for the concept of speech language models can be found in Table 1. Hereafter, the term "SLM" only refers to the LMs aiming to solve the speech language modeling task and being able to generate speech directly without text transcription guidance.

In this field, since GSLM (Lakhotia et al., 2021) and AudioLM (Borsos et al., 2023) addressed this issue, despite attracting increasing research interest, a significant gap between speech and text modalities has yet to be bridged in transformerbased models. Efforts to improve SLMs primarily focus on reducing bit rates and aligning speech with text. Lowering frame rates (Lakhotia et al., 2021; Hassid et al., 2023; Cho et al., 2024) increases semantic density but faces low scalability (Cuervo and Marxer, 2024) and poor reconstruction quality. Aligning speech with text through pretraining (Hassid et al., 2023), fine-tuning (Zhang et al., 2023), or interleaved training (Nguyen et al., 2024) shows some improvements but still struggles to achieve coherence without explicit transcription guidance.

Table 1: Overview of generalized speech language models for different tasks. The *Transcription Guidance* column indicates whether text transcription guidance is used for synthesizing speech. This paper focuses on investigating the challenges associated with the last row.

Task	Input	Output	Transcription Guidance	Representative Work
TTS Synthesis	Text	Speech	✓	VALL-E (Wang et al., 2023)
Speech Understanding	Speech	Text	-	SALMOON (Tang et al., 2023)
Speech Interaction	Speech	Text + Speech	1	Mini-Omni (Xie and Wu, 2024)
Speech Language Modeling	Speech	Speech	×	GSLM (Lakhotia et al., 2021)

Despite these advances, SLMs lag behind textguided systems, and the underlying reasons for their limitations remain unexplored. While they have vaguely recognized problems in current SLMs, such as overly long sequences and low semantic density, little research has yet comprehensively and deeply investigated the underlying reasons why SLMs struggle to run end-to-end under transformer-based architectures. As a result, the community lacks insight into the differences between how SLMs and text LLMs work, and current improvements in SLMs are largely empirical attempts to approximate text LLMs in terms of data length and form.

In this paper, we systematically analyze the low performance of SLMs based on discrete semantic speech tokens and aim to answer the question below:

Question What are the critical factors that make the speech modality significantly harder to train compared to the text modality? Possible factors are:

- (A) Speech tokens such as HuBERT are more phonetic than truly semantic (Choi et al., 2024). Extracting semantic information becomes harder when using phonetic-based representations.
- (B) The length of the speech token sequence is considerably longer than its transcription text token sequence since the pronunciation duration information is included in the speech sequence by assigning each frame a token.
- (C) The sequence retains some paralinguistic information, such as prosody and timbre, introducing additional complexity and variability.

To answer this question, we propose viewing the significant gap between text and speech modalities from an evolving perspective (§ 4). We train separate LMs on the same speech dataset, using different modalities: text-based, phone-based, and speech-based token representations. The differences between modalities correspond to the possible factors listed in the question. Therefore, by evaluating the performance of LMs trained by these modalities in various tasks (§ 5), a systematical study is established and the impact of these factors can be comprehensively analyzed.

Our findings reveal that the three factors affect performance to varying degrees. Factor A has a relatively minor impact, factor B more noticeably influences syntactic and semantic modeling, and factor C exerts the most significant impact, particularly in lexical modeling (§ 6). Based on the experimental findings, we propose a few possible ways to achieve end-to-end speech modeling (§ 7).

2 Related Works

We categorize prior efforts on SLMs mainly into two directions: reducing representation bit rates and aligning speech with text.

Reducing Bit Rates The direction is to reduce the bit rates of the speech token sequence to increase its semantic information density and lower the difficulty of modeling semantics. Reducing the frame rate is the most common way to achieve this goal. GLSM (Lakhotia et al., 2021) proposed that lower frame-rate, self-supervised semantic representations facilitate language modeling, which uses de-duplicated HuBERT (Hsu et al., 2021) to achieve an average frame rate below 40 Hz. Other works create their own semantic speech tokens with lower frame rates, reaching 25 Hz (Hassid et al., 2023), 20 Hz (Shen et al., 2023) and even 5 Hz (Baade et al., 2024; Cho et al., 2024). However, this approach faces a hard trade-off between preserving semantic clarity and scalability while maintaining audio reconstruction quality.

Aligning with Text The second direction is to align the representation of speech with text. TWIST (Hassid et al., 2023) finds that initializing sLLM with a pre-trained text LLM can enhance its performance. The SpeechGPT works (Zhang et al., 2023) utilize speech-text-paired data for the model fine-tuning process. SpiritLM (Nguyen et al., 2024) interleaved speech and text tokens at the word level

Text-BPE	т	h	е		b	r	C	o v	v r	ı	f	c)	<		j	u	m	р	s		0	v	е	r		ł	t I	h	е		I	а	z	у			d	o i	g		_	1		
Text-Raw	Т	h	е		b	r	C	o v	v r	۱	f	c))	‹		j	u	m	р	s		0	v	е	r			t	h	е		I	а	z	у			d	o g	g		٦			
Phone-BPE	D H	A	i	в	R	A	ì	N	F	A A	ł	¢	s		ì	J	A	N	1	Р	s	0 W	1	v	E R			D H		I Y	L	E Y		z	I Y	C)	A O	G	i		+		Factor A	4
Phone-Raw	D H	A	i I	в	R	A W	ì	N	F	A A	ł	٢	s		ì	J	A	N	ı	Р	s	0 W	,	v	E R			D H	ł	l Y	L	E Y		z	I Y	C)	A	G	i		┛	1	Factor F	R
Phone-Repeat	D I H H	D D	A	Â	ĥ	R	R	ŵ	λ ν	N	F /		к	s	J		A	м	PS	s s	o w	ŵ	v١		E R			D I H I		Y	ł	L	ΕE	, z	I Y	I Y	I Y	D	A A	G		+	1		ĺ
Speech-HuBERT	10	202	102	506	881 924	32	488	289	1001	234	445	374	382	684	299	187	189	289	1028	456	829	189	718	667	104	859	907	802	270 1760	872	812	12	142	124	90	90	572	510	910	623	277	+		Factor C	2

Figure 1: Illustration of modality evolving. In Text-Raw and Phone-Raw, each character or phone is treated as an individual token. Text-BPE and Phone-BPE are derived by independently applying the BPE algorithm to Text-Raw and Phone-Raw, respectively. In Phone-Repeat, each phone is repeated according to its duration. For Speech-HuBERT, the 50Hz *discrete* semantic token IDs are used to train the SLM.

during pre-training. Align-SLM (Lin et al., 2024) uses ASR transcription to build a reinforcement learning curriculum with LLM feedback. Although this modality alignment approach improve speech language modeling to some extent, the models still struggle to synthesize semantically coherent speech without text guidance.

3 Prelimiary: Language Modeling

Language modeling aims to learn the joint probability distribution over token sequences, $P(t_1, t_2, \ldots, t_n)$. Using the chain rule, this can be decomposed into conditional probabilities for causal modeling:

$$P(t_1, t_2, \dots, t_n) = P(t_1 | ~~) \cdot \prod_{i=2}^n P(t_i | T_{[1:i-1]}),~~$$

where <s> denotes the beginning token. Neural language models are trained to minimize the crossentropy loss between the predicted and actual token distributions.

In this paper, we will build neural LMs with various data modalities, which will be elaborated on in the next section (§ 4). Note that the goal of our paper is to analyze and compare the modalities themselves, so we focus exclusively on mono-modality models, training LMs on individual data modalities without incorporating cross-modal information.

4 Modality Evolving

4.1 Overview

This section addresses the significant gap between text and semantic speech tokens by adopting a gradual data modality evolution perspective. By progressively transitioning from text (§ 4.2) to phones (§ 4.3) and then to speech (§ 4.4), we can identify the critical modality shift where performance degradation becomes significant.

Table 2: Modalities overview. The *Vocab Size* column shows the vocabulary size of the modality. The *#Tokens* column represents the number of encoded tokens of the training set. The *#Tokens/s* column represents the average number of tokens per second. The *Factor* column represents the corresponding factor IDexplored by the modality.

Modality	Vocab Size	#Tokens	#Tokens/s	Factor
Text-BPE	2048	696.2M	4.45	Toplina
Text-Raw	${\sim}80$	2.249B	14.53	Topine
Phone-BPE	2048	625.7M	4.04	
Phone-Raw	${\sim}80$	1.542B	9.97	ŦΑ
Phone-Repeat	~ 80	7.737B	50	+B
Speech-HuBERT	2048	7.737B	50	+C

We provide an illustration (Figure 1) and an overview (Table 2) of the modalities used in this paper. The Phone-BPE and Phone-Raw modalities are designed to be compared to Text-BPE and Text-Raw respectively to explore the influence of factor A: exploring how language models perform when using phonetic representations. Phone-Rep is for factor B: integrating duration information into the Phone-Raw sequence. Speech-HuBERT is for factor C: further including paralinguistic information. Note that for simplicity, the definition of "modality" in this paper is not particularly strict. For example, even though text BPE tokens and text character tokens are both text-based data forms with identical information content, we still consider them as two different modalities due to differences in tokenization strategies.

4.2 Text-Based Modalities

Text LLMs have exhibited strong and rich capabilities and have become a foundation for various applications. We utilize two text-based modalities with different text tokenization strategies:

Text-BPE This modality is intended to be used as a topline that employs *semantic* inputs. Among all modalities used in this paper, the tokenizer of Text-BPE is closest to the widely used largevocabulary LLM tokenizer (Touvron et al., 2023) in terms of vocabulary size. Sentencepiece (Kudo and Richardson, 2018) is utilized to train a BPE tokenizer on the transcription corpus of LibriHeavymedium (Kang et al., 2023) dataset (approximately 5k hours, a subset of the training set) with 2048 subwords. We then use this tokenizer to encode the text transcription of all datasets.

Text-Raw This modality treats each character (including letters, digits, and punctuation) as a separate token. While less compact than subword-based tokenization, Text-Raw provides a straightforward representation of text and serves as a baseline for comparison with phone-level representations.

4.3 Phone-Based Modalities

Phones, as the basic pronunciation units of human language, serve as a critical bridge between text and speech modalities. They have strong connections to both modalities: phones can be directly mapped to graphemes using predefined phonetic dictionaries and they exhibit simpler relations with speech sequences compared to text. This study analyzes the performance gap between text and speech in language modeling by training and evaluating phone-based models, exploring modality transformation from an evolving perspective.

Phone-Raw This modality treats each monophone as a token. Pure phonetic tokens allow us to verify the influence of factor A (phonetic than semantic) mentioned in Question I. Specifically, we use a modified ARPAbet symbol set (approximately 80 types of phone), as defined by CMU-Dict¹, to capture these pronunciation units. A silence token is appended to mark pauses or background noise. To extract phone sequences while preserving as much original speech information as possible, we utilize the Kaldi toolkit (Povey et al., 2011), which provides accurate speech-to-phone alignments. This approach ensures a more faithful phonetic representation compared to directly relying on grapheme-to-phone (G2P) models.

Phone-BPE This modality is built upon Phone-Raw and aims to compare with Text-BPE modality. We utilize SentencePiece to train a BPE tokenizer, where the basic symbols are monophones. To avoid cross-word phone merging during both the training and encoding processes, we transform the phone corpus into a format where each line corresponds to a single word, using alignment results produced by Kaldi. Phone-BPE has the same vocabulary size as Text-BPE and produces a similar number of encoded tokens. It can be expected that Phone-BPE tokens also possess abstract and packed semantic information similar to Text-BPE tokens.

Phone-Repeat This modality is to align with the frame rate of speech semantic tokens (50 Hz). Instead of using semantic tokens, we directly utilize phone tokens in this modality. Pure phonetic tokens with duration integrated make it possible to explore how factor B (sequence length) affects language modeling. To construct the Phone-Repeat modality, we repeat each phone in the Phone-Raw sequence according to its duration. The duration of each phone is derived from the Kaldi-produced alignments and transformed to match 50 Hz.

4.4 Speech-Based Modality

Numerous discrete speech representations have been explored in prior research (Baevski et al., 2020; Hsu et al., 2021; Défossez et al., 2022; Kumar et al., 2023; Ju et al., 2024). In this work, we adopt discrete HuBERT representations as the target for language modeling. This choice aims to add a modest amount of paralinguistic information while preserving the rich phonetic content.

Speech-HuBERT We utilize the HuBERT-Large model (Hsu et al., 2021) to extract speech representations. Specifically, we train a k-means model with 2048 clusters on the LibriSpeech dataset (Panayotov et al., 2015), using the hidden representations from the last layer of HuBERT. The resulting discrete tokens are generated at a frame rate of 50 Hz. By comparing the LMs trained on Speech-HuBERT and phone-based modalities, we can learn how factor C (paralinguistic information) impacts the LM performance. To maintain simplicity and universality in our study, we avoid additional modifications to the HuBERT tokens, such as deduplication (Lakhotia et al., 2021) or incorporating prosody representations (Nguyen et al., 2024; Kharitonov et al., 2022). These methods often discard certain types of information or require supplementary modules to restore them, introducing parallel sequences and increasing complexity. Instead, we use the unmodified, original HuBERT tokens as our primary target.

¹https://github.com/cmusphinx/cmudict

5 Experimental Setup

5.1 Training

Datasets We use LibriHeavy-large (Kang et al., 2023) dataset as our training set for all the modalities. It is a filtered subset of English speech dataset LibriLight-60k (Kahn et al., 2020) with approximately 50k hours of speech. We utilize the text transcriptions provided by LibriHeavy as the corpus for training text-based modalities (§ 4.2), after filtering out non-English characters. Following the steps in § 4.3, we obtain the phone-based data using Kaldi. To train speech LMs (§ 4.4), speech semantic tokens are directly extracted through the official HuBERT-large checkpoint².

Configurations We adopt the TinyLlama architecture (Zhang et al., 2024b), consisting of 22 Transformer layers and 32 attention heads with Group Query Attention (Ainslie et al., 2023), totaling 1.1 billion parameters. All LMs are trained from scratch. The training uses the AdamW optimizer (Loshchilov and Hutter, 2019) with a learning rate of 4×10^{-4} . A cosine learning rate scheduler is employed. We use NVIDIA-A800-80G ×4 to train the LMs, and the global batch sizes are all set as 128. Utterances in a batch are padded individually to the maximum window length. All LMs are trained to converge based on the validation set loss.

5.2 Tasks for Test

We evaluate speech LMs using various tasks in terms of lexical, syntactic, and semantic modeling, and a continuation task to assess generation. All tasks have a random baseline performance of 50% and are evaluated in a zero-shot prompting setting.

5.2.1 Objective Tasks

Following previous works (Nguyen et al., 2024; Cuervo and Marxer, 2024), we employ three objective datasets sWUGGY, sBLIMP (Nguyen et al., 2020) and Topic-StoryCloze (Hassid et al., 2023) (Topic-SC for short), to evaluate the speech LM performance in terms of lexicon, syntax, and semantics respectively.

sWUGGY This dataset is designed to assess a model's lexical modeling ability to distinguish between real spoken words and pseudo-words. The dataset provides word pairs in speech, text, and

phone forms, which we transform into the modalities outlined in Table 2. For each word pair, the language model performs a forward pass on both the real word and the pseudo-word to compute their likelihoods. If the model assigns a higher likelihood to the real word, the test for that word pair is considered successful.

sBLIMP This dataset is similar to sWUGGY but aims to evaluate the model's syntactic modeling ability. Correspondingly, the dataset is based on BLiMP (Warstadt et al., 2020) and made up of grammatically correct and incorrect sentence pairs. It provides the data in speech and text forms, and we use Kaldi to get the alignment to construct the phone-based data.

Topic-StoryCloze This dataset focuses on assessing the semantic modeling performance of speech LMs. Derived from the StoryCloze dataset (Mostafazadeh et al., 2017), this task requires the model to select the more appropriate continuation sentence for a given short base story. Topic-StoryCloze simplifies the task by providing easier negative choices.

5.2.2 Continuation Task

This evaluation aims to measure the free AR generation ability of the models. We manually design 20 prompts with varying lengths and content, which are listed in Appendix A.4. These prompts are transformed into each modality as defined in Table 2. For decoding, we select the optimal temperature value for each modality within the range of [1.0, 1.2], and set top-p to 0.9. For every prompt, each LM generates 10 outputs using different random seeds.

To evaluate the generation quality, we employ the pretrained text LLM. Outputs from non-text modalities are transcribed back into text, and their perplexity is calculated through the pretrained Llama-3.1 8B model³ (Dubey et al., 2024). Details about the models used for phone-to-text and speechto-text transcription are provided in Appendix A.2.

6 Results and Analysis

In this section, we systematically analyze the impact of the three potential factors on SLM performance. We examine the results from multiple angles and conclude with a summary.

²https://github.com/facebookresearch/fairseq/tree/main/ examples/hubert

³https://huggingface.co/meta-llama/Llama-3.1-8B

	sWUGGY	sBLIMP	Topic-StoryCloze	Contii	nuation
Modality	$\Lambda oo (\%)$	$\Lambda \alpha \alpha (0/a) \uparrow$	$\Lambda o (0/)$	PI	PL↓
	Att.(70)	Att.(%)	Acc.(%)	mean	std
Text-BPE	85.1	74.9	73.6	51.3	32.0
Text-Raw	85.6	73.3	66.0	54.6	33.4
Phone-BPE	85.0	75.0	70.9	59.1	42.9
Phone-Raw	85.8	74.5	66.6	69.1	58.9
Phone-Repeat	85.5	66.2	58.3	130.1	283.6
Speech-HuBERT	50.8	57.3	52.9	313.2	296.1

Table 3: Main results. All LMs are trained until converged.

Table 4: Impact of the three factors on task performance. The 4 columns on the right report relative changes in accuracy (Δ Acc%) and perplexity (Δ PPL%) for the subjective tasks and the continuation task respectively.

Baseline Modality	Factor	Resulting Modality	sWUGGY	sBLIMP	Topic-SC	Continuation
Text-BPE	+A	Phone-BPE	-0.0	+0.0	-3.7	+7.8
Text-Raw	+A	Phone-Raw	+0.0	+1.6	+0.9	+26.6
Phone-Raw	+B	Phone-Repeat	-0.3	-11.1	-12.5	+88.3
Phone-Repeat	+C	Speech-HuBERT	-40.6	-13.4	-9.3	+140.7

6.1 Comparison: LMs of Different Modalities

This section compares the LMs when they have learned the same amount of semantic information, so the LMs are trained on the same dataset in their respective modalities until the validation loss converges. The results of three objective tasks and the continuation task are shown in Table 3 and Table 4.

For the lexical task sWUGGY, text-based and phone-based modalities achieve similar high accuracy, exceeding 85%, implying that factors A and B have a minor impact on lexical modeling. In contrast, the Speech-HuBERT modality performs only slightly better than the random baseline of 50%. This highlights the substantial difficulty in modeling speech-based lexicon compared to text and phone-based modalities, which is mainly caused by factor C. This is understandable because the representation of the same semantic unit, such as a word, is basically consistent in text and phone modalities. Recognizing valid words in these modalities is an empirical task, requiring only a judgment of whether the input has appeared in the training data. For speech LMs, however, the representation of the same text token or phonetic unit word would be combinatorial exploded. Lexical modeling in speech demands strong generalization capabilities, which is extremely challenging under unsupervised training. Since the positive examples in sWUGGY consist of words that are not frequently occurring in the training data, the disadvantage of Speech-HuBERT is further amplified.

For the syntactic task sBLIMP, factor A still has a minor impact. Under the influence of factor B, the accuracy of Phone-Repeat decreased by 11.1%. This suggests that adding the uncertainty of duration increases the difficulty of syntactic modeling. Furthermore, factor C introduced additional complexity through paralinguistic information, and the unsuccessful lexical modeling makes syntax recognition even harder. As a result, it causes the accuracy of Speech-HuBERT to drop by 13.4% compared to Phone-Repeat.

For the semantic task Topic-StoryCloze, the accuracy of the LMs gradually decreases under the influence of factors B and C. It declines from 66.6% in Phone-Raw to 58.3% in Phone-Repeat, and finally to 52.9% in Speech-HuBERT.

For the continuation task, both factors B and C significantly impact generation quality, with the perplexity increasing sharply. They bring 88.3% and 140.7% PPL increases, respectively. This highlights that duration variability and paralinguistic complexity severely challenge the language model's ability to maintain coherent and high-quality generation over extended sequences. Generation examples of LMs in all modalities can be found in Appendix A.4.

6.2 Data Scaling Analysis

Following the methodology of scaling laws (Kaplan et al., 2020), this subsection compares LMs trained with an equivalent amount of computational



Figure 2: Results after training the same number of tokens (within the first epoch).

Table 5: Scaling factors for different modalities. *lex*, *syn* and *sem* stand for sWUGGY, sBLIMP and Topic-StoryCloze tasks, respectively.

Modality	klex	b_{lex}	k _{syn}	b_{syn}	ksem	bsem
Text-BPE	0.01	4.18	0.04	3.51	0.12	1.79
Text-Raw	0.01	4.19	0.04	3.52	0.12	1.79
Phone-BPE	0.01	4.22	0.04	3.57	0.13	1.56
Phone-Raw	0.01	4.31	0.04	3.42	0.10	2.04
Phone-Repeat	0.01	4.16	0.03	3.37	0.05	2.92
Speech-HuBERT	-0.00	4.04	0.01	3.72	0.02	3.41

resources. In this work, since we train models of the same size, we measure computational effort by the number of tokens the model has processed within the first epoch of training. For each objective task, we evaluate the LM checkpoints across various stages of progress within the first epoch. The results are presented in Figure 2. Each point in the figure corresponds to a specific checkpoint, where the x-axis represents the number of trained tokens, and the y-axis denotes the corresponding task accuracy. The points are color-coded to distinguish between different modalities.

We fit a scaling law-inspired straight line to the set of points corresponding to each (task, modality) pair (Kaplan et al., 2020). Specifically, let computation (number of trained tokens) be denoted as C and downstream task accuracy as y. We assume the following relationship holds within a certain range:

$$y = b' \cdot C^{k'} \iff \log y = k \cdot \log C + b,$$
 (1)

where the linear coefficients k and b can be inferred from the experimental results. A higher value of kindicates that increasing the same amount of training computation improves the downstream task performance of the modality more rapidly. In the figure, both axes are log-scaled to better visualize the linear scaling trends.



Figure 3: Layer-wise accuracy changes for the sWUGGY task.

Almost all straight lines fit their respective point sets well, and except for the combination of (sWUGGY, Speech-HuBERT), all slopes are positive. The specific fitting parameters are shown in Table 5. It can be observed that, for lexical tasks, except for Speech-HuBERT, the k values of other modality LMs are approximately similar, indicating that factor C has the most significant impact. This result aligns with Table 4. Similarly, in syntactic tasks, both factors B and C negatively affect the scaling speed of the models. In semantic tasks, factors A, B, and C all influence performance scaling to some extent.

6.3 Analysis on Internal Outputs

We have observed that it is challenging for the speech LM to learn the lexicon. For other modalities, although they eventually converge to similar accuracies on sWUGGY with comparable scaling slopes, the process of lexical modeling within their cascaded Transformer models differs. We analyze the intermediate layers by passing the LM outputs through the output projection layer to obtain multinomial distributions, which serve as the intermediate representations for investigation. Figure 3 shows the accuracies of each modality's LM out-



(b) Phone-Repeat Modality

Figure 4: Accuracy results of internal layers outputs for all objective tasks. Figures of other modalities are shown in Appendix B.1.

puts at different layers on the sWUGGY task. In the earlier layers, Text-BPE and Phone-BPE achieve lexical modeling the fastest, as BPE-based tokens inherently contain certain lexical prior knowledge. Phone-Raw and Text-Raw follow, as they require combining multiple nearby context tokens to reach the word level. Phone-Repeat is slower due to the expanded lexical space introduced by the duration variable. Speech tokens further exacerbate this issue by causing a combinatorial explosion in the lexical space, and the model cannot even "memorize" the lexical representation it extracts from the earlier layers.

We select Text-BPE and Phone-Repeat as examples to illustrate the layer-wise accuracy changes for each objective task, as shown in Figures 4a and 4b. These modalities are chosen because, despite achieving similar overall accuracy on the sWUGGY task, their intermediate layer behaviors differ significantly. It shows that if a modality fails to efficiently model lexicon in the earlier layers, it will hinder its ability to learn semantics effectively, demonstrating that lexical modeling serves as the foundation for syntactic and semantic modeling.

6.4 Summary

The experiments reveal the potential factors that make speech modalities harder to train. Factor A (phonetic information) has a relatively minor impact. Factor B (longer sequence length) increases the syntactic and semantic modeling difficulty by adding duration variability. Factor C (paralinguistic information) further amplifies the challenge in all tasks, especially in lexical modeling. Even with "semantic" discrete token HuBERT to minimize paralinguistic information, language modeling remains significantly more difficult.

7 Future Directions

This study highlights that effective lexical-level modeling may be the first crucial step toward realizing end-to-end SLMs. To reach this, factors B and C need to be addressed. We correspondingly propose two potential future directions:

Shorten Speech Sequence Length One promising direction is to shorten the speech sequence length. Fixed-length approaches, such as using common low-bit-rate codecs or fixed-length downsampling, may face challenges due to mismatches between the fixed segmentation boundaries and semantic units. Alternatively, variable-length methods show greater potential to significantly reduce the information rate, as demonstrated by the effectiveness of Phone-BPE. However, a simple, variable-length, low-frame-rate speech representation with relatively high synthesis quality remains to be explored.

Extra Semantic Supervision Incorporating additional lexical-level abstract semantic supervision signals may enhance performance. Prior attempts use data interleaving or reinforcement learning to facilitate the construction of lexical context, but the supervision signal remains weak and indirect, leaving low training effectiveness and efficiency. During training, introducing stronger semantic supervision, such as time-aligned information, could help SLMs surpass prior methods and achieve more advanced performance.

8 Conclusion

This study systematically explores the performance degradation from text language models to speech language models, identifying key factors hindering speech LMs' semantic effectiveness. On the whole, we find that the factor of paralinguistic information has a greater impact, especially on lexical modeling, than other factors like longer sequence length. We also emphasize that working on the lexicallevel modeling is important for catching up on text LLMs, and several practical future directions are provided based on these findings.

Limitations

This study primarily relies on the LibriHeavy-50k dataset for training, and incorporating additional datasets could enhance the generalizability of the findings. While we investigated the use of word boundaries as lexical supervision, future work could experiment with alternative or more advanced forms of lexical supervision to further improve performance.

References

- Joshua Ainslie, James Lee-Thorp, Michiel de Jong, Yury Zemlyanskiy, Federico Lebron, and Sumit Sanghai. 2023. GQA: Training generalized multi-query transformer models from multi-head checkpoints. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 4895– 4901, Singapore. Association for Computational Linguistics.
- Alan Baade, Puyuan Peng, and David Harwath. 2024. SyllableLM: Learning Coarse Semantic Units for Speech Language Models.
- Alexei Baevski, Yuhao Zhou, Abdelrahman Mohamed, and Michael Auli. 2020. wav2vec 2.0: A framework for self-supervised learning of speech representations. In Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual.
- Zalán Borsos, Raphaël Marinier, Damien Vincent, Eugene Kharitonov, Olivier Pietquin, Matt Sharifi, Dominik Roblek, Olivier Teboul, David Grangier, Marco Tagliasacchi, and Neil Zeghidour. 2023. AudioLM: A Language Modeling Approach to Audio Generation. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 31:2523–2533. Conference Name: IEEE/ACM Transactions on Audio, Speech, and Language Processing.
- Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020. Language models are few-shot learners. In Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual.
- Kai Chen, Yunhao Gou, Runhui Huang, Zhili Liu, Daxin Tan, Jing Xu, Chunwei Wang, Yi Zhu, Yihan Zeng,

Kuo Yang, Dingdong Wang, Kun Xiang, Haoyuan Li, Haoli Bai, Jianhua Han, Xiaohui Li, Weike Jin, Nian Xie, Yu Zhang, James T. Kwok, Hengshuang Zhao, Xiaodan Liang, Dit-Yan Yeung, Xiao Chen, Zhenguo Li, Wei Zhang, Qun Liu, Lanqing Hong, Lu Hou, and Hang Xu. 2024. EMOVA: Empowering Language Models to See, Hear and Speak with Vivid Emotions. *arXiv preprint*. ArXiv:2409.18042 [cs] version: 1.

- Cheol Jun Cho, Nicholas Lee, Akshat Gupta, Dhruv Agarwal, Ethan Chen, Alan W. Black, and Gopala K. Anumanchipalli. 2024. Sylber: Syllabic Embedding Representation of Speech from Raw Audio.
- Kwanghee Choi, Ankita Pasad, Tomohiko Nakamura, Satoru Fukayama, Karen Livescu, and Shinji Watanabe. 2024. Self-Supervised Speech Representations are More Phonetic than Semantic. *arXiv preprint*. ArXiv:2406.08619 [cs] version: 1.
- Santiago Cuervo and Ricard Marxer. 2024. Scaling Properties of Speech Language Models.
- Wenqian Cui, Dianzhi Yu, Xiaoqi Jiao, Ziqiao Meng, Guangyan Zhang, Qichao Wang, Yiwen Guo, and Irwin King. 2024. Recent Advances in Speech Language Models: A Survey.
- Alexandre Defossez, Laurent Mazare, Manu Orsini, Amelie Royer, Patrick Perez, Herve Jegou, Edouard Grave, and Neil Zeghidour. 2024. Moshi: a speechtext foundation model for real-time dialogue.
- Chenpeng Du, Yiwei Guo, Feiyu Shen, Zhijun Liu, Zheng Liang, Xie Chen, Shuai Wang, Hui Zhang, and Kai Yu. 2024. UniCATS: A Unified Context-Aware Text-to-Speech Framework with Contextual VQ-Diffusion and Vocoding. *Proceedings of the AAAI Conference on Artificial Intelligence*, 38(16):17924– 17932.
- Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, and et al Mathur, Akhil. 2024. The Llama 3 Herd of Models.
- Alexandre Défossez, Jade Copet, Gabriel Synnaeve, and Yossi Adi. 2022. High Fidelity Neural Audio Compression.
- Qingkai Fang, Shoutao Guo, Yan Zhou, Zhengrui Ma, Shaolei Zhang, and Yang Feng. 2024. LLaMA-Omni: Seamless Speech Interaction with Large Language Models. *arXiv preprint*. ArXiv:2409.06666 [cs].
- Chaoyou Fu, Haojia Lin, Zuwei Long, Yunhang Shen, Meng Zhao, Yifan Zhang, Shaoqi Dong, Xiong Wang, Di Yin, Long Ma, Xiawu Zheng, Ran He, Rongrong Ji, Yunsheng Wu, Caifeng Shan, and Xing Sun. 2024.
 VITA: Towards Open-Source Interactive Omni Multimodal LLM. arXiv preprint. ArXiv:2408.05211 [cs].
- Michael Hassid, Tal Remez, Tu Anh Nguyen, Itai Gat, Alexis Conneau, Felix Kreuk, Jade Copet, Alexandre Défossez, Gabriel Synnaeve, Emmanuel Dupoux,

Roy Schwartz, and Yossi Adi. 2023. Textually pretrained speech language models. In Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023.

- Wei-Ning Hsu, Benjamin Bolte, Yao-Hung Hubert Tsai, Kushal Lakhotia, Ruslan Salakhutdinov, and Abdelrahman Mohamed. 2021. HuBERT: Self-Supervised Speech Representation Learning by Masked Prediction of Hidden Units.
- Shengpeng Ji, Yifu Chen, Minghui Fang, Jialong Zuo, Jingyu Lu, Hanting Wang, Ziyue Jiang, Long Zhou, Shujie Liu, Xize Cheng, Xiaoda Yang, Zehan Wang, Qian Yang, Jian Li, Yidi Jiang, Jingzhen He, Yunfei Chu, Jin Xu, and Zhou Zhao. 2024. WavChat: A Survey of Spoken Dialogue Models. arXiv preprint. ArXiv:2411.13577 [eess].
- Zeqian Ju, Yuancheng Wang, Kai Shen, Xu Tan, Detai Xin, Dongchao Yang, Yanqing Liu, Yichong Leng, Kaitao Song, Siliang Tang, Zhizheng Wu, Tao Qin, Xiang-Yang Li, Wei Ye, Shikun Zhang, Jiang Bian, Lei He, Jinyu Li, and Sheng Zhao. 2024. Natural-Speech 3: Zero-Shot Speech Synthesis with Factorized Codec and Diffusion Models.
- Jacob Kahn, Morgane Rivière, Weiyi Zheng, Evgeny Kharitonov, Qiantong Xu, Pierre-Emmanuel Mazaré, Julien Karadayi, Vitaliy Liptchinsky, Ronan Collobert, Christian Fuegen, Tatiana Likhomanenko, Gabriel Synnaeve, Armand Joulin, Abdelrahman Mohamed, and Emmanuel Dupoux. 2020. Libri-light: A benchmark for ASR with limited or no supervision. In 2020 IEEE International Conference on Acoustics, Speech and Signal Processing, ICASSP 2020, Barcelona, Spain, May 4-8, 2020, pages 7669–7673. IEEE.
- Wei Kang, Xiaoyu Yang, Zengwei Yao, Fangjun Kuang, Yifan Yang, Liyong Guo, Long Lin, and Daniel Povey. 2023. Libriheavy: a 50,000 hours ASR corpus with punctuation casing and context.
- Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B. Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. 2020. Scaling Laws for Neural Language Models.
- Eugene Kharitonov, Ann Lee, Adam Polyak, Yossi Adi, Jade Copet, Kushal Lakhotia, Tu Anh Nguyen, Morgane Riviere, Abdelrahman Mohamed, Emmanuel Dupoux, and Wei-Ning Hsu. 2022. Text-free prosody-aware generative spoken language modeling. In Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 8666–8681, Dublin, Ireland. Association for Computational Linguistics.
- Taku Kudo and John Richardson. 2018. SentencePiece: A simple and language independent subword tokenizer and detokenizer for neural text processing. In *Proceedings of the 2018 Conference on Empirical*

Methods in Natural Language Processing: System Demonstrations, pages 66–71, Brussels, Belgium. Association for Computational Linguistics.

- Rithesh Kumar, Prem Seetharaman, Alejandro Luebs, Ishaan Kumar, and Kundan Kumar. 2023. Highfidelity audio compression with improved RVQGAN. In Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023.
- Kushal Lakhotia, Evgeny Kharitonov, Wei-Ning Hsu, Yossi Adi, Adam Polyak, Benjamin Bolte, Tu-Anh Nguyen, Jade Copet, Alexei Baevski, Adelrahman Mohamed, and Emmanuel Dupoux. 2021. Generative Spoken Language Modeling from Raw Audio.
- Sang-Hoon Lee, Ha-Yeong Choi, Seung-Bin Kim, and Seong-Whan Lee. 2023. HierSpeech++: Bridging the Gap between Semantic and Acoustic Representation of Speech by Hierarchical Variational Inference for Zero-shot Speech Synthesis. *arXiv preprint*. ArXiv:2311.12454 [cs].
- Guan-Ting Lin, Prashanth Gurunath Shivakumar, Aditya Gourav, Yile Gu, Ankur Gandhe, Hungyi Lee, and Ivan Bulyko. 2024. Align-SLM: Textless Spoken Language Models with Reinforcement Learning from AI Feedback. *arXiv preprint*. ArXiv:2411.01834 [cs].
- Ilya Loshchilov and Frank Hutter. 2019. Decoupled weight decay regularization. In 7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019. OpenReview.net.
- Nasrin Mostafazadeh, Michael Roth, Annie Louis, Nathanael Chambers, and James Allen. 2017. LS-DSem 2017 shared task: The story cloze test. In Proceedings of the 2nd Workshop on Linking Models of Lexical, Sentential and Discourse-level Semantics, pages 46–51, Valencia, Spain. Association for Computational Linguistics.
- Tu Anh Nguyen, Benjamin Muller, Bokai Yu, Marta R. Costa-jussa, Maha Elbayad, Sravya Popuri, Paul-Ambroise Duquenne, Robin Algayres, Ruslan Mavlyutov, Itai Gat, Gabriel Synnaeve, Juan Pino, Benoit Sagot, and Emmanuel Dupoux. 2024. SpiRit-LM: Interleaved Spoken and Written Language Model.
- Tu Anh Nguyen, Maureen de Seyssel, Patricia Rozé, Morgane Rivière, Evgeny Kharitonov, Alexei Baevski, Ewan Dunbar, and Emmanuel Dupoux. 2020. The Zero Resource Speech Benchmark 2021: Metrics and baselines for unsupervised spoken language modeling.
- Vassil Panayotov, Guoguo Chen, Daniel Povey, and Sanjeev Khudanpur. 2015. Librispeech: An ASR corpus based on public domain audio books. In 2015 IEEE International Conference on Acoustics, Speech and Signal Processing, ICASSP 2015, South Brisbane, Queensland, Australia, April 19-24, 2015, pages 5206–5210. IEEE.

- Daniel Povey, Arnab Ghoshal, Gilles Boulianne, Luka`s Burget, Ond`rej Glembek, Nagendra Goel, Mirko Hannemann, Petr Moth`cek, Yanmin Qian, Petr Schwarz, Jan Silovsky, Georg Stemmer, and Karel Vesely. 2011. The Kaldi Speech Recognition Toolkit.
- Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. 2023. Robust speech recognition via large-scale weak supervision. In *Proceedings of the 40th International Conference on Machine Learning*, ICML'23. JMLR.org.
- Colin Raffel, Noam M. Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. 2019. Exploring the limits of transfer learning with a unified text-to-text transformer. J. Mach. Learn. Res., 21:140:1–140:67.
- Feiyu Shen, Yiwei Guo, Chenpeng Du, Xie Chen, and Kai Yu. 2023. Acoustic BPE for Speech Generation with Discrete Tokens.
- Changli Tang, Wenyi Yu, Guangzhi Sun, Xianzhao Chen, Tian Tan, Wei Li, Lu Lu, Zejun Ma, and Chao Zhang. 2023. SALMONN: Towards Generic Hearing Abilities for Large Language Models.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, and et al Batra, Soumya. 2023. Llama 2: Open Foundation and Fine-Tuned Chat Models.
- Chengyi Wang, Sanyuan Chen, Yu Wu, Ziqiang Zhang, Long Zhou, Shujie Liu, Zhuo Chen, Yanqing Liu, Huaming Wang, Jinyu Li, Lei He, Sheng Zhao, and Furu Wei. 2023. Neural Codec Language Models are Zero-Shot Text to Speech Synthesizers. *arXiv preprint*. ArXiv:2301.02111 [cs, eess].
- Xiong Wang, Yangze Li, Chaoyou Fu, Yunhang Shen, Lei Xie, Ke Li, Xing Sun, and Long Ma. 2024. Freeze-Omni: A Smart and Low Latency Speechto-speech Dialogue Model with Frozen LLM. *arXiv preprint*. ArXiv:2411.00774 [cs].
- Alex Warstadt, Alicia Parrish, Haokun Liu, Anhad Mohananey, Wei Peng, Sheng-Fu Wang, and Samuel R. Bowman. 2020. BLiMP: The benchmark of linguistic minimal pairs for English. *Transactions of the Association for Computational Linguistics*, 8:377– 392.
- Zhifei Xie and Changqiao Wu. 2024. Mini-Omni: Language Models Can Hear, Talk While Thinking in Streaming.
- Wenyi Yu, Siyin Wang, Xiaoyu Yang, Xianzhao Chen, Xiaohai Tian, Jun Zhang, Guangzhi Sun, Lu Lu, Yuxuan Wang, and Chao Zhang. 2024. SALMONNomni: A Codec-free LLM for Full-duplex Speech Understanding and Generation. arXiv preprint. ArXiv:2411.18138 [eess].

- Heiga Zen, Viet Dang, Robert A. J. Clark, Yu Zhang, Ron J. Weiss, Ye Jia, Z. Chen, and Yonghui Wu. 2019. Libritts: A corpus derived from librispeech for text-to-speech. In *Interspeech*.
- Dong Zhang, Shimin Li, Xin Zhang, Jun Zhan, Pengyu Wang, Yaqian Zhou, and Xipeng Qiu. 2023. SpeechGPT: Empowering large language models with intrinsic cross-modal conversational abilities. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 15757–15773, Singapore. Association for Computational Linguistics.
- Dong Zhang, Xin Zhang, Jun Zhan, Shimin Li, Yaqian Zhou, and Xipeng Qiu. 2024a. SpeechGPT-Gen: Scaling Chain-of-Information Speech Generation.
- Peiyuan Zhang, Guangtao Zeng, Tianduo Wang, and Wei Lu. 2024b. TinyLlama: An Open-Source Small Language Model.
- Zhisheng Zhong, Chengyao Wang, Yuqi Liu, Senqiao Yang, Longxiang Tang, Yuechen Zhang, Jingyao Li, Tianyuan Qu, Yanwei Li, Yukang Chen, Shaozuo Yu, Sitong Wu, Eric Lo, Shu Liu, and Jiaya Jia. 2024. Lyra: An Efficient and Speech-Centric Framework for Omni-Cognition. *arXiv preprint*. ArXiv:2412.09501 [cs].

A Free Generation Setup

A.1 Free Generation Parameters

The generation parameters used for each modality are shown in Table 6. Note that the temperature for Phone-Repeat and Speech-Rep50Hz is set higher to mitigate the risk of low-temperature settings, which often result in repetitive looped generations that lack coherence. Additionally, for these two modalities, if more than eight consecutive tokens with the same value are generated, the current generation will be terminated. If the resulting transcribed text contains fewer than 50 characters (excluding the prompt), a new generation will be initiated using a different random seed. While for the other modalities, the generation always full-fill max_length tokens. For all generated sequences (after being transcribed into text if needed), the last word is deleted since it may not be a complete word.

Modality	Max Length	Тор-К	Top-P	Temperature
Text-BPE	45	1000	0.9	1.00
Text-Raw	135	-	0.9	1.05
Phone-BPE	45	1000	0.9	1.00
Phone-Raw	96	-	0.9	1.05
Phone-Repeat	500	-	0.9	1.15
Speech-HuBERT	500	1000	0.9	1.20

Table 6: Parameters for free-generation.

A.2 Phone-to-Text and Speech-to-Text Transcription

Phone-to-Text We fine-tune the T5 model⁴(Raffel et al., 2019) to develop an English phone-to-text translator (T5-PTT). The model is trained on the LibriHeavy-50k dataset(Kang et al., 2023), with phone and duration information extracted using Kaldi scripts (Povey et al., 2011). Two versions of T5-PTT are trained: T5-PTT-Original and T5-PTT-Deduped. For the Phone-Raw and Phone-BPE modalities, each phone is treated as a separate input token. For the Phone-Repeat modality, adjacent phones in the sequence are deduplicated during training. This approach allows us to use the deduplicated phone sequence directly as input during inference. The word error rates (WER) on the test set for both versions are presented in Table 7, showing that deduplication does not compromise the precision of phone-to-text translation and may even improve it slightly.

Table 7:	Word	Error	Rates	(WER)	of T5-	-PTT	Models.
----------	------	-------	-------	-------	--------	------	---------

Model	T5-PTT-Original	T5-PTT-Deduped
WER (%)	2.64	1.97

Speech-to-Text To leverage the capabilities of powerful pretrained end-to-end ASR models for accurate speech token transcription, we first utilize CTX-vec2wav (Du et al., 2024) to synthesize wav files from HuBERT tokens. The utterance "1089_134686_000001_000001" from the LibriTTS (Zen et al., 2019) evaluation set is chosen as the speaker prompt. Subsequently, the pretrained Whisper-Large-V3⁵ (Radford et al., 2023) model is employed for wav-to-text recognition. Whisper's transcription includes punctuation marks and is case-sensitive, making it suitable for direct input to text LLMs and enabling a fair comparison with the output of our fine-tuned T5 models.

A.3 Prompts

The prompts we used are listed in 8. For the prompts picked from the training data, the text, phones, durations and HuBERT tokens are directly truncated from the training set. For the prompts out of the

⁴https://huggingface.co/google/flan-t5-base

⁵https://huggingface.co/openai/whisper-large-v3

training data, the speech prompts are synthesized through Hierspeech++(Lee et al., 2023) and then obtain phones and durations through aligning.

In Training Data	Not in Training Data
This	Alice is a nice
I will	How much water do you
How do	We decide to go to the
When I	In the morning, I like to
She said	A little bird told me that
These are	Mary went to the market to
The boy is	In the morning, I like to eat
The moon is	Bob is a tennis player, and he
What a lovely	He looked up to the sky and saw
He looked up to the sky and said	A little girl is playing with her

A.4 Selected Examples

See Table 10 and Table 11.

B Additional Experiments

B.1 Layer-wise Evaluation Results over All Modalities



Figure 5: Layer-wise accuracy analysis for selected modalities.

B.2 Adding Explicit Word Boundaries

Indicating lexical-level semantics is the foundation of language modeling. However, speech tokens perform poorly at this stage. We attempt to add explicit word boundary tokens to the training data of non-text modalities to provide the LM with clear boundaries of semantic units during training. The evaluation data is also processed in the same way to ensure consistency with the training data. The results are shown in Table 9. The results indicate similar trends across the Phone-Raw, Phone-Repeat, and Speech-HuBERT modalities: slight degradation in lexical tasks and slight improvements in syntactic and semantic tasks. Phone-BPE, which inherently avoids cross-word merging due to its construction, already implicitly contains word boundaries. As a result, adding explicit word boundary tokens increases sequence length and decreases performance on semantic tasks.

In summary, adding explicit word boundaries provides little to no improvement in the performance of SLMs on lexical and other tasks.

Modality	sWUGGY	sBLIMP	Topic-SC
Phone-Raw	85.8	74.5	66.6
+word boundary	85.6	75.7	66.8
Phone-BPE	85.0	75.0	70.9
+word boundary	84.1	75.4	69.6
Phone-Repeat	85.5	66.2	58.3
+word boundary	85.2	66.9	59.0
Speech-HuBERT	50.8	57.3	52.9
+word boundary	50.3	57.7	53.6

Table 9: Comparison of training and evaluation data with or without word boundary tokens.

Modality	Generation		
Prompt : What a	Prompt: What a lovely		
Toxt DD5	What a lovely country this is! I like it from the doorway of the caf in it to the sea. It is like Rome,		
Text-BPE	built in that there are Roman doors in the wall,		
	What a lovely, beautiful place this is! You see all the loveliness is in it. I was thinking I wonder how		
	I shall like the place when my aunt's jewels are		
Taxt Daw	What a lovely life he has led these two years. He has been here four years, never more. And now,		
Text-Raw	what will he be?" She sat in an arm		
	What a lovely morning! My dear, isn't it always like this?" "I've only just come from school, but		
	I'm not worse than you, Aunt Sarah		
Phone-BPF	What a lovely place! Can't you understand? "A little while back. Something terrible happened.		
THORE DIE	Uncle and I came into here to live. There was a magnet in it for me. I ran to it.		
	What a lovely sunset! exclaimed Dorothy, as the glaring sun was shown out of the cabin windows.		
	The day had been a lovely one, indeed, now that the sun had descended.		
Phone-Raw	What a lovely story! I'll be precious glad to hear it, Mr. Parker agreed. And then Mrs. Brigham's		
Thone Run	eyes softened. She knew a lot more about.		
	What a lovely thing that is to see you, my lady, said the little blonde in her sister's arms. "You are		
	the best fellow I ever heard of, I think. So you are.		
Phone-Repeat	"What a lovely place!" said Trotty, in his Dublin lady's parlour. "What do you suppose flags and		
	red mitts?" asked his friend.		
	What a lovely thing! And how it did stretch out in stockings with a cotton tails!		
Speech-HuBERT	What a lovely place! If old as Markwright say, Why am I wasting my height? When shoulder the		
	hair, on his ear		
	What a lovely flower! On the road. Why wake how long? What a hum full! Why where? Here		
Prompt : He look	ed up to the sky and said		
Text-BPE	He looked up to the sky and said that the air was almost full of falling drops. They made the honey		
	flow. The tree was shaking, his eyes flashed, and he opened his mouth		
	He looked up to the sky and said, "Come down. Come down and lie on the hill." The thing he had		
	sala remained with him. At last he sala to the tree, The tree,		
Text-Raw	He looked up to the sky and sala: On, no, we may never come back, but some day I doubt if the old		
	ones will come back, but surely in He looked up to the sky and said "Our Lady bids us take no head of the face of the great builder.		
	whom she sees toiling over her belo		
	Whom she sees tolling over her belo		
Phone-BPE	the river wandering into the sky and suddenly its silvery shay		
	He looked up to the sky and saw that the moon was rising and that the stars had just begun to		
	appear and it was not far from dawn already when he looked round him		
	He looked up to the sky and said "See how large and bright are the stars of heaven! 'Tis the love		
Phone-Raw	that preserves her very thrown from heaven!"		
	He looked up to the sky and said. "O sovereign of the world, it has been my mission to instruct thee		
	into the innermost recesses of the heaven.		
	He looked up to the sky and said such fine words to her, but the old lady took the harp and blew		
Phone-Repeat	with all her might, and the man lay down the harp.		
	<i>He looked up to the sky and said to him, "Where are you? Where are you, little fox and your deer?"</i>		
	And the King's son took his hand and said to him, "Where are you going?"		
	He looked up to the sky and said that it ought to be saved. Wish I would be gone. Wahawai. Wah		
Speecn-HUBERI	number six years ago, squadron bothers discipline.		
	He looked up to the sky and said that was what we thought a hundred deaths since that disastrous		
	dwelling leave to save us by some suitable visit		

Table 10: Free generation examples (part 1). The prompts are truncated from sentences in the train set.

Modality	Generation
Prompt : Alice is	anice
Taut DD5	Alice is a nice good girl, and I expect she will stick to you. She will take your right hand, you know,
TEXT-DFE	and you'll meet her on the sands at night. She was in
	Alice is a nice girl, and I hope she's got money enough, and that her house will stand a good
	reception. And she'll get a husband to look after her property, so
Toxt-Pow	Alice is a nice little lady, and has just come up. You are off too. Come in. The watchman stands in
Text Raw	the doorway. I heard him say it w
	Alice is a nice girl, the girl will never be out of this house. She has been a little bored lately, poor
	girl! she devoted herself to
Phone-BPF	Alice is a nice, elderly woman, and very willing to give a home to any one who needs it. Elsie has
	an apartment in the cottage of a friend of hers.
	Alice is a nice niece. I suppose he'll leave her some money?" "I certainly think he will." "You'll
	have to look up some other bank for her. It's about time for her to be asked to the honey."
Phone-Raw	Alice is a nice street name for a street so much bigger than England. It's such a drear fix that it
	isn't safe to speak about it. How?"
	Alice is a nice, cool deer who is coming here some night. They are treating me to stay two days,
	and Alice will not object to letting me come and se.
Phone-Repeat	Alice is a nice little house," said Kate, surveying herself in the linen dress, and she took part in the
	labors of the other women.
	Ance is a nice ofa, jai ofa woman, with a origin ofae eye and wisijai jace, and a plainty presuming
	Juce I suppose she is going to.
Speech-HuBERT	apinioned nittle me by her objection
	Alice is a nice little model and has a good clothes monsieur. Well sweetheart
Prompt: Mary w	ant to the market to
	Mary want to the market to huy candles for a stuff therewith and after she had looked about the
Text-BPE	shop and questioned everyone she came out to them crying: "
	Mary went to the market to see the men carrying the bricks, and when they saw the roof they thought
	"They have never known anything about that till to day." "What do you
	Mary went to the market to sell some of her supplies, and a day later was thrown into the workhouse.
Text-Raw	The estate is situated on a stre
	Mary went to the market town and found the outhouses of wood and iron, and as they were all
	covered with grass, and pretty copper clo
Dhana BDC	Mary went to the market to buy me some fruit, my dog some cake and some pickles, but Mary said
Phone-BPE	she might look for occasion for some articles that day, and to tell.
	Mary went to the market to buy a pig. "A pig," said she. "I, too, will bring a pig. Meet, meet, bring
	it." The rich brother was afraid of his wife. "Who was I?"
Phone-Raw	Mary went to the market to purchase food, and returned soon with a huge fish which she had caught
Thone Raw	by the hook of the net fastened to the.
	Mary went to the market to mend a boat for herself. She went down the river with her father and
	children, and settled there. She was.
Phone-Repeat	Mary went to the market buy some things, and after a time sat upon one of them, and little hunger
	followed her.
	Mary went to the market to labour for the plate, and worked steadily at it all the weekly. The night
	of watches fiercely, unfortunately produced in.
Speech-HuBERT	Mary went to the market, to being her nusbana, as was the first, and in the tomb she stayed there in a city O Mr. de Vendell, O Learne by to din
	u cuy. O win, as voluel. O I came by 10 alp. Many want to the market to huy a class extra husiness, and then he sport two and two costing
	himself at his mother's trading carriages with her mud-handling brives like a fork while Miss
	Nevillee

rubic 11. 1100 generation examples (part 2). The prompts do not appear in the train se
--