Enhancing Topic Interpretability for Neural Topic Modeling through Topic-wise Contrastive Learning

Xin Gao^{\dagger}[§], Yang Lin^{\dagger}[§], Ruiqing Li^{\dagger}[§], Yasha Wang^{\ast †¶}, Xu Chu^{\ddagger}, Xinyu Ma^{\dagger}[§] and Hailong Yu ^{\dagger}[§]

Email: xingao@pku.edu.cn, bdly@pku.edu.cn, lrq@stu.pku.edu.cn, wangyasha@pku.edu.cn,

chu xu@pku.edu.cn, maxinyu@pku.edu.cn, and hailong.yu@pku.edu.cn

[§]Software Engineering Institution, School of Computer Science, Peking University, Beijing, China

[†]Key Lab of High Confidence Software Technologies, Ministry of Education, Beijing China

[‡]Center on Frontiers of Computing Studies, School of Computer Science, Peking University

[¶]National Engineering Research Center of Software Engineering, Peking University, Beijing, China

*Corresponding author

Abstract-Data mining and knowledge discovery are essential aspects of extracting valuable insights from vast datasets. Neural topic models (NTMs) have emerged as a valuable unsupervised tool in this field. However, the predominant objective in NTMs, which aims to discover topics maximizing data likelihood, often lacks alignment with the central goals of data mining and knowledge discovery which is to reveal interpretable insights from large data repositories. Overemphasizing likelihood maximization without incorporating topic regularization can lead to an overly expansive latent space for topic modeling. In this paper, we present an innovative approach to NTMs that addresses this misalignment by introducing contrastive learning measures to assess topic interpretability. We propose a novel NTM framework, named ContraTopic, that integrates a differentiable regularizer capable of evaluating multiple facets of topic interpretability throughout the training process. Our regularizer adopts a unique topic-wise contrastive methodology, fostering both internal coherence within topics and clear external distinctions among them. Comprehensive experiments conducted on three diverse datasets demonstrate that our approach consistently produces topics with superior interpretability compared to state-of-the-art NTMs.

I. INTRODUCTION

In the realm of data mining and knowledge discovery, topic modeling stands as a fundamental unsupervised statistical technique. Its primary aim is to unveil latent semantic topics within a corpus of textual documents. One prominent model in this domain is Latent Dirichlet Allocation (LDA)[1]. LDA relies on a generative framework grounded in the Dirichlet prior and employs variational Bayesian algorithms for approximate inference. Crucially, topic interpretability plays a pivotal role in the context of data mining, as it empowers researchers and users to extract meaningful insights, comprehend underlying patterns, and effectively employ the identified topics for diverse applications[2], [3], [4], [5], [6], [7].

Recent years have borne witness to an unprecedented surge in the scale of corpora requiring analysis through topic modeling. Nonetheless, generating high-quality topics on substantial corpora using LDA and its extensions has been recognized as a formidable challenge [8], [9]. To address these challenges and enhance adaptability and scalability, researchers have integrated Auto-encoding Variational Bayes [10] into the inference process. This integration has given rise to a class of models known as neural topic models (NTMs)[8], [9], [11]. However, despite these advancements, some NTMs have faced criticism for generating topics that are less interpretable to humans[12].

The main obstacle hindering NTMs from generating highly interpretable topics stems from the inconsistency between the current objective, which focuses on discovering topics that maximize the likelihood of observed data and the users' intention in topic modeling, which includes discovering topics with high interpretability that facilitate human comprehension of large corpora. By solely focusing on likelihood maximization without incorporating any regularization, the latent space for topic modeling may become excessively large to comprehensively explore. Traditional topic models like LDA implicitly maintain topic interpretability by leveraging their Dirichlet prior, which promotes sparsity in topic-word distribution to restrict the latent space. Nevertheless, devising appropriate and accurate reparameterization tricks for the Dirichlet distribution poses a challenging task, leading researchers to employ various approximations in NTMs, which ultimately compromises the topics' interpretability. Consequently, we propose to integrate measurements of topic interpretability into the objective to regulate the latent space and steer NTMs toward uncovering better topics.

At present, the evaluation of topic interpretability typically revolves around two aspects: *topic coherence* and *topic diversity*, where coherence measures the degree of semantic consistency among the most relevant words within a topic, while diversity gauges the distinctiveness of the most relevant words across different topics as shown in Figure 1. In order to constrain the latent space, we propose an idea that **explicitly incorporates topic interpretability as a regularizer into the objective function of NTMs**. While the idea appears intuitive, several challenges persist that require further investigation.

Challenge 1: Developing a computationally friendly regularizer. One approach is to directly incorporate interpretabilitybased evaluation metrics as regularizers. However, these metrics, e.g., *topic coherence*, rely on look-up operations in a large reference corpus, making them non-differentiable and computationally intensive [13]. Such non-differential operations may make it challenging to calculate gradients and perform backpropagation. Even though methods like policy gradient can address the non-differentiability issue, they usually introduce higher computational complexity and gradient variance. A preferable solution would involve designing differentiable surrogates that capture human cognition and encompass various aspects of topic interpretability.

Challenge 2: Addressing the consideration of multiple aspects in topic interpretability? Drawing from relevant literature [14], [11], [15], [16], [17], it is widely recognized that topic interpretability necessitates the generation of topics that are both semantically coherent and distinctive to human understanding. Neglecting the aspect of distinctiveness may result in redundant topics with overlapping global themes, while overlooking coherence can result in superficially distinctive topics lacking a coherent semantic meaning. Balancing coherence and distinctiveness among topics remains a challenging task. To address this, we propose a topic-wise contrastive term that different from previous document-wise contrastive terms in NTMs. The core concept of contrastive learning involves promoting similarity between positive sample pairs while discouraging similarity between negative sample pairs. In the context of Contratopic, positive samples consist of words sampled from the same topic, while negative samples encompass words from different topics. Therefore, encouraging positive samples promotes coherence within a topic, while discouraging negative samples fosters distinctiveness across topics.

Within this paper, we propose an innovative framework for NTMs that introduces topic interpretability during the training phase through the integration of a topic-wise contrastive learning regularizer. This regularizer treats words associated with the same topic as positive samples and words associated with different topics as negative samples, thus enhancing the coherence and distinctiveness of the topic-word distribution. We additionally utilize a novel sampling technique that leverages the Gumbel-Softmax trick [18], enabling us to efficiently draw top-k related words from the topic-word distribution in a differentiable manner, generating pairs of positive and negative samples without replacement. To evaluate the effectiveness of our regularizer in improving topic interpretability, we conducted extensive experiments on three datasets. The results demonstrate the superior performance of our proposed ContraTopic approach compared to all baseline methods.

The contribution can be summarized as follows:

- To mitigate the inconsistency between the current objective of NTMs and the intent usage of topic modeling, we propose an innovative framework for NTMs, named ContraTopic.
- Based on the multiple aspects of topic interpretability, we devise a differentiable regularizer via topic-wise contrastive learning, promoting coherence within individual topics and diversity across different topics.
- Through experiments conducted on three datasets, we demonstrate that ContraTopic consistently generates topics with significantly higher levels of interpretability compared to all baseline approaches.

II. RELATED WORKS

In this section, we will first briefly introduce the development and main branches of the NTMs based on their architectures. Then we focus on NTMs that also leverage contrastive learning but with different goals and methodologies. Last but not least, we introduce NTMs that also attempt to improve the interpretability of generated topics.

A. Neural Topic Models

A major challenge in applying conventional topic models and developing new methods was the complex inference algorithms of the posterior distribution. The employment of neural networks and black-box inference methods has enabled topic models to automatically solve the inference process via backpropagation, which led to the thriving of NTMS. NVDM [8] and ProdLDA [9] leveraged autoencoding variational Bayes [10] as the basic architecture and respectively applied Gaussian and logistic normal distribution in approximations of the Dirichlet prior in the original LDA. Subsequently, various constructions of the prior distributions have been proposed [19], [15], [20], [11] aiming for a better approximation of the Dirichlet prior. On top of variational autoencoders (VAE), other famous architectures, such as generative adversarial networks [21], [22] and graph neural networks [23], [24], have also been applied into NTMs. Recently, many researchers have proposed novel NTMs via the theory of optimal transport (OT). By naturally incorporating word embeddings into the cost function of the optimal transport distance, their models [12], [25] were able to achieve a better balance between obtaining good document representation and generating topics with high quality. Recently, ECRTM [26] proposes a novel embedding clustering regularization that avoids the collapsing of topic embeddings.

B. Contrastive Learning in NTMs

The idea of contrastive learning is to measure the similarity relations between samples by contrasting positive pairs against negative pairs. There have been various efforts to study contrastive methods to learn meaningful representation in a selfsupervised way. It has been widely explored in enormous fields including image classification [27], [28], object detection [29], [30], adversarial training [31], and sequence modeling [32]. In recent years, contrastive learning also has been applied in topic modeling to leverage the relations among documents [33]. Nguyen et al. [34] proposed CLNTM with a novel contrastive objective that captured the mutual information between the document prototypes and their positive samples by modeling the relations among augmented samples. TSCTM [35] was proposed to sufficiently model the relations between documents against data sparsity via a new contrastive learning method with efficient sampling strategies.

A pivotal distinction between our method and other topic models that incorporate contrastive terms stems from the foundational insights underlying each approach. Other methods, such as CLNTM, employ a **document-wise** contrastive term, with their guiding principle centered around encouraging similar document-topic distribution among similar documents, which will "implicitly" benefit the topicword distribution and thereby contribute to topics with higher quality. In stark contrast, our approach adopts a **topic-wise** contrastive term, which, in a more direct and unequivocal manner, **fosters coherence and diversity of the topic-word distribution**, leading to an enhancement in the quality of topics. Empirical experiments corroborate this distinction, revealing that our topic-wise contrastive term eclipses the quality achieved by CLNTM, thus underscoring the merits of directly optimizing the topic-word distribution. More details about the differences can be found in subsection G of section Methodology.

C. Improving Topic Interpretability in NTMs

There have been lots of works aiming at improving the topic interpretability of NTMs. Some works [8], [9], [19], [15] focused on finding better approximations for Dirichlet distribution, which encourages the sparsity among topics and implicitly improves the topic interpretability. Besides, another popular way to improve topic interpretability is to incorporate other external meta information into topic modeling, such as seed words [36], [37] and document labels [22], that are closely related to topics. Different from these methods, we do not incorporate such external information, which means that there are no extra human-annotation costs and expertise in ContraTopic. Apart from incorporating external information, an alternative straightforward solution is to incorporate topic interpretability on the specific corpus into the objectives. Gui et al. [38] borrow the idea of reinforcement learning and incorporate topic coherence measures as rewards to guide the NTMs. However, their approach updates the topic-word distribution using rigid pre-defined rules, and the intricate complexity of the states poses challenges for achieving convergence. Ding et al. [13] also propose a method to incorporate topic coherence based on word embeddings that is differentiable and computationefficient, but their method only focuses on topic coherence and ignores other aspects of topic interpretability such as topic *diversity*. In contrast, our approach uses the pre-computed NPMI in the given corpus to provide extra supervision and introduces a topic-wise contrastive regularizer that incorporates multiple facets of topic interpretability.

III. PRELIMINARY

A. Problem Formulation

Consider a corpus consisting of D documents, where the vocabulary contains V distinct terms. Each document is represented as a bag-of-word vector $x \in \mathcal{R}^V$. Our goal is to derive K topics, which are set of distributions over words noted as $\beta_1, ..., \beta_K \in \Delta^V$, and latent topic distribution for each document noted as $\theta_1, ..., \theta_D \in \Delta^K$, where Δ^K is a K-1 dimensional simplex.

B. Neural Topic Modeling

The common generative story of NTMs is similar to [9], where the Dirichlet prior is approximated via a logistic normal distribution. The generative story is summarized as follows, where α is the parameter for prior distribution:

- 1. Draw topic distribution $\theta \sim \mathcal{LN}(\mu_0(\alpha), \sigma_0^2(\alpha));$
- 2. For w_{dn} in this document:
 - a. Draw topic $z_{dn} \sim Cat(\theta)$;
 - b. Draw word $w_{dn} \sim Cat(\beta_{z_{dn}})$;

The subscripts like w_{dn} on the third page indicate the nth word in the d-th document of the corpus, following conventions from seminal topic model papers [1], [11]. The $\mathcal{LN}(\cdot)$ denotes the logistic-normal distribution, and $Cat(\cdot)$ denotes the multinomial distribution. To leverage the pretrained word embeddings, ETM [11] uses the word embeddings for the vocabulary $\rho \in \mathcal{R}^{V \times e}$, where *e* is the dimension of embedding, and the assigned topic embedding $t_{z_{dn}} \in \mathcal{R}^e$ to draw the observed word from the assigned topic z_{dn} , noted by $\beta_{z_{dn}} = \operatorname{softmax}(\rho t_{z_{dn}}/\tau_{\beta})$, where τ_{β} is a temperature forcing the distribution to be sharp.

Based on the generative story, the variational inference is used to approximate the posterior distribution of latent variables ρ , θ_d , $\mathbf{z}_d = \{z_{d1}, z_{d2}, \dots, z_{dN_d}\}$ and $\mathbf{t} = \{t_1, t_2, \dots, t_K\}$ to maximize the likelihood of observed data. The evidence lower bound (ELBO) can be derived as

$$\mathcal{L}(\boldsymbol{w}) = E_{q(\theta, \boldsymbol{z} | \boldsymbol{w})} \log \left(p(\boldsymbol{w} | \theta, \boldsymbol{z}; \boldsymbol{t}) \right) - E_{q(\theta, \boldsymbol{z} | \boldsymbol{w})} \log \left(\frac{q(\theta, \boldsymbol{z} | \boldsymbol{w})}{p(\theta, \boldsymbol{z})} \right).$$
(1)

The first term noted as \mathcal{L}_{rec} encourages variational distribution q to favor information that is good at explaining the observed words, and the second term noted as \mathcal{L}_{kl} encourages q to match the prior distribution.

Specifically, for the encoder $q(\theta|\boldsymbol{w})$, we have $\pi = MLP(\boldsymbol{w})$, $\mu(\boldsymbol{w}) = l_1(\pi), \ log\sigma(\boldsymbol{w}) = l_2(\pi)$ and finally $\theta(\boldsymbol{w}) = softmax(\mu + \sigma \odot \epsilon)$, where $\epsilon \sim \mathcal{N}(0, I)$. The functions l_1 and l_2 are linear transformations. For the decoder network, we collapse \boldsymbol{z} and compute $p(\boldsymbol{w}|\theta, \rho, \boldsymbol{t}) = \theta^{\top}\boldsymbol{\beta}$.

IV. METHODOLOGY

A. Topic-wise Contrastive Regularizer

As shown in the ELBO, the current objective of NTMs lacks consideration of topic interpretability during the training process of VAE-based NTMs, making it difficult to control the topic quality. To incorporate topic interpretability, we propose a topic-wise contrastive regularizer that simultaneously controls the coherence and distinction of generated topics. Figure 1 shows the fundamental insight of ContraTopic.

Following [28], we first introduce the contrastive loss with multiple positive samples and negative samples¹. For a set of M samples $S = s_1, ..., s_M$, the contrastive loss can be calculated as Eq.2.

$$\mathcal{L}_{con} = \sum_{i \in I} -\log\left(\frac{\sum_{p \in P(i)} \exp\left(\mathcal{K}(i,p)\right)}{\sum_{a \in I} \exp\left(\mathcal{K}(i,a)\right)}\right),\tag{2}$$

where $I \equiv \{1 \dots M\}$ is the full set of the indices of all samples, P(i) is the set of indices of all positive samples for anchor i.

¹It should be noted that the samples in our contrastive regularizer refer to words, not documents.



Fig. 1. The fundamental insight of ContraTopic. During the training of NTMs, words are sampled from each topic for the evaluation of topic coherence and diversity. Words in the same color are sampled from the same topic. By encouraging similarity between positive word pairs and discouraging similarity between negative word pairs, the coherence and diversity of generated topics can be improved.

Concretely, the full set of samples S consists of K sets of words that are sampled from each topic, noted by $S = \bigcup_{k=1}^{K} T_i$, where T_k denotes the most v related words in the k-th topic, $v = \frac{M}{K}$. P(i) denotes the indices of samples from the same topic as s_i , noted by $P(i) = \{j | s_i \in T_k, s_j \in T_k, \text{ and } i \neq j\}$. The function $\mathcal{K}(\cdot)$ measures the similarity between two words. It can be implemented with dot product of word embeddings or the pre-computed Normalized Point-wise Mutual Information (NPMI) in the corpus. By employing the pre-computed NPMI in the corpus for $\mathcal{K}(\cdot)$, the positive samples in our regularizer serve to optimize topic coherence directly during training, while the negative samples aim to encourage the sampling of words with low NPMI from distinct topics.

The choice of NPMI in $\mathcal{K}(\cdot)$: It is indeed a subject of ongoing discourse to ascertain whether these automatic evalution metrics such as NPMI or C_v genuinely align with the intricacies of human evaluation criteria [4], [39], [14], challenging whether the target of interpretability in Contratopic is ambiguous. However, there are also several works pointing out that these automated coherence metrics are still meaningful. For instance, recent research [40] attested to the significance of coherence metrics like NPMI across a spectrum of datasets, encompassing both general corpora such as Wiki and specialized ones like ArXiv and Pubmed. Their findings substantiated that NPMI remains a meaningful automatic coherence metric, showcasing a substantial correlation with human cognition.

The rationale behind our selection of NPMI lies in its established status as a widely employed coherence metric within topic modeling. Moreover, the incorporation of mutual information estimation resonates with our contrastive term's objectives: minimizing mutual information between distinct topics while simultaneously maximizing mutual information within individual topics.

B. Sampling Strategy

The remaining problem is how to sample T_k from topic k, given the topic-word distribution β_k calculated by the word embeddings ρ and topic embedding t_k . However, sampling from a discrete distribution is non-differential. The Gumbel-softmax trick [18] provides a simple and efficient way to parameterize a discrete distribution and allow for the propagation of gradients in the sampling process. In detail, the Gumbel-softmax estima-

tor gives an approximate one-hot sample $\mathbf{y} = \{y_1, y_2, ..., y_n\}$ with Eq.3.

$$y_{i} = \frac{\exp\left(\left(\log w_{i} + g_{i}\right)/\tau_{g}\right)}{\sum_{j=1}^{V}\exp\left(\left(\log w_{j} + g_{j}\right)/\tau_{g}\right)},$$
(3)

where τ_g is the temperature and $\log(w_i)$ are logits for a softmax distribution $p(x_i|w) = w_i/Z$ and Z is the partition function. y_i denotes the probability of random variable x_i being sampled from the discrete distribution in the Gumbel-Softmax estimator. $g_i = -\log(-\log u_i)$ is called a Gumbel random variable and $u_i \sim \text{Uniform } (0,1)$. Since the randomness g is independent of w, the reparameterization trick can be leveraged to optimize the model with back-propagation.

As we are interested in sampling a subset of words from the topic-word distribution, i.e., drawing samples without replacement, we employ a relaxed subset sampling algorithm proposed by [41]. Given the topic-word distribution β , consisting of β_k , and Gumbel variables \mathbf{g}_k , a Gumbel-max key is computed for each word as $\hat{\mathbf{r}}_k = \log \beta_k + \mathbf{g}_k$, where \mathbf{r}_k, β_k , and $\mathbf{g}_k \in \mathcal{R}^V$. A relaxed subset sample of the items can be drawn by applying a relaxed top-v procedure directly on \hat{r}_k . The procedure defines

$$\mathbf{r}_{k}^{j+1} := \mathbf{r}_{k}^{j} + \log(1 - p(\mathbf{r}_{k}^{j} = 1)),$$
 (4)

where $\mathbf{r}_k^1 := \hat{\mathbf{r}}_k$ and

$$p(\mathbf{r}_k^j = 1) = \frac{\exp(\mathbf{r}_k^j / \tau)}{\sum_{m=1}^{V} \exp(\mathbf{r}_k^j / \tau)}.$$
(5)

Finally, a relaxed v-hot vector for topic k, representing the v words sampled can be computed as $\mathbf{y}_k = \sum_{j=1}^{v} p(\mathbf{r}_k^j = 1)$.

Balance between Positive and Negative Samples: To maintain the simplicity of our method, we abstain from introducing any components aimed at balancing the quantity of positive and negative samples. Nevertheless, our approach does entail the sampling of "v" top words from each topic, which results in $k \cdot C_v^2$ positive word pairs and $v^2 \cdot C_k^2$ negative word pairs in all the possible word pairs. The balance between these pairs can be modulated by tuning v, thereby achieving a proportionate ratio. Of course, other methods such as incorporating a hyper-parameter to balance the weights of negative word pairs can also be considered if necessary.

Input: the input corpus \mathcal{D} , topic number K, total epoch number T, hyperparameter λ , v, temperatures τ_q , τ_β **Output:** K topic-word distributions β_k , D document-topic distribution θ_d Initialize model and variational parameters for epoch from 1 to T do for a random batch of B documents do $\mathcal{L}_{batch} \leftarrow 0;$ $\boldsymbol{\beta} \leftarrow \operatorname{softmax}(\rho \boldsymbol{t} / \tau_{\beta})$ for each document d in the batch do $\theta_d \leftarrow q(\theta | \boldsymbol{w_d})$ $p(\boldsymbol{w}|\boldsymbol{\theta}, \boldsymbol{\rho}, \boldsymbol{t}) \leftarrow \boldsymbol{\theta}_{\boldsymbol{d}}^{\top} \boldsymbol{\beta}.$ $\mathcal{L}_{batch} \leftarrow \mathcal{L}_{batch} + (\mathcal{L}_{rec} + \mathcal{L}_{kl})$ by Eq.1; end for for k from 1 to K do $\mathbf{\hat{r}}_k \leftarrow \log \beta_k + \mathbf{g}_k$ for j from 1 to v do Compute $p(\mathbf{r}_k^j = 1)$ by Eq. 4 and Eq. 5 end for $\mathbf{y}_k \leftarrow \sum_{j=1}^v p(\mathbf{r}_k^j = 1)$ Generate the subset T_k with the v-hot vector \mathbf{y}_k end for $\mathcal{L}_{batch} \leftarrow \mathcal{L}_{batch} + \lambda \mathcal{L}_{con}$ by Eq.2; Update model parameters with $\nabla \mathcal{L}_{batch}$ end for end for

C. Training Objective

Our final training objective is

$$\mathcal{L}_{tr} = \mathcal{L}_{rec} + \mathcal{L}_{kl} + \lambda \mathcal{L}_{con}, \tag{6}$$

where λ is a hyperparameter. The training procedure is described in Algorithm 1.

A possible concern on Contratopic could be whether optimizing evaluation metrics in training objectives is valid or perfectly fair. Our objective function encompasses not solely the contrastive term, intricately tied to the evaluation metrics, but also integrates the conventional KL-divergence term and reconstruction term. The efforts to make the evaluation metrics to be incorporated in the training objectives are also parts of our contribution. Moreover, optimizing an objective closely aligned with the evaluation metrics is not rare in the domain of machine learning. For instance, the ubiquitous crossentropy objective function maintains a significant correlation with diverse evaluation metrics, including AUC scores and accuracy measurements. Besides, there are also works in image classification that focus on directly optimizing the AUROC and AUPRC scores during the training stage [42], [43].

D. From Mutual Information Estimation Perspective

The loss function of contrastive learning in our ContraTopic is similar to most mutual information neural estimation methods such as MINE [44]. However, there are still some differences during the optimization. MINE uses a lower bound to the mutual information based on the Donsker-Varadhan representation of the KL-divergence and chooses \mathcal{F} to be the family of functions $K_{\phi}: \mathcal{X} \times \mathcal{Z} \to \mathcal{R}$ parameterized by a deep neural network with parameters $\phi \in \Phi$,

$$I(X;Z) \ge I_{\Phi}(X,Z) := \sup_{\phi \in \Phi} \mathbb{E}_{\mathbb{P}_{XZ}} \left[K_{\phi} \right] - \log \left(\mathbb{E}_{\mathbb{P}_{X} \otimes \mathbb{P}_{Z}} \left[e^{K_{\phi}} \right] \right)$$
⁽⁷⁾

where X and Z are random variables and \mathbb{P}_{XZ} is the joint distribution and $\mathbb{P}_X \otimes \mathbb{P}_Z$ is the product of their marginal distribution. Given the joint and marginal distribution, MINE optimizes the K_{ϕ} to maximize the objective, which measures the similarities between samples from X and Z.

In most mutual information neural estimation scenarios, the marginal distribution of variables X and Z is typically available, while the similarity measure network $\mathcal{K}(\cdot)$ is unknown and necessitates parameterization and optimization. However, in the case of ContraTopic, the similarity measure network $\mathcal{K}(\cdot)$ is pre-defined as the NPMI score between two given words and cannot undergo optimization during training. In contrast, we parameterize the marginal distribution of X and Z and optimize their distributions to maximize the objective. In summary, to enhance the coherence and diversity of topics, we employ parameterization and optimization techniques by optimizing the topic-word distribution based on provided similarity measure networks and NPMI scores, thereby maximizing the mutual information within a single topic and minimizing that across different topics.

E. Differences between ContraTopic and Other methods

A pivotal distinction between our method and other topic models that incorporate contrastive terms stems from the foundational insights that underscore each approach. As delineated in related works, other methods, exemplified by CLNTM [34], employ a "document-wise" contrastive term, with their guiding principle centered around nurturing similar document-topic distribution among similar documents, which will implicitly benefit the topic-word distribution and thereby contribute to topics with higher quality. In stark contrast, our approach adopts a "topic-wise" contrastive term, which, in a more direct and unequivocal manner, fosters coherence and diversity of the topic-word distribution, leading to an enhancement in the quality of topics. Empirical experiments corroborate this distinction, revealing that our topic-wise contrastive term eclipses the quality achieved by CLNTM, thus underscoring the tangible merits of optimizing the topic-word distribution to improve topic quality.

Compared with CLNTM, our definitions of samples, noted as i or a in eq(2), are different. In Contratopic, we treat predominant words from topics as samples while CLNTM treats documents as samples. Such differences mainly result from the different fundamental insights discussed above.

Besides, the definitions of similarity functions, noted as $\mathcal{K}(\cdot)$ in eq(2), are also different. In Contratopic, we use the precomputed NPMI scores to measure the similarity between words while CLNTM leverages dot product among document representations to measure the similarity between documents.

 TABLE I

 Summary of the statistics for three datasets

	Vocabulary Size	Training Samples	Test Samples	Average Length	Number of Tokens
20NG	5,770	10,827	7,183	59.8	1,076,941
Yahoo	7,394	89,808	59,873	45.9	6,872,000
NYTimes	34,330	179,814	119,876	345.7	103,608,732

Last but not least, the sampling strategies, noted as P(i) and I in eq(2), for generating positive and negative samples are still different. CLNTM indeed leverages a word-based sampling strategy to draw positive and negative documents via modifying the weights of significant tokens based on the tf-idf scores. However, our positive and negative words are defined by the topics they sampled from, which is completely different.

V. EXPERIMENTS

A. Datasets

Our experiments are conducted on three widely-used datasets, including 20 newsgroups (20NG), UIUC Yahoo Answers (Yahoo), and New York Times (NYTimes). 20NG [45] is a dataset that contains around 20,000 newsgroup documents and is commonly used in the topic modeling field. Yahoo [46] is a larger dataset that contains nearly 150,000 documents related to lots of questions and corresponding answers. NYTimes 2 is a collection of about 300,000 news articles with a huge vocabulary. We preprocess documents in each dataset by tokenizing, filtering out stop words, words with document frequency above 70%, and words appearing in less than around 100 documents (depending on the dataset). Then we remove the documents shorter than two words. It should be noted that 20NG and Yahoo are associated with document labels. We follow the original division of training and test sets on 20NG. For Yahoo and NYTimes, the ratio of training to test samples is 6:4. The statistic details of our used datasets are shown in Table I.

B. Evaluation Metrics

For topic interpretability, we choose two kinds of common metrics: topic coherence, and topic diversity. **Topic coherence** measures the average NPMI over the topic K_{TC} words of the selected topics. **Topic diversity** measures the percentage of unique words in the top K_{TD} words of selected topics. To comprehensively evaluate the topics, we follow the experimental settings in NSTM [12] and report the average NPMI scores in different percentages of topics. The proportions of the selected topics vary from 10% to 100%. Following previous works [12], [25], K_{TC} is set to 10 and K_{TD} is set to 25.

For the evaluation of document-topic distributions, we perform document clustering tasks. We report the purity and Normalized Mutual Information (NMI) on 20NG and Yahoo, where the document labels are available. Given the document-topic distribution as the document representation, we apply the KMeans algorithm on test data and report the scores of the KMeans clusters (denoted by **km-Purity** and **km-NMI**),

²https://archive.ics.uci.edu/ml/datasets/Bag+of+Words

following [25]. The number of clusters in KMeans varies in the range of 20, 40, 60, 80, 100. For all the metrics, higher values indicate better performance.

C. Experimental Settings

We compare the performance of our proposed model with the following baselines: 1) conventional topic models, LDA [1], the most famous topic model; 2) VAE-based NTMs, such as ProdLDA [9], which replaces the mixture model in LDA with a product of experts, and WLDA [15], which replaces the KL-divergence with the Maximum Mean Discrepancy, and ETM [11]. which incorporates word embeddings into NTMs; 3) OT-based NTMs, NSTM [12], which learns the topics proportions by directly minimizing the OT distance to the document-word distribution, and WeTe [25], which views each document as a set of word embeddings and projects topics into the same embedding space; 4) NTMs that incorporate topic interpretability into objectives, such as NTM-R [13], which designs a topic coherence objective into the training process and VTMRL [38], which incorporates topic coherence measures as reward signals. 5) NTMs that also leverage contrastive learning but in a document-wise manner, such as CLNTM [34] which encourage similar document-topic distribution among related documents. For all the above baselines, we either use their official code or reproduce their models with the best reported settings.

D. Settings for Our Proposed Model

We implement ContraTopic on Pytorch. We use ETM as our backbone model and share the same hyper-parameters. For the encoder, we use a three-layer perceptron of 800 hidden units and SeLU as the activation function, followed by a dropout layer (rate = 0.5) and a batch norm layer. Similar to several baselines, we use the GloVe word embeddings pre-trained on Wikipedia³. We freeze the word embeddings during the training time for stability. The number of topics is set to 100 in all the topics. We use the Adam optimizer with a learning rate of 0.0005 and batch size of 1000 for 100 epochs. For our regularizer, we implement the function $\mathcal{K}(\cdot)$ with the pre-computed NPMI scores on the training set. Therefore, we evaluate the topic coherence on the unseen test data to make fair comparisons. Since our method only adds a regularizer to the backbone model, we keep the shared hyperparameters unchanged and perform the grid search for other hyper-parameters such as λ, v, τ_g , and τ_g on a validation set split from the training corpus. The λ is set to 40, 40, and 300

³https://nlp.stanford.edu/projects/glove/



Fig. 2. The results of topic interpretability evaluation. The first row shows the topic coherence of all the datasets in the test set, respectively. The second row shows the corresponding topic diversity scores. In each subfigure, the horizontal axis indicates the proportion of selected topics according to their NPMIs.



Fig. 3. The results of document representation evaluation. (a) The two subfigures show the km-Purity scores on 20NG (left) and Yahoo(right). (b) The two subfigures show the km-NMI scores on 20NG (left) and Yahoo (right).

for 20NG, Yahoo, and NYTimes respectively. Other hyperparameters such as v, τ_{β} , and τ_{g} are set to the same among three datasets where v is set to 10, τ_{β} is set to 0.1 and τ_{g} is set to be 0.5. The code and our used 20NG dataset can be found in supplementary materials.

E. Computational Analysis

Theoretically, the increased time and space requirements in the proposed approach can be attributed to two factors: the sampling process and the pair-wise computation of NPMI in $\mathcal{K}(\cdot)$. The sampling process primarily contributes to additional time costs, with a complexity of O(M) where Mrepresents the number of samples. On the other hand, the pairwise computation of NPMI leads to increased spatial costs, specifically $O(V^2)$, as it involves storing the precomputed NPMI matrix. Additionally, the precomputation of NPMI can be performed during preprocessing, requiring a time equivalent to approximately 30 training epochs.

Empirically, our experiments, conducted on a machine equipped with 2 Nvidia RTX8000 GPUs and Intel Xeon Gold 6230 CPUs, show that ContraTopic, **even with the complete NPMI matrix in GPU memory**, requires 14593MiB GPU memory (8673MiB GPU memory if we only maintain the matrix in CPU memory) and 65.68 sec/epoch for NYTimes, a relatively modest resource consumption. We believe the extra computational expense is justified by the improvements.

F. Results

The results of topic coherence and topic diversity on three datasets are shown in Figure 2. We run each model in comparison three times by modifying only the random seeds and reporting the mean values. The error bars are omitted in the figure for brevity. From the results, we can observe that

Metrics	Topic Coherence			Topic Diversity			km-Purity		
Percentage	10%	50%	90%	10%	50%	90%	20%	60%	100%
ContraTopic	0.54±0.2	$0.36{\pm}0.1$	0.28±0.3	0.98±0.1	$0.86{\pm}0.2$	$0.72{\pm}0.2$	0.37±0.0	$0.44 {\pm} 0.1$	$0.46{\pm}0.0$
ContraTopic-P	$0.44{\pm}0.2$	$0.33 {\pm} 0.1$	0.27 ± 0.1	0.98 ± 0.1	0.83 ± 0.2	$0.69{\pm}0.1$	0.36 ± 0.0	0.45±0.0	$0.44{\pm}0.0$
ContraTopic-N	0.42 ± 0.2	0.27 ± 0.4	$0.19 {\pm} 0.5$	0.95 ± 0.1	0.69 ± 0.3	0.61 ± 0.2	$0.34{\pm}0.1$	$0.37 {\pm} 0.1$	$0.38 {\pm} 0.1$
ContraTopic-I	0.45 ± 0.1	$0.33 {\pm} 0.2$	$0.26 {\pm} 0.2$	0.95 ± 0.1	$0.84{\pm}0.3$	$0.70 {\pm} 0.2$	0.35 ± 0.0	$0.45{\pm}0.0$	$0.44 {\pm} 0.0$
ContraTopic-S	$0.50 {\pm} 0.2$	$0.34{\pm}0.1$	$0.26 {\pm} 0.1$	0.96 ± 0.1	$0.85{\pm}0.2$	$0.72{\pm}0.1$	0.36 ± 0.1	$0.44{\pm}0.0$	$0.45{\pm}0.0$

TABLE II Results of different variants on 20NG.



Fig. 4. The sensitivity analysis results of λ and v on 20NG and Yahoo.



Fig. 5. The sensitivity analysis results of λ and v on NYTimes.

ContraTopic outperforms almost every baseline in terms of topic coherence. Though NSTM has competitive results on 20NG, its topic diversity still has a certain gap with ContraTopic. **Some baselines have shown an obvious decline in topic coherence but an increment in topic diversity when the evaluated topics increase.** A possible reason is that the topics in the tail are of very low quality containing some infrequent words that are quite different from the words in topics with high NPMI. Despite achieving a high level of topic diversity in NYTimes, both WeTe and ProdLDA exhibit a significant decline in their topic coherence, which falls considerably short of those achieved by ContraTopic.

Figure 3 presents the results of km-Purity and km-NMI. Despite not incorporating any specific techniques for document representation, ContraTopic manages to achieve competitive outcomes on 20NG. Although ETM and VTMRL outperform ContraTopic on Yahoo, they fall short in terms of topic coherence and diversity. **Besides, we have to posit that the**

results obtained from km-Purity and km-NMI, despite their application in numerous studies, merely encapsulate a fraction of the multifaceted nature inherent in document representation quality. These metrics essentially measure the alignment between unsupervised document-topic distributions and human-annotated labels. Nonetheless, the alignment between the generated topics in unsupervised topic models and the annotated labels of the dataset remains uncertain. Consider, for instance, a toy dataset comprising nine news articles, each centered around politics, sports, and economics within the United States, Japan, and China. In the course of manual annotation, we designated three articles for each category: "politics," "sports," and "economics." When subjecting these articles to topic modeling, there is no assurance that the acquired topics will precisely correspond to politics, sports, and economics. It is plausible that due to the involvement of common public figures in news from the same nation, the model might discern "United States," "Japan," and "China" as three



Fig. 6. The results of backbone model substitution for 20NG in the first row and Yahoo in the second row. The blue lines correspond to various backbone models, while the pink lines represent backbone models improved by our regularizer. Matching markers indicate the usage of the same backbone models.

distinct topics. In such a scenario, even if we obtain high-quality topics, the model may still achieve low scores in km-Purity and km-NMI. As a consequence, we posit that a lower score in km-Purity and km-NMI does not mean worse document representation but the inconsistency between generated topics and annotated dataset labels.

In summary, ContraTopic excels in extracting high-quality, interpretable topics while also preserving the capability to learn useful document representations for clustering.

G. Ablation Study

The results of our ablation study are shown in Table II. The percentage values for topic coherence and topic diversity indicate the proportion of selected topics, whereas the percentage values for km-Purity represent the proportion of clusters.

Contrastive objective. The crucial design decision in ContraTopic centers around the contrastive learning objective denoted as \mathcal{L}_{con} , which can be broken down into two components: the calculation involving positive sample pairs and negative sample pairs. To assess the impact of each component, we introduce two variants: 1) ContraTopic-P, which solely focuses on positive sample pairs, and 2) ContraTopic-N, which solely focuses on negative sample pairs. The performance of topic coherence and diversity exhibits a decline of approximately 5% for ContraTopic-P and 12% for ContraTopic-N. This finding underscores the significance of considering multiple facets of interpretability. Comparatively, the km-Purity remains competitive for ContraTopic-S, while ContraTopic-N experiences a significant deterioration. These results indicate that exclusively considering negative sample pairs is detrimental to the performance of NTMs.

Similarity measure network. Another core component of ContraTopic is the similarity measure network which is implemented as pre-defined NPMI scores. We design a variant following NTM-R [13] to implement $\mathcal{K}(\cdot)$ with the inner product between word embeddings, noted as ContraTopic-I. We find that ContraTopic substantially outperforms this variant, suggesting the advantage of using NPMI for $\mathcal{K}(\cdot)$, which aligns closer with the current evaluation of topic interpretability. **Sampling strategy.** The final key design of ContraTopic is that we introduce a sampling process in the estimation of mutual information between topics. A possible variant is to leverage the weight sum operation of topic-word distribution as an expectation for the mutual information estimation, noted as ContraTopic-S. We find that ContraTopic-S has the least performance decline. The result suggests that the sampling strategy helps the model to improve topic interpretability.

H. Sensitivity Analysis

The sensitive analysis is conducted on two significant hyper parameters, λ , controlling the power of our regularizer and v, the number of words sampled for topic-word distribution. Similar to Table II, we only report the highest and lowest results (under the maximum and minimum percentages) of topic coherence, topic diversity, and km-Purity. The results for other percentages exhibit a consistent trend, thus we exclude them for the sake of conciseness. The results are provided in Figure 4 and Figure 5. We plot the results of 20NG and Yahoo in the same subfigure due to space limitations. Besides, the scale of λ in the NYTimes is also much larger than the other two datasets. The trends on all three datasets are similar.

When we vary λ from 0 to 90, the topic coherence increases gradually, especially for most coherent topics. As for the diversity, the maximal and minimal scores increase at first and decline when the λ gets too large. The km-Purity has a similar tendency with topic diversity. Interestingly, when λ gets larger, the topic diversity, though declining, seems to have a smaller variance among topics. As we vary the parameter v within the range of 1 to 19, we observe a rapid initial increase in both topic coherence and km-Purity, followed by a sustained high level. We found the choice of λ is more sensitive to different datasets while v seems to be less sensitive. Empirically, choosing an appropriate λ is important for different datasets. We believe our sensitivity analysis can help readers apply our method to their own dataset.

A discernible trade-off emerges between topic coherence and topic diversity when λ gets large values, a phenomenon acknowledged by other studies as well [47]. This observation is

TABLE III Results of the word intrusion scores on 20NG

LDA	ProdLDA	WLDA	ETM	NSTM	WeTe	NTMR	VTMRL	CLNTM C	ontraTopic
WIS 0.34	0.37	0.34	0.58	0.68	0.67	0.29	0.46	0.64	0.80

potentially attributable to the emergence of multiple repetitive topics with exceedingly high coherence, leading to elevated topic coherence scores but terrible topic diversity scores. Alternatively, the phenomenon may also arise due to the risk of an excessively large lambda overshadowing the original loss function in favor of the contrastive term, thus compromising the integrity of topic modeling.

I. Backbone Model Substitution

To validate ContraTopic's effectiveness across different architectures, we substitute ContraTopic's backbone model from ETM to WLDA and WeTe. The results are shown in Figure 6. Our regularizer consistently improves topic coherence and diversity across different backbone models, as indicated by the results. Furthermore, backbone models with our regularizer demonstrate competitive performance in terms of km-Purity and km-NMI. Notably, WLDA benefits significantly from our regularizer, exhibiting substantial improvements in both km-Purity and km-NMI. This observation guides our future exploration towards enhancing both topic quality and document representation quality simultaneously.

J. Human Evaluation

One primary use of topic models is in computer-assisted content analysis, where topics help humans understand large amounts of text, organize information, retrieve relevant documents, personalize recommendations, detect trends, facilitate knowledge sharing, and gain valuable insights from complex datasets. As a result, human evaluation is crucial in deriving new topic models because it helps ensure that the models align with human understanding and expectations. Human evaluators can provide subjective judgments, validate the quality of topics generated that automatic evaluation alone may not capture, leading to more accurate and effective topic models.

1) Human evaluation Design: Based on the research conducted by Hoyle et al [4], we conducted a word intrusion task as our human evaluation for topic quality. The word intrusion task involves identifying words that do not belong when the top words in a topic represent a coherent latent category. We invited 20 participants to perform the human evaluation, ensuring their privacy and not collecting any personal information. To evaluate both the coherence and diversity of topics, we generated "intruder" words from the top words in other topics. The word intrusion scores (WIS), ranging from 0 to 1, quantitatively measure the ability of annotators to detect the "intruder" word.

2) *Questionnaire Generation:* The questionnaire has been completed by all participants. For each evaluated method, thirty topics were selected from the total of 100 topics in 20NG for evaluating each model, including Contratopic. Consequently, our questionnaire comprises 300 questions (10 methods * 30

topics per method). Each question requires selecting an intruder word from a set of five top words within a given topic.

Topic Selection: Due to the impracticality and time constraints of evaluating all topics across each method, we employ a selective approach in human evaluation, focusing on a subset of topics. To ensure fairness in our comparisons, we randomly sample 3 topics from each decile of topics sorted by topic coherence, ensuring even representation across all topics. To avoid bias caused by repeated or similar topics in different models, we iterate the topic selection process until no duplicates are present in a single questionnaire.

Intruder Generation: The intruder word is chosen from topics that were not included in the question set. To manage the workload of participants, we only chose the five most probable words from each selected topic. Along with these words, we randomly select an intruder word from a pool of words with low probabilities in the current topic (to minimize the chance of it belonging to the same semantic group) but a high probability in other unselected topics (to ensure it is not outright rejected due solely to rarity). All six words are then shuffled and presented to the participant. An example of our questionnaires is shown in Figure 7.



Fig. 7. An Example of the questionnaire used in our human evaluation.

3) Participants: We recruit 20 participants including 12 males and 8 females with a computer science background, familiar with basic news concepts and topic models. The majority of the participants recruited have at least a graduate degree or are undergraduates. The average age is 26.3.

We do understand that a larger sample size of participants from diverse demographic groups would have increased the statistical power and generalizability of the human evaluation. However, our sample size was determined based on available resources and time constraints. Furthermore, we note that our sample size is still comparable to previous works, as cited in [48] and [17], which have conducted similar human evaluation experiments that meet scientific standards. Besides, [4] also shows that a minimum of fifteen crowd-workers per topic for human evaluation is enough to ensure sufficient statistical power.

TABLE IV GENERATED TOPICS ON 20NG.

Models	NPMI	Topic Word Examples
	0.41	israel jews israeli war jewish arab state land
	0.37	space nasa data earth launch orbit moon shuttle
LDA	0.37	people gun government armenian armenians turkish police guns
	0.36	game team year games season hockey league players
	0.35	key encryption chip keys clipper public security government
	0.67	armenian armenians turkish people turkey greek turks ottoman
	0.52	patients health medical disease cancer drug study drugs
ETM	0.43	space nasa launch orbit earth satellite lunar shuttle
	0.42	drive scsi disk hard controller drives bus floppy
	0.42	government people jobs russian work program working money
	0.63	cadre geb pitt surrender gordon skepticism chastity intellect
	0.46	disease pain patients drugs medical cancer symptoms blood
WeTe	0.46	god jesus bible church christian faith christ christians
	0.41	armenian turkish armenians people jews war government turkey
	0.40	fbi koresh fire news waco police batf compound
	0.68	chastity cadre geb surrender shameful dsl intellect gordon
	0.68	shameful geb cadre intellect chastity surrender skepticism gordon
CLNTM	0.68	chastity cadre geb shameful dsl intellect skepticism surrender
	0.53	glenn rice readme solaris oz gcc compatibility ftp
	0.46	detroit rangers rockies louis chicago toronto pittsburgh boston
ContraTopic	0.69	armenian armenians turkish armenia genocide azerbaijan turks turkey
	0.52	health patients medical disease cancer drug diseases study
	0.50	god jesus church christ christian bible faith holy
	0.45	server motif application widget export uk applications client
	0.43	image graphics images jpeg color gif format picture

We pay participants 18 USD for finishing the questionnaire, equivalent to nearly 14 USD/hour.

4) Results: Table III displays the results of our human evaluation. The findings exhibit similarity to the topic coherence results, showcasing ContraTopic's superior performance over all baseline models. While the selection of intruder words is important, we have observed that participants face greater challenges in correctly identifying intruders within topics with lower coherence. This observation highlights the alignment between automatic and human evaluations of topic models, further strengthening their reliability and consistency.

K. Case Study

We present the generated topics for 20NG, Yahoo, and NYTimes datasets. Topics with the highest NPMI values are shown in Table IV, V, and VI. We show the top topics generated by our method and some representative baselines such as LDA, ETM, WeTe, and CLNTM. Besides, with the popularity of large language models, there are works [49] utilizing large language models to evaluate the quality of generated topics, so we also use large language models to generate a description of our topic to better express the semantic information of each topic based on their topic-word distribution and their most related documents. We only present the top words of the top 5 topics for each method and descriptions for the top 5 topics in ContraTopic due to space limitations.

We can observe that some baselines generate topics that mix with other topics, resulting in a decrease in NPMI, such as the third topic of LDA in 20NG. Besides, some baselines also generate topics that overlap with other topics which leads to a decline in topic diversity, such as the topics generated by ETM on Yahoo. Although the top topics displayed look good, the two types of issues mentioned above often occur for topics with slightly lower NPMI rankings in WeTe. For baselines like CLNTM with high topic consistency and poor topic diversity, there are obvious repetitions in their top topics.

TABLE V Generated topics on Yahoo.

Models	NPMI	Topic Word Examples
	0.48	oil cheese sauce pepper garlic juice fresh green
	0.47	cup add salt minutes sugar butter mix cream
LDA	0.45	weight body fat lose eat healthy diet exercise
	0.40	product stores forever asp shoes shirt outfit category
	0.38	food eat chicken meat rice eating cook corn
	0.47	phone number send email mail cell plan service
	0.47	food eat drink milk foods eating meat fruit
ETM	0.46	god believe religion church christians christian jesus faith
	0.44	ipod music ps song phone itunes xbox cell
	0.43	cat cats food vet feed pet eat foods
	0.47	cup add chicken oil cheese salt minutes flour
	0.47	god religion believe bible jesus christian religious church
WeTe	0.43	eat food weight eating diet healthy lose fat
	0.36	download ipod video dvd file music player files
	0.36	dog dogs cat vet puppy cats animals pet
	0.48	pokemon team diamond pearl earthquake surf beam dragon
	0.42	add minutes oil just cook salt heat garlic
CLNTM	0.42	pokemon trade pearl diamond fc code battle shiny
	0.41	laptop pc card memory graphics ram mb processor
	0.40	video dvd download format convert videos ipod movie
	0.59	pentium mhz nvidia ghz intel mb geforce laptop
	0.58	preheated parmesan browned preheat bake grated mozzarella saute
ContraTopic	0.57	wcs aeropostale servlet jsp fid asp abercrombie pacsun
	0.56	hhh khali cena batista umaga wwe vs orton
	0.52	sugar cup cream butter mix chocolate baking flour

Topic Descriptions for 20NG in ContraTopic:

- Topic 1: Armenian Genocide and Turkish-Armenian Relations. This topic revolves around historical and geopolitical aspects related to the Armenian Genocide, Armenian people, and their interactions with Turkey and Azerbaijan. It highlights the historical conflict and tensions between Armenia and Turkey, as well as the involvement of the Soviet Union and Azerbaijan in the region.
- Topic 2: Medical Research and Treatment. This topic focuses on various aspects of healthcare, including patients, medical conditions, diseases, cancer, drugs, and treatment. It suggests discussions related to medical studies, advancements in treatment methods, and the exploration of different drugs for managing diseases.
- **Topic 3: Christianity and Faith.** This topic delves into matters of faith, particularly centered around Christianity. It includes references to God, Jesus, the Church, the Bible, and the beliefs and practices of Christians. It reflects discussions about religious faith, the significance of Jesus and Christian teachings, and the concept of heaven.
- Topic 4: Software Applications and Development. This topic centers on software development and related concepts. It mentions servers, applications, clients, user interfaces. It suggests discussions about developing software, creating widgets and applications, exporting data, and user interactions in the context of Unix-based systems.
- Topic 5: Image Formats and Graphics Software. This topic revolves around graphic design, specifically discussing image formats such as JPEG and GIF. It touches upon graphics software and the representation of images using different color formats. It implies discussions about graphic design software, image file types.

Topic Descriptions for Yahoo in ContraTopic:

• Topic 1: Computer Hardware. This topic revolves around

TABLE VI GENERATED TOPICS ON NYTIMES.

Models	NPMI	Topic Word Examples
	0.62	palestinian israel israeli arafat yasser peace sharon israelis
	0.50	russian russia soviet vladimir putin moscow union chechnya
LDA	0.42	con una mas las por como dice los
	0.40	cup minutes add tablespoon oil pepper sugar teaspoon
	0.35	military army taliban afghanistan forces war troop soldier
	0.69	palestinian israeli israel arafat peace yasser israelis arab
	0.49	cup tablespoon add teaspoon sauce minutes sugar butter
ETM	0.45	military war taliban forces afghanistan army afghan soldier
	0.44	game coach quarterback yard football bowl touchdown defensive
	0.41	film movie character actor movies comedy starring hollywood
	0.67	dicen informacion algunos telefono para notas tienen estan
	0.51	habla clase aparecen nuevas pocos busca sigue tiempos
WeTe	0.44	bush republican campaign bill clinton gore house
	0.35	run hit game baseball team season manager league
	0.35	team game season lay player win won point
	0.53	pelzer berkley kiyosaki how zukav lechter bantam jove distinguishable
	0.49	kostunica serbian vojislav belgrade serbia yugoslav serb yugoslavia
CLNTM	0.46	additionally toder oder eta column pageex nytsyn rickc
	0.43	pga bogey birdie birdies putt fairway par tee
	0.40	anos disney sus parte gran ser entre estan
ContraTopic	0.78	economia dedicada notas cubrir transmiten comercio temas expertos
	0.72	erstad spiezio glaus bengie schoeneweis darin disarcina garret
	0.71	palestinian israeli israel arafat israelis yasser sharon jerusalem
	0.61	taliban afghanistan laden afghan bin pakistan islamic osama
	0.56	laker nba neal shaquille bryant kobe phil jackson

computer hardware components and specifications. The topic seems to focus on aspects like processors, graphics cards, memory, and connectivity.

- Topic 2: Cooking Instructions. This topic provides instructions and techniques for cooking. The topic suggests actions such as preheating, baking, sautéing, and sprinkling ingredients to create delicious dishes.
- **Topic 3: Fashion Brands and Stores.** This topic relates to fashion brands and retail stores. The topic indicates a focus on brands, online catalogs, and physical stores associated with clothing and fashion.
- **Topic 4: Professional Wrestling.** This topic revolves around professional wrestling and wrestling personalities. The topic suggests discussions or comparisons between various wrestlers, their matches, and their involvement in the WWE (World Wrestling Entertainment).
- **Topic 5: Baking Ingredients.** This topic focuses on ingredients used in baking. The topic suggests the use of these ingredients in recipes to create baked goods.

Topic Descriptions for NYTimes in ContraTopic:

- **Topic 1: Economy and Trade Expertise.** This topic likely focuses on economic issues, trade, and expertise in Spanish. It may involve discussions about economic activities, market trends, trade policies, and insights shared by experts in the field.
- **Topic 2: Baseball Players** This topic revolves around baseball players and possibly specific teams. It includes mentions of players such as Darin Erstad, Scott Spiezio, Troy Glaus, Bengie Molina, Scott Schoeneweis, and Garret Anderson, suggesting discussions about their careers.
- **Topic 3: Israeli-Palestinian Conflict.** This topic centers on the Israeli-Palestinian conflict and related issues. It includes references to Palestinian and Israeli identities, key figures like Yasser Arafat and Ariel Sharon, as well as Jerusalem, the contested city central to the conflict.

- Topic 4: Taliban and Osama bin Laden. This topic revolves around the Taliban, Afghanistan, and Osama bin Laden, focusing on Islamic extremism and terrorism. It likely involves discussions about the Taliban's rule in Afghanistan, Bin Laden's involvement in terrorism, and related geopolitical implications.
- Topic 5: Los Angeles Lakers and NBA. This topic pertains to the Los Angeles Lakers basketball team and the NBA. It includes references to players such as Shaquille O'Neal and Kobe Bryant, as well as coach Phil Jackson, suggesting discussions about their careers, achievements, and the team's performance in the NBA.

VI. LIMITATION

We consider the following limitations also as our future work. For the methodology, while our method primarily focuses on topic-wise contrastive learning to enhance topic interpretability, there is room for further improvement in the quality of document representation compared to certain baselines. Subsequent research can explore a unified multi-level contrastive learning framework that incorporates both topicwise and document-wise approaches, aiming to enhance both topic interpretability and document representation. Besides, we utilize pre-computed NPMI scores from the training dataset to evaluate topic interpretability to humans, but leveraging the remarkable capabilities of large language models could offer a superior alternative for more human-aligned measurements. For the extra computational cost, though our method does not demand any human-annotation cost, we still need to compute the NPMI matrix on the corpus. Though the extra computational expenses are acceptable as we discussed in the "Computational Analysis" section, there is still some room for improvement. For the online setting, our method is designed under the common offline setting of topic modeling. An important future work can be to extend our method to an online setting where documents are partitioned into time slices [50], [51]. For the experiments, despite efforts to diversify participant recruitment, the human evaluation predominantly involved subjects with high education levels in science-related fields.

VII. CONCLUSION

We propose ContraTopic, an innovative framework for NTMs, with the aim of enhancing the interpretability of generated topics. ContraTopic integrates human cognition of topic interpretability into the training process by incorporating a topicwise contrastive regularizer, which serves as a differentiable surrogate for evaluation metrics. Through contrastive learning, our regularizer encourages topic coherence by bringing positive samples closer together and promotes topic diversity by pushing negative samples apart. Extensive experiments demonstrate that ContraTopic surpasses competing methods in generating highly interpretable topics and deriving document representations.

VIII. ACKNOWLEDGEMENT

This work is supported by the National Natural Science Foundation of China (No.82241052).

REFERENCES

- D. M. Blei, A. Y. Ng, and M. I. Jordan, "Latent dirichlet allocation," *the Journal of machine Learning research*, vol. 3, pp. 993–1022, 2003.
- [2] Y. Zhang, R. Jiang, and L. Petzold, "Survival topic models for predicting outcomes for trauma patients," in 2017 IEEE 33rd International Conference on Data Engineering (ICDE). IEEE, 2017, pp. 1497–1504.
- [3] J. Wood, P. Tan, W. Wang, and C. Arnold, "Source-Ida: Enhancing probabilistic topic models using prior knowledge sources," in 2017 IEEE 33rd International Conference on Data Engineering (ICDE). IEEE, 2017, pp. 411–422.
- [4] A. Hoyle, P. Goel, A. Hian-Cheong, D. Peskov, J. Boyd-Graber, and P. Resnik, "Is automated topic model evaluation broken? the incoherence of coherence," *Advances in Neural Information Processing Systems*, vol. 34, 2021.
- [5] H. Jelodar, Y. Wang, C. Yuan, X. Feng, X. Jiang, Y. Li, and L. Zhao, "Latent dirichlet allocation (lda) and topic modeling: models, applications, a survey," *Multimedia Tools and Applications*, vol. 78, no. 11, pp. 15169– 15211, 2019.
- [6] L. Ziyue, "Tensor topic models with graphs and applications on individualized travel patterns," in 2021 IEEE 37th International Conference on Data Engineering (ICDE). IEEE, 2021, pp. 2756–2761.
- [7] W. Wang, X. Cheng, Z. Liu, Y. Lin, Y. Shen, B. Hu, Z. Zhang, X. Zeng, J. Zhou, J. Gu *et al.*, "Intent mining: A social and semantic enhanced topic model for operation-friendly digital marketing," in 2022 IEEE 38th International Conference on Data Engineering (ICDE). IEEE, 2022, pp. 3254–3267.
- [8] Y. Miao, L. Yu, and P. Blunsom, "Neural variational inference for text processing," in *International conference on machine learning*. PMLR, 2016, pp. 1727–1736.
- [9] A. Srivastava and C. Sutton, "Autoencoding variational inference for topic models," in 5th International Conference on Learning Representations, 2017.
- [10] D. P. Kingma and M. Welling, "Auto-encoding variational bayes," arXiv preprint arXiv:1312.6114, 2013.
- [11] A. B. Dieng, F. J. Ruiz, and D. M. Blei, "Topic modeling in embedding spaces," *Transactions of the Association for Computational Linguistics*, vol. 8, pp. 439–453, 2020.
- [12] H. Zhao, D. Phung, V. Huynh, T. Le, and W. Buntine, "Neural topic model via optimal transport," arXiv preprint arXiv:2008.13537, 2020.
- [13] R. Ding, R. Nallapati, and B. Xiang, "Coherence-aware neural topic modeling," in *Proceedings of the 2018 Conference on Empirical Methods* in *Natural Language Processing*, 2018, pp. 830–836.
- [14] C. Doogan and W. Buntine, "Topic model or topic twaddle? reevaluating semantic interpretability measures," in *Proceedings of the* 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, 2021, pp. 3824–3848.
- [15] F. Nan, R. Ding, R. Nallapati, and B. Xiang, "Topic modeling with wasserstein autoencoders," in *Proceedings of the 57th Annual Meeting* of the Association for Computational Linguistics, 2019, pp. 6345–6381.
- [16] J. Chang, S. Gerrish, C. Wang, J. L. Boyd-Graber, and D. M. Blei, "Reading tea leaves: How humans interpret topic models," in *Advances in neural information processing systems*, 2009, pp. 288–296.
- [17] Y. Meng, J. Huang, G. Wang, Z. Wang, C. Zhang, Y. Zhang, and J. Han, "Discriminative topic mining via category-name guided text embedding," in *Proceedings of The Web Conference 2020*, 2020, pp. 2121–2132.
- [18] E. Jang, S. Gu, and B. Poole, "Categorical reparameterization with gumbel-softmax," arXiv preprint arXiv:1611.01144, 2016.
- [19] H. Zhang, B. Chen, D. Guo, and M. Zhou, "Whai: Weibull hybrid autoencoding inference for deep topic modeling," in *International Conference on Learning Representations*, 2018.
- [20] S. Burkhardt and S. Kramer, "Decoupling sparsity and smoothness in the dirichlet variational autoencoder topic model." J. Mach. Learn. Res., vol. 20, no. 131, pp. 1–27, 2019.
- [21] R. Wang, D. Zhou, and Y. He, "Atm: Adversarial-neural topic model," Information Processing & Management, vol. 56, no. 6, p. 102098, 2019.
- [22] X. Wang and Y. Yang, "Neural topic model with attention for supervised learning," in *International Conference on Artificial Intelligence and Statistics*. PMLR, 2020, pp. 1147–1156.
- [23] L. Yang, F. Wu, J. Gu, C. Wang, X. Cao, D. Jin, and Y. Guo, "Graph attention topic modeling network," in *Proceedings of The Web Conference* 2020, 2020, pp. 144–154.

- [24] Q. Xie, J. Huang, P. Du, M. Peng, and J.-Y. Nie, "Graph topic neural network for document representation," in *Proceedings of the Web Conference 2021*, 2021, pp. 3055–3065.
- [25] D. Wang, D. Guo, H. Zhao, H. Zheng, K. Tanwisuth, B. Chen, and M. Zhou, "Representing mixtures of word embeddings with mixtures of topic embeddings," *arXiv preprint arXiv:2203.01570*, 2022.
- [26] X. Wu, X. Dong, T. T. Nguyen, and A. T. Luu, "Effective neural topic modeling with embedding clustering regularization," in *International Conference on Machine Learning*. PMLR, 2023, pp. 37335–37357.
- [27] R. D. Hjelm, A. Fedorov, S. Lavoie-Marchildon, K. Grewal, P. Bachman, A. Trischler, and Y. Bengio, "Learning deep representations by mutual information estimation and maximization," *arXiv preprint* arXiv:1808.06670, 2018.
- [28] P. Khosla, P. Teterwak, C. Wang, A. Sarna, Y. Tian, P. Isola, A. Maschinot, C. Liu, and D. Krishnan, "Supervised contrastive learning," *Advances in Neural Information Processing Systems*, vol. 33, pp. 18661–18673, 2020.
- [29] E. Xie, J. Ding, W. Wang, X. Zhan, H. Xu, P. Sun, Z. Li, and P. Luo, "Detco: Unsupervised contrastive learning for object detection," in *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2021, pp. 8392–8401.
- [30] B. Sun, B. Li, S. Cai, Y. Yuan, and C. Zhang, "Fsce: Few-shot object detection via contrastive proposal encoding," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2021, pp. 7352–7362.
- [31] T. Miyato, S.-i. Maeda, M. Koyama, and S. Ishii, "Virtual adversarial training: a regularization method for supervised and semi-supervised learning," *IEEE transactions on pattern analysis and machine intelligence*, vol. 41, no. 8, pp. 1979–1993, 2018.
- [32] L. Logeswaran and H. Lee, "An efficient framework for learning sentence representations," in *International Conference on Learning Representations*, 2018.
- [33] X. Zhou, J. Bu, S. Zhou, Z. Yu, J. Zhao, and X. Yan, "Improving topic disentanglement via contrastive learning," *Information Processing & Management*, vol. 60, no. 2, p. 103164, 2023.
- [34] T. Nguyen and A. T. Luu, "Contrastive learning for neural topic model," Advances in Neural Information Processing Systems, vol. 34, 2021.
- [35] X. Wu, A. T. Luu, and X. Dong, "Mitigating data sparsity for short text topic modeling by topic-semantic contrastive learning," *arXiv preprint arXiv:2211.12878*, 2022.
- [36] B. Harandizadeh, J. H. Priniski, and F. Morstatter, "Keyword assisted embedded topic model," in *Proceedings of the Fifteenth ACM International Conference on Web Search and Data Mining*, 2022, pp. 372–380.
- [37] Y. Lin, X. Gao, X. Chu, Y. Wang, J. Zhao, and C. Chen, "Enhancing neural topic model with multi-level supervisions from seed words," in *Findings of the Association for Computational Linguistics: ACL 2023*, 2023, pp. 13 361–13 377.
- [38] L. Gui, J. Leng, G. Pergola, Y. Zhou, R. Xu, and Y. He, "Neural topic model with reinforcement learning," in *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, 2019, pp. 3478–3483.
- [39] A. Hoyle, P. Goel, R. Sarkar, and P. Resnik, "Are neural topic models broken?" arXiv preprint arXiv:2210.16162, 2022.
- [40] J. P. Lim and H. Lauw, "Large-scale correlation analysis of automated metrics for topic models," in *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2023, pp. 13874–13898.
- [41] S. M. Xie and S. Ermon, "Reparameterizable subset sampling via continuous relaxations," arXiv preprint arXiv:1901.10517, 2019.
- [42] Q. Qi, Y. Luo, Z. Xu, S. Ji, and T. Yang, "Stochastic optimization of areas under precision-recall curves with provable convergence," *Advances* in neural information processing systems, vol. 34, pp. 1752–1765, 2021.
- [43] M. Liu, Z. Yuan, Y. Ying, and T. Yang, "Stochastic auc maximization with deep neural networks," arXiv preprint arXiv:1908.10831, 2019.
- [44] M. I. Belghazi, A. Baratin, S. Rajeshwar, S. Ozair, Y. Bengio, A. Courville, and D. Hjelm, "Mutual information neural estimation," in *International conference on machine learning*. PMLR, 2018, pp. 531–540.
- [45] K. Lang, "Newsweeder: Learning to filter netnews," in Machine Learning Proceedings 1995. Elsevier, 1995, pp. 331–339.
- [46] M.-W. Chang, L.-A. Ratinov, D. Roth, and V. Srikumar, "Importance of semantic representation: Dataless classification." in AAAI, vol. 2, 2008, pp. 830–835.

- [47] X. Wu, C. Li, Y. Zhu, and Y. Miao, "Short text topic modeling with topic distribution quantization and negative sampling decoder," in *Proceedings* of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP), 2020, pp. 1772–1782.
- [48] B. Harandizadeh, J. H. Priniski, and F. Morstatter, "Keyword assisted embedded topic model," arXiv preprint arXiv:2112.03101, 2021.
- [49] D. Stammbach, V. Zouhar, A. Hoyle, M. Sachan, and E. Ash, "Re-visiting automated topic model evaluation with large language models," *arXiv* preprint arXiv:2305.12152, 2023.
- [50] L. AlSumait, D. Barbará, and C. Domeniconi, "On-line Ida: Adaptive topic models for mining text streams with applications to topic detection and tracking," in 2008 eighth IEEE international conference on data mining. IEEE, 2008, pp. 3–12.
- mining. IEEE, 2008, pp. 3–12.
 [51] J. H. Lau, N. Collier, and T. Baldwin, "On-line trend analysis with topic models:# twitter trends detection topic model online," in *Proceedings of COLING 2012*, 2012, pp. 1519–1534.