The evolution of cooperation in spatial public goods game with tolerant punishment based on reputation threshold

Gui Zhang,¹ Yichao Yao,¹ Ziyan Zeng,¹ Minyu Feng^{*},¹ and Manuel Chica^{2, 3}

¹⁾The College of Artificial Intelligence, Southwest University, No.2 Tiansheng Road, Beibei, Chongqing, 400715, China.

²⁾Department of Computer Science and A.I. Andalusian Research Institute DaSCI "Data Science and Computational Intelligence", University of Granada, 18071, Granada, Spain.

³⁾School of Information and Physical Sciences, The University of Newcastle, NSW 2308, Callaghan, Australia.

(*Electronic mail: myfeng@swu.edu.cn)

(Dated: 24 December 2024)

Reputation and punishment are significant guidelines for regulating individual behavior in human society, and those with a good reputation are more likely to be imitated by others. In addition, society imposes varying degrees of punishment for behaviors that harm the interests of groups with different reputations. However, conventional pairwise interaction rules and the punishment mechanism overlook this aspect. Building on this observation, this paper enhances a spatial public goods game in two key ways: 1) We set a reputation threshold and use punishment to regulate the defection behavior of players in low-reputation groups while allowing defection behavior in high-reputation game groups. 2) Differently from pairwise interaction rules, we combine reputation and payoff as the fitness of individuals to ensure that players with both high payoff and reputation have a higher chance of being imitated. Through simulations, we find that a higher reputation threshold, combined with a stringent punishment environment, can substantially enhance the level of cooperation within the population. This mechanism provides deeper insight into the widespread phenomenon of cooperation that emerges among individuals.

In the real world, individual behavioral choices have attracted a large amount of attention. In complex networks, cooperation and defection of nodes reflect real-life behaviors. Edges generate interactions, and spatial public goods games (SPGG) help to understand social choices. Realistic social individuals are more likely to choose bad behaviors due to the high rewards of free-riding behaviors, and reputation and punishment mechanisms are crucial to behavioral regulation. A good reputation leads to trust and cooperation, while a bad reputation leads to isolation. In addition, real societies have an assessment of individual reputations, resulting in different communities and corresponding management systems. This paper explores the evolutionary punishment mechanism of reputation and tolerance, combining reputation and punishment to construct a community mechanism that promotes cooperation, aiming to reveal behavioral patterns and provide guidance for social cooperation.

I. INTRODUCTION

The study of cooperation in biology, sociology, and economics is extensive¹⁻⁶. When confronted with conflicts between individual interests and general interests, the self-ish choices of individuals often clash with the public interests of the group, thereby hindering the emergence of cooperation⁷⁻¹⁰. Consequently, evolutionary game theory has attracted significant attention and extensive research. Prisoner dilemma game (PDG)¹¹⁻¹⁴, snow drift game (SDG)¹⁵⁻¹⁸, and public goods game (PGG)¹⁹⁻²¹ are used to address dilemmas observed in evolutionary games^{22,23}. The resolution of

the social dilemma is noteworthy, with numerous studies proposed to elucidate the emergence of cooperation. For example, Nowak and May²⁴ are the first to show that spatial structure can promote the development of cooperation in the PDG in 1992. Since then, substantial research on cooperative behavior has been carried out in various evolutionary game models, including those based on square grids²⁵, small world networks^{26–29}, scale-free networks^{30–33}, and hypergraphs^{34–36}. Considering that the previously mentioned network models neglect the typical social phenomenon of temporarily offline vertices and the need to account for hidden vertices, as well as the switching of vertex phases between online and hidden states, Zeng's work on temporal network modeling with online and hidden vertices, based on the birth-and-death process, provides a framework for evolutionary games³⁷.

As researchers strive to elucidate the dilemma, various mechanisms that facilitate cooperation are investigated. Nowak³⁸ put forward five cooperative evolutionary rules, namely kin selection, direct reciprocity, indirect selection, group selection, and network reciprocity. Subsequently, with the rapid advancement of social network theory, numerous mechanisms, including rewards^{39,40}, punishment⁴¹, and social exclusion^{42,43} are thoroughly studied in recent decades. For example, Liu incorporates both prosocial and antisocial exclusion strategies related to public pools into the public goods game, examining their effects on cooperation. The findings indicate that social exclusion proves to be more effective in reducing defection and fostering cooperation compared to costly punishment⁴⁴. In addition, Liu demonstrates that unequal status significantly influences cooperative behavior, with smaller nodes more likely to engage in positive cooperation, thus providing a supplementary perspective on the aforementioned mechanisms⁴⁵.

In contrast to biological systems, human societies possess a credit system in which reputation plays a crucial role, particularly in business collaborations. Since Nowak and Sigmund⁴⁶ propose the image-scoring reputation model, reputation-based mechanisms are shown to effectively enhance cooperation in various social dilemmas^{41,47}. In recent years, Xia et al. review the research related to reputation, with a focus on image scores as the bearers of reputation and various forms of reciprocity including direct, indirect, and network reciprocity, demonstrating how these definitions influence the evolution of cooperation in social dilemmas⁴⁸. In the context of cooperation, reputation can influence an individual's behavior and decisions. For example, individuals with a good reputation are more likely to be trusted and cooperate with others^{49,50}. Punishment is also one of the important mechanisms for regulating individual behavior. It is another important aspect of the promotion of cooperation. When individuals face punishment for non-cooperative behavior, they are more likely to choose cooperation 51-53. However, there is no agreed-upon norm for the mechanism of individual punishment. Some studies prove that expensive punishment is not applicable, as well as its role in rewards⁵⁴ and the imposition of antisocial punishment^{55–58}. Furthermore, reputation and punishment mechanisms are confirmed to play a particularly important role in influencing the ability of groups to participate in effective collective actions. For example, Brandt integrates reputation and punishment mechanisms into the PGG. By studying the complex situation of interaction among three individuals, he demonstrates the promoting effects of territoriality, punishment opportunities, and reputation on cooperative behavior. He reveals the interesting phenomenon that less cooperative individuals can create a more cooperative society⁵⁹. Furthermore, Podder finds that choosing social norms that impose more moderate reputation-based punishment will increase cooperation⁴¹. In general, effectively combining these two mechanisms to promote cooperation in groups remains one of the difficulties in current research.

In community development projects, public facility construction projects are similar to PGG. Individuals can choose to cooperate or defect. Due to the high returns brought about by defecting, individuals often tend to choose this option. Several studies show that the addition of punishment or reputation mechanisms can significantly promote the emergence of cooperation. Inspired by the tolerance mechanism for defectors in a harsh environment⁴⁹ and considering community development, if a resident group actively participates in community volunteer services for a long time and has a good reputation, then even if the contribution of individual members is slightly lower than expected, they will not be severely punished. This reflects the concept of tolerance for highreputation groups.

Therefore, this paper focuses on the combination of reputation and punishment mechanisms. We set a reputation threshold for the incorporation of punishment in the SPGG, with a third-party punishment institution showing tolerance to defectors when the average reputation of a game group is above this threshold. Our model has two major improvements: one is a reputation evaluation mechanism that allows individuals in high-reputation groups to defect without corresponding punishment. The second is the use of fitness functions based on reputation.

Simulations in square lattices show that the tolerance and punishment mechanism based on average reputation promotes cooperation. In addition, a larger reputation threshold and punishment can create a better cooperation environment.

The remainder of this paper is organized as follows. The reputation-based tolerant punishment PGG model is elaborated in Section II, including the reputation evolution, punishment, and strategy update rules. Subsequently, the specific process and details of the simulation, along with the results and discussions of the experiment, are presented in Section III. Finally, we summarize the entire context in Section IV.

II. MODEL

A. Spatial public goods game

SPGGs are vital for analyzing the cooperative dilemma present in spatially structured populations. This model involves multiple participants and operates as a two-strategy game. In an SPGG, each player occupies a node in the network and engages with their neighboring participants. Let N(i) denote the set of direct neighbors of the player *i*. At each stage, the player *i* participates in the N(i) + 1 groups of the SPGG simultaneously. One group revolves around the player *i* itself, while the other N(i) groups involve each of its neighboring participants.

In these multi-group games, the individual *i* must decide whether to contribute one unit to the public pool. In each group game, all contributions to the public pool are multiplied by an enhancement factor *r* (r > 1). The resulting total is then equally distributed among all participants in that group. Let s_i denote the strategy chosen by the player *i*. In this framework, the player *i* has two choices: cooperation ($s_i = 1$) or defection ($s_i = 0$). In the *g*-th group game ($1 \le g \le N(i) + 1$, with the set of vertices of this group denoted as G_g), the payoff for player *i* as cooperator, denoted as Π_g^C and as defector, denoted as Π_g^D , is defined as Eq. (1).

$$\begin{cases} \Pi_{g}^{C} = r \frac{(N_{g}^{C}+1)}{|G_{g}|} - 1 \\ & . \\ \Pi_{g}^{D} = r \frac{N_{g}^{C}}{|G_{g}|} \end{cases}$$
(1)

Here, N_g^C indicates the count of cooperators, in addition to player *i*, within their *g*-th group game. Consequently, the total payoff Π_i for individual *i*, who participates in N(i) + 1 group games, can be calculated as $\Pi_i = \sum_{g=1}^{N(i)+1} \Pi_g^{s_i}$.

B. Reputation assessment of the players

We incorporate reputation assessment into the SPGG. In this subsection, all players receive reputation scores over time, $R_i(t)$, based on their actions within the evolutionary game. Additionally, when a player contributes to the public pool, their reputation increases by one unit during that time step. In contrast, if a player does not contribute, their reputation will decrease by one unit, as defined in Eq. (2). For simplicity and to avoid an unbounded increase in individual reputations, we restrict the reputation values to a range of [0, 20]. If a player's reputation surpasses 20, it will be capped at this maximum value. Conversely, if a player's reputation falls below 0, it will be adjusted to remain at 0.

$$R_i(t) = \begin{cases} R_i(t-1) + 1, & \text{if } s_i(t) = 1\\ R_i(t-1) - 1, & \text{if } s_i(t) = 0 \end{cases}.$$
 (2)

C. Punishment based on low reputation individuals of the group

Furthermore, we incorporate a punishment mechanism into the SPGG to encourage cooperation rather than defection. Based on dynamic reputation, each group has a distinct average reputation. We set a reputation threshold R_0 . In the *k*-th group game, if the average reputation of the players is less than R_0 , a third-party institution will punish *b*, being $0 \le b \le 1$, on defectors. Therefore, the benefit function in a low-reputation group changes from Eq. (1) to the following Eq. (3).

$$\begin{cases} \Pi_{g}^{C} = r \frac{(N_{g}^{C}+1)}{|G_{g}|} - 1 \\ & . \\ \Pi_{g}^{D} = r \frac{N_{g}^{C}}{|G_{g}|} - b \end{cases}$$
(3)

D. Strategy evolution

In this way, we take the reputation into account in the update of the strategy. In order to be more in line with real society, we determine that individuals with higher reputation and higher payoff have higher fitness. In the model, individuals with a reputation higher than the reputation threshold will have a higher fitness. In contrast, these individuals with a reputation lower than the reputation threshold will have a lower fitness. We adopt a simple linear weighted method and use a damping factor δ to adjust the relative importance of these two factors. Therefore, we evaluate the fitness of the agent *i* according to Eq. (4).

$$f_i(\Pi_i, R_i) = \delta \Pi_i + (1 - \delta) \frac{R_i - R_0}{\lambda}.$$
 (4)

In this paper, we set λ as the maximum reputation of 20 to ensure that the difference in fitness brought by reputation is fixed between 0 and 1. Next, the probability that agent *i* adopts the strategy of agent *j* in the upcoming round of the game is determined by

$$\Gamma(S_i \to S_j) = \frac{1}{1 + e^{\frac{f_j(\Pi_j R_j) - f_i(\Pi_i R_i)}{\kappa}}}.$$
(5)

Here, $f_j(\Pi_j R_j)$ and $f_i(\Pi_i R_i)$ denote the fitness of player j and player i, respectively. κ ($\kappa > 0$) is a noise parameter that represents the uncertainty in the updating of the strategy. When $\kappa \to 0$, if the player j has a higher fitness, the player i will definitely imitate the player j. When $\kappa \to \infty$, whether the player i imitates the player j is completely random. Based on other scholarly works, we set $\kappa = 0.5$ in this study.



FIG. 1. The node strategy update process in the network. Red nodes represent defectors and blue nodes represent cooperators. (a) All nodes are randomly assigned reputations and strategies. (b) All groups of public goods as circled by the dotted line interact. (c) Punishment is carried out according to the average reputation of the game group and update strategy using Eq. (5). Punishment is implemented within the low-reputation group (red dashed box) but not within the high-reputation group (green dashed box). (d) The network is updated, and the next Monte Carlo step is taken.

To summarize our model process, Fig. 1 illustrates the process in which nodes in the network start from the initial stage. Their reputation is dynamically updated based on individual strategy, and then the average reputation of the game group is calculated to depend on whether to punish the defector. Finally, the strategy is updated in combination with the new fitness function.

III. SIMULATION RESULT AND DISCUSSION

This section presents the evolution of cooperation that uses a tolerant punishment mechanism across various parameter settings.

A. Experimental setup and model parameters

We conducted Monte Carlo simulations on square lattices with periodic boundary conditions, setting $N = 60 \times 60$. The simulation engine was implemented in Python 3.8 within the Anaconda environment. Asynchronous update rules were implemented. Initially, strategies *C* and *D* were assigned to each node with the same probability, and each player's reputation was uniformly distributed within the range of [0,20]. All simulation evolutionary steps are set to $t = 10^4$. For the final results of the evolutionary process, we ensure the accuracy of the data by averaging 20 independent experiments. Our focus is on the average level of cooperation in the population, defined as $\rho_C = \frac{1}{N} \sum_{i=1}^{N} s_i$.

B. Integrating reputation and payoff in fitness function

First, we study the change of cooperation ratio ρ_C with the damping factor δ under a different reputation threshold R_0 to explore how to organically combine reputation and payoff to determine individual fitness, which involves an examination of the evolutionary process of cooperation ratio ρ_C as it progresses toward a stable state over time. As illustrated in Fig. 2, for the cooperation ratio under a different reputation threshold R_0 , when the damping factor δ is relatively small ($\delta < 0.36$), the cooperation ratio is 1 after the evolution reaches a stable state. That is because when ρ_C is relatively small, individual fitness is mainly determined by reputation. Since defection will bring about a reduction in reputation, players will tend to choose cooperation. As time accumulates, cooperators will occupy the entire population.



FIG. 2. Frequency of cooperators ρ_C as a function of damping factor δ for different reputation threshold R_0 . Each data is obtained by averaging the proportion of cooperators in the last 500 iterations after the system reaches evolutionary stability. Note that the more an individual's fitness depends on reputation, the more it promotes the emergence of cooperation.

In addition, as δ increases, the fitness of the individuals will be primarily influenced by the payoffs. It can be found that for different reputation thresholds R_0 , a phase transition from cooperation to defection will occur, which is due to the fact that the high payoff brought about by free-riding behavior is more conducive to the survival of defectors. In particular, when $R_0 = 0$, the cooperation ratio will drop rapidly from 1 to 0. However, when $R_0 = \{4, 8, 12, 16\}$, due to the emergence of punishment, cooperators can stably appear in the population. It should be noted that when cooperation emerges in the population, the higher the reputation threshold R_0 , the higher the cooperation ratio. This reflects that the looser the inclusion condition of punishment is, the more it can promote cooperation. Based on this simulation, we set $\delta = 0.5$ to organically combine reputation and payoff as individual fitness in the following simulations.

C. Influence of enhancement factor and punishment on cooperation

In this section, we analyze the evolution of cooperation under two different reputation thresholds depending on reputation and payoff ($R_0 = 1$ and 4). From Fig. 3, when $R_0=1$, we observe that for some smaller values of b (b = 0, 0.25, 0.5), here r will appear to correspond to a critical value when cooperation arises. When b = 0, the model degenerates into SPGG with only reputation evolution, and our simulation results are similar to those of the previous study⁶⁰. In particular, when r < 2.8, all players decide to defect, and the ratio of cooperation is 0. When r = 2.8, a phase transition takes place, leading to an increase in the proportion of cooperators within the population. As the punishment level b increases, the critical value of r required for this phase transition decreases. Especially, when b = 0.75, the group has a large punishment for the defector.

Therefore, in this environment with a low reputation threshold and high punishment, defectors are unable to survive, and then cooperation is the dominant strategy. Even when the enhancement factor r is 1, defectors are unable to replace cooperators fully in competition with them either. Hence, a phase transition will not occur. For a more in-depth study, we establish a harsher punishment environment ($R_0 = 4$). Through comparison, we find that in this case only when b = 0 will there be a phase transition from defection to cooperation. The result at this time is the same as the result when $(R_0 = 1)$. This is because punishment b = 0. Therefore, regardless of the size of the reputation threshold, there will be no punishment for defectors in the group. When b is equal to 0.25, 0.5, or 0.75, cooperators can survive when r is relatively small, demonstrating that punishment favors cooperation. This shows that punishment under the reputation threshold plays a significant role in the emergence of collective cooperative behavior.

Next, we demonstrate the process of evolution of the cooperation ratio over time under different punishment *b* with a fixed enhancement factor r = 2.5, and in Fig. 4, we compared two different reputation thresholds ($R_0 = 1$ and $R_0 = 4$). This value is extremely representative, since cooperation cannot



FIG. 3. Frequency of cooperators ρ_C as a function of enhancement factor *r* for different punishment of *b*. Each data is obtained by averaging the proportion of cooperators in the last 500 iterations after the system reaches evolutionary stability. Different panels display the cooperation level under different reputation thresholds, as (a) $R_0 = 1$, (b) $R_0 = 4$. The curves show the critical values *r* at which the phase transition from defection to cooperation occurs under different punishment *b*. For instance, the phase transition points for the emergence of cooperation corresponding to b = 0, 0.25, and 0.50 in (a) are r = 1.1, 2.1, and 2.8, respectively.



FIG. 4. Frequency of cooperators ρ_C varies with time for different *b*. Fixed enhancement factor r = 2.5. Different panels display the cooperation level under different reputation thresholds, as (a) $R_0 = 1$, (b) $R_0 = 4$. In different punishment *b*, the system can reach evolutionarily stable in 10⁴ iterations. For *b*=0, 0.25, 0.5, and 0.75, the frequency of cooperators initially declines and then gradually increases towards a dynamically stable and non-zero level, whereas b = 0, the level of cooperation finally drops to zero.

emerge without the introduction of punishment in the SPGG. However, in this model, if reputation and punishment act simultaneously, cooperation can exist under different punishment *b*. As shown in this figure, When in an environment with a relatively large punishment (b = 0.25, 0.50, 0.75), the cooperation ratio first decreases and then gradually increases to a stable value. After about 100 steps, the proportion of cooperators ρ_C in the population does not fluctuate much. This implies that there is intense competition between cooperators and defectors within the population at this time.

However, in the least favorable environment (b = 0), that is, regardless of the reputation threshold, there will be no punishment for defectors in the environment. Eventually, the proportion of cooperation will drop to zero. That is because when b = 0, the game degenerates into a PGG with only a reputation mechanism. At this time, the strategy update rule of the nodes depends on the income difference and their reputation. The income difference becomes the factor that dominates strategy updates so that cooperators will tend to imitate the strategies of defectors, resulting in free-riding behavior and leading to the cooperation proportion dropping to zero. When b = 0.25, 0.50 and 0.75, punishment plays a role in promoting cooperation in the cluster. Therefore, the cooperation level reaches a dynamic equilibrium and is in a mixed state of cooperators and defectors. By comparing these four curves, it can be found that there is a risk of inducing cooperators to be-



FIG. 5. Snapshots of the spatial arrangements of strategies at four representative moments for different reputation thresholds. (a) R_0 = 0; (b) R_0 = 4; (c) R_0 = 12 and (d) R_0 =16 and fixed enhancement factor r = 2.5 and b=0.2. Each row from top to bottom represents a situation corresponding to a different reputation threshold R_0 . Each column from left to right represents a different time step t. White pixels stand for cooperators and blue pixels for defectors. It is noteworthy that defectors can survive in an environment where no punishment is introduced (R_0 = 0). However, in an environment with a higher reputation threshold (R_0 = 4, 12, and 16), after 100 time steps, cooperators gradually gather to form stable clusters. Thus, a strict reputation environment can induce the formation and development of cooperator clusters.

come defectors. Punishment below the reputation threshold can maintain the proportion of cooperation at a medium level. In addition, in the groups with the highest punishment *b*, cooperators have more advantages. This consolidates the conclusion in Fig. 1 that the greater the punishment, the more it can promote cooperation in SPGG. Moreover, by comparing the cooperation evolution with different reputation thresholds $(R_0 = 1 \text{ and } R_0 = 4)$, it can be found that a higher reputation threshold $(R_0 = 4)$ leads to a stricter environment of punishment, that is, in the case of the same punishment *b*, a higher reputation threshold results in a wider range of punishment, thereby enhancing the survival of cooperators, which is consistent with the result shown in Fig. 3.

D. Evolution of strategy and reputation on the lattice

To gain deeper insights into the emergence of cooperation and the formation of cooperative clusters in space, we analyze the spatial distribution of defectors and cooperators as shown



FIG. 6. Snapshots of the spatial distributions of individuals' reputation at four representative moments for different reputation thresholds. (a) $R_0 = 0$; (b) $R_0 = 4$; (c) $R_0 = 12$ and (d) $R_0 = 16$. Fixed enhancement factor r = 2.5 and b = 0.2. From top to bottom, each row corresponds to a situation with a different reputation threshold R_0 . From left to right, each column represents a different time step *t*. The color bar shows the reputation values corresponding to different colors. It should be noted that the reputation distribution snapshots are not entirely in line with the strategy distribution snapshots in Fig. 5 because the reputation evaluation criteria vary under different reputation thresholds.

in Fig. 5. This figure illustrates the evolutionary dynamics of the spatio-temporal distribution of both strategies at different time intervals. At the beginning ($t \le 100$), the node strategies are randomly distributed. We observe that only a small number of nodes are clustered. This is possibly due to the random distribution of node strategies and reputations, which means that cooperators are unable to identify defectors well in the group. Therefore, cooperators find it difficult to resist the

invasion of defectors, causing defectors to occupy the most population. As time passes, the role of reputation and punishment becomes more and more obvious, providing a good environment for the survival of cooperators.

In the dual mechanism of reputation and punishment ($R_0 = 4, 12, 16$), as the simulation evolves, the role of reputation and punishment becomes more and more obvious, providing a good environment for the survival of cooperators. With





FIG. 7. Heatmap of cooperation under different reputation thresholds. Different panels display the cooperation level under different reputation thresholds, as (a) $R_0 = 1$, (b) $R_0 = 4$. The density ρ_C of cooperators is shown in the r - b parameter plane. The legend on the right side of the panel explains the meaning of colors. The value of the cooperation level ρ_C is the average of the last 500 steps obtained through 10,000 MC steps. It is generally the case that when we increase the factor r or penalty b simultaneously, the level of cooperation will also increase correspondingly. However, when r reaches a certain threshold, regardless of how large the punishment b is, pure cooperation will appear in the entire population.

the survival of the cooperators, the remaining cooperators form clusters to resist the invasion of defectors. At time step t = 10000, cooperators will dominate, especially when $R_0 = 16$, cooperators will completely replace defectors. However, when $R_0 = 0$, at this time, the average reputation of all groups will be higher than this reputation threshold, resulting in the inability to incorporate punishment. Therefore, cooperators cannot resist the invasion of defectors, and thus there is the behavior of all players free-riding in the end. The results indicate that a lenient environment is not suitable for facilitating cooperation or resisting the invasion of defectors. Eventually, cooperators in the population completely disappear. In contrast, a strict environment, that is, the higher the reputation threshold, the more it can promote the emergence of cooperation.

Similarly, based on the snapshots of strategies shown in Fig. 5, we have represented snapshots of individual reputation distributions in Fig. 6 to more thoroughly study the influence of reputation on the evolutionary game. In various scenarios, initial node reputation distributions are uniformly distributed within the range of [0, 20]. As demonstrated in Fig. 6, in groups where reputation and punishment act in concert ($R_0 = 4, 12$), at t = 100 individuals with high reputation will gradually emerge. Thus, a player with high reputation will exert an impact on the strategy update of those with low reputation, making the latter more inclined to learn the cooperative strategy of the former, thus leading to an increase in their own reputation. Consequently, at t = 10000, individuals with high reputation will gradually form groups, thus resisting the invasion of the defection strategy of individuals with low reputation, and the phenomenon of high reputation being

surrounded by low reputation will occur.

It should be noted that when $R_0 = 0$, the snapshot of the reputation evolves to pure blue, which means that the reputation corresponding to its players is the lowest reputation. This is because players in the group will adopt the more profitable defection behavior because they will not be punished for defection, resulting in all players in the group choosing to defect, thus low-reputation individuals occupying the entire population. However, when $R_0 = 16$, At t = 100, a large number of players with a high reputation will occupy the entire population. At t = 10000, they will completely occupy it. This is because when the reputation threshold is set too high, it will severely crack down on most defecting individuals. As a result, the group is more inclined to choose the cooperative strategy. Moreover, due to cooperation, the reputation of players accumulates rapidly. Thus, high-reputation players become part of the entire population.

E. Impact of reputation-punishment synergy on cooperation

Finally, as illustrated in Fig. 7, we study how the level of cooperation changes by varying the main parameters of the model (the enhancement factor r and the punishment b) under the extended model of cluster reputation punishment. To gain a generally valid observation on the behavior of the system, we present the results obtained simultaneously under different reputation thresholds ($R_0 = 1$ and 4). Under both reputation thresholds, the density of cooperation increases as the parameter r or b increases. Within the explored range of pa-

rameters, regions of pure cooperation and pure defection are observed. In general, higher values of r and b lead to a higher likelihood of cooperation, while lower values are associated with an increase in defection. Moreover, when the enhancement factor r reaches a certain threshold, a pure cooperation region emerges, regardless of the magnitude of the third party punishment b. In addition, when r is sufficiently large, the proportion of cooperators in the system changes less significantly with increasing b. This can be attributed to the increase in r, which leads to a significant growth in the payoffs of both cooperators and defectors. Consequently, the impact of the payoff difference caused by punishment on the change in the proportion of cooperation is reduced. In this kind of SPGG with high benefits, players are more inclined to choose the cooperation strategy. By comparing the heatmaps with two different reputation thresholds, it can be observed that when $R_0 = 4$, which corresponds to a higher reputation threshold, the cooperative region is larger than that of a lower reputation threshold ($R_0 = 1$). Similarly, the defective region is also smaller. This further confirms the synergistic effect of reputation and punishment in promoting cooperation in grid networks. This aligns with the theoretical expectations of the extended public goods game presented in the paper.

IV. CONCLUSIONS AND OUTLOOK

In this paper, we enhance the existing SPGG from two perspectives. First, we consider the average reputation of the game group and the reputation threshold in reputation evolution to determine punishment. Second, we assume that players with high payoff and reputation have a higher probability of learning strategies. Therefore, the paper combines reputation and punishment to jointly construct the player fitness function and extends the individuals with a higher reputation threshold who are fitter to the traditional strategy update. A reputation threshold was included into the model to distinguish between the high-reputation and low-reputation groups of the game, thus determining whether to punish during the game interaction process.

We have examined the effects of an enhanced reputation threshold in SPGG, along with a punishment mechanism that incorporates tolerance and strategy learning influenced by both income and reputation on the evolution of cooperation. Our simulations demonstrated that incorporating reputation into the fitness function is crucial to fostering cooperation, particularly in stringent environments. Generally, imitation based on income and reputation, combined with a rigorous reputation evaluation framework, supports the sustainable survival of cooperators. This mechanism provides valuable information on the ubiquitous phenomenon of cooperation within social systems.

There are still many shortcomings in our model that need to be improved. For example, when making the decision on whether to punish or not, the reputation threshold in our model is fixed for all game groups. This fact simplifies real situations, more complex in general. In addition, when constructing the fitness function using payoff and reputation, we use a simple linear function to combine both reputation and payoff. Other extensions can also be used in more in-depth research on the evolution of cooperation in SPGG. For example, certain rewards can be given for cooperative behaviors in low-reputation groups. Punishment and reward values can be linked to individual reputations rather than a fixed value.

ACKNOWLEDGEMENTS

Gui Zhang, Y. Yao, Z. Zeng and M. Feng are supported by grant No. 62206230 funded by the National Natural Science Foundation of China (NSFC), and grant No. CSTB2023NSCQ-MSX0064 funded by the Natural Science Foundation of Chongqing. M. Chica is supported by EMER-GIA21_00139, granted by Consejería de Universidad, Investigación e Innovación of the Andalusian Government.

- ²Joel L Sachs, Ulrich G Mueller, Thomas P Wilcox, and James J Bull. The evolution of cooperation. *The Quarterly review of biology*, 79(2):135–160, 2004.
- ³Marco Archetti, István Scheuring, Moshe Hoffman, Megan E Frederickson, Naomi E Pierce, and Douglas W Yu. Economic game theory for mutualism and cooperation. *Ecology letters*, 14(12):1300–1312, 2011.
- ⁴Robert Axelrod. The emergence of cooperation among egoists. *American political science review*, 75(2):306–318, 1981.
- ⁵Minyu Feng, Ziyan Zeng, Qin Li, Matjaž Perc, and Jürgen Kurths. Information dynamics in evolving networks based on the birth-death process: Random drift and natural selection perspective. *IEEE Transactions on Systems, Man, and Cybernetics: Systems*, 2024.
- ⁶Xiaopeng Li, Zhonglin Wang, Yan Xu, Hui Zhang, and Guihai Yu. Asymmetrical interactions driven by strategic persistence effectively alleviate social dilemmas. *Chaos, Solitons & Fractals*, 184:115054, 2024.
- ⁷Stuart A Ludsin and Andrea D Wolfe. Biological invasion theory: Darwin's contributions from the origin of species. *Bioscience*, 51(9):780–789, 2001.
 ⁸Oliver P Hauser, David G Rand, Alexander Peysakhovich, and Martin A
- ⁹David G Rand and Martin A Nowak. Human cooperation. *Trends in cog-*
- nitive sciences, 17(8):413–425, 2013.
- ¹⁰Tim Clutton-Brock. Cooperation between non-kin in animal societies. *Nature*, 462(7269):51–57, 2009.
- ¹¹Ziyan Zeng, Qin Li, and Minyu Feng. Spatial evolution of cooperation with variable payoffs. *Chaos: An Interdisciplinary Journal of Nonlinear Science*, 32(7), 2022.
- ¹²Zhengzhi Yang, Lei Zheng, Matjaž Perc, and Yumeng Li. Interaction state q-learning promotes cooperation in the spatial prisoner's dilemma game. *Applied Mathematics and Computation*, 463:128364, 2024.
- ¹³Yao Zhang, Qing-Yi Hao, Jia-Li Qian, Chao-Yun Wu, Ning Guo, and Xiang Ling. The cooperative evolution in the spatial prisoner's dilemma game with the local loyalty of two-strategy. *Applied Mathematics and Computation*, 466:128484, 2024.
- ¹⁴Danyang Jia, Chen Shen, Xiangfeng Dai, Xinyu Wang, Junliang Xing, Pin Tao, Yuanchun Shi, and Zhen Wang. Freedom of choice disrupts cyclic dominance but maintains cooperation in voluntary prisoner's dilemma game. *Knowledge-Based Systems*, page 111962, 2024.
- ¹⁵Si-Ping Zhang, Ji-Qiang Zhang, Li Chen, and Xu-Dong Liu. Oscillatory evolution of collective behavior in evolutionary games played with reinforcement learning. *Nonlinear Dynamics*, 99(4):3301–3312, 2020.
- ¹⁶Christoph Hauert and Michael Doebeli. Spatial structure often inhibits the evolution of cooperation in the snowdrift game. *Nature*, 428(6983):643– 646, 2004.
- ¹⁷Max O Souza, Jorge M Pacheco, and Francisco C Santos. Evolution of cooperation under n-person snowdrift games. *Journal of Theoretical Biology*, 260(4):581–588, 2009.

¹Matjaž Perc. Phase transitions in models of human cooperation. *Physics Letters A*, 380(36):2803–2808, 2016.

- ¹⁸Yuying Zhu, Jianlei Zhang, Qinglin Sun, and Zengqiang Chen. Evolutionary dynamics of strategies for threshold snowdrift games on complex networks. *Knowledge-Based Systems*, 130:51–61, 2017.
- ¹⁹Tianyi Li and Charles N Noussair. Conditional cooperation and group size: experimental evidence from a public good game. *Journal of the Economic Science Association*, 10(1):98–112, 2024.
- ²⁰Francisco C Santos, Marta D Santos, and Jorge M Pacheco. Social diversity promotes the emergence of cooperation in public goods games. *Nature*, 454 (7201):213–216, 2008.
- ²¹Christoph Hauert, Silvia De Monte, Josef Hofbauer, and Karl Sigmund. Volunteering as red queen mechanism for cooperation in public goods games. *Science*, 296(5570):1129–1132, 2002.
- ²²Herbert Gintis. Game theory evolving: A problem-centered introduction to modeling strategic behavior. Princeton university press, 2000.
- ²³Matjaž Perc and Attila Szolnoki. Coevolutionary games—a mini review. *BioSystems*, 99(2):109–125, 2010.
- ²⁴Martin A Nowak and Robert M May. Evolutionary games and spatial chaos. *nature*, 359(6398):826–829, 1992.
- ²⁵Xiaopeng Li, Gang Hao, Zhipeng Zhang, and Chengyi Xia. Evolution of cooperation in heterogeneously stochastic interactions. *Chaos, Solitons & Fractals*, 150:111186, 2021.
- ²⁶Xiao-Heng Deng, Yi Liu, and Zhi-Gang Chen. Memory-based evolutionary game on small-world network with tunable heterogeneity. *Physica A: Statistical Mechanics and its Applications*, 389(22):5173–5181, 2010.
- ²⁷Feng Fu, L-H Liu, and Long Wang. Evolutionary prisoner's dilemma on heterogeneous newman-watts small-world network. *The European Physical Journal B*, 56:367–372, 2007.
- ²⁸Naoki Masuda and Kazuyuki Aihara. Spatial prisoner's dilemma optimally played in small-world networks. *Physics Letters A*, 313(1-2):55–61, 2003.
- ²⁹György Szabó and Gabor Fath. Evolutionary games on graphs. *Physics reports*, 446(4-6):97–216, 2007.
- ³⁰Kaj-Kolja Kleineberg. Metric clusters in evolutionary games on scale-free networks. *Nature communications*, 8(1):1888, 2017.
- ³¹Zhi-Xi Wu, Jian-Yue Guan, Xin-Jian Xu, and Ying-Hai Wang. Evolutionary prisoner's dilemma game on barabási–albert scale-free networks. *Physica* A: Statistical Mechanics and its Applications, 379(2):672–680, 2007.
- ³²Martin A Nowak and Karl Sigmund. Evolutionary dynamics of biological games. *science*, 303(5659):793–799, 2004.
- ³³Hongyan Dui, Xueyu Meng, Hui Xiao, and Jianjun Guo. Analysis of the cascading failure for scale-free networks based on a multi-strategy evolutionary game. *Reliability Engineering & System Safety*, 199:106919, 2020.
- ³⁴Andrea Civilini, Nejat Anbarci, and Vito Latora. Evolutionary game model of group choice dilemmas on hypergraphs. *Physical Review Letters*, 127 (26):268301, 2021.
- ³⁵Dini Wang, Peng Yi, Yiguang Hong, Jie Chen, and Gang Yan. Evolutionary game on any hypergraph. arXiv preprint arXiv:2404.03305, 2024.
- ³⁶Yan Xu, Juan Wang, Jiaxing Chen, Dawei Zhao, Mahmut Özer, Chengyi Xia, and Matjaž Perc. Reinforcement learning and collective cooperation on higher-order networks. *Knowledge-Based Systems*, 301:112326, 2024.
- ³⁷Ziyan Zeng, Minyu Feng, and Jürgen Kurths. Temporal network modeling with online and hidden vertices based on the birth and death process. *Applied Mathematical Modelling*, 122:151–166, 2023.
- ³⁸Martin A Nowak. Five rules for the evolution of cooperation. *science*, 314 (5805):1560–1563, 2006.
- ³⁹Shashank Motepalli and Hans-Arno Jacobsen. Reward mechanism for blockchains using evolutionary game theory. In 2021 3rd Conference on Blockchain Research & Applications for Innovative Networks and Services (BRAINS), pages 217–224. IEEE, 2021.

- ⁴⁰Attila Szolnoki and Matjaz Perc. Reward and cooperation in the spatial public goods game. *Europhysics Letters*, 92(3):38003, 2010.
- ⁴¹Shirsendu Podder, Simone Righi, and Francesca Pancotto. Reputation and punishment sustain cooperation in the optional public goods game. *Philo-sophical Transactions of the Royal Society B*, 376(1838):20200293, 2021.
- ⁴²Attila Szolnoki and Xiaojie Chen. Alliance formation with exclusion in the spatial public goods game. *Physical Review E*, 95(5):052316, 2017.
- ⁴³Linjie Liu, Xiaojie Chen, and Matjaž Perc. Evolutionary dynamics of cooperation in the public goods game with pool exclusion strategies. *Nonlinear Dynamics*, 97:749–766, 2019.
- ⁴⁴Linjie Liu and Xiaojie Chen. Evolutionary game dynamics in multiagent systems with prosocial and antisocial exclusion strategies. *Knowledge-Based Systems*, 188:104835, 2020.
- ⁴⁵Mengmeng Liu, Yinghong Ma, Le Song, and Changyu Liu. Understanding the game behavior with sentiment and unequal status in cooperation network. *Knowledge-Based Systems*, 212:106588, 2021.
- ⁴⁶Martin A Nowak and Karl Sigmund. Evolution of indirect reciprocity by image scoring. *Nature*, 393(6685):573–577, 1998.
- ⁴⁷Manfred Milinski, Dirk Semmann, and Hans-Jürgen Krambeck. Reputation helps solve the 'tragedy of the commons'. *Nature*, 415(6870):424–426, 2002.
- ⁴⁸Chengyi Xia, Juan Wang, Matjaž Perc, and Zhen Wang. Reputation and reciprocity. *Physics of life reviews*, 46:8–45, 2023.
- ⁴⁹Ji Quan, Caixia Tang, Yawen Zhou, Xianjia Wang, and Jian-Bo Yang. Reputation evaluation with tolerance and reputation-dependent imitation on cooperation in spatial public goods game. *Chaos, Solitons & Fractals*, 131: 109517, 2020.
- ⁵⁰Kehuan Feng, Songlin Han, Minyu Feng, and Attila Szolnoki. An evolutionary game with reputation-based imitation-mutation dynamics. *Applied Mathematics and Computation*, 472:128618, 2024.
- ⁵¹Toshio Yamagishi. The provision of a sanctioning system as a public good. Journal of Personality and social Psychology, 51(1):110, 1986.
- ⁵²Elinor Ostrom, James Walker, and Roy Gardner. Covenants with and without a sword: Self-governance is possible. *American political science Review*, 86(2):404–417, 1992.
- ⁵³Ernst Fehr and Simon Gächter. Cooperation and punishment in public goods experiments. *American Economic Review*, 90(4):980–994, 2000.
- ⁵⁴David G Rand, Anna Dreber, Tore Ellingsen, Drew Fudenberg, and Martin A Nowak. Positive interactions promote public cooperation. *Science*, 325(5945):1272–1275, 2009.
- ⁵⁵Benedikt Herrmann, Christian Thoni, and Simon Gachter. Antisocial punishment across societies. *Science*, 319(5868):1362–1367, 2008.
- ⁵⁶David G Rand, Joseph J Armao IV, Mayuko Nakamaru, and Hisashi Ohtsuki. Anti-social punishment can prevent the co-evolution of punishment and cooperation. *Journal of theoretical biology*, 265(4):624–632, 2010.
- ⁵⁷Simon Gächter and Benedikt Herrmann. The limits of self-governance when cooperators get punished: Experimental evidence from urban and rural russia. *European economic review*, 55(2):193–210, 2011.
- ⁵⁸David G Rand and Martin A Nowak. The evolution of antisocial punishment in optional public goods games. *Nature communications*, 2(1):434, 2011.
- ⁵⁹Hannelore Brandt, Christoph Hauert, and Karl Sigmund. Punishment and reputation in spatial public goods games. *Proceedings of the royal society* of London. Series B: biological sciences, 270(1519):1099–1104, 2003.
- ⁶⁰Attila Szolnoki, Matjaž Perc, and György Szabó. Topology-independent impact of noise on cooperation in spatial public goods games. *Physical Review E—Statistical, Nonlinear, and Soft Matter Physics*, 80(5):056109, 2009.