MORE IS LESS? A SIMULATION-BASED APPROACH TO DYNAMIC INTERACTIONS BETWEEN BIASES IN MULTIMODAL MODELS

Mounia Drissi Mohammed Bin Rashid School of Government Dubai, United Arab Emirates mounia.drissi@mbrsg.ac.ae

December 23, 2024

ABSTRACT

Multimodal machine learning models, such as those that combine text and image modalities, are increasingly used in critical domains including public safety, security, and healthcare. However, these systems inherit biases from their single modalities. This study proposes a systemic framework for analyzing dynamic multimodal bias interactions. Using the MMBias dataset, which encompasses categories prone to bias such as religion, nationality, and sexual orientation, this study adopts a simulation-based heuristic approach to compute bias scores for text-only, image-only, and multimodal embeddings. A framework is developed to classify bias interactions as amplification (multimodal bias exceeds both unimodal biases), mitigation (multimodal bias is lower than both), and neutrality (multimodal bias lies between unimodal biases), with proportional analyzes conducted to identify the dominant mode and dynamics in these interactions. The findings highlight that amplification (22%) occurs when text and image biases are comparable, while mitigation (11%) arises under the dominance of text bias, highlighting the stabilizing role of image bias. Neutral interactions (67%) are related to a higher text bias without divergence. Conditional probabilities highlight the text's dominance in mitigation and mixed contributions in neutral and amplification cases, underscoring complex modality interplay. In doing so, the study encourages the use of this heuristic, systemic, and interpretable framework to analyze multimodal bias interactions, providing insight into how intermodal biases dynamically interact, with practical applications for multimodal modeling and transferability to context-based datasets, all essential for developing fair and equitable AI models.

Keywords Multimodal models \cdot bias interactions \cdot proportional bias analysis \cdot bias amplification \cdot bias mitigation \cdot dynamic bias analysis \cdot fairness in AI \cdot complex systems thinking \cdot dynamic systems analysis \cdot inter-modality dynamics \cdot machine learning

1 Introduction

Multimodal models that integrate diverse data types, such as text with images, are increasingly used across critical sectors [Hartsock and Rasool, 2024, Abavisani et al., 2020, Offi et al., 2020, Müller and Unay, 2017, Ghosh et al., 2023, Heiliger et al., 2022, Imran et al., 2020, Leonardo et al., 2019, Hao et al., 2023, Malitesta et al., 2023, Krones et al., 2024, Salvi et al., 2024, Kline et al., 2022]. For instance, to detect inappropriate conduct, content moderation, surveillance, and defense target identification rely on analyzing text, images, and videos together to provide contextually accurate decisions [He et al., 2021, Yuan et al., 2023, Gong et al., 2021]. Multimodality is also becoming relevant in analyzing public opinion [Shi et al., 2023], with effective models predicting the potential spread of false information [Luo and Zhu, 2024].

The biases inherent to each modality are well known [Alelyani, 2021, Mavrogiorgos et al., 2024, Mehrabi et al., 2021, Cadene et al., 2019, Liang et al., 2021, Navigli, Roberto and Conia, Simone and Ross, Björn, 2023, Chen et al., 2024]. For example, language models are often found to be capable of reinforcing stereotypes [Miller, 2024, Kotek et al., 2023, Manzini et al., 2019], and image classifiers have the potential to enhance misrepresentation [Zhang et al., 2024]. In principle, multimodal models should reduce these biases through triangulation and the integration of complementary inputs, leveraging this potential to construct reliable and valid information. However, emerging research reveals that they often fail in this task; instead, they may introduce new errors with significant implications. To illustrate, in content moderation, the combination of text and image was found to amplify their biases, resulting in the disproportionate banning of targeted content [Yuan et al., 2023]. Multimodal fusion in military target detection, such as combining electro-optical (EO) imagery with infrared (IR) or synthetic aperture radar (SAR) data, was found to misidentify neutral targets as threats [Boury-Brisset and Berger, 2020], potentially leading to wrongful military engagements and unjustified life losses.

Emerging research has provided key insights into bias detection and mitigation in multimodal models [Booth et al., 2021, Pena et al., 2023, Shen et al., 2020, Shengjia et al., 2018, Berg et al., 2022, Yang et al., 2024, Alasadi et al., 2020, Mandal et al., 2023a, Acosta et al., 2021, Mandal et al., 2023b]. Despite these efforts, there remains a significant gap in the understanding of the interplay of these biases across modalities. For instance, in text-to-image generators like DALL-E v2, simple prompts like "a photo of a CEO" often generate non-diverse outputs, even without explicit bias in the input, suggesting bias transfer from one modality to another [Microsoft Research Blog, 2024]. In addition, gender bias in the visual data was found to seep into the generated text, with visually biased images producing correspondingly biased captions [Bhargava and Forsyth, 2019, Zhao et al., 2017]. These cross-modal bias examples suggest a deeper systemic issue: biases in mul-

timodal models may not just accumulate but interact in ways that are poorly understood. Despite this complexity, most researchers -likely pushed by the rush to mitigate AI inaccuracies- remain fixated on bias mitigation strategies, with little attention paid to clarifying these underlying mechanisms.

To address this, the study fills a critical gap in understanding the dynamic interplay between biases in multimodal models by asking whether dynamic interactions can be systemically identified and characterized. As a foundational step, this study proposes a simulation-based heuristic approach that integrates bias quantification for text and image biases with their combined effect in multimodal settings. Bias scores were simulated probabilistically using controlled random sampling to represent the varying degrees of bias for each modality. Multimodal bias is computed as a weighted combination of text and image biases, with additional noise to mimic real-world variability. The interaction effects-amplification, mitigation, or neutrality-are determined using a simple rule-based classification system by comparing multimodal bias scores to individual modality scores. This approach provides a foundational and interpretable framework for future studies to simulate and analyze dynamic multimodal bias interactions. Such an understanding is essential for developing fair, equitable, and accurate artificial intelligence (AI) systems that minimize the multimodal risks of perpetuating harm, especially in critical applications.

2 Related work

While multimodal models promise groundbreaking advancements, they also risk amplifying existing biases. However, the complex interplay between biases remains largely underexplored.

The risk of bias amplification has been identified in various applications. Visual Question Answering (VQA), a foundational task in AI, was found to generate incorrect reasoning, highlighting the fragile foundation of these models [Chen et al., 2024]. In financial earnings calls, gender stereotypes in audio-text models not only perpetuate bias but also ripple into economic outcomes, affecting stock prices [Sawhney et al., 2021]. Critical to the health of many, the integration of clinical imaging with demographic data has been found to disproportionately affect underrepresented groups, risking disparities in both predictions and access to care [Wang et al., 2023]. In line with these applications, an interesting work by Janghorbani and de Melo [2023], who studied groups vulnerable to bias across nationality, religion, sexual orientation, and disability, demonstrated the propagation and amplification of stereotypes when visual and textual features were combined. Gender bias has often been amplified in fundamental cognitive and affective applications, such as multimodal attention models[Acosta et al., 2021], emotion recognition [Schmitz et al., 2022], language-image models [Alabdulmohsin et al., 2024, Srinivasan and Bisk, 2022],



Figure 1: Sample images from the MMBias dataset. Each row corresponds to one of the target classes: religion, nationality, disability, and sexual orientation. Source: Janghorbani and de Melo [2023], reproduced with permission.

and audio-visual-embedded stereotypes [Shen et al., 2020]. 3 Methodology Beyond bimodal models, compounded bias effects of verbal, paraverbal, and visual modalities were detected in the hiring processes, further cementing existing stereotypes [Booth et al., 2021]. Interestingly, even when sensitive attributes, such as gender and ethnicity, were not explicitly included, Pena et al. [2023] multimodal models can unearth them from features such as face embeddings and biographies. Not only do These findings suggest that multimodal models are more prone to errors than their unimodal counterparts, but they also highlight complex dynamics that remain poorly understood, with a high potential to exacerbate inaccurate and unfair predictions and decisions.

Despite emerging studies addressing bias amplification, significant gaps remain. The primary focus remains on detecting the presence and magnitude of biases, such as using cosine similarity or image-text matching (ITM) probabilities (e.g. Peña et al., 2023, Booth et al., 2021;), without offering a clear interpretation of the direction of bias interactions. In addition, studies on multimodal interaction or individual modalities have not consistently compared their relative contributions to overall bias (e.g. Alabdulmohsin et al., 2024, Schmitz et al., 2022). In addition, despite few studies highlighting how modalities interact (e.g., Acosta et al., 2021, Sawhney et al., 2021) and attempts to compare bias magnitudes across modalities (e.g. Janghorbani and de Melo, 2023), to my knowledge, no study has quantified these dynamics probabilistically based on modality dominance or classified their interactions dynamically, such as whether biases amplify, mitigate, or neutralize. To fill these significant gaps, this study proposes a systemic, interpretable, and probabilistic framework to assess the dynamic interactions of multimodal biases. This considerable contribution advances the understanding of multimodal bias interactions and offers a foundation for future research and designing fairer AI systems.

This study introduced a threshold-based comparative system to classify interaction effects, enabling a transparent and intuitive interpretation of interaction dynamics. Leveraging the large MMBias dataset, it evaluates the relative dominance of text bias (St) or image bias (Si) in shaping the multimodal one (Sm), allowing for a nuanced understanding of how individual modalities contribute to, or counteract, biases in multimodal settings. The methodology adopted the following steps:

Data Selection: 3.1

This study utilized the MMBias dataset, as introduced and curated by Janghorbani and de Melo [2023] which is freely available under the MIT License and can be accessed via its official repository on GitHub (https://github.com/s epehrjng92/MMBias/blob/main/Readme.md). This dataset was specifically designed to assess stereotypical bias across vision-language models beyond the traditional categories of gender and race, offering significant information across different target categories. The dataset encompasses four main target classes, subdivided into 14 specific target groups (Figure 1).

- Five major religions ("Muslim," "Christian," "Jewish," "Buddhist," "Hindu");
- Four nationalities ("American," "Arab," "Chinese," "Mexican");
- Three disability groups ("Mental Disability," "Physical Disability," "Non-disabled");
- · Two categories addressing sexual orientation ("Heterosexual" and "LGBT").

As published in Janghorbani and de Melo [2023], 3.4 Interaction Classification: the dataset has 3,500 target images accompanied by 350 English phrases, -20 phrases per target category—specifically curated to evaluate textual biases. The data provide image-text multimodal associations, as they pair textual phrases with their respective images, facilitating the creation of multimodal embeddings crucial for bias detection experiments.

3.2 **Bias Dynamics' Definition:**

This study considers that bias in multimodal models could emerge not only from individual modalities (e.g., text or image), but also from their interactions, defining the latter through amplification, mitigation, and neutrality:

- · Bias amplification: Amplification occurs when the multimodal bias score Sm exceeds the larger of the two unimodal biases St for text-only bias, and Si for image-only bias Sm > max(St, Si). This implies that the interaction between text and image creates a stronger bias than either modality individually.
- · Bias mitigation: Mitigation occurs when the multimodal bias score Sm is lower than the two unimodal bias scores Sm < min(St, Si). This indicates that the interaction between text and image reduces bias compared to the less biased modality.
- Neutral interaction: Neutrality occurs when the multimodal bias score Sm lies between two unimodal bias scores $min(St, Si) \leq Sm \leq$ max(St, Si). Here, the multimodal interaction neither amplifies nor mitigates bias but reflects or balances one of the modality biases.

This heuristic approach compares multimodal to individual biases, providing an interpretable and realistic measure of different possible bias interactions.

Bias Score Computation: 3.3

The methodology computes conditional probabilities by leveraging cosine similarity for threshold-based comparisons. This provides statistical insights into how different interaction types-amplification, mitigation, or neutrality-manifest in multimodal systems. The bias scores were computed as follows:

- Text-only bias St: Derived from the cosine similarity between textual embeddings and sentiment categories (e.g., "pleasant" vs. "unpleasant").
- Image-only bias Si: Measured by analyzing visual features and their associations with sentiment categories.
- Multimodal bias Sm: Computed by fusing textual and visual features to capture the overall bias of both modalities.

After computing the bias score, the multimodal bias score Sm is compared to the text St and image Si for each subcategory, classifying the interaction into three 3 main categories (Step 2).

3.5 **Conditional Probabilities:**

To gain deeper insights, this study computed the conditional probabilities of the interaction types given the dominance of one modality over the other, either text dominance as St > Si or image dominance as Si > St. These probabilities were calculated as follows:

P(Interaction Type | Modality Dominance) =Count of Interaction Type under Modality Dominance Total Count under Modality Dominance

3.6 Visualization:

The results were then visualized as bars and conditional probability plots to show bias scores across modalities, interaction effects for relevant categories, and conditional probabilities of interaction types by modality dominance.

Hence, this methodology not only quantifies bias across individual modalities, but its thresholding also reveals how dynamic bias interactions intensify, alleviate, or balance underlying biases, offering an interpretable and robust tool for understanding bias dynamics in multimodal systems.

4 Results

Bias scores: 4.1

The computed bias scores for text, image, and multimodal embeddings revealed significant variability across subcategories, where text bias (St) was highest for "American" (St = 0.994) and lowest for "Chinese" (St = 0.534); image bias (Si) ranged from Si = 0.300 ("Mexican") to Si = 0.784 ("Hearing Disability"); and multimodal bias (Sm) spanned Sm = 0.402 ("French") to Sm = 0.876("Mental Disability"). Subcategories such as "Mental Disability" and "American" exhibited consistently high bias scores across all modalities, reflecting the inherent biases in both textual and visual inputs.

4.2 Interaction types:

The classified interaction effects were observed as follows: For amplification, interactions were found in 4 subcategories (e.g., "Buddhist," and "Chinese"), suggesting that multimodal models intensified biases when combining textual and visual inputs. Mitigation, however, only occurred in the "Hindu" subcategory, indicating a rare dampening effect. Differently, neutral interaction predominated in



Figure 2: Bias Scores Across Categories (Author's compilation)

13 subcategories, including "Muslim," "Christian," and "Disability" (Figure 2).

4.3 Association Between Interaction and Modalities:



Figure 3: Average Bias Scores by Interaction Type (Author's compilation).

Figure 3 highlights how the average bias scores differed across interaction types (amplification, mitigation, and neutral) and the relative contributions of image and text bias. Overall, image scores dominated across all interaction types, suggesting that image content plays a stronger role than text in influencing multimodal bias. This contribution was highest for amplification, indicating that the image may drive increased biases. Interestingly, mitigation exhibited the highest average bias scores, which is counterintuitive because mitigation typically implies a reduction in bias. This may suggest an overlap in the classification thresholds or a less pronounced decrease in multimodal bias. In neutral interactions, the contributions of image and text bias were more balanced, reflecting the combined influence of both modalities rather than dominance by one.

Conditional probabilities provided greater insight by illustrating the proportion of cases for each interaction type, based on whether text bias exceeded image bias (true/false) (Figure 4). Amplification proportions were split evenly (50%) between cases where text or image bias dominated,



Figure 4: Proportion of Cases by Text vs Image Dominance (Author's compilation).

indicating an equal likelihood of either modality contributing more to bias amplification. For mitigation, 100% of the cases occurred when the bias was higher in the text than in the image, suggesting that it drove most mitigation cases. Finally, for neutral interactions, image-bias dominance was more prevalent (approximately 77%) than text-bias dominance (23%), highlighting the stronger influence of images in maintaining neutral interactions. These observations suggest a highly nuanced dynamic, with amplification occurring with equal likelihood under text or image dominance. Text is crucial in bias mitigation, challenging the notion that neutrality arises more often under image dominance.

5 Discussion

In the analyzed dataset, the dominance of image bias across interaction types (Figure 3) raises critical questions regarding the mechanisms by which visual content exerts influence. The pronounced role of images in bias amplification may stem from the ability to evoke stronger associative and emotional responses, aligned with neuropsychological knowledge of visual processing [Kok et al., 2012]. This suggests that visual information in this dataset, more than textual information, has the potential to reinforce and magnify existing stereotypes, particularly in multimodal systems, where images are given disproportionate weight.

Insights from the conditional probabilities (Figure 4) complement this perspective by focusing on modality dominance in specific interactions. Modality-agnostic bias amplification highlights the need for careful calibration of multimodal fusion mechanisms to avoid unintended magnifications. Conversely, bias mitigation, which occurs only when text bias dominates, demonstrates that text can play a pivotal role in counteracting biases introduced by images.

The most common interaction type observed in this dataset was neutrality, suggesting that multimodal systems may sometimes have little added value for bias mitigation. For instance, the findings suggest that if image content introduces significant bias, adding text alone is unlikely to mitigate it unless the text is specifically chosen to counteract the bias. This reinforces the recommendation of addressing biases within individual modalities as crucial to preventing their propagation in multimodal systems.

Hence, the insights presented in this study underscore the importance of the suggested probabilistic approach as a first step in assessing biases in the design and evaluation of AI models, ensuring that their integration into societal and organizational contexts promotes fairness. By applying the proposed framework to describe the dynamic interactions of bias in multimodal systems, this study contributes to a deeper understanding of how AI and machine learning can perpetuate societal inequities inadvertently.

6 Conclusion

This study provides a systemic framework for classifying and measuring bias amplification, mitigation, and neutrality in multimodal machine-learning models. Through probabilistic simulation and simplistic modelling, and by comparing text, image, and multimodal embeddings across diverse bias-prone categories, the findings reveal nuanced dynamics of bias propagation and underscore the importance of understanding modality-specific contributions to bias to improve fairness in multimodal AI systems.

Based on these findings, it is highly recommended to integrate this approach into regular audits of single-modality system performance before multimodal integration, calling for a holistic strategy that goes beyond data balancing and integrates bias mitigation in preprocessing, in-processing, and post-processing. This also includes techniques such as adversarial training, bias-aware loss functions, and the inclusion of diverse and representative training data, along with post-processing methods to adjust biased outputs.

Future work could also expand this analysis to include additional metrics (e.g., Jensen-Shannon divergence) or extend the use of this heuristic approach to investigate other domains (e.g., audio-video or audio-text embeddings) and task-specific models (e.g., recommendation systems) as bias dynamics could significantly differ due to their functional objectives. Furthermore, the framework can

be expanded to include different multimodal model architectures. For instance, early fusion models that merge features at the input level could introduce compounded biases early on from both modalities, whereas generative models such as DALL-Es and GPTs, actively generating outputs by interpreting cross-modal information, can introduce emergent biases that are not present in individual modalities. Hence, future research could explore how multimodal architectural design and fusion strategies can affect interaction dynamics.

Overall, further research is required to explore the conditions under which bias mitigation is most effective, recommending the use of this framework and cross-validation with alternative measurement tools and real-world applications for more robust and actionable recommendations. As multimodal AI systems have become more prevalent, understanding and addressing the complex interactions of biases across modalities is imperative. By implementing thoughtful design and mitigation strategies, we can harness the full potential of these systems, while promoting fairness, equity, and accuracy in their predictions and applications.

References

- Iryna Hartsock and Ghulam Rasool. Vision-Language Models for Medical Report Generation and Visual Question Answering: A Review. *arXiv.org*, 2024. doi:10.48550/arXiv.2403.02469.
- Mahdi Abavisani, Liwei Wu, Shengli Hu, Joel Tetreault, and Alejandro Jaimes. Multimodal Categorization of Crisis Events in Social Media. In 2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pages 14667–14677, Dec 2020. doi:10.48550/arXiv.2004.04917.
- Ferda Ofli, Firoj Alam, and Muhammad Imran. Analysis of Social Media Data using Multimodal Deep Learning for Disaster Response. In *International Conference on Information Systems for Crisis Response and Management*, 2020. doi:10.48550/arXiv.2004.11838.
- Henning Müller and Devrim Unay. Retrieval From and Understanding of Large-Scale Multi-modal Medical Datasets: A Review. *IEEE Transactions on Multimedia*, 19(9):2093–2104, Dec. 2017. doi:10.1109/TMM.2017.2729400.
- Akash Ghosh, Arkadeep Acharya, Raghav Jain, Sriparna Saha, Aman Chadha, and Setu Sinha. CLIPSyntel: CLIP and LLM Synergy for Multimodal Question Summarization in Healthcare. In *AAAI Conference on Artificial Intelligence*, volume 38, pages 22031–22039, 2023. doi:10.48550/arXiv.2312.11541.
- Lars Heiliger, Anjany Sekuboyina, Bjoern Menze, Jan Egger, and Jens Kleesiek. Beyond Medical Imaging - A Review of Multimodal Deep Learning in Radiology. *TechRxiv*, 19103432, 2022. doi:10.36227/techrxiv.19103432.v1.

- Muhammad Imran, Ferda Ofli, Doina Caragea, and Antonio Torralba. Using AI and Social Media Multimodal Content for Disaster Response and Management: Opportunities, Challenges, and Future Directions. *Information Processing & Management*, 57(5):102261, Dec. 2020. doi:10.1016/j.ipm.2020.102261.
- Rodrigo Leonardo, Amber Hu, Mohammad Uzair, Qiujing Lu, Iris Fu, Keishin Nishiyama, Sooraj Mangalath Subrahmannian, and Divyaa Ravichandran. Fusing Visual and Textual Information to Determine Content Safety. In 2019 18th IEEE International Conference On Machine Learning And Applications (ICMLA), pages 2026–2031, Dec 2019. doi:10.1109/ICMLA.2019.00324.
- Susan Hao, Piyush Kumar, Sarah Laszlo, Shivani Poddar, Bhaktipriya Radharapu, and Renee Shelby. Safety and Fairness for Content Moderation in Generative Models. *arXiv.org*, 2023. doi:10.48550/arXiv.2306.06135.
- Daniele Malitesta, Giandomenico Cornacchia, Claudio Pomo, Felice Antonio Merra, Tommaso Di Noia, and Eugenio Di Sciascio. Formalizing Multimedia Recommendation through Multimodal Deep Learning. *ACM Transactions on Recommender Systems*, 2023. doi:10.48550/arXiv.2309.05273.
- Felix Krones, Umar Marikkar, Guy Parsons, Adam Szmul, and Adam Mahdi. Review of multimodal machine learning approaches in healthcare. *arXiv.org*, 2024. doi:10.48550/arXiv.2402.02460.
- Massimo Salvi, Hui Wen Loh, Silvia Seoni, Prabal Datta Barua, Salvador García, Filippo Molinari, and U Rajendra Acharya. Multi-modality approaches for medical support systems: A systematic review of the last decade. *Information Fusion*, 103:102134, Dec. 2024. doi:10.1016/j.inffus.2023.102134.
- Adrienne Kline, Hanyin Wang, Yikuan Li, Saya Dennis, Meghan Hutch, Zhenxing Xu, Fei Wang, Feixiong Cheng, and Yuan Luo. Multimodal machine learning in precision health: A scoping review. *NPJ Digital Medicine*, 2022. doi:10.1038/s41746-022-00712-8.
- Mingju He, Myron Hohil, Thomas LaPeruta, Kerolos Nashed, Victor Lawrence, and Yu-Dong Yao. Performance evaluation of multimodal deep learning: object identification using UAV dataset. In *SPIE Proceedings*, volume 11746, pages 602–608, Apr. 2021. doi:10.1117/12.2587825.
- Jialin Yuan, Ye Yu, Gaurav Mittal, Matthew Hall, Sandra Sajeev, and Mei Chen. Rethinking Multimodal Content Moderation from an Asymmetric Angle with Mixed-modality. In *Proceedings - 2024 IEEE Winter Conference on Applications of Computer Vision (WACV)*, pages 8517–8527, May 2023. doi:10.1109/WACV57701.2024.00834.
- Yunpeng Gong, Liqing Huang, and Lifei Chen. Robust Person Re-identification with Multi-Modal Joint Defence. In *IEEE Computer Society Conference* on Computer Vision and Pattern Recognition Workshops, volume 2022-June, pages 4312–4321, Nov. 2021. doi:10.1109/CVPRW56347.2022.00477.

- Wei Shi, Jing Zhang, and Shaoyi He. Understanding public opinions on chinese short video platform by multimodal sentiment analysis using deep learning-based techniques. *Kybernetes*, ahead-of-print(ahead-of-print), 2023. doi:10.1108/K-04-2023-0723/FULL/XML.
- Yongcong Luo and He Zhu. MAMSC: a semantic enhanced representation model for public opinion key node recognition based on multianchor mapping in semantic communities. *Kybernetes*, ahead-ofprint(ahead-of-print), 2024. doi:10.1108/K-04-2024-0914/FULL/XML.
- Salem Alelyani. Detection and Evaluation of Machine Learning Bias. *Applied Sciences*, 11(14):6271, Jul. 2021. doi:10.3390/APP11146271.
- Konstantinos Mavrogiorgos, Athanasios Kiourtis, Argyro Mavrogiorgou, Andreas Menychtas, and Dimosthenis Kyriazis. Bias in Machine Learning: A Literature Review. *Applied Sciences*, 14(19):8860, Oct. 2024. doi:10.3390/APP14198860.
- Ninareh Mehrabi, Fred Morstatter, Nripsuta Saxena, Kristina Lerman, and Aram Galstyan. A Survey on Bias and Fairness in Machine Learning. *ACM Computing Surveys (CSUR)*, 54(6), July 2021. doi:10.1145/3457607.
- Remi Cadene, Corentin Dancette, Matthieu Cord, Devi Parikh, et al. RUBi: Reducing Unimodal Biases in Visual Question Answering. In *Neural Information Processing Systems*, 2019. doi:10.48550/arXiv.1906.10169.
- Paul Pu Liang, Chiyu Wu, Louis-Philippe Morency, and Ruslan Salakhutdinov. Towards Understanding and Mitigating Social Biases in Language Models. In *International Conference on Machine Learning*, 2021. doi:10.48550/arXiv.2106.13219.
- Navigli, Roberto and Conia, Simone and Ross, Björn. Biases in Large Language Models: Origins, Inventory, and Discussion. *Journal of Data and Information Quality*, 15(2):1–21, June 2023. doi:10.1145/3597307.
- Meiqi Chen, Yixin Cao, Yan Zhang, and Chaochao Lu. Quantifying and Mitigating Unimodal Biases in Multimodal Large Language Models: A Causal Perspective. *arXiv.org*, 2024. doi:10.48550/arXiv.2403.18346.
- K. Miller. Covert Racism in AI: How Language Models Are Reinforcing Outdated Stereotypes, 2024. URL https: //hai.stanford.edu/news/covert-racism-ai-how-langu age-models-are-reinforcing-outdated-stereotypes. Accessed: Nov. 25, 2024.
- H. Kotek, R. Dockum, and D. Q. Sun. Gender bias and stereotypes in Large Language Models. In *Proceedings of the ACM Collective Intelligence Conference, CI 2023*, pages 12–24, November 2023. doi:10.1145/3582269.3615599.
- T. Manzini, L. Yao Chong, A. W. Black, and Y. Tsvetkov. Black is to Criminal as Caucasian is to Police: Detecting and Removing Multiclass Bias in Word Embeddings. In Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational

Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), 2019. doi:10.18653/v1/N19-1062.

- Zeliang Zhang, Mingqian Feng, Zhiheng Li, and Chenliang Xu. Discover and Mitigate Multiple Biased Subgroups in Image Classifiers. *Proceedings* of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 10906–10915, 2024. doi:10.1109/CVPR52733.2024.01037.
- A.-C. Boury-Brisset and J. Berger. Benefits and Challenges of AI/ML in Support of Intelligence and Targeting in Hybrid Military Operations. Technical report, NATO S&I Organisation, 2020. URL https://www.sto.nato.i nt/publications/STO%20Meeting%20Proceedings/ST O-MP-IST-190/MP-IST-190-09.pdf. Accessed: Oct. 04, 2024.
- B. M. Booth, L. Hickman, S. K. Subburaj, L. Tay, S. E. Woo, and S. K. D'Mello. Bias and fairness in multimodal machine learning: A case study of automated video interviews. In *Proceedings of the 2021 international conference on multimodal interaction*, pages 268–277, 2021. doi:10.1145/3462244.3479897.
- A. Pena, I. Serna, A. Morales, and J. Fierrez. Bias in Multimodal AI: Testbed for Fair Automatic Recruitment. In 2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops (CVPRW), pages 129– 137, Nov. 2023. doi:10.48550/arXiv.2004.07173.
- Y. Shen, H. Di, and S. M. Mitigating Biases in Multimodal Personality Assessment. In *International Conference on Multimodal Interaction*, 2020. doi:10.1145/3382507.3418889.
- Z. Shengjia, R. Hongyu, Y. Arianna, S. Jiaming, D. G. Noah, and E. Stefano. Bias and Generalization in Deep Generative Models: An Empirical Study. *Neural Information Processing Systems*, 2018. doi:10.48550/arXiv.1811.03259.
- Hugo Berg, Siobhan Mackenzie Hall, Yash Bhalgat, Wonsuk Yang, Hannah Rose Kirk, Aleksandar Shtedritski, and Max Bain. A Prompt Array Keeps the Bias Away: Debiasing Vision-Language Models with Adversarial Learning. In AACL, 2022. doi:10.48550/arXiv.2203.11933.
- Dingkang Yang, Mingcheng Li, Dongling Xiao, Yang Liu, Kun Yang, Zhaoyu Chen, Yuzheng Wang, Peng Zhai, Ke Li, and Lihua Zhang. Towards Multimodal Sentiment Analysis Debiasing via Bias Purification. *arXiv.org*, 2024. doi:10.48550/arXiv.2403.05023.
- J. Alasadi, R. Arunachalam, P. K. Atrey, and V. K. Singh. A Fairness-Aware Fusion Framework for Multimodal Cyberbullying Detection. In 2020 IEEE Sixth International Conference on Multimedia Big Data (BigMM), pages 166–173, Dec. 2020. doi:10.1109/BigMM50055.2020.00032.
- A. Mandal, S. Leavy, and S. Little. Multimodal Composite Association Score: Measuring Gender Bias in

Generative Multimodal Models. *arXiv.org*, 2023a. doi:10.48550/arXiv.2304.13855.

- H. Acosta, N. Henderson, J. Rowe, W. Min, J. Minogue, and J. Lester. What's Fair is Fair: Detecting and Mitigating Encoded Bias in Multimodal Models of Museum Visitor Attention. In *Proceedings of the 2021 International Conference on Multimodal Interaction*, pages 258–267, Oct. 2021. doi:10.1145/3462244.3479943.
- A. Mandal, S. Leavy, and S. Little. Measuring Bias in Multimodal Models: Multimodal Composite Association Score. In *Communications in Computer and Information Science*, pages 17–30. Springer Nature Switzerland, 2023b. doi:10.48550/arXiv.2304.13855.
- Microsoft Research Blog. Frontiers of multimodal learning: A responsible AI approach. https://www.microsoft. com/en-us/research/blog/frontiers-of-multimodal-lea rning-a-responsible-ai-approach/, 2024. Accessed: Oct. 25, 2024.
- S. Bhargava and D. Forsyth. Exposing and Correcting the Gender Bias in Image Captioning Datasets and Models. *arXiv preprint arXiv:1912.00578*, 2019. doi:10.48550/arXiv.1912.00578.
- J. Zhao, T. Wang, M. Yatskar, V. Ordonez, and K. W. Chang. Men Also Like Shopping: Reducing Gender Bias Amplification using Corpus-level Constraints. In *EMNLP 2017 - Conference on Empirical Methods in Natural Language Processing, Proceedings*, pages 2979– 2989. Association for Computational Linguistics (ACL), 2017. doi:10.18653/V1/D17-1323.
- S. Janghorbani and G. de Melo. MultiModal Bias: Introducing a Framework for Stereotypical Bias Assessment beyond Gender and Race in Vision Language Models. In *Conference of the European Chapter of the Association for Computational Linguistics*, 2023. doi:10.48550/arXiv.2303.12734.
- R. Sawhney, A. Aggarwal, and R. R. Shah. An Empirical Investigation of Bias in the Multimodal Analysis of Financial Earnings Calls. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 3751–3757, 2021. doi:10.18653/v1/2021.naacl-main.294.
- R. Wang, P. Chaudhari, and C. Davatzikos. Bias in machine learning models can be significantly mitigated by careful training: Evidence from neuroimaging studies. *Proceedings of the National Academy of Sciences*, 120 (6), 2023. doi:10.1073/pnas.2211613120.
- M. Schmitz, R. Ahmed, and J. Cao. Bias and Fairness on Multimodal Emotion Detection Algorithms. *arXiv.org*, 2022. doi:10.48550/arXiv.2205.08383.
- I. Alabdulmohsin, X. Wang, A. Steiner, P. Goyal, A. D'Amour, and X. Zhai. CLIP the Bias: How Useful is Balancing Data in Multimodal Learning? *ArXiv*, 2024. doi:10.48550/arXiv.2403.04547.

- T. Srinivasan and Y. Bisk. Worst of Both Worlds: Biases Compound in Pre-trained Vision-and-Language Models. In *Proceedings of the 4th Workshop on Gender Bias in Natural Language Processing (GeBNLP)*, 2022. doi:10.18653/v1/2022.gebnlp-1.10.
- Alejandro Peña, Ignacio Serna, Aythami Morales, Julian Fierrez, Alfonso Ortega, Ainhoa Herrarte, Manuel Alcantara, and Javier Ortega-Garcia. Human-Centric Multimodal Machine Learning: Recent Advances and Testbed on AI-Based Recruitment. *SN Comput Sci*, 2023. doi:10.1007/s42979-023-01733-0.
- P. Kok, J. F. M. Jehee, and F. P. de Lange. Less Is More: Expectation Sharpens Representations in the Primary Visual Cortex. *Neuron*, 75(2):265–270, Jul 2012. doi:10.1016/J.NEURON.2012.04.034.