YANLI WANG, Sun Yat-sen University, China YANLIN WANG^{*}, Sun Yat-sen University, China SUIQUAN WANG, Sun Yat-sen University, China DAYA GUO, Sun Yat-sen University, China JIACHI CHEN, Sun Yat-sen University, China JOHN GRUNDY, Monash University, Australia XILIN LIU, Huawei Cloud Computing Technologies Co., Ltd, China YUCHI MA, Huawei Cloud Computing Technologies Co., Ltd, China MINGZHI MAO, Sun Yat-sen University, China HONGYU ZHANG, Chongqing University, China ZIBIN ZHENG, Sun Yat-sen University, China

Repository-level code translation refers to translating an entire code repository from one programming language to another while preserving the functionality of the source repository. Many benchmarks have been proposed to evaluate the performance of such code translators. However, previous benchmarks mostly provide fine-grained samples, focusing at either code snippet, function, or file-level code translation. Such benchmarks do not accurately reflect real-world demands, where entire repositories often need to be translated, involving longer code length and more complex functionalities. To address this gap, we propose a new benchmark, named **RepoTransBench**, which is a real-world repository-level code translation benchmark with an automatically executable test suite. We conduct experiments on RepoTransBench to evaluate the translation performance of 11 advanced LLMs. We find that the Success@1 score (test success in one attempt) of the best-performing LLM is only 7.33%. To further explore the potential of LLMs for repository-level code translation, we provide LLMs with error-related feedback to perform iterative debugging and observe an average 7.09% improvement on Success@1. However, even with this improvement, the Success@1 score of the best-performing LLM is only 21%, which may not meet the need for reliable automatic repository-level code translation. Finally, we conduct a detailed error analysis and highlight current LLMs' deficiencies in repository-level code translation, which could provide a reference for further improvements.

1 INTRODUCTION

Code translation refers to translating code from one programming language to another while preserving the functionality of the source code [1–4]. It has broad applications, including refactoring code written in outdated languages [5], transitioning from simple but slow languages to more complex and faster ones [6], enabling programming language migration in software development [7–14], and addressing data scarcity issues through synthetic data generation [15, 16]. Automatic code translation can significantly reduce manual effort and has thus garnered widespread attention in recent years [17–25]. With the popularity of large language models (LLMs), researchers are trying to translate code with LLMs, yielding promising results [26–28].

To evaluate the performance of code translation tools, various benchmarks have been introduced [29–38]. Based on translation granularity, current fine-grained code translation benchmarks can be classified into three levels [1]: snippet-level, function-level, and file-level. Specifically, **snippet-level** code translation benchmarks, such as CoST [29], XLCost [30], typically refer to evaluating the translation of program segments, that are located between two consecutive code comments. **Function-level** code translation benchmarks, such as TransCoder-test [31], CodeXGIUE [32], HumanEval-X [33] and EvalPlus [34], focus on evaluating the translation of a

^{*} Yanlin Wang is the corresponding author, wangylin36@mail.sysu.edu.cn.

function. **File-level** code translation benchmarks which include CodeNet [35], Avatar [36], Code-Scope [37] and CodeTransOcean [38] refer to evaluating the translation of a complete program file. However, these fine-grained code translation benchmarks may not meet the demands of real development scenarios, which require the translation of entire repositories. Recently, Pan et al. [1] manually study two open-source repositories (Apache Commons CLI [39] and Python Click [40]), and find that current LLMs struggle to perform code translation for entire repositories. Although this work has conducted preliminary research on repository-level code translation, we identify the following problems:

- **Problem 1: Limited Data Scale.** Current works lack enough repository samples to evaluate repository-level code translation. For instance, Pan et al. [1] conduct their research on only two repository samples, which limits the representativeness.
- **Problem 2: Lack of Automated Test Suite.** Although Pan et al. [1] manually inspect two repository translations, it is impractical to conduct manual inspections on large-scale datasets. Therefore, an automated test suite is needed to evaluate the performance of translators.
- **Problem 3: Ignoring the Resource Files.** A real-world code repository migration often requires the migration of corresponding resources in the repository as well. However, Pan et al. [1] ignore resource files [1], which are commonly found in code repositories. Some resource files may interact with the program data flows during execution through I/O operations. Neglecting the handling of these resource files may result in translated code that is not functionally equivalent to the source code.
- **Problem 4: Ignoring the Configuration File.** The configuration file is often required for an entire repository. For example, a Java Maven [41] repository requires a "pom.xml" file to manage repository configuration and dependencies. However, Pan et al. [1] only consider the translation of functional code files, ignoring the generation of the corresponding configuration file.

In this paper, we introduce a *repository-level code translation benchmark*, named **Repo-TransBench**. RepoTransBench includes 100 repository samples and provides an automatic test suite to evaluate the **compilability and functional correctness** of the translated repositories to address the aforementioned problem. To construct RepoTransBench, firstly, we collect real-world repositories from *The Stack* [42] and *The Stack v2* [43], which are the training data of StarCoder series LLMs [44, 45]. Secondly, we select two popular languages from the TIOBE index [46] as our translation pair. We further filter the repositories to exclude those with fewer than 50 stars, those that contain language-specific packages, those lacking test cases, and those that are not executable. Ultimately, we obtain the candidate repositories that meet these criteria. Thirdly, to provide the automatic test suite, we construct test cases of the target language through a collaborative effort involving LLMs and human translators to ensure both quality and efficiency. Specifically, we first translate automatically using LLM. Then, we perform iterative manual checking based on the execution of test cases. Finally, we obtain 100 repository samples with corresponding automatic test suites.

To evaluate the translation performance of current LLMs on RepoTransBench, we conduct experiments with 11 advanced LLMs, which include 8 general LLMs (4 open-source and 4 closed-source LLMs) and 3 code LLMs. Our experimental results show that LLMs are far from satisfactory for repository-level code translation. The best-performing LLM, Claude-3.5-Sonnet, only achieves 7.33% on Success@1 (test success in one attempt) and 12% on Success@3 (test success in three attempts). We also observe that LLMs with limited parameters may not have the ability to perform repository-level code translation. The experiment results indicate that even after three attempts, Llama-3.1-8B-Instruct [47] fails to generate even one compilable translation.

To further explore the potential of LLMs for repository-level code translation, we follow Pan et al. [1] and adopt an iterative debugging approach, providing error-related information to LLMs. After five iterative debugging phases, the Success@1 scores of all LLMs achieve an improvement ranging from 3.47% to 17%, except for Llama-3.1-8B-Instruct and CodeLlama-34B-Instruct. However, the best-performing LLM, GPT-40, only achieves 21% on Success@1 and 34% on Success@3, respectively. Such performance may still fall well short of meeting the need for reliable automatic repository-level code translation.

To investigate the cause of errors in repository-level code translation, we conduct a study on errors that occur in the translation and debugging phase. We categorize the common errors into five categories: configuration file issues, limited understanding ability issues, incomplete generation issues, language feature issues, and encoding issues. The error study highlights current LLMs' deficiencies in repository-level code translation and may suggest directions for future improvement.

The key contributions of this research are:

- We introduce a large-scale real-world repository-level code translation benchmark named **RepoTransBench** with an automatic execution-based test suite. RepoTransBench has a longer code length (more tokens and lines) and higher functional complexity (more functions and import statements) than previous fine-grained code translation benchmarks.
- We evaluate the translation performance of 11 advanced LLMs on RepoTransBench. We find that the Success@1 score of the best-performing LLM is only 7.33%, revealing that current LLMs may struggle to achieve repository-level translation.
- We provide LLMs with error-related feedback to perform debugging and observe an average 7.09% improvement on Success@1. However, the Success@1 score of the best-performing LLM is still only 21%, which may fall short of meeting the need for reliable automatic repository-level code translation.
- We conduct a detailed error analysis on the translation and debugging process and categorize the common errors made by LLMs when used for code translation into five categories. The error study highlights current LLMs' deficiencies in repository-level code translation and provides a reference for further improvements in translation tools.

2 BACKGROUND

2.1 Code Translation

Code translation involves converting source code written in one programming language into another language while preserving the original program's functionality and logic [1–4]. This process is essential in software engineering for several reasons, such as migrating legacy systems to modern languages [7, 8], improving code performance by translating to more efficient languages [5] and enabling cross-platform compatibility [6]. As programming languages continue to evolve, the demand for accurate and efficient code translation techniques has grown, making it a critical area of research and development [17–25]. Many studies focus on code translation, which can be broadly divided into two main categories: **non-learning-based** and **learning-based** approaches [1].

Non-Learning-Based Methods. Existing non-learning-based code translation techniques can be categorized into several main groups. Parser-based tools like ANTLR [48] rely on manually defined grammar rules to translate source code between languages. Transpilers such as Babel [49], Emscripten [50], JSweet [51], and GWT [52] convert source code from one language to another, often used to ensure compatibility across platforms or systems. Domain-specific translators like CxGo [53], C2Rust [54], and JavaToCSharp [55] focus on specific language pairs, offering targeted translation solutions. Intermediate language compilers like Haxe [56] compile code to a variety of target languages by using an intermediate format. Interface generators such as SWIG [57] create



Fig. 1. Comparison of different code translation granularity.

cross-language bindings, allowing different languages to interact with each other without direct code translation.

Learning-Based Methods. There are many previous works investigating Learning-based code generation tasks [58-80]. Early learning-based approaches often train a neural network to achieve the ability of code translation [21, 22, 24, 81]. Aggarwal et al. [5] convert Python 2 code to Python 3 code using trained Moses [82], which is an open-source toolkit for statistical machine translation. Chen et al. [18] design a tree-to-tree neural network to translate a source tree into a target one. DeepAM [14] discusses the limitations of bilingual projects, as well as the automatic mining of API mappings to reduce manual effort in code migration. Zheng et al. [83] propose an approach for zeroresource NMT using maximum expected likelihood estimation. TransCoder [31] is a transformer with 6 layers to perform code translation at function level. Besides, Some models pre-trained on multilingual corpora like Codex [84], CodeT5 [81], and CodeGen [85] demonstrate remarkable code translation capability. In recent years, large language models such as StarCoder [44, 45], SantaCoder [86] and more latest models such as the Llama series [87–89], the ChatGPT series [90], the DeepSeek series [91], and the Claude series [92] have shown remarkable performance on traditional code translation tasks. These models are trained on large code corpus and have strong comprehension and instruction following abilities, which can perform accurate and efficient code translations on previous fine-grained code benchmarks. Rectifier [93] is a fine-tuned micro model that acts as a general corrector to correct the translation errors of unknown LLMs. Vert [94] leverages LLM's strong few-shot learning ability to produce readable Rust translations with formal guarantees of correctness. Bhattarai et al. [95] enhance code translation in LLMs with few-shot learning via retrieval-augmented generation. TransAgent [96] is an LLM-based multi-agent system for code translation. SpecTra [28] considers the different kinds of specifications that can be extracted from a program to enhance the code translation ability of LLMs. Momoko et al. [97] propose an LLM-based translation scheme that improves the success rate of translating large-scale C code into compilable Rust code. SolMover [98] can convert smart contracts written in Solidity [99] to Move [100] with LLMs. CCTrans [101] can transpile concurrent Java files to JavaScript using multiple workers while maintaining identical behavior. GlueTest [102] systematically and semiautomatically validates translations for non-trivial libraries. UniTrans [26] is a unified code translation framework applicable to various LLMs to unleash their power in code translation.

2.2 Code Translation Granularity

Figure 1 shows a comparison of code granularities used in different code translation approaches. Most previous works focus on the translations with a granularity not exceeding a single code file (left-hand side). Specifically, **snippet-level** code translation [29, 30] typically refers to evaluating the translation of program segments that are located between two consecutive code comments, and each program may consist of one or more code snippets. **Function-level** code translation [29–34] refers to translating a function into another programming language, with the data sources often being manually crafted datasets [103] or coding practice websites [104]. **File-level** code translation [35–38, 93, 105] often refers to translating a complete program file into the target language. The data sources are usually from code contest platforms [106–109] or task solutions websites [110–112]. G-TransEval [113] also provides a more fine-grained taxonomy, including token-level, syntax-level, library-level, and algorithm-level, which is part of a function.

Unlike the previous fine-grained granularity code translation, repository-level code translation involves migrating an entire repository from one language to another. Recently, **repository-level** code translation has gradually gained the attention of researchers [1]. As shown in the right-hand side of Figure 1, a typical code repository contains **functional code files** and **test code files** and may also include **resource files** and **configuration files**. Functional code files refer to those code files that implement specific functionalities of the code repository, such as the files located in the readtime/ directory. Test code files refer to the files used to verify the correctness of the functional code where test_readtime.py is an example. Resource files like those in samples/ folder are used to test the functional correctness of the functional code. The functional code needs to implement how to perform I/O operations with these resources. In addition, for certain language-specific frameworks, it is necessary to complete the configuration file correctly, such as the "pom.xml" file in Java's Maven [41] repositories.

Compared with previous fine-grained code translation granularity, repository-level code translation has the following four differences:

- **Diff 1: Complex Functional Implementation.** Real-world code repositories typically include numerous functions, classes, and import statements to realize complex functionalities. This characteristic requires translators to have an understanding of the entire repository, which may involve a long code length, necessitating that translators have sufficient processing ability.
- Diff 2: Challenging File Management. Code repositories often exhibit complex file structures, necessitating that translators effectively manage these structures during translation. Furthermore, code repositories may require an appropriate setup of configuration files, such as the "pom.xml" file in a Java Maven repository, to make the project compilable.
- **Diff 3: Resource Existence.** Except for migrating code files, those resource files that may perform I/O operations with code files should also be migrated together. This aspect has not been explored in previous work [1].
- **Diff 4: Test Case Existence.** Unlike previously crafted datasets [35, 36], for repository-level code translation, the source repository usually contains corresponding test cases, so making full use of the existing test cases may achieve better performance.

Recent studies have shown interest in repository-level code translation. Pan et al. [1] attempt to perform mutual conversion between Python and Java projects [39, 40], but find that the advanced LLMs are largely ineffective, with success rates of 8.1% for GPT-4 and 0% for the rest of the models.

3 REPOTRANSBENCH

In this section, we will introduce the two steps of building RepoTransBench : data collection and test case construction. Besides, we will provide the statistics between RepoTransBench and previous fine-grained benchmarks.



Fig. 2. Data Collection Pipeline.

3.1 Data Collection

As shown in Figure 2, the data collection pipeline of RepoTransBench consists of four steps: Preliminary Filtering, Info Updating, Repo Downloading, and Final Filtering.

3.1.1 Preliminary Filtering. We select Python as the source language and Java as the target language for our benchmark. Referring to the TIOBE index [46] for programming language popularity, the top five languages are Python, C++, Java, C, and C#. Given Python's popularity for its simplicity, ease of use, and suitability for rapid prototyping, alongside Java's reputation for enterprise-level applications due to its better performance, stability, and faster execution [6], we explore translating Python code to Java. For the data source, we choose to use the training data of StarCoder [44, 45] series models, *The Stack* and *The Stack v2*. We download the Python portion information of *The Stack* and *The Stack v2* from Hugging Face [114] and group the information by repository name ("*max_stars_repo_name*" for *The Stack* and "*repo_name*" for *The Stack v2*) to aggregate code files belonging to the same repository. To ensure that the repositories we select are publicly recognized, we filter out those with fewer than 10 stars, obtaining the *Raw Repo List*. It is worth noting that the star count here is outdated and tends to be lower than the actual number. Further filtering will be conducted later.

3.1.2 Information Updating. Due to using the early-released data source, some information may be outdated in *Raw Repo List*, where star counts tend to be lower than the actual numbers, and many repositories are forks (a commonly occurring phenomenon, especially in *The Stack*), we use the *GitHub REST API* [115] to update the information and apply further filtering. We check whether a repository exists, removing non-existing repositories. For those repositories forked from others, we redirect to the origin repository and use the original repository information. We also find that although we filter the data from the Python dataset in Section 3.1.1, many repositories have a main language other than Python. To ensure we obtain a Python repository, we require the percentage of Python language to be the largest among all languages in a repository, excluding those frontend languages (e.g., HTML, CSS). We then use the updated star count for further filtering, retaining repositories with more than 50 stars. Then we obtain the cleaned *Updated Repo List*.

3.1.3 Repository Downloading. We clone the raw repositories in the *Updated Repo List* to the local environment using *Git command* [116] to enable further filtering.

3.1.4 Final Filtering. To ensure the quality of the repositories, we perform further filtering on downloaded repositories. Firstly, we use a blacklist to block repositories with packages which is difficult to implement from scratch. It is worth noting that we aim to evaluate individual repositories. However, due to contributions from the open-source community, a Python repository may include many third-party packages, like *pytorch* [117], *tensorflow* [118], etc. These packages do not have corresponding implementations in Java language, and it is challenging to implement these libraries from scratch. Therefore, these libraries are not within the scope of our research. We manually review 200 Python repositories and obtain a package blacklist. If a repository contains any package



Fig. 3. Overview of the translation process.

from the blacklist, it would be excluded. Examples of packages on the blacklist include (1) deep learning libraries like *pytorch* [117], *tensorflow* [118], and *nltk* [119], (2) data science libraries like *scikit-learn* [120] and *jupyter-notebook* [121], (3) data visualization libraries like *seaborn* [122] and *matplotlib* [123]. However, we retain repositories that contain libraries like *numpy* [124] selectively if it is just used for basic calculations.

Additionally, we ensure that test cases in the source repository are available. By parsing file paths and searching file contents, we retain repositories with test cases available. Then, we manually review the filtered repositories, run the test cases, and only keep repositories that successfully pass all the test cases. Finally, we obtain the *Candidate Repos*.

3.2 Test Case Construction

To evaluate the quality of the translations, test cases of target code are needed. HumanEval-X [33] involves manually rewriting test cases into the target language, whereas EvalPlus [34] utilizes ChatGPT [125] for the automated generation of test cases. However, relying solely on manual translation to generate test cases for repository-level code can be quite labor-intensive, requiring human translators with substantial development expertise in both Python and Java. While test cases generated exclusively by LLMs may not always be reliable. Therefore, we choose to construct test cases of the target language through a collaborative effort involving human translators and LLMs to ensure both quality and efficiency. The test case construction pipeline consists of four steps, including (1) Translation Demonstration, (2) Automatic Translation, (3) Resources Migration and Path Transformation, and (4) Execution-Based Iterative Manual Checking.

3.2.1 Translation Demonstration. To ensure the quality of the translation assessment, we standardize the format of the translations, as the implementation of the repository code may vary during translation. We provide a demonstration shown in Figure 3 to help understand the translation process. We will introduce the translation demonstration from three aspects: framework selection, mapping method, and language feature handling.

1) Framework Selection. We use the popular Java framework Maven [41] as the standard framework for target Java repositories. Figure 3 is an example of translating a Python repository into a Java Maven repository. In this example, paths and resources need to be migrated according to Maven conventions. We expect functional code to be placed in the "src/main/java" directory and test code to be placed in the "src/test/java" directory. Resource files in Python can exist anywhere,



Fig. 4. Language Feature Problem: An example that translates a Python function with default argument to Java language with method overloading.

but we follow Maven's conventions and expect them to be located in the "src/main/resources" or "src/test/resources" directories in the Java repository.

2) Mapping Method. For previous function-level code translation, we expect a Python function to be translated into a Java function wrapped in a class [33, 34]. However, translating all functions in a Python repository into individual Java classes and combining them to form the Java repository may not align with the style of real-world Java repositories. To observe how LLMs perform mapping, we conduct a preliminary experiment with GPT-40 [126] on 50 Python repositories using a simple prompt: "Please translate the given Python repository to a Java Maven repository". We manually review the translations and find that in most samples, if a Python file contains multiple classes, each class is typically translated into a separate Java class and placed in an individual Java file. If a Python file contains code not wrapped in a class, all that code will be mapped into a single class when translated into Java. We follow this observation and name this approach **One-to-One File/Class Mapping** as our mapping method. Besides, for naming convention, we use "camelCase" to replace "snake_case" from Python, referring to CodeGeeX [25].

3) Language Feature Handling. The language features of Python and Java include many different implementations, such as data types, object initialization methods, the implementation of multiple inheritance, etc. After reviewing the results of the preliminary experiment, we introduce two common different implementations as follows. When using Python language to perform member variable access, we typically access through a format of "object._attribute" or "object._ClassName__attribute", even though sometimes the attribute may be a protected attribute (with a "_" prefix) or a private attribute (with a "__" prefix). However, for a Java class, member variables are usually declared with the "private" modifier and are accessed or modified through "getters" and "setters". We ensure the test cases constructed meet the characteristics through manual checks rather than token-by-token translation, which omits the language features [1]. For Java language, there is no equivalent implementation for Python function with default arguments. Instead, method overloading can be used to mimic similar functionality. Figure 4 is a simple example, a function with default arguments in Python repositories will be implemented by method overloading in our test case construction phase.

3.2.2 Automatic Translation. Here we translate not only the test code files but also the functional code files to further ensure the correctness of the generated test cases (details in Section 3.2.4). We leverage GPT-40 [126] as the backbone LLM to perform translation. The context window of GPT-40 is 128k. For repositories where the total token count exceeds this limit, we split the repository into several chunks, making sure that each chunk consists of several complete code files and does not exceed the context window. These chunks are then provided to GPT-40 in a multi-turn conversion format. Through the above approach, we obtain the raw translations without corresponding resources.

3.2.3 Resource Migration and Path Transformation. As shown in Figure 3, after obtaining the raw translations from the previous step, we manually migrate the resources to the corresponding

Table 1. Statistics of RepoTransBench compared to other existing code translation datasets. Considering the translation of Python to Java, we report the number of samples and the average number of tokens, lines, functions, classes, and import statements per sample of each task. #Tokens counts are based on OpenAl's tiktoken tokenizer (https://github.com/openai/tiktoken). #Funcs, #Classes and #Imports counts are based on tree-sitter (https://tree-sitter.github.io). Code comments are removed before computation.

Dataset	Year	Source	Level	Config File	Evaluation	#Samples	#Tokens	#Lines	#Funcs	#Classes	#Imports
TransCoder-test [31]	2020	GeeksforGeeks [104]	Function	Not Req	Execution	868	127	12	1	0	0
CodeNet [35]	2021	AIZU [108], AtCoder [107]	File	Not Req	Execution	200	99	12	1	0	0
Avatar [36]	2021	AtCoder [107], etc ¹	File	Not Req	Execution	250	175	18	1	0	1
CaST [20]	2022	Cooleafor Coolea [104]	Snippet	Not Req	Similarity	351	33	3	0	0	0
031 [29]	2022	GeeksioiGeeks [104]	Function	Not Req	Similarity	69	173	15	1	0	0
XI CoST [30]	2022	GeeksforGeeks [104]	Snippet	Not Req	Similarity	6861	24	2	0	0	0
ALC031 [50]	2022	Geeksiol Geeks [104]	Function	Not Req	Similarity	864	196	19	1	0	0
HumanEval-X [33]	2022	HumanEval [103]	Function	Not Req	Execution	164	65	8	1	0	0
G-TransEval [113]	2023	HumanEval [103], etc ²	<function<sup>3</function<sup>	Not Req	Similarity	400	90	10	1	0	0
xCodeEval [105]	2023	Codeforces [106]	File	Not Req	Execution	1942	209	22	1	0	1
EvalPlus [34]	2023	HumanEval [103]	Function	Not Req	Execution	164	65	8	1	0	0
CodeScope [37]	2023	Codeforces [106]	File	Not Req	Execution	30	259	28	1	0	1
CodeTransOcean [38]	2023	Rosetta Code [112], d2l-ai [111]	File	Not Req	Similarity	1029	253	24	2	0	1
RepoTransBench	2024	The Stack v1&v2 [42, 43]	Repository	Require	Execution	100	3431	352	34	5	12

directory ("src/main/resources" or "src/test/resources") in the Java repositories. Then, we transform any incorrect file path in the Java repositories to align with the mapping method and language features mentioned in Section 3.2.1.

3.2.4 Execution-Based Iterative Manual Checking. To ensure the test cases are complete and free from syntax errors and calls to non-existent APIs, which may be difficult to discover and laborintensive by manual inspection, we use compilability as a metric to evaluate the quality of test cases. We execute the repositories obtained from the previous step to evaluate the compilability. Three of the authors are involved as participants to check the correctness of test cases. These participants have 3-6 years of coding experience. Two of the participants independently check the completeness of the test cases to ensure their test range is consistent with those in the source repository. They also correct errors that occur during the execution until the repository is compileable or more than 30 minutes are consumed. For repositories that fail to be compiled, the two participants ensure the errors do not originate from the test cases by inspecting and fixing related code. Another participant performs a double-check on the results of the previous two participants. For repositories deemed contentious by the three participants, they discuss and achieve a mutually agreed solution. Ultimately, 83% of the repositories compile successfully from the processing results of the two participants, which means the test cases of these repositories are free from syntax errors and calls to non-existent APIs. For the remaining 17% of the repositories, the three participants discuss and maintain that the issues mentioned above are not present in the test cases.

3.3 Statistics of RepoTransBench

Table 1 shows the statistics of RepoTransBench compared with other existing code translation benchmarks. To ensure fair statistics, we only take into account the portions of multilingual benchmarks where Python serves as the source language. Unlike previous fine-grained benchmarks, RepoTransBench uses the entire repository as its data samples. Since the goal of translation is to translate the entire code repository, it also requires the correct configuration of project files, such as the "pom.xml" file for a Java Maven project. To better evaluate the syntactic and functional

¹The source of AVATAR includes open-source programming contest sites: AtCoder [107], AIZU Online Judge [108], Google Code Jam [109], Codeforces [106], and online platforms: GeeksforGeeks [104], LeetCode [127], Project Euler [128].

²The source of G-TransEval includes humaneval [103], GeeksforGeeks [104], .NET samples [110].

³Taxonomy of G-TransEval includes four types: token-level, syntax-level, library-level, and algorithm-level. These granularities are all part of a function. To simplify, the statistics are calculated based on the entire function.

Туре	Source	Model Name	Company	Size	Context Window	Release Date
		Llama-3.1-8B-Instruct [47]	Meta	8B	128k	July 2024
General	Open	Llama-3.1-70B-Instruct [130]	Meta	70B	128k	July 2024
	Source	Llama-3.1-405B-Instruct [131]	Meta	405B	128k	July 2024
		DeepSeek-V2.5 [91]	DeepSeek	$236B^1$	128k	Sep 2024
LLM		GPT-3.5-Turbo-16k [125]	OpenAI	-	16k	Jun 2023
	Closed	GPT-4 ² [132]	OpenAI	-	128k	Dec 2023
So	Source	GPT-40 [126]	OpenAI	-	128k	May 2024
		Claude-3.5-Sonnet [133]	Anthropic	-	200k	Jun 2024
Cada	Onen	CodeLlama-34B-Instruct [134]	Meta	34B	100k	Aug 2023
LLM S	Open	Codestral-22B [135]	Mistral AI	22B	32k	May 2024
	Source	DeepSeek-Coder-V2-Instruct [136]	DeepSeek	236B ¹	128k	Jun 2024

correctness of the repository, we use execution-based metrics (Success@k, Build@k, and APR, details in Section 4.3). Through the data collection process described in Section 3.1, we ultimately obtain 100 repository samples (#Samples). According to our statistics, the average number of tokens (#Tokens) and lines (#Lines) per sample are 3431 and 352, respectively, which are 13 times the previous benchmark. Additionally, By utilizing *tree-sitter* [129], we obtain the average number of functions (#Funcs), classes (#Classes), and import statements (#Imports) to be 34, 5, and 12, respectively. In contrast, none of these statistics exceed 2 in the previous fine-grained benchmarks.

4 EXPERIMENTAL SETUP

4.1 Research Questions

We aim to answer the following key research questions (RQs) that explore the utility of RepoTrans-Bench for evaluating diverse LLMs for the repository-level code translation task:

- **RQ1 (Performance of Translation):** How do the recent advanced general and code LLMs perform in repository-level code translation?
- **RQ2 (Performance of Iterative Debugging):** Can iterative error-related information feedback to LLMs further improve their performance?
- **RQ3 (Effect of Code Length Functional Complexity):** How do code length and functional complexity of the repository affect the performance of translation?
- **RQ4 (Error Analysis):** What are the main types of errors that occur in repository-level code translation?

4.2 Model Selection

As shown in Table 2, we select 11 advanced LLMs from five different companies as our subject LLMs, which include 8 general LLMs (4 open-source and 4 closed-source LLMs) and 3 code LLMs. For general open-source LLMs, we include Meta's three latest LLMs, Llama-3.1-Instruct, with parameter sizes of 8B, 70B, and 405B. The 405B LLM is claimed to be comparable with closed-source LLMs. Additionally, we study DeepSeek-V2.5 [91], a Mixture-of-Experts (MoE) LLM that was updated in early September 2024 by DeepSeek. DeepSeek-V2.5 combines DeepSeek-V2-Chat and DeepSeek-Coder-V2-Instruct, integrating the general and coding abilities of the two previous versions. The coding and math capabilities surpass many closed-source LLMs [137]. For general closed-source LLMs, we examine three well-known LLMs from OpenAI, GPT-3.5-Turbo-16k [125], GPT-4 [132], and GPT-40 [126]. Furthermore, we also evaluate one of Anthropic's advanced LLM, Claude-3.5-Sonnet [133], in our experiments. For code LLMs, we select three advanced LLMs from

¹DeepSeek-V2.5 and DeepSeek-Coder-V2-Instruct are Mixture-of-Experts (MoE) LLMs with 21B activated parameters. ²We use GPT-4-0125-Preview in our experiments.

three companies. CodeLlama-34B-Instruct [134] is an early-released code LLM in 2023. Codestral-22B [135] and DeepSeek-Coder-V2-Instruct [136] are two code LLMs released recently. Notably, most of the LLMs used in our experiments support a long context window, which may help to understand long code in repository-level code translation.

4.3 Evaluation Metrics

We evaluate the translation and debugging performance by the following metrics:

- **Success@k** (test success in *k* attempts): The metric Success@k measures the percentage of repositories that successfully **pass all test cases** in at least one of the *k* selected rounds of experiments.
 - Let T_i represent the set of repositories that pass all test cases in the *i*-th round of experiments. $|T_i|$ denotes the number of repositories that have test success in round *i*.

The general formula for Success@k is given by:

Success@k =
$$\frac{1}{\binom{n}{k} \times N} \sum_{1 \le i_1 < i_2 < \dots < i_k \le n} |T_{i_1} \cup T_{i_2} \cup \dots \cup T_{i_k}|$$
 (1)

where $\binom{n}{k}$ is the binomial coefficient, representing the number of ways to choose *k* rounds from the *n* rounds of experiments. $T_{i_1} \cup T_{i_2} \cup \cdots \cup T_{i_k}$ represents the union of test success sets from the selected *k* rounds.

In our experiments, n = 3 and N = 100 because we repeat the experiments three times under the same settings and the number of repository samples in our benchmark is 100.

• **Build@k** (build success in *k* attempts): The metric Build@k measures the percentage of repositories that **successfully build** in at least one of the *k* selected rounds of experiments. Let B_i represent the set of repositories successfully built in the *i*-th round of experiments. $|B_i|$ denotes the number of repositories that build successfully in round *i*.

The general formula for Build@k is analogous to Success@k and is given by:

Build@k =
$$\frac{1}{\binom{n}{k} \times N} \sum_{1 \le i_1 < i_2 < \dots < i_k \le n} \left| B_{i_1} \cup B_{i_2} \cup \dots \cup B_{i_k} \right|$$
(2)

where $\binom{n}{k}$ is the binomial coefficient, representing the number of ways to choose *k* rounds from the *n* rounds of experiments. $B_{i_1} \cup B_{i_2} \cup \cdots \cup B_{i_k}$ represents the union of build success sets from the selected *k* rounds.

• APR (average pass rate of test cases): The metric *APR* measures the **average percentage of test cases passed** across all repositories and rounds in the benchmark. It is calculated as follows:

$$APR = \frac{1}{n} \sum_{j=1}^{n} \left(\frac{1}{N} \sum_{i=1}^{N} \frac{N_{\text{pt}}^{(i,j)}}{N_{\text{at}}^{i}} \right)$$
(3)

where $N_{\text{pt}}^{(i,j)}$ represents the number of passed test cases for the *i*-th repository in the *j*-th round, and N_{at}^i represents the total number of test cases for the *i*-th repository. *n* is the total number of experimental rounds, and *N* is the total number of repositories in the benchmark.

It is worth noting that many previous works use **similarity-based metrics** like *BLEU* [138], *CodeBLEU* [16], or other metrics which calculate the overlapping tokens between references and translations [5, 7, 38, 139, 140] to evaluate the quality of translations. However, similarity-based metrics ignore the **syntactic correctness** and **functional correctness** of translations [31]. On the



Fig. 5. Overview of the evaluation process.

one hand, translations with high similarity to the reference cannot avoid having grammatical errors and functional errors. On the other hand, equivalent programs with different implementations may have low similarity. Therefore, we decide to use **execution-based metrics** mentioned above to evaluate the performance.

4.4 Execution Environment

To prevent LLMs from generating malicious code that could execute on the local machine and cause damage, we run the generated code in a sandbox (an isolated environment). We use *Docker* [141] as our code execution space. To check the executability of the Python projects in Section 3.1.4, we install both *Python 2.7* [142] and *Python 3.10* [143] versions in the Docker container and all needed packages by *PyPI pip* [144]. For the Java environment, we consistently use the *Oracle JDK 11* [145]. Additionally, we bridge Docker's network with the local machine, allowing it to access the internet to ensure the dependencies in the "pom.xml" file can be successfully installed.

4.5 Evaluation Process

As shown in Figure 5, the evaluation process includes three phases: translation, verification, and debugging. We conduct **three rounds** of experiments in the same setup. Each round of experiments consists of **one translation phase** and **five debugging phases**, with each phase followed by a **verification phase**.

Translation: In previous function-level code translation benchmarks [33, 34], test cases are given to let LLMs know the input and output format. We follow this practice for the repository-level code translation. Given a Python repository, we provide the corresponding Java test cases in the system prompt as the translation goal. We perform a topological sort using *tree-sitter* [129] on the files within the Python repository based on their call relationships, which ensures that any file being called appears before the file that calls it. Then we provide the sorted Python files and Java repository tree to form the translation prompt. We provide the system prompt and translation prompt to the LLM to generate a series of Java files (including functional code files and configuration files, without test code files). In our experiment, we follow the sampling strategy of the LLMs as adopted by Pan et al. [1], using a temperature of 0.7. For translations that are not fully generated in

Model	Success@1	Success@2	Success@3	Build@1	Build@2	Build@3	APR
Llama-3.1-8B-Inst	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%	0.00%
Llama-3.1-70B-Inst	1.33%	2.33%	3.00%	2.67%	4.33%	6.00%	1.30%
Llama-3.1-405B-Inst	2.67%	3.33%	4.00%	5.67%	8.00%	10.00%	4.70%
DeepSeek-V2.5	3.00%	4.67%	6.00%	12.00%	17.00%	20.00%	6.20%
GPT-3.5-Turbo	0.67%	1.00%	1.00%	2.33%	4.00%	5.00%	1.10%
GPT-4	2.33%	3.33%	4.00%	4.33%	7.00%	9.00%	2.00%
GPT-40	4.00%	6.33%	8.00%	9.00%	14.67%	19.00%	6.40%
Claude-3.5-Sonnet	7.33%	10.33%	12.00%	28.33%	37.67%	42.00%	16.50%
CodeLlama-34B-Inst	0.00%	0.00%	0.00%	0.37%	0.67%	1.00%	0.00%
Codestral-22B	2.08%	3.33%	5.00%	5.90%	8.33%	12.00%	2.60%
DeepSeek-Coder-V2-Inst	4.86%	6.33%	7.00%	16.84%	20.33%	24.00%	8.40%

Table 3. Translation performance on RepoTransBench.

one generation, we prompt the LLM with "Continue" until the translation is completely generated or reaches the maximum continuation count, which is set as 5 in our experiments. The generated functional code files and configuration files, combined with our given Java test files, form the Java repository. Then, the Java repository will be transferred to the docker container to perform verification in the next step.

Verification: In the verification phase, we switch to the root directory of the Java repository and execute the "mvn clean test" command to compile and execute the test cases in the repository. Notably, all dependencies referenced in the "pom.xml" file will be automatically installed. This process yields evaluation results and corresponding error messages.

Debugging: For repositories that execute failed in the verification phase, the error log will be used to compose the debugging prompt with the Java repository files. The system prompt and sampling strategy are the same as the translation phase. Then, we prompt the LLM to generate the fixed file and replace the original file in the previous Java repository. Figure 5 shows an example of fixing the private member variable access issue by employing a "getter".

5 EVALUATION RESULTS

5.1 RQ1: Performance of Translation

Table 3 provides an overview of the code translation performance on studied LLMs. The results illustrate significant differences in the abilities of these LLMs to perform repository-level code translation. Claude-3.5-Sonnet, which is the best-performing LLM among all LLMs, achieves 7.33% on Success@1, 28.33% on Build@1, and 16.5% on APR. However, it achieves only 12% test success even for three attempts. For open-source general LLMs and open-source code LLMs, the best-performing LLM only achieves 6% and 7% on Success@3, respectively. These results indicate that the current capabilities of LLMs are limited and insufficient to consistently generate executable and functionally correct translations.

Finding 1: The best-performing LLM only achieves 7.33% on Success@1 and 28.33% on Build@1 when testing on RepoTransBench, indicating that it is difficult for current LLMs to perform reliable repository-level code translation.

GPT-3.5-Turbo, which is an earlier-released LLM, achieves only 1% on Success@3. Its performance falls short compared to other closed-source LLMs. The poor performance may be due to its outdated training and optimization. Llama-3.1-8B-Instruct performs even worse and fails to generate even one compilable translation across three rounds. The result indicates that LLMs with limited parameters may not have enough abilities to perform repository-level code translation. CodeLlama-34B-Instruct only achieves one compilable translation, which fails to test successfully. This may be due to its



Fig. 6. Iterative debugging performance on RepoTransBench.

limited instruction following capabilities, making it difficult to understand the prompt and fail to generate code in the required format.

Compared to Llama-3.1-8B-Instruct, Llama-3.1-70B-Instruct achieves 3% on Success@3 and 6% on Build@3, while Llama-3.1-405B-Instruct performs better, achieving 4% and 10% respectively. These results indicate that LLMs with larger parameters may have more likelihood of generating both syntactically and functionally correct translations, which may be due to the stronger instruction following and code generation capabilities.

Finding 2: Earlier-released LLMs or smaller parameter LLMs, such as GPT-3.5-Turbo, CodeLlama-34B-Instruct, and Llama-3.1-8B-Instruct, may not have enough ability to generate executable repositories. While LLMs with larger parameters may have more likelihood of generating both syntactically and functionally correct repository code translations.

5.2 RQ2: Performance of Iterative Debugging

Figure 6 presents the iterative debugging performance of LLMs across five iterations. We observe an average 7.09% improvement on Success@1 across all LLMs. GPT-40 performs best on most metrics after five rounds of iterative debugging. Specifically, the Success@1 and Success@3 increase from 4% to 21% and from 8% to 34%, respectively. Notably, from the 3-th iteration of iterative debugging, GPT-40 surpasses Claude-3.5-Sonnet in all Success@k metrics, despite Claude-3.5-Sonnet being the best-performing LLM in the previous translation-only evaluation. This improvement is likely due to GPT-40's superior debugging capabilities, which allow it to refine and enhance its translations more effectively across iterations. Despite these improvements, the best-performing LLM, GPT-40, only achieves 21% on Success@1 and 34% on Success@3, respectively. This performance may indicate that current LLMs still cannot consistently achieve reliable repository-level code translation.



Fig. 7. The effect of code length and functional complexity. The light color (**•••**) represents the results of "*non-success/non-build*", while the dark color (**•••**) represents "*success/build*". In each subplot, the first two groups (**•••**) display the results of "*success/non-success*", while the last two groups (**•••**) show "*build/non-build*". To improve clarity, we've hidden some outliers, entries where <#Tokens, #Lines, #Functions, #Imports> exceed <8,000, 800, 80, 100> have been omitted.

Finding 3: LLMs can improve their performance on repository-level code translation through iterative debugging, leading to obtaining more executable and functionally correct repositories. Despite these advancements, all the LLMs still cannot consistently achieve reliable repository-level code translation. Besides, different backbone LLMs perform differently across tasks, with some excelling in translation and others showing stronger capabilities in debugging.

For open-source LLMs, DeepSeek-Coder-V2-Instruct performs the best. After five iterations, the Success@1 and Success@3 of DeepSeek-Coder-V2-Instruct achieve 17.71% and 25.00%, respectively, which even surpasses Claude-3.5-Sonnet, one of the latest closed-source LLM. The Build@1 score of DeepSeek-Coder-V2-Instruct stands at 54.86%, marking it as the best performer among all LLMs. Besides, DeepSeek-V2.5, the best-performing LLM among all open-source general LLMs, achieves 23% on Success@3 and 52% on Build@3, which surpasses some earlier-released closed-source LLMs, such as GPT-4 and GPT-3.5-Turbo-16k. These observations suggest that further training open-source LLMs may be a promising direction for future improvements, potentially enabling them to achieve even better performance, rivaling closed-source LLMs.

Finding 4: Through iterative debugging, some open-source LLMs can perform comparably to the latest closed-source LLMs. Further training of these open-source LLMs presents a promising direction for future improvements.

5.3 RQ3: Effect of Code Length and Functional Complexity

Figure 7 shows the effect of repository length and complexity on translation quality. We analyze the experiment results of both translation (Section 5.1, **— — —**) and iterative debugging phases (Section 5.2, **— — —**). It is evident that the median for *success/build* outcomes across almost all four complexity metrics is lower than the median for *non-success/non-build* outcomes for all the LLMs. This suggests that longer code length (with more #Tokens and #Lines) and higher functional complexity (with more #Functions and #Imports) may be more challenging for LLMs to translate or debug successfully. The increased code length and functional complexity lead to a higher likelihood of failure in generating executable and functional correct translations.

Finding 5: Longer code length and higher functional complexity repositories may be more difficult for LLMs to process, making it challenging to generate compilable and functional correct translations.

<pre><dependency></dependency></pre>	<pre>cplugins</pre>				
[ERROR] Could not resolve dependencies for project com.example:readtime-java:jar:1.0- SNAPSHOT: Could not find artifact com.github.rjeschke:txtmark:jar:0.16 in central	[ERROR] Source option 5 is no longer supported. Use 6 or later. [ERROR] Target option 1.5 is no longer supported. Use 1.6 or later.				
Fig. 8. Error Type 1: Configuration File Issues.					
<pre>public static String encodeUrl(int n, int min_length) {</pre>	E2.2 FMFTRLMachine learner = new FMFTRLMachine(fmDim, fmInitDev, L1, L2, L1Fm, L2Fm, D, alpha, beta, alphaFm, betaFm);				
[ERROR] src/main/java/ShortUrl.java:[45,19] method encodeUrl(int,int) is already defined in class ShortUrl	[ERROR] constructor FMFTRLMachine cannot be applied to given types; required: int.double.double.double.double.double.double.double.double.double.double				

Fig. 9. Error Type 2: Limited Understanding Ability Issues.

5.4 RQ4: Error Analysis

We conduct an error analysis across three rounds of experiments, ultimately identifying common errors in repository-level code translation. These errors are classified into five categories: E1 (Configuration File Issues), E2 (Limited Understanding Ability Issues), E3 (Incomplete Generation Issues), E4 (Language Feature Issues), E5 (Encoding Issues). Limited by the space, we provide two cases for each category.

E1. Configuration File Issues often arise due to the configuration file ("pom.xml" in a Java Maven project) related content not being configured correctly. Figure 8 (E1.1) shows an error due to an unresolved dependency as the artifact cannot be found in the central Maven repository [146]. Figure 8 (E1.2) shows that the current Java version is unsupported. This occurs as the Java version is not explicitly configured in the "pom.xml" file, the Maven project uses the default version 1.5, and this doesn't match the required version. Except for the two commonly occurring errors, we notice that some APIs are imported in the functional code files, but there is not a corresponding entry in the "pom.xml" configuration file. Some LLMs, especially those with limited instruction following capability, sometimes generate content that does not belong in the "pom.xml" file, leading to Leading to build failures.

Finding 6: Unlike fine-grained code translation works, repository-level code translation requires proper configuration of files such as the "pom.xml" file in Java Maven repositories. This can lead to dependency-related issues (e.g., non-existent dependencies, version mismatches, etc.). Solving these problems requires a clear understanding of the related calls and the latest dependencies.

E2. Limited Understanding Ability Issues usually arise due to unfamiliarity with the code context during translation. Figure 8 (E2.1) shows two methods with the same name and parameter type list, leading to a semantic conflict. These occur because the previously generated method is overlooked (which may be due to the long code length) when generating a new function. Figure 8 (E2.2) shows a function being called with incorrect argument types. This happens because the data types in the source language are dynamically defined, making it challenging to identify during translation. In addition to these examples, another error commonly occurring is due to a misunderstanding of the repository structure, leading to the incorrect imports of files or directories.

Finding 7: Due to the long code length and complex repository structure, a lack of understanding of the repository context may result in generating inappropriate code. To mitigate these issues, taking measures to enhance the focus on relevant context within the repository might be helpful.

E3. Incomplete Generation Issues often occur due to LLMs' limitation in instruction following and code generation abilities. Figure 10 (E3.1) shows an example where some LLMs may struggle to generate long code. Even though we prompt these LLMs to continue generating, their limited instruction following capability often causes them to restart the generation from the beginning and



<pre>private class UrlEncoder { } E4.1</pre>	<pre>public abstract class UnitNode { E4.2</pre>
<pre>public static String encodeUrl(int n, int min_length) { UrlEncoder encoder = new UrlEncoder(DEFAULT_ALPHABET, DEFAULT_BLOCK_SIZE);)</pre>	<pre>protected Position position; } root = new UnitNode(new Position("root", "", -1), 0, "");</pre>
[ERROR] src/main/java/ShortUrl.java:[36,30] non-static variable this cannot be referenced from a static context	[ERROR] src/main/java/Tree.java:[12,16] UnitNode is abstract; cannot be instantiated



E5.1 System.out.println(" Building image nytimes/blender:" + tag);	<pre>// checkin.json E5.2 "teaseText", "unlockText": "unlockText 👻"},</pre>
[ERROR] src/main/java/Build.java:[20,37] unmappable character (0xF0) for	[ERROR] src/test/java/TestSaveCheckin.java:[33,44] unmappable character
encoding US-ASCII	(0xF0) for encoding US-ASCII

Fig. 12. Error Type 5: Encoding Issues.

terminate around the same point again. Figure 10 (E3.2) shows an example where the LLM calls a package "Map" but the corresponding import statement is missing. This phenomenon often occurs when LLMs tend to generate example code while omitting elements they consider unimportant.

Finding 8: Some LLMs may struggle to continue generating due to the limited instruction following capability, and others may tend to generate example code with some elements omitted. These issues can be automatically identified by dependency analysis and syntax checking. Then we can fix these issues by regenerating or replacing them with stronger LLMs.

E4. Language Feature Issues occur frequently in repository-level code translation due to its Functional complexity. Figure 11 (E4.1) shows a case of accessing a non-static class from a static function, which is not allowed in Java language. Figure 11 (E4.2) is an example of instantiating an abstract class ("UnitNode"). However, abstract classes cannot be instantiated directly and must be extended by a subclass that provides implementations for the abstract methods in Java language. Another case is shown in Figure 5, which shows an issue of directly accessing a private member variable. Due to the differences between Python and Java language, it is important to understand the different language features. However, some LLMs may translate tokens from the source language to the target language sequentially while overlooking the specific features, leading to language feature issues that are not permissible in the target language.

Finding 9: When translating a repository to another language, some LLMs may lack sufficient understanding of language features, leading to related issues. Providing LLMs with more information about the language features in the prompt may help improve the translation performance.

E5. Encoding Issues occur due to incompatible repository encoding formats and can lead to issues when using special characters, such as emojis. An example is shown in Figure 12 (E5.1), where an error occurs due to using an emoji and US-ASCII encoding, which does not support certain characters. Figure 12 (E5.2) is another example showing that current encoding configuration does not support reading emojis from the resources. To resolve these errors, a possible solution is to make sure to use UTF-8 encoding in the "pom.xml" file.

Finding 10: Non-US-ASCII characters commonly occur in repositories, and encoding-related issues can sometimes arise when reading or writing resources. These problems can be resolved by configuring correct encoding format of the repository.

6 THREATS TO VALIDITY

Internal Threats. The first potential internal threat is the *scope of the tested LLMs*. In this paper, we evaluate 11 LLMs, including 8 general models and 3 code models. Due to the lack of large-scale, repository-level code translation datasets, we do not apply fine-tuning methods to these LLMs, which may impact their performance on certain tasks. In future work, we aim to fine-tune these models to achieve more accurate results. Additionally, this threat is mitigated to some extent, as the 3 code LLMs have already been fine-tuned on code-related tasks. Another potential threat is the *selection of programming languages*. We only evaluate Python and Java, and the results may differ for other languages. However, since these two languages are the most widely used languages, our benchmark and findings remain important for evaluating LLM performance in this task. Furthermore, in the future, we plan to apply the method proposed in this paper to other programming languages to extend our benchmark and findings.

External Threats. The first external threat is the *uncertainty in LLM output*. In Section 4.5, we evaluate LLMs' performance using their outputs from the generations in the translation and debugging phases. However, the generations may not represent the real performance of LLMs due to the uncertainty in generation. To mitigate this threat, we perform three rounds of experiments under the same settings, ensuring that our findings are obtained from consistent performance rather than isolated instances. Another potential threat is the *evaluation of translated code quality*. In Section 5, we use the test cases translated from the source repositories to test the translated repositories. However, even if the translations pass all the test cases, they could still have poor quality in terms of readability and maintainability. Nevertheless, ensuring executability and functional correctness is a foundational step toward achieving automatic code translation. Besides, we use test cases from real-world repositories to evaluate the basic quality. In the future, we plan to incorporate additional evaluations from various aspects.

7 RELATED WORK

Many Benchmarks have been introduced to compare the performance of different translation techniques objectively. CoST [29] and XLCost [30] introduce a snippet and function-level code translation benchmark. CodeXGLUE [32] includes a dataset for function-level Java-C# code translation. TransCoder-test is the evaluation dataset for TransCoder [31], which includes the function-level code translation on Python, Java, and C++. Some other benchmarks like HumanEval-X [33] and EvalPlus [34] source from HumanEval [103] to construct a function-level code translation benchmark. G-TransEval [113] provides a more fine-grained taxonomy, including token-level, syntax-level, library-level, and algorithm-level, which is part of a function. CodeNet [35], Avatar [36], xCodeEval [105] CodeScope [37] and CodeTransOcean [38] introduce file-level code translation benchmarks which source from code contest platforms like codeforces [106], atcoder [107], aizu [108], Google Code Jam [109], etc. or task solutions websites like samples from .Net [110], d2lai [111], rosetta code [112], etc. Although these benchmarks can evaluate the capabilities of existing code translation techniques to some extent, they cannot evaluate the performance of current techniques on real-world repository-level code translation tasks. Recently, pan et al. [1] manually study two open-source repositories (Apache Commons CLI [39] and Python Click [40]) and find that current LLMs struggle to complete the translation tasks of entire repositories. However, they do not provide a sufficient number of repositories and corresponding automatic test suites for evaluation. Besides, the resource and configuration files are ignored in this research.

8 CONCLUSION

In this paper, we provide a comparison of code translation granularity, introducing the differences between repository-level code translation and previous benchmarks. We collect real-world repositories from *The Stack* and *The Stack v2* to build RepoTransBench. Moreover, we conduct an experiment with 8 advanced general LLMs and 3 code LLMs to evaluate the translation abilities on RepoTransBench. To further explore the possibility of LLMs in repository-level code translation, we provide error-related feedback to the LLMs and observe improvements across all the LLMs after iterative debugging. We also conduct a detailed error analysis. Our work highlights current LLMs' deficiencies in repository-level code translation and suggests directions for future improvement.

REFERENCES

- R. Pan, A. R. Ibrahimzada, R. Krishna, D. Sankar, L. P. Wassi, M. Merler, B. Sobolev, R. Pavuluri, S. Sinha, and R. Jabbarvand, "Lost in translation: A study of bugs introduced by large language models while translating code," in Proceedings of the IEEE/ACM 46th International Conference on Software Engineering, 2024, pp. 1–13.
- [2] Q. Sun, Z. Chen, F. Xu, K. Cheng, C. Ma, Z. Yin, J. Wang, C. Han, R. Zhu, S. Yuan et al., "A survey of neural code intelligence: Paradigms, advances and beyond," <u>arXiv preprint arXiv:2403.14734</u>, 2024.
- [3] H. F. Eniser, H. Zhang, C. David, M. Wang, B. Paulsen, J. Dodds, and D. Kroening, "Towards translating real-world code with llms: A study of translating to rust," <u>arXiv preprint arXiv:2405.11514</u>, 2024.
- [4] S. Dou, H. Jia, S. Wu, H. Zheng, W. Zhou, M. Wu, M. Chai, J. Fan, C. Huang, Y. Tao <u>et al.</u>, "What's wrong with your code generated by large language models? an extensive study," arXiv preprint arXiv:2407.06153, 2024.
- [5] K. Aggarwal, M. Salameh, and A. Hindle, "Using machine translation for converting python 2 to python 3 code," PeerJ PrePrints, Tech. Rep., 2015.
- [6] M. Szafraniec, B. Roziere, H. Leather, F. Charton, P. Labatut, and G. Synnaeve, "Code translation with compiler representations," arXiv preprint arXiv:2207.03578, 2022.
- [7] A. T. Nguyen, T. T. Nguyen, and T. N. Nguyen, "Lexical statistical machine translation for language migration," in Proceedings of the 2013 9th Joint Meeting on Foundations of Software Engineering, 2013, pp. 651–654.
- [8] --, "Migrating code with statistical machine translation," in <u>Companion Proceedings of the 36th International</u> <u>Conference on Software Engineering</u>, 2014, pp. 544–547.
- [9] M. Mossienko, "Automated cobol to java recycling," in <u>Seventh European Conference onSoftware Maintenance and</u> <u>Reengineering</u>, 2003. Proceedings. IEEE, 2003, pp. 40–50.
- [10] A. E. Hassan and R. C. Holt, "A lightweight approach for migrating web frameworks," <u>Information and Software</u> Technology, vol. 47, no. 8, pp. 521–532, 2005.
- [11] T. T. Bartolomei, K. Czarnecki, and R. Lämmel, "Swing to swt and back: Patterns for api migration by wrapping," in 2010 IEEE International Conference on Software Maintenance. IEEE, 2010, pp. 1–10.
- [12] H. Zhong, S. Thummalapenta, T. Xie, L. Zhang, and Q. Wang, "Mining api mapping for language migration," in Proceedings of the 32nd ACM/IEEE International Conference on Software Engineering-Volume 1, 2010, pp. 195–204.
- [13] A. T. Nguyen, H. A. Nguyen, T. T. Nguyen, and T. N. Nguyen, "Statistical learning approach for mining api usage mappings for code migration," in <u>Proceedings of the 29th ACM/IEEE international conference on Automated software</u> engineering, 2014, pp. 457–468.
- [14] X. Gu, H. Zhang, D. Zhang, and S. Kim, "Deepam: Migrate apis with multi-modal sequence to sequence learning," arXiv preprint arXiv:1704.07734, 2017.
- [15] Y. Xie, A. Naik, D. Fried, and C. Rose, "Data augmentation for code translation with comparable corpora and multiple references," arXiv preprint arXiv:2311.00317, 2023.
- [16] S. Ren, D. Guo, S. Lu, L. Zhou, S. Liu, D. Tang, N. Sundaresan, M. Zhou, A. Blanco, and S. Ma, "Codebleu: a method for automatic evaluation of code synthesis," arXiv preprint arXiv:2009.10297, 2020.
- [17] D. Bahdanau, "Neural machine translation by jointly learning to align and translate," <u>arXiv preprint arXiv:1409.0473</u>, 2014.
- [18] X. Chen, C. Liu, and D. Song, "Tree-to-tree neural networks for program translation," <u>Advances in neural information</u> processing systems, vol. 31, 2018.
- [19] M. Artetxe, G. Labaka, and E. Agirre, "Unsupervised statistical machine translation," <u>arXiv preprint arXiv:1809.01272</u>, 2018.
- [20] J. Devlin, "Bert: Pre-training of deep bidirectional transformers for language understanding," <u>arXiv preprint</u> <u>arXiv:1810.04805</u>, 2018.
- [21] Z. Feng, D. Guo, D. Tang, N. Duan, X. Feng, M. Gong, L. Shou, B. Qin, T. Liu, D. Jiang et al., "Codebert: A pre-trained model for programming and natural languages," arXiv preprint arXiv:2002.08155, 2020.

- [22] D. Guo, S. Ren, S. Lu, Z. Feng, D. Tang, S. Liu, L. Zhou, N. Duan, A. Svyatkovskiy, S. Fu et al., "Graphcodebert: Pre-training code representations with data flow," arXiv preprint arXiv:2009.08366, 2020.
- [23] W. U. Ahmad, S. Chakraborty, B. Ray, and K.-W. Chang, "Unified pre-training for program understanding and generation," arXiv preprint arXiv:2103.06333, 2021.
- [24] D. Guo, S. Lu, N. Duan, Y. Wang, M. Zhou, and J. Yin, "Unixcoder: Unified cross-modal pre-training for code representation," arXiv preprint arXiv:2203.03850, 2022.
- [25] Q. Zheng, X. Xia, X. Zou, Y. Dong, S. Wang, Y. Xue, L. Shen, Z. Wang, A. Wang, Y. Li et al., "Codegeex: A pre-trained model for code generation with multilingual benchmarking on humaneval-x," in <u>Proceedings of the 29th ACM</u> <u>SIGKDD Conference on Knowledge Discovery and Data Mining</u>, 2023, pp. 5673–5684.
- [26] Z. Yang, F. Liu, Z. Yu, J. W. Keung, J. Li, S. Liu, Y. Hong, X. Ma, Z. Jin, and G. Li, "Exploring and unleashing the power of large language models in automated code translation," <u>Proceedings of the ACM on Software Engineering</u>, vol. 1, no. FSE, pp. 1585–1608, 2024.
- [27] K. Lano and H. Siala, "Using model-driven engineering to automate software language translation," <u>Automated</u> Software Engineering, vol. 31, no. 1, p. 20, 2024.
- [28] V. Nitin and B. Ray, "Spectra: Enhancing the code translation ability of language models by generating multi-modal specifications," arXiv preprint arXiv:2405.18574, 2024.
- [29] M.-Y. Zhu, K. Suresh, and C. K. Reddy, "Multilingual code snippets training for program translation," in <u>AAAI</u> <u>Conference on Artificial Intelligence</u>, 2022. [Online]. Available: https://api.semanticscholar.org/CorpusID:245216916
- [30] M. Zhu, A. Jain, K. Suresh, R. Ravindran, S. Tipirneni, and C. K. Reddy, "Xlcost: A benchmark dataset for cross-lingual code intelligence," arXiv preprint arXiv:2206.08474, 2022.
- [31] M.-A. Lachaux, B. Roziere, L. Chanussot, and G. Lample, "Unsupervised translation of programming languages," <u>arXiv</u> preprint arXiv:2006.03511, 2020.
- [32] S. Lu, D. Guo, S. Ren, J. Huang, A. Svyatkovskiy, A. Blanco, C. Clement, D. Drain, D. Jiang, D. Tang et al., "Codexglue: A machine learning benchmark dataset for code understanding and generation," <u>arXiv preprint arXiv:2102.04664</u>, 2021.
- [33] "humaneval-x," https://huggingface.co/datasets/THUDM/humaneval-x, 2022.
- [34] J. Liu, C. S. Xia, Y. Wang, and L. Zhang, "Is your code generated by chatgpt really correct? rigorous evaluation of large language models for code generation," Advances in Neural Information Processing Systems, vol. 36, 2024.
- [35] R. Puri, D. S. Kung, G. Janssen, W. Zhang, G. Domeniconi, V. Zolotov, J. Dolby, J. Chen, M. Choudhury, L. Decker et al., "Codenet: A large-scale ai for code dataset for learning a diversity of coding tasks," <u>arXiv preprint arXiv:2105.12655</u>, 2021.
- [36] W. U. Ahmad, M. G. R. Tushar, S. Chakraborty, and K.-W. Chang, "Avatar: A parallel corpus for java-python program translation," arXiv preprint arXiv:2108.11590, 2021.
- [37] W. Yan, H. Liu, Y. Wang, Y. Li, Q. Chen, W. Wang, T. Lin, W. Zhao, L. Zhu, S. Deng et al., "Codescope: An executionbased multilingual multitask multidimensional benchmark for evaluating llms on code understanding and generation," arXiv preprint arXiv:2311.08588, 2023.
- [38] W. Yan, Y. Tian, Y. Li, Q. Chen, and W. Wang, "Codetransocean: A comprehensive multilingual benchmark for code translation," arXiv preprint arXiv:2310.04951, 2023.
- [39] "Apache commons cli," https://commons.apache.org/proper/commons-cli/, 2023.
- [40] "Click," https://click.palletsprojects.com/en/8.1.x/, 2023.
- [41] "maven," https://maven.apache.org/, 2024.
- [42] "the-stack," https://huggingface.co/datasets/bigcode/the-stack, 2023.
- [43] "the-stack-v2," https://huggingface.co/datasets/bigcode/the-stack-v2, 2024.
- [44] R. Li, L. B. Allal, Y. Zi, N. Muennighoff, D. Kocetkov, C. Mou, M. Marone, C. Akiki, J. Li, J. Chim et al., "Starcoder: may the source be with you!" arXiv preprint arXiv:2305.06161, 2023.
- [45] A. Lozhkov, R. Li, L. B. Allal, F. Cassano, J. Lamy-Poirier, N. Tazi, A. Tang, D. Pykhtar, J. Liu, Y. Wei et al., "Starcoder 2 and the stack v2: The next generation," <u>arXiv preprint arXiv:2402.19173</u>, 2024.
- [46] "Tiobe-index," https://www.tiobe.com/tiobe-index/, 2024.
- [47] Meta, "Llama-3.1-8b-instruct," https://huggingface.co/meta-llama/Meta-Llama-3.1-8B-Instruct, 2024.
- [48] "Antlr," https://www.antlr.org/, 2024.
- [49] "Babel," https://babeljs.io/, 2024.
- [50] "Emscripten," https://emscripten.org/, 2024.
- [51] "Jsweet," https://www.jsweet.org/, 2024.
- [52] "Gwt," https://www.gwtproject.org/overview.html, 2024.
- [53] "Cxgo," https://github.com/gotranspile/cxgo, 2024.
- [54] "c2rust," https://github.com/immunant/c2rust, 2024.
- [55] "Javatocsharp," https://github.com/paulirwin/JavaToCSharp, 2024.

, Vol. 1, No. 1, Article . Publication date: December 2024.

- [56] "Haxe," https://haxe.org/, 2024.
- [57] "Swig," https://swig.org/, 2024.
- [58] Y. Wang, W. Zhong, Y. Huang, E. Shi, M. Yang, J. Chen, H. Li, Y. Ma, Q. Wang, and Z. Zheng, "Agents in software engineering: Survey, landscape, and vision," arXiv preprint arXiv:2409.09030, 2024.
- [59] Z. Zhang, Y. Wang, C. Wang, J. Chen, and Z. Zheng, "Llm hallucinations in practical code generation: Phenomena, mechanism, and mitigation," 2024. [Online]. Available: https://arxiv.org/abs/2409.20550
- [60] Y. Wang, Y. Wang, D. Guo, J. Chen, R. Zhang, Y. Ma, and Z. Zheng, "Rlcoder: Reinforcement learning for repository-level code completion," 2024. [Online]. Available: https://arxiv.org/abs/2407.19487
- [61] W. Tao, Y. Zhou, Y. Wang, W. Zhang, H. Zhang, and Y. Cheng, "Magis: Llm-based multi-agent framework for github issue resolution," 2024. [Online]. Available: https://arxiv.org/abs/2403.17927
- [62] L. Guo, Y. Wang, E. Shi, W. Zhong, H. Zhang, J. Chen, R. Zhang, Y. Ma, and Z. Zheng, "When to stop? towards efficient code generation in llms with excess token prevention," 2024. [Online]. Available: https://arxiv.org/abs/2407.20042
- [63] J. Chen, C. Chen, J. Hu, J. Grundy, Y. Wang, T. Chen, and Z. Zheng, "Identifying smart contract security issues in code snippets from stack overflow," in <u>Proceedings of the 33rd ACM SIGSOFT International Symposium</u> <u>on Software Testing and Analysis</u>, ser. ISSTA '24. ACM, Sep. 2024, p. 1198–1210. [Online]. Available: <u>http://dx.doi.org/10.1145/3650212.3680353</u>
- [64] J. Chen, Q. Zhong, Y. Wang, K. Ning, Y. Liu, Z. Xu, Z. Zhao, T. Chen, and Z. Zheng, "Rmcbench: Benchmarking large language models' resistance to malicious code," in <u>Proceedings of the 39th IEEE/ACM International</u> <u>Conference on Automated Software Engineering</u>, ser. ASE '24. ACM, Oct. 2024, p. 995–1006. [Online]. Available: <u>http://dx.doi.org/10.1145/3691620.3695480</u>
- [65] Y. Wang, T. Jiang, M. Liu, J. Chen, and Z. Zheng, "Beyond functional correctness: Investigating coding style inconsistencies in large language models," 2024. [Online]. Available: https://arxiv.org/abs/2407.00456
- [66] J. Zhang, Y. Shen, J. Chen, J. Su, Y. Wang, T. Chen, J. Gao, and Z. Chen, "Demystifying and detecting cryptographic defects in ethereum smart contracts," 2024. [Online]. Available: https://arxiv.org/abs/2408.04939
- [67] S. Yang, X. Lin, J. Chen, Q. Zhong, L. Xiao, R. Huang, Y. Wang, and Z. Zheng, "Hyperion: Unveiling dapp inconsistencies using llm and dataflow-guided symbolic execution," 2024. [Online]. Available: https://arxiv.org/abs/2408.06037
- [68] J. Gong, Y. Wu, L. Liang, Z. Zheng, and Y. Wang, "Cosqa+: Enhancing code search dataset with matching code," 2024. [Online]. Available: https://arxiv.org/abs/2406.11589
- [69] W. Bi, L. Du, Q. Fu, Y. Wang, S. Han, and D. Zhang, "Make heterophily graphs better fit gnn: A graph rewiring approach," 2022. [Online]. Available: https://arxiv.org/abs/2209.08264
- [70] F. Hu, Y. Wang, L. Du, H. Zhang, S. Han, D. Zhang, and X. Li, "Tackling long code search with splitting, encoding, and aggregating," 2024. [Online]. Available: https://arxiv.org/abs/2208.11271
- [71] Y. Liu, J. Chen, T. Bi, J. Grundy, Y. Wang, J. Yu, T. Chen, Y. Tang, and Z. Zheng, "An empirical study on low code programming using traditional vs large language model support," 2024. [Online]. Available: https://arxiv.org/abs/2402.01156
- [72] W. Tao, Y. Zhou, Y. Wang, H. Zhang, H. Wang, and W. Zhang, "Kadel: Knowledge-aware denoising learning for commit message generation," 2024. [Online]. Available: https://arxiv.org/abs/2401.08376
- [73] Y. Wang, Y. Huang, D. Guo, H. Zhang, and Z. Zheng, "Sparsecoder: Identifier-aware sparse transformer for file-level code summarization," 2024. [Online]. Available: https://arxiv.org/abs/2401.14727
- [74] J. Zhou, W. Zhong, Y. Wang, and J. Wang, "Adaptive-solver framework for dynamic strategy selection in large language model reasoning," 2023. [Online]. Available: https://arxiv.org/abs/2310.01446
- [75] E. Shi, F. Zhang, Y. Wang, B. Chen, L. Du, H. Zhang, S. Han, D. Zhang, and H. Sun, "Sotana: The open-source software development assistant," 2023. [Online]. Available: https://arxiv.org/abs/2308.13416
- [76] Z. Zheng, K. Ning, Y. Wang, J. Zhang, D. Zheng, M. Ye, and J. Chen, "A survey of large language models for code: Evolution, benchmarking, and future trends," 2024. [Online]. Available: https://arxiv.org/abs/2311.10372
- [77] C. Chen, J. Su, J. Chen, Y. Wang, T. Bi, J. Yu, Y. Wang, X. Lin, T. Chen, and Z. Zheng, "When chatgpt meets smart contract vulnerability detection: How far are we?" 2024. [Online]. Available: https://arxiv.org/abs/2309.05520
- [78] E. Shi, Y. Wang, H. Zhang, L. Du, S. Han, D. Zhang, and H. Sun, "Towards efficient fine-tuning of pre-trained code models: An experimental study and beyond," 2023. [Online]. Available: https://arxiv.org/abs/2304.05216
- [79] K. Ning, J. Chen, Q. Zhong, T. Zhang, Y. Wang, W. Li, Y. Zhang, W. Zhang, and Z. Zheng, "Mcgmark: An encodable and robust online watermark for llm-generated malicious code," 2024. [Online]. Available: https://arxiv.org/abs/2408.01354
- [80] Z. Zheng, K. Ning, Q. Zhong, J. Chen, W. Chen, L. Guo, W. Wang, and Y. Wang, "Towards an understanding of large language models in software engineering tasks," 2024. [Online]. Available: https://arxiv.org/abs/2308.11396
- [81] Y. Wang, W. Wang, S. Joty, and S. C. Hoi, "Codet5: Identifier-aware unified pre-trained encoder-decoder models for code understanding and generation," arXiv preprint arXiv:2109.00859, 2021.
- [82] P. Koehn, H. Hoang, A. Birch, C. Callison-Burch, M. Federico, N. Bertoldi, B. Cowan, W. Shen, C. Moran, R. Zens et al., "Moses: Open source toolkit for statistical machine translation," in Proceedings of the 45th annual meeting

of the association for computational linguistics companion volume proceedings of the demo and poster sessions. Association for Computational Linguistics, 2007, pp. 177–180.

- [83] H. Zheng, Y. Cheng, and Y. Liu, "Maximum expected likelihood estimation for zero-resource neural machine translation." in <u>IJCAI</u>, 2017, pp. 4251–4257.
- [84] M. Chen, J. Tworek, H. Jun, Q. Yuan, H. P. D. O. Pinto, J. Kaplan, H. Edwards, Y. Burda, N. Joseph, G. Brockman et al., "Evaluating large language models trained on code," arXiv preprint arXiv:2107.03374, 2021.
- [85] E. Nijkamp, B. Pang, H. Hayashi, L. Tu, H. Wang, Y. Zhou, S. Savarese, and C. Xiong, "Codegen: An open large language model for code with multi-turn program synthesis," arXiv preprint arXiv:2203.13474, 2022.
- [86] L. B. Allal, R. Li, D. Kocetkov, C. Mou, C. Akiki, C. M. Ferrandis, N. Muennighoff, M. Mishra, A. Gu, M. Dey et al., "Santacoder: don't reach for the stars!" arXiv preprint arXiv:2301.03988, 2023.
- [87] H. Touvron, T. Lavril, G. Izacard, X. Martinet, M.-A. Lachaux, T. Lacroix, B. Rozière, N. Goyal, E. Hambro, F. Azhar et al., "Llama: Open and efficient foundation language models," arXiv preprint arXiv:2302.13971, 2023.
- [88] H. Touvron, L. Martin, K. Stone, P. Albert, A. Almahairi, Y. Babaei, N. Bashlykov, S. Batra, P. Bhargava, S. Bhosale et al., "Llama 2: Open foundation and fine-tuned chat models," arXiv preprint arXiv:2307.09288, 2023.
- [89] A. Dubey, A. Jauhri, A. Pandey, A. Kadian, A. Al-Dahle, A. Letman, A. Mathur, A. Schelten, A. Yang, A. Fan et al., "The llama 3 herd of models," <u>arXiv preprint arXiv:2407.21783</u>, 2024.
- [90] OpenAI, "Gpt-4 technical report," 2023.
- [91] DeepSeek-AI, "Deepseek-v2: A strong, economical, and efficient mixture-of-experts language model," 2024.
- [92] Anthropic, "The claude 3 model family: Opus, sonnet, haiku." [Online]. Available: https://api.semanticscholar.org/ CorpusID:268232499
- [93] X. Yin, C. Ni, T. N. Nguyen, S. Wang, and X. Yang, "Rectifier: Code translation with corrector via llms," <u>arXiv preprint</u> arXiv:2407.07472, 2024.
- [94] A. Z. Yang, Y. Takashima, B. Paulsen, J. Dodds, and D. Kroening, "Vert: Verified equivalent rust transpilation with few-shot learning," arXiv preprint arXiv:2404.18852, 2024.
- [95] M. Bhattarai, J. E. Santos, S. Jones, A. Biswas, B. Alexandrov, and D. O'Malley, "Enhancing code translation in language models with few-shot learning via retrieval-augmented generation," <u>arXiv preprint arXiv:2407.19619</u>, 2024.
- [96] Z. Yuan, W. Chen, H. Wang, K. Yu, X. Peng, and Y. Lou, "Transagent: An llm-based multi-agent system for code translation," arXiv preprint arXiv:2409.19894, 2024.
- [97] M. Shiraishi and T. Shinagawa, "Context-aware code segmentation for c-to-rust translation using large language models," arXiv preprint arXiv:2409.10506, 2024.
- [98] R. Karanjai, L. Xu, and W. Shi, "Teaching machines to code: Smart contract translation with llms," <u>arXiv preprint</u> arXiv:2403.09740, 2024.
- [99] "solidity," https://soliditylang.org/, 2024.
- [100] "move," https://github.com/move-language/move, 2024.
- [101] W. Yang, Y. Guo, and Y. Xue, "Cctrans: A java-to-javascript translation with concurrency runtime," 2024.
- [102] M. S. Abid, M. Pawagi, S. Adhikari, X. Cheng, R. Badr, M. Wahiduzzaman, V. Rathi, R. Qi, C. Li, L. Liu10 et al., "Gluetest: Testing code translation via language interoperability."
- [103] M. Chen, J. Tworek, H. Jun, Q. Yuan, H. P. D. O. Pinto, J. Kaplan, H. Edwards, Y. Burda, N. Joseph, G. Brockman <u>et al.</u>, "Evaluating large language models trained on code," arXiv preprint arXiv:2107.03374, 2021.
- [104] "geeksforgeeks," https://www.geeksforgeeks.org/, 2024.
- [105] M. A. M. Khan, M. S. Bari, X. L. Do, W. Wang, M. R. Parvez, and S. Joty, "xcodeeval: A large scale multilingual multitask benchmark for code understanding, generation, translation and retrieval," <u>arXiv preprint arXiv:2303.03004</u>, 2023.
- [106] "Codeforces," https://codeforces.com/, 2024.
- [107] "atcoder," https://atcoder.jp/, 2024.
- [108] "aizu," https://onlinejudge.u-aizu.ac.jp, 2024.
- [109] "Googlecodejam," https://codingcompetitionsonair.withgoogle.com/, 2024.
- [110] "dotnetsamples," https://learn.microsoft.com/en-us/samples/dotnet/try-samples/101-linqsamples/, 2024.
- [111] "d2lai," https://github.com/d2l-ai/d2l-zh, 2024.
- [112] "rosettacode," https://rosettacode.org/wiki/Rosetta_Code, 2024.
- [113] M. Jiao, T. Yu, X. Li, G. Qiu, X. Gu, and B. Shen, "On the evaluation of neural code translation: Taxonomy and benchmark," in <u>2023 38th IEEE/ACM International Conference on Automated Software Engineering (ASE)</u>. IEEE, 2023, pp. 1529–1541.
- [114] "Hugging-face," https://huggingface.co/, 2024.
- [115] "github-rest-api," https://docs.github.com/en/rest, 2024.
- [116] "git," https://github.com/git-guides, 2024.
- [117] "pytorch," https://pytorch.org/, 2024.
- [118] "tensorflow," https://www.tensorflow.org/, 2024.

- [119] "nltk," https://www.nltk.org/, 2024.
- [120] "scikit-learn," https://scikit-learn.org/stable/index.html, 2024.
- [121] "jupyter," https://jupyter.org/, 2024.
- [122] "seaborn," https://seaborn.pydata.org/, 2024.
- [123] "matplotlib," https://matplotlib.org/, 2024.
- [124] "numpy," https://numpy.org/, 2024.
- [125] Openai, "gpt-3-5-turbo," https://platform.openai.com/docs/models, 2023.
- [126] ---, "gpt-4o," https://platform.openai.com/docs/models, 2024.
- [127] "Leetcode," https://leetcode.com/, 2024.
- [128] "Projecteuler," https://projecteuler.net/, 2024.
- [129] "tree-sitter," https://tree-sitter.github.io/, 2024.
- [130] Meta, "Llama-3.1-70b-instruct," https://huggingface.co/meta-llama/Meta-Llama-3.1-70B-Instruct, 2024.
- $[131] \ --, ``Llama-3.1-405b-instruct, ``https://huggingface.co/meta-llama/Meta-Llama-3.1-405B-Instruct, 2024.$
- [132] Openai, "gpt-4-0125-preview," https://platform.openai.com/docs/models, 2024.
- [133] Anthropic, "claude-3-5-sonnet," https://www.anthropic.com/news/claude-3-5-sonnet, 2024.
- $[134] \ ``Codellama-34b-instruct," https://huggingface.co/meta-llama/CodeLlama-34b-Instruct-hf, 2024.$
- [135] "Codestral-22b," https://huggingface.co/mistralai/Codestral-22B-v0.1, 2024.
- [136] "Deepseek-coder-v2-instruct," https://huggingface.co/deepseek-ai/DeepSeek-Coder-V2-Instruct, 2024.
- [137] "deepseekwebpage," https://www.deepseek.com/en, 2024.
- [138] K. Papineni, S. Roukos, T. Ward, and W.-J. Zhu, "Bleu: a method for automatic evaluation of machine translation," in Proceedings of the 40th annual meeting of the Association for Computational Linguistics, 2002, pp. 311–318.
- [139] S. Karaivanov, V. Raychev, and M. Vechev, "Phrase-based statistical translation of programming languages," in Proceedings of the 2014 ACM international symposium on new ideas, new paradigms, and reflections on programming & software, 2014, pp. 173–184.
- [140] A. V. M. Barone and R. Sennrich, "A parallel corpus of python functions and documentation strings for automated code documentation and code generation," <u>arXiv preprint arXiv:1707.02275</u>, 2017.
- [141] "docker," https://www.docker.com/, 2024.
- [142] "python27," https://www.python.org/download/releases/2.7/, 2024.
- [143] "python310," https://www.python.org/downloads/release/python-3100/, 2024.
- [144] "pip," https://pypi.org/project/pip/, 2024.
- [145] "jdk11," https://www.oracle.com/cn/java/technologies/javase/jdk11-archive-downloads.html, 2024.
- [146] "maven2centerwebpage," https://repo.maven.apache.org/maven2, 2024.