Hiding, Shuffling, and Triangle Finding

Quantum Algorithms on Edge Lists

Amin Shiraz Gilani[∗] Daochen Wang† Pei Wu‡ Xingyu Zhou§

Abstract

The edge list model is arguably the simplest input model for graphs, where the graph is specified by a list of its edges. In this model, we study the quantum query complexity of three variants of the triangle finding problem. The first asks whether there exists a triangle containing a target edge and raises general questions about the *hiding* of a problem's input among irrelevant data. The second asks whether there exists a triangle containing a target vertex and raises general questions about the shuffling of a problem's input. The third asks for finding a triangle in the input edge list; this problem bridges the 3-distinctness and 3-sum problems, which have been extensively studied by both cryptographers and complexity theorists. We provide tight or nearly tight results for all of our problems as well as some first answers to the general questions they raise. In particular, given a graph with low maximum degree, such as a random sparse graph, we prove that the quantum query complexity of triangle finding in its length-m edge list is $m^{5/7\pm o(1)}$. We prove the lower bound in Zhandry's recording query framework [\[Zha19\]](#page-52-0) and the upper bound by adapting Belovs's learning graph algorithm for 3 distinctness [\[Bel12b\]](#page-50-0).

Contents

[∗]University of Maryland. asgilani@umd.edu

[†]University of British Columbia. wdaochen@gmail.com

[‡]The Pennsylvania State University. pei.wu@psu.edu

[§]University of British Columbia. zxingyu@cs.ubc.ca

1 Introduction

The study of graph problems forms a cornerstone of research in theoretical computer science. These problems have been studied when the input data structure is the adjacency matrix or adjacency list of the graph [\[Gol10,](#page-50-1) [KY14,](#page-51-0) [AF15,](#page-49-1) BCG^+20 BCG^+20]. In the adjacency matrix model of an *n*-vertex undirected simple graph, one is given the presence or absence status of every one of the $\binom{n}{2}$ $\binom{n}{2}$ edges in an $n \times n$ binary matrix. In the adjacency list model, the input is given as n lists of neighbors, one for each of the n vertices. In this work, we study graph problems in an alternative but arguably the simplest model, the edge list model. The edge list of a graph is simply the list of its edges given without any particular ordering and possibly with repetitions. An edge list is a less stringent data structure than the adjacency list in that the edges are not ordered according to which vertex they are incident to. Put another way, the edge list can be seen as the adjacency list but with possible shuffling. To illustrate, the following edge list and adjacency list inputs specify the same graph on four vertices.

In this work, we study the edge list model in the context of quantum query complexity. In quantum query complexity, we assume access to a quantum computer and characterize the complexity of a problem by the number of times the computer queries a black box encoding the input, which will be the edge list of a graph in this work. The edge list model has been studied in classical algorithm design, often under different guises. For instance, it has been studied in the context of approximation algorithms, property testing given random samples, and streaming algorithms under space constraints [\[Kar94,](#page-51-1) [GGR98,](#page-50-2) [AF15\]](#page-49-1).

Quantum versions of these results exist, notably in the area of streaming algorithms. For example, [\[Kal22\]](#page-51-2) showed that triangle counting can be solved by a quantum streaming algorithm using less space than any classical rival. However, the quantum computational model employed differs significantly from the quantum query model that we study. In the former case, the edge list is still queried classically only the memory is quantum — whereas we assume the edge list can be queried in quantum superposition. As we will see in this work, this change of model leads to new and interesting questions.

Historically, the triangle problem in the adjacency matrix model has been a breeding ground for innovations in quantum algorithm design and lower bound techniques (see, e.g., [\[MSS07,](#page-52-1) [Bel12b,](#page-50-0) [JKM13,](#page-51-3) [LMS13,](#page-51-4) [Le 14\]](#page-51-5)). This motivates us to study the triangle problem in the edge list model. More specifically, we study three variants of the triangle problem. While these problems are interesting in their own right, we find them even more interesting as windows into general questions concerning the relationship between a problem's structure and complexity.

- **TriangleEdge** asks whether there exists a triangle containing a target edge and raises general questions about how a problem's complexity increases if its input is hidden among irrelevant data. For the specific problem, the irrelevant data consists of those edges in the input that are not incident to the target edge.
- **TriangleVertex** asks whether there exists a triangle containing a target vertex and raises general questions about how a problem's complexity increases if its input is shuffled. For the specific problem, two parts of the input are shuffled: one part containing edges incident to the target vertex and the other part containing the remaining edges. The notion of shuffling is also inherent in the comparison between the edge list and adjacency list models.
- **F** FTriangle asks for finding a triangle. FTriangle bridges the 3-distinctness and 3-sum problems. The latter problems have been extensively studied, both in the worst-case setting by complexity theorists seeking to better understand problem structure [\[Bel12b,](#page-50-0) [BS13,](#page-50-3) [BCJ](#page-49-3)+13, [BR14\]](#page-50-4) and in the averagecase setting by cryptographers seeking to undergird the security of cryptosystems [\[Wag02,](#page-52-2) [LZ19\]](#page-51-6).

We provide tight or nearly tight results for all of our problems as well as some first answers to the general questions they raise.

1.1 Our results

In the following, we write $Q(\cdot)$ for the worst-case (bounded-error) quantum query complexity and $[n] :=$ $\{1, \ldots, n\}$ for any positive integer n.

TriangleEdge and Hiding. In TriangleEdge, when searching for a triangle containing a target edge $\{u, v\}$, any edge in the input of the form $\{u', v'\}$ such that $\{u', v'\} \cap \{u, v\} = \emptyset$ can be viewed as irrelevant data that hides the relevant part of the input. This observation motivates a general definition of hiding.

Definition 1.1 (Hiding transform). Given integers $b \ge a \ge 1$ and a function $f: \widetilde{D} \subseteq \Sigma^a \to \{0,1\}$, we define the hiding transform of f to be

$$
\text{HIDE}_b[f]: D \subseteq (\Sigma \cup \{*\})^b \to \{0, 1\},\tag{1.1}
$$

where * is a symbol outside of Σ , D contains all strings $y \in (\Sigma \cup \{*\})^b$ with exactly a non-* symbols, and HIDE_b[f](y) is defined to be $f(\tilde{y})$, where \tilde{y} is the length-a subsequence of y containing y's a non-* symbols (in the same order as they appear in y).^{[1](#page-2-1)}

Then TriangleEdge can be seen as $HIDE_m[ED_d]$, where ED_d is the element distinctness function that decides whether an input string of length d has two distinct positions containing the same symbol. We show the following.^{[2](#page-2-2)}

Theorem 1.2 (Informal version of [Theorem 3.5](#page-11-0) and [Corollary 3.7\)](#page-12-0). $Q(\text{HIDE}_m[\text{ED}_d]) = \widetilde{\Theta}(\sqrt{m}d^{1/6})$. Consequently,

$$
Q(\text{TriangleEdge}) = \widetilde{\Theta}(\sqrt{m}d^{1/6}),\tag{1.2}
$$

where the input is a length-m edge list and the target edge has d neighboring edges.

The study of TriangleEdge naturally led us to investigate how $Q(f)$ relates to $Q(HIDE_b[f])$ for arbitrary $f: \Sigma^a \to \{0,1\}$. As a first step in this direction, we show

$$
Q(\text{HIDE}_b[f]) = \widetilde{\Theta}(\sqrt{b/a} \cdot Q(f)) \quad \text{for any symmetric } f \colon \{0,1\}^a \to \{0,1\},\tag{1.3}
$$

where "symmetric" refers to "symmetric under permuting the *positions* of input symbols" throughout this work. The symmetry condition is necessary since [Eq. \(1.3\)](#page-2-3) fails for the simple dictator function. On the other hand, we conjecture that [Eq. \(1.3\)](#page-2-3) holds for any symmetric $f: \Sigma^a \to \{0, 1\}$ even if $|\Sigma| > 2$. We support our conjecture by showing that its randomized analogue is true in [Proposition 3.10.](#page-13-0)

TriangleVertex and shuffling. We show in [Propositions 4.1](#page-14-2) and [4.2](#page-15-0) that the quantum query complexity of TriangleVertex, when the input is a length-m edge list and the target vertex u has degree d, satisfies

$$
\Omega(\sqrt{m/d} \cdot Q(3\text{-DIST}_d)) \le Q(\text{TriangleVertex}) \le O(\sqrt{m}d^{1/4}),\tag{1.4}
$$

where 3-DIST_d is the 3-distinctness function that decides whether an input string of length d has three distinct positions containing the same symbol. Note that $Q(3-D\mathsf{IST}_d)$ is between $\Omega(d^{2/3})$ – because it is no easier than ED_d (which could be also called 2-DIST_d) – and $O(d^{5/7})$ [\[Bel12b\]](#page-50-0).

When seeking a triangle containing the target vertex u , it is helpful to think of the input edge list as consisting of two parts: part A containing edges that are incident u , and part B containing edges that are not incident to u. We do not apriori know where parts A and B are but neither part contains irrelevant data — indeed two edges of the triangle must come from A and one edge from B (if it exists). The *shuffling* of parts A and B contributes to the hardness of TriangleVertex.

¹In general, for integers $b \ge a \ge 1$, Σ a finite non-empty set, and a string $x \in \Sigma^b$: a length-a subsequence of x is a string of the form $x_{i_1}x_{i_2}...x_{i_a}$ for some integers $1 \leq i_1 < i_2 < \cdots < i_a \leq b$.

²We use the notation $\tilde{O}, \tilde{\Omega}, \tilde{\Theta}$ to denote big- O, Ω , and Θ up to poly-logarithmic factors.

The above discussion and the comparison of the edge list model with the adjacency list and adjacency matrix models naturally led us to investigate how shuffling a function's input affects its complexity. We formalize and study two concrete versions of this problem.

(I) Shuffled functions. As discussed, the edge list can be seen as a "shuffled version" of the adjacency list. We now formalize this notion.

Definition 1.3 (Shuffling transform). Given a function $f: \widetilde{D} \subseteq \Sigma^n \to \{0,1\}$, we define the *shuffling* transform of f to be

$$
\mathsf{SHUFFLE}[f] \colon D \subseteq (\Sigma \times [n])^n \to \{0, 1\},\tag{1.5}
$$

where

- (i) D consists of $x = ((v_1, \pi(1)), \ldots, (v_n, \pi(n))) \in (\Sigma \times [n])^n$ such that $\pi : [n] \to [n]$ is a bijection (so π) can be viewed as a permutation of [n]) and $(v_{\pi^{-1}(1)}, v_{\pi^{-1}(2)}, \ldots, v_{\pi^{-1}(n)}) \in D$.
- (ii) SHUFFLE[f](x) := $f(v_{\pi^{-1}(1)}, v_{\pi^{-1}(2)}, \ldots, v_{\pi^{-1}(n)})$.

In other words, the inputs to $SHUFFLE[f]$ are shuffled versions of the inputs to f such that each symbol of the input to $SHUFFLE[f]$ additionally contains its position pre-shuffling.

Of course, any (worst-case) query complexity measure of $SHUFFLE[f]$ is at least that of f, since SHUFFLE $[f]$ contains a copy of f under the restriction of the domain D to those inputs of the form $(x_1, 1), \ldots, (x_n, n)$, where $x = x_1 \ldots x_n \in \overline{D}$. If f is symmetric, then any query complexity measure on f is the same as that measure on $SHUFFLE[f]$ since the algorithm computing $SHUFFLE[f]$ could simply ignore the second coordinates of the input. For non-symmetric function, the dictator function $f(x) = x_1$ witnesses a 1 vs $\Omega(\sqrt{n})$ separation between $Q(f)$ and $Q(\text{SHUFFLE}[f]).$

Given the above discussion, the interesting question becomes: how does the separation between $Q(f)$ and $Q(SHUFFLE[f])$ depend on "how symmetric" f is? Natural (partially) symmetric f arises from graph properties. We show that there can be massive separations between $Q(f)$ and $Q(SHUFFLE[f])$ even if f has significant symmetry by being defined as a graph property in either (i) the adjacency list model (exponential separation) or (ii) adjacency matrix model (unbounded separation).

Since an edge list can be interpreted as a shuffled adjacency list, result (i) can be interpreted as "quantum computers can compute a graph property exponentially faster given an adjacency list instead of an edge list"; the proof of result (ii) can also be adapted to show "quantum computers can compute a graph property unboundedly faster given an adjacency matrix instead of an edge list".

Theorem 1.4 (Informal version of [Theorems 4.5](#page-16-1) and [4.6\)](#page-17-0).

(i) There exists a (family of) graph property $\mathcal{P}_1 : A \to \{0,1\}$, where A denotes a set of adjacency lists of size n such that

$$
Q(\mathcal{P}_1) = O(\text{polylog}(n))
$$
 and $Q(\text{SHUFFLE}[\mathcal{P}_1]) = n^{\Omega(1)}$.

(ii) There exists a (family of) graph property $\mathcal{P}_2 : M \to \{0,1\}$, where M denotes a set of $n \times n$ adjacency matrices such that

 $Q(\mathcal{P}_2) = O(1)$ and $Q(\text{SHUFFLE}[\mathcal{P}_2]) = n^{\Omega(1)}$.

(II) Shuffled direct sum. In TriangleVertex, the hardness arising from shuffling is intuitively not due to shuffling within parts A and B but rather between them. We formalize a toy version of this type of shuffling in the context of direct sum as follows.

Definition 1.5 (Shuffled direct sum). For $f: \Sigma^n \to \{0,1\}$, we define the k-shuffled direct sum of f to be

$$
\mathsf{SHUFFLE}^k[f]: D \subseteq (\Sigma \times [k])^{kn} \to \{0,1\}^k,\tag{1.6}
$$

where

(i) $x = ((v_1, c_1), \ldots, (v_{kn}, c_{kn})) \in D$ if and only if for all $j \in [k]$, there are exactly n indices $i \in [kn]$ such that $c_i = j$.

(ii) SHUFFLE^k[f](x) is defined to be $(f(v^{(1)}), \ldots, f(v^{(k)}))$, where $v^{(j)}$ is the subsequence of $v := v_1 \ldots v_{kn}$ indexed by those $i \in [kn]$ such that $c_i = j$.

We have $Q(\text{SHUFFLE}^k[f]) \ge \Omega(kQ(f))$, since computing SHUFFLE^k[f] is at least as hard as computing k independent copies of f, which costs $\Omega(kQ(f))$ queries by a well-known direct-sum theorem for quantum query complexity [\[ACLT10,](#page-49-4) [Rei11\]](#page-52-3). This direct sum lower bound can be far from tight for SHUFFLE^{k}[f]: consider f being the dictator function. At first sight, computing SHUFFLE k [f] seems harder than computing the k independent copies of f even if f is symmetric.

Perhaps counterintuitively, we show in [Proposition 4.9](#page-21-0) that this is not the case if f is symmetric and has Boolean domain $\{0,1\}^n$: for such f, we show $Q(\text{SHUFFLE}^k[f]) \leq O(kQ(f)).$

We can analogously define shuffling for other ways of composing k functions, for example, by taking the XOR of their outputs. We leave the study of such types of shuffling to future work.

Triangle Finding. Having discussed TriangleEdge and TriangleVertex, we now turn to FTriangle, a problem that has played an important role in the area of quantum query complexity. In the edge list model, we find that FTriangle bridges the 3-DIST and 3-SUM problems since its structure lies between theirs. Recall that in 3-DIST, the goal is to decide whether the input contains three repetitions of the same symbol. In 3-SUM, the input contains symbols from some abelian group and the goal is to decide if there are three symbols that sum to the zero-element of the group.

Intuitively, FTriangle should be at least as hard as 3-DIST and no harder than 3-SUM from considering its "certificate structure" [\[BR14\]](#page-50-4). In 3-DIST, once we have found one symbol of a 1-certificate, the next symbol (for completing the certificate) is determined. In 3-SUM, once we have found one symbol of a 1-certificate, the next symbol can be arbitrary. In comparison, in FTriangle, once we have found one edge (i, j) of a 1-certificate, the next edge must be incident to one of i or j so it is neither determined nor arbitrary. In [Proposition 5.1,](#page-22-2) we show that this intuition is formally correct by reducing 3-DIST to Triangle (the decision version of FTriangle) and Triangle to 3-SUM.

Our first main result is [Theorem 5.5,](#page-24-1) restated informally below.

Theorem 1.6 (Informal version of [Theorem 5.5\)](#page-24-1). Given a uniformly random edge list on n vertices containing $m = \Theta(n)$ edges, which corresponds to a random sparse graph, any quantum query algorithm must make at least $\Omega(m^{5/7} / \log^{2/7}(m))$ queries to find a triangle.

We find [Theorem 1.6](#page-4-0) interesting for several reasons. Firstly, proving the theorem pushed us to develop new techniques for the recording query framework, which we believe to be of independent interest. The recording query framework was pioneered by Zhandry [\[Zha19\]](#page-52-0) to prove the security of cryptosystems against quantum adversaries. The framework is particularly well-suited for proving average-case quantum query lower bounds, where the input is sampled from certain types of distributions. The framework can also yield optimal worst-case lower bounds if the worst-case distribution is of a type it can handle.

There is now a growing line of work developing new techniques within the recording query framework, including [\[LZ19,](#page-51-6) [CFHL21,](#page-50-5) [HM23,](#page-51-7) [BKW24,](#page-50-6) [MMW24,](#page-51-8) [MH24\]](#page-51-9). Of particular relevance to our work is [\[HM23\]](#page-51-7) by Hamoudi and Magniez, which generalized Zhandry's original framework in order to lower bound the quantum query complexity of finding collision pairs. However, [\[HM23\]](#page-51-7) only considers *disjoint* collision pairs to, in their words, "avoid the recording of more than one new collision in one query".[3](#page-4-1) At a high level, our proof of [Theorem 1.6](#page-4-0) develops the first techniques for handling the case where more than one new collision can be recorded in one query. This is an intrinsic feature of the triangle problem since each queried edge could contribute to more than one *wedge*, i.e., a length-2 path, that could then be used to complete to a triangle.

[Theorem 1.6](#page-4-0) is also interesting because the lower bound curiously matches the best-known upper bound on the quantum query complexity of 3-distinctness, which is $Q(3-D\mathsf{IST}_{m}) \leq O(m^{5/7})$, up to

³For readers unfamiliar with the recording query framework, the word "recorded" roughly means "found". In this paper, we have aimed to give a succinct but self-contained introduction to the recording query framework for such readers.

logarithmic factors. This upper bound was first proven by Belovs [\[Bel12b\]](#page-50-0) more than a decade ago using a ground-breaking learning graph algorithm [\[Bel12a\]](#page-50-7). There have been no improvements since. On the other hand, the best-known lower bound on $Q(3\text{-}D\text{IST}_m)$ is *still* $\Omega(m^{2/3})$, which is simply inherited from the element distinctness lower bound of Aaronson and Shi [\[AS04\]](#page-49-5). We strongly believe that the matching of the lower bound in [Theorem 1.6](#page-4-0) and the best-known upper bound on $Q(3-DIST_m)$ is not a coincidence. This is because the "collision structure" of a uniformly random edge list on n vertices containing $m = \Theta(n)$ edges resembles that of a candidate worst-case distribution on inputs to 3-DIST_m. By collision structure, we mean the counts of wedges and triangles in the input edge list (and their analogues for 3-distinctness).

Indeed, the similarities between the collision structures were so striking that we were led to ask whether Belovs's learning graph algorithm for 3-distinctness could be adapted to provide a matching upper bound to [Theorem 1.6.](#page-4-0) As our second main result, we answer this question affirmatively.

Theorem 1.7 (Informal version of [Corollary 5.25\)](#page-40-1). Given a uniformly random edge list on n vertices containing $m = \Theta(n)$ edges, which corresponds to a random sparse graph, there exists a quantum query algorithm that uses $O(m^{5/7+o(1)})$ queries to find a triangle. Moreover, the algorithm is an adaptation of Belovs's learning graph algorithm for 3-distinctness as developed in [\[Bel12b\]](#page-50-0).

Taken together, [Theorems 1.6](#page-4-0) and [1.7](#page-5-1) give the first example of a problem for which Belovs's learning graph algorithm in [\[Bel12b\]](#page-50-0) is provably optimal, up to an $m^{\overline{o}(1)}$ factor.^{[4](#page-5-2)} [Theorem 1.6](#page-4-0) also suggests that any quantum algorithm that polynomially improves the best-known $O(m^{5/7})$ upper bound on $Q(3\text{-}\mathsf{DIST}_m)$ must exploit more than just the collision structure of the problem, which seems improbable to us.

1.2 Technical overview

We now highlight some of our work's main technical contributions. We inherit the notation above.

TriangleEdge and Hiding. To lower and upper bound $Q(HIDE_m[ED_d])$, our main observation is that the problem "self-reduces" to a more structured version of itself, $HIDE'_{m}[\text{ED}_{d}]$, whose query complexity is easier to characterize. The inputs to $HIDE'_m[ED_d]$ are restricted to have the form of d blocks each of length m/d ,^{[5](#page-5-3)} where each block contains $(m/d - 1)$ *s and exactly one non-* symbol. Remarkably, imposing the block structure causes no decrease in hardness.

Observe that $HIDE'_m[ED_d]$ can be viewed as the composition of ED_d with the so-called pSearch function that extracts the unique non- $*$ symbol from m/d symbols. The latter function has query complexity $\Theta(\sqrt{m/d})$ and a composition theorem [\[BHK](#page-50-8)⁺19, Theorem 9] yields $Q(\text{HIDE}_{m}[\text{ED}_{d}]) \ge Q(\text{HIDE}_{m}'[\text{ED}_{d}]) \ge$ $\Omega(\sqrt{m/d} \cdot d^{2/3}) = \Omega(\sqrt{m}d^{1/6})$. To upper bound $Q(\text{HIDE}_m[\text{ED}_d])$, we consider a quantum algorithm that first randomly permutes the positions of a given input string x. A standard probability argument – like that used to bound the maximum load in a balls-into-bins experiment – implies that the resulting string \tilde{x} is highly likely to be in a block form similar to inputs of $HIDE'_{m}[\text{ED}_{d}]$, except each block may contain up to log(d) non-∗ symbols. Since the number of non-∗ symbols in each block is so small, we simply Grover search for all of them on the fly while running the quantum algorithm for $ED_{d \log(d)}$ on $d \log(d)$ symbols. This algorithm has query complexity $\widetilde{O}(\sqrt{m}d^{1/6})$.

By considering the block structure, we also see $Q(\text{HIDE}_m[f]) = \Omega(\sqrt{m/d} \cdot Q(f))$ for any $f: \Sigma^d \to$ $\{0,1\}$. We show $Q(\text{HIDE}_m[f]) = \widetilde{O}(\sqrt{m/d} \cdot Q(f))$ for symmetric $f: \{0,1\}^d \rightarrow \{0,1\}$ using the characterization of the optimal quantum query algorithm for such functions in $[BBC^+01]$. We show $R(\text{HIDE}_m[f]) = O((m/d) \cdot R(f))$ for symmetric $f: \Sigma^d \to \{0,1\}$, where $R(\cdot)$ denotes the worst-case (bounded-error) randomized query complexity, using the characterization of the optimal randomized query algorithm for such functions in [\[BKS01\]](#page-50-9).

⁴Note that the best-known quantum query lower bound for k-DIST for any $k \geq 4$ (see [\[BKT18,](#page-50-10) [MTZ20\]](#page-52-4)) is also polynomially far from the upper bound witnessed by Belovs's learning graph algorithm.

⁵We may assume $m/d \in \mathbb{Z}$ without loss of generality. We will not make further remarks like this in the technical overview.

TriangleVertex and Shuffling. To obtain our upper bound $Q(\text{TriangleVertex}) \le O(\sqrt{m}d^{1/4})$ in [Proposition 4.1,](#page-14-2) we use a quantum walk algorithm that walks on the Hamming graph with vertices labeled by $r = \lceil d^{3/4} \rceil$ positions from part A (the part containing edges incident to the target vertex) of the input. Since we do not apriori know where part A is, we perform amplitude amplification in both the setup and update steps of the quantum walk to keep the walk on part A. Importantly, this uses the fact that the underlying random walk is uniformly random on the Hamming graph. To lower bound $Q(\textsf{TriangleVertex}) \ge \Omega(\sqrt{m/d} \cdot Q(3\textsf{-DIST})),$ we give a reduction from $\textsf{HIDE}_m[3\textsf{-DIST}]$ to TriangleVertex in [Proposition 4.2.](#page-15-0)

We obtain an exponential separation between $Q(f)$ and $Q(\text{SHUFFLE}[f])$ when f is defined by the graph property $\mathcal P$ from [\[BCG](#page-49-2)+20, Section 6] in the adjacency list model as follows. [BCG+20] showed that computing f witnesses an exponential separation between randomized and quantum query complexities. But the quantum query complexity of computing $\text{SHUFFLE}[f]$ is polynomially related to its randomized query complexity since the problem is symmetric [\[Cha19\]](#page-50-11).

If f is defined by a graph property in the adjacency matrix model, the above argument cannot work since $[BCG^+20]$ showed that the quantum query complexity of computing f is polynomially related to its randomized query complexity. Nonetheless, we found that an unbounded separation between $Q(f)$ and $Q(SHUFFLE[f])$ can be witnessed by the following Majority-of-Majority function on a restricted partial domain, that we name ΣMAJ :^{[6](#page-6-0)}

Definition 1.8.

$$
\Sigma MAJ_n: D_0 \dot{\cup} D_1 \subseteq \{0, 1\}^{n^2} \to \{0, 1\},\tag{1.7}
$$

where $\Sigma MAJ_n(x) = 0$ if and only if $x \in D_0$ and

- (i) $x = (x_{1,1}, x_{1,2}, \ldots, x_{n,n}) \in \{0,1\}^{n^2}$ is in D_0 if and only if there exists a subset $S \subseteq [n]$ of size $\geq 2n/3$ such that for all $i \in S$, $x^i \coloneqq (x_{i,1}, \ldots, x_{i,n})$ has Hamming weight $|x^i| \geq 2n/3$ and for all $i \in [n]-S$, $|x^i|\leq n/3.$
- (ii) $x = (x_{1,1}, x_{1,2}, \ldots, x_{n,n}) \in \{0,1\}^{n^2}$ is in D_1 if and only if there exists a subset $S \subseteq [n]$ of size $\leq n/3$ such that for all $i \in S$, $x^i := (x_{i,1}, \ldots, x_{i,n})$ has Hamming weight $|x^i| \geq 2n/3$ and for all $i \in [n]-S$, $|x^i|\leq n/3.$

In other words, inputs in D_0 have at least $2n/3$ "dense" rows, i.e., a substring of the form $x_{i,1}x_{i,2}...x_{i,n}$ for some $i \in [n]$, where the number of 1s is at least $2n/3$; and at most $n/3$ "sparse" rows where the number of 1s is at most $n/3$; inputs in D_1 have at most $n/3$ dense rows where the number of 1s is at least $2n/3$, and at least $2n/3$ sparse rows where the number of 1s is at most $2n/3$.

It is not hard to see that $R(\Sigma MAJ_n) = O(1)$ as follows. For a given row, we can test whether it is dense or sparse using $O(1)$ queries. Since the fraction of dense blocks for inputs in D_0 and D_1 differ by a constant, we can distinguish between these cases using $O(1)$ queries. Therefore $Q(\Sigma \text{MAJ}_n) \leq R(\Sigma \text{MAJ}_n) = O(1)$.

Computing SHUFFLE $[\Sigma MAJ_n]$ seems harder. The previous algorithm is no longer efficient since we cannot efficiently target a given row and test its sparsity. Intuitively, the problem seems at least as hard as finding two distinct input symbols $(x_{i_1,j_1}, (i_1,j_1))$ and $(x_{i_2,j_2}, (i_2,j_2))$ that came from the same row pre-shuffling, i.e., $i_1 = i_2$ but $j_1 \neq j_2$ (call this a row collision), which would yield a lower bound of $\Omega(\sqrt{n})$ by a standard collision argument.

A formal proof is more challenging because there does not appear to be a direct reduction from the collision problem to SHUFFLE $[\Sigma M A J_n]$. Our proof of $R(\text{SHUFFLE}[\Sigma M A J_n]) = \Omega(\sqrt{n})$ in [Theorem 4.6](#page-17-0) shows that two particular distributions, one supported on the set D_0 and another on D_1 , are hard to distinguish by any few-query randomized algorithm using a hands-on total variation distance argument. Therefore, $Q(\mathsf{SHUFFLE}[\Sigma \mathbf{MAJ}_n]) = \Omega(R(\mathsf{SHUFFLE}[\Sigma \mathbf{MAJ}_n])^{1/3}) = \Omega(n^{1/6}),$ where the first equality uses [\[Cha19\]](#page-50-11), which applies since $\text{SHUFFLE}[\Sigma \text{MAJ}_n]$ is symmetric.

⁶We chose this name because Σ resembles a rotated M and ΣMAJ_n is (a restriction of) the composition of two MAJ_n s.

Triangle Finding (lower bound). We prove our lower bound on triangle finding [\(Theorem 1.6\)](#page-4-0) in Zhandry's recording query framework [\[Zha19\]](#page-52-0). Following the framework, we define a "progress quantity" that tracks the progress the algorithm has made in "recording" the searched-for object in its internal memory. The progress quantity can be roughly thought of as the square root of the probability with which the quantum algorithm can find the searched-for object, where the probability is over randomness in both the input distribution and the algorithm. The progress quantity depends on the number of queries the quantum algorithm makes. If this quantity is small after the last query, then the algorithm cannot find what it is searching for with high probability.

Our proof has two steps:^{[7](#page-7-0)}

- (i) we first show that the progress in recording much more than $r^*(t) := t^{3/2} \log(n)/\sqrt{n}$ wedges in t queries is negligible;
- (ii) then we show that, given we record $O(r^*(t))$ wedges in t queries, the progress of recording a triangle at the $(t+1)$ -th query increases by at most $O(\sqrt{r^*(t)}/n)$, which corresponds to the square root of the probability that a random edge completes one of the $r^*(t)$ recorded wedges to a triangle.

Therefore, at the T-th query, the progress of recording a triangle is $\sum_{t=0}^{T} \sqrt{r^*(t)}/n$, which equals $O(T^{7/4}\sqrt{\log(n)}/n^{5/4})$, and is $o(1)$ unless $T \geq \Omega(n^{5/7}/\log^{2/7}(n))$. The ability to perform this type of step-by-step analysis is a known strength of the recording query framework.^{[8](#page-7-1)} For example, it was exploited to great effect by Liu and Zhandry [\[LZ19\]](#page-51-6) in proving their tight lower bound on the quantum query complexity of average-case k-distinctness.

What is new to our work is how we perform step (i) above. As previously discussed, the issue is that a newly queried edge could contribute to more than one wedge. Let us now see how this issue manifests itself at a technical level. We begin by following the recording queries framework and define a progress quantity $\Lambda_{t,r} \in [0,1]$ for integer t,r with $t \geq 0$ where $\Lambda_{t,r}^2$ represents the probability a quantum query algorithm has recorded at least r wedges immediately after the t -th query. Directly using existing techniques in the framework gives the following recurrence for $\Lambda_{t,r}$:

$$
\Lambda_{t,r} \le \Lambda_{t-1,r} + O(\sqrt{t/n}) \cdot \Lambda_{t-1,r-t+1},\tag{1.8}
$$

where the factor $O(\sqrt{t/n}) = O(\sqrt{tn/n^2})$ arises as the square root of the probability that a randomly chosen edge is incident to one of the at most $t-1$ edges that can be recorded after the $(t-1)$ -th query; the subscript $r - t + 1 = r - (t - 1)$ arises from the possibility of the new edge recorded at the t-th query contributing $t-1$ additional wedges. However, solving [Eq. \(1.8\)](#page-7-2) leads to a trivial lower bound for triangle finding that does not even beat the $\Omega(m^{2/3})$ lower bound it inherits from element distinctness.

The main problem with [Eq. \(1.8\)](#page-7-2) is the subscript $r - t + 1$ on the second term on the right-hand side. However, the event it corresponds to seems unlikely to happen when the input is a sparse graph and t is large: if the new edge contributes $t-1$ additional wedges, it must be incident to a degree- $\Omega(t)$ vertex recorded by the quantum query algorithm. Now, our input is a random sparse graph whose maximum degree is at most $O(\log(n)/\log\log(n)) \leq O(\log(n))$ with high probability, *independent of t*. Does this property also hold for the internal memory of the quantum query algorithm doing the recording? Our first technical contribution, the Mirroring Lemma [\(Lemma 5.17\)](#page-30-0), answers this question affirmatively. This lemma allows us to transfer, or mirror, properties of the initial input distribution onto the internal memory of the quantum algorithm, independently of the value of t. Directly using this technique allows us to improve Eq. (1.8) to

$$
\Lambda_{t,r} \le \Lambda_{t-1,r} + O(\sqrt{t/n}) \cdot \Lambda_{t-1,r-O(\log(n))} + \varepsilon,
$$
\n(1.9)

⁷The arguments here are better understood by considering n, which represents the number of vertices in the graph. But recall that [Theorem 1.6](#page-4-0) concerns the regime $m = \Theta(n)$, so all results here can also be expressed in terms of m.

 8 To quantum query lower bound experts: the standard quantum adversary method [\[Amb00,](#page-49-7) [HLS07\]](#page-51-10) is not well-suited to performing this type of step-by-step analysis because it gives only weak lower bounds for small success probabilities, and step (ii) needs the progress in step (i) to be inverse-polynomially small to work. If we were forced to redo this analysis using the adversary method, we would have to switch to its *multiplicative* version, see, e.g., $[\hat{ASdW06}, \hat{LR13}]$.

where $\varepsilon > 0$ is a small number corresponding to the tail probability of the input graph having a vertex of degree $\Omega(\log(n))$.

Unfortunately, $Eq. (1.9)$ still does not yield the desired result: to see this, note that the solution to a similar recurrence $A_{t,r} = A_{t-1,r} + pA_{t-1,r-1} + \varepsilon$ (with $p, \varepsilon \in [0,1]$ and boundary conditions $A_{0,0} = 1$ and $A_{0,r} = 0$ for all $r > 0$) is $A_{t,r} = \binom{t}{r}$ r_r^t) $p^r + \varepsilon(1 + (1 + p) + \cdots + (1 + p)^{t-1})$. Even for an exponentially small ε, the term $\varepsilon(1+p)^{t-1}$ blows up for large t. Our second technical contribution, the Exclusion Lemma [\(Lemma 5.14\)](#page-28-0), allows us to overcome this problem. To employ this lemma, we introduce a new progress quantity called $\Lambda'_{t,r}$ that is defined like $\Lambda_{t,r}$ except we additionally require the quantum query algorithm to not have recorded a degree- $\Omega(\log(n))$ vertex at any point before the t-th query. By definition, $\Lambda'_{t,r}$ satisfies recurrence [Eq. \(1.9\)](#page-7-3) with ε set to 0, that is,

$$
\Lambda_{t,r}' \le \Lambda_{t-1,r}' + O(\sqrt{t/n}) \cdot \Lambda_{t-1,r-O(\log(n))}'.
$$
\n(1.10)

The Exclusion Lemma allows us to upper bound $\Lambda_{t,r}$ by $\Lambda'_{t,r} + O(t\varepsilon)$, where the second term no longer blows up for large t and is easy to make negligible. Therefore, solving [Eq. \(1.10\)](#page-8-1) first for $\Lambda'_{t,r}$ and then using $\Lambda_{t,r} \leq \Lambda'_{t,r} + O(t\varepsilon)$ yields the claimed result of step (i).

Triangle Finding (upper bound). We prove our upper bound on triangle finding [\(Theorem 1.6\)](#page-4-0) by adapting Belovs's learning graph algorithm for 3-distinctness from [\[Bel12b\]](#page-50-0). A "learning graph algorithm" is formally a directed acyclic graph that encapsulates a solution to a semi-definite program whose minimum solution upper bounds the quantum query complexity [\[Rei09,](#page-52-5) [Rei11\]](#page-52-3). Our main adaptation of Belovs's algorithm pertains to its handling of so-called faults in [\[Bel12b,](#page-50-0) Section 6].

The notion of a fault is easier to explain in Jeffery and Zur's interpretation of Belovs's algorithm as a quantum walk $[JZ23]$ ^{[9](#page-8-2)}. The following explanation is based on $[JZ23,$ Section 1.3]. The quantum walk first creates a uniform superposition over subsets R_1 of indices of some size r_1 , and queries all r_1 indices. Then, for each R_1 in the superposition, the algorithm creates a uniform superposition over all subsets R_2 (disjoint from R_1) of indices of some size r_2 . But rather than querying every index in R_2 , the algorithm only queries those $i_2 \in R_2$ that have a match in R_1 , i.e., $x_{i_2} = x_{i_1}$ for some $i_1 \in R_1$, where x is the input. This significantly reduces query complexity by exploiting the structure of 3-distinctness: any two unequal symbols could not be part of a 1-certificate. Unfortunately, it also leads to the aforementioned faults. The issue is that when performing the update step of the quantum walk by adding a new index j_1 to R_1 , we cannot afford the queries needed to update a corresponding R_2 by searching for a $j_2 \in R_2$ such that $x_{j_2} = x_{j_1}$ because R_2 was not fully queried. But if we do not search and there does exist $j_2 \in R_2$ with $x_{j2} = x_{j1}$, then the set of queried indices in R_2 becomes incorrect, introducing a fault.

In our setting, there can be more faults because "matching" in our case naturally needs to be redefined to mean: $i_2 \in R_2$ matches with $i_1 \in R_1$ if and only if x_{i_2} (which is an edge in our case) is *incident* to x_{i_1} . In particular, i_2 could match i_1 even if $x_{i_2} \neq x_{i_1}$. However, the number of faults introduced is bounded above by using the maximum degree d of the input, which for a random sparse graph satisfies $d \leq O(\log(n)/\log\log(n))$. Then we fully verify that the "error-correcting" technique of [\[Bel12b\]](#page-50-0) can be adapted to correct $O(d)$ faults by paying a multiplicative factor of $2^{O(d)} = n^{O(1)}$ on the quantum query complexity, which leads to the theorem. As we verify from scratch, we also construct a learning graph algorithm that may be easier to understand than that in [\[Bel12b\]](#page-50-0); for example, our algorithm genuinely corresponds to a graph, unlike that in [\[Bel12b\]](#page-50-0).

2 Preliminaries

Notation. N denotes the set of positive integers. Notation such as $\mathbb{Z}_{\geq 0}$ denotes the set of non-negative integers, $\mathbb{R}_{>0}$ denotes the set of positive reals, and so on. For $n \in \mathbb{N}$, $[n]$ denotes the set $\{1, \ldots, n\}$. For

⁹[\[JZ23\]](#page-51-12) goes much beyond merely interpreting Belovs's algorithm. However, in this paper, we will only use [\[JZ23\]](#page-51-12) to aid our explanation of Belovs's algorithm.

two complex square matrices X, Y of the same dimension, we write $X \leq Y$ to mean $Y - X$ is positive semidefinite, and $X \geq Y$ to mean $X - Y$ is positive semidefinite. We use I to denote an identity matrix of a context-appropriate dimension.

An alphabet is a finite non-empty set. For an alphabet A and $k \in \mathbb{Z}_{\geq 0}$, $\binom{A}{k}$ denotes the set of all size-k subsets of A. Given two disjoint sets A, B , we sometimes write $A \cup B$ for their union, where the dot emphasizes that A and B are disjoint. (If we write $A \cup B$ instead, A and B could still be disjoint.) For an alphabet Σ , we write $x \leftarrow \Sigma$ for sampling x uniformly at random from Σ . For $x \in \Sigma^n$ and $a, b \in \mathbb{N}$, $x[a \tcdot b]$ denotes the substring of x from index a to b inclusive; if $b < a$, then this denotes the empty string. For $n \in \mathbb{N}$, we say $\{u_1, v_1\}$, $\{u_2, v_2\}$, $\{u_3, v_3\} \in {n \choose 2}$ $\binom{n}{2}$ form a triangle if there exists distinct $x, y, z \in [n]$ such that $\{u_1, v_1\} = \{x, y\}, \{u_2, v_2\} = \{y, z\}, \text{ and } \{u_3, v_3\} = \{z, x\}.$

For an alphabet U, we denote the symmetric group acting on U by \mathfrak{S}_U . For $n \in \mathbb{N}$, we also use \mathfrak{S}_n to denote the symmetric group acting on [n]. We say a function $f: E \subseteq \Sigma^n \to \{0,1\}$ is symmetric if $x_1, \ldots, x_n \in E \implies x_{\sigma(1)}, \ldots, x_{\sigma(n)} \in E$ and $f(x_1, \ldots, x_n) = f(x_{\sigma(1)}, \ldots, x_{\sigma(n)})$ for all $x \in \Sigma^n$ and for all permutations $\sigma \in \mathfrak{S}_n$. Note that we do *not* require a symmetric f to be invariant under permutations of the alphabet Σ.

The abbreviation "wlog" stands for "without loss of generality"; "s.t." stands for "such that"; "with high probability" stands for "with probability at least $1 - 10^{-10}$ " unless stated otherwise. The symbol log stands for the base-2 logarithm.

For a function $f: D \subseteq \Sigma^n \to \Gamma$, where D, Σ, Γ are alphabets and $n \in \mathbb{N}$, and $\varepsilon \in (0, 1/2)$, we write $Q_{\varepsilon}(f)$ and $R_{\varepsilon}(f)$ for the quantum and randomized query complexities for f with two-sided failure probability at most ε , respectively. We write $Q(f)$ and $R(f)$ for $Q_{1/3}(f)$ and $R_{1/3}(f)$, respectively.

Function definitions. For $m, d, n, s, k \in \mathbb{N}$ with $m \geq d, u, v \in [n]$ with $u \neq v, G$ a finite abelian group with identity element 0, we define the following functions of interest in this work.

- (i) k -DIST_m: $[s]^m \to \{0,1\}$ denotes the k-distinctness function which is defined by k-DIST_m(x) = 1 if and only if there exist k distinct indices $1 \leq i_1 < i_2 < \cdots < i_k \leq n$ such that $x_{i_1} = x_{i_2} = \cdots = x_{i_k}$.
- (ii) $ED_m: [s]^m \to \{0,1\}$ denotes the element distinctness function which is the same as 2-DIST_m. (iii) k-SUM_m: $G^m \to \{0,1\}$ denotes the k-sum function which is defined by k-SUM_m $(x) = 1$ if and only
- if there exist k distinct indices $1 \leq i_1 < i_2 < \cdots < i_k \leq n$ such that $x_{i_1} + x_{i_2} + \cdots + x_{i_k} = 0$.
- (iv) TriangleEdge $_{m}^{\{u,v\}}$: $D \subseteq \binom{[n]}{2}$ $\binom{n}{2}^m \to \{0,1\}$ denotes the triangle edge function which is defined by $x \in D$ if and only if $x_i \neq x_j$ for all $i \neq j$, and TriangleEdge ${}_{m}^{\{u,v\}}(x) = 1$ if and only if there exist distinct $i, j \in [m]$ such that x_i, x_j and $\{u, v\}$ form a triangle.
- (v) TriangleEdge ${}_{m,d}^{\{u,v\}}: D_d \subseteq \binom{[n]}{2}$ $\binom{n}{2}^m \rightarrow \{0,1\}$ is the restriction of TriangleEdge $\binom{\{u,v\}}{m}$ such that $x \in D_d$ if and only if $x_i \neq x_j$ for all $i \neq j$ and $|\{i \in [m] \mid |x_i \cap \{u, v\}| = 1\}| = d$.
- (vi) TriangleVertex $_m^u$: $\binom{[n]}{2}$ $\binom{n}{2}^m$ \rightarrow {0,1} denotes the triangle vertex function which is defined by TriangleVertex $u_m^u(x) = 1$ if and only if there exist distinct $i, j, k \in [m]$ such that x_i, x_j and x_k form a triangle containing vertex u .
- (vii) TriangleVertex $_{m,d}^u$: $D_d \subseteq \binom{[n]}{2}$ $\mathbb{Z}_2^{(n)} \rightarrow \{0,1\}$ is the restriction of TriangleVertex $^u_{m,d}$ such that $x \in D_d$ if and only if $|\{i \in [m] \mid |x_i \cap \{u\}| = 1\}| \le d$.
- (viii) $\text{Triangle}_m: \binom{[n]}{2}$ $\binom{n}{2}$ \rightarrow {0, 1} denotes the triangle function which is defined by Triangle_m $(x) = 1$ if and only if there exist distinct $i, j, k \in [m]$ such that x_i, x_j and x_k form a triangle.
- (ix) Triangle_{m,d}: $D_d \subseteq \binom{[n]}{2}$ $\binom{n}{2}^m \rightarrow \{0,1\}$ denotes the restriction of the Triangle_m such that $x \in D_d$ if and only if for all $u \in [n]$, $|\{i \in [m] \mid |x_i \cap \{u\}| = 1\}| \le d$. (That is, the maximum degree of the graph represented by x is at most d .)
- (x) FTriangle_m denotes the search-version version of Triangle_m and is formally a relation $R \subseteq \binom{[n]}{2}$ ${n \choose 2}^m \times$ $[m]^3$ such that $(x, (i, j, k)) \in R$ if and only if x_i, x_j , and x_k form a triangle. (Note that an $x \in \binom{[n]}{2}$ $\binom{n}{2}^m$ may contain multiple triangles.)
- (xi) FTriangle_{m,d} denotes the restriction $R' \subseteq R$ of the relation R defining FTriangle_m such that $(x,(i,j,k)) \in R'$ if and only if $x \in D_d$, where D_d is the domain of Triangle_{m,d}.

For TriangleEdge $^{ \{u,v\} }_{m} ,$ TriangleEdge $^{ \{u,v\} }_{m,d},$ TriangleVertex u_m, and TriangleVertex $^u_{m,d},$ we refer to their superscripts as their target edge and target vertex respectively. We will often omit these superscripts since the (quantum) query complexity of these problems does not depend on it.

We note that the definitions of TriangleEdge_m and TriangleEdge_{m,d} appear more restrictive than that of the other triangle problems: the input cannot have duplicate edges and the number of input edges incident (but not equal) to the target edge is *exactly d*. These restrictions allow us to more directly relate them to the hiding transform of element distinctness.

Search-to-decision reduction. Any algorithm for FTriangle_m serves as an algorithm for Triangle_m by definition. Conversely, we can construct a FTriangle_m algorithm using $O(log(m))$ calls to a Triangle_m algorithm. Given that any positive instance of Triangle_m contains a size-3 certificate, we can divide the input into 4 parts. Among these, there exist 3 parts that together contain the certificate. Identifying these 3 parts requires $\binom{4}{3}$ S_3^4 = $O(1)$ calls to the Triangle_m algorithm, and in each call, we pad the input with a disjoint triangle-free graph to maintain the input size. By doing this, we reduce the search range by a factor of 3/4. Repeating this process $O(\log(m))$ times shrinks the search range to $O(1)$, at which point the certificate can be directly identified. Therefore,

$$
Q(\text{Triangle}_m) \le Q(\text{FTriangle}_m) \le O(\log(m))Q(\text{Triangle}_m). \tag{2.1}
$$

The same reduction also works for the other triangle problems. In this work, we distinguish between the search and decision problems mostly for convenience in presentation.

A convention. Technically, all of the above functions should also be parametrized by their input alphabet size, especially since their (quantum) query complexity can strictly increase as a function of this size.^{[10](#page-10-1)} In this work, we often omit this parametrization under the *convention* that the input alphabet size is sufficiently large. For example, consider $ED_m: [s] \to \{0, 1\}$ as defined above. We write $Q(ED_m)$ = $\Omega(m^{2/3})$ to mean: for all sufficiently large $s \in \mathbb{N}$, $Q(\text{ED}_m) = \Omega(m^{2/3})$. We write $Q(\text{ED}_m) = O(m^{2/3})$ to mean: for all $s \in \mathbb{N}$, $Q(\text{ED}_m) = O(m^{2/3})$. Note that we do not need "sufficiently large" s here since the (quantum) query complexity is always non-decreasing with respect to s. We write $Q(ED_m) = \Theta(m^{2/3})$ to mean: $Q(ED_m) = O(m^{2/3})$ and $Q(ED_m) = \Omega(m^{2/3})$ in the aforementioned senses.

3 TriangleEdge and Hiding

As discussed in the introduction, TriangleEdge can be seen as an instantiation of the general hiding phenomenon. We recall the formal definition of hiding from the introduction.

Given a function $f: \Sigma^a \to \{0,1\}$, and integers $b \ge a \ge 1$, recall [Definition 1.1](#page-2-4) that the hiding transform of f is

$$
\text{HIDE}_b[f]: D \subseteq (\Sigma \cup \{*\})^b \to \{0, 1\},\tag{3.1}
$$

where $*$ is a symbol outside of Σ , D contains all strings $y \in (\Sigma \cup \{*\})^b$ with exactly a non- $*$ symbols, and $HIDE_b[f](y)$ is defined to be $f(\tilde{y})$, where \tilde{y} is the length-a subsequence of y containing y's a non-* symbols (in the same order as they appear in y).

By hiding the input in a more structured way, one can get a composition-like problem, for which it is easier to show lower bounds.

Definition 3.1 (pSearch [\[BHK](#page-50-8)⁺19]). Let $m \in \mathbb{N}$ and Σ an alphabet. The pSearch_m function is defined by pSearch_m: $D \subseteq (\{*\}\dot{\cup}\Sigma)^m \to \Sigma$, where D contains all length-m strings in $(\{*\}\dot{\cup}\Sigma)^m$ with exactly one non-∗ symbol and pSearch(x) outputs the non-∗ symbol in $x \in D$.

¹⁰As a simple example, $ED_m: [s]^m \to \{0,1\}$ when $s < m$ is the constant 1 function by the pigeonhole principle so $Q(\text{ED}_m) = 0$; but when $s \geq m$, $Q(\text{ED}_m) = \Theta(m^{2/3})$.

Theorem 3.2 ([\[BHK](#page-50-8)⁺19, Theorem 9]). Let $n, m \in \mathbb{N}$ and $f: \Sigma^n \to \{0, 1\}$. Then

$$
Q(f \circ \text{pSearch}_m) = \Omega(\sqrt{m} \cdot Q(f)).
$$
\n(3.2)

We begin with a general result on hiding.

Proposition 3.3. Let $m, n \in \mathbb{N}$ with $m \ge n$ and $f: \Sigma^n \to \{0, 1\}$. Then $Q(\text{HIDE}_m[f]) \ge \Omega(\sqrt{m/n} \cdot Q(f))$. Moreover, if $\Sigma = \{0,1\}$ and f is symmetric, then $Q(\text{HIDE}_m[f]) \le \widetilde{O}(\sqrt{m/n} \cdot Q(f)).$

Proof. For the lower bound, we observe that $f \circ pSearch_{m/n}$ is a subfunction of $HIDE_m[f]$. Therefore, by [Theorem 3.2,](#page-10-2) $Q(\text{HIDE}_m[f]) \ge \Omega(\sqrt{m/n} \cdot Q(f)).$

Consider the "moreover" part. From [\[BBC](#page-49-6)+01], we have $Q(f) = \Theta(\sqrt{n(n - \Gamma(f))})$, where $\Gamma(f)$:= $\min\{|2k - n + 1| \mid f_k \neq f_{k+1}\}\$ and $f_k := f(x)$ for all x such that $|x| = k$ as f is symmetric. Observe that f_k must be constant for all $k \in \{(n-\Gamma(f))/2,\ldots,(n+\Gamma(f)-2)/2\}$. Call this constant $b \in \{0,1\}$. We also write $A := (n - \Gamma(f))/2$ and $B := (n + \Gamma(f) - 2)/2$ for convenience.

We consider the following quantum algorithm for $HIDE_m[f]$.

Algorithm for $HIDE_m(f)$

On input $y \in \{0, 1, *\}^m$:

- (i) Use Grover search to collect up to A distinct positions $i \in [m]$ such that $y_i = 1$, treating any ∗ as 0. If the search fails at step $k \in \{1, ..., A\}$, stop and output f_{k-1} . Otherwise, continue.
- (ii) Use Grover search to collect up to $(n B)$ distinct positions $i \in [m]$ such that $y_i = 0$, treating any $*$ as 1. If the search fails at step $k \in \{1, \ldots, (n-B)\}\)$, stop and output f_{n-k+1} . Otherwise, output b.

The quantum query complexity of this algorithm, accounting for error suppression, is

$$
\widetilde{O}(\sqrt{mA} + \sqrt{m(n - B)}) = \widetilde{O}(\sqrt{m/n} \cdot \sqrt{nA}) = \widetilde{O}(\sqrt{m/n} \cdot Q(f)),\tag{3.3}
$$

using the basic fact that collecting (up to) α marked items from a list of β items costs $\tilde{O}(\sqrt{\alpha\beta})$ quantum queries by Grover search [\[vAGN24\]](#page-52-6).

Correctness can be seen as follows. If $|y| < A$, the first part of the algorithm determines $|y|$ exactly and outputs accordingly. Otherwise, $|y| \ge A$ and the algorithm continues. Then, if $|y| > B$, so that y contains fewer than $(n - B)$ 0s, the second part of the algorithm determines |y| exactly and outputs accordingly. Otherwise, $A \le |y| \le B$, so $HIDE_m[f](y) = b$. accordingly. Otherwise, $A \le |y| \le B$, so $HIDE_m[f](y) = b$.

Remark 3.4. The "moreover" part of [Proposition 3.3](#page-11-1) is false if f is not symmetric. For example, if $f(x) = x_1$, then it is not hard to see that $Q(g) = \Omega(\sqrt{m-n})$, which is not $O(\sqrt{m/n})$.

Now, TriangleEdge can be seen as the hiding transform of the element distinctness function. Intuitively, having no triangle that contains the target edge $\{u, v\}$ is equivalent to the neighbors of u and the neighbors of v being distinct.

Theorem 3.5. For $m, d \in \mathbb{N}$ with $m \geq d$, $Q(\text{HIDE}_m[\text{ED}_d]) = \widetilde{\Theta}(\sqrt{m} \cdot d^{1/6})$.

Proof. Since $Q(\text{ED}_d) = \Omega(d^{2/3})$, the lower bound $Q(\text{HIDE}_m[\text{ED}]) = \Omega(\sqrt{m} \cdot d^{1/6})$ follows directly from the lower bound in [Proposition 3.3.](#page-11-1) The upper bound, however, does not follow from the upper bound in [Proposition 3.3](#page-11-1) since that is only stated for $\Sigma = \{0, 1\}$. We can nonetheless prove the upper bound by a different argument as follows.

We can assume $r := m/d$ is an integer, or we can work with the least integer $m' > m$ such that m'/d is an integer since $m' \leq m + d \leq 2m$. We proceed to describe a quantum algorithm for $HIDE_m[ED_d]$.

Given an input $\tilde{x} \in (\Sigma \cup \{*\})^m$ to $HIDE_m[ED_d]$, we first apply a uniformly random permutation to \tilde{x} . Let x denote the resulting string. For $b \in [d]$, let $x^{(b)} \coloneqq x[(b-1)r+1 \dots br] \in (\Sigma \cup \{*\})^r$. A standard probability argument, such as that used to bound the maximum load in a balls-into-bins experiment [\[RS98,](#page-52-7) Theorem 1], yields

$$
\Pr[\forall b \in [d], x^{(b)} \text{ contains at most } \log(d) \text{ non-* symbols}] \ge 1 - O(1/d),\tag{3.4}
$$

where the probability is over the random permutation. We continue assuming the event in Eq. (3.4) occurs.

For any given $b \in [d]$, we can Grover search for all of the non-* symbols in $x^{(b)}$ using $O(\sqrt{r \log(d)})$ queries [\[vAGN24\]](#page-52-6) and output a string of length $\lceil \log(d) \rceil$, such that its first symbols are the non- $*$ symbols in $x^{(b)}$ and the rest are *s. Therefore, we can instantiate one query to a string y of length $d \cdot \lceil \log(d) \rceil$ containing *s and precisely the same non-* symbols as x using $O(\sqrt{r \log(d)})$ queries to x.

Now, we run the optimal quantum algorithm for element distinctness on y while mapping y_i to some symbol \perp_i outside of $\Sigma \cup \{*\}$ if $y_i = *$. (The \perp_i s are distinct for distinct *is*.) This allows us to compute $\text{HIDE}_m[\text{ED}_d]$ with $O(\sqrt{r \log(d)} \cdot (d \log(d))^{2/3}) = \widetilde{O}(\sqrt{m} \cdot d^{1/6})$ queries to the original input x, as required. \Box

Remark 3.6.

- (i) Another way of showing the upper bound in [Theorem 3.5](#page-11-0) is by a quantum walk that is amplified to the non-* part of the input x using $\tilde{O}(\sqrt{m/d})$ overhead, cf. proof of [Proposition 4.1.](#page-14-2)
- (ii) A benefit of the upper bound approach described in [Theorem 3.5](#page-11-0) is that it does not rely on the implementation details of the optimal quantum algorithm for element distinctness but rather only the structure of the problem. More specifically, this structure is used in the line "mapping y_i to some symbol \perp_i outside of $\Sigma \cup \{*\}$ if $y_i = *$ ". In particular, the same argument would also show that, for any constant integer $k \geq 2$, $Q(\text{HIDE}_m[k-\text{DIST}_d]) \leq \widetilde{O}(\sqrt{m/d} \cdot Q(k-\text{DIST}_d))$ because k-DIST_d has that same structure. Informally, using the same argument as in [Corollary 3.7,](#page-12-0) this implies that the problem of deciding whether a length-m edge list contains a $(k + 1)$ -clique that completes a target k-clique with d neighbor has quantum query complexity $\widetilde{O}(\sqrt{m/d} \cdot Q(k\text{-DIST}_d)).$

We now formally show that TriangleEdge_{m,d} has the same quantum query complexity as $HIDE_m(ED_d)$ by reducing these problems to each other. Our reduction also works in non-quantum query models.

Corollary 3.7. For $m, d \in \mathbb{N}$ with $m \geq d$, $Q(\text{Triangle}_{m,d}) = \widetilde{\Theta}(\sqrt{m}d^{1/6})$.

Proof. Let $x \in \binom{[n]}{2}$ $\binom{[n]}{2}^m$ be in the domain of $\mathsf{Triangle}_{m,d}^{\{1,2\}}.$ Let $\mathrm{ED}_d\colon [n]^d \rightarrow \{0,1\}.$ We can compute TriangleEdge ${}_{m,d}^{\{1,2\}}(x)$ by computing ${\sf HIDE}_m[\mathrm{ED}_d](\tilde{x})$, where for each $i\in[m],$ \tilde{x}_i is defined from $x_i\coloneqq\{u,v\}$ by

$$
\tilde{x}_i := \begin{cases}\n* & \text{if } \{u, v\} \cap \{1, 2\} = \varnothing \text{ or } \{u, v\} = \{1, 2\}, \\
v & \text{if } u = 1 \text{ and } v \neq 2, \\
u & \text{if } u \neq 1 \text{ and } v = 2,\n\end{cases}
$$
\n(3.5)

Observe that the mapping from x_i to \tilde{x}_i can be performed on the fly. Therefore $Q(\text{Triangle} \mathcal{A}) \leq$ $O(Q(HIDE_m[ED_d])) \le \widetilde{O}(\sqrt{m}d^{1/6})$ by [Theorem 3.5.](#page-11-0)

Conversely, let $\tilde{x} \in (\infty s] \cup \{*\}^m$ be in the domain of $HIDE_m[ED_d']$, where ED_d is ED_d but restricted to inputs containing at most a single collision pair (i.e., two symbols that are the same). Assume that $s\geq m.^{11}~$ $s\geq m.^{11}~$ $s\geq m.^{11}~$ Let TriangleEdge $_{m,d}^{\{s+1,s+2\}}\colon\binom{[s+2]}{2}$ $\binom{+2}{2}$ ^{*m*} \rightarrow {0, 1}. Then we can compute $\text{HIDE}_m[\text{ED}'_d](\tilde{x})$ by

¹¹This assumption is without loss of generality under our convention in the preliminaries of what $Q(\text{Triangle} \text{Hg}_{m,d})$ means when the alphabet size is not specified.

computing $\textsf{Triangle}^{\{s+1,s+2\}}_{m,d}(x)$, where for each $i \in [m],\,x_i$ is defined by

$$
x_i := \begin{cases} \{s+1, \tilde{x}_i\} & \text{or } \{s+2, \tilde{x}_i\} & \text{if } \tilde{x}_i \in [s], \\ \{1, i\} & \text{if } \tilde{x}_i = *, \end{cases}
$$
 (3.6)

where the choice of "or" in the first case is made uniformly at random. (Note that we consider ED'_{d} instead of ED_d and assume $s \geq m$ so that the x defined above is in the domain of TriangleEdge ${}_{m,d}^{\{s+1,s+2\}}$ for some choices of "or".)

If \tilde{x} contains a collision pair, then with probability at least $1/2$, x will be an yes-instance of $\text{Triangle}_{m,d}^{\{s+1,s+2\}}$. On the other hand, if \tilde{x} does not contain any collision pairs, x will be a no-instance of $triangle{f_{m,d}}^{s+1,s+2}$. Therefore, by repeating the above reduction a constant number of times, we can distinguish between these cases with high probability. Therefore $Q(\textsf{Triangle}_{m,d}^{\{s+1,s+2\}}) \geq \Omega(Q(\textsf{HIDE}_m[\text{ED}'_d])) = \Omega(\sqrt{m/d} \cdot Q(\text{ED}'_d)) = \Omega(\sqrt{m d}^{1/6})$ by [Proposition 3.3](#page-11-1) since $Q(ED'_d) = \Omega(d^{2/3})$.^{[12](#page-13-1)} \Box

Remark 3.8. The quantum query complexity of the analogue of the TriangleEdge for 3-DIST_m is $\Theta(\sqrt{m})$ and for 3-SUM_m is $\Theta(m^{2/3})$. By analogue, we mean detecting whether the input contains a full certificate given one position of the certificate. So we see that the quantum query complexity of TriangleEdge lies between that of these analogues.

The results of this section naturally raise the following conjecture.

Conjecture 3.9. Let $m, n \in \mathbb{N}$ with $m \geq n$. For any symmetric $f: \Sigma^n \to \{0,1\}$, $Q(\text{HIDE}_m[f]) \leq$ $O(\sqrt{m/n} \cdot Q(f)).$

We proved this conjecture (up to logarithmic factors) when the domain of f is Boolean using the structure of the optimal quantum query algorithm for such f . On the other hand, we proved this conjecture when $f = ED_d$ using the structure of the function itself. We believe that attacking this conjecture for arbitrary f would yield further insights into the structure of symmetric functions and their optimal quantum query algorithms.

Towards the above conjecture, we show the following proposition.

Proposition 3.10. Let $m, n \in \mathbb{N}$ with $m \geq n$. For any symmetric $f: \Sigma^n \to \{0,1\}$, $R(\text{HIDE}_m[f]) \leq$ $O(\frac{m}{n})$ $\frac{m}{n} \cdot R(f)$). Moreover, $Q(\text{HIDE}_m[f]) \le \widetilde{O}(\sqrt{m/n} \cdot Q(f)^3)$.

Proof. Write $k := R_{1/100}(f) \geq 1$. Since f is symmetric, [\[BKS01,](#page-50-9) Lemma 4.8 of full version] applies and shows that there exists a *variable oblivious*, uniform k -query randomized algorithm for computing f with bounded error 1/100 of the following form.

Given input $x \in \Sigma^n$:

- (i) Choose a uniformly random subset $S \subseteq [n]$ of size k.
- (ii) Query x_i for all $i \in S$.
- (iii) Output 1 with probability p, where $p = p(X)$ is a function of the size-k multiset $X \coloneqq \{x_i \mid$ $i \in S$.

Let $K \coloneqq \frac{m}{n}$ $\frac{m}{n}$ ·100k and consider the following K-query randomized algorithm for computing $HIDE_m[f]$:

¹²The $Q(\text{HIDE}_m[f]) = \Omega(\sqrt{m/n} \cdot Q(f))$ part of [Proposition 3.3](#page-11-1) also holds for partial f (like ED'_d) by the same argument.

Given input $y \in (\{*\} \cup \Sigma)^m$ in the domain of $HIDE_m[f]$:

- (i) Choose a uniformly random subset $T \subseteq [m]$ of size K. Let Y denote the multiset $\{y_i \mid i \in T\}$.
- (ii) If the number of non- $*$ symbols in Y is less than k, output 0 or 1 uniformly at random.
- (iii) If the number of non- $*$ symbols in Y is at least k, choose a uniformly random size-k submultiset X of the non- $*$ symbols in Y and output 1 with probability $p(X)$, where $p(X)$ is as defined above.

This algorithm behaves exactly the same as the previous algorithm provided we reach the third step. The expected number of non- $*$ symbols in Y is 100k. By the Paley-Zygmund inequality, the probability of Y containing at least k non-* symbols is at least $(1 - 1/100)^2 K^2 / (K + K^2) \ge 0.97$ since $K \ge 100$. Therefore, we reach the third step with probability at least 0.97. Therefore the algorithm is correct with probability at least $0.97(1 - 1/100) \ge 2/3$. Hence $R(\text{HIDE}_m[f]) \le O(\frac{m}{n})$ $\frac{m}{n} \cdot R(f)$).

For the "moreover" part, by the same permutation argument as in the proof of the upper bound in [Theorem 3.5,](#page-11-0) it follows that $Q(\text{HIDE}_m[f]) \leq O(\sqrt{(m/n) \cdot \log(n)} \cdot Q(\text{HIDE}_{\lceil n \log(n) \rceil}[f]))$. Therefore, it suffices to show that $Q(\text{HIDE}_{\lceil n \log(n) \rceil}[f]) \le \widetilde{O}(Q(f)^3)$. But this is true since

$$
Q(\text{HIDE}_{\lceil n \log(n) \rceil}[f]) \le R(\text{HIDE}_{\lceil n \log(n) \rceil}[f]) \le O(\log(n) \cdot R(f))
$$

$$
\le O(\log(n) \cdot Q(f)^3) \le \widetilde{O}(Q(f)^3),
$$

where the first inequality uses $Q(\cdot) \leq R(\cdot)$, the second inequality uses the first part of this proposition, and the third inequality uses the result of [Cha19] for symmetric functions f. and the third inequality uses the result of $[Cha19]$ for symmetric functions f .

4 TriangleVertex and Shuffling

In this section, we consider the TriangleVertex problem of deciding whether an input edge list of length m has a triangle containing a target vertex of degree $d \leq m$.

We take this opportunity to study the shuffling transformation as well. As mentioned in the introduction, the edge list itself can be viewed as a shuffled adjacency list. In TriangleVertex, there is an additional "block-wise" notion of shuffling, where the blocks consist of edges incident and not incident to the target vertex, respectively. This latter notion motivates our definition of shuffled direct sum.

4.1 TriangleVertex

We first build intuition by directly working out some upper and lower bounds on the quantum query complexity of TriangleVertex. The upper bound uses a quantum walk algorithm, and the lower bound uses a reduction from the hiding transform of 3-DIST.

Proposition 4.1. For $m, d \in \mathbb{N}$ with $m \geq d$, $Q(\text{TriangleVertex}_{m,d}) = \widetilde{O}(\sqrt{m}d^{1/4})$.

Proof. Suppose the given vertex is vertex 1. Let $x \in \binom{[n]}{2}$ $\left\lbrack n\atop2\right\rbrack^m$ be the input to the TriangleVertex $_{m,d}$ problem. Then $|\{i \in [m] \mid |x_i \cap \{u\}| = 1\}| \leq d$ and we may wlog assume the inequality is saturated. Observe that x can be viewed as having two parts: one part $A \subseteq [m]$ such that $i \in A$ if and only if x_i is an edge incident to vertex 1, and the other part $B \coloneqq [m] - A$ containing the remaining edges.

We perform a quantum walk based on the uniform random walk on the Hamming graph G labeled by r-tuples of indices from A, where $r \in \mathbb{N}$ will be optimized later. We say a vertex $(i_1, \ldots, i_r) \in A^r$ of G is marked if there exists an $i \in B$ such that x_i forms a triangle with x_{i_j} and x_{i_k} for some $j, k \in [r]$. At each vertex, we also store the data $(x_{i_1},...,x_{i_r})$.

We now analyze the query complexity of this quantum walk following [\[MNRS11\]](#page-52-8).

- (i) The setup cost S of the quantum walk is $S = \tilde{O}(r\sqrt{m/d})$ by amplitude amplification, where the \ddot{O} accounts for error reduction.
- (ii) The update cost of the quantum walk is $U = \tilde{O}(\sqrt{m/d})$ by amplitude amplification, where the \ddot{O} accounts for error reduction, which crucially uses the uniformity of the underlying random walk.
- (iii) The checking cost of the quantum walk is $C = O(\sqrt{m})$ by Grover search.
- (iv) The fraction of marked vertices is $\varepsilon = \Omega((r/d)^2)$ if x is a yes-instance, else $\varepsilon = 0$.
- (v) The spectral gap of the transition matrix of the random walk is $\delta = \Omega(1/r)$.

Therefore, [\[MNRS11\]](#page-52-8) shows that the query complexity of the quantum walk is

$$
O\left(S + \frac{1}{\sqrt{\varepsilon}} \left(\frac{1}{\sqrt{\delta}} \cdot U + C\right)\right) = \widetilde{O}\left(r\sqrt{\frac{m}{d}} + \frac{1}{\sqrt{r}}\sqrt{md} + \frac{d}{r}\sqrt{m}\right) = \widetilde{O}(\sqrt{m} \cdot d^{1/4}),\tag{4.1}
$$

by optimally setting r to be $\lceil d^{3/4} \rceil$.

Proposition 4.2. For $m, d \in \mathbb{N}$ with $m \geq d$, $Q(\text{TriangleVertex}_{m,d}) \geq \Omega(\sqrt{m/d} \cdot Q(3\text{-DIST}_d)).$

Proof. We describe a reduction from $HIDE_m[3-DIST_d]$ to TriangleVertex_{m,d}. Assume wlog that m is a multiple of 3. Let $x \in ([s] \cup \{*\})^m$ be an input to $HIDE_m[3-DIST_d]$. Choose a uniformly random partition of $[m]$ into three subsets X, Y, Z of the same size $m/3$. Let x^X, x^Y, x^Z denote the subsequence of x formed by indices in X, Y, Z respectively. If x has a 3-collision, the probability of the event that exactly one of the three colliding indices is in each of X, Y , and Z is at least $2/9$.

We can compute $HIDE_m[3-DIST_d](x)$ by computing TriangleVertex_{m,d} on an edge list y with vertex set

$$
\{v\} \dot{\cup} \{u\} \dot{\cup} \{a^X \mid a \in [s]\} \dot{\cup} \{a^Y \mid a \in [s]\} \dot{\cup} \{*_i \mid i \in [m]\}\tag{4.2}
$$

 \Box

and target vertex v. For each $i \in [m]$, we map x_i to an edge y_i as follows.

(i) Case $x_i \in [s]$: Map x_i to edge $\{x_i^X, v\}$ if $i \in X$, edge $\{x_i^Y, v\}$ if $i \in Y$, and edge $\{x_i^X, x_i^Y\}$ if $i \in Z$. (ii) Case $x_i = *$: Map x_i to $\{u, *_{i}\}.$

Note that y defined this way is of length m, and the number of edges in y incident to v is exactly d. Therefore, y is a valid input to TriangleVertex $_{m,d}$.

If x has a 3-collision, then y has a triangle containing vertex v with probability at least $2/9$. If x does not have a 3 collision, then y never has a triangle containing vertex v. Therefore, repeating the reduction a constant number of times allows us to compute $HIDE_m[3-DIST_d](x)$ with high probability. Therefore, $Q(\mathsf{TriangleVertex}_{m,d})$ is lower bounded by $Q(\mathsf{HIDE}_m[3\text{-DIS}\mathsf{T}_d]),$ which is $\Omega(\sqrt{m/d}\!\cdot\!Q(3\text{-DIS}\mathsf{T}_d))$ by [Proposition 3.3,](#page-11-1) as required.

Observe that in the proof of [Proposition 4.1](#page-14-2) above, the algorithm does not apriori know which part of the input x is in A and which part is in B. It appears that the shuffling of these parts adds to the complexity of the problem. To investigate how generic this phenomenon is, we consider two types of questions motivated by shuffling.

- (i) How does shuffling a function change its complexity?
- (ii) How does shuffling affect direct sum theorems?

We formalize these questions in the next two sections and prove some first results.

4.2 Shuffled functions

We recall [Definition 1.3](#page-3-0) of shuffling from the introduction. Given a function $f: D \subseteq \Sigma^n \to \{0,1\}$, the shuffling transform of f is defined by $\text{SHUFFLE}[f] : D \subseteq (\Sigma \times [n])^n \to \{0,1\}$ such that for $v \in \Sigma^n$ and $\pi \in \mathfrak{S}_{[n]}$ with $(v_{\pi^{-1}(1)}, v_{\pi^{-1}(2)}, \ldots, v_{\pi^{-1}(n)}) \in \widetilde{D}$,

SHUFFLE[f] : $((v_1, \pi(1)), \ldots, (v_n, \pi(n))) \mapsto f(v_{\pi^{-1}(1)}, v_{\pi^{-1}(2)}, \ldots, v_{\pi^{-1}(n)}).$

Next, we collect some simple facts about $SHUFFLE[f]$.

Fact 4.3. For any $f: E \subseteq \Sigma^n \rightarrow \{0,1\}$, the following holds

- (i) $Q(\text{SHUFFLE}[f]) = \Omega(Q(f)).$
- (ii) If f is symmetric, then $Q(\text{SHUFFLE}[f]) = Q(f)$.
- (iii) $Q(\text{SHUFFLE}[f]) = O(\sqrt{n} \cdot Q(f))$. Moreover, there exists f such that $Q(\text{SHUFFLE}[f]) = \Omega(\sqrt{n} \cdot Q(f))$.

Proof. [Item \(i\):](#page-16-2) Any query complexity measure on $SHUFFLE[f]$ is at least that on the f since $SHUFFLE[f]$ contains f as a subfunction. [Item \(ii\):](#page-16-3) If f is symmetric, then any query complexity measure on f is the same as that measure on $SHUFFLE[f]$ since the algorithm computing $SHUFFLE[f]$ could simply ignore the second coordinate of each input symbol. [Item \(iii\):](#page-16-4) Let A be an arbitrary algorithm for f. For any $z \in \Sigma^n$, we can simulate the quantum query oracle in the algorithm A by exact Grover search through $x \in (\Sigma \times [n])^n$ over the second coordinate for the target index, and exact Grover search incurs a multiplicative overhead of $O(\sqrt{n})$. The "moreover" part follows by simply taking $f(x) = x_1$ to be the dictator function. This f witnesses a 1 vs $\Omega(\sqrt{n})$ separation between $Q(f)$ and $Q(\text{SHUFFLE}[f])$. \Box

We record one more fact that relates the quantum and randomized query complexities for **SHUFFLE**[f].

Fact 4.4 (cf. [\[Cha19\]](#page-50-11)). For any $f: E \subseteq \Sigma^n \to \{0, 1\}$,

 $Q(\mathsf{SHUFFLE}[f])) = \Omega(R(\mathsf{SHUFFLE}[f])^{1/3}).$

The importance of the above fact is that it provides a generic lower bound method for the quantum query complexity for problems in the edge list model, since analyzing the randomized query complexity is often easier. The proof of this fact is based on the simple observation that $SHUFFLE[f]$ transforms any f into a symmetric function. The beautiful work of Chailloux $[Cha19]$ shows that the quantum query complexity of any symmetric function is at least big- Ω of its randomized query complexity raised to the power 1/3.

As we have observed, for general f, $Q(\text{SHUFFLE}[f])$ can be unboundedly larger than $Q(f)$ while for symmetric f, $Q(\text{SHUFFLE}[f]) = Q(f)$. Therefore, the interesting question becomes what happens when f is partially symmetric, for example, by being defined via graph properties? This question can be used to understand how the complexity of a graph property changes in the edge list model versus the adjacency list and adjacency matrix models.

Can there be a large separation between the quantum query complexity of a graph property in the edge list model versus the adjacency list model?

We show there can be an exponential separation.

Theorem 4.5. There is (partial) graph property P on graphs of maximum degree 5, such that its quantum query complexity in the adjacency list model is $O(polylog(n))$, but its quantum query complexity in the edge list model is $\Omega(n^{1/48})$.

Proof. We know from [\[BCG](#page-49-2)⁺20] that there is a graph property $\mathcal P$ in the adjacency list model on graphs of maximum degree 5 with quantum query complexity $O(polylog(n))$ and randomized query complexity $\Omega(n^{1/16})$, where the input adjacency list has size n. Now, by [Fact 4.4,](#page-16-5) when we try to compute P in the edge list model, the quantum query complexity is at least $\Omega(n^{1/48})$.

As the edge list model is the shuffled version of the adjacency list model, we find it natural to also consider the shuffled version of the adjacency matrix model and ask the following question.

Can there be a large separation between the quantum query complexity of a graph property in the adjacency matrix model versus the shuffled adjacency matrix model?

We can no longer appeal to the previous argument because $[BCG^+20]$ shows that the quantum query complexity of any graph property in the adjacency matrix model is at least that of its randomized query complexity raised to the 1/6 power. Nonetheless, we can answer the question with "yes" by considering a function ΣMAJ_n defined in [Definition 1.8.](#page-6-1) ΣMAJ_n can be seen as a (directed) graph property computed in the adjacency matrix model.

Recall that $\Sigma MAJ_n: D_0 \dot{\cup} D_1 \subseteq \{0,1\}^{n^2} \to \{0,1\}$ is defined to be the following restriction of $MAJ_n \circ$ MAJ_n on n^2 bits.

$$
\Sigma \mathbf{MAJ}_n : x \mapsto \begin{cases} 0, & x \in D_0, \\ 1, & x \in D_1, \end{cases}
$$

where D_0 consists of all the $x = (x_{1,1}, x_{1,2}, \ldots, x_{n,n}) \in \{0,1\}^{n^2}$ such that there exists a subset $S \subseteq [n]$ of size at least $2n/3$ such that for all $i \in S$, $x^i := (x_{i,1}, \ldots, x_{i,n})$ has Hamming weight $|x^i| \geq 2n/3$ and for all $i \in [n] - S$, $|x^i| \leq n/3$; while for $x = (x_{1,1}, x_{1,2}, \ldots, x_{n,n}) \in \{0,1\}^{n^2}$ in D_1 if and only if there exists a subset $S \subseteq [n]$ of size at most $n/3$ such that for all $i \in S$, $x^i := (x_{i,1}, \ldots, x_{i,n})$ has Hamming weight $|x^{i}| \geq 2n/3$ and for all $i \in [n] - S$, $|x^{i}| \leq n/3$.

Theorem 4.6. $R(\Sigma MAJ_n) = O(1)$ but $R(\text{SHUFFLE}[\Sigma MAJ_n]) = \Omega(\sqrt{n})$. In addition, $Q(\Sigma MAJ_n) =$ $O(1)$ but $Q(\mathsf{SHUFFLE}[\Sigma \mathbf{MAJ}_n]) = \Omega(n^{1/6}).$

Proof. To see that $R(\Sigma MAJ_n) = O(1)$, observe that for a given x^i we can test with high probability whether $|x^{i}| \geq 2n/3$ (call such an x^{i} dense) or $|x^{i}| \leq n/3$ (call such an x^{i} sparse) by querying x^{i} repeatedly at uniformly random locations a constant number of times. Then we choose a subset of $T \subseteq [n]$ of constant size uniformly at random and for each $i \in T$ test whether x^i is dense or sparse. If more than half are dense, we output 0. If at most half are dense, we output 1. It is not hard to see that this algorithm computes ΣMAJ_n with at most 1/3 probability of error.^{[13](#page-17-1)} Therefore, $Q(\Sigma MAJ_n) \le R(\Sigma MAJ_n) = O(1)$.

For the lower bounds, by [Fact 4.4,](#page-16-5) it suffices to show $R(\text{SHUFFLE}[\Sigma \text{MAJ}_n]) = \Omega(\sqrt{n})$ to conclude the proof. Assume wlog that n is a multiple of 12. Then by Yao's lemma, it suffices to show that the following two distributions \mathcal{D}_0 and \mathcal{D}_1 on inputs to SHUFFLE[\sum MAJ_n] are hard to distinguish by a deterministic algorithm of query complexity $O(\sqrt{n})$, where we define

 \mathcal{D}_b : sample $x \leftarrow H_b$ and $\pi \leftarrow \mathfrak{S}_{[n] \times [n]}$ (the set of all permutations on $[n] \times [n]$), then output

$$
(x_{\pi(1,1)}, \pi(1,1)), (x_{\pi(1,2)}, \pi(1,2)), \dots, (x_{\pi(n,n)}, \pi(n,n)).
$$
\n(4.3)

Here, $H_0 \subseteq D_0$ and $H_1 \subseteq D_1$ are defined by

$$
H_0 := \{ (x_{1,1}, x_{1,2}, \dots, x_{n,n}) \in \{0, 1\}^{n^2} \mid \exists S \subseteq [n], \text{ s.t.}
$$

\n(i) $|S| = 2n/3$, (ii) $\forall i \in S, |x^i| = 3n/4$, and (iii) $\forall i \notin S, |x^i| = 0 \}$,
\n
$$
H_1 := \{ (x_{1,1}, x_{1,2}, \dots, x_{n,n}) \in \{0, 1\}^{n^2} \mid \exists S \subseteq [n], \text{ s.t.}
$$

\n(i) $|S| = n/3$, (ii) $\forall i \in S, |x^i| = n$, and (iii) $\forall i \notin S, |x^i| = n/4 \}$.
\n(4.4)

Let $t \in \mathbb{N}$. For $0 \le \beta < 1/2 < \alpha \le 1$ and $\gamma \in [0,1]$, define the random process $P(\alpha,\beta,\gamma)$ as follows. We refer to $P(3/4, 0, 2/3)$ as P_0 and $P(1, 1/4, 1/3)$ as P_1 . The P_i s are defined in such a way that the

¹³An alternative way to see this is simply that ΣMAJ_n is the composition of two gapped MAJ_n functions, each of which has constant randomized query complexity. Therefore, the randomized query complexity of the composition is also constant using the fact that $R(f \circ g) = O(R(f) \cdot R(g) \cdot \log(R(f))).$

distribution on query outcomes induced by any t-query deterministic decision tree (that we assume wlog never queries an index it has already queried and is a balanced tree) running on an input chosen sampled according to \mathcal{D}_i is the same as the distribution P_i .

Process $P(\alpha, \beta, \gamma)$.

Set SEEN = \emptyset , DENSE = \emptyset , SPARSE = \emptyset , and $\forall i \in [n]$, $M_i = N_i = 0$. Repeat the following t times:

- (i) Randomly select $(i, j) \leftarrow [n] \times [n] \text{SEEN}$.
- (ii) If $i \in$ DENSE, select "dense". If $i \in$ SPARSE, select "sparse". Else randomly select "dense" or "sparse" such that "dense" is selected with probability

$$
p_{\text{dense}} \coloneqq \frac{\gamma \cdot n - |\text{DENSE}|}{n - |\text{DENSE}| - |\text{SPARSE}|}. \tag{4.5}
$$

(i) If "dense" is selected, randomly set a bit b to be 1 or 0 such that 1 is selected with probability

$$
p_1 := \frac{(\alpha n - M_i)}{n - N_i}.\tag{4.6}
$$

- If $b = 1$, set M_i to $M_i + 1$. Set DENSE to DENSE ∪ $\{i\}$.
- (ii) If "sparse" is selected, randomly set a bit b to be 1 or 0 such that 1 is selected with probability

$$
q_1 := \frac{(\beta n - M_i)}{n - N_i}.\tag{4.7}
$$

If $b = 1$, set M_i to $M_i + 1$. Set SPARSE to SPARSE ∪ $\{i\}$.

- (iii) Set SEEN to SEEN ∪ (i, j) . Set N_i to $N_i + 1$.
- (iv) Output $(i, j, b) \in [n] \times [n] \times \{0, 1\}.$

Our goal is to show that the total variation distance between the output distributions of P_0 and P_1 scales as $O(t^2/n)$. We write TVD for this particular total variation distance. In the following, we write $Pr_i[\cdot]$ for taking the probability of an event over the randomness in the process P_i . We also assume $t-1 \leq n^2/2$ to help simplify calculations.

Let Bad denote the subset of $([n] \times [n] \times \{0,1\})^t$ such that a t-tuple (i_k, j_k, b_k) , $k = 1, 2, \ldots, t$ belongs to Bad if and only if there exists $k_1 \neq k_2$ such that $i_{k_1} = i_{k_2}$. Then it is easy to see that

$$
\Pr_0[\text{Bad}] = \Pr_1[\text{Bad}] = 1 - 1 \cdot \frac{n^2 - n}{n^2 - 1} \cdot \frac{n^2 - 2n}{n^2 - 2} \cdots \frac{n^2 - (t - 1)n}{n^2 - (t - 1)}
$$
\n
$$
= 1 - 1 \cdot \left(1 - \frac{n - 1}{n^2 - 1}\right) \cdot \left(1 - \frac{2n - 2}{n^2 - 2}\right) \cdots \left(1 - \frac{(t - 1)(n - 1)}{n^2 - (t - 1)}\right) \le \frac{t^2}{n},\tag{4.8}
$$

where the last inequality uses $\forall a, b \geq 0, (1 - a)(1 - b) \geq 1 - a - b$ and $t - 1 \leq n^2/2$.

Let $X, Y \in ([n] \times [n] \times \{0, 1\})^t$ denote the output of process P_0 and P_1 respectively. Then

$$
TVD = \sum_{x} |Pr_0[X = x] - Pr_1[Y = x]| \le \sum_{x \notin \text{Bad}} |Pr_0[X = x] - Pr_1[Y = x]| + \frac{2t^2}{n}.
$$
 (4.9)

We proceed to analyze the first term. Write $X^1 \in ([n] \times [n])^t$ for the non-bit-part of X. Write $X^2 \in \{0,1\}^t$ for bit-part of X. Similarly write Y^i, x^i . Write Bad¹ $\subseteq ([n] \times [n])^t$ for the non-bit-part of Bad. Then

$$
\sum_{x \notin \text{Bad}} |\Pr_0[X = x] - \Pr_1[Y = x]|
$$
\n
$$
= \sum_{x \notin \text{Bad}} |\Pr_0[X^1 = x^1, X^2 = x^2] - \Pr_1[Y^1 = x^1, Y^2 = x^2]|
$$
\n
$$
= \sum_{x \notin \text{Bad}} |\Pr_0[X^2 = x^2 | X^1 = x^1] \Pr[X^1 = x^1] - \Pr_1[Y^2 = x^2 | Y^1 = x^1] \Pr[Y^1 = x^1]|
$$
\n
$$
= \sum_{x \notin \text{Bad}} |\Pr_0[X^2 = x^2 | X^1 = x^1] - \Pr_1[Y^2 = x^2 | Y^1 = x^1]| \cdot \Pr[X^1 = x^1],
$$
\n
$$
= \sum_{x^1 \notin \text{Bad}^1} \left(\sum_{x^2} |\Pr_0[X^2 = x^2 | X^1 = x^1] - \Pr_1[Y^2 = x^2 | Y^1 = x^1]| \right) \cdot \Pr[X^1 = x^1], \tag{4.10}
$$

where the second-to-last equality uses $Pr[X^1 = x^1] = Pr[Y^1 = x^1]$, which holds because the first steps defining P_0 and P_1 are identical.

Now, write $U, V \in \{\text{dense}, \text{sparse}\}\$ for the sequence of "dense" or "sparse" choices during the process P_0 and P_1 respectively. Given $u \in {\text{dense, sparse}}^t$, write \bar{u} for u but switching "dense" and "sparse" component-wise.

For a fixed $x \notin$ Bad, write $Pr_1[\cdot \mid X^1 = x^1]$ and $Pr_2[\cdot]$ for $Pr_1[\cdot \mid Y^1 = x^1]$. Then,

$$
\Pr_0[X^2 = x^2 | X^1 = x^1] - \Pr_1[Y^2 = x^2 | Y^1 = x^1] \n= \sum_u \widetilde{\Pr}_1[X^2 = x^2 | U = u] \widetilde{\Pr}_1[U = u] - \widetilde{\Pr}_2[Y^2 = x^2 | V = u] \widetilde{\Pr}_2[V = u] \n= \sum_u (\widetilde{\Pr}_1[X^2 = x^2 | U = u] - \widetilde{\Pr}_2[Y^2 = x^2 | V = \bar{u}]) \widetilde{\Pr}_1[U = u],
$$
\n(4.11)

where the last equality uses $Pr_0[U = u \mid X^1 = x^1] = Pr_1[V = \bar{u} \mid Y^1 = x^1]$, which holds because when $x \notin$ Bad, "dense" and "sparse" choices are made randomly in both P_0 and P_1 ; the important bar over u on the right-hand side arises from the fact that the γ defining P_1 is 1 minus that defining P_0 .

Now let $W \in {\text{dense, sparse}}^t$ denote a random variable such that each $W_i \in {\text{dense, sparse}}$ is independently distributed and equal to "dense" with probability $2/3$. Consider a bag of n balls such that $2n/3$ are labeled "dense" and $n/3$ are labeled "sparse". Observe that the distribution on $u \in$ {dense, sparse}^t defined by $Pr_1[U = u]$ is the same as the distribution of labels when drawing t balls from the bag without replacement. On the other hand, the distribution of W is the same as the distribution of labels when drawing t balls from the bag with replacement. Therefore, we can appeal to [Fre 77] to deduce that

$$
\sum_{u} \left| \Pr[W = u] - \widetilde{\Pr}_1[U = u] \right| \le \frac{t(t - 1)}{2n}.
$$
\n(4.12)

Therefore, summing Eq. (4.11) over $x^2 \in \{0,1\}^t$ gives

$$
\sum_{x^2} \left| \Pr_0[X^2 = x^2 \mid X^1 = x^1] - \Pr_1[Y^2 = x^2 \mid Y^1 = x^1] \right|
$$

\n
$$
= \sum_{x^2} \left| \sum_u \left(\widetilde{\Pr}_1[X^2 = x^2 \mid U = u] \widetilde{\Pr}_1[U = u] - \widetilde{\Pr}_2[Y^2 = x^2 \mid V = \bar{u}] \widetilde{\Pr}_1[U = u] \right) \right|
$$

\n
$$
\leq \sum_{x^2} \left| \sum_u \left(\widetilde{\Pr}_1[X^2 = x^2 \mid U = u] \widetilde{\Pr}_1[U = u] - \widetilde{\Pr}_1[X^2 = x^2 \mid U = u] \Pr[W = u] \right) \right|
$$

\n
$$
+ \sum_{x^2} \left| \sum_u \left(\widetilde{\Pr}_1[X^2 = x^2 \mid U = u] \Pr[W = u] - \widetilde{\Pr}_2[Y^2 = x^2 \mid V = \bar{u}] \Pr[W = u] \right) \right|
$$

\n
$$
+ \sum_{x^2} \left| \sum_u \left(\widetilde{\Pr}_2[Y^2 = x^2 \mid V = \bar{u}] \Pr[W = u] - \widetilde{\Pr}_2[Y^2 = x^2 \mid V = \bar{u}] \widetilde{\Pr}_1[U = u] \right) \right|
$$

\n
$$
\leq \sum_{x^2} \left| \sum_u \left(\widetilde{\Pr}_1[X^2 = x^2 \mid U = u] - \widetilde{\Pr}_2[Y^2 = x^2 \mid V = \bar{u}] \right) \Pr[W = u] + \frac{2t^2}{n} = \frac{2t^2}{n}, \quad (4.13)
$$

where the first inequality is the triangle inequality, the second inequality uses [Eq. \(4.12\)](#page-19-1) twice, and the last equality follows from the observations that

- (i) the distribution over $x^2 \in \{0,1\}^t$ defined by $\sum_u \Pr_1[X^2 = x^2 \mid U = u] \cdot \Pr[W = u]$ is the same as binomial $B \coloneqq \text{Bin}(t, \frac{2}{3} \cdot \frac{3}{4})$ $\frac{3}{4}) = \text{Bin}(t, \frac{1}{2}).$
- (ii) the distribution over $x^2 \in \{0,1\}^t$ defined by $\sum_u \widetilde{\Pr}_2[Y^2 = x^2 \mid V = \bar{u}] \Pr[W = u]$ is the same as binomial $\text{Bin}(t, \frac{2}{3} \cdot \frac{1}{4} + \frac{1}{3})$ $(\frac{1}{3} \cdot 1) = \text{Bin}(t, \frac{1}{2}) = B.$

Combining Eqs. (4.9) , (4.10) and (4.13) , we see

TVD
$$
\leq \frac{2t^2}{n} + \sum_{x \notin \text{Bad}} \left| \Pr_0[X = x] - \Pr_1[Y = x] \right|
$$

 $\leq \frac{2t^2}{n} + \sum_{x^1 \notin \text{Bad}^1} \frac{2t^2}{n} \Pr[X^1 = x^1] \leq \frac{4t^2}{n},$

as required, where the first step uses Eq. (4.9) , and the second step uses Eq. (4.10) and (4.13) .

 \Box

Remark 4.7. The lower bound for $R(\text{SHUFFLE}[\Sigma \text{MAJ}_n]) = \Omega(\sqrt{n})$ is tight: for large enough constant C, when we query $C\sqrt{n}$ random positions of the input, there will be $\Omega(1)$ blocks in each of which we have queried at least 2 entries. Then we can determine $\text{SHUFFLE}[\Sigma \text{MAJ}_n]$ with an $\Omega(1)$ advantage. We conjecture that $Q(\text{SHUFFLE}[\Sigma \text{MAJ}_n]) = \Omega(n^{1/3}).$

4.3 Shuffled direct sum

In the TriangleVertex problem, the shuffling can be seen as arising from a two-step process. The first step shuffles among edges incident to the target vertex v (or not incident to v), and the second step shuffles between edges incident or not incident to v . The latter type of shuffling motivates the notion of shuffled direct sum in [Definition 1.5.](#page-3-1)

Recall that for $f: \Sigma^n \to \{0,1\}$, the k-shuffled direct sum of f, SHUFFLE^k[f]: $D \subseteq (\Sigma \times [k])^{kn} \to$ $\{0,1\}^k$, is defined by

- (i) $x = ((v_1, c_1), \ldots, (v_{kn}, c_{kn})) \in D$ if and only if for all $j \in [k]$, there are exactly n indices $i \in [kn]$ such that $c_i = j$.
- (ii) SHUFFLE^k[f](x) is defined to be $(f(v^{(1)}), \ldots, f(v^{(k)}))$, where $v^{(j)}$ is the subsequence of $v := v_1 \ldots v_{kn}$ indexed by those $i \in [kn]$ such that $c_i = j$.

Naturally, the question is how $Q(\text{SHUFFLE}^k(f))$ relates to $Q(\text{SHUFFLE}(f))$. Since SHUFFLE $^k(f)$ restricts to the k-fold direct sum of f, the direct sum theorem for the quantum query complexity $[ACLT10,$ [Rei11\]](#page-52-3) immediately gives the following.

Fact 4.8. For any any $f: \Sigma^n \to \{0,1\}$, $Q(\text{SHUFFLE}^k[f]) = \Omega(k \cdot Q(f)).$

The following result shows that the above lower bound is tight when the domain of f is $\{0,1\}^n$.

Proposition 4.9. For any symmetric $f: \{0,1\}^n \to \{0,1\}$, $Q(\text{SHUFFLE}^k[f]) = \widetilde{\Theta}(k \cdot Q(f)).$

Proof. As in the proof of [Proposition 3.3,](#page-11-1) we use the fact from $[BBC^+01]$ that $Q(f) = \Theta(\sqrt{n(n - \Gamma(f))})$, where $\Gamma(f) := \min\{|2k - n + 1| \mid f_k \neq f_{k+1}\}\$ and $f_k := f(x)$ for all x such that $|x| = k$. Observe that f_k must be constant for all $k \in \{(n-\Gamma(f))/2, \ldots, (n+\Gamma(f)-2)/2\}$. Call this constant $b \in \{0,1\}$. We also write $A := (n - \Gamma(f))/2$ and $B := (n + \Gamma(f) - 2)/2$ for convenience.

We consider the following quantum algorithm for SHUFFLE^k[f].

Algorithm for SHUFFLE $k[f]$

On input $x := ((v_1, c_1), \ldots, (v_{kn}, c_{kn})) \in (\{0, 1\} \times [k])^{kn}$:

- (i) Use Grover search to collect up to kA distinct indices $i \in [kn]$ such that $v_i = 1$, but as soon as we collect at least A such indices i from a fixed copy $c \in [k]$ of f, i.e., $c_i = c$, we stop collecting all further indices i from copy c and record that "copy c is above lower threshold". (This stopping can be done on the fly since c_i tells which copy of f it is associated with.) When no more indices i can be collected, for each copy of f not "above lower threshold", record the number of indices i collected that are associated with it.
- (ii) Use Grover search to collect up to $k(n-B)$ distinct indices $i \in [kn]$ such that $v_i = 0$, but as soon as we collect at least $(n - B)$ such indices i from a fixed copy $c \in [k]$ of f, i.e., $c_i = c$, we stop collecting all further indices i from copy c and record that "copy c is below upper threshold". When no more indices i can be collected, for each copy of f not "below upper threshold", record the number of indices i collected that are associated with it.

Then:

- (i) For copies of f that are "above lower threshold" and "below upper threshold", output b .
- (ii) For copies of f that are not "above lower threshold", output f_k where k is the number of indices i recorded that are associated with that copy in step I.
- (iii) For copies of f that are not "below upper threshold", output f_{n-k} where k is the number of indices i recorded that are associated with that copy in step II.

The quantum query complexity of this algorithm, accounting for error suppression, is

$$
\widetilde{O}(\sqrt{kA \cdot (kn)} + \sqrt{k(n-B) \cdot (kn)}) = \widetilde{O}(k\sqrt{n(n-\Gamma(f))}) = \widetilde{O}(k \cdot Q(f)),\tag{4.14}
$$

 \Box

using the basic fact that collecting (up to) α marked items from a list of β items costs $\tilde{O}(\sqrt{\alpha\beta})$ quantum queries by Grover search [\[vAGN24\]](#page-52-6).

The correctness of the algorithm can be argued similarly to [Proposition 3.3](#page-11-1) so we omit it.

We conjecture that [Proposition 4.9](#page-21-0) still holds for symmetric $f: \Sigma^n \to \{0,1\}$ even if Σ is non-Boolean.

Conjecture 4.10. For any symmetric $f: \Sigma^n \to \{0,1\}$, $Q(\text{SHUFFLE}^k[f]) = \Theta(k \cdot Q(f)).$

We remark that the analogue of this conjecture for randomized query complexity is true by a similar argument to the proof of [Proposition 3.10.](#page-13-0)

5 Triangle Finding

In this final section, we study the triangle-finding problem, FTriangle, in the edge list model. We first show that this problem bridges 3-DIST and 3-SUM. Then, we give a nearly tight characterization of the problem's quantum query complexity when the input has low maximum degree, for example, if it is a random sparse graph. Our proof of this characterization constitutes the most technically demanding part of this paper.

5.1 Bridging 3-DIST and 3-SUM

We now formalize the aforementioned connection of triangle finding to 3-DIST and 3-SUM in the following proposition.

Proposition 5.1. $\Omega(Q(3\text{-}DIS\mathsf{T}_m)) \leq Q(\text{Triangle}_m) \leq O(Q(3\text{-}SUM_m))$. In particular, if $Q(3\text{-}DIS\mathsf{T}_m) \geq$ $\Omega(m^{\alpha})$, then $\Omega(m^{\alpha}) \leq Q(\textsf{Triangle}_m) \leq O(m^{3/4})$.

For a comparison, the "trivial" lower bound one obtains from [Fact 4.4](#page-16-5) would be $Q(\text{Triangle}_m)$ = $\Omega(m^{1/3})$, while the above connection gives $Q(\textsf{Triangle}_m) = \Omega(m^{2/3})$ as the latter is the current record for lower bounding 3-DIST [\[AS04\]](#page-49-5).

Proof. The argument for $\Omega(Q(3\text{-}DIS\mathsf{T}_m)) \leq Q(\text{Triangle}_m)$ is analogous to, but easier than, the proof of [Proposition 4.2](#page-15-0) and so we omit it.

We show $Q(\text{Triangle}_m) \leq O(Q(3\text{-SUM}_m))$ by the following reduction. Assume wlog that m is a multiple of 3. Let \tilde{x} be an input to Triangle_m. Apply a uniformly random permutation to \tilde{x} and denote the resulting string as x. Choose a uniformly random element $s \in (\{-1,1\}^2)^m$. For a given $i \in [m]$, we map the edge $x_i = \{a, b\}$, where $a < b$, to the 4-dimensional vector $(0, s_i(1)a, s_i(2)b, -1)$ if $i \in [1, m/3]$, $(s_i(1)a, 0, s_i(2)b, -2)$ if $i \in [m/3 + 1, 2m/3]$, and $(s_i(1)a, s_i(2)b, 0, 3)$ if $i \in [2m/3 + 1, m]$, where $s_i =$ $(s_i(1), s_i(2)) \in \{-1, 1\}^2$. Denote the string after the mapping by $y \in (\mathbb{Z}^4)^m$. Compute 3-SUM (y) and output the result. Repeat the entire procedure a large but constant number of times, if the output of any repeat is 1, output 1, otherwise, output 0.

We see the correctness of this reduction as follows. Write $y^i := y[(i-1)m/3+1...im/3]$ for $i \in \{1, 2, 3\}$. Suppose \tilde{x} contains the triangle $\{a, b\}$, $\{b, c\}$, $\{a, c\}$ where $a < b < c$. Then with probability at least a constant, y will contain symbols $(0, -b, -c, -1)$ in $y¹$, $(-a, 0, c, -2)$ in $y²$, and $(a, b, 0, 3)$ in $y³$, which sum to 0. Conversely, if y is a yes-instance for 3-SUM, then y must contain symbol $(0, a_1, b_1, -1)$ in $y¹$, $(a_2, 0, b_2, -2)$ in y^2 , and $(a_3, b_3, 0, 3)$ in y^3 that sum to 0 for some $a_i, b_i \in \mathbb{Z}$. (Note that the last coordinate ensures that one symbol must come from each of y^1, y^2, y^3 in the yes-certificate.) Therefore $|a_2| = |a_3|$ (call a), $|a_1| = |b_3|$ (call b), and $|b_1| = |b_2|$ (call c), so x contains edges $\{b, c\}$, $\{a, c\}$, and $\{a, b\}$, which form a triangle.

The "in particular" part follows from $Q(3\text{-SUM}_m) \leq O(m^{3/4})$ [\[CE05,](#page-50-13) [Amb07\]](#page-49-9).

 \Box

Remark 5.2. Notice that the lower bound of Triangle_m in [Proposition 5.1](#page-22-2) applies when $n = \Omega(m)$. On the other hand, when $n = O(1)$, we have $Q(\text{Triangle}_m) = O(\sqrt{m})$ since we can search whether any of the 3-sized subsets of [n] form a triangle. What is the complexity of Triangle_m when $n = \omega(1)$ and $n = o(m)$? In particular, can we show a better lower bound when $n = \Theta(\sqrt{m})$, which also captures dense graphs? The answer is yes, and we can reduce ED_{n^2} to Triangle $\Theta(n^2)$ (with $\Theta(n)$ vertices) as follows.

Let $x \in ([n] \times [n])^{n^2}$ be an input to ED_{n^2} . We create an edge list y of size $m = n^2 + n$ as follows. Let $V = \{j^A, j^B, j^C : j \in [n]\}.$ For each $j \in [n]$, add an edge (j^A, j^B) in y. Partition the set $[n^2]$ into two sets A and B of equal size. For each $i \in [n^2]$, denote $x_i = (j_i, k_i) \in ([n] \times [n])$, if $i \in A$ (respectively B), add the edge (j_i^A, k_i^C) (respectively (j_i^B, k_i^C)) in y.

We see the correctness of this reduction as follows. Suppose x is a positive instance of ED_{n^2} . Then, with probability 1/2, we will have indices i_1 and i_2 such that $i_1 \in A$, $i_2 \in B$ and $x_{i_1} = x_{i_2} = (j, k)$ for some $j, k \in [n]$. Thus, we will have $(j^A, j^B), (j^A, k^C), (j^B, k^C) \in y$ so y will be a positive instance of

triangle. On the other hand, suppose that y is a positive instance of triangle. Then, for some $j, k \in [n]$, we will have $(j^A, j^B), (j^A, k^C), (j^B, k^C) \in y$ since this is the only way there could be a triangle in y. It follows that (j, k) must have appeared at least twice in x so x is a positive instance of ED_{n^2} .

5.2 The average-case edge list

We now turn to the average-case analysis of **FT**riangle. In particular, we consider the random graph model with m (multi-)edges, such that the m edges are each sampled independently and uniformly from $\binom{[n]}{2}$. In other words, we consider the sample-with-replacement model. In this model, the input edge list x can in the words, we consider the sample-with-replacement model. In this model, the input edge list x can be written succinctly as $x \leftarrow {\binom{[n]}{2}}$ $\binom{n}{2}^m$.

Denote the graph on n vertices formed by the edges in x by $\mathcal{G}(x)$. We use $\Delta(\mathcal{G}(x))$ or simply $\Delta(x)$ to denote the max vertex degree of $\mathcal{G}(x)$. A wedge in $\mathcal{G}(x)$ is a length-two path. Since x could contain repeated edges, $\mathcal{G}(x)$ could be non-simple. In particular, the degree and wedge counts of $\mathcal{G}(x)$ account for the multiplicities of repeated edges. Later, we will also consider strings $x \in \left(\binom{[n]}{2} \right)$ $\binom{n}{2}$ \cup $\{\perp\}$ ^m, where \perp means the input edge has not yet been revealed.

Our focus will be the $m = O(n)$ regime of sparse graphs. In this regime, we obtain near-matching upper and lower bounds for the quantum query complexity of triangle finding.

First, we note some basic facts about sparse random graphs.

Fact 5.3 (Sparse Random Graph). Let $x \leftarrow \begin{pmatrix} [n] \\ 2 \end{pmatrix}$ $\binom{n}{2}$ ^m.

(i) (Low max degree.) For $m \leq O(n)$,

$$
\Pr[\Delta(x) \le O(\log(n)/\log\log(n))] \ge 1 - o(1). \tag{5.1}
$$

(ii) (Existence of triangle.) For $m \geq \Omega(n)$,

$$
Pr[x \text{ contains a triangle}] \ge \Omega(1). \tag{5.2}
$$

In particular, for $m = \Theta(n)$,

$$
\Pr[\Delta(x) \le O(\log(n)/\log\log(n)) \text{ and } x \text{ contains a triangle}] \ge \Omega(1). \tag{5.3}
$$

Proof. [Item \(i\)](#page-23-1) is the well-known maximum load of balls-into-bins problem, see [\[RS98,](#page-52-7) Theorem 1]. [Item \(ii\)](#page-23-2) follows the second-moment method. Let $N := \binom{n}{2}$ $_{2}^{n}$) and

$$
X \coloneqq \sum_{i,j,k \in [m]} \mathbb{1}[x_i, x_j, x_k \text{ form a triangle}].
$$

Then

$$
E[X] = {m \choose 3} \frac{N \cdot 2(n-2)}{N^3} = \frac{4}{3} {m \choose n}^3 + o(1),
$$

\n
$$
E[X^2] = {m \choose 3} {m-3 \choose 3} \cdot \left(\frac{N \cdot 2(n-2)}{N^3}\right)^2 + {m \choose 1} {m-1 \choose 2} {m-3 \choose 2} \cdot \frac{N \cdot (2(n-2))^2}{N^5} + {m \choose 2} {m-2 \choose 1} {m-3 \choose 1} \cdot \frac{N \cdot 2(n-2)}{N^4} + {m \choose 3} \cdot \frac{N \cdot 2(n-2)}{N^3}
$$

\n
$$
= \frac{16}{9} {m \choose n}^6 + \frac{4}{3} {m \choose n}^3 + o(1),
$$

where $E[X^2]$ is calculated by expanding X^2 and grouping summands by the number of shared indices. Therefore, the second-moment method gives

$$
\Pr[X > 0] \ge \mathbb{E}[X]^2 / \mathbb{E}[X^2] = 1 - \frac{3}{4(m/n)^3 + 3} + o(1). \tag{5.4}
$$

Since $m > \Omega(n)$, our statement holds.

The "in particular" part follows immediately from [Items \(i\)](#page-23-1) and [\(ii\).](#page-23-2)

For a technical reason, we also need the following simple fact.

Fact 5.4 (Vertex Avoidance). Given any graph $x \leftarrow \begin{pmatrix} [n] \\ 2 \end{pmatrix}$ $\left(\begin{smallmatrix} n\ 2\end{smallmatrix}\right)^m$, let d be the max degree of x (counting multiplicity). Let $T \subseteq [n]$ be some vertex subset of size t. Suppose x' is a uniformly random size-s subset of edges from x, then

$$
\Pr[x' \cap T = \varnothing] \ge 1 - \frac{tds}{m - td + 1}.\tag{5.5}
$$

Proof. We directly calculate the probability that a random subset of edges of size s that avoids T :

$$
\binom{m - td}{s} \binom{m}{s}^{-1} = \frac{(m - td)!(m - s)!}{m!(m - td - s)!} = \frac{(m - s) \cdot (m - s - 1) \cdots (m - s - td + 1)}{m \cdot (m - 1) \cdots (m - td + 1)}
$$

$$
= \left(1 - \frac{s}{m}\right) \cdots \left(1 - \frac{s}{m - td + 1}\right)
$$

$$
\geq 1 - \frac{tds}{m - td + 1}.
$$

We call a graph $x \in \binom{[n]}{2}$ $\binom{n}{2}^m$ good if $\Delta(\mathcal{G}(x)) = O(\log(n)/\log \log(n))$ and x contains a triangle. Our quantum lower and upper bounds will hold for good graphs. By [Fact 5.3,](#page-23-3) a random graph $x \leftarrow \binom{[n]}{2}$ $\binom{n}{2}^m$ is good with probability $\Omega(1)$ for $m = O(n)$.

[Fact 5.4](#page-24-2) states that a small subgraph of good graph x does not touch any vertices from some small subset T with high probability. The vertex set T that the subgraph wants to avoid will be a triangle, and x' will be of size $o(m)$. Thus, the avoidance property holds almost surely.

5.3 Triangle finding lower bound

Our lower bound result reads.

Theorem 5.5. Let $n \in \mathbb{N}$. Suppose $m, T \in \mathbb{N}$ are functions of n such that $m = \Theta(n)$ and $T \leq$ $o(m^{5/7} / \log^{2/7}(m))$. Then, for any T-query quantum query algorithm \mathcal{A}_T , we have

$$
Pr[\mathcal{A}_T(x) = (i, j, k) \text{ such that } x_i, x_j, x_k \text{ form a triangle}] \le o(1),
$$
\n(5.6)

where $\mathcal{A}_T(x)$ denotes the output of \mathcal{A}_T when its t queries are made to x, the probability is over $x \leftarrow \binom{[n]}{2}$ $\binom{n}{2}^m$ and the randomness of $A_T(x)$.

A simple corollary of [Theorem 5.5](#page-24-1) is that the search version of Triangle_m, i.e., FTriangle_m, has worstcase quantum query complexity $\Omega(m^{5/7}/\log^{2/7}(m))$. In fact, the lower bound holds even if we are promised the maximum degree of the input graph is low.

Corollary 5.6. Let $\varepsilon > 0$. Then for all $m \in \mathbb{N}$ and $d = \log(m) / \log \log(m)$,

$$
Q_{\varepsilon}(\mathsf{FTriangle}_m) \ge Q_{\varepsilon}(\mathsf{FTriangle}_{m,d}) \ge \Omega(m^{5/7}/\log^{2/7}(m)).\tag{5.7}
$$

Proof. The first inequality follows by restriction so it suffices to prove the second inequality. Suppose for $\binom{n}{2}$ ^m. contradiction that $Q(\textsf{FTriangle}_{m,d}) \leq o(m^{5/7} / \log^{2/7}(m))$. Let $n \in \mathbb{N}$ and consider an input $x \leftarrow \binom{[n]}{2}$ By [Fact 5.3,](#page-23-3) for $n = m$, x contains a triangle and has degree at most d with at least constant probability, so a triangle can be found by a quantum algorithm for $\mathsf{FTriangle}_{m,d}$ using $o(m^{5/7}/\log^{2/7}(m))$ queries with at least constant probability, contradicting [Theorem 5.5.](#page-24-1) □

For the rest of this section, we prove [Theorem 5.5.](#page-24-1)

5.3.1 Setting up

Recording query framework. We start by reviewing the recording query framework [\[Zha19,](#page-52-0) [HM23\]](#page-51-7). For convenience of notation, we write $N \coloneqq \binom{n}{2}$ $\binom{n}{2}$ and identify $[N]$ with $\binom{[n]}{2}$ $\binom{n}{2}$ for the rest of this section. A projector refers to a complex square matrix P of some context-appropriate dimension such that $P^{\dagger} = P$ and $P^2 = P$.

Let $m, T \in \mathbb{N}$ and Σ be an alphabet. Given a relation $R \subseteq [N]^m \times \Sigma$, a T-query quantum query algorithm for computing R is specified by a sequence of unitary matrices U_0, \ldots, U_T acting on $\mathbb{C}^m \otimes \mathbb{C}^N \otimes$ \mathbb{C}^K for some $K \in \mathbb{N}$. \mathbb{C}^K is referred to as a workspace register.

For $t \in \{0, 1, \ldots, T\}$, the state of the algorithm at the t-th step given input $x \in [N]^m$ is defined by

$$
|\psi_t^x\rangle := U_t \mathcal{O}_x U_{t-1} \mathcal{O}_x \cdots U_1 \mathcal{O}_x U_0 | \phi_0 \rangle.
$$
 (5.8)

Here, \mathcal{O}_x is the quantum oracle of x, i.e., the unitary matrix acting on $\mathbb{C}^m \otimes \mathbb{C}^N \otimes \mathbb{C}^K$ defined by

$$
\forall (i, u, w) \in [m] \times [N] \times [K]: \mathcal{O}_x | i, u, w \rangle \coloneqq \omega_N^{ux_i} | i, u, w \rangle,
$$
\n(5.9)

where the $|i, u, w\rangle$ s form the computational basis of $\mathbb{C}^m \otimes \mathbb{C}^N \otimes \mathbb{C}^K$ and $\omega_N := \exp(2\pi i/N)$ is the N-th root of unity.

The algorithm finishes by measuring \mathbb{C}^K in the computational basis, parses the output $w \in [K]$ as a string, and outputs a substring of w at a fixed location.^{[14](#page-25-0)} For $x \in [N]^m$, let $W_x \coloneqq \{s \in \Sigma \mid (x, s) \in R\}$ denote the set of all desired outputs associated with x, and let Π_{succ}^x be the projector onto all basis states $|i, u, w\rangle$ such that the substring w' of w at the fixed location satisfies $w' \in W_x$. The success probability of the quantum algorithm on input $x \in [N]^m$ is then defined by $\|\Pi_{\text{succ}}^x \ket{\phi_T}\|^2$.

Following [\[Amb00\]](#page-49-7), a quantum query algorithm can be viewed as acting on basis states $|i, u, w\rangle |x\rangle$, where $x \in [N]^m$ and $|x\rangle := \bigotimes_{i \in [m]} |x_i\rangle$ is the state on an additional *input register*. Suppose \mathcal{D} is a probability distribution over $[N]^{\overline{m}}$, the state of the algorithm at the t-th step given an input sampled according to $\mathcal D$ can be represented by

$$
|\psi_t^{\mathcal{D}}\rangle := (U_t \otimes \mathbb{I})\mathcal{O}(U_{t-1} \otimes \mathbb{I})\mathcal{O}\cdots (U_1 \otimes \mathbb{I})\mathcal{O}(U_0 \otimes \mathbb{I})(|0\rangle |\mathcal{D}\rangle),
$$
\n(5.10)

where O is the standard query operator that maps any basis state $|i, u, w \rangle |x\rangle$ to $(\mathcal{O}_x | i, u, w \rangle |x\rangle$, and

$$
|\mathcal{D}\rangle \coloneqq \sum_{x \in [N]^m} \sqrt{\Pr[x \leftarrow \mathcal{D}]} \, |x\rangle \,. \tag{5.11}
$$

Let $\Pi_{\text{succ}} := \sum_{x \in [N]^m} \Pi_{\text{succ}}^x \otimes |x\rangle\langle x|$. The success probability of the algorithm on \mathcal{D} is defined to be $\left\|\Pi_{\text{succ}}\left|\psi_{T}^{\mathcal{D}}\right\rangle\right\|$. It is not hard to see that

$$
\left\| \Pi_{\text{succ}} \left| \psi_T^{\mathcal{D}} \right> \right\|^2 = \sum_{x \in [N]^m} \Pr[x \leftarrow \mathcal{D}] \left\| \Pi_{\text{succ}}^x \left| \psi_T^x \right> \right\|^2. \tag{5.12}
$$

which shows that $\left\|\Pi_{\text{succ}}\ket{\psi^{\mathcal{D}}_T}\right\|^2$ equals the expected success probability of the quantum query algorithm when the input is sampled from the distribution \mathcal{D} .

The recording query framework works with an alternative view of [Eq. \(5.10\).](#page-25-1) We follow the prescription of this method described by Hamoudi and Magniez in [\[HM23\]](#page-51-7) that specializes to the case where

$$
\mathcal{D} = \mathcal{D}_1 \otimes \mathcal{D}_2 \otimes \cdots \otimes \mathcal{D}_m \tag{5.13}
$$

is a product distribution on $[N]^m$. To reach this alternative view, we first augment the alphabet $[N]$ by an additional character \perp , and extend the action of $\mathcal O$ by defining

$$
\mathcal{O}\left|i,u,w\right\rangle\left|x\right\rangle:=\left|i,u,w\right\rangle\left|x\right\rangle,
$$
\n(5.14)

¹⁴ Formally, \mathbb{C}^K is identified with a tensor product space $\bigotimes_{i=1}^k \mathbb{C}^{\Sigma_i}$ for some alphabets Σ_i and the output on measuring the string $w = w_1 \dots w_k$, where $w_i \in \Sigma_i$, is the substring $w' \coloneqq w_1 \dots w_{k'}$ for some $k' \leq k$.

whenever $x_i = \bot$. (The lack of change in the above equation explains why $x_i = \bot$ can be thought of as the algorithm's lack of knowledge of the value of x_i .

Now, define $|\mathcal{D}_i\rangle \coloneqq \sum_{y \in [N]}$ $\sqrt{\Pr[y \leftarrow \mathcal{D}_i]} |y\rangle$ so that the initial state of the input register in the standard query model can be written as $|\mathcal{D}\rangle = \bigotimes_{i \in [m]} |\mathcal{D}_i\rangle$. In the recording query model, the corresponding initial state of the input register in the recording query model is defined to be $\bigotimes_{i\in[m]} |\perp\rangle = |\perp^m\rangle$.

Then, we define the recording query operator, which is $\mathcal O$ under a change of basis defined using $\mathcal D$.

Definition 5.7 ([\[HM23,](#page-51-7) Definition 3.1]). For all $i \in [m]$, define the unitary matrix S_i acting on \mathbb{C}^{N+1} by

$$
S_i: \begin{cases} |\bot\rangle \mapsto |\mathcal{D}_i\rangle, \\ |\mathcal{D}_i\rangle \mapsto |\bot\rangle, \\ |\phi\rangle \mapsto |\phi\rangle, & \text{if } \langle \phi|\bot\rangle = \langle \phi|\mathcal{D}_i\rangle = 0. \end{cases}
$$
(5.15)

The registers of $|i, u, w\rangle |x\rangle \in \mathcal{H} := \mathbb{C}^m \otimes \mathbb{C}^N \otimes \mathbb{C}^K \otimes \mathbb{C}^{N^m}$ are labeled as $|i\rangle_Q |u\rangle_P |w\rangle_W |x\rangle_I$. The register labels Q, P, W, I stand for "query", "phase", "work", and "input" respectively. Then, define the following unitary operators acting on H .

$$
\mathcal{T}_{\mathcal{D}} \coloneqq \mathbb{I}_{QPW} \otimes \bigotimes_{i \in [m]} \mathcal{S}_i,\tag{5.16}
$$

$$
S_{\mathcal{D}} \coloneqq \sum_{i \in [m]} |i\rangle\langle i|_Q \otimes \mathbb{I}_{PW} \otimes \bigotimes_{j=1}^{i-1} \mathbb{I}_{I_j} \otimes S_i \otimes \bigotimes_{j=i+1}^{m} \mathbb{I}_{I_j}, \qquad (5.17)
$$

$$
\mathcal{R}_{\mathcal{D}} \coloneqq \mathcal{S}_{\mathcal{D}}^{\dagger} \mathcal{O} \mathcal{S}_{\mathcal{D}} \,. \tag{5.18}
$$

 $\mathcal{R}_\mathcal{D}$ is referred to as the *recording query operator*.

In the recording query model, the state of the quantum query algorithm after the t-th recording query is defined by

$$
|\phi_t^{\mathcal{D}}\rangle := (U_t \otimes \mathbb{I}_I) \mathcal{R}_{\mathcal{D}}(U_{t-1} \otimes \mathbb{I}_I) \mathcal{R}_{\mathcal{D}} \cdots (U_1 \otimes \mathbb{I}_I) \mathcal{R}_{\mathcal{D}}(U_0 \otimes \mathbb{I}_I)(|0\rangle \setminus \mathbb{I}^m).
$$
(5.19)

For convenience, we will often abuse notation and write U_i for the $U_i \otimes \mathbb{I}_I$ in [Eq. \(5.19\).](#page-26-0)

The recording query model is particularly useful due to the following results. First, the recording query model is essentially the same as the standard average-case query model up to a rotation on the input register at the end of the algorithm. Consequently, a measurement on the other registers sees no difference at all. Formally, we have

Theorem 5.8 ([\[HM23,](#page-51-7) Theorem 3.3]). For any $t \in \{0, 1, ..., T\}$,

$$
|\phi_t^{\mathcal{D}}\rangle = \mathcal{T}_{\mathcal{D}}|\psi_t^{\mathcal{D}}\rangle,\tag{5.20}
$$

where $|\phi_t^D\rangle$ and $|\psi_t^D\rangle$ are defined in Eqs. [\(5.10\)](#page-25-1) and [\(5.19\)](#page-26-0) respectively.

A crucial but easy-to-see fact in the recording query framework $\rm is^{15}$ $\rm is^{15}$ $\rm is^{15}$

Fact 5.9 ([\[HM23,](#page-51-7) Fact 3.2]). The state $|\psi_t^D\rangle$ is a linear combination of basis states $|i, u, w\rangle |x\rangle$ where x contains at most t entries different from \bot .

Moreover, the effect of the recording query operator can be exactly calculated as

¹⁵For intuition only, if we view each non- \perp symbol in x as contributing one unit of "degree", then this fact is akin to the polynomial method $[BBC^+01]$. We remark that (essentially) this fact *alone* can be used to prove non-trivial lower bounds, see, e.g., [\[BKW24\]](#page-50-6).

Lemma 5.10 ([\[HM23,](#page-51-7) Lemma 4.1]). For \mathcal{D}_i uniform over [N]. Suppose the recording query operator $\mathcal{R}_{\mathcal{D}}$ is applied to a basis state $|i, u, w \rangle |x\rangle$. If $u \neq 0$, the register $|x_i\rangle_{I_i}$ is mapped to

$$
\begin{cases}\n\sum_{y \in [N]} \frac{\omega_N^{uy}}{\sqrt{N}} |y\rangle, & \text{if } x_i = \bot, \\
\frac{\omega_N^{ux_i}}{\sqrt{N}} | \bot \rangle + \frac{1 + \omega_N^{ux_i}(N - 2)}{N} |x_i\rangle + \sum_{y \in [N] \setminus \{x_i\}} \frac{1 - \omega_N^{uy} - \omega_N^{ux_i}}{N} |y\rangle, & \text{if } x_i \in [N],\n\end{cases}
$$
\n(5.21)

and the other registers are unchanged. If $u = 0$ then none of the registers are changed.

[Fact 5.9](#page-26-2) is due to the "reveal-on-demand" or "lazy-sampling" nature of the recording query operator. [Lemma 5.10](#page-26-3) formally grounds the intuition that once a value of x_i has been recorded, later queries should not significantly alter it (note the coefficient on $|x_i\rangle$ has large norm).

As we are proving [Theorem 5.5,](#page-24-1) we will henceforth specialize D to be the uniform (product) distribution on $[N]^m = \binom{[n]}{2}$ $\binom{[n]}{2}^m$. We abbreviate

$$
|\phi_t\rangle, |\psi_t\rangle, \mathcal{T}, \mathcal{S}, \mathcal{R} \quad \text{for} \quad |\phi_t^{\mathcal{D}}\rangle, |\psi_t^{\mathcal{D}}\rangle, \mathcal{T}_{\mathcal{D}}, \mathcal{S}_{\mathcal{D}}, \mathcal{R}_{\mathcal{D}}, \tag{5.22}
$$

respectively. These states and operators depend on the m and n that parametrize \mathcal{D} , but we leave these parameters implicit for notational convenience.

Roadmap for the proof of [Theorem 5.5.](#page-24-1) Recall that $x \in \binom{[n]}{2}$ $\binom{n}{2}^m$, we write $\mathcal{G}(x)$ for the graph on *n* vertices formed by the edges in x. The notation trivially generalizes to $x \in \left(\binom{[n]}{2}\right)$ $\binom{n}{2}$ \cup $\{\perp\}\right)^m$. We say x (or $|x\rangle$) records a triangle if $\mathcal{G}(x)$ contains a triangle; we say x (or $|x\rangle$) records k wedges if $\mathcal{G}(x)$ contains k wedges; and so on. Since there is a trivial bijection between $N = \binom{n}{2}$ $\binom{n}{2}$ and $\binom{[n]}{2}$ $\binom{n}{2}$. We don't distinguish [N] and $\binom{[n]}{2}$ $\binom{n}{2}$, as for the recording query framework, the notation $[N]^m$ is arguably more natural. We will assume that $m = n$. This is without loss of generality since the only property of the regime $m = \Theta(n)$ that we use in the proof is $\Delta(x) \leq O(\log(n))$, which is promised with high probability by [Fact 5.3.](#page-23-3) Nonetheless, we will keep the notation m and n separate until we need to use $m = n$. This is for clarity as most parts of the proof do not use $m = n$. Indeed, the only places that do are [Corollary 5.18](#page-32-0) and the few results invoking it, which includes [Theorem 5.5.](#page-24-1)

Our analysis revolves around bounding the norm of the projection of $|\phi_t\rangle$ onto computational basis states $|i, u, w\rangle |x\rangle$ such that x records properties key to finding triangles, such as: $\mathcal{G}(x)$ contains a large number of high-degree vertices; $\mathcal{G}(x)$ contains a large number of wedges; and, of course, $\mathcal{G}(x)$ contains a triangle. [Lemma 5.10](#page-26-3) allows us to carry out our analysis on a query-by-query basis. This discussion motivates the following definitions.

Definition 5.11 (Recording projectors). For $R \subseteq \mathbb{R}$, and $y \in {n \choose 2}$ $\binom{n}{2}$ \cup { \perp }, we define the following projectors by giving the basis states onto which they project.

 Π^{Δ} : any basis state $|i, u, w \rangle |x\rangle$ such that $\mathcal{G}(x)$ contains a triangle.

 Π_R^{\wedge} : any basis state $|i, u, w \rangle |x\rangle$ such that the number of wedges in $\mathcal{G}(x)$ is in R.

 Π_y : any basis state $|i, u, w \rangle |x\rangle$ such that $u \neq 0$ and $x_i = y$.

Definition 5.12 (Progress measures). For $t \in \mathbb{Z}_{\geq 0}$,

$$
\Lambda_{t,r} := \left\| \Pi_{[r,\infty]}^{\wedge} \left| \phi_t \right> \right\| \quad \text{and} \quad \Delta_t := \left\| \Pi^{\triangle} \left| \phi_t \right> \right\|.
$$

Thus, $\Lambda_{t,r}$ measures the progress of recording r wedges in t queries; while Δ_t measures the progress of recording a triangle in t queries. Our strategy is to first show that a large investment of queries is needed to record many wedges. That is, $\Lambda_{t,r}$ is negligible when t is small and r large. Then, we show that, to record a triangle, a large number of wedges must have been recorded during the execution of the algorithm. That is, Δ_t will be negligible as long as $\Lambda_{t,r}$ remains negligible for a somewhat large r.

A naive implementation of the above strategy falls short of giving the tight bound. One technical challenge is that a single query in principle can record as many as $\Omega(t)$ extra wedges, resulting in an overestimate on the progress in each step and therefore an underestimate on the final query lower bound. However, as the input is drawn from the distribution \mathcal{D} , the underlying graph has a maximum degree of $O(\log(n))$ with high probability. By excluding graphs with a maximum degree of $\Omega(\log n)$, we ensure that each query records at most $O(1)$ wedges. This motivates the following definitions.

Definition 5.13 (Excluding projectors). For $d \in \mathbb{Z}_{\geq 0}$, vertex $v \in [n]$, we define the following projectors by giving the basis states onto which they project.

- Π^{\deg}_v $v \geq d$: any basis state $|i, u, w \rangle |x\rangle$ such that the degree of v in $\mathcal{G}(x)$ is at least d.
- $\Pi_{>d}^{\deg}$ $\geq d$: any basis state $|i, u, w \rangle |x\rangle$ such that $\mathcal{G}(x)$ contains a vertex with degree at least d.
- Π_{Bad} : any basis state $|i, u, w\rangle |x\rangle$ such that $\mathcal{G}(x)$ contains a vertex with degree at least $12 \log(n)$.

In the next three subsections, we discuss the above three pieces in details, starting from controlling the high-degree vertices, and then analyzing $\Lambda_{t,r}$ and Δ_t .

5.3.2 Excluding high-degree graphs

Exclusion lemma. A random sparse graph is rarely a high-degree graph. We show how we can exclude these graphs in the recording query framework so that the wedge count does not jump by a large amount at each query. While some aspects of our presentation are tailored to our specific problem, we have made an effort to generalize our proofs so that they can be applied in other contexts in the future.

Specifically, [Lemma 5.14](#page-28-0) enables us to exclude unfavorable events from consideration during the analysis of recording progress, deferring their accounting to the final recording probability. [Lemma 5.17](#page-30-0) establishes that when the input is sampled from \mathcal{D} , if a certain event occurs with negligible probability, then no quantum algorithm can reliably record that event.

For the next lemma, we recall the definition of $|\phi_i\rangle$ from [Eq. \(5.19\),](#page-26-0)

$$
|\phi_i\rangle := U_i \mathcal{R} U_{i-1} \mathcal{R} \cdots U_1 \mathcal{R} U_0(|0\rangle | \perp^m \rangle).
$$
 (5.23)

(As mentioned above, we have dropped D-superscripts, D-subscripts, and the identities tensored to the U_i s for notational convenience.)

Lemma 5.14 (Exclusion Lemma). Let $t \in \mathbb{N}$. Let $\Pi_1, \Pi_2, \ldots, \Pi_{t-1}$ be projectors. For $i \in [t]$, let $|\phi'_i\rangle$ denote the (possibly unnormalized) state

$$
|\phi_i'\rangle := U_i \mathcal{R}(\mathbb{I} - \Pi_{i-1}) U_{i-1} \mathcal{R}(\mathbb{I} - \Pi_{i-2}) U_{i-2} \mathcal{R} \cdots (\mathbb{I} - \Pi_1) U_1 \mathcal{R} U_0(|0\rangle |\perp^m\rangle).
$$
(5.24)

Then,

$$
\left\| |\phi_t\rangle - |\phi'_t\rangle \right\| \le \sum_{i=1}^{t-1} \|\Pi_i |\phi_i\rangle\|.
$$
 (5.25)

In particular, for any projector Π_{rec} ,

$$
\|\Pi_{\text{rec}}\left|\phi_{t}\right\rangle\| \leq \left\|\Pi_{\text{rec}}\left|\phi_{t}'\right\rangle\right\| + \sum_{i=1}^{t-1} \|\Pi_{i}\left|\phi_{i}\right\rangle\|.
$$
\n(5.26)

Proof. We adopt the product notation \prod for the non-commutative product in right-to-left order, i.e., for positive integers a and b, adopt

$$
\prod_{i=a}^{b} X_i \coloneqq \begin{cases} X_b X_{b-1} \cdots X_{a+1} X_a, & \text{if } a \le b, \\ \mathbb{I}, & \text{if } a > b. \end{cases}
$$
\n(5.27)

Then,

$$
\begin{split}\n\left|\phi_{t}\right\rangle &= U_{t} \mathcal{R} \left(\prod_{i=1}^{t-1} (\Pi_{i} + (\mathbb{I} - \Pi_{i})) U_{i} \mathcal{R} \right) U_{0}(|0\rangle \left| \perp^{m} \right\rangle) \\
&= U_{t} \mathcal{R} \left(\left(\prod_{i=1}^{t-1} (\mathbb{I} - \Pi_{i}) U_{i} \mathcal{R} \right) + \sum_{i=1}^{t-1} \left(\prod_{j=i+1}^{t-1} (\mathbb{I} - \Pi_{j}) U_{j} \mathcal{R} \right) \Pi_{i} \left(\prod_{k=1}^{i} U_{k} \mathcal{R} \right) \right) U_{0}(|0\rangle \left| \perp^{m} \right\rangle) \\
&= \left|\phi_{t}'\right\rangle + \sum_{i=1}^{t-1} U_{t} \mathcal{R} \left(\prod_{j=i+1}^{t-1} (\mathbb{I} - \Pi_{j}) U_{j} \mathcal{R} \right) \Pi_{i} \left|\phi_{i}\right\rangle,\n\end{split} \tag{5.28}
$$

where the second equality can be interpreted as the hybrid argument [\[BBBV97\]](#page-49-10).

Observe that

$$
\left\| U_t \mathcal{R} \left(\prod_{j=i+1}^{t-1} (\mathbb{I} - \Pi_j) U_j \mathcal{R} \right) \Pi_i \left| \phi_i \right> \right\| \leq \|\Pi_i \left| \phi_i \right> \|\tag{5.29}
$$

because the Π_j s are projectors, and $\mathcal R$ and the U_j s are unitaries.

Therefore, applying the triangle inequality on [Eq. \(5.28\)](#page-29-0) gives

$$
\left\| |\phi_t\rangle - |\phi'_t\rangle \right\| \le \sum_{i=1}^{t-1} \|\Pi_i |\phi_i\rangle\|,\tag{5.30}
$$

The "in particular" part of the lemma follows from $\|\Pi_{\text{rec}}(\phi_t) - \Pi_{\text{rec}}(\phi'_t)\| \leq ||\|\phi_t\rangle - \|\phi'_t\rangle||$ and the reverse triangle inequality.

The Hamming events. Now we study a rather general situation using the exclusion lemma. Consider the product distribution $\mathcal{D} = \bigotimes_{i \in [m]} \mathcal{D}_i$, where \mathcal{D}_i is over some finite domain [N]. Fix some partition

$$
[N] = \Sigma_0^{(i)} \dot{\cup} \Sigma_1^{(i)}, \qquad \text{for all } i \in [m].
$$
 (5.31)

The sets $\Sigma_1^{(i)}$ here can be interpreted as a "logical 1" for any symbol from $\Sigma_1^{(i)}$, roughly corresponding to the set of the symbols of interest for the *i*-th coordinate. We abuse the notation $|\cdot|$ (for Hamming weight) to apply to $x \in \Sigma_1^{(1)} \times \cdots \times \Sigma_1^{(m)}$ $\binom{m}{1}$, such that

$$
|x| := \left| \{ i \in [m] \mid x_i \in \Sigma_1^{(i)} \} \right|.
$$
\n(5.32)

Then we have the natural probability distribution in the form of the product of independent Bernoulli distributions, where the probability p_i of *i*-th symbol being a logical 1 is,

$$
p_i \coloneqq \Pr[e \in \Sigma_1^{(i)} \mid e \leftarrow \mathcal{D}_i]. \tag{5.33}
$$

Further, let

$$
p \coloneqq \max_{i \in [m]} p_i, \quad \text{and} \quad \hat{p} \coloneqq \max_{i \in [m], j \in [N]} \Pr[z = j \mid z \leftarrow \mathcal{D}_i]. \tag{5.34}
$$

The above definition hints at the events that we are going to focus on, i.e., $|x|$ being large. Chernoff's bound tells us that the probability that $|x|$ is large decays exponentially.

Lemma 5.15. For any $c \geq e$, we have

$$
\Pr[|x| \geq cpm \log(m) \mid x \leftarrow \mathcal{D}] \leq m^{-cp \cdot m \log \log(m)}.\tag{5.35}
$$

In particular, the above lemma is a straightforward consequence of the following version of Chernoff bound specialized to i.i.d. Bernoulli random variables.

Lemma 5.16 (Chernoff bound). Let $m \in \mathbb{N}$, $p \in [0,1]$, and $\mu := pm$. Let X_1, \ldots, X_m be independent and identically distributed Bernoulli random variables such that $Pr[X_i = 1] = p$. Then, for any $c > 0$,

$$
\Pr[X_1 + \dots + X_m \ge c] \le \left(\frac{e \cdot \mu}{c}\right)^c. \tag{5.36}
$$

Proof. We may assume $p \neq 0$, else the lemma trivially holds. If $p > 0$, so that $\mu > 0$, there are two cases:

- (i) $0 < c \leq \mu$: in this case, $\mu/c \geq 1$ so $(e\mu/c)^{c} \geq e^{c} > 1$ so the lemma trivially holds.
- (ii) $c > \mu$: in this case, the lemma follows from [\[MU17,](#page-52-9) Theorem 4.4 (part 1)].

Now we instantiate our exclusion lemma to handle the kind of rare events arising from the large deviation property of i.i.d. random variables. To formally state the result, define the following projectors:

- **For** $r \geq 0$, let $\Pi_{\geq r}$ be the projector onto those $|g\rangle$ s such that $g \in ([N] \cup {\perp})^m$ and $|g| \geq r$.
- **■** For $r \geq 0$, let $P_{\geq r}$ be the projector onto those $|f\rangle$ s such that $f \in [N]^m$ and $|f| \geq r$; let $P_{\leq r}$ be the projector that projects onto those $|f\rangle$ s such that $f \in [N]^m$ and $|f| < r$.

These projectors look similar but will serve different purposes. The projector $\Pi_{\geq r}$ will be applied to the input register of the recording query model; while projects $P_{\geq r}$ and $P_{\leq r}$ will be applied to the input register of the standard query model.

With the above preparation, we are now ready to state the key technical result of this part that allows us to exclude high Hamming-weight inputs (which form the "Hamming event") during the quantum query algorithm's execution:

Lemma 5.17 (Mirroring Lemma). For any $c, m \geq e$ and $k \geq 1$, we have

$$
\left\| \left(\mathbb{I} \otimes \Pi_{\geq (k+1)cpm \log(m)} \right) \left| \phi_t \right> \right\|^2
$$

\$\leq 2 \Pr[|x| \geq cpm \log(m) | x \leftarrow \mathcal{D}] + 2m^{-cpmk \log\left(\frac{k \log(m) \sqrt[k]{p \log(m)}}{\tilde{p}}\right)\$} \tag{5.37}

In view of [Lemma 5.15,](#page-29-1) we obtain by taking $k = 1$,

$$
\left\| \left(\mathbb{I} \otimes \Pi_{\geq 2cpm \log(m)} \right) \left| \phi_t \right| \right\|^2 \leq 2m^{-cpm \log \log(m)} + 2m^{-cpm \log \left(\frac{p \log(m)^2}{\hat{p}} \right)}. \tag{5.38}
$$

Proof. Let $|\psi_t\rangle$ be the state after t queries of the quantum algorithm in the standard oracle model (with additional input register) as defined in [Eq. \(5.10\).](#page-25-1) Note for some unit vector $|\psi_x\rangle$,

$$
|\psi_t\rangle = \sum_{x \in [N]^m} \sqrt{\Pr[x \leftarrow \mathcal{D}]} |\psi_x\rangle |x\rangle.
$$
 (5.39)

Let

$$
C := (k+1)c, \qquad \theta := pm \log m, \qquad \alpha_x := \sqrt{\Pr[x \leftarrow \mathcal{D}]}.
$$

By [Theorem 5.8,](#page-26-4) we can write $(\mathbb{I} \otimes \Pi_{\geq Cpm \log m}) |\phi_t\rangle$ as

$$
\left(\mathbb{I} \otimes \Pi_{\geq C\theta}\right) \left|\phi_t\right\rangle = \left(\mathbb{I} \otimes \Pi_{\geq C\theta}\right) \mathcal{T} \left|\psi_t\right\rangle. \tag{5.40}
$$

 \Box

Then,

$$
\|(\mathbb{I} \otimes \Pi_{\geq C\theta}) |\phi_t\rangle\|^2 = \|(\mathbb{I} \otimes \Pi_{\geq C\theta}) \mathcal{T}(\mathbb{I} \otimes (P_{\geq c\theta} + P_{
\n
$$
\leq (\|(\mathbb{I} \otimes \Pi_{\geq C\theta}) \mathcal{T}(\mathbb{I} \otimes P_{\geq c\theta}) |\psi_t\rangle\| + \|(\mathbb{I} \otimes \Pi_{\geq C\theta}) \mathcal{T}(\mathbb{I} \otimes P_{
\n
$$
\leq (\|(\mathbb{I} \otimes P_{\geq c\theta}) |\psi_t\rangle\| + \|(\mathbb{I} \otimes \Pi_{\geq C\theta}) \mathcal{T}(\mathbb{I} \otimes P_{
\n
$$
\leq 2 \|(\mathbb{I} \otimes P_{\geq c\theta}) |\psi_t\rangle\|^2 + 2 \|(\mathbb{I} \otimes \Pi_{\geq C\theta}) \mathcal{T}(\mathbb{I} \otimes P_{
\n
$$
\leq 2 \Pr[x] \geq c\theta | x \leftarrow \mathcal{D} + 2 \|(\mathbb{I} \otimes \Pi_{\geq C\theta}) \mathcal{T}(\mathbb{I} \otimes P_{
\n
$$
\leq 2m^{-cpm \log \log(m)} + 2 \|(\mathbb{I} \otimes \Pi_{\geq C\theta}) \mathcal{T}(\mathbb{I} \otimes P_{ (5.41)
$$
$$
$$
$$
$$
$$

where the first inequality uses the triangle inequality; the second inequality holds as ($\mathbb{I} \otimes \Pi_{\geq C\theta} \mathcal{T}$) is a contraction; the third step is by Cauchy-Schwarz inequality, and the final step uses [Lemma 5.15.](#page-29-1)

We proceed to bound the second term in Eq. (5.41) by bounding

$$
\|\Pi_{\geq C\theta} \mathcal{T} P_{< c\theta} |v\rangle\|,\tag{5.42}
$$

for an arbitrary unit vector $|v\rangle \in \mathbb{C}^{([N] \cup \{\perp\})^m}$. First, write

$$
P_{< c\theta} |v\rangle = \sum_{g \in [N]^m} \beta_g |g\rangle \,,\tag{5.43}
$$

where $\beta_g \in \mathbb{C}$ satisfy $\sum_g \vert \beta_g \vert^2 \leq 1$ and

$$
|g| \ge c\theta \implies \beta_g = 0. \tag{5.44}
$$

Define $\Pi_1^{(i)} \coloneqq \sum$ $y \in \Sigma_1^{(i)} |y\rangle\langle y|$ for all $i \in [m]$. For each $g \in [N]^m$, we have

$$
\mathcal{T}|g\rangle = \bigotimes_{i=1}^{m} \mathcal{S}_i |g_i\rangle \tag{5.45}
$$

by the definition of $\mathcal T$. We perform case analysis on each tensor factor as follows.

(i) If $g_i \in \Sigma_0^{(i)}$ (i). Write $|g_i\rangle = \sqrt{p_{g_i}} |D_i\rangle + (|g_i\rangle - \sqrt{p_{g_i}} |D_i\rangle)$, where the second term $|g_i\rangle - \sqrt{p_{g_i}} |D_i\rangle$ is orthogonal to span $\{\vert\perp\rangle$, $\vert\mathcal{D}_i\rangle\}$. Then, by definition of \mathcal{S}_i ,

$$
\left\| \Pi_1^{(i)} \mathcal{S}_i | g_i \rangle \right\|^2 = \left\| \Pi_1^{(i)} \left(\sqrt{p_{g_i}} \left| \bot \right\rangle + \left| g_i \right\rangle - \sqrt{p_{g_i}} \left| \mathcal{D}_i \right\rangle \right) \right\|^2
$$

$$
= \left\| \sqrt{p_{g_i}} \Pi_1^{(i)} \left| \mathcal{D}_i \right\rangle \right\|^2 = p_{g_i} p \le \hat{p} p. \tag{5.46}
$$

(ii) If $g_i \in \Sigma_1^{(i)}$ $i^{(i)}_1$, we trivially have

$$
\left\| \Pi_1^{(i)} \mathcal{S}_i \left| g_i \right> \right\|^2 \le 1. \tag{5.47}
$$

Since $\mathcal{S}|g\rangle$ is a product state, $\|\Pi_{\geq C\theta} S |g\rangle\|^2$ equals the probability that we make m measurements to each $S_i | g_i \rangle$ with projectors $\{\Pi_0^{(i)}\}$ $_0^{\left(i \right)},\Pi _1^{\left(i \right)}$ $\binom{1}{1}$ and obtain more than $C\theta$ outcomes equal to 1. Therefore, for all $g \in [N]^m$ such that $|g| < c\theta$, we have

$$
\|\Pi_{\geq C\theta} \mathcal{T} |g\rangle\|^2 \leq \Pr[X_1 + X_2 + \dots + X_{m-\lfloor c\theta \rfloor} + \lfloor c\theta \rfloor \geq C\theta] \leq \Pr[X_1 + X_2 + \dots + X_m \geq (C - c)\theta],
$$
\n(5.48)

where by Eq. (5.46) the X_i s are independent and identically distributed as

$$
X_i = \begin{cases} 1 & \text{with probability } \hat{p}p, \\ 0 & \text{with probability } 1 - \hat{p}p. \end{cases} \tag{5.49}
$$

Recall that $C = (k+1)c$, by [Lemma 5.16,](#page-30-1)

$$
\Pr\left[\sum_{i=1}^{m} X_i \ge kc\theta\right] \le \left(\frac{em\hat{p}p}{kc\theta}\right)^{kc\theta} = \left(\frac{e\hat{p}}{kc\log(m)}\right)^{kc\theta}.\tag{5.50}
$$

For any $k \geq 1$, and $c, m \geq e$,

$$
\Pr\left[\sum_{i=1}^{m} X_i \ge kc\theta\right] \le \left(\frac{\hat{p}}{k\log(m)}\right)^{ck\theta}.\tag{5.51}
$$

Therefore, applying the Cauchy-Schwarz gives

$$
\|\Pi_{\geq C\theta} \mathcal{T} P_{< c\theta} |v\rangle\|^2 \leq \left(\sum_{g \in [N]^m, |g| < c\theta} |\beta_g|^2 \right) \left(\sum_{g' \in [N]^m, |g'| < c\theta} \|\Pi_{\geq C\theta} \mathcal{T} |g'\rangle\|^2\right) \leq \left(\frac{m}{< c\theta}\right) \cdot \left(\frac{\hat{p}}{k \log(m)}\right)^{ck\theta},\tag{5.52}
$$

where

$$
\binom{n}{\lt k} := \sum_{i=0}^{k-1} \binom{n}{i} \le \left(\frac{en}{k}\right)^k. \tag{5.53}
$$

Since Eq. (5.52) holds for an arbitrary unit vector $|v\rangle$, we deduce

$$
\|\Pi_{\geq C\theta} \mathcal{T} P_{\n(5.54)
$$

Therefore, substituting Eq. (5.54) into Eq. (5.41) , we obtain

$$
\|(\mathbb{I} \otimes \Pi_{\geq C\theta}) |\phi_t\rangle\|^2 \leq 2m^{-cpm\log\log(m)} + 2m^{-cpmk\log\left(\frac{k\log(m)}{\hat{p}}\right)}.
$$
\n(5.55)

as required.

Excluding high-degree graphs. Recall that $|\phi_t\rangle$ depends on the m and n that specifies the distribution D. When $m = n$, the previous lemma implies that only a tiny fraction of basis states $|i, u, w\rangle |x\rangle$ in the support $|\phi_t\rangle$ can have x recording a high-degree vertex, *irrespective* of the value of t. This is because $\mathcal{G}(x)$ for x sampled from the initial distribution D, no vertex v has high-degree with high probability. Notice that for any fixed v , its property of being high-degree is captured by Hamming events. More formally, we have the following corollary.

Corollary 5.18. Suppose $m = n \ge 16$. Then for any $d, c \in \mathbb{R}$ such that $c \ge e$ and $d \ge 4c \log(n)$, and any $t \in \mathbb{Z}_{\geq 0}$, we have

$$
\left\| \Pi_{\geq d}^{\text{deg}} \left| \phi_t \right> \right\| \leq \frac{2}{n^{c-1}}.\tag{5.56}
$$

In particular, for any $t \leq n$, we have

$$
\sum_{i=1}^{t} \|\Pi_{\text{Bad}}\|\phi_i\|\leq \frac{2}{n}.\tag{5.57}
$$

Proof. For any $d \geq 0$ and each $v \in [n]$, choose $\Sigma_1^{(i)} = \{(a, b) \in [n]^2 \mid a \neq b, \{a, b\} \cap \{v\} \neq \emptyset\}$ for all $i \in [m], \text{ then } \mathbb{I} \otimes \Pi_d = \Pi_{v, \geq d}^{\text{deg}}, \ p = p_i = (n-1)/N = \frac{2}{n}$ $\frac{2}{n}$ for all $i \in [m]$, and $\hat{p} = {n \choose 2}$ $\binom{n}{2}^{-1}$. As we consider the case $m = n$, we have $pm = 2$ and $m\hat{p} = 2/(m - 1)$. By [Eq. \(5.38\)](#page-30-2) in [Lemma 5.17,](#page-30-0) for any $c \ge e$ and $n \geq 16$,

$$
\left\| \left(\mathbb{I} \otimes \Pi_{\geq 2cpm \log(m)} \right) \left| \phi_t \right> \right\|^2 \leq 2m^{-cpm \log \log(m)} + 2m^{-cpm \log \left(\frac{p \log(m)^2}{\hat{p}} \right)}
$$

= $2n^{-2c \log(\log(n))} + 2n^{-2c \log \left(\log(n)(n-1) \log(n) \right)}$ (5.58)

$$
\leq \frac{4}{n^{2c \log(\log(16))}} \leq \frac{4}{n^{2c}},
$$

so for any $d \geq 2cpm \log(m) = 4c \log(n)$ and $v \in [n]$,

$$
\left\| \Pi_{v,\geq d}^{\text{deg}} \left| \phi_t \right> \right\| \leq \left\| \left(\mathbb{I} \otimes \Pi_{\geq 2cpm \log(m)} \right) \left| \phi_t \right> \right\| \leq \frac{2}{n^c}.
$$
\n(5.59)

Finally, note that the projectors $\Pi^{\text{deg}}_{\geq d}$ and $\Pi^{\text{deg}}_{v,\geq d}$ commute, hence,

$$
\Pi^{\text{deg}}_{\geq d} \leq \sum_{v} \Pi^{\text{deg}}_{v,\geq d} \implies \left(\Pi^{\text{deg}}_{\geq d} \right)^2 \leq \left(\sum_{v} \Pi^{\text{deg}}_{v,\geq d} \right)^2.
$$

Consequently,

$$
\left\|\Pi_{\geq d}^{\text{deg}}\left|\phi_{t}\right\rangle\right\| \leq \left\|\sum_{v\in[n]} \Pi_{v,\geq d}^{\text{deg}}\left|\phi_{t}\right\rangle\right\| \leq \sum_{v\in[n]} \left\|\Pi_{v,\geq d}^{\text{deg}}\left|\phi_{t}\right\rangle\right\| \leq \frac{2}{n^{c-1}}.\tag{5.60}
$$

For the "in particular" part, we choose $c = 3$, so that $\Pi_{\text{Bad}} = \Pi^{\text{deg}}_{\geq 4c \log(n)}$ by definition. Then

$$
\|\Pi_{\text{Bad}}\left|\phi_{i}\right\rangle\| = \left\|\Pi_{\geq 12\log(n)}^{\text{deg}}\left|\phi_{i}\right\rangle\right\| \leq \frac{2}{n^{2}},\tag{5.61}
$$

from which the corollary follows by the triangle inequality.

5.3.3 Progress in recording wedges

To reliably record a triangle, there must be many wedges recorded along the way. In this part, we bound the progress of a quantum query algorithm in recording wedges. Recall the measure of progress of recording at least r wedges in t queries is defined as

$$
\Lambda_{t,r} := \left\| \Pi_{[r,\infty)}^{\wedge} \left| \phi_t \right> \right\|. \tag{5.62}
$$

As mentioned previously, high-degree vertices can potentially cause an overestimate of the power of quantum algorithms to record wedges. We apply the exclusion lemma to suppress these high-degree vertices. In particular, invoking [Lemma 5.14](#page-28-0) with $\Pi_i := \Pi_{\text{Bad}}$ for all $i \in [t-1]$ and $\Pi_{\text{rec}} := \Pi'_{[r,\infty)}$ gives

$$
\Lambda_{t,r} \le \left\| \Pi_{[r,\infty)}^{\wedge} \left| \phi_t' \right> \right\| + \sum_{i=1}^{t-1} \left\| \Pi_{\text{Bad}} \left| \phi_i \right> \right\|, \tag{5.63}
$$

where $|\phi_t\rangle$ is the (possibly unnormalized) state defined by

$$
|\phi_t'\rangle := U_t \mathcal{R}(\mathbb{I} - \Pi_{t-1})U_{t-1} \mathcal{R}(\mathbb{I} - \Pi_{t-2})U_{t-2} \mathcal{R} \cdots (\mathbb{I} - \Pi_1)U_1 \mathcal{R} U_0(|0\rangle | \mathbb{L}^m)).
$$
\n(5.64)

The term $\sum_{i=1}^{t-1} \|\Pi_{\text{Bad}}\ket{\phi_i}\|$ in [Eq. \(5.63\)](#page-33-0) can be bounded using [Corollary 5.18.](#page-32-0) Therefore, to bound $\Lambda_{t,r}$, it suffices to bound

$$
\Lambda_{t,r}' := \left\| \Pi_{[r,\infty)}^{\wedge} \left| \phi_t' \right> \right\|. \tag{5.65}
$$

 \Box

Lemma 5.19 (Wedges progress recurrence). For any $t, r \in \mathbb{Z}_{\geq 0}$, we have

$$
\Lambda'_{t+1,r} \le \Lambda'_{t,r} + 8\sqrt{\frac{t}{n}} \Lambda'_{t,r-2\lfloor 12 \log(n) \rfloor}.
$$
\n(5.66)

In addition, $\Lambda'_{0,0} = 1$, and $\Lambda'_{0,r} = 0$ for all $r \ge 1$.

Proof. It is clear that the boundary condition $\Lambda'_{0,0} = 1$, and $\Lambda'_{0,r} = 0$ for all $r \ge 1$ since $|\phi_0\rangle = |\phi_0\rangle = |\phi_0\rangle$ $|0\rangle |\perp^m\rangle$. So in the remainder of the proof, we focus on deriving the recurrence [Eq. \(5.66\).](#page-34-0)

For $t \in \mathbb{Z}_{\geq 0}$, since U_{t+1} acts as identity on the input register, thus

$$
\Lambda'_{t+1,r} = \left\| \Pi^\wedge_{[r,\infty)} U_{t+1} \mathcal{R}(\mathbb{I} - \Pi_{\text{Bad}}) \, | \phi'_t \rangle \right\| = \left\| \Pi^\wedge_{[r,\infty)} \mathcal{R}(\mathbb{I} - \Pi_{\text{Bad}}) \, | \phi'_t \rangle \right\|. \tag{5.67}
$$

Consider a basis state $|i, u, w\rangle |x\rangle$. If x does not record at least r wedges, then x must record at least $r-2\Delta(\mathcal{G}(x))$ wedges in order for $\Pi_{[r,\infty)}^{\hat{\wedge}}\mathcal{R}\left|i,u,w\right\rangle|x\rangle\neq0$. Recall $\Delta(\mathcal{G}(x))$ denotes the maximum degree of $\mathcal{G}(x)$. This is because R can introduce at most one new edge in register I_i and that new edge can introduce at most $2\Delta(\mathcal{G}(x))$ new wedges. (This bound is saturated when the new edge connects two disconnected vertices in $\mathcal{G}(x)$ of degree $\Delta(\mathcal{G}(x))$ each.) If $|i, u, w \rangle |x\rangle$ is in the support of $(\mathbb{I} - \Pi_{\text{Bad}}) | \phi'_{t}\rangle$, then $\Delta(G(x)) < 12 \log(n)$ by the definition of Π_{Bad} and so $\Delta(G(x)) \leq 12 \log(n)$ since the left-hand side is an integer. Therefore,

$$
\Lambda'_{t+1,r} \leq \left\| \Pi'_{[r,\infty)} \mathcal{R} (\mathbb{I} - \Pi_{\text{Bad}}) \Pi'_{[r,\infty)} |\phi'_t \rangle \right\| + \left\| \Pi'_{[r,\infty)} \mathcal{R} (\mathbb{I} - \Pi_{\text{Bad}}) \Pi'_{[r-2\lfloor 12 \log(n) \rfloor,r)} |\phi'_t \rangle \right\|
$$
\n
$$
= \left\| \Pi'_{[r,\infty)} \mathcal{R} (\mathbb{I} - \Pi_{\text{Bad}}) \Pi'_{[r,\infty)} |\phi'_t \rangle \right\| + \left\| \Pi'_{[r,\infty)} \mathcal{R} (\mathbb{I} - |0) \langle 0|_P) (\mathbb{I} - \Pi_{\text{Bad}}) \Pi'_{[r-2\lfloor 12 \log(n) \rfloor,r)} |\phi'_t \rangle \right\|
$$
\n
$$
\leq \left\| \Pi'_{[r,\infty)} |\phi'_t \rangle \right\| + \sum_{y \in [N] \cup \{\perp\}} \left\| \Pi'_{[r,\infty)} \mathcal{R} \Pi_y (\mathbb{I} - \Pi_{\text{Bad}}) \Pi'_{[r-2\lfloor 12 \log(n) \rfloor,r)} |\phi'_t \rangle \right\|
$$
\n
$$
= \Lambda'_{t,r} + \sum_{y \in [N] \cup \{\perp\}} \left\| \Pi'_{[r,\infty)} \mathcal{R} \Pi_y (\mathbb{I} - \Pi_{\text{Bad}}) \Pi'_{[r-2\lfloor 12 \log(n) \rfloor,r)} |\phi'_t \rangle \right\|. \tag{5.68}
$$

To go from the second term in the first line to that in the second line, we used the fact that $\mathcal R$ acts as identity on any basis state $|i, u, w\rangle |x\rangle$ when $u = 0$, so no more wedges will be recorded. In the third step, note that $\mathbb{I}_P - |0\rangle\langle 0|_P = \sum_{y \in [N] \cup \{\perp\}} \Pi_y$, then it follows from triangle inequality.

Abbreviate

$$
|\rho\rangle := (\mathbb{I} - \Pi_{\text{Bad}}) \Pi_{[r-2\lfloor 12 \log(n) \rfloor, r)}^{\wedge} |\phi_t'\rangle,
$$

we bound the second term in [Eq. \(5.68\)](#page-34-1) based on whether $y = \perp$ or not. We will show

$$
\left\| \Pi_{[r,\infty)}^{\wedge} \mathcal{R} \Pi_{\perp} \left| \rho \right> \right\| \leq 2 \sqrt{\frac{t}{n}} \Lambda_{t,r-2\lfloor 12 \log(n) \rfloor}^{\prime},\tag{5.69}
$$

$$
\sum_{y \in [N]} \left\| \Pi_{[r,\infty)}^{\wedge} \mathcal{R} \Pi_y \left| \rho \right> \right\| \le 6 \sqrt{\frac{t}{n}} \Lambda_{t,r-2\lfloor 12 \log(n) \rfloor}^{\prime}.
$$
\n(5.70)

Plugging [Eqs. \(5.69\)](#page-34-2) and [\(5.70\)](#page-34-3) into [Eq. \(5.68\),](#page-34-1) we obtain our main recurrence [Eq. \(5.66\)](#page-34-0) stated in the lemma, concluding the proof.

Bound Eq. (5.69) for $y = \bot$. When $y = \bot$, consider any basis state $|i, u, w \rangle |x\rangle$ in the support of

$$
\Pi_{\perp}(\mathbb{I} - \Pi_{\text{Bad}}) \Pi_{[r-2\lfloor 12 \log(n) \rfloor, r)}^{\wedge} |\phi_t^{\prime}\rangle. \tag{5.71}
$$

Due to Π_{\perp} , we have $x_i = \perp$ and $u \neq 0$, so [Lemma 5.10](#page-26-3) states

$$
\mathcal{R} |i, u, w\rangle |x\rangle = |i, u, w\rangle \left(\sum_{y \in [N]} \frac{\omega_N^{uy}}{\sqrt{N}} |y\rangle_{I_i} \right) \otimes \bigotimes_{j \neq i} |x_j\rangle_{I_j}.
$$
 (5.72)

Since $|i, u, w\rangle |x\rangle$ is also in the support of $|\phi_t'\rangle$, x records at most t edges by [Fact 5.9.](#page-26-2) Due to $\Pi_{[r-2\lfloor 12\log(n)\rfloor,r)}^{\wedge}$, x records fewer than r wedges. Therefore, in order for $|y\rangle_{I_i} \otimes \bigotimes_{j\neq i}|x_j\rangle_{I_j}$ to record at least r wedges, y must be an edge adjacent to some edge recorded in x , of which there are at most $t \cdot 2(n-1)$ possibilities. Therefore,

$$
\left\| \Pi_{[r,\infty)}^{\wedge} \mathcal{R} \left| i, u, w \right\rangle \left| x \right\rangle \right\| \leq \sqrt{\frac{t \cdot 2(n-1)}{N}} = 2\sqrt{\frac{t}{n}}.\tag{5.73}
$$

Since any two distinct basis states in the support of $\Pi_{\perp}(\mathbb{I}-\Pi_{\text{Bad}})\Pi^{\wedge}_{[r-2\lfloor 12\log(n)\rfloor,r)}|\phi_t\rangle$ remain orthogonal after $\Pi_{[r,\infty)}^{\wedge} \mathcal{R}$ is applied,^{[16](#page-35-0)} we have

$$
\left\| \Pi_{[r,\infty)}^{\wedge} \mathcal{R} \Pi_{\perp} (\mathbb{I} - \Pi_{\text{Bad}}) \Pi_{[r-2\lfloor 12 \log(n) \rfloor, r)}^{\wedge} |\phi_t' \rangle \right\|
$$
\n
$$
\leq 2 \sqrt{\frac{t}{n}} \left\| \Pi_{\perp} (\mathbb{I} - \Pi_{\text{Bad}}) \Pi_{[r-2\lfloor 12 \log(n) \rfloor, r)}^{\wedge} |\phi_t' \rangle \right\| \leq 2 \sqrt{\frac{t}{n}} \Lambda_{t, r-2\lfloor 12 \log(n) \rfloor}^{\prime}.
$$
\n(5.74)

Bound Eq. (5.70) for $y \in [N]$. When $y \in [N]$, consider any basis state $|i, u, w \rangle |x\rangle$ with non-zero amplitude in

$$
\Pi_y (\mathbb{I} - \Pi_{\text{Bad}}) \Pi_{[r-2\lfloor 12 \log(n) \rfloor, r)}^{\wedge} \ket{\phi'_t}.
$$
\n(5.75)

Due to Π_y , we have $x_i = y$ and $u \neq 0$, so [Lemma 5.10](#page-26-3) states

$$
\mathcal{R}|i, u, w\rangle |x\rangle = |i, u, w\rangle \left(\frac{\omega_N^{uy}}{\sqrt{N}} | \perp \rangle_{I_i} + \frac{1 + \omega_N^{uy}(N-2)}{N} |y\rangle_{I_i} + \sum_{y' \in [N] \setminus \{y\}} \frac{1 - \omega_N^{uy'} - \omega_N^{uy}}{N} |y'\rangle_{I_i}\right) \otimes \bigotimes_{j \neq i} |x_j\rangle_{I_j}.
$$
\n(5.76)

Applying similar reasoning as in the previous case, we deduce

$$
\left\| \Pi_{[r,\infty)}^{\wedge} \mathcal{R} \left| i, u, w \right\rangle \left| x \right\rangle \right\| \leq 3 \frac{\sqrt{t \cdot 2(n-1)}}{N}.
$$
\n(5.77)

Since any two distinct basis states in the support of $\Pi_y(\mathbb{I}-\Pi_{\text{Bad}})\Pi_{[r-2\lfloor 12\log(n)\rfloor,r)}^{\wedge}|\phi_t\rangle$ remain orthogonal after $\Pi^{\wedge}_{[r,\infty)}$ *R* is applied, we have

$$
\left\| \Pi_{[r,\infty)}^{\wedge} \mathcal{R} \Pi_y (\mathbb{I} - \Pi_{\text{Bad}}) \Pi_{[r-2\lfloor 12 \log(n) \rfloor, r)}^{\wedge} |\phi_t' \rangle \right\|
$$
\n
$$
\leq 3 \frac{\sqrt{t \cdot 2(n-1)}}{N} \left\| \Pi_y (\mathbb{I} - \Pi_{\text{Bad}}) \Pi_{[r-2\lfloor 12 \log(n) \rfloor, r)}^{\wedge} |\phi_t' \rangle \right\|. \tag{5.78}
$$

Therefore, applying the Cauchy-Schwarz inequality gives

$$
\sum_{y \in [N]} \left\| \Pi_{[r,\infty)}^{\wedge} \mathcal{R} \Pi_y (\mathbb{I} - \Pi_{\text{Bad}}) \Pi_{[r-2\lfloor 12 \log(n) \rfloor,r)}^{\wedge} \left| \phi_t' \right> \right\|
$$

\n
$$
\leq 3 \sqrt{\frac{t \cdot 2(n-1)}{N}} \sqrt{\sum_{y \in [N]} \left\| \Pi_y (\mathbb{I} - \Pi_{\text{Bad}}) \Pi_{[r-2\lfloor 12 \log(n) \rfloor,r)}^{\wedge} \left| \phi_t' \right> \right\|^2}
$$

\n
$$
\leq 6 \sqrt{\frac{t}{n}} \Lambda_{t,r-2\lfloor 12 \log(n) \rfloor}^{\prime}.
$$

¹⁶Suppose basis state $|i',u',w'\rangle |x'\rangle$ is orthogonal to $|i,u,w\rangle |x\rangle$. If $(i',u',w') \neq (i,u,w)$, then it is clear that the two states remain orthogonal after applying $\Pi_{[r,\infty)}^{\wedge}$ R since the operator can only act non-trivially on the input register. If $(i', u', w') = (i, u, w)$ and $x_j \neq x'_j$ for some $j \neq i$, then the two states still remain orthogonal since R does not act on the I_j register and $\Pi_{[r,\infty)}^{\wedge}$ is diagonal in the $\{|z\rangle | z \in ([N] \cup \{\perp\})^m\}$ basis. The case $(i',u',w') = (i,u,w)$ and $x_i \neq x'_i$ is forbidden by the assumption that the basis states lie in the support of Π_{\perp} . We will later reuse similar arguments without comment.

Solving the wedges progress recurrence, we obtain

Lemma 5.20 (Wedges progress). For any $t, r \in \mathbb{Z}_{\geq 0}$ with $r \geq 24 \log(n)$, we have

$$
\Lambda_{t,r}' \le \left(\frac{8et^{3/2}}{\lfloor \frac{r}{2\lfloor 12\log(n)\rfloor} \rfloor \sqrt{n}}\right)^{\lfloor \frac{r}{2\lfloor 12\log(n)\rfloor} \rfloor}.
$$
\n(5.79)

Proof. Let $k \coloneqq \lfloor \frac{r}{2 \lfloor 12 \log r} \rfloor$ $\frac{r}{2\lfloor 12 \log(n) \rfloor}$ $\rfloor \geq 1$. By definition, $\Lambda'_{t,r} \leq \Lambda'_{t,k \cdot 2\lfloor 12 \log(n) \rfloor}$. Therefore,

$$
\Lambda_{t,r}' \le \Lambda_{t,k\cdot 2\lfloor 12\log(n)\rfloor}' \le \binom{t}{k} \left(8\sqrt{\frac{t}{n}}\right)^k \le \left(\frac{8et^{3/2}}{k\sqrt{n}}\right)^k,\tag{5.80}
$$

where we solved the recurrence from [Lemma 5.19](#page-33-1) in the second inequality.

5.3.4 Progress in recording a triangle

We move on to bounding the progress of a quantum query algorithm in recording a triangle. Recall that we defined the progress measure of finding a triangle within t queries

$$
\Delta_t \coloneqq \left\| \Pi^\triangle \left| \phi_t \right> \right\|. \tag{5.81}
$$

We first derive the triangle progress recurrence for Δ_t . The key idea here is to decompose the state $|\phi_t\rangle$ based on the number of wedges recorded to some buckets parameterized by r_1, \ldots, r_l . This way we get to choose between the following two facts to our advantage: (i) It is in general hard to record many wedges with a small number of queries as formally shown in [Lemma 5.20;](#page-36-0) (ii) When the number of wedges recorded is small, it is hard to find a triangle with one extra query.

Lemma 5.21 (Triangle progress recurrence). For any $t \in \mathbb{Z}_{\geq 2}$ and $0 = r_0 < r_1 < r_2 < \cdots < r_l = \binom{t}{2}$ $_{2}^{t}\big),$ we have

$$
\Delta_{t+1} \le \Delta_t + \sum_{k=0}^{l-1} \left(4\Lambda_{t,r_k} \sqrt{\frac{2r_{k+1}}{n(n-1)}} \right).
$$
\n(5.82)

In addition, $\Delta_0 = \Delta_1 = \Delta_2 = 0$.

Proof. The boundary conditions $\Delta_0 = \Delta_1 = \Delta_2 = 0$ hold by [Fact 5.9,](#page-26-2) since it takes three edges to form a triangle. In the remainder of the proof, we focus on deriving [Eq. \(5.82\).](#page-36-1)

For $t \in \mathbb{Z}_{\geq 0}$, since U_{t+1} acts as identity on the input register, we have

$$
\Delta_{t+1} = \left\| \Pi^{\Delta} U_{t+1} \mathcal{R} \left| \phi_t \right> \right\| = \left\| \Pi^{\Delta} \mathcal{R} \left| \phi_t \right> \right\|.
$$
\n(5.83)

For any basis state $|i, u, w \rangle |x\rangle$ in $|\phi_t\rangle$ with non-zero amplitude, x can have recorded at most $\binom{t}{2}$ $_{2}^{t}$) wedges by [Fact 5.9.](#page-26-2) Decompose the state $|\phi_t\rangle$ based on the number of wedges recorded of the computational basis element to some buckets parameterized by r_1, \ldots, r_l . Then, analogous to [Eq. \(5.68\),](#page-34-1) we obtain

$$
\Delta_{t+1} \leq \left\| \Pi^{\triangle} \mathcal{R} \Pi^{\triangle} |\phi_t \rangle \right\| + \sum_{k=0}^{l-1} \left\| \Pi^{\triangle} \mathcal{R} (\mathbb{I} - \Pi^{\triangle}) \Pi^{\wedge}_{[r_k, r_{k+1}]} |\phi_t \rangle \right\|
$$

\n
$$
\leq \left\| \Pi^{\triangle} |\phi_t \rangle \right\| + \sum_{k=0}^{l-1} \sum_{y \in [N] \cup \{\perp\}} \left\| \Pi^{\triangle} \mathcal{R} \Pi_y (\mathbb{I} - \Pi^{\triangle}) \Pi^{\wedge}_{[r_k, r_{k+1}]} |\phi_t \rangle \right\|
$$

\n
$$
= \Delta_t + \sum_{k=0}^{l-1} \sum_{y \in [N] \cup \{\perp\}} \left\| \Pi^{\triangle} \mathcal{R} \Pi_y (\mathbb{I} - \Pi^{\triangle}) \Pi^{\wedge}_{[r_k, r_{k+1}]} |\phi_t \rangle \right\|. \tag{5.84}
$$

 \Box

Next, we bound the second term in [Eq. \(5.84\)](#page-36-2) based on whether $y = \perp$ or not. Abbreviate

$$
|\rho_k\rangle := (\mathbb{I} - \Pi^{\triangle})\Pi^{\wedge}_{[r_k,r_{k+1}]}\,|\phi_t\rangle.
$$

We will show that for any $k = 0, 1, \ldots, l - 1$,

$$
\left\| \Pi^{\triangle} \mathcal{R} \Pi_{\perp} | \rho_k \rangle \right\| \leq \sqrt{\frac{2r_{k+1}}{n(n-1)}} \Lambda_{t, r_k}, \tag{5.85}
$$

$$
\sum_{y \in [N]} \left\| \Pi^{\triangle} \mathcal{R} \Pi_y \left| \rho_k \right> \right\| \le 3 \sqrt{\frac{2r_{k+1}}{n(n-1)}} \Lambda_{t, r_k}.
$$
\n(5.86)

Plugging [Eqs. \(5.85\)](#page-37-0) and [\(5.86\)](#page-37-1) into [Eq. \(5.84\),](#page-36-2) we obtain our main recurrence [Eq. \(5.82\)](#page-36-1) stated in the lemma, concluding the proof.

Bound Eq. (5.85) for $y = \perp$. When $y = \perp$, consider any basis state $|i, u, w \rangle |x\rangle$ in the support of

$$
\Pi_{\perp}(\mathbb{I}-\Pi^{\triangle})\Pi^{\wedge}_{[r_k,r_{k+1}]}\ket{\phi_t}.
$$
\n(5.87)

Due to Π_{\perp} , we have $x_i = \perp$ and $u \neq 0$, so [Lemma 5.10](#page-26-3) states

$$
\mathcal{R} |i, u, w\rangle |x\rangle = |i, u, w\rangle \left(\sum_{y \in [N]} \frac{\omega_N^{uy}}{\sqrt{N}} |y\rangle_{I_i} \right) \otimes \bigotimes_{j \neq i} |x_j\rangle_{I_j}.
$$
 (5.88)

Due to $\Pi^{\wedge}_{[r_k,r_{k+1}]}, x$ records at most r_{k+1} wedges. Due to $(\mathbb{I}-\Pi^{\triangle})$, x does not record a triangle. Therefore, in order for $|y\rangle_{I_i} \otimes \bigotimes_{j \neq i} |x_j\rangle_{I_j}$ to record a triangle, y must be an edge that completes some wedge recorded in x to a triangle, of which there are at most r_{k+1} possibilities. Therefore,

$$
\left\| \Pi^{\triangle} \mathcal{R} \left| i, u, w \right\rangle |x\rangle \right\| \leq \sqrt{\frac{r_{k+1}}{N}} = \sqrt{\frac{2r_{k+1}}{n(n-1)}},\tag{5.89}
$$

Since any two distinct basis states in the support of $\Pi_{\perp}(\mathbb{I}-\Pi^{\triangle})\Pi^{\wedge}_{[r_k,r_{k+1}]}\ket{\phi_t}$ remain orthogonal after $\Pi^{\triangle} \mathcal{R}$ is applied, we have

$$
\left\| \Pi^{\triangle} \mathcal{R} \Pi_{\perp} (\mathbb{I} - \Pi^{\triangle}) \Pi^{\wedge}_{[r_k, r_{k+1}]} |\phi_t \rangle \right\|
$$
\n
$$
\leq \sqrt{\frac{2r_{k+1}}{n(n-1)}} \left\| \Pi_{\perp} (\mathbb{I} - \Pi^{\triangle}) \Pi^{\wedge}_{[r_k, r_{k+1}]} |\phi_t \rangle \right\| \leq \sqrt{\frac{2r_{k+1}}{n(n-1)}} \Lambda_{t, r_k}.
$$
\n(5.90)

Bound Eq. (5.86) for $y \in [N]$. When $y \in [N]$, consider any basis state $|i, u, w \rangle |x\rangle$ with non-zero amplitude in

$$
\Pi_y(\mathbb{I} - \Pi^{\triangle})\Pi^{\wedge}_{[r_k, r_{k+1}]} |\phi_t\rangle, \qquad (5.91)
$$

Due to Π_y , we have $x_i = y$ and $u \neq 0$, so [Lemma 5.10](#page-26-3) states

$$
\mathcal{R}|i, u, w\rangle |x\rangle = |i, u, w\rangle \left(\frac{\omega_N^{uy}}{\sqrt{N}} | \perp \rangle_{I_i} + \frac{1 + \omega_N^{uy}(N-2)}{N} |y\rangle_{I_i} + \sum_{y' \in [N] \setminus \{y\}} \frac{1 - \omega_N^{uy'} - \omega_N^{uy}}{N} |y'\rangle_{I_i}\right) \otimes \bigotimes_{j \neq i} |x_j\rangle_{I_j}.
$$
\n(5.92)

Applying similar reasoning as in the previous case, we deduce

$$
\left\| \Pi^{\triangle} \mathcal{R} \left| i, u, w \right\rangle \left| x \right\rangle \right\| \leq 3 \frac{\sqrt{r_{k+1}}}{N}.
$$
\n(5.93)

Since any two distinct basis states in the support of $\Pi_y(\mathbb{I}-\Pi^\triangle)\Pi_{[r_k,r_{k+1}]}^\wedge|\phi_t\rangle$ remain orthogonal after $\Pi^{\triangle} \mathcal{R}$ is applied, we have

$$
\left\|\Pi^{\triangle} \mathcal{R} \Pi_y(\mathbb{I} - \Pi^{\triangle})\Pi^{\wedge}_{[r_k, r_{k+1}]} |\phi_t\rangle\right\| \le 3 \frac{\sqrt{r_{k+1}}}{N} \left\|\Pi_y(\mathbb{I} - \Pi^{\triangle})\Pi^{\wedge}_{[r_k, r_{k+1}]} |\phi_t\rangle\right\|. \tag{5.94}
$$

Therefore, applying the Cauchy-Schwarz inequality gives

$$
\sum_{y\in[N]} \left\| \Pi^{\Delta} \mathcal{R} \Pi_y (\mathbb{I} - \Pi^{\Delta}) \Pi_{[r_k, r_{k+1}]}^{\wedge} \left| \phi_t \right> \right\|
$$

$$
\leq 3 \sqrt{\frac{r_{k+1}}{N}} \sqrt{\sum_{y\in[N]} \left\| \Pi_y (\mathbb{I} - \Pi^{\Delta}) \Pi_{[r_k, r_{k+1}]}^{\wedge} \left| \phi_t \right> \right\|^2} \leq 3 \sqrt{\frac{2r_{k+1}}{n(n-1)}} \Lambda_{t, r_k}.
$$

In the next lemma, we optimize over some r_1, r_2, \ldots, r_l and solve the triangle progress recurrence. In fact, it suffices to choose l to be at most 2.

Lemma 5.22 (Hardness of recording a triangle). Suppose $m = n \ge 16$, then

$$
\Delta_T \le O\left(\frac{T\log^{2/7}(n)}{n^{5/7}} + T\left(\frac{T^{3/2}\log^{3/7}(n)}{n^{15/14}}\right)^{\Theta(n^{4/7}/\log^{3/7}(n))} + \frac{T}{n}\right).
$$
(5.95)

In particular, if $T \le o(n^{5/7} / \log^{2/7}(n))$, then $\Delta_T \le o(1)$.

Proof. Fix some $t \in \{2, 3, ..., T\}$. Note that $\binom{t}{2}$ $\binom{t}{2}$ is the trivial upper bounds on the number of wedges recorded at time t. To choose r_1, r_2, \ldots, r_l in [Lemma 5.21,](#page-36-3) we only consider the partition of $\{0, 1, \ldots, \binom{t}{2}$ $_{2}^{t})\}$ in the middle by a fixed point r^* given by

$$
r^* := \left\lceil \frac{n^{4/7}}{\log^{3/7}(n)} \right\rceil \lfloor 12 \log(n) \rfloor. \tag{5.96}
$$

In particular, if $\binom{t}{2}$ $\binom{t}{2}$ > r^* , then invoke [Lemma 5.21](#page-36-3) by setting $l = 2$ and $r_1 = r^*$, obtaining

$$
\Delta_{t+1} \le \Delta_t + 4\Lambda_{t,0} \sqrt{\frac{2r^*}{n(n-1)}} + 4\Lambda_{t,r^*} \sqrt{\frac{2\binom{t}{2}}{n(n-1)}} \le \Delta_t + 8\frac{\sqrt{r^*}}{n} + 4\Lambda_{t,r^*};
$$
\n(5.97)

If $\binom{t}{2}$ $\binom{t}{2} \leq r^*$, then invoke [Lemma 5.21](#page-36-3) by setting $l = 1$, obtaining

$$
\Delta_{t+1} \le \Delta_t + 4\Lambda_{t,0} \sqrt{\frac{2\binom{t}{2}}{n(n-1)}} \le \Delta_t + 8\frac{\sqrt{r^*}}{n} \le \Delta_t + 8\frac{\sqrt{r^*}}{n} + 4\Lambda_{t,r^*}.
$$
\n(5.98)

Therefore, irrespective of the value of t , we have

$$
\Delta_{t+1} \leq \Delta_t + 8 \frac{\sqrt{r^*}}{n} + 4 \Lambda_{t,r^*} \n\leq \Delta_t + 8 \frac{\sqrt{r^*}}{n} + 4 \left(\Lambda_{t,r^*}^{\prime} + \frac{2}{n} \right) \n\leq \Delta_t + 8 \frac{\sqrt{r^*}}{n} + 4 \left(\left(\frac{8et^{3/2}}{\left[\frac{r^*}{2[12 \log(n)]} \right] \sqrt{n}} \right)^{\left[\frac{r^*}{2[12 \log(n)]} \right]} + \frac{2}{n} \right),
$$
\n(5.99)

where the second inequality uses [Eq. \(5.63\)](#page-33-0) and [Corollary 5.18,](#page-32-0) which applies since $m = n \ge 16$; and the last inequality uses [Lemma 5.20,](#page-36-0) which applies since $r^* \geq 24 \log(n)$ for $n \geq 12$.

Since $\Delta_0 = \Delta_1 = \Delta_2 = 0$, the recurrence in [Eq. \(5.99\)](#page-38-0) yields

$$
\Delta_T \le T \cdot \left(\frac{8\sqrt{r^*}}{n} + 4 \left(\left(\frac{8e^{2\sqrt{r^*}}}{\left[\frac{r^*}{2\left[12\log(n) \right]} \right] \sqrt{n}} \right)^{2\left[\frac{r^*}{2\left[12\log(n) \right]} \right]} + \frac{2}{n} \right) \right) \n\le O\left(\frac{T\log^{2/7}(n)}{n^{5/7}} + T \left(\frac{T^{3/2}\log^{3/7}(n)}{n^{15/14}} \right)^{\Theta(n^{4/7}/\log^{3/7}(n))} + \frac{T}{n} \right),
$$
\n(5.100)

where we substituted the definition of r^* in the second inequality.

The "in particular" part of the lemma follows immediately.

5.3.5 Completing the proof of [Theorem 5.5](#page-24-1)

To finish the proof, we use the next lemma, which bounds the probability of the algorithm succeeding even if it does not record a triangle. Intuitively, if the algorithm does not record a triangle, it should not be significantly better at finding a triangle than random guessing. The lemma is standard in the recording query framework — indeed, our proof is based on [\[HM23,](#page-51-7) Proof of Proposition 4.4] — but we include it for completeness.

Let Π_{succ} denote the projector onto basis states $|i, u, w \rangle |x\rangle$ such that w contains an output substring (i.e., a substring located at some fixed output register) of the form $(a_1, a_2, a_3, b_1, b_2, b_3) \in [m]^3 \times \binom{[n]}{2}$ ${n \brack 2}^3$ where the a_i s are distinct, the b_i s form a triangle, and $x_{a_i} = b_i$ for all *i*.

Lemma 5.23 (Hardness of guessing a triangle). For any state $|\phi\rangle$, $\left\|\Pi_{\text{succ}}\mathcal{T}(\mathbb{I}-\Pi^{\Delta})\ket{\phi}\right\| \leq O(\frac{1}{n})$ $\frac{1}{n}$).

Proof. For $k, l \in \mathbb{Z}_{\geq 0}$ with $k+l \leq 3$, we define the projector $P_{k,l}$ to be onto basis states $|i, u, w\rangle |x\rangle$, where

- (i) w contains the output substring $(a_1, a_2, a_3, b_1, b_2, b_3) \in [m]^3 \times \binom{[n]}{2}$ $\binom{n}{2}^3$ where the a_i s are distinct and the b_i s form a triangle;
- (ii) there are exactly k indices $i \in [3]$ such that $x_{a_i} = \perp$;

(iii) there are exactly l indices $i \in [3]$ such that $x_{a_i} \neq \perp$ and $x_{a_i} \neq b_i$.

Observe that if $|i, u, w\rangle |x\rangle$ is in the support of $\mathbb{I} - \Pi^{\Delta}$, then $P_{0,0} |i, u, w\rangle |x\rangle = 0$. This is because if $|i, u, w\rangle |x\rangle$ is in the support of $P_{0,0}$, then $x_{a_i} = b_i$ for all i and the b_i s form a triangle, which contradicts the assumption.

For a state $|i, u, w \rangle |x\rangle$ in the support of $P_{k,l}$, we have

$$
\|\Pi_{\text{succ}}\mathcal{T}|i,u,w\rangle\,x\rangle\| \leq (1/\sqrt{N})^k (1/N)^l,\tag{5.101}
$$

using the definition of \mathcal{T} .

For $|i, u, w\rangle |x\rangle$ in the support of $P_{k,l}$, we write $w_a := \{a_1, a_2, a_3\}$ for the set containing the first three elements of the output substring. Observe that $|i, u, w \rangle |x\rangle$ and $|i', u', w' \rangle |x'\rangle$ remain orthogonal after applying Π_{succ} \mathcal{T} unless $i' = i, u = u', w = w'$ and $x_s = x'_s$ for all $s \in [m] - \{a_1, a_2, a_3\}.$

Therefore, for a state $|\chi\rangle := \sum_{i,u,w,x} \alpha_{i,u,w,x} |i,u,w\rangle |x\rangle$ in the support of $P_{k,l}$, we have

$$
\|\Pi_{\text{succ}}\mathcal{T}|\chi\rangle\|^2 = \sum_{i,u,w,(x_{a'})_{a'\notin w_a}} \left\|\sum_{(x_{a'})_{a'\in w_a}} \alpha_{i,u,w,x} \Pi_{\text{succ}}\mathcal{T}|i,u,w\rangle |x\rangle\right\|^2
$$

\$\leq \sum_{i,u,w,(x_{a'})_{a'\notin w_a}} \left(\sum_{(x_{a'})_{a'\in w_a}} |\alpha_{i,u,w,x}|^2\right) \left(\sum_{(x_{a'})_{a'\in w_a}} \|\Pi_{\text{succ}}\mathcal{T}|i,u,w\rangle |x\rangle\|^2\right)\$ (5.102)
\$\leq \left(\frac{3}{k,l,3-(k+l)}\right)(N-1)^l \cdot \left(\frac{1}{N}\right)^k \left(\frac{1}{N^2}\right)^l \leq \frac{6}{N^{k+l}},

 \Box

where the first inequality is Cauchy-Schwarz and the second inequality is Eq. (5.101) .

Finally, write P for the projector onto basis states $|i, u, w \rangle |x\rangle$ not satisfying the first condition defining $P_{k,l}$ so that $\mathbb{I} = P + \sum_{k,l \in \mathbb{Z}_{\geq 0}: k+l \leq 3} P_{k,l}$. Therefore

$$
\left\| \Pi_{\text{succ}} \mathcal{T}(\mathbb{I} - \Pi^{\Delta}) \, |\phi\rangle \right\|^2 = \left\| \Pi_{\text{succ}} \mathcal{T}(\mathbb{I} - \Pi^{\Delta}) \left(P + \sum_{k,l \in \mathbb{Z}_{\geq 0} : \, k+l \leq 3} P_{k,l} \right) |\phi\rangle \right\|^2
$$

$$
= \left\| \Pi_{\text{succ}} \mathcal{T}(\mathbb{I} - \Pi^{\Delta}) \left(\sum_{k,l \in \mathbb{Z}_{\geq 0} : \, 0 < k+l \leq 3} P_{k,l} \right) |\phi\rangle \right\|^2
$$

$$
= \left\| \Pi_{\text{succ}} \mathcal{T} \left(\sum_{k,l \in \mathbb{Z}_{\geq 0} : \, 1 \leq k+l \leq 3} P_{k,l} \right) (\mathbb{I} - \Pi^{\Delta}) |\phi\rangle \right\|^2 \leq \frac{54}{N},\tag{5.103}
$$

where the second equality uses $\Pi_{succ}P = 0$ and $(\mathbb{I} - \Pi^{\triangle})P_{0,0} = 0$ as observed previously, and the last inequality uses [Eq. \(5.102\)](#page-39-1) and the restriction on the sum of $P_{k,l}$ s to $1 \leq k+l$.

The lemma follows from [Eq. \(5.103\)](#page-40-2) after taking square roots on both sides and recalling $N = \binom{n}{2}$ $\binom{n}{2}$.

We can now complete the proof of [Theorem 5.5.](#page-24-1) If $T \le o(n^{5/7} / \log^{2/7}(n))$, we have

$$
\|\Pi_{\text{succ}} |\psi_T\rangle\| = \|\Pi_{\text{succ}} \mathcal{T} |\phi_T\rangle\| \le \left\|\Pi^{\triangle} |\phi_T\rangle\right\| + \left\|\Pi_{\text{succ}} \mathcal{T}(\mathbb{I} - \Pi^{\triangle}) |\phi_T\rangle\right\| \le o(1),\tag{5.104}
$$

where we used [Lemma 5.22](#page-38-1) to bound the first term and [Lemma 5.23](#page-39-2) to bound the second term.

5.4 Triangle finding upper bound

In this section, we prove the following theorem.

Theorem 5.24. For all $m, d \in \mathbb{N}$, $Q(\text{Triangle}_{m,d}) \leq O(2^{(10/7)d}d^{2/7}m^{5/7})$.

Corollary 5.25. For all $m \in \mathbb{N}$ and $d \leq O(\log(m)/\log \log(m))$, $Q(\text{Triangle}_{m,d}) \leq O(m^{5/7+o(1)})$. In view of [Fact 5.3,](#page-23-3) if $n \ge \Omega(m)$ there exists a quantum query algorithm using $O(m^{5/7+o(1)})$ that finds a triangle in a random sparse graph $x \leftarrow \binom{[n]}{2}$ $\binom{n}{2}^m$, or decides it does not exist, with success probability $\geq 1 - o(1)$.

We prove [Theorem 5.24](#page-40-3) by adapting Belovs's learning graph algorithm for 3-distinctness [\[Bel12b\]](#page-50-0). A key challenge in Belovs's work is the presence of faults, as intuitively described in the introduction. At a technical level, faults are violations of the feasibility conditions in the semi-definite program characterizing quantum query complexity. Belovs found that directly using a learning graph algorithm of the type in his earlier work [\[Bel12a\]](#page-50-7) led to faults. In [\[Bel12b\]](#page-50-0), for k-distinctness, Belovs devised a technique based on the inclusion-exclusion principle to "error-correct" these faults at the cost of an exponential-in- k factor, which is constant for constant k.

Technically speaking, in 3-distinctness, at most one fault can occur because negative instances are limited to having 2-collisions, and once one index of a 2-collision is fixed, only its second index could possibly contribute a fault. In our problem, however, a single edge can belong to up to $2(d-1)$ wedges, where d is the maximum degree of the graph, introducing the possibility of multiple faults. Fortunately, Belovs's learning graph algorithm for k-distinctness for general k shows how inclusion-exclusion can be used to handle multiple faults. We adapt this technique to our problem and it represents the main change we make to his 3-distinctness algorithm. The additional changes we make, such as explicitly defining the graph, replacing the concept of "arcs taken" with "active arcs," and elaborating on somewhat opaque definitions, are primarily for improved clarity and accessibility. These adjustments do not alter the underlying algorithm and are not strictly necessary.

In summary, our algorithm for triangle finding is closely aligned with Belovs's original learning graph algorithm for 3-distinctness, which highlights the deep structural similarities between 3-distinctness and triangle finding.

5.4.1 Setting up proof of [Theorem 5.24](#page-40-3)

When $d \geq \log_2(m)$, the trivial bound $Q(\text{Triangle}_m) \leq m$ applies, ensuring [Theorem 5.24](#page-40-3) is satisfied. When $d \leq \log_2(m)$, we employ the learning graph method along with [Fact 5.4](#page-24-2) to confirm the validity of [Theorem 5.24.](#page-40-3)

Adversary bound and learning graphs. In [\[Bel12b\]](#page-50-0), Belovs used a learning graph approach to construct matrices for the adversary bound. For any function $g: \mathcal{D} \subseteq \Sigma^m \to \{0,1\}$, the adversary bound $Adv^{\pm}(g)$ satisfies the following theorem.

Theorem 5.26 ([\[HLS07\]](#page-51-10),[\[LMR](#page-51-13)⁺11]). $Q(q) = \Theta(\text{Adv}^{\pm}(q)).$

 $\text{Adv}^{\pm}(g)$ can be formulated as the following semi-definite program [\[Rei09,](#page-52-5) Theorem 6.2]:

minimize
$$
\max_{x \in \mathcal{D}} \sum_{j \in [m]} X_j[x, x],
$$
 (5.105)

subject to

$$
\sum_{j \in [m]: \ x_j \neq y_j} X_j[x, y] = 1 \qquad \text{if } g(x) \neq g(y); \tag{5.106}
$$

$$
0 \le X_j \in \mathbb{C}^{\mathcal{D} \times \mathcal{D}} \quad \text{for all } j \in [m]. \tag{5.107}
$$

Any valid construction of $\{X_j\}_{j\in[m]}$ provides an upper bound for $\text{Adv}^{\pm}(g)$ and, consequently, an upper bound for $Q(g)$ up to constant factors. We construct $\{X_j\}_{j\in[m]}$ using the learning graph framework, following a similar approach to that in [\[Bel12b\]](#page-50-0). Specifically, for each arc $A_i^{R,S}$ $j^{h,5}$ in the learning graph from vertex R and to vertex S where R and S uniquely determines j (to be shown in detail later), we associate a positive semi-definite matrix $X_i^{R,S}$ $j^{R, S}$, and define

$$
X_j \coloneqq \sum_{R,S} X_j^{R,S}.\tag{5.108}
$$

5.4.2 Learning graph construction

We first describe the construction of the learning graph. For simplicity, we use f to denote $\text{Triangle}_{m,d}$. The vertices of the learning graph are

$$
\dot{\bigcup}_{i \in \{0,1,2,3,4\}} V^{(i)},\tag{5.109}
$$

where a vertex $S^{(i)}$ in $V^{(i)}$ is (labelled by) an array of length $(2^{2d}-1)+2d$ containing pairwise disjoint subsets of $[m]$; we refer to entries of $S^{(i)}$ by

$$
S^{(i)} = (S_1^{(i)}(\Gamma), S_2^{(i)}(\gamma))_{\emptyset \neq \Gamma \subseteq [2d], \gamma \in [2d]} = (S_1^{(i)}(\{1\}), \dots, S_1^{(i)}([2d]), S_2^{(i)}(1), \dots, S_2^{(i)}(2d)).
$$
 (5.110)

For vertices in $V^{(1)}$, we have the following size requirements:

$$
\forall \varnothing \neq \Gamma \subseteq [2d], \gamma \in [2d], \quad \left| S_1^{(1)}(\Gamma) \right| = r_1 \quad \text{and} \quad \left| S_2^{(1)}(\gamma) \right| = r_2. \tag{5.111}
$$

We partition $V^{(2)}$, $V^{(3)}$ and $V^{(4)}$ with label $\varnothing \neq \Gamma \subseteq [2d]$ such that $V^{(2)}(\Gamma)$ consists of all collections of $S^{(2)}$ with

$$
\left| S_1^{(2)}(\Gamma) \right| = r_1 + 1, \qquad \forall \Gamma' \neq \Gamma, \left| S_1^{(2)}(\Gamma') \right| = r_1, \qquad \forall \gamma \in [2d], \left| S_2^{(2)}(\gamma) \right| = r_2. \tag{5.112}
$$

For any finite $\Gamma \subseteq \mathbb{Z}$, let $\mu(\Gamma)$ denote the minimum element of Γ . $V^{(3)}(\Gamma)$ consists of all collections of $S^{(3)}$ such that

$$
\left| S_1^{(3)}(\Gamma) \right| = r_1 + 1, \qquad \forall \Gamma' \neq \Gamma, \left| S_1^{(3)}(\Gamma') \right| = r_1,\tag{5.113}
$$

and

$$
\left| S_2^{(3)}(\mu(\Gamma)) \right| = r_2 + 1, \qquad \forall \gamma \neq \mu(\Gamma), \left| S_2^{(3)}(\gamma) \right| = r_2.
$$
 (5.114)

 $V^{(4)}(\Gamma)$ consists of all collections of $S^{(4)}$ such that

$$
\left| S_1^{(4)}(\Gamma) \right| = r_1 + 1, \qquad \forall \Gamma' \neq \Gamma, \left| S_1^{(4)}(\Gamma') \right| = r_1,\tag{5.115}
$$

and

$$
\left| S_2^{(4)}(\mu(\Gamma)) \right| = r_2 + 2, \qquad \forall \gamma \neq \mu(\Gamma), \left| S_2^{(4)}(\gamma) \right| = r_2.
$$
 (5.116)

For any vertex R in the learning graph, define

$$
\bigcup R_1 := \bigcup_{\varnothing \neq \Gamma \subseteq [2d]} R_1(\Gamma), \quad \bigcup R_2 := \bigcup_{\gamma \in [2d]} R_2(\gamma), \quad \text{and} \quad \bigcup R := \bigcup R_1 \cup \bigcup R_2. \tag{5.117}
$$

We refer to indices contained in the first, second, and third sets as having been loaded in R_1 , R_2 , and R , respectively. All arcs in the graph from vertex R to vertex S are of the form $A_i^{R,S}$ $_{j}^{R,S}$, where $\bigcup S = \bigcup R \cup \{j\}$. Accordingly, we say that the arc $A_i^{R,S}$ $j^{h,5}$ is associated with the loading of j.

There exists a unique vertex in $R^{(0)} \in V^{(0)}$ such that $\bigcup R^{(0)} = \emptyset$. We refer to this vertex as the source, denoted by \emptyset . Any vertex $R^{(1)} \in V^{(1)}$ loads exactly

$$
r \coloneqq r_1 \cdot (2^{2d} - 1) + r_2 \cdot (2d) \tag{5.118}
$$

indices. We fix an arbitrary ordering t_1, \ldots, t_r of indices in $\bigcup R^{(1)}$ such that all indices in $\bigcup R_1^{(1)}$ $1^{(1)}$ precede those in $\bigcup R_2^{(1)}$ $2⁽¹⁾$. There exists a length r path from the source \varnothing to $R⁽¹⁾$, with all intermediate vertices lying in $V^{(0)}$. Along this path, the element t_i is loaded on the *i*-th arc for $i \in [r]$ during stages I.1 and I.2. Specifically,

- **If** $t_i \in \bigcup R_1^{(1)}$ $\mathcal{L}^{(1)}_{1}$, it is loaded during stage I.1,
- **If** $t_i \in \bigcup R_2^{(1)}$ $_2^{(1)}$, it is loaded during stage I.2.

All such paths are disjoint except at the source \varnothing . Therefore, there are $r|V^{(1)}|$ arcs in stages I.1 and I.2 in total.

In stage II.1, for each $R^{(1)} \in V^{(1)}$, $j \notin \bigcup R^{(1)}$ and $\varnothing \neq \Gamma \subseteq [2d]$, there is an arc, denoted $A_j^{R^{(1)},R^{(2)}}$ $j^{(1)},n^{(2)},$ from $R^{(1)}$ to $R^{(2)} \in V^{(2)}(\Gamma)$ defined by

$$
\begin{cases}\nR_1^{(2)}(\Gamma) = R_1^{(1)}(\Gamma) \cup \{j\}, \\
R_1^{(2)}(\Gamma') = R_1^{(1)}(\Gamma'), \quad \text{for all } \emptyset \neq \Gamma' \subseteq [2d] \text{ s.t. } \Gamma' \neq \Gamma, \\
R_2^{(2)}(\gamma) = R_2^{(1)}(\gamma), \quad \text{for all } \gamma \in [2d].\n\end{cases} (5.119)
$$

In stage II.2, for each $\varnothing \neq \Gamma \subseteq [2d]$, $R^{(2)} \in V^{(2)}(\Gamma)$, and $j \notin \bigcup R^{(2)}$, there is an arc, denoted $A_j^{R^{(2)},R^{(3)}}$ $j^{K^{(-)},K^{(+)}},$ from $R^{(2)}$ to $R^{(3)} \in V^{(3)}(\Gamma)$ defined by

$$
\begin{cases}\nR_1^{(3)}(\Gamma') &= R_1^{(2)}(\Gamma'), & \text{for all } \varnothing \neq \Gamma' \subseteq [2d], \\
R_2^{(3)}(\gamma) &= R_2^{(2)}(\gamma), & \text{for all } \gamma \neq \mu(\Gamma), \\
R_2^{(3)}(\mu(\Gamma)) = R_2^{(2)}(\mu(\Gamma)) \cup \{j\}.\n\end{cases}
$$
\n(5.120)

In stage II.3, for each $\varnothing \neq \Gamma \subseteq [2d], R^{(3)} \in V^{(3)}(\Gamma)$, and $j \not\in \bigcup R^{(3)}$, there is an arc, denoted $A_j^{R^{(3)},R^{(4)}}$ $j^{n_{\vee},n_{\vee}},$ from $R^{(3)}$ to $R^{(4)} \in V^{(4)}(\Gamma)$ defined by

$$
\begin{cases}\nR_1^{(4)}(\Gamma') &= R_1^{(3)}(\Gamma'), & \text{for all } \varnothing \neq \Gamma' \subseteq [2d], \\
R_2^{(4)}(\gamma) &= R_2^{(3)}(\gamma), & \text{for all } \gamma \neq \mu(\Gamma), \\
R_2^{(4)}(\mu(\Gamma)) = R_2^{(3)}(\mu(\Gamma)) \cup \{j\}.\n\end{cases}
$$
\n(5.121)

5.4.3 Active arcs

For any $x \in f^{-1}(1)$, let $\mathcal{C}(x) = \{a_1, a_2, a_3\} \subseteq [m]$ be a specific certificate for x such that $a_1 < a_2 < a_3$ and x_{a_1} , x_{a_2} , and x_{a_3} form a triangle.

We say $R^{(1)} \in V^{(1)}$ is consistent with $x \in f^{-1}(1)$ if edges indexed by $\mathcal{C}(x)$ are vertex disjoint from edges indexed by $\bigcup R^{(1)}$. Let n_x be the the number of $R^{(1)} \in V^{(1)}$ that are consistent with x, and define

$$
Q := \left(\min_{x \in f^{-1}(1)} \{n_x\}\right)^{-1},\tag{5.122}
$$

so that for all $x \in f^{-1}(1)$, there exists at least Q^{-1} vertices in $V^{(1)}$ that are consistent with x. By [Fact 5.4,](#page-24-2) when $rd \le o(m)$ — a condition satisfied since we only need to consider $d \le \log_2(m)$ and use the r specified in [Section 5.4.5](#page-45-0) — it follows that $Q^{-1} \ge \Omega(|V^{(1)}|)$.

Let Cst(x) denote a fixed but arbitrary set of Q^{-1} vertices $R^{(1)} \in V^{(1)}$ that are consistent with x. For each $R^{(1)} \in \text{Cst}(x)$, $\text{Act}(x, R^{(1)})$ is a set of active arcs consisting of the following arcs:

- In stage I.1 and I.2, all arcs along the unique shortest length r path from source \emptyset to $R^{(1)}$.
- In stage II.1, all arcs from $R^{(1)}$ that loads a_1 into $R^{(1)}$. Notice that there are $2^{2d} 1$ such arcs, one for each choice of $\varnothing \neq \Gamma \subset [2d]$.
- In stage II.2, for each vertex $R^{(2)} \in V^{(2)}$ that has an incoming active arc from $\text{Act}(x, R^{(1)})$, the arc that loads a_2 into $R^{(2)}$.
- In stage II.3, for each vertex $R^{(3)} \in V^{(3)}$ that has an incoming active arc from Act $(x, R^{(1)})$, the arc that loads a_3 into $R^{(3)}$.

Notice that in stage II.2 and II.3, for each vertex that has an incoming active arc, there is only one outgoing active arc, so the total number of active arcs in stage II.2 and II.3 is $2(2^{2d} - 1)$.

Lastly, all active arcs of x is defined as

$$
Act(x) := \dot{\bigcup}_{R^{(1)} \in \text{Cst}(x)} Act(x, R^{(1)}).
$$
\n(5.123)

5.4.4 Matrices for the adversary bound

For any vertex R in the learning graph, an *assignment on* R refers to a function $\alpha_R : \bigcup R \to {\binom{[n]}{2}}$ $\binom{n}{2} \cup \{*\}$ such that:

(i) for all $j \in \bigcup_{\Gamma} R_1(\Gamma)$,

$$
\alpha_R(j) \neq *, \tag{5.124}
$$

(ii) for all $\gamma \in [2d]$ and $j \in R_2(\gamma)$,

$$
\alpha_R(j) \in \{*\} \cup \left\{ e \in \binom{[n]}{2} \mid \exists k \in \bigcup_{\Gamma \ni \gamma} R_1(\Gamma) \text{ s.t. } e \text{ is incident to } \alpha_R(k) \right\}.
$$
 (5.125)

We say an input $z \in \binom{[n]}{2}$ $\binom{n}{2}^m$ satisfies assignment α_R if, for all $t \in \bigcup R$,

$$
\alpha_R(t) = \begin{cases} z_t, & \text{if } \exists \emptyset \neq \Gamma \subseteq [2d], \text{ s.t. } t \in R_1(\Gamma), \\ z_t, & \text{if } t \in R_2(\gamma) \text{ and } \exists k \in \bigcup_{\Gamma \ni \gamma} R_1(\Gamma), \text{ s.t. } z_t \text{ is incident to } z_k, *, & \text{otherwise.} \end{cases} \tag{5.126}
$$

For each vertex R in the learning graph, we write α_R^x for the unique assignment on R that x satisfies. We say arc $A_i^{R,S}$ ${}_{j}^{R,S}$ uncovers j if $\alpha_{S}^{x}(j) \neq *$. We say inputs $x, y \in \binom{[n]}{2}$ $\binom{n}{2}$ $\stackrel{\frown}{n}$ agree on R if they satisfy $\alpha_R^x = \alpha_P^y$ $_{R}^{y}$; we also say they agree on a subset of $\bigcup R$ if the restriction of α_R^x and α_R^y R^y to that subset equal.

Define

$$
X_j^{R,S} := \sum_{\alpha_R} Y_{\alpha_R},\tag{5.127}
$$

where the sum is over all assignments α_R on R.

For each arc $A_i^{R,S}$ $_{j}^{R,S}$ in stage I.1, define $Y_{\alpha_R} := Q\psi_{\alpha_R}\psi_{\alpha_R}^{\dagger}$, where ψ_{α_R} is a real vector indexed by $\binom{[n]}{2}$ $\binom{n}{2}$ ^m and defined entry-wise by

$$
\psi_{\alpha_R}[z] := \begin{cases}\n1/\sqrt{w}, & \text{if } f(z) = 1, \ z \text{ satisfies } \alpha_R, \text{ and } A_j^{R,S} \in \text{Act}(z) \\
\sqrt{w}, & \text{if } f(z) = 0, \text{ and } z \text{ satisfies } \alpha_R, \\
0, & \text{otherwise.} \n\end{cases}
$$
\n(5.128)

Here, w is a positive real number that will be specified later. With the above definition, we see that $X_i^{R,S}$ j consists of blocks of the form:

$$
\begin{array}{c|c}\n & x & y \\
\hline\nx & Q/w & Q \\
\hline\ny & Q & Qw\n\end{array} \tag{5.129}
$$

where $x \in f^{-1}(1)$, $y \in f^{-1}(0)$, $A_j^{R,S} \in \text{Act}(x)$, and both x and y agree on R.

For arcs $A_i^{R,S}$ ^{*n*},^{*s*} in stage I.2, define $Y_{\alpha_R} := Q(\psi_{\alpha_R} \psi_{\alpha_R}^{\dagger} + \phi_{\alpha_R} \phi_{\alpha_R}^{\dagger})$ where ψ_{α_R} and ϕ_{α_R} are real vectors indexed by $\binom{[n]}{2}$ $\binom{n}{2}^m$ and defined entry-wise by

$$
\psi_{\alpha_R}[z] := \begin{cases} 1/\sqrt{w_1}, & \text{if } f(z) = 1, \, \alpha_S^z(j) \neq *, \, z \text{ satisfies } \alpha_R, \text{ and } A_j^{R,S} \in \text{Act}(z), \\ \sqrt{w_1}, & \text{if } f(z) = 0, \text{ and } z \text{ satisfies } \alpha_R, \\ 0, & \text{otherwise}; \end{cases} \tag{5.130}
$$

and

$$
\phi_{\alpha_R}[z] \coloneqq \begin{cases} 1/\sqrt{w_0}, & \text{if } f(z) = 1, \ \alpha_S^z(j) = *, \ z \text{ satisfies } \alpha_R, \text{ and } A_j^{R,S} \in \text{Act}(z), \\ \sqrt{w_0}, & \text{if } f(z) = 0, \ \alpha_S^z(j) \neq *, \text{ and } z \text{ satisfies } \alpha_R, \\ 0, & \text{otherwise.} \end{cases} \tag{5.131}
$$

Here, w_0 and w_1 are positive real numbers that will be specified later. With the above definition, we see that $X_i^{R,S}$ $j^{R,S}$ consists of blocks of the form:

where $x \in f^{-1}(1)$, $y \in f^{-1}(0)$, $A_j^{R,S} \in \text{Act}(x)$, and both x and y agree on R.

For arcs $A_i^{R,S}$ $_{j}^{R,S}$ in stage II.s for $s \in [3]$, there exists a unique $\varnothing \neq \Gamma \subseteq [2d]$ such that $S \in V^{(s+1)}(\Gamma)$. Define $Y_{\alpha_R} \coloneqq Q \psi_{\alpha_R} \psi_{\alpha_R}^{\dagger}$ where

$$
\psi_{\alpha_R}[z] := \begin{cases}\n1/\sqrt{w}, & \text{if } f(z) = 1, z \text{ satisfies } \alpha_R, \text{ and } A_j^{R,S} \in \text{Act}(z), \\
(-1)^{1+|\Gamma|}\sqrt{w}, & \text{if } f(z) = 0, \text{ and } z \text{ satisfies } \alpha_R, \\
0, & \text{otherwise.} \n\end{cases}
$$
\n(5.133)

 $X_i^{R,S}$ $j^{R,S}$ consists of blocks of the form:

$$
\begin{array}{c|c|c}\n & x & y \\
\hline\nx & Q/w & (-1)^{1+|\Gamma|}Q \\
\hline\ny & (-1)^{1+|\Gamma|}Q & Qw\n\end{array} \tag{5.134}
$$

where $x \in f^{-1}(1)$, $y \in f^{-1}(0)$, $A_j^{R,S} \in \text{Act}(x)$, and both x and y agree on R.

5.4.5 Complexity

We show $Q(\text{Triangle}_{m,d}) = O(2^{(10/7)d}m^{5/7}d^{2/7})$ by computing [Eq. \(5.105\).](#page-41-0) Define W as the maximum number of wedges in any input. Since the graph has maximum degree d , each edge in the graph contributes to at most $2(d-1)$ wedges, we get $W \leq O(md)$.

- (i) For stage I.1, we set the weight $w = 1$ for all arcs in this stage. There are $r_1(2^{2d} 1)|V^{(1)}|$ arcs in this stage. By [Eq. \(5.129\),](#page-44-0) each of them contributes at most $Qw + Q/w = 2Q$ to the complexity, so the complexity of this stage is $O(r_1(2^{2d}-1)|V^{(1)}|2Q) = O(2^{2d}r_1)$.
- (ii) For stage I.2, there are $2dr_2|V^{(1)}|$ arcs in this stage. For any input z, we need to bound the number of arcs that can uncover an element, so we get a refined bound on the contribution from [Eq. \(5.132\).](#page-44-1) Suppose such an arc in this stage is on the shortest length-r path from source \varnothing to $R^{(1)} \in V^{(1)}$, and is uncovering j in $R_2^{(1)}$ $2^{(1)}(\gamma)$ for some $\gamma \in [2d]$, then, z_j must form a wedge with z_i for some $i \in R_1^{(1)}$ $1^{(1)}(\Gamma)$ and $\gamma \in \Gamma \subseteq [2d]$. The number of such ordered tuples (i, j) is at most $2W$, and the number of vertices in stage I.2 that loads j in its outgoing arc and has loaded i in stage I.1 is

$$
\binom{m-2}{r_1-1, \underbrace{r_1, \cdots, r_1}_{2^{2d}-2}, r_2-1, \underbrace{r_2, \cdots, r_2}_{2d-1}} = O\left(\frac{r_1r_2}{m^2} |V^{(1)}|\right).
$$
\n(5.135)

Therefore, for a negative input, by [Eq. \(5.132\),](#page-44-1) stage I.2's contribution to the complexity is

$$
O\left(Qw_0W\frac{r_1r_2}{m^2}\Big|V^{(1)}\Big| + Qw_12dr_2\Big|V^{(1)}\Big|\right) = O\left(\frac{r_1r_2d}{m}w_0 + r_2dw_1\right);
$$
\n(5.136)

and for a positive input, by [Eq. \(5.132\),](#page-44-1) stage I.2's contribution to the complexity is

$$
O\left(\frac{Q}{w_1}W\frac{r_1r_2}{m^2}\Big|V^{(1)}\Big| + \frac{Q}{w_0}2dr_2\Big|V^{(1)}\Big|\right) = O\left(\frac{r_1r_2d}{mw_1} + \frac{r_2d}{w_0}\right). \tag{5.137}
$$

If we set $w_0 = \sqrt{m/r_1}$, and $w_1 = \sqrt{r_1/m}$, the total contribution to the complexity is $O(r_2d\sqrt{r_1/m})$. (iii) For stage II,

■ The total number of arcs in stage II.1 is

$$
(m-r)(2^{2d}-1)\left|V^{(1)}\right| \le O\left(2^{2d}m\left|V^{(1)}\right|\right).
$$
\n(5.138)

■ The total number of arcs in stage II.2 is

$$
(m-r-1)\left|V^{(2)}\right| = \frac{(m-r-1)(m-r)(2^{2d}-1)\left|V^{(1)}\right|}{r_1+1},\tag{5.139}
$$

since each vertex in $V^{(1)}$ has $(m-r)(2^{2d}-1)$ outgoing arcs into $V^{(2)}$, and each vertex in $V^{(2)}$ has $r_1 + 1$ incoming arcs from $V^{(1)}$. There are $O(2^{2d}m^2|V^{(1)}|/r_1)$ arcs in this stage.

■ The total number of arcs in stage II.3 is

$$
(m-r-2)\left|V^{(3)}\right| = \frac{(m-r-2)(m-r-1)(m-r)(2^{2d}-1)\left|V^{(1)}\right|}{(r_1+1)(r_2+1)},\tag{5.140}
$$

since each vertex in $V^{(2)}$ has $m-r-1$ outgoing arcs into $V^{(3)}$, and each vertex in $V^{(3)}$ has r_2+1 incoming arcs from $V^{(2)}$. There are $\tilde{O}(2^{2d}m^3|V^{(1)}|/(r_1r_2))$ arcs in this stage.

For any negative input, by Eq. (5.134) , each arc contributes Qw to the complexity, so the total contribution is

$$
O\left(\frac{2^{2d}m^3|V^{(1)}|}{r_1r_2}Qw\right) = O\left(\frac{2^{2d}m^3w}{r_1r_2}\right) \tag{5.141}
$$

For any positive input, there are exactly $3Q^{-1}(2^{2d}-1)$ active arcs in stage II, by [Eq. \(5.134\),](#page-45-1) each of them contributes Q/w to the complexity, so the total contribution is

$$
\frac{3(2^{2d}-1)}{Q} \cdot \frac{Q}{w} = \frac{3(2^{2d}-1)}{w} \le O\left(\frac{2^{2d}}{w}\right).
$$
\n(5.142)

To balance the contribution from negative inputs and positive inputs, we can set $w = \sqrt{r_1 r_2/m^3}$ so that the total contribution in stage II is

$$
O\left(2^{2d}\sqrt{\frac{m^3}{r_1r_2}}\right). \tag{5.143}
$$

The total complexity of all stages is

$$
O\left(2^{2d}r_1 + r_2d\sqrt{\frac{r_1}{m}} + 2^{2d}\sqrt{\frac{m^3}{r_1r_2}}\right).
$$
\n(5.144)

To balance the summands, we set $r_1 = \lceil m^{5/7} d^{2/7} / 2^{(4/7)d} \rceil$ and $r_2 = \lceil 2^{(12/7)d} m^{6/7} / d^{6/7} \rceil$, which leads to a complexity of $O(2^{(10/7)d}m^{5/7}d^{2/7})$.

5.4.6 Feasibility

Fix $x \in f^{-1}(1)$ and $y \in f^{-1}(0)$, to prove [Eq. \(5.106\)](#page-41-1) holds, it is equivalent to show

$$
\sum_{A_j^{R,S} \in \text{Act}(x) \colon x_j \neq y_j} X_j^{R,S}[x, y] = 1. \tag{5.145}
$$

Since $\text{Act}(x) = \dot{\bigcup}_{R^{(1)} \in \text{Cst}(x)} \text{Act}(x, R^{(1)}),$ it suffices to prove

$$
\sum_{A_j^{R,S} \in \text{Act}(x, R^{(1)}) \colon x_j \neq y_j} X_j^{R,S}[x, y] = \frac{1}{|\text{Cst}(x)|} = Q,\tag{5.146}
$$

for each $R^{(1)} \in \mathrm{Cst}(x)$.

Recall $\mathcal{C}(x) = \{a_1, a_2, a_3\}$ is a specific certificate for x we choose. Let $t_1, t_2, \dots, t_r \in [m]$ be the order of elements in $\bigcup R^{(1)}$ get loaded in $R^{(1)}$. Let $T_i, i \in [r] \cup \{0\}$, be the vertex that has loaded i elements on the unique shortest length-r path from source \varnothing to $R^{(1)}$ (i.e. $|\bigcup T_i| = i$, $T_0 = \varnothing$ and $T_r = R^{(1)}$), so that arcs from \emptyset to $R^{(1)}$ is in the form of $A_{t_i}^{T_{i-1},T_i} \in \text{Act}(x,R^{(1)})$. Depending on if x and y agree on $R^{(1)}$,

If x and y disagree on $R^{(1)}$, there exists $i^* \in [r]$ such that x and y disagree on T_i if and only if $i \geq i^*$. This follows from the fact that, for any arc $A_i^{R,S}$ $j_j^{R,S}$ in stage I, the following holds by [Eq. \(5.126\):](#page-44-2)

$$
\forall k \in \bigcup R, \alpha_S^x(k) = \alpha_R^x(k) \text{ and } \alpha_S^y(k) = \alpha_R^y(k), \tag{5.147}
$$

so if x and y disagree on R, then they disagree on S .

We show that $X^{T_{i^*-1},T_{i^*}}_{t_{i^*}}[x,y] = Q$, and for any $A_j^{R,S} \in \text{Act}(x,R^{(1)})\setminus\{A^{T_{i^*-1},T_{i^*}}_{t_{i^*}}\}$, either $x_j = y_j$ or $X^{R,S}_i$ $j^{n, s}[x, y] = 0.$

− When we load t_{i^*} into T_{i^*-1} , x and y agree on T_{i^*-1} but not T_{i^*} . Since x and y agree on T_{i^*-1} , for any $i \in \bigcup T_{i^*-1}$, we have

$$
\alpha_{T_{i^*}}^x(i) = \alpha_{T_{i^*-1}}^x(i) = \alpha_{T_{i^*-1}}^y(i) = \alpha_{T_{i^*}}^y(i),\tag{5.148}
$$

so we must have $\alpha_{T_{i^*}}^x(t_{i^*}) \neq \alpha_{T}^y$ $T_{i*}^y(t_{i*})$ as x and y disagree on T_{i*} . Therefore, $x_{t_{i*}} \neq y_{t_{i*}}$ as otherwise $\alpha^x_{T_{i^*}}(t_{i^*}) = \alpha^x_{T_{i^*}}(t_{i^*})$. Hence, the term $X^{T_{i^*-1},T_{i^*}}_{t_{i^*}}[x,y]$ is included in the summation in [Eq. \(5.146\).](#page-46-0) From [Eq. \(5.129\)](#page-44-0) and [Eq. \(5.132\),](#page-44-1)

$$
X_{t_{i^*}}^{T_{i^*-1}, T_{i^*}}[x, y] = Q,\t\t(5.149)
$$

since $\alpha^x_{T_{i^*}}(t_{i^*}) \neq \alpha^y_T$ $T_{i^*}(t_{i^*})$, so they cannot be both $*$.

- − When we load t_i into T_{i-1} such that $i \in [i^*-1]$, x and y agree on both T_{i-1} and T_i . Then, either $x_{t_i} = \alpha_{T_i}^x(t_i) = \alpha_T^y$ $y_{T_i}^y(t_i) = y_i \neq *, \text{ or } \alpha_{T_i}^x(t_i) = \alpha_T^y$ $T_i(t_i) = *$, and by [Eq. \(5.132\),](#page-44-1) $X_{t_i}^{T_{i-1},T_i}[x,y] =$ 0. Therefore, arc $A_{t_i}^{T_{i-1},T_i}$ does not contribute to [Eq. \(5.146\).](#page-46-0)
- $-$ Any other arc $A_j^{R,S}$ ∈ Act $(x, R^{(1)})$ is either in stage I and of the form $A_{t_i}^{T_{i-1}, T_i}$ for some $i > i^*$, $i \in [r]$, or the arc is in stage II. If the arc is in stage I, then x and y disagree on R. By Eq. (5.129) and Eq. (5.132) , $X_i^{R,S}$ $j^{n, s}[x, y] = 0.$

If $A_i^{R,S}$ $j^{R,S}$ is in stage II, it suffices to show that if x and y disagree on R, then they also disagree on S. If this holds, a short induction establishes that x and y disagree on R for all $A_j^{R,S}$ \in Act $(x, R^{(1)})$ in stage II. By [Eq. \(5.134\),](#page-45-1) it then follows that $X_i^{R,S}$ $j^{n, s}[x, y] = 0.$ By the definition of consistency, after loading $j \in \mathcal{C}(x)$,

$$
\forall i \in \bigcup R, \alpha_S^x(i) = \alpha_R^x(i). \tag{5.150}
$$

Since x and y disagree on R, after loading j, we must establish that

$$
\forall i \in \bigcup R, \alpha_S^y(i) = \alpha_S^x(i) = \alpha_R^x(i). \tag{5.151}
$$

However, if the above equation holds, there exists $k \in \bigcup R$ such that α_I^y $\alpha_R^y(k) \neq \alpha_R^x(k) = \alpha_S^y$ $S^y(k)$ because x and y disagree on R. Since $\{\alpha_p^y\}$ $R^y(R)$, α_S^y $\{g(k)\}\subseteq \{*, y_k\},\$ it follows that α^y_k $R_R^y(k) = *$ and $y_k = \alpha_S^y$ $S(S(k) = \alpha_S^x(k) = x_k$. Consequently, we must have $k \in \bigcup S_2$ and $j \in \bigcup S_1$, meaning $j = a_1$, and $y_k = x_k$ is incident to $y_{a_1} = x_{a_1}$. This contradicts the definition of consistency. Therefore, x and y must disagree on S.

If x and y agree on $R^{(1)}$, we first show the contribution from arcs in Act $(x, R^{(1)})$ in stage I to [Eq. \(5.146\)](#page-46-0) is 0. When we load t_i into T_{i-1} for any $i \in [r]$, x and y agree on both T_{i-1} and T_i . An identical argument as in a previous case when $i \in [i^* - 1]$ shows arc $A_{t_i}^{T_{i-1}, T_i}$ does not contribute to [Eq. \(5.146\).](#page-46-0)

For stage II, let k be the smallest number in [3] that $x_{a_k} \neq y_{a_k}$. k must exist because y is a negative instance. For active arcs in stage II.k' such that $k' < k$, those arcs are loading $a_{k'}$ but $x_{a_{k'}} = y_{a_{k'}}$, so those arcs' X are not included in the summation in Eq. (5.146) .

For arcs in stage II.k' such that $k' > k$, x and y disagree on the vertices before loading $a_{k'}$. This is because a_k gets uncovered in x, so y_{a_k} must be equal to x_{a_k} for x and y to agree, which leads a contradiction. Then, by Eq. (5.134) , those active arcs' contribution to Eq. (5.146) is also 0.

Next, we show the contribution from arcs in Act $(x, R^{(1)})$ in stage II.k to [Eq. \(5.146\)](#page-46-0) is exactly Q.

– If $k = 1$, there are $2^{2d} - 1$ arcs in $\text{Act}(x, R^{(1)})$ in stage II.1. They are of the form $A_{a_1}^{R^{(1)}, R_{\Gamma}^{(2)}}$ where $R_{\Gamma}^{(2)} \in V^{(2)}(\Gamma)$, one for each $\varnothing \neq \Gamma \subseteq [2d]$. Since x and y agree on $R^{(1)}$ (and $x_{a_1} \neq y_{a_1}$), [Eq. \(5.134\)](#page-45-1) gives $X_{a_1}^{R^{(1)}, R_\Gamma^{(2)}}[x, y] = (-1)^{1+|\Gamma|}Q$. Therefore, the total contribution of stage II.1 to [Eq. \(5.146\)](#page-46-0) is

$$
\sum_{\varnothing \neq \Gamma \subseteq [2d]} (-1)^{1+|\Gamma|} Q = Q. \tag{5.152}
$$

– If $k = 2$, there are $2^{2d} - 1$ arcs in Act $(x, R^{(1)})$ in stage II.2. They are of the form $A_{a_2}^{R_1^{(2)}, R_\Gamma^{(3)}}$ where $R_{\Gamma}^{(2)} \in V^{(2)}(\Gamma)$ and $R_{\Gamma}^{(3)} \in V^{(3)}(\Gamma)$, one for each $\varnothing \neq \Gamma \subseteq [2d]$. In this case, x and y may not agree on $R_{\Gamma}^{(2)}$ Γ ⁽²⁾ due to what are known as *faults*. We say that an index $i \in \bigcup_R (R_{\Gamma}^{(2)})$ $(\sum_{i=1}^{N} a_i)$ is faulty if y_i is incident to y_{a_1} . For $\gamma \in [2d]$, we say the subset $(R_{\Gamma}^{(2)}$ $\binom{2}{\Gamma}$ ₂(γ) is *faulty* if $(R_{\Gamma}^{(2)})$ $(\binom{2}{r})_2(\gamma)$ contains a faulty index. Let I denote the set of all $\gamma \in [2d]$ such that $(R_{\Gamma}^{(2)}$ $\int_{\Gamma}^{(2)}(1)}(1)$ is not faulty.

We now show

$$
x, y \text{ agree on } R_{\Gamma}^{(2)} \iff \varnothing \neq \Gamma \subseteq I.
$$
 (5.153)

(i) " \implies ": consider the contrapositive. Let $\gamma \in \Gamma - I$. Suppose $j \in (R_{\Gamma}^{(2)})$ $\int_{\Gamma}^{(2)}$)₂(γ) is faulty. Then by our definition of assignment, α_x^y $y_{R_{\Gamma}^{(2)}}(j) = y_j$. On the other hand, $\alpha_{\overline{R}}^x$ $R^{(2)}_\Gamma$ (j) cannot

be equal to y_j since y_j is incident to $y_{a_1} = x_{a_1}$ and $R^{(1)}$ is consistent with x.

(ii) " \iff ": note that x and y certainly agree on $\bigcup (R_{\Gamma}^{(2)})$ (\mathcal{L}^2) ₁ since $x_{a_1} = y_{a_1}$ and x and y agreed on $\bigcup R_1^{(1)}$ ⁽¹⁾. But since $\Gamma \subseteq I$, and x and y agreed on $\bigcup R_2^{(1)}$ $_2^{(1)}$ the definition of I implies that x and y must agree on $\bigcup_R (R_\Gamma^{(2)})$ $\binom{2}{\Gamma}$ as well.

Since $\Delta(\mathcal{G}(y)) \leq d$, y_{a_1} can be part of at most $2(d-1)$ wedges. Therefore, the set I defined above has size $|I| \geq 2d - 2(d-1) = 2 > 0$. Therefore, by [Eq. \(5.134\),](#page-45-1) the total contribution of stage II.2 to Eq. (5.146) is

$$
\sum_{\varnothing \neq \Gamma \subseteq I} X_{a_2}^{R_{\Gamma}^{(2)}, R_{\Gamma}^{(3)}}[x, y] = \sum_{\varnothing \neq \Gamma \subseteq I} (-1)^{1+|\Gamma|} Q = Q.
$$
 (5.154)

- If $k = 3$, arcs in Act $(x, R^{(1)})$ in stage II.3 are of the form $A_{a_3}^{R_{\Gamma}^{(3)}, R_{\Gamma}^{(4)}}$ where $R_{\Gamma}^{(3)} \in V^{(3)}(\Gamma)$ and $R_{\Gamma}^{(4)} \in V^{(4)}(\Gamma)$, one for each $\varnothing \neq \Gamma \subseteq [2d]$.

For each arc $A_{a_2}^{R_\Gamma^{(2)},R_\Gamma^{(3)}}$ in stage II.2, since $x_{a_2}=y_{a_2}$, and loading a_2 does not uncover additional elements by the definition [Eq. \(5.126\),](#page-44-2) it follows that x and y agree on $R_{\Gamma}^{(3)}$ $\int_{\Gamma}^{(0)}$ if and only if x and y agree on $R_{\Gamma}^{(2)}$ $\Gamma^{(2)}$.

Therefore, using the same I as defined in the previous case, the total contribution of stage II.3 to [Eq. \(5.146\)](#page-46-0) is

$$
\sum_{\varnothing \neq \Gamma \subseteq I} X_{a_3}^{R_{\Gamma}^{(3)}, R_{\Gamma}^{(4)}}[x, y] = \sum_{\varnothing \neq \Gamma \subseteq I} (-1)^{1+|\Gamma|} Q = Q. \tag{5.155}
$$

Acknowledgments

We thank François Le Gall for suggesting the study of quantum algorithms in the edge list model. We thank Yassine Hamoudi for helpful discussions on [\[HM23\]](#page-51-7) and for simplifying our original proof of the Mirroring Lemma [\(Lemma 5.17\)](#page-30-0).

References

- [ACLT10] Andris Ambainis, Andrew M. Childs, François Le Gall, and Seiichiro Tani. The quantum query complexity of certification. Quantum Info. Comput., 10(3):181-189, 2010. [doi:10.26421/QIC10.3-4-1](https://doi.org/10.26421/QIC10.3-4-1). $[pp. 5, 22]$ $[pp. 5, 22]$ $[pp. 5, 22]$ $[pp. 5, 22]$
- [AF15] Noga Alon and Jacob Fox. Easily testable graph properties. Combinatorics, Probability and Computing, 24(4):646–657, 2015. [doi:10.1017/S0963548314000765](https://doi.org/10.1017/S0963548314000765). [p. [2\]](#page-1-1)
- [Amb00] Andris Ambainis. Quantum lower bounds by quantum arguments. In Proceedings of the 32nd ACM Symposium on Theory of Computing (STOC), pages 636–643, 2000. [doi:10.1145/335305.335394](https://doi.org/10.1145/335305.335394). [pp. [8,](#page-7-4) [26\]](#page-25-2)
- [Amb07] Andris Ambainis. Quantum walk algorithm for element distinctness. SIAM Journal on Computing, 37(1):210-239, 2007. [doi:10.1137/S0097539705447311](https://doi.org/10.1137/S0097539705447311). [p. [23\]](#page-22-3)
- [AS04] Scott Aaronson and Yaoyun Shi. Quantum lower bounds for the collision and the element distinctness problems. Journal of the ACM, 51(4):595–605, 2004. [doi:10.1145/1008731.1008735](https://doi.org/10.1145/1008731.1008735). [pp. [6,](#page-5-4) [23\]](#page-22-3)
- [ASdW06] Andris Ambainis, Robert Spalek, and Ronald de Wolf. A new quantum lower bound method,: with applications to direct product theorems and time-space tradeoffs. In *Proceed*ings of the 38th ACM Symposium on Theory of Computing (STOC), pages 618–633, 2006. [doi:10.1145/1132516.1132604](https://doi.org/10.1145/1132516.1132604). [p. [8\]](#page-7-4)
- [BBBV97] Charles H. Bennett, Ethan Bernstein, Gilles Brassard, and Umesh Vazirani. Strengths and weaknesses of quantum computing. *SIAM Journal on Computing*, 26(5):1510–1523, 1997. [doi:10.1137/S0097539796300933](https://doi.org/10.1137/S0097539796300933). [p. [30\]](#page-29-2)
- [BBC+01] Robert Beals, Harry Buhrman, Richard Cleve, Michele Mosca, and Ronald de Wolf. Quantum lower bounds by polynomials. Journal of the ACM, 48(4):778–797, 2001. [doi:10.1145/502090.502097](https://doi.org/10.1145/502090.502097). [pp. [6,](#page-5-4) [12,](#page-11-2) [22,](#page-21-1) [27\]](#page-26-5)
- [BCG⁺20] Shalev Ben-David, Andrew M. Childs, András Gilyén, William Kretschmer, Supartha Podder, and Daochen Wang. Symmetries, graph properties, and quantum speedups. In Proceedings of the 61st IEEE Symposium on Foundations of Computer Science (FOCS), pages 649–660, 2020. [doi:10.1109/FOCS46700.2020.00066](https://doi.org/10.1109/FOCS46700.2020.00066). [pp. [2,](#page-1-1) [7,](#page-6-2) [17,](#page-16-6) [18\]](#page-17-2)
- [BCJ⁺13] Aleksandrs Belovs, Andrew M. Childs, Stacey Jeffery, Robin Kothari, and Frédéric Magniez. Time-efficient quantum walks for 3-distinctness. In Proceedings of the $40th$ International Colloquium on Automata, Languages, and Programming (ICALP), pages 105–122, 2013. [doi:10.1007/978-3-642-39206-1_10](https://doi.org/10.1007/978-3-642-39206-1_10). [p. [2\]](#page-1-1)
- [Bel12a] Aleksandrs Belovs. Span programs for functions with constant-sized 1-certificates. In Proceedings of the 44th ACM Symposium on Theory of Computing (STOC), pages 77–84, 2012. [doi:10.1145/2213977.2213985](https://doi.org/10.1145/2213977.2213985). [pp. [6,](#page-5-4) [41\]](#page-40-4)
- [Bel12b] Aleksandrs Belovs. Learning-graph-based quantum algorithm for k-distinctness. In Proceedings of the 53rd IEEE Symposium on Foundations of Computer Science (FOCS), pages 207–216, 2012. [doi:10.1109/FOCS.2012.18](https://doi.org/10.1109/FOCS.2012.18). [pp. [1,](#page-0-0) [2,](#page-1-1) [3,](#page-2-5) [6,](#page-5-4) [9,](#page-8-3) [41,](#page-40-4) [42\]](#page-41-2)
- [BHK+19] Gilles Brassard, Peter Høyer, Kassem Kalach, Marc Kaplan, Sophie Laplante, and Louis Salvail. Key establishment à la Merkle in a quantum world. Journal of Cryptology, $32(3):601-$ 634, 2019. [doi:10.1007/s00145-019-09317-z](https://doi.org/10.1007/s00145-019-09317-z). [pp. [6,](#page-5-4) [11,](#page-10-3) [12\]](#page-11-2)
- [BKS01] Ziv Bar-Yossef, Ravi Kumar, and D. Sivakumar. Sampling algorithms: lower bounds and applications. In Proceedings of the 33rd ACM Symposium on Theory of Computing (STOC), pages 266–275, 2001. [doi:10.1145/380752.380810](https://doi.org/10.1145/380752.380810). [pp. [6,](#page-5-4) [14\]](#page-13-2)
- [BKT18] Mark Bun, Robin Kothari, and Justin Thaler. The polynomial method strikes back: tight quantum query bounds via dual polynomials. In *Proceedings of the 50th ACM Symposium on* Theory of Computing (STOC), pages 297–310, 2018. [doi:10.1145/3188745.3188784](https://doi.org/10.1145/3188745.3188784). [p. [6\]](#page-5-4)
- [BKW24] Paul Beame, Niels Kornerup, and Michael Whitmeyer. Quantum time-space tradeoffs for matrix problems. In Proceedings of the 56th ACM Symposium on Theory of Computing (STOC), pages 596–607, 2024. [doi:10.1145/3618260.3649700](https://doi.org/10.1145/3618260.3649700). [pp. [5,](#page-4-2) [27\]](#page-26-5)
- [BR14] Aleksandrs Belovs and Ansis Rosmanis. On the power of non-adaptive learning graphs. computational complexity, 23(2):323–354, 2014. [doi:10.1007/s00037-014-0084-1](https://doi.org/10.1007/s00037-014-0084-1). [pp. [2,](#page-1-1) [5\]](#page-4-2)
- [BS13] Aleksandrs Belovs and Robert Spalek. Adversary lower bound for the k-sum problem. In Proceedings of the 4th Innovations in Theoretical Computer Science Conference (ITCS), pages 323–328, 2013. [doi:10.1145/2422436.2422474](https://doi.org/10.1145/2422436.2422474). [p. [2\]](#page-1-1)
- [CE05] Andrew Childs and Jason Eisenberg. Quantum algorithms for subset finding. Quantum Information and Computation, 5(7), 2005. [doi:10.26421/qic5.7](https://doi.org/10.26421/qic5.7). [p. [23\]](#page-22-3)
- [CFHL21] Kai-Min Chung, Serge Fehr, Yu-Hsuan Huang, and Tai-Ning Liao. On the compressed-oracle technique, and post-quantum security of proofs of sequential work. In Advances in Cryptology $-$ EUROCRYPT 2021, pages 598–629, 2021. [doi:10.1007/978-3-030-77886-6_21](https://doi.org/10.1007/978-3-030-77886-6_21). [p. [5\]](#page-4-2)
- [Cha19] Andr´e Chailloux. A Note on the Quantum Query Complexity of Permutation Symmetric Functions. In Proceedings of the 10th Innovations in Theoretical Computer Science Conference (ITCS), volume 124, pages 19:1–19:7, 2019. [doi:10.4230/LIPIcs.ITCS.2019.19](https://doi.org/10.4230/LIPIcs.ITCS.2019.19). [pp. [7,](#page-6-2) [15,](#page-14-3) [17\]](#page-16-6)
- [Fre77] David Freedman. A remark on the difference between sampling with and without replacement. Journal of the American Statistical Association, 72(359):681–681, 1977. [doi:10.1080/01621459.1977.10480637](https://doi.org/10.1080/01621459.1977.10480637). $[p. 20]$ $[p. 20]$
- [GGR98] Oded Goldreich, Shari Goldwasser, and Dana Ron. Property testing and its connection to learning and approximation. *Journal of the ACM*, 45(4):653–750, 1998. [doi:10.1145/285055.285060](https://doi.org/10.1145/285055.285060). [p. [2\]](#page-1-1)
- [Gol10] Oded Goldreich. Introduction to testing graph properties. In Property Testing: Current Research and Surveys, pages 105–141, 2010. [doi:10.1007/978-3-642-16367-8_7](https://doi.org/10.1007/978-3-642-16367-8_7). [p. [2\]](#page-1-1)
- [HLS07] Peter Hoyer, Troy Lee, and Robert Spalek. Negative weights make adversaries stronger. In Proceedings of the 39th ACM Symposium on Theory of Computing (STOC), pages 526–535, 2007. [doi:10.1145/1250790.1250867](https://doi.org/10.1145/1250790.1250867). [pp. [8,](#page-7-4) [42\]](#page-41-2)
- [HM23] Yassine Hamoudi and Frédéric Magniez. Quantum time–space tradeoff for finding multiple collision pairs. ACM Transactions on Computation Theory, $15(1-2):1-22$, 2023. [doi:10.1145/3589986](https://doi.org/10.1145/3589986). [pp. [5,](#page-4-2) [26,](#page-25-2) [27,](#page-26-5) [28,](#page-27-0) [40,](#page-39-3) [50\]](#page-49-11)
- [JKM13] Stacey Jeffery, Robin Kothari, and Frédéric Magniez. Nested quantum walks with quantum data structures. In Proceedings of the $24th$ ACM-SIAM Symposium on Discrete Algorithms (SODA), pages 1474–1485, 2013. [doi:10.1137/1.9781611973105.106](https://doi.org/10.1137/1.9781611973105.106). [p. [2\]](#page-1-1)
- [JZ23] Stacey Jeffery and Sebastian Zur. Multidimensional quantum walks. In Proceedings of the 55th ACM Symposium on Theory of Computing (STOC), pages 1125–1130, 2023. [doi:10.1145/3564246.3585158](https://doi.org/10.1145/3564246.3585158). [p. [9\]](#page-8-3)
- [Kal22] J. Kallaugher. A quantum advantage for a natural streaming problem. In Proceedings of the 62nd IEEE Symposium on Foundations of Computer Science (FOCS), pages 897–908, 2022. [doi:10.1109/FOCS52979.2021.00091](https://doi.org/10.1109/FOCS52979.2021.00091). [p. [2\]](#page-1-1)
- [Kar94] David R. Karger. Random sampling in cut, flow, and network design problems. In Proceedings of the 26th ACM Symposium on Theory of Computing (STOC), pages 648–657, 1994. [doi:10.1145/195058.195422](https://doi.org/10.1145/195058.195422). [p. [2\]](#page-1-1)
- [KY14] Mitsuru Kusumoto and Yuichi Yoshida. Testing forest-isomorphism in the adjacency list model. In Automata, Languages, and Programming, pages 763–774, 2014. [doi:10.1007/978-3-662-43948-7_63](https://doi.org/10.1007/978-3-662-43948-7_63). [p. [2\]](#page-1-1)
- [Le 14] François Le Gall. Improved quantum algorithm for triangle finding via combinatorial arguments. In Proceedings of the 55th IEEE Symposium on Foundations of Computer Science (FOCS), pages 216–225, 2014. [doi:10.1109/FOCS.2014.31](https://doi.org/10.1109/FOCS.2014.31). [p. [2\]](#page-1-1)
- [LMR+11] Troy Lee, Rajat Mittal, Ben W. Reichardt, Robert Spalek, and Mario Szegedy. Quantum query complexity of state conversion. In Proceedings of the 52nd IEEE Symposium on Foundations of Computer Science (FOCS), pages 344–353, 2011. [doi:10.1109/FOCS.2011.75](https://doi.org/10.1109/FOCS.2011.75). [p. [42\]](#page-41-2)
- [LMS13] Troy Lee, Frédéric Magniez, and Miklos Santha. Improved quantum query algorithms for triangle finding and associativity testing. In Proceedings of the 24th $ACM-SIAM$ Symposium on Discrete Algorithms (SODA), pages 1486–1502, 2013. [doi:10.1007/s00453-015-0084-9](https://doi.org/10.1007/s00453-015-0084-9). [p. [2\]](#page-1-1)
- [LR13] Troy Lee and Jérémie Roland. A strong direct product theorem for quantum query complexity. computational complexity, 22(2):429–462, 2013. [doi:10.1007/s00037-013-0066-8](https://doi.org/10.1007/s00037-013-0066-8). [p. [8\]](#page-7-4)
- [LZ19] Qipeng Liu and Mark Zhandry. On finding quantum multi-collisions. In Advances in Cryptol $ogy - EUROCRYPT 2019$, pages 189-218, 2019. [doi:10.1007/978-3-030-17659-4_7](https://doi.org/10.1007/978-3-030-17659-4_7). [pp. [2,](#page-1-1) [5,](#page-4-2) [8\]](#page-7-4)
- [MH24] Fermi Ma and Hsin-Yuan Huang. How to construct random unitaries, 2024. [arXiv:2410.10116](https://arxiv.org/abs/2410.10116). [p. [5\]](#page-4-2)
- [MMW24] Christian Majenz, Giulio Malavolta, and Michael Walter. Permutation superposition oracles for quantum query lower bounds, 2024 . $arXiv:2407.09655$. [p. [5\]](#page-4-2)
- [MNRS11] Frédéric Magniez, Ashwin Nayak, Jérémie Roland, and Miklos Santha. Search via quantum walk. *SIAM Journal on Computing*, 40(1):142–164, 2011. [doi:10.1137/090745854](https://doi.org/10.1137/090745854). [pp. [15,](#page-14-3) [16\]](#page-15-1)
- [MSS07] Frédéric Magniez, Miklos Santha, and Mario Szegedy. Quantum algorithms for the triangle problem. SIAM Journal on Computing, 37(2):413–424, 2007. [doi:10.1137/050643684](https://doi.org/10.1137/050643684). [p. [2\]](#page-1-1)
- [MTZ20] Nikhil S. Mande, Justin Thaler, and Shuchen Zhu. Improved Approximate Degree Bounds for k-Distinctness. In Proceedings of the 15th Conference on the Theory of Quantum Computation, Communication and Cryptography (TQC), volume 158, pages 2:1–2:22, 2020. $doi:10.4230/LIPIcs.TQC.2020.2.$ $doi:10.4230/LIPIcs.TQC.2020.2.$ $[p. 6]$ $[p. 6]$
- [MU17] Michael Mitzenmacher and Eli Upfal. Probability and Computing: Randomization and Probabilistic Techniques in Algorithms and Data Analysis. Cambridge University Press, 2nd edition, 2017. [p. [31\]](#page-30-3)
- [Rei09] Ben W. Reichardt. Span programs and quantum query complexity: The general adversary bound is nearly tight for every Boolean function. In Proceedings of the 50th IEEE Symposium on Foundations of Computer Science (FOCS), pages 544–551, 2009. [doi:10.1109/FOCS.2009.55](https://doi.org/10.1109/FOCS.2009.55). $[p, 9, 42]$ $[p, 9, 42]$ $[p, 9, 42]$ $[p, 9, 42]$
- [Rei11] Ben W. Reichardt. Reflections for quantum query algorithms. In Proceedings of the 22nd ACM-SIAM Symposium on Discrete Algorithms (SODA), pages 560–569, 2011. [doi:10.5555/2133036.2133080](https://doi.org/10.5555/2133036.2133080). [pp. [5,](#page-4-2) [9,](#page-8-3) [22\]](#page-21-1)
- [RS98] Martin Raab and Angelika Steger. "Balls into bins" — a simple and tight analysis. In International Workshop on Randomization and Approximation Techniques in Computer Science, pages 159–170. Springer, 1998. [pp. [13,](#page-12-3) [24\]](#page-23-4)
- [vAGN24] Joran van Apeldoorn, Sander Gribling, and Harold Nieuwboer. Basic quantum subroutines: finding multiple marked elements and summing numbers. Quantum, 8:1284, 2024. [doi:10.22331/q-2024-03-14-1284](https://doi.org/10.22331/q-2024-03-14-1284). [pp. [12,](#page-11-2) [13,](#page-12-3) [22\]](#page-21-1)
- [Wag02] David Wagner. A generalized birthday problem. In Advances in Cryptology – CRYPTO 2002, pages 288–304, 2002. [doi:10.1007/3-540-45708-9_19](https://doi.org/10.1007/3-540-45708-9_19). [p. [2\]](#page-1-1)
- [Zha19] Mark Zhandry. How to record quantum queries, and applications to quantum indifferentiability. In Advances in Cryptology — CRYPTO 2019: 39th Annual International Cryptology Conference, pages 239–268, 2019. [doi:10.1007/978-3-030-26951-7_9](https://doi.org/10.1007/978-3-030-26951-7_9). [pp. [1,](#page-0-0) [5,](#page-4-2) [8,](#page-7-4) [26\]](#page-25-2)