

UNIFIED STOCHASTIC FRAMEWORK FOR NEURAL NETWORK QUANTIZATION AND PRUNING

HAOYU ZHANG^{1†} AND RAYAN SAAB²

ABSTRACT. Quantization and pruning are two essential techniques for compressing neural networks, yet they are often treated independently, with limited theoretical analysis connecting them. This paper introduces a unified framework for post-training quantization and pruning using stochastic path-following algorithms. Our approach builds on the Stochastic Path Following Quantization (SPFQ) method, extending its applicability to pruning and low-bit quantization, including challenging 1-bit regimes. By incorporating a scaling parameter and generalizing the stochastic operator, the proposed method achieves robust error correction and yields rigorous theoretical error bounds for both quantization and pruning as well as their combination.

1. INTRODUCTION

Modern deep neural networks (DNNs) have achieved significant success but require substantial memory and computation due to their large number of parameters. Model compression techniques, including quantization, pruning, knowledge distillation, and low-rank decomposition, mitigate these issues. We focus on quantization and pruning.

Quantization replaces the weights in a DNN with elements from a finite set, allowing them to be represented with fewer bits and consequently not only compresses the network but also accelerates inference. DNN quantization methods include quantization-aware training and post-training quantization. Quantization-aware training (e.g., [3, 4, 7, 14, 26, 28, 33]) modifies standard neural network training to account for weight quantization, often requiring retraining and hyperparameter tuning, which can be computationally expensive, especially if one needs to repeat the process for multiple bit depths. In contrast, post-training quantization (e.g., [5, 6, 10, 13, 18, 20, 21, 27, 30, 32]) operates on pre-trained models, using relatively little data to replace floating-point parameters with quantized counterparts. Post-training quantization methods are generally much less demanding than the original training process, allowing for easy re-quantization of a base model at various bit depths.

Meanwhile, pruning techniques aim to set as many of a DNN’s weights to zero as possible. Pruning techniques can also be categorized into those that operate pre-training, during training, or post-training. Pre-training pruning methods (e.g., [15, 23, 24, 25]) prune the model before training and often rely significantly on good initialization. Methods that prune during training (e.g., [8, 12, 11, 17, 31]) attempt to identify and remove unnecessary parameters during training, and can increase overall training cost. Post-training pruning methods

¹ Department of Mathematics, University of California-San Diego, La Jolla, California 92093, USA. (haz053@ucsd.edu).

² Department of Mathematics, Halıcıoğlu Data Science Institute, University of California-San Diego, La Jolla, California 92093, USA. (rsaab@ucsd.edu).

[†] Corresponding author.

(e.g., [2, 9, 16, 19]) prune already trained models and fine-tune them if necessary. Similar to their quantization counterparts, post-training methods allow models to be pruned to various sparsity levels, enabling implementation on platforms with different memory, power, and computational resources.

In this theory-focused paper, we extend post-training algorithms for quantization and pruning by building on the work presented in [29], which introduced Stochastic Path Following Quantization (SPFQ). SPFQ is a stochastic error-correcting algorithm that sequentially quantizes a neuron’s weights to minimize accumulated error, with an accompanying theoretical upper bound on the error that scales as $\sqrt{\log(N)}$, where N is the dimension of the neuron. This scaling compares favorably to the \sqrt{N} scaling associated with other techniques. However, SPFQ’s focus on minimizing accumulated error without constraints limits its applicability to extremely low-bit quantizers, as it cannot guarantee rigorous error bounds in such cases. Additionally, while SPFQ includes an analysis for finite-bit quantization when the number of bits is not too small, its framework does not readily extend to pruning.

We provide some important generalizations to SPFQ and its analysis. We show that one can replace the quantization operator in SPFQ by any stochastic operator that satisfies certain properties, and we introduce a scaling parameter into the argument of this operator. Loosely speaking, this scaling parameter controls the amount of error correction in the algorithm, and is critical to allowing us to handle the low-bit (even 1-bit) quantization regime. These modifications make our approach versatile for various tasks, including pruning and the afore-mentioned quantization, and we prove rigorous error bounds for these applications.

This paper is organized as follows. Section 2 introduces notation. In Section 3, we present our algorithm and the intuition behind it. Section 4 states and proves the main theoretical result. Sections 5, 6, and 7 discuss applications—quantization, pruning, and combined quantization with pruning—and apply the main theorem to derive error bounds, demonstrating the algorithm’s versatility for low-bit quantization and sparsification.

2. NOTATION

We define an L -layer perceptron $\Phi : \mathbb{R}^{N_0} \rightarrow \mathbb{R}^{N_L}$ via its action

$$\Phi(x) = \rho^{(L)} \circ A^{(L)} \circ \rho^{(L-1)} \circ A^{(L-1)} \circ \dots \circ \rho^{(1)} \circ A^{(1)}(x),$$

where $\rho^{(i)} : \mathbb{R}^{N_i} \rightarrow \mathbb{R}^{N_i}$ is an entry-wise nonlinear activation function, and $A^{(i)} : \mathbb{R}^{N_{i-1}} \rightarrow \mathbb{R}^{N_i}$ is an affine map defined by $A^{(i)}(x) = W^{(i)\top}x + b^{(i)}$. Here, $W^{(i)} \in \mathbb{R}^{N_{i-1} \times N_i}$ is the *weight* matrix and $b^{(i)} \in \mathbb{R}^{N_i}$ is the *bias* vector in the i -th layer. It is worth noting that $W^{(i)\top}x + b^{(i)}$ can be rewritten as $(W^{(i)\top} \ b^{(i)})(x^\top \ 1)^\top$. Therefore, we can absorb the bias vector into the weight matrix by extending the data x to $(x^\top \ 1)^\top$. As a result, we assume throughout this paper without loss of generality, that the bias vector $b^{(i)} = 0$. Additionally, we assume $\max_{i,j,k} |W_{jk}^{(i)}| \leq K$.

We denote by $\Phi^{(i)}$ the composition of the first i layers of the model, so that

$$\Phi^{(i)}(x) = \rho^{(i)} \circ A^{(i)} \circ \rho^{(i-1)} \circ A^{(i-1)} \circ \dots \circ \rho^{(1)} \circ A^{(1)}(x)$$

represents the *activations* at layer i . Similarly, we denote the compressed model by $\tilde{\Phi}$, and its first i layers by $\tilde{\Phi}^{(i)}$. $X \in \mathbb{R}^{m \times N_0}$ represents the data used for compressing the network, where each row is a data point in \mathbb{R}^{N_0} . We extend notation so $\Phi^{(i)}(X) \in \mathbb{R}^{m \times N_i}$ denotes the application of $\Phi^{(i)}$ to each row of X .

For a matrix $M \in \mathbb{R}^{m \times n}$, $M_j \in \mathbb{R}^m$ represents the j -th column of M , M_{ij} represents the (i, j) -th entry of M , and for a vector $v \in \mathbb{R}^n$, $v_j \in \mathbb{R}$ represents the j -th entry of v . If A and B are two symmetric matrices, $A \preceq B$ means $B - A$ is positive semi-definite. For vectors $x \in \mathbb{R}^d$, we require the ℓ_2 and ℓ_∞ norms $\|x\|_\infty := \max_i |x_i|$, $\|x\| := \sqrt{\sum_i x_i^2}$. Meanwhile for matrices X , $\|X\|_F = \sqrt{\sum_{i,j} X_{ij}^2}$ denotes its Frobenius norm. We use $\mathcal{N}(\mu, \Sigma)$ to denote a Gaussian random vector with mean μ and covariance matrix Σ , and $U[a, b]$ to denote a random variable drawn uniformly on the interval $[a, b]$. Finally, P_v , where v is a vector, denotes the orthogonal projection onto $\text{span}(v)$.

3. STOCHASTIC PATH FOLLOWING COMPRESSION

We focus on the L -layer perceptron¹ Φ defined above. The aim is to compress the weights of Φ through quantization or pruning to obtain a network $\tilde{\Phi}$ with $\Phi(X) \approx \tilde{\Phi}(X)$. We accomplish this via Algorithm 1 below which we now briefly explain.

Algorithm 1 STOCHASTIC PATH FOLLOWING COMPRESSION($\mathcal{T}, \theta, C, \Phi, X$)

Parameters: Stochastic operator \mathcal{T} , failure threshold $\theta > 0$, constant $C > 0$.

Input: L -layer perceptron Φ with weight matrices $W^{(i)} \in \mathbb{R}^{N_{i-1} \times N_i}$, data $X \in \mathbb{R}^{m \times N_0}$.

Output: Compressed neural network $\tilde{\Phi}$.

- 1: **for** $i = 1$ to L **do**
 - 2: Set $X^{(i-1)} = \Phi^{(i-1)}(X) \in \mathbb{R}^{m \times N_{i-1}}$.
 - 3: Set $\tilde{X}^{(i-1)} = \tilde{\Phi}^{(i-1)}(X) \in \mathbb{R}^{m \times N_{i-1}}$.
 - 4: **repeat**
 - 5: Choose a column $w \in \mathbb{R}^{N_{i-1}}$ of $W^{(i)}$.
 - 6: Run Algorithm 2 to obtain ‘‘compressed’’ weights q :

$$q = \text{COMPRESSION}(\mathcal{T}, \theta, C, w, X, \tilde{X}).$$
 - 7: **until** All columns of $W^{(i)}$ are compressed into $Q^{(i)}$.
 - 8: Set: $\tilde{\Phi}^{(i)}(\cdot) = \rho^{(i)} \circ \tilde{A}^{(i)} \circ \rho^{(i-1)} \circ \dots \circ \rho^{(1)} \circ \tilde{A}^{(1)}(\cdot)$, where $\tilde{A}^{(i)}(x) = Q^{(i)\top} x$.
 - 9: **end for**
-

Algorithm 1 uses m data points in \mathbb{R}^{N_0} represented by $X \in \mathbb{R}^{m \times N_0}$ to guide the compression. The basic idea is to perform the compression one layer at a time, starting with the first. Thus, at layer i , we have access to $X^{(i-1)} := \Phi^{(i-1)}(X)$ and $\tilde{X}^{(i-1)} := \tilde{\Phi}^{(i-1)}(X)$, both in $\mathbb{R}^{m \times N_{i-1}}$, and the goal is to compress $W^{(i)} \in \mathbb{R}^{N_{i-1} \times N_i}$ into $Q^{(i)} \in \mathbb{R}^{N_{i-1} \times N_i}$ such that $X^{(i-1)} W^{(i)} \approx \tilde{X}^{(i-1)} Q^{(i)}$. To accomplish this we use Algorithm 2 to independently, and possibly in parallel, replace each column (neuron) $w \in \mathbb{R}^{N_{i-1}}$ of $W^{(i)}$, entry by entry, with a new neuron q such that $X^{(i-1)} w \approx \tilde{X}^{(i-1)} q$. In Algorithm 2, to ensure $X^{(i-1)} w \approx \tilde{X}^{(i-1)} q$, we proceed sequentially by computing, for $t = 1, 2, \dots, N_{i-1}$, the quantized or pruned coefficient q_t that aligns the sums $\sum_{j=1}^t w_j X_j^{(i-1)}$ and $\sum_{j=1}^t q_j \tilde{X}_j^{(i-1)}$. This step forms the core of our method. It balances two competing requirements, namely reducing the error while ensuring

¹Our algorithm and theory are also applicable to convolutional neural networks, but for simplicity we consider only multi-layer perceptrons (see, e.g., [30])

that q_t lies within the quantization alphabet or has a high likelihood of being set to zero, depending on the application.

Denote the accumulated error at step $t - 1$ by $u_{t-1} := \sum_{j=1}^{t-1} w_j X_j^{(i-1)} - \sum_{j=1}^{t-1} q_j \tilde{X}_j^{(i-1)}$. To balance these requirements, we choose q_t such that $\frac{1}{C} \cdot u_{t-1} + w_t X_t^{(i-1)} - q_t \tilde{X}_t^{(i-1)} \approx 0$, where C controls the trade-off between correcting the prior error and only approximating w_t . If we were picking q_t to minimize $\|\frac{1}{C} \cdot u_{t-1} + w_t X_t^{(i-1)} - q_t \tilde{X}_t^{(i-1)}\|$ over \mathbb{R} , in the absence of quantization or sparsity constraints, q_t is best chosen by projecting $\frac{1}{C} \cdot u_{t-1} + w_t X_t^{(i-1)}$ onto $\tilde{X}_t^{(i-1)}$, yielding $q_t = \frac{\langle h_t, \tilde{X}_t^{(i-1)} \rangle}{C \|\tilde{X}_t^{(i-1)}\|^2}$, where $h_t = C w_t X_t^{(i-1)} + u_{t-1}$. However, since our goal is quantization or pruning, we instead set $q_t = \mathcal{T} \left(\frac{\langle h_t, \tilde{X}_t^{(i-1)} \rangle}{C \|\tilde{X}_t^{(i-1)}\|^2} \right)$, where \mathcal{T} is a stochastic operator that promotes sparsity and/or quantizes its argument. Each neuron w can be handled this way in parallel to compress the entire layer.

In the case of quantization, if $\frac{\langle h_t, \tilde{X}_t^{(i-1)} \rangle}{C \|\tilde{X}_t^{(i-1)}\|^2}$ falls outside of the boundaries of the chosen alphabet, the error can become uncontrollable. In [29], where $C = 1$, this is prevented by simply adding more elements to the alphabet. In contrast, in order to work with 1-bit alphabets we allow $C > 1$, set a threshold θ , and terminate our algorithm if $\left| \frac{\langle u_{t-1}, \tilde{X}_t^{(i-1)} \rangle}{C \|\tilde{X}_t^{(i-1)}\|^2} \right| > \theta$. For instance, if $\{-2K, 2K\}$ is the alphabet, then θ is set to K . Meanwhile, for pruning, no such termination is necessary, so θ is set to infinity. In the remainder of this paper, we show that these modifications allow us to control the error with high probability on the stochasticity of the operator \mathcal{T} .

Algorithm 2 COMPRESSION($\mathcal{T}, \theta, C, w, X, \tilde{X}$)

Parameters: Stochastic operator \mathcal{T} , failure threshold $\theta > 0$, constant $C > 0$.

Input: Neuron $w = (w_1, w_2, \dots, w_N)^\top \in \mathbb{R}^N$, data (activations) $X = (X_1, X_2, \dots, X_N) \in \mathbb{R}^{m \times N}$, activations from quantized network $\tilde{X} = (\tilde{X}_1, \tilde{X}_2, \dots, \tilde{X}_N) \in \mathbb{R}^{m \times N}$.

Output: Compressed weights $q = (q_1, \dots, q_N)^\top$.

- 1: Initialize accumulated error $u_0 = 0$.
 - 2: **for** $t = 1$ to N **do**
 - 3: **if** $\left| \frac{\langle u_{t-1}, \tilde{X}_t \rangle}{C \|\tilde{X}_t\|^2} \right| > \theta$ **then**
 - 4: **Algorithm Fails**
 - 5: **return**
 - 6: **end if**
 - 7: Compute $h_t = C w_t X_t + u_{t-1}$
 - 8: Compute $v_t = \frac{\langle h_t, \tilde{X}_t \rangle}{C \|\tilde{X}_t\|^2}$
 - 9: Compute $q_t = \mathcal{T}(v_t)$
 - 10: Update accumulated error: $u_t = u_{t-1} + w_t X_t - q_t \tilde{X}_t$
 - 11: **end for**
-

4. THEORETICAL ANALYSIS

The primary focus of our theoretical analysis of Algorithm 1 is the error analysis for a single layer of the network. Specifically, we aim to bound the error introduced when compressing the weight matrix of a single layer. Consider the first layer of a neural network, characterized by the weight matrix $W = (W_1, W_2, \dots, W_{N_1}) \in \mathbb{R}^{N_0 \times N_1}$, where each W_i represents a neuron (column) of W ². Given the input data $X \in \mathbb{R}^{m \times N_0}$, Algorithm 1 compresses W into $Q = (Q_1, Q_2, \dots, Q_{N_1})$ and the error of this compression is measured in the Frobenius norm,

$$\|XW - XQ\|_F^2 = \sum_{i=1}^{N_1} \|X(W_i - Q_i)\|_2^2.$$

Since this function is separable with respect to Q_1, \dots, Q_{N_1} , Algorithm 1 processes each column W_1, W_2, \dots, W_{N_1} independently to produce Q_1, Q_2, \dots, Q_{N_1} . To simplify notation, we represent a single column by lowercase letters w and q , denoting the uncompressed and compressed versions, respectively. The error analysis for the entire layer thus reduces to bounding $\|X(w - q)\|_2^2$, which corresponds to the error from Algorithm 2. The remainder of this section is dedicated to proving Theorem 4.2, which provides explicit bounds on the accumulated error at each step t . Its proof requires the concept of convex ordering which we will first introduce. Then, we state and prove Theorem 4.2 using a series of technical lemmas, which we also subsequently prove.

4.1. Main Theorem. We now define *convex ordering*, a notion that will allow us to control random vectors generated by our algorithm by replacing them with Gaussian random vectors.

Definition 4.1. Let X, Y be n -dimensional random vectors such that

$$\mathbb{E}f(X) \leq \mathbb{E}f(Y)$$

holds for all convex functions $f : \mathbb{R}^n \rightarrow \mathbb{R}$, provided the expectations exist. Then X is said to be less than Y in the *convex order*, denoted by $X \prec_{cx} Y$.

In order to state and prove our main result on the error associated with Algorithm 2 when $X = \tilde{X}$, we will first introduce an equivalent formulation of our algorithm. Recall that we initialize the accumulated error as $u_0 = 0$ and note that at each step t , we first check a failure condition. If the condition is not met, we compute $h_t = Cw_tX_t + u_{t-1}$. Then we use h_t to compute $v_t = \frac{\langle h_t, X_t \rangle}{C\|X_t\|^2}$ and compute the compressed entry $q_t = \mathcal{T}(v_t)$. Finally, we update the accumulated error $u_t = u_{t-1} + w_tX_t - q_tX_t$ and move on to the next step. Since the algorithm fails when the failure condition is met at any step, we also have to track whether the algorithm fails at some step. Thus, instead of studying u_t directly, we introduce and analyze an auxiliary quantity \tilde{u}_t , which encodes the information about failure. The sequence \tilde{u}_t with $\tilde{u}_1 = u_1$ is recursively defined via

$$\tilde{u}_t = \begin{cases} 0, & \text{if } \left| \frac{\langle \tilde{u}_{t-1}, X_t \rangle}{C\|X_t\|^2} \right| > \theta \text{ for any } i \leq t, \\ \tilde{u}_{t-1} + w_tX_t - q_tX_t, & \text{otherwise.} \end{cases}$$

²One could also consider any arbitrary layer and work with X being either the corresponding activations of the compressed or original network

Above, to compute q_t in the second case, we simply proceed as before with $\tilde{h}_t = Cw_tX_t + \tilde{u}_{t-1}$, $\tilde{v}_t = \frac{\langle \tilde{h}_t, X_t \rangle}{C\|X_t\|^2}$, and let $q_t = \mathcal{T}(\tilde{v}_t)$. Note that with this modification, if the threshold is not exceeded at any step, then Algorithm 2 does not fail. Thus, $u_t = \tilde{u}_t$ for all t and we get the same $q = (q_1, \dots, q_{N_0})$ as produced by the original Algorithm 2. The reverse is also true. As a result, $\mathbb{P}\{\text{Algorithm 2 does not fail and } \|u_N\|_\infty \leq \kappa\} = \mathbb{P}\{|\frac{\langle \tilde{u}_{i-1}, X_i \rangle}{C\|X_i\|^2}| \leq \theta \text{ for all } i \text{ and } \|\tilde{u}_N\|_\infty \leq \kappa\}$. So it suffices to study the latter event for a suitable κ .

Using convex ordering, we can control the probability $\mathbb{P}\{|\frac{\langle \tilde{u}_{i-1}, X_i \rangle}{C\|X_i\|^2}| \leq \theta \text{ for all } i \text{ and } \|\tilde{u}_N\|_\infty \leq \kappa\}$ by showing that \tilde{u}_i is dominated by a Gaussian random vector. This result, stated in the theorem below, allows us to control the errors and probabilities for the quantization and pruning applications in Sections 5, 6, and 7. Here we adapt the proof technique from [1].

Theorem 4.2. *Assume the weight vector satisfies $\|w\|_\infty \leq K$. Further, assume that the operator \mathcal{T} satisfies $\mathbb{E}[\mathcal{T}(v)] = v$ and $|\mathcal{T}(v) - v| \leq M$ for all v with $|v| \leq K + \theta$. Then, by running Algorithm 2 with $w \in \mathbb{R}^{N_0}$ and $X \in \mathbb{R}^{m \times N_0}$, the resulting \tilde{u}_j satisfies*

$$\tilde{u}_j \prec_{\text{cx}} \mathcal{N}(0, \beta_j I), \quad \text{for } 1 \leq j \leq N,$$

where β_j is given by

$$\beta_j = \frac{C\pi M^2}{2} \max_{1 \leq i \leq j} \|X_i\|^2.$$

Proof. First by Lemma 4.4, we deduce $\tilde{u}_j \prec_{\text{cx}} \mathcal{N}(0, \Sigma_j)$, where Σ_j is defined as in Lemma 4.4. Further by Lemma 4.5, we have $\Sigma_j \preceq \beta_j I$. We then apply Lemmas 4.3, c and a to complete the proof. \square

4.2. Technical Lemmas. In this subsection, we present the lemmas used for the proof of Theorem 4.2. We start with a lemma collecting various results on convex ordering, with the proofs in [1, 22].

Lemma 4.3. *The following all hold:*

- a. *If $X \prec_{\text{cx}} Y$ and $Y \prec_{\text{cx}} Z$, then $X \prec_{\text{cx}} Z$.*
- b. *If $X \prec_{\text{cx}} Y$, then for any linear transformation M on \mathbb{R}^n , we have $MX \prec_{\text{cx}} MY$.*
- c. *If A and B are two positive semi-definite matrices and $A \preceq B$, then $\mathcal{N}(0, A) \prec_{\text{cx}} \mathcal{N}(0, B)$.*
- d. *Let X, Y, W , and Z be random vectors and suppose that X and Y live on the same probability space. Let W and Z be independent and suppose that $X \prec_{\text{cx}} W$ and $(Y - X)|X \prec_{\text{cx}} Z$. Then $Y \prec_{\text{cx}} W + Z$.*
- e. *Let X be a real-valued random variable with $\mathbb{E}X = 0$ and $|X| \leq C$. Then $X \prec_{\text{cx}} \mathcal{N}(0, \frac{\pi C^2}{2})$.*
- f. *Let X be a symmetric random vector in \mathbb{R}^n , i.e., X and $-X$ have the same distribution, and let $A \subset \mathbb{R}^n$ be a symmetric set (i.e., $x \in A \Rightarrow -x \in A$). Define X' by*

$$X' = \begin{cases} X, & \text{if } X \in A^c, \\ 0, & \text{otherwise.} \end{cases}$$

Then $X' \prec_{\text{cx}} X$.

- g. *Let X be an n -dimensional random vector such that $X \prec_{\text{cx}} \mathcal{N}(\mu, \sigma^2 I)$, and let $\alpha > 0$. Then*

$$\mathbb{P}(\|X - \mu\|_\infty \leq \alpha) \geq 1 - \sqrt{2}ne^{-\frac{\alpha^2}{4\sigma^2}}.$$

In particular, if $\alpha = 2\sigma\sqrt{\log(\frac{\sqrt{2n}}{\gamma})}$ with $\gamma \in (0, 1]$, we have

$$\mathbb{P}(\|X - \mu\|_\infty \leq 2\sigma\sqrt{\log(\frac{\sqrt{2n}}{\gamma})}) \geq 1 - \gamma.$$

Using Lemma 4.3 allows to deduce the following result on the distribution of \tilde{u}_j . We use a proof technique similar to that in [1].

Lemma 4.4. *Under the same assumptions as in Theorem 4.2, by running Algorithm 2 with $w \in \mathbb{R}^{N_0}$ and $X \in \mathbb{R}^{m \times N_0}$, we obtain \tilde{u}_j such that:*

$$\tilde{u}_j \prec_{cx} \mathcal{N}(0, \Sigma_j) \text{ for } 1 \leq j \leq N,$$

where $\Sigma_0 = 0$ and $\Sigma_j, j \geq 1$ is defined recursively as

$$\Sigma_j = \left(I - \frac{P_{X_j}}{C}\right) \Sigma_{j-1} \left(I - \frac{P_{X_j}}{C}\right) + \frac{\pi M^2}{2} X_j X_j^\top.$$

Proof. We use induction. For $j = 0$, the statement is trivial. Assume the statement is true for $j = t - 1$. Define u'_{t-1} as

$$u'_{t-1} = \begin{cases} \tilde{u}_{t-1}, & \text{if } \left| \frac{\langle \tilde{u}_{t-1}, X_t \rangle}{C \|X_t\|^2} \right| \leq \theta, \\ 0, & \text{otherwise.} \end{cases}$$

The random variable \tilde{u}_{t-1} is symmetric, so $u'_{t-1} \prec_{cx} \tilde{u}_{t-1}$ by Lemma 4.3, f. If $\left| \frac{\langle \tilde{u}_{t-1}, X_t \rangle}{C \|X_t\|^2} \right| \leq \theta$, then the algorithm does not fail and we have

$$\begin{aligned} \tilde{u}_t &= \tilde{u}_{t-1} + w_t X_t - q_t X_t \\ &= \tilde{u}_{t-1} + w_t X_t - \tilde{v}_t X_t + (\tilde{v}_t - q_t) X_t \\ &= \left(I - \frac{P_{X_t}}{C}\right) \tilde{u}_{t-1} + (\tilde{v}_t - \mathcal{T}(\tilde{v}_t)) X_t \end{aligned}$$

due to the definition of \tilde{v}_t and q_t . If $\left| \frac{\langle \tilde{u}_{t-1}, X_t \rangle}{C \|X_t\|^2} \right| > \theta$, then we have $\tilde{u}_t = 0$ by definition. Thus we can express \tilde{u}_t using u'_{t-1} as

$$\tilde{u}_t = \left(I - \frac{P_{X_t}}{C}\right) u'_{t-1} + R_t X_t$$

where

$$R_t = \begin{cases} \tilde{v}_t - \mathcal{T}(\tilde{v}_t), & \text{if } \left| \frac{\langle \tilde{u}_{t-1}, X_t \rangle}{C \|X_t\|^2} \right| \leq \theta, \\ 0, & \text{else.} \end{cases}$$

When $\left| \frac{\langle \tilde{u}_{t-1}, X_t \rangle}{C \|X_t\|^2} \right| \leq \theta$, we have

$$|\tilde{v}_t| = \left| \frac{\langle \tilde{h}_t, X_t \rangle}{C \|X_t\|^2} \right| = \left| w_t + \frac{\langle \tilde{u}_{t-1}, X_t \rangle}{C \|X_t\|^2} \right| \leq K + \theta.$$

By the assumption about \mathcal{T} , R_t is mean zero and $|R_t| \leq M$. We then use e from Lemma 4.3, to deduce $R_t \prec_{cx} \mathcal{N}(0, \frac{\pi M^2}{2})$. Further applying Lemma 4.3, b, we obtain

$$R_t X_t \prec_{cx} \mathcal{N}\left(0, \frac{\pi M^2}{2} X_t X_t^\top\right).$$

Since $u'_{t-1} \prec_{cx} \tilde{u}_{t-1} \prec_{cx} \mathcal{N}(0, \Sigma_{t-1})$, we have

$$\left(I - \frac{P_{X_t}}{C}\right) u'_{t-1} \prec_{cx} \mathcal{N}\left(0, \left(I - \frac{P_{X_t}}{C}\right) \Sigma_{t-1} \left(I - \frac{P_{X_t}}{C}\right)\right).$$

Finally, by Lemma 4.3, d, we conclude

$$\tilde{u}_t \prec_{cx} \mathcal{N}\left(0, \left(I - \frac{P_{X_t}}{C}\right) \Sigma_{t-1} \left(I - \frac{P_{X_t}}{C}\right) + \frac{\pi M^2}{2} X_t X_t^\top\right).$$

This completes the induction. \square

Having controlled our object of interest by a Gaussian random vector with a known covariance matrix, Σ_j defined in Lemma 4.4, we next control the covariance matrix itself.

Lemma 4.5. *Let $C > 1$, then for the above defined Σ_j , we have*

$$\Sigma_j \preceq \beta_j I,$$

where $\beta_0 = 0$ and $\beta_j = \frac{C\pi M^2}{2} \max_{1 \leq i \leq j} \|X_i\|^2$, when $j \geq 1$.

Proof. The base case $j = 0$ is obvious. Let us now proceed by induction. Suppose $\Sigma_{t-1} \preceq \beta_{t-1} I$. Then

$$\begin{aligned} \Sigma_t &= \left(I - \frac{P_{X_t}}{C}\right) \Sigma_{t-1} \left(I - \frac{P_{X_t}}{C}\right) + \frac{\pi M^2 X_t X_t^\top}{2} \\ &\preceq \beta_{t-1} \left(I - \frac{P_{X_t}}{C}\right)^2 + \frac{\pi M^2 X_t X_t^\top}{2} \\ &= \beta_{t-1} \left(I + \frac{1}{C^2} \frac{X_t X_t^\top}{\|X_t\|^2} - 2 \frac{X_t X_t^\top}{C \|X_t\|^2}\right) + \frac{\pi M^2 X_t X_t^\top}{2} \\ &\preceq \beta_t \left(I + \frac{1}{C^2} \frac{X_t X_t^\top}{\|X_t\|^2} - 2 \frac{X_t X_t^\top}{C \|X_t\|^2}\right) + \frac{\pi M^2 X_t X_t^\top}{2} \\ &= \beta_t I + \frac{1}{\|X_t\|^2} \left(\beta_t \left(\frac{1}{C^2} - \frac{2}{C}\right) + \frac{\pi M^2}{2} \|X_t\|^2\right) X_t X_t^\top \\ &= \beta_t I + \frac{\pi M^2}{\|X_t\|^2} \left(\frac{C}{2} \max_{1 \leq i \leq t} \|X_i\|^2 \left(\frac{1-2C}{C^2}\right) + \frac{1}{2} \|X_t\|^2\right) X_t X_t^\top. \end{aligned}$$

Since $C > 1$, we know $1 - 2C < 0$, then we can further deduce

$$\begin{aligned} \Sigma_t &\preceq \beta_t I + \frac{\pi M^2}{\|X_t\|^2} \left(\frac{C}{2} \|X_t\|^2 \left(\frac{1-2C}{C^2}\right) + \frac{1}{2} \|X_t\|^2\right) X_t X_t^\top \\ &= \beta_t I + \left(\frac{\pi M^2}{2} \left(\frac{1}{C} - 2\right) + \frac{\pi M^2}{2}\right) X_t X_t^\top \\ &\preceq \beta_t I + \left(-\frac{\pi M^2}{2} + \frac{\pi M^2}{2}\right) X_t X_t^\top \\ &= \beta_t I. \end{aligned}$$

This completes the induction. \square

5. ONE-BIT QUANTIZATION

We are now ready to first describe the selection of \mathcal{T} and θ for one-bit quantization and then provide the corresponding error analysis for running Algorithm 1 on a single layer of a neural network. Notably, our analysis extends with minimal additional effort to finite multi-bit quantization, a consideration we leave to the interested reader.

5.1. Choice of \mathcal{T} and θ for one-bit quantization. Suppose we want to quantize an L -layer perceptron which has all its weights bounded in absolute value by $K > 0$. We use $\mathcal{A} = \{-2K, 2K\}$ as the alphabet. Then, we can choose \mathcal{T} to be the stochastic scalar quantizer $\mathcal{Q} : \mathbb{R} \rightarrow \mathcal{A}$, with

$$\mathcal{Q}(z) = \begin{cases} 2K & \text{with probability } p_z \text{ if } |z| \leq 2K \\ -2K & \text{with probability } 1 - p_z \text{ if } |z| \leq 2K \\ \text{sgn}(z) \cdot 2K & \text{if } |z| > 2K, \end{cases}$$

where $p_z = \frac{1}{2} + \frac{z}{4K}$. Moreover, we choose the threshold $\theta = K$. It is straightforward to verify that the operator \mathcal{Q} satisfies the assumptions in Theorem 4.2 with $M = 4K$.

5.2. Error analysis. Consider one layer of a neural-network, and denote its action by $\Phi(x) = \rho(W^\top x)$, where $x \in \mathbb{R}^{N_0}$ represents the input data or activations, $W \in \mathbb{R}^{N_0 \times N_1}$ is the weight matrix and ρ is the ReLU activation function, or any (say) 1-Lipschitz function. Now, we use Algorithm 1 to quantize Φ using $X \in \mathbb{R}^{m \times N_0}$, where each row represents a data point. The following holds.

Proposition 1. *Suppose that Q is the quantized weight matrix resulting from Algorithm 1, applied to Φ with the stochastic quantizer \mathcal{Q} . Then, the resulting error satisfies*

$$\max_{i,j} |\rho(XW)_{ij} - \rho(XQ)_{ij}| \leq 4K \sqrt{2\pi Cp \log N_0} \max_{1 \leq i \leq N} \|X_i\|$$

with probability greater than

$$1 - N_1 \sum_{t=1}^{N_0} \sqrt{2} \exp\left(-\frac{C\|X_t\|^2}{32\pi \max_{1 \leq i \leq t-1} \|X_i\|^2}\right) - \sqrt{2}mN_1N_0^{-p},$$

where X_t represents the t -th column of X .

Proof. Let $\kappa := 4K \sqrt{2\pi Cp \log N_0} \max_{1 \leq i \leq N} \|X_i\|$. Consider any neuron (column) $w \in \mathbb{R}^{N_0}$ from W . Let q and \tilde{u}_i be as defined in Subsection 4.1. We run Algorithm 2 independently for each w . We can deduce

$$\begin{aligned} & \mathbb{P}(\text{Algorithm 2 does not fail and } \|u_N\|_\infty \leq \kappa) \\ &= \mathbb{P}\left(\left|\frac{\langle \tilde{u}_{t-1}, X_t \rangle}{C\|X_t\|^2}\right| \leq \theta \text{ for all } t \text{ and } \|\tilde{u}_N\|_\infty \leq \kappa\right) \\ &= 1 - \mathbb{P}\left(\left|\frac{\langle \tilde{u}_{t-1}, X_t \rangle}{C\|X_t\|^2}\right| > K \text{ for some } t \text{ or } \|\tilde{u}_{N_0}\|_\infty > \kappa\right) \\ &\geq 1 - \sum_t \mathbb{P}\left(\left|\frac{\langle \tilde{u}_t, X_{t+1} \rangle}{C\|X_{t+1}\|^2}\right| > K\right) - \mathbb{P}(\|\tilde{u}_{N_0}\|_\infty > \kappa). \end{aligned}$$

By Theorem 4.2 and Lemma 4.3, b, we have

$$\frac{\langle \tilde{u}_t, X_{t+1} \rangle}{C \|X_{t+1}\|^2} \prec_{cx} \mathcal{N}\left(0, \frac{\beta_t}{C^2 \|X_{t+1}\|^2}\right),$$

where $\beta_t = 8C\pi K^2 \max_{1 \leq i \leq t} \|X_i\|^2$. Applying Lemma 4.3, g, we obtain

$$\mathbb{P}\left(\left|\frac{\langle \tilde{u}_t, X_{t+1} \rangle}{C \|X_{t+1}\|^2}\right| > K\right) \leq \sqrt{2} \exp\left(-\frac{C \|X_{t+1}\|^2}{32\pi \max_{1 \leq i \leq t} \|X_i\|^2}\right). \quad (1)$$

For $\mathbb{P}(\|\tilde{u}_{N_0}\|_\infty > \kappa)$, we use the second part of Lemma 4.3, g with $\gamma = \sqrt{2}mN_0^{-p}$ to get

$$\mathbb{P}(\|\tilde{u}_{N_0}\|_\infty > \kappa) \leq \sqrt{2}mN_0^{-p}. \quad (2)$$

Thus using (1) and (2), we obtain

$$\begin{aligned} & \mathbb{P}\{\text{Algorithm 2 does not fail and } \|u_N\|_\infty \leq \kappa\} \\ & \geq 1 - \sum_{t=2}^{N_0} \sqrt{2} \exp\left(-\frac{C \|X_t\|^2}{32\pi \max_{1 \leq i \leq t-1} \|X_i\|^2}\right) - \sqrt{2}mN_0^{-p}. \end{aligned}$$

This implies that

$$\begin{aligned} & \mathbb{P}(\|\rho(Xw) - \rho(Xq)\|_\infty \leq \kappa) \\ & \geq 1 - \sum_{t=2}^{N_0} \sqrt{2} \exp\left(-\frac{C \|X_t\|^2}{32\pi \max_{1 \leq i \leq t-1} \|X_i\|^2}\right) - \sqrt{2}mN_0^{-p}, \end{aligned} \quad (3)$$

by the definition of \tilde{u}_{N_0} and the Lipschitz property of the activation function ρ . Inequality (3) holds true for each column of $W \in \mathbb{R}^{m \times N_1}$. Taking a union bound on the probability completes the proof. \square

Remark 1. This result demonstrates that by choosing C proportional to $\log(N_0N_1)$ the error associated with quantization scales as polylog N_0 , with high probability. This stands in sharp contrast to the error from naive rounding algorithms, where each entry of w is rounded to the nearest element of \mathcal{A} . In the naive case, the error scales as $\sqrt{N_0}$.

Remark 2. For multi-layer analysis, we can use the ‘data alignment’ technique introduced in [29], which would allow establishing an error bound for the entire neural network. We leave this to the reader.

6. PRUNING

In this section, we specify the choice of \mathcal{T} and the threshold θ used for pruning, and we present the error analysis of applying Algorithm 1 to a single layer of a neural network.

6.1. Choice of \mathcal{T} and θ for Pruning. Suppose our layer weights are bounded by $K > 0$ in absolute value. Given $c > 0$, our goal is to encourage weights below cK to be set to 0 while keeping weights above cK unchanged. To achieve this, we set \mathcal{T} to the stochastic operator \mathcal{S} , with

$$\mathcal{S}(v) = \begin{cases} v, & \text{if } |v| > cK, \\ \xi_v, & \text{if } |v| \leq cK. \end{cases} \quad (4)$$

Here ξ_v is a random variable that is set to 0 with probability $1 - \frac{1}{(c+1/2)K}|v|$ and is sampled from $\text{sgn}(v) \cdot U[cK, K]$ with probability $\frac{1}{(c+1/2)K}|v|$. Additionally, we set θ to be ∞ . It is straightforward to verify that the operator \mathcal{S} satisfies the assumptions in Theorem 4.2 with M being K .

6.2. Error analysis. Consider again $\Phi(x) = \rho(W^\top x)$, where $x \in \mathbb{R}^{N_0}$ is the input data or activation, $W \in \mathbb{R}^{N_0 \times N_1}$ is the weight matrix and ρ is the ReLU (or any 1-Lipschitz) activation function. We apply Algorithm 1 to prune Φ using $X \in \mathbb{R}^{m \times N_0}$, where each row represents a data point. We can then deduce the following result.

Proposition 2. *Suppose that Q is the pruned weight matrix resulting from Algorithm 1, applied to Φ with the stochastic pruning operator \mathcal{S} . Then, the resulting error satisfies*

$$\max_{i,j} |\rho(XW)_{ij} - \rho(XQ)_{ij}| \leq K \sqrt{2C\pi p \log N_0} \max_{1 \leq i \leq N_0} \|X_i\|$$

with probability greater than $1 - \sqrt{2}mN_1N_0^{-p}$, where X_t represents the t -th column of X .

Proof. Consider any neuron (column) $w \in \mathbb{R}^{N_0}$ from W . Let q and \tilde{u}_i be defined as in Subsection 4.1. We run Algorithm 2 independently for each w . In this case, $\tilde{u}_i = u_i$ for all i .

It is straightforward to verify that the assumptions in Theorem 4.4 are satisfied with $M = K$. Thus, from Theorem 4.2, we deduce the accumulated error satisfies

$$u_j \prec_{cx} \mathcal{N}(0, \beta_j I) \text{ for } 1 \leq j \leq N_0,$$

where $\beta_j = \frac{C\pi K^2}{2} \max_{1 \leq i \leq j} \|X_i\|^2$.

Applying Lemma 4.3, g with $\gamma = \sqrt{2}mN_0^{-p}$, we obtain

$$\mathbb{P}(\|u_{N_0}\|_\infty > K \sqrt{2C\pi p \log N_0} \max_{1 \leq i \leq N} \|X_i\|) \leq \sqrt{2}mN_0^{-p}.$$

This implies

$$\mathbb{P}(\|\rho(Xw) - \rho(Xq)\|_\infty > K \sqrt{2C\pi p \log N_0} \max_{1 \leq i \leq N} \|X_i\|) \leq \sqrt{2}mN_0^{-p}. \quad (5)$$

The inequality (5) holds for any column w of $W \in \mathbb{R}^{N_0 \times N_1}$. Applying a union bound on the probability completes the proof. \square

7. QUANTIZATION WITH PRUNING

In this section, we show that our methods can handle combinations of operators, and provide the choices for \mathcal{T} and the threshold θ used in quantization with pruning, followed by an error analysis for applying Algorithm 1 to a single layer of a neural network.

7.1. Choice of \mathcal{T} and θ for Quantization with Pruning. Consider an L -layer perceptron with all weights bounded by $K > 0$ in absolute value. Given $c > 0$, and alphabet $\mathcal{A} = \{-2K, 0, 2K\}$, our goal is to encourage weights below cK to be set to 0 and then quantize the weights using \mathcal{A} . Let \mathcal{S} be the operator defined in Section 6. Also, we define the following stochastic rounding operator $\mathcal{Q} : \mathbb{R} \rightarrow \mathcal{A}$

$$\mathcal{Q}(z) = \begin{cases} \lfloor \frac{z}{2K} \rfloor \cdot 2K & \text{with probability } p_z \text{ if } |z| \leq 2K \\ (\lfloor \frac{z}{2K} \rfloor + 1) \cdot 2K & \text{with probability } 1 - p_z \text{ if } |z| \leq 2K \\ \text{sgn}(z) \cdot 2K & \text{if } z > 2K, \end{cases}$$

where $p_z = 1 - \frac{z}{2K} + \lfloor \frac{z}{2K} \rfloor$. We then define $\mathcal{T} = \mathcal{Q} \circ \mathcal{S}$ with the threshold $\theta = K$. As before, it is straightforward to verify that the operator \mathcal{S} satisfies the assumptions of Theorem 4.2 with $M = 2K$.

7.2. Error analysis. With the same notation as before, we can deduce the following result.

Proposition 3. *Suppose that Q is the pruned and quantized weight matrix resulting from Algorithm 1, applied to Φ with the stochastic operator $\mathcal{Q} \circ \mathcal{S}$. Then, the resulting error satisfies*

$$\max_{i,j} |\rho(XW)_{ij} - \rho(XQ)_{ij}| \leq 2K \sqrt{2\pi C p \log N_0} \max_{1 \leq i \leq N} \|X_i\|$$

with probability greater than

$$1 - N_1 \sum_{t=1}^{N_0} \sqrt{2} \exp\left(-\frac{C \|X_t\|^2}{8\pi \max_{1 \leq i \leq t-1} \|X_i\|^2}\right) - \sqrt{2m} N_1 N_0^{-p},$$

where X_t represents the t -th column of X .

The proof of this Proposition is essentially identical to that of Proposition 1, so we omit the details.

ACKNOWLEDGMENT

We gratefully acknowledge partial support by National Science Foundation Grants DMS-2012546 and DMS-2410717.

REFERENCES

- [1] R. Alweiss, Y. P. Liu, and M. Sawhney. Discrepancy minimization via a self-balancing walk. In *Proceedings of the 53rd Annual ACM SIGACT Symposium on Theory of Computing, STOC 2021*, page 14–20, New York, NY, USA, 2021. Association for Computing Machinery.
- [2] S. Ashkboos, M. L. Croci, M. G. do Nascimento, T. Hoefler, and J. Hensman. SliceGPT: Compress large language models by deleting rows and columns. In *The Twelfth International Conference on Learning Representations*, 2024.
- [3] Y. Cai, Z. Yao, Z. Dong, A. Gholami, M. W. Mahoney, and K. Keutzer. Zeroq: A novel zero shot quantization framework. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 13169–13178, 2020.
- [4] J. Choi, Z. Wang, S. Venkataramani, P. I.-J. Chuang, V. Srinivasan, and K. Gopalakrishnan. Pact: Parameterized clipping activation for quantized neural networks. *arXiv preprint arXiv:1805.06085*, 2018.
- [5] Y. Choukroun, E. Kravchik, F. Yang, and P. Kisilev. Low-bit quantization of neural networks for efficient inference. In *2019 IEEE/CVF International Conference on Computer Vision Workshop (ICCVW)*, pages 3009–3018. IEEE, 2019.
- [6] I. Colbert, F. Grob, G. Franco, J. Zhang, and R. Saab. Accumulator-aware post-training quantization. *arXiv preprint arXiv:2409.17092*, 2024.
- [7] M. Courbariaux, Y. Bengio, and J.-P. David. Binaryconnect: Training deep neural networks with binary weights during propagations. *Advances in neural information processing systems*, 28, 2015.
- [8] U. Evci, T. Gale, J. Menick, P. S. Castro, and E. Elsen. Rigging the lottery: Making all tickets winners. In *International conference on machine learning*, pages 2943–2952. PMLR, 2020.
- [9] E. Frantar and D. Alistarh. Sparsegpt: Massive language models can be accurately pruned in one-shot. In *International Conference on Machine Learning*, pages 10323–10337. PMLR, 2023.
- [10] E. Frantar, S. Ashkboos, T. Hoefler, and D. Alistarh. OPTQ: Accurate quantization for generative pre-trained transformers. In *The Eleventh International Conference on Learning Representations*, 2023.

- [11] Y. He, G. Kang, X. Dong, Y. Fu, and Y. Yang. Soft filter pruning for accelerating deep convolutional neural networks. *arXiv preprint arXiv:1808.06866*, 2018.
- [12] Z. Huang and N. Wang. Data-driven sparse structure selection for deep neural networks. In *Proceedings of the European conference on computer vision (ECCV)*, pages 304–320, 2018.
- [13] I. Hubara, Y. Nahshan, Y. Hanani, R. Banner, and D. Soudry. Improving post training neural quantization: Layer-wise calibration and integer programming. *arXiv preprint arXiv:2006.10518*, 2020.
- [14] B. Jacob, S. Kligys, B. Chen, M. Zhu, M. Tang, A. Howard, H. Adam, and D. Kalenichenko. Quantization and training of neural networks for efficient integer-arithmetic-only inference. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2704–2713, 2018.
- [15] N. Lee, T. Ajanthan, and P. H. Torr. Snip: Single-shot network pruning based on connection sensitivity. *arXiv preprint arXiv:1810.02340*, 2018.
- [16] L. Liu, S. Zhang, Z. Kuang, A. Zhou, J.-H. Xue, X. Wang, Y. Chen, W. Yang, Q. Liao, and W. Zhang. Group fisher pruning for practical network compression. In *International Conference on Machine Learning*, pages 7021–7032. PMLR, 2021.
- [17] Z. Liu, H. Mu, X. Zhang, Z. Guo, X. Yang, K.-T. Cheng, and J. Sun. Metapruning: Meta learning for automatic neural network channel pruning. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 3296–3305, 2019.
- [18] E. Lybrand and R. Saab. A greedy algorithm for quantizing neural networks. *Journal of Machine Learning Research*, 22(156):1–38, 2021.
- [19] X. Ma, G. Fang, and X. Wang. Llm-pruner: On the structural pruning of large language models. *Advances in neural information processing systems*, 36:21702–21720, 2023.
- [20] J. Maly and R. Saab. A simple approach for quantizing neural networks. *Applied and Computational Harmonic Analysis*, 66:138–150, 2023.
- [21] M. Nagel, R. A. Amjad, M. Van Baalen, C. Louizos, and T. Blankevoort. Up or down? adaptive rounding for post-training quantization. In *International Conference on Machine Learning*, pages 7197–7206. PMLR, 2020.
- [22] M. Shaked and J. Shanthikumar. *Stochastic Orders*. Springer Series in Statistics. Springer New York, 2007.
- [23] J. Su, Y. Chen, T. Cai, T. Wu, R. Gao, L. Wang, and J. D. Lee. Sanity-checking pruning methods: Random tickets can win the jackpot. *Advances in neural information processing systems*, 33:20390–20401, 2020.
- [24] H. Tanaka, D. Kunin, D. L. Yamins, and S. Ganguli. Pruning neural networks without any data by iteratively conserving synaptic flow. *Advances in neural information processing systems*, 33:6377–6389, 2020.
- [25] C. Wang, G. Zhang, and R. Grosse. Picking winning tickets before training by preserving gradient flow. *arXiv preprint arXiv:2002.07376*, 2020.
- [26] K. Wang, Z. Liu, Y. Lin, J. Lin, and S. Han. Haq: Hardware-aware automated quantization with mixed precision. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 8612–8620, 2019.
- [27] P. Wang, Q. Chen, X. He, and J. Cheng. Towards accurate post-training network quantization via bit-split and stitching. In *International Conference on Machine Learning*, pages 9847–9856. PMLR, 2020.
- [28] D. Zhang, J. Yang, D. Ye, and G. Hua. Lq-nets: Learned quantization for highly accurate and compact deep neural networks. In *Proceedings of the European conference on computer vision (ECCV)*, pages 365–382, 2018.
- [29] J. Zhang and R. Saab. Spfq: A stochastic algorithm and its error analysis for neural network quantization. *arXiv preprint arXiv:2309.10975*, 2023.
- [30] J. Zhang, Y. Zhou, and R. Saab. Post-training quantization for neural networks with provable guarantees. *SIAM Journal on Mathematics of Data Science*, 5(2):373–399, 2023.
- [31] C. Zhao, B. Ni, J. Zhang, Q. Zhao, W. Zhang, and Q. Tian. Variational convolutional neural network pruning. In *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 2775–2784, 2019.

- [32] R. Zhao, Y. Hu, J. Dotzel, C. De Sa, and Z. Zhang. Improving neural network quantization without retraining using outlier channel splitting. In *International conference on machine learning*, pages 7543–7552. PMLR, 2019.
- [33] A. Zhou, A. Yao, Y. Guo, L. Xu, and Y. Chen. Incremental network quantization: Towards lossless cnns with low-precision weights. *arXiv preprint arXiv:1702.03044*, 2017.

(HZ) DEPARTMENT OF MATHEMATICS, UNIVERSITY OF CALIFORNIA-SAN DIEGO, LA JOLLA, CALIFORNIA 92093, USA.

Email address: haz053@ucsd.edu

(RS) DEPARTMENT OF MATHEMATICS, HALICIOĞLU DATA SCIENCE INSTITUTE, UNIVERSITY OF CALIFORNIA-SAN DIEGO, LA JOLLA, CALIFORNIA 92093, USA.

Email address: rsaab@ucsd.edu