Addressing Spatial-Temporal Data Heterogeneity in Federated Continual Learning via Tail Anchor

Hao Yu Southwestren University of Finance and Economics yuhao2033@163.com

Xin Yang Southwestern University of Finance and Economics yangxin@swufe.edu.cn

Le Zhang University of Electronic Science and Technology of China lezhang@uestc.edu.cn

Hanlin Gu WeBank allengu@webank.com

Tianrui Li Southwest Jiaotong University trli@swjtu.edu.cn

Lixin Fan WeBank lixinfan@webank.com

Qiang Yang Hong Kong University of Science and Technology qyang@cse.ust.hk

Abstract

Federated continual learning (FCL) allows each client to continually update its knowledge from task streams, enhancing the applicability of federated learning in real-world scenarios. However, FCL needs to address not only spatial data heterogeneity between clients but also temporal data heterogeneity between tasks. In this paper, empirical experiments demonstrate that such input-level heterogeneity significantly affects the model's internal parameters and outputs, leading to severe spatial-temporal catastrophic forgetting of local and previous knowledge. To this end, we propose Federated Tail Anchor (FedTA) to mix trainable Tail Anchor with the frozen output features to adjust their position in the feature space, thereby overcoming parameter-forgetting and output-forgetting. Moreover, three novel components are also included in FedTA: Input Enhancement for improving the performance of pre-trained models on downstream tasks; Selective Input Knowledge Fusion for fusion of heterogeneous local knowledge on the server side; and Best Global Prototype Selection for finding the best anchor point for each class in the feature space. Extensive experiments demonstrate that FedTA not only outperforms existing FCL methods but also effectively preserves the relative positions of features, remaining unaffected by spatial and temporal changes.

1 Introduction

Data heterogeneity across different clients (Non-IID) is one of the most important challenges in traditional Federated Learning (FL), which greatly hinders the integration of knowledge, leading to the aggregated global model underperforming on local tasks. Many studies have attempted to address this issue and have made some progress [\[1–](#page-9-0)[3\]](#page-9-1). However, they are based on an unrealistic static assumption that the training data of all clients will remain unchanged. Federated Continual Learning (FCL) breaks the static limits by allowing clients to continually accumulate knowledge from task sequences [\[4,](#page-9-2) [5\]](#page-9-3). While FCL expands the applicability of FL in real-world scenarios, it also introduces a more challenging issue, i.e., *spatial-temporal data heterogeneity*. Not only is the data heterogeneous across different clients (spatial), but also the data within different tasks of the same client is heterogeneous (temporal), as shown on the left side of [Fig. 1.](#page-1-0)

Figure 1: Illustration of FCL and the negative impact of spatial-temporal data heterogeneity.

The most direct negative impact of spatial-temporal data heterogeneity is *spatial-temporal catastrophic forgetting* (ST-CF) [\[6\]](#page-10-0), as illustrated on the right side of [Fig. 1.](#page-1-0) Catastrophic Forgetting (CF) is a term from Continual Learning (CL), used to describe the phenomenon where a deep model, after learning multiple tasks, tends to forget the knowledge of previous tasks, resulting in a decrease in accuracy [\[7–](#page-10-1)[9\]](#page-10-2). In FCL, clients face *temporal catastrophic forgetting* as local models would continually learn different tasks over time. Additionally, Non-IID data would lead the aggregated global model to *spatial catastrophic forgetting* (i.e., a decline in the performance of the global model on local test sets). Moreover, *spatial forgetting will interact with temporal forgetting*, as clients use the global model as the base model to learn the next task [\[6\]](#page-10-0).

Spatial-temporal data heterogeneity, which manifests as differences at the *model input*, leads to corresponding changes in *model parameters and outputs*. We believe this is the fundamental cause of forgetting. To be specific, as data changes over time and space, feature extractor and classification head of the model will adapt to the most recent inputs, leading to forgetting of previous and clientspecific knowledge (a detailed analysis of the effect of forgetting is presented in [Sec. 3.2\)](#page-3-0). Fortunately, the use of pre-trained large models can effectively mitigate catastrophic forgetting at the parameter level, as they have sufficient capacity to extract features without changing internal parameters [\[10–](#page-10-3) [12\]](#page-10-4). However, frozen pre-trained models often perform poorly in downstream tasks, making them unsuitable for direct application [\[13\]](#page-10-5). Additionally, they cannot handle forgetting at the output since the classification head is trainable and will fit to the most recent task data.

To fully leverage the power of pre-trained models and address spatial-temporal forgetting from both the parameter and the output aspects, we propose Federated Tail Anchor (FedTA) in this paper. Firstly, each client shares a pre-trained vision Transformer (ViT) [\[14\]](#page-10-6) and a two-stage training strategy is designed to enhance the performance of pre-trained models at the input level and alleviate forgetting at the output level. By adding *tail anchors* to the output features, the features of samples that experience forgetting can quickly return to their original positions in the feature space, thereby avoiding forgetting caused by spatial-temporal changes. After completing local training, the server will separately process the parameters added during input enhancement by the client and the local prototype. On the one hand, we design a *selective input knowledge fusion* mechanism to selectively integrate the knowledge used for input enhancement from different clients; on the other hand, the server will calculate the similarity between local prototypes to form a similarity adjacency matrix. In each iteration, the server will select the local prototype with the lowest average similarity for each class as the global prototype. If the average similarity falls below a threshold, the global prototype will be fixed to prevent forgetting.

Currently, there is little research on spatial-temporal heterogeneity in FCL. To our knowledge, we are the first to attempt to address both temporal and spatial data heterogeneity from the perspective of forgetting. The main contributions can be summarized as:

- 1. Empirical experiments are conducted to show that spatial-temporal data heterogeneity can cause significant changes in the important features extracted by the model for the same samples, and it also causes shifts in their positions within the feature space. This leads to severe ST-CF of previous knowledge and local knowledge. We refer to these two phenomena as "parameter-forgetting" and "output-forgetting", respectively.
- 2. FedTA leverages a pre-trained ViT along with four novel components, aiming to prevent features from shifting their positions in the feature space due to spatial-temporal data heterogeneity. FedTA efficiently overcomes both parameter-forgetting and output-forgetting in FCL caused by spatial-temporal data heterogeneity.

3. Extensive experiments not only demonstrate the state-of-the-art performance of FedTA but also show its remarkable ability to resist spatial-temporal forgetting. Moreover, visualization results indicate that FedTA effectively preserves the relative positions of features, preventing positional shifts due to spatial-temporal variations.

2 Related Work

Spatial data heterogeneity, as known as the Non-IID problem, has attracted much attention [\[15,](#page-10-7) [16,](#page-10-8) [2,](#page-9-4) [17\]](#page-10-9). Existing methods tackle data heterogeneity by either incorporating more effective local training or devising more comprehensive aggregation mechanisms [\[18\]](#page-10-10).

Although these studies have made progress in overcoming spatial data heterogeneity, they are unable to cope with more realistic and dynamic scenarios where each client continually learns on their own task stream.

FCL has indeed greatly enhanced the practical value of FL in real-world scenarios, especially on the edge computing side [\[19,](#page-10-11) [20\]](#page-10-12). It allows each client to rapidly learn knowledge from the current task without forgetting previously knowledge, thus avoiding the need to retrain from scratch and greatly saving computational resources.

Existing FCL papers have achieved promising results. FedWeIT [\[4\]](#page-9-2) decomposes parameters into local, global-based and task-adaptive parts to address both practical and pathological data heterogeneity in FCL. GLFC [\[21\]](#page-10-13) utilizes a class-aware gradient compensation loss and a class-semantic relation distillation loss to mitigate forgetting, and a proxy server to alleviate data heterogeneity. TARGET [\[22\]](#page-10-14) generates synthetic data on the server and adopts knowledge distillation to alleviate forgetting of previous tasks. MFCL [\[5\]](#page-9-3) trains a generative model in a data-free manner on the server and generates synthetic data via this model to mitigate forgetting and preserve data privacy.

In a survey paper on FCL, the authors identified a key issue that existing FCL articles have overlooked: the interaction between spatial heterogeneity and temporal heterogeneity, which leads to a unique challenge: spatial-temporal catastrophic forgetting (ST-CF) [\[6\]](#page-10-0). It means that models not only forget previous knowledge due to continual learning but also forget local knowledge due to federated aggregation. Existing FCL methods do not realize that spatial heterogeneity can exacerbate the temporal forgetting, so when the spatial heterogeneity becomes stronger, the performance is not as expected. Besides, effective FCL methods currently heavily rely on replaying or generating pseudo data to mitigate the effects of spatial-temporal data heterogeneity [\[22,](#page-10-14) [5,](#page-9-3) [23](#page-10-15)[–26\]](#page-11-0). However, this may pose certain privacy risks and incur high computational cost.

Only a very small portion of work has attempted to address data heterogeneity from time and space simultaneously now [\[27,](#page-11-1) [28\]](#page-11-2). However, none of them have delved into how this heterogeneity leads to forgetting, nor have they ensured sufficiently strong spatial-temporal heterogeneity in their experimental settings. To our best knowledge, we are the first to deeply analyze how the heterogeneity of inputs affects model parameters and outputs.

3 Spatial-Temporal Data Heterogeneity

3.1 Problem Definition

The purpose of Spatial-Temporal Data Heterogeneity is to continually integrate knowledge from different clients and different time periods. We extend the traditional FL to FCL with strong spatialtemporal data heterogeneity.

For spatial heterogeneity, given a clients (denoted as $A = \{A_1, A_2, \ldots, A_n\}$), and a central server S, each client's data is composed of private classes C_v^i and public classes C_p , where private classes refer to the class of data that can only be seen by the client itself. We ensure that the data of C_p is non-overlapping between clients. Further, we can set $|C_p| = 0$ to ensure extreme spatial heterogeneity. We run experiments with $|C_p| = 0$ on Imagenet-R dataset.

For temporal heterogeneity, the task sequence of client A_i is denoted as $\mathcal{T}_i = \{T_i^1, T_i^2, \dots, T_i^{n_i}\},$ where n_i represents the total number of tasks on client A_i . Each task consists of the same number but entirely different classes.

During the training of task r , the global model on the server already possesses the knowledge of T_i^1 to T_i^{r-1} from client $\{A_i, 1 \le i \le a\}$. The server S then distributes it back to clients. After personalizing the received global model $\hat{\theta}_g^{r-1}$, the client A_i continually trains it on T_i^r as the initial model to get the new local model θ_i^r . The local model θ_i^r should perform well in classifying classes of $\{\mathcal{T}_1^1 \cup \mathcal{T}_1^{r-1} \dots, \mathcal{T}_i^1 \cup \mathcal{T}_i^r \cup \dots, \mathcal{T}_a^1 \cup \mathcal{T}_a^{r-1}\}.$

3.2 Negative Impact

Spatial-temporal data heterogeneity is a type of heterogeneity in model inputs. Due to the backpropagation mechanism, it would significantly affect the internal parameters of the model and the outputs [\[29\]](#page-11-3). It not only introduces differences between models of different clients but also causes the features output by the same sample to undergo significant changes, thereby causing spatial-temporal forgetting of previous knowledge and local knowledge.

Figure 2: Illustrations of the negative impact of spatial-temporal data heterogeneity on the feature extractor and feature space. [Left Side] illustrates the variation of significant features extracted by the feature extractor for the same input sample, where brighter colors indicate more important features. As spatial-temporal changes occur, the extracted features gradually shift away from "cat", even extracting features near the image edges. [Right Side] depicts the changes in the positions of the features in the feature space after undergoing spatial-temporal transformations for the same batch.

For the feature extractor, as shown on *the left side* of [Fig. 2,](#page-3-1) traditional centralized single-task training can accurately extract beneficial features. However, after continual learning of four other tasks, for the same image, the extracted features are completely unrelated to the cat. Similarly, for FL, the aggregated global model also fails to extract features related to the cat itself. More critically, when the model encounters spatial-temporal data heterogeneity, the crucial features extracted by the feature extraction layer are predominantly concentrated at the edges of the images, which is highly negative to classification task. We term this phenomenon as parameter-forgetting.

For the output (feature space), as shown on *the right side* of [Fig. 2,](#page-3-1) the features extracted by the initial model have clear classification boundaries, and the features of each class are relatively concentrated in the same area. However, after CL or FL, the features extracted for the same samples no longer possess clear boundaries, especially in FCL. Moreover, the positions of the features gradually deviate from their original locations with the spatial-temporal variation, leading to the forgetting of old samples. We term this phenomenon as output-forgetting.

Let's delve even further into the effects of spatial-temporal data heterogeneity. For deep neural networks, changes at the input level directly affect model parameters and corresponding outputs, *thereby causing continual variations of the feature space.* For spatial data heterogeneity, the absence of a common feature space among clients makes it challenging to share heterogeneous knowledge. For temporal data heterogeneity, changes in the feature space over time lead to variations in the locations of features of the same samples. If we can address the issues mentioned above simultaneously, then spatial-temporal catastrophic forgetting will be resolved.

3.3 Motivation

Based on the above analysis, it is evident that spatial-temporal data heterogeneity leads to both parameter-forgetting and output-forgetting. Therefore, to effectively handle spatial-temporal data heterogeneity, methods need to possess the following three capabilities: (1) Ensure that the model extracts nearly identical features for the same sample; (2) Fix the positions of extracted features in the feature space. (3) Allow clients to have a common feature space to better utilize heterogeneous knowledge.

However, due to the training method of deep networks and the large number of parameters involved, parameter updates are uncontrollable, *making it nearly impossible to mitigate parameter-forgetting*. Similarly, since ensuring consistency within the parameters is impossible, it is also hard to guarantee the invariance of outputs in the feature space.

Pre-trained large models have attracted considerable attention due to their powerful representation capabilities. There are already articles attempting to apply pre-trained ViT to the traditional continual learning to overcome forgetting [\[30,](#page-11-4) [31\]](#page-11-5). Inspired by this, we find that freezing the feature extractor of pre-trained ViT can effectively **eliminate parameter-forgetting**. In FCL, clients share the same pretrained model, ensuring that they have the same knowledge/feature space, which makes knowledge transfer between clients easier. Furthermore, by mixing learnable parameters (referred to as "tail anchor" in this paper) with frozen features, we can effectively control their positions in the feature space, thus addressing output-forgetting. The server is responsible for selecting anchor points with the lowest similarity to other classes' anchor points, which will be used as the global anchor point of a class in the feature space. When training the tail anchor on the client side, it will converge towards the anchor point of each class. Therefore, we mitigate the performance degradation caused by parameter-forgetting and output-forgetting induced by spatial-temporal data heterogeneity.

4 Methodology: FedTA

To address the spatial-temporal catastrophic forgetting caused by the heterogeneity of spatial-temporal data heterogeneity, which includes parameter-forgetting in the feature extractor and output-forgetting in the feature space, we propose Federated Tail Anchor (FedTA). Its aim is to leverage a frozen pre-trained model and cross-mix learnable parameters after the output features, ensuring that the position of features in the feature space remains fixed and unaffected by spatial-temporal changes.

Specifically, each client has a ViT pre-trained on ImageNet-21K as the foundation model, with all parameters frozen, *ensuring that the feature space across all clients remains entirely consistent and unchanged*. On the client side, we design two components: *Input Enhancement* to enhance the performance of the pre-trained ViT on the chosen datasets [\(Sec. 4.1\)](#page-4-0) and *Tail Anchor* to control the distance (i.e., similarity) between output features [\(Sec. 4.2\)](#page-5-0). On the server side, we have two modules designed for aggregating knowledge extracted from client inputs and outputs, respectively. *Selective Knowledge Fusion* is used to merge the knowledge applied to inputs accordingly [\(Sec. 4.3\)](#page-6-0). *Best Global Prototype Selection* iteratively chooses the prototype with the lowest average similarity from the class prototypes uploaded by clients as the global prototype. When the average similarity drops below a threshold, it is fixed and becomes an anchor point in the feature space [\(Sec. 4.4\)](#page-6-1).

4.1 Input Enhancement

Inspired by the cognitive processes of humans, knowledge transfer among humans is effective because there is a fundamental shared cognition, enabling the meaningful exchange of knowledge. Therefore, we assign each client with the same pre-trained ViT model as a foundational cognitive system. With ViT's parameters frozen, clients learn common knowledge that operate at the input level. The purpose is to extract knowledge into a common space through the same model and enhance ViT's performance.

Knowledge Base. We devise a knowledge base for storing and selecting the input enhancement parameters. The knowledge base of client i is defined as

$$
\mathcal{KB}_i = \{IE_1, IE_2, \dots, IE_M\},\tag{1}
$$

where M is the base size and IE is a set of learnable parameters. Then, let x and $E = f_e(x)$ be the input and its corresponding embedding feature, respectively. Denoting $\{s_i\}_1^N$ be the indices of N

Figure 3: An overview of FedTA. Local training is a two-stage training process. The first stage involves adding *input enhancement* to the image embeddings to fully utilize ViT (see 1). In the second stage, the extracted features are fixed, and the corresponding *tail anchor* is mixed with them to adjust the similarity between classes by applying contrastive learning with global prototypes (see 2). Then, the local knowledge base of input enhancements and the local prototypes of each class are uploaded to the server, where *selective input knowledge fusion* for the knowledge base (see 4) and *global best prototype selection* for the local prototypes (see 3) are performed, respectively.

sets, then we can modify the embedding feature as follows:

$$
E' = [IE_{s_1}, \dots, IE_{s_N}; E], 1 \le N \le M,
$$
\n(2)

where [;] represents concatenation along the token length dimension. Each set has a corresponding key, denoted as K^{ie} , to facilitate the selection of the parameter set based on the similarity of keys.

Optimization for the input enhancement. Each client has a classification head used for training input enhancement parameters, denoted as H_e^i . At the beginning of training, it is necessary to load the pre-trained model with H_e^i to enable it to perform the classification task, and we denote the model with H_e^i as \mathcal{V}_e^i . Overall, the training loss function is as follows:

$$
\min \mathcal{L}(\mathcal{V}_e^i(E'), y) + \lambda_1 \sum_{\mathcal{K}_s^i} \text{dis}(K_{in}^{ie}, K s_i^{ie}),\tag{3}
$$

where λ_1 is a hyperparameter, K_s^{ie} and K_{in}^{ie} are used to find the best input enhancement parameter sets. The initial term comprises the softmax cross-entropy loss, while the subsequent term serves as a surrogate loss aimed at bringing selected keys closer to their corresponding query features. Cosine similarity is used as the distance function.

4.2 Tail Anchor

Query function. Once the input enhancement parameters are well trained, they will be frozen, including their corresponding keys, until the next task training. The enhanced input embedding would be processed by the frozen ViT again to get the features, denoted as \mathcal{F}_{out} . Then it will be used as the key to find the corresponding tail anchor based on the cosine similarity. We associate each tail anchor with a learnable key, denoted as $\mathcal{TA} = \{(K_1^{ta}, TA_1), (K_2^{ta}, TA_2), \dots, (K_m^{ta}, TA_m)\}\$. TA is a parameter set with the same shape as \mathcal{F}_{out} , so it can easily be mixed with \mathcal{F}_{out} . Then, the query process can be summarized by the following expression:

$$
K_s^{ta} = \underset{\mathcal{K}^{ta}}{\operatorname{argmin}} \operatorname{dis}(\mathcal{F}_{out}, K_i^{ta}),\tag{4}
$$

where \mathcal{K}_s^{ta} denotes the chosen tail anchor's key, and \mathcal{K}^{ta} represents the set of keys for all tail anchors. Notice that this querying method is also used to select the parameter sets for input enhancement.

Optimization for the tail anchor. Once the tail anchor is chosen, it will be frozen and mixed with \mathcal{F}_{out} to form a new feature \mathcal{F}_{TA} . If a client has global prototypes (i.e., not the first round), then

contrastive learning is utilized to unify the features across clients through the following unified representation loss function:

$$
\mathcal{L}_{cons}\left(\mathcal{F}_{TA}\right) = -\log \frac{\exp \left(\mathcal{F}_{TA} \cdot \mathcal{G}^{y}/\tau\right)}{\sum_{y_a \in \mathcal{Y}^t} \exp \left(\mathcal{F}_{TA} \cdot \mathcal{G}^{y_a/\tau}\right)},\tag{5}
$$

where \mathcal{Y}^t represents the global available classes up to task t and \mathcal{G}^y represents the global prototypes of class y. τ denotes the temperature that controls the tolerance of difference between extracted features and the corresponding global prototype. The overall loss function to optimize the tail anchor can be formulated as follows:

$$
\mathcal{L}_{ta} = \mathcal{L}_{CE}(\mathcal{F}_{TA}) + \lambda_2 \mathcal{L}_{cons}(\mathcal{F}_{TA}) + \lambda_3 \operatorname{dis}(\mathcal{F}_{TA}, K_s^{ta}), \tag{6}
$$

where \mathcal{L}_{CE} is the standard cross-entropy loss.

Local prototypes. Once the training process of the tail anchor is done, the tail anchors will be frozen and remain unchanged. The local prototype is obtained by averaging features with tail anchors belonging to the same class, computed through

$$
P_i^y = \frac{1}{|\mathcal{D}_a^y|} \sum_{(x,y) \in \mathcal{D}_a^y} \mathcal{F}_{TA}^x,
$$
\n⁽⁷⁾

where \mathcal{D}_i^y denotes the subset of private dataset of client a of class y. Each client forms a local set of prototypes, which is then uploaded to the server. The server iteratively selects the prototype with the lowest average similarity as the global prototype for that class.

4.3 Selective Input Knowledge Fusion

To fuse the input enhancement knowledge more precisely, we devise a novel *selective Input Knowledge Fusion* mechanism that aggregates knowledge base from different clients through knowledge distillation, enhancing their generalization. To our knowledge, it is a novel approach to distill knowledge of input from different clients.

We follow a common setting, which allows the server to possess a small-scale surrogate dataset, denoted as \mathcal{D}_s . $\{x_s, y_s\}$ are the samples and corresponding labels from \mathcal{D}_s for the distillation process. For the convenience of writing and understanding, we will only consider two input enhancement knowledge base here, denoted as KB_i and KB_j . KB_i is chosen as the student pool. Initially, the input x_p searches for the corresponding input enhancement within \mathcal{KB}_i , and then concatenates to form an embedding E'_i . Similarly, E'_j represents the embedding of the same input but concatenated with the input enhancement from \mathcal{KB}_j . Therefore, the distillation loss can be formulated as follows:

$$
\mathcal{L}_{KD} = \underset{x_s \in \mathcal{D}_s}{\text{MSE}} (\mathcal{V}(E'_i), \mathcal{V}(E'_j)),\tag{8}
$$

where $V(E'_i)$ represents the feature of E'_i though ViT.

4.4 Best Global Prototype Selection

When the server receives local prototype sets from different clients, it reorders them to form a new set P_G according to the class. Specifically, when two clients both have prototypes related to class q, denoted as $P_i^{\bar{q}}$ and P_j^q , they will be adjacent to each other in the reordered prototype set. Then, the server computes the similarity between each pair of sets in the collection, forming an adjacency matrix M . The element of M is computed through:

$$
\mathcal{M}_{ij} = \text{dis}(P_G^i, P_G^j), 0 < i \le j \le |P_G|\,. \tag{9}
$$

Notice that if P_G^i and P_G^j belong to same class, then $\mathcal{M}_{ij} = 1$. In each round, the server selects the prototype with the lowest average similarity with all local prototypes as the global prototype for one class. The selection process of the global prototype \mathcal{G}^y for class y can be expressed as follows:

$$
\mathcal{G}^y = P_g^s = \underset{y_{low} \le i \le y_{high}}{\text{argmin}} \bar{\mathcal{M}}_i = \frac{1}{|P_G|} \sum_{j=1}^{|P_G|} A_{ij},\tag{10}
$$

where y_{low} and y_{high} are the start index and end index of the local prototypes of class y in P_G . P_g^s is the local prototype who has lowest similarity for class y. If the average similarity $\bar{\mathcal{M}}_i$ falls below the threshold Thr during the iteration process, then that prototype is fixed as the global prototype for its class and will not be altered further. As a result, this global prototype will serve as a fixed anchor point for that class in the feature space.

5 Experiments

5.1 Setup

Table 1: Accuracy of the aggregated global model on local test sets with 5 class-incremental tasks.

Continual Setting. To ensure that the impact of spatial-temporal data heterogeneity is adequately reflected, we partition the data as follows: Each client continually learn from a task sequence of 5 tasks, and there are 5 clients in the experimental setting. For *CIFAR-100* [\[37\]](#page-11-11), we allow each client to have access to 15 private classes exclusive to itself, resulting in 25 public classes. Thus, each client has data for a total of 40 classes, with each task consisting of only 8 classes. For *ImageNet-R* [\[38\]](#page-11-12), we exacerbate spatial data heterogeneity by assigning 40 private classes to each client, with no public classes across clients. Similarly, each task consists of 8 classes. Notice that we use the Dirichlet distribution for the public classes to assign data, ensuring there is no overlap between different clients.

Surrogate Data. We follow the common setting [\[39,](#page-11-13) [40\]](#page-11-14) where the server possesses a small surrogate dataset. For CIFAR-100, each class has only 20 samples, while for ImageNet-R, each class has only 5 samples.

5.2 Metrics

To verify whether the method can effectively address the challenges brought by spatial-temporal data heterogeneity, we use two new metrics from [\[6\]](#page-10-0) to evaluate the performance of mitigating forgetting.

Definition 1. (Temporal Knowledge Retention):

$$
KR_t = \frac{1}{a} \sum_{i=1}^{a} \frac{Acc(\theta_i^r; T_i^0)}{Acc(\theta_i^0; T_i^0)},
$$
\n(11)

where $Acc(\theta_i^r; T_i^0)$ denotes the test accuracy of client A_i 's local model at r-th round on the 0-th task and $Acc(\theta_i^0; T_i^0)$ denotes the accuracy of client A_i 's local model at the initial round on the 0-th task. *Definition 2. (Spatial Knowledge Retention)*:

$$
KR_s = \frac{1}{a} \sum_{i=1}^{a} \frac{Acc(\theta_g^r; T_i^r)}{Acc(\theta_i^r; T_i^r)},
$$
\n(12)

where $Acc(\theta_g^r; T_i^r)$ denotes the accuracy of the global model θ_g^r on the current local task T_i^r at client A_i and $Acc(\check{\theta}_i^r; T_i^r)$ denotes the accuracy of the local model θ_i^r on its current local task T_i^r .

5.3 Results & Ablation Study

Figure 4: Knowledge retention on different dataset.

Figure 5: T-SNE for position changes of features corresponding to the same samples after FCL. [Table 1](#page-7-0) illustrates the average accuracy of the aggregated global model on local test sets. The performance of *FedViT* is acceptable because all the parameters of its feature extractor are frozen, and only the classification head is involved in training and aggregation. However, it still experiences a certain degree of forgetting. *FedL2P* and *FedDualP*, which introduce trainable parameters on the input side and within the model, perform very well on the local side, achieving around 90% accuracy. However, as we concluded in [Sec. 3.2,](#page-3-0) almost all trainable parameters are directly affected by the data. Consequently, after aggregation, there is significant forgetting on the local test sets.

Surprisingly, the performance of *TARGET*, *FedLwF* and *MFCL*, the three baseline methods that use replay data to mitigate forgetting, is extremely poor. We speculate that the large size of data $(3\times224\times224)$ results in the low quality of replayed pseudo-samples. Moreover, replay-based methods pose a certain risk of privacy leakage in federated learning, limiting the further application of these methods in real-world scenarios. *GLFC*, the most representative baseline method in FCL, also suffers significant performance degradation when faced with severe spatial-temporal data heterogeneity. However, its performance in [Table 1](#page-7-0) remains the best among the baseline methods.

FedTA demonstrates the superior performance in these two settings, indicating its successful mitigation of the impact of spatial data heterogeneity. Furthermore, ablation studies highlight the effectiveness of the proposed novel components, with the *Tail Anchor* contributing the most to the performance improvement. However, the selective input knowledge fusion at the server-side sometimes falls below the results of direct weighted averaging on ImageNet-R. We believe this is due to insufficient surrogate data, which prevents adequate selective knowledge fusion.

[Fig. 4](#page-8-0) further illustrates the impact of spatial-temporal data heterogeneity on the methods using [Equation 12](#page-8-1) and [Equation 11.](#page-7-1) Only FedTA maintains a high level of temporal and spatial knowledge retention, both at around 98%. While other baseline methods, especially in KR_t , perform extremely poorly. *Tail Anchor* also has been verified to play a significant role in overcoming ST-CF.

Visualization & Sensitivity Analysis. [Fig. 5](#page-8-2) illustrates that FedTA can effectively control the relative distances between features, ensuring that even after spatial-temporal changes, their positions in the feature space do not experience significant shifts.

5.4 Privacy & Efficiency Analysis

Computational Burden. During the local training phase, clients train both the Input Enhancement and Tail Anchor components while the ViT itself remains frozen. Therefore, the number of parameters in these two components, along with the classification head, determines the training overhead of FedTA. The size of Input Enhancement is determined by the number, length and embedding dimension, which are set to 10, 10, and 768 in our setting. The size of the Tail Anchor is set to 100×768 . The total size of keys is $(100+10)\times 768$. Therefore, the total number of trainable parameters amounts to 253,440. Compared to a ResNet-18 with 11,306,804 parameters, FedTA is efficient.

Communication Cost. Each client only needs to submit its own input enhancement and local prototypes to the server, with sizes of 76,800 and 768×2 per class, respectively. Such small communication cost makes FedTA highly efficient, and also makes FedTA scalable for multi-clients.

Privacy Protection. For *Input Enhancement*, on the one hand, ViT is frozen, and on the other hand, due to its minimal number of parameters, it contains extremely little information. Moreover, since this method does not use replay data to alleviate forgetting, privacy protection is further strengthened. However, the uploaded local prototypes are class-specific, and employing cross-mixing might easily reveal the original features, posing a certain degree of privacy risk. If we randomly mix Tail Anchor with features, this issue will be resolved.

6 Conclusion

This article extends the issue of data heterogeneity in static FL to the more realistic problem of spatial-temporal data heterogeneity in FCL. Empirical experiments are conducted to demonstrate that spatial-temporal data heterogeneity can cause parameter-forgetting and spatial forgetting. Based on this finding, FedTA utilizes a frozen pre-trained ViT to overcome parameter-forgetting and mixes Tail Anchors with the output features to adjust their positions in the feature space in order to address output-forgetting. Extensive experiments have verified the superiority of our method, and ablation studies demonstrate the effectiveness of each component, especially *Tail Anchor*. Finally, the visualized results demonstrate that our method effectively fixes the features' relative positions, preventing them from being affected by spatial-temporal changes.

References

- [1] Yang, Z., Y. Zhang, Y. Zheng, et al. Fedfed: Feature distillation against data heterogeneity in federated learning. *Advances in Neural Information Processing Systems*, 36, 2024.
- [2] Crawshaw, M., Y. Bao, M. Liu. Federated learning with client subsampling, data heterogeneity, and unbounded smoothness: A new algorithm and lower bounds. *Advances in Neural Information Processing Systems*, 36, 2024.
- [3] Liu, Z., Z. Xu, B. Coleman, et al. One-pass distribution sketch for measuring data heterogeneity in federated learning. *Advances in Neural Information Processing Systems*, 36, 2024.
- [4] Yoon, J., W. Jeong, G. Lee, et al. Federated continual learning with weighted inter-client transfer. In *International Conference on Machine Learning*, pages 12073–12086. PMLR, 2021.
- [5] Babakniya, S., Z. Fabian, C. He, et al. A data-free approach to mitigate catastrophic forgetting in federated class incremental learning for vision tasks. *Advances in Neural Information Processing Systems*, 36, 2024.
- [6] Yang, X., H. Yu, X. Gao, et al. Federated continual learning via knowledge fusion: A survey. *IEEE Transactions on Knowledge and Data Engineering*, 2024.
- [7] Kirkpatrick, J., R. Pascanu, N. Rabinowitz, et al. Overcoming catastrophic forgetting in neural networks. *Proceedings of the national academy of sciences*, 114(13):3521–3526, 2017.
- [8] Hadsell, R., D. Rao, A. A. Rusu, et al. Embracing change: Continual learning in deep neural networks. *Trends in cognitive sciences*, 24(12):1028–1040, 2020.
- [9] Li, Z., D. Hoiem. Learning without forgetting. *IEEE transactions on pattern analysis and machine intelligence*, 40(12):2935–2947, 2017.
- [10] Wang, Z., L. Liu, Y. Duan, et al. Continual learning with lifelong vision transformer. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 171–181. 2022.
- [11] Smith, J. S., J. Tian, S. Halbe, et al. A closer look at rehearsal-free continual learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 2409–2419. 2023.
- [12] Ermis, B., G. Zappella, M. Wistuba, et al. Continual learning with transformers for image classification. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 3774–3781. 2022.
- [13] Kang, Y., T. Fan, H. Gu, et al. Grounding foundation models through federated transfer learning: A general framework. *arXiv preprint arXiv:2311.17431*, 2023.
- [14] Dosovitskiy, A., L. Beyer, A. Kolesnikov, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.
- [15] Kim, T., E. Lin, J. Lee, et al. Navigating data heterogeneity in federated learning: a semisupervised federated object detection. In *Thirty-seventh Conference on Neural Information Processing Systems*. 2023.
- [16] Pieri, S., J. Restom, S. Horvath, et al. Handling data heterogeneity via architectural design for federated visual recognition. *Advances in Neural Information Processing Systems*, 36:4115– 4136, 2023.
- [17] Zhao, Y., M. Li, L. Lai, et al. Federated learning with non-iid data. *arXiv preprint arXiv:1806.00582*, 2018.
- [18] Li, Q., Y. Diao, Q. Chen, et al. Federated learning on non-iid data silos: An experimental study. In *2022 IEEE 38th international conference on data engineering (ICDE)*, pages 965–978. IEEE, 2022.
- [19] Zhang, Z., B. Guo, W. Sun, et al. Cross-fcl: Toward a cross-edge federated continual learning framework in mobile edge computing systems. *IEEE Transactions on Mobile Computing*, 23(1):313–326, 2022.
- [20] Xu, Z., L. Wang, W. Liang, et al. Age-aware data selection and aggregator placement for timely federated continual learning in mobile edge computing. *IEEE Transactions on Computers*, 2023.
- [21] Dong, J., L. Wang, Z. Fang, et al. Federated class-incremental learning. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 10164–10173. 2022.
- [22] Zhang, J., C. Chen, W. Zhuang, et al. Target: Federated class-continual learning via exemplarfree distillation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 4782–4793. 2023.
- [23] Liang, J., J. Zhong, H. Gu, et al. Diffusion-driven data replay: A novel approach to combat forgetting in federated class continual learning. In *European Conference on Computer Vision*, pages 303–319. Springer, 2025.
- [24] Li, Y., W. Xu, H. Wang, et al. Sr-fdil: Synergistic replay for federated domain-incremental learning. *IEEE Transactions on Parallel and Distributed Systems*, 2024.
- [25] Li, Y., Q. Li, H. Wang, et al. Towards efficient replay in federated incremental learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 12820–12829. 2024.
- [26] Li, Y., W. Xu, H. Wang, et al. Personalized federated domain-incremental learning based on adaptive knowledge matching. In *European Conference on Computer Vision*, pages 127–144. Springer, 2025.
- [27] Yu, H., X. Yang, X. Gao, et al. Overcoming spatial-temporal catastrophic forgetting for federated class-incremental learning. In *ACM Multimedia 2024*. 2024.
- [28] Li, B., P. Song, C. Zhao, et al. Facing spatiotemporal heterogeneity: A unified federated continual learning framework with self-challenge rehearsal for industrial monitoring tasks. *Knowledge-Based Systems*, 289:111491, 2024.
- [29] Rumelhart, D. E., G. E. Hinton, R. J. Williams. Learning representations by back-propagating errors. *nature*, 323(6088):533–536, 1986.
- [30] Li, Y., X. Yang, H. Wang, et al. Learning to prompt knowledge transfer for open-world continual learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 38, pages 13700–13708. 2024.
- [31] Pelosin, F., S. Jha, A. Torsello, et al. Towards exemplar-free continual learning in vision transformers: an account of attention, functional and weight regularization. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 3820–3829. 2022.
- [32] McMahan, B., E. Moore, D. Ramage, et al. Communication-efficient learning of deep networks from decentralized data. In *Artificial intelligence and statistics*, pages 1273–1282. PMLR, 2017.
- [33] Li, T., A. K. Sahu, M. Zaheer, et al. Federated optimization in heterogeneous networks. *Proceedings of Machine learning and systems*, 2:429–450, 2020.
- [34] Wang, J., Q. Liu, H. Liang, et al. Tackling the objective inconsistency problem in heterogeneous federated optimization. *Advances in neural information processing systems*, 33:7611–7623, 2020.
- [35] Wang, Z., Z. Zhang, S. Ebrahimi, et al. Dualprompt: Complementary prompting for rehearsalfree continual learning. In *European Conference on Computer Vision*, pages 631–648. Springer, 2022.
- [36] Yu, H., X. Yang, X. Gao, et al. Personalized federated continual learning via multi-granularity prompt. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pages 4023–4034. 2024.
- [37] Krizhevsky, A., G. Hinton, et al. Learning multiple layers of features from tiny images. 2009.
- [38] Hendrycks, D., S. Basart, N. Mu, et al. The many faces of robustness: A critical analysis of out-of-distribution generalization. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 8340–8349. 2021.
- [39] Ma, Y., Z. Xie, J. Wang, et al. Continual federated learning based on knowledge distillation. In *IJCAI*, pages 2182–2188. 2022.
- [40] Huang, W., M. Ye, B. Du. Learn from others and be yourself in heterogeneous federated learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10143–10153. 2022.