# Is Large Language Model Good at Triple Set Prediction? An Empirical Study

Yuan Yuan School of Software Technology Zhejiang University Ningbo, Zhejiang, China yuanyuanyy@zju.edu.cn Yajing Xu

College of Computer Science of Technology Zhejiang University Hangzhou, Zhejiang, China yajingxu@zju.edu.cn Wen Zhang<sup>\*</sup> School of Software Technology Zhejiang University Ningbo, Zhejiang, China zhang.wen@zju.edu.cn

Abstract—The core of the Knowledge Graph Completion (KGC) task is to predict and complete the missing relations or nodes in a KG. Common KGC tasks are mostly about inferring unknown elements with one or two elements being known in a triple. In comparison, the Triple Set Prediction (TSP) task is a more realistic knowledge graph completion task. It aims to predict all elements of unknown triples based on the information from known triples. In recent years, large language models (LLMs) have exhibited significant advancements in language comprehension, demonstrating considerable potential for KGC tasks. However, the potential of LLM on the TSP task has not yet to be investigated. Thus in this paper we proposed a new framework to explore the strengths and limitations of LLM in the TSP task. Specifically, the framework consists of LLMbased rule mining and LLM-based triple set prediction. The relation list of KG embedded within rich semantic information is first leveraged to prompt LLM in the generation of rules. This process is both efficient and independent of statistical information, making it easier to mine effective and realistic rules. For each subgraph, the specified rule is applied in conjunction with the relevant triples within that subgraph to guide the LLM in predicting the missing triples. Subsequently, the predictions from all subgraphs are consolidated to derive the complete set of predicted triples on KG. Finally, the method is evaluated on the relatively complete CFamily dataset. The experimental results indicate that when LLMs are required to adhere to a large amount of factual knowledge to predict missing triples, significant hallucinations occurs, leading to a noticeable decline in performance. To further explore the causes of this phenomenon, this paper presents a comprehensive analysis supported by a detailed case study. The datasets and code for experiments are available at https://github.com/zjukg/LLM-based-TSP.

Index Terms—Knowledge Graph, Knowledge Graph Completion, Triple Set Prediction, Large Language Model

#### I. INTRODUCTION

Knowledge Graph (KG) [1] serves as a framework for representing and storing structured knowledge. It is typically organized in the form of a triple, i.e., (head entity, relationship, tail entity). The nodes in KG represent the entities in the triple, while the edges represent the relations between the entities. In this way, the information is more well-organized and easier to understand, so KG is also widely used in a variety of application scenarios such as search engines [2], recommender systems [3], question answering [4], [5] and so on. The construction of large open KGs, such as Freebase [6], DBpedia [7], Wikidata [8], etc., provides robust knowledge support for various intelligent applications.

Most KGs are far from complete. Therefore, the Knowledge Graph Completion (KGC) task has become a prominent research focus in the field of KG. The core of the KGC task is to predict and complete the missing relations or nodes in a KG. Specifically, it can be categorized into head entity prediction (?, r, t), tail entity prediction (h, r, ?), relationship prediction (h, ?, t), instance completion (h, ?, ?). Zhang et al. [9] suggested that these KGC tasks require knowing at least one or two elements of the missing triples, which does not align with real-world scenarios, and thus a new KGC task Triple Set Prediction (TSP) is defined and a corresponding method called GPHT is proposed. The goal of the TSP task is to directly predict the head entity, tail entity and relation of missing triples from given triples.

In recent years, Large Language Models (LLMs) [10] have achieved obvious advantages and been widely applied, as well as showing great potential in KGC tasks [11]–[15]. On the one hand, LLMs have powerful language comprehension and generation capabilities, and can quickly process a large amount of complex textual information to complete the inference of KG. On the other hand, the accurate and interpretable knowledge provided by KG can alleviate the hallucination of LLMs. In related studies, LLMs can be leveraged to generate predicted triples from given inputs [11] or to create valid contexts that can enhance predictive accuracy [12]. Researchers have also merged the structural information of KG into LLMs to realize structure-aware reasoning [13]. It can be seen that LLM can play an important role in KGC tasks. Therefore, we propose the idea of applying LLM to the task of TSP to analyze the advantages and limitations of LLM in this context.

Depending on good textual comprehension and generative capabilities, LLM is able to understand different relation names in KG and the connections among them. Without giving triples, LLM can also mine rules based on known relations. Compared to traditional rule mining methods, the process of generating rules utilizing LLM is fast and unaffected by statistical information of the KG. In traditional statistical-based rule mining methods [16]–[18], when the number of a certain type of relationship in a KG is small, the metrics of

<sup>\*</sup>Corresponding Author.

rules containing this type of relationship will be significantly affected. For example, when there are very few triples in the KG that contain the relation *sisterOf*, the metrics such as confidence and support for rules involving *sisterOf* will significantly decrease. As a result, even though these rules may hold substantial value for specific reasoning tasks, they are often not retained during the rule-mining process. LLM, on the other hand, mines rules based on the semantics of the relations themselves and the patterns obtained from a large amount of text data during pre-training. Therefore, we believe that LLM is capable of mining richer and more realistic rules, especially when the data in KG is not balanced. Therefore, we apply LLM to both rule mining and triple set prediction stages and propose the specific methods and experimental ideas as follows.

We first write a list of all relations in KG, including inverse relations, to prompt. Then the LLM is guided by the instructions of the prompt to mine the rules based on the connections between different relations. Eventually, valid rules are selected based on rule quality metrics. Further, the KG is divided into subgraphs. The information and rules of the subgraphs are then written into the prompt and provided to the LLM to generate the missing triples. Three classification metrics [9], namely Joint Precision (*JPrecision*), Squared Test Recall (*STRecall*), and TSP score ( $F_{TSP}$ ), are chosen to evaluate the effectiveness of the method.

The final experimental results demonstrated that when LLM needs to comply with a given large amount of factual knowledge to predict the missing triples, significant hallucinations occur, which is mainly manifested by 1) the triples used for reasoning do not really exist; and 2) the reasoning is not made exactly according to the given rule. We believe that the reason for this phenomenon may be related to the way information is stored in KG and the dependence of LLM on context. To enhance the performance of LLM in TSP, future research will focus on optimizing the way LLM acquires relevant triples and handles contextual information, thereby reducing reliance on irrelevant data and mitigating the occurrence of hallucinations.

## II. RELATED WORKS

The key to the KGC task is to utilize the information in the KG to speculate and complete the missing relations or nodes in it. Common KGC methods can be categorized into translationbased methods such as TransE [19], TransH [20], RotatE [21], tensor decomposition-based methods such as DistMult [22], HolE [23], SimplE [24], deep learning-based methods such as ConvE [25], convKB [26], CapsE [27]. In recent years, Graph Neural Network (GNN) techniques have gained increasing attention in KG complementation tasks. Models such as R-GCN [28] and CompGCN [29] have achieved outstanding performance. The various approaches complement each other and together they drive the research and application of KGC tasks. With its excellent language comprehension and generation capabilities, LLM shows great potential in KGC tasks as it is able to process large amounts of complex text and extract useful information from it. Luo et al. [14] pointed out that existing methods for mining logical rules in KGs face challenges due to high computational costs and a lack of scalability for large-scale KGs. To address these issues, they proposed the ChatRule framework, which utilizes LLMs to generate and optimize logical rules by integrating both the semantic and structural information of KGs, thereby enhancing reasoning performance and interpretability. Yao et al. [11] proposed a method called KG-LLM. This model utilizes LLMs to generate candidate triples from given text inputs. This approach enables the generation of meaningful knowledge graph completion information even in the absence of structured data. In response to the ineffective use of structural information in existing methods, Zhang et al. [13] proposed the KoPA model. This model integrates structural embeddings into LLMs through pre-training, enhancing the model's reasoning ability. Zhu et al. [15] conducted a comprehensive evaluation of LLMs in KG construction and reasoning, emphasizing their advantages in reasoning tasks. They further proposed the AutoKG multi-agent approach to further enhance KG construction and reasoning capabilities. These works have shown that large language models demonstrate significant potential in KGC tasks. Therefore, we focus on applying LLM to the task of triple set prediction, which has not been studied in detail.

## **III. PRELIMINARIES**

**Background.** A KG can be denoted as  $\mathcal{G} = \{\mathcal{E}, \mathcal{R}, \mathcal{T}\}$ , where  $\mathcal{E}$  is a set of entities,  $\mathcal{R}$  is a set of relations, such as *sisterOf*, and  $\mathcal{T} = \{(h, r, t) | h, t \in \mathcal{E}, r \in \mathcal{R}\}$  is a set of triples. h, r are called the head entity and the tail entity of a triple. The core of the KGC task is to find those triples that are correct but not in the KG. Specifically, triple classification, relation prediction, and entity prediction are three common KGC tasks, where relation/entity prediction is to predict the missing element with two other elements given.

**TSP Task [9]**. Given a KG  $\mathcal{G}$ , the purpose of the TSP task is to discover the missing but correct triple  $\mathcal{T}_{predict}$  in the KG. Specifically, the training dataset  $\mathcal{G}_{train} = \{\mathcal{E}, \mathcal{R}, \mathcal{T}\}$  is provided to the model. After the model predicts the candidate triple, the test set  $\mathcal{T}_{test} = \{(h, r, t) | h, t \in \mathcal{E}, r \in \mathcal{R}, (h, r, t) \notin \mathcal{T}\}$  to evaluate the model.

**Logical Rule.** A path-based logic rule that is widely studied [17], [30]–[33] can be expressed as:

$$r_h(X,Y) \leftarrow r_1(X,Z_1) \wedge \dots \wedge r_K(Z_{K-1},Y)$$
(1)

where  $r_h(X, Y)$  represents the rule head,  $r_1(X, Z_1) \land \cdots \land r_K(Z_{K-1}, Y)$  represents the rule body, and K represents the length of the rule. When the rule body holds, we can derive the rule head. In the rule,  $\{r, r_1, \ldots, r_K\}$  corresponds to relations in KG, while  $\{X, Y, Z_1, \ldots, Z_{K-1}\}$  corresponds to entities in KG. For convenience and brevity, we can abbreviate the rule as  $r \leftarrow r_1 \land r_2 \land \cdots \land r_K$  without causing confusion.

# IV. METHOD

In this subsection, we present the specific framework and composition of the proposed LLM-based triple set prediction model. The framework of the model is shown in Figure. 1,



Fig. 1. Framework for the TSP task based on Large Language Models.

which includes three parts: rule mining based on LLM, graph partitioning, and triple set prediction.

## A. Rule Miner Based on LLMs

For a given KG  $\mathcal{G}$ , we first add the inverse triple of each triple to KG, i.e.,  $\mathcal{G} \leftarrow \mathcal{G} \cup \{(h, r^{-1}, t) | (h, r, t) \in \mathcal{G}\}$ . Specifically, we generate the corresponding inverse relation by adding the prefix "inv\_" to each relation, i.e.,  $\mathcal{R} \leftarrow \mathcal{R} \cup \{r^{-1} | r \in \mathcal{R}\}$ .

Since the large language model has been trained on a large corpus, it is capable of understanding the connections between different relations. Therefore, we utilize the LLM to mine rules based on the relations in the KG. Specifically, we design a detailed prompt which is shown in Fig. 2. We can see that the prompt consists of five parts: background, relations in KG, rule head, example, and notes. In the background part, we describe the KG as well as the composition and definition of logical rules. Next, we provide all the relations in the KG for LLM. We then specify the rule header as one of the relations in KG (e.g. *nieceOf*) and then direct the LLM to generate rules based on the given lits of relations. To make LLM better understand the problem and answer the questions, we give a concrete example. The example gives two rules with *fatherOf* as the rule head and the corresponding logical explanations. At the end of the prompt, we provided some guidelines to ensure that the LLM generates rules in the correct format. Then, we generate rules by setting each relation in turn as the rule head. In this way, LLM analyzes the interconnections and logical relationships among different relations based on the information in prompt and then generates effective rules. Ultimately, we utilize two commonly used metrics confidence (conf) and head coverage (hc) [34] to filter out high-quality rules from the generated results. Specifically, we retain the rules that confidence and head coverage are higher than the thresholds  $\alpha_{conf} = 0.45$  and  $\alpha_{hc} = 0.05$ .

# B. Triple Set Prediction with LLMs

Considering the fact that the LLM input length is limited, KGs with a large number of triples cannot be input at once, we divide the knowledge graph and then perform triple set prediction for each subgraph individually.



Fig. 2. A specific prompt for LLM-based rule miner with *nieceof* as the rule header.

1) Graph Partition: We follow the "soft" vertex-cut KG partition method proposed in [9] to obtain subgraphs from KG. This method allows subgraphs to share some of their entities with each other, thus ensuring the completeness of information in the division process as much as possible. It consists of two main steps: primary entity grouping and entity group fine-tuning.

In the primary entity grouping stage, we first initialize the ungrouped entity set  $\mathcal{E}_U = \mathcal{E}$  and the grouped entity set  $\mathcal{E}_G = \{\}$ , and divide  $\mathcal{E}$  into a number of disjoint entity subsets. The smaller entity sets are then processed and the entity sets with the proper size are removed from  $\mathcal{E}_U$  and added to the entity group set  $\mathcal{E}_G$ . Then an entity is selected from  $\mathcal{E}_U$  and its neighbor entity set within L-hop is extracted. Finally, the set of neighboring entities within L-1 hop is removed from  $\mathcal{E}_U$ . This process continues until all entities in  $\mathcal{E}_U$  have been

traversed.

In the entity group fine-tuning stage, a random entity e is selected from  $\mathcal{E}_U$ , then the neighboring entities of e are merged into the smallest entity group  $\mathcal{E}'$  that contains e, and e is removed from  $\mathcal{E}_U$ . When all entities are grouped, we obtain the size-balanced entity group set  $\mathcal{E}_G$ . Finally, for each  $\mathcal{E}' \in \mathcal{E}_G$ , the subgraph  $\mathcal{G}_{\mathcal{E}'}$  is constructed by adding triple with head and tail entities in  $\mathcal{E}'$ , ultimately getting the set of subgraphs  $\mathcal{G}_{part} = {\mathcal{G}_1, \mathcal{G}_2, ..., \mathcal{G}_k}.$ 

2) LLM-based Triple Set Prediction: When predicting missing triples, we first need to write the information of subgraphs and related rules into a detailed prompt, and then provide the prompt to LLM. Specifically, the prediction process includes three steps: subgraph information extraction, prompt generation, and LLM reasoning.

Subgraph information extraction: For each subgraph  $\mathcal{G}_i \in \mathcal{G}_{part}$ , we first extract all known triples from the subgraphs which will be written into the prompt. This step is crucial since the information of triples is the basis for model inference. Meanwhile, considering the possible hallucination phenomenon of LLMs, we further filter out the rule-related triples from the subgraph. Specifically, for a rule  $r \leftarrow r_1 \land r_2 \land \cdots \land r_m$ , we extract the relations contained in the rule body  $\mathcal{R}_{rule} = \{r_1, r_2, \ldots, r_m\}$ . Then the triples containing any relation in  $\mathcal{R}_{rule}$  is further extracted from the subgraph  $\mathcal{G}_i$ , i.e.,  $\mathcal{T}_i = \{(h, r, t) | h, t \in \mathcal{E}_i, r \in \mathcal{R}_{rule}\}$ . By providing  $\mathcal{T}_i$  to the LLM instead of all triples in the subgraph, it can help mitigate the risk of the LLM using triples that do not actually exist in the subgraph during reasoning.

Prompt generation: We utilize the information of rulerelated triples from the subgraph, along with the rule to generate a prompt. We incorporate corresponding explanations for these rules to enhance the prompts. In the large model inference process, we do not provide explicit reasoning examples, which means that this process can be considered a form of zero-shot reasoning. In addition, we introduced the thought of Chain-of-Thought (CoT) [35] in the design of Prompt to make LLMs simulate the human's step-by-step thinking process. A specific prompt with  $uncleOf(X,Y) \leftarrow$  $brotherOf(X, Z_1) \wedge fatherOf(Z_1, Y)$  as the rule is shown in Figure 3.

*LLM reasoning*: In the reasoning process, LLMs will predict the missing triples based on the information in the prompt. For each subgraph  $\mathcal{G}_i \in \mathcal{G}_{part}$ , all rules in  $\mathcal{R}ule$  will be traversed sequentially to make multiple predictions. After traversing all subgraphs, the predicted triples are extracted from the LLM responses to form the set  $\mathcal{T}_{predict}$ .

#### V. EXPERIMENTS

In this section, we describe the procedure and results of the experiment in detail. We first introduce the dataset, model, and evaluation metrics used in the experiment. Then we analyze the results of our method. Finally, a specific case is used to analyze the significant hallucination phenomenon that occurs when LLM performs the task of triple set prediction.



Fig. 3. A specific prompt for LLM-based triple set prediction with  $uncleOf(X, Y) \leftarrow brotherOf(X, Z_1) \wedge fatherOf(Z_1, Y)$  as the rule.

#### A. Settings

**Dataset.** The dataset we use is CFamily, which was proposed in the previous work [9]. Specifically, it is a more complete dataset constructed by supplementing missing triples through rules on the basis of an initial set of triples about family. The statistical information of CFamily is shown in Table I.

TABLE I STATISTICAL INFORMATION OF CFAMILY.

Dataset	#Ent	#Rel	#Triple	#Train	#Test
CFamily	2378	12	22986	18388	4598

**Model.** Throughout the experiments, we used GPT-3.5turbo and GPT-40 as LLMs respectively in both rule generation and triple set prediction phases. In rule generation, we utilize GPT to mine valid rules from KG. The rule generation process is fast and unaffected by statistical information. In the triple set prediction phase, we use the logical reasoning ability of GPT to predict the missing triples from the existing triples. For the parameter settings, we select the rule length K from  $\{2,3\}$ ,  $\alpha_{conf} = 0.45$ ,  $\alpha_{hc} = 0.05$ .

# B. Metrics

Considering that CFamily is a more complete dataset, we will evaluate the effectiveness of our method under the Closed World Assumption (CWA), which assumes that a proposition is considered false if it is not explicitly declared true. Therefore, under the CWA, a triple that does not exist in the KG is considered as a false triple. Based on this assumption, we

TABLE II Rules mined on CFAMILY by LLMs.

LLMs	Index	Rule	Support	Head coverage	Confidence
GPT-3.5-turbo	1	$auntOf(X, Y) \leftarrow sisterOf(X, Z_1) \land inv\_daughterOf(Z_1, Y)$	364	0.15	0.8
	2	$auntOf(X, Y) \leftarrow sisterOf(X, Z_1) \land motherOf(Z_1, Y)$	319	0.13	0.8
	3	$fatherOf(X, Y) \leftarrow husbandOf(X, Z_1) \land motherOf(Z_1, Y)$	184	0.21	0.5
	4	$fatherOf(X,Y) \leftarrow inv_wifeOf(X,Z_1) \land motherOf(Z_1,Y)$	196	0.22	0.49
	5	$fatherOf(X,Y) \leftarrow inv\_wifeOf(X,Z_1) \land motherOf(Z_1,Z_2) \land sisterOf(Z_2,Y)$	145	0.16	0.52
	6	$nephewOf(X,Y) \leftarrow sonOf(X,Z_1) \land brotherOf(Z_1,Y)$	594	0.21	0.77
	7	$nieceOf(X,Y) \leftarrow sisterOf(X,Z_1) \land nephewOf(Z_1,Y)$	1427	0.63	0.61
	8	$nieceOf(X,Y) \leftarrow sisterOf(X,Z_1) \land nieceOf(Z_1,Y)$	1287	0.57	0.6
	9	$uncleOf(X,Y) \leftarrow brotherOf(X,Z_1) \wedge fatherOf(Z_1,Y)$	627	0.24	0.82
	10	$uncleOf(X,Y) \leftarrow brotherOf(X,Z_1) \land motherOf(Z_1,Z_2) \land sisterOf(Z_2,Y)$	262	0.1	0.64
GPT-4o	1	$auntOf(X,Y) \leftarrow sisterOf(X,Z_1) \land fatherOf(Z_1,Y)$	532	0.21	0.78
	2	$auntOf(X, Y) \leftarrow sisterOf(X, Z_1) \land inv\_daughterOf(Z_1, Z_2) \land inv\_sisterOf(Z_2, Y)$	312	0.13	0.63
	3	$auntOf(X, Y) \leftarrow sisterOf(X, Z_1) \land inv\_sonOf(Z_1, Z_2) \land inv\_brotherOf(Z_2, Y)$	377	0.15	0.59
	4	$auntOf(X,Y) \leftarrow sisterOf(X,Z_1) \land motherOf(Z_1,Y)$	319	0.13	0.8
	5	$fatherOf(X,Y) \leftarrow husbandOf(X,Z_1) \land motherOf(Z_1,Y)$	184	0.21	0.5
	6	$fatherOf(X,Y) \leftarrow inv\_wifeOf(X,Z_1) \land motherOf(Z_1,Y)$	196	0.22	0.49
	7	$nephewOf(X,Y) \leftarrow sonOf(X,Z_1) \land inv\_brotherOf(Z_1,Y)$	501	0.18	0.78
	8	$nephewOf(X,Y) \leftarrow sonOf(X,Z_1) \land inv\_sisterOf(Z_1,Y)$	464	0.17	0.79
	9	$uncleOf(X,Y) \leftarrow brotherOf(X,Z_1) \land fatherOf(Z_1,Y)$	627	0.24	0.82
	10	$uncleOf(X,Y) \leftarrow brotherOf(X,Z_1) \land motherOf(Z_1,Y)$	364	0.14	0.8

 TABLE III

 Individual and averaged TSP results for experiments on the CFamily dataset.

LLMs	#Triples		Metrics		
	$T_{predict}$	$T^+_{predict}$	JPrecision	STRecall	$F_{TSP}$
GPT-3.5-turbo	3583 3287 3338	105 83 101	0.029 0.025 0.03	0.171 0.159 0.174	0.05 0.044 0.052
	3403±158	96±12	0.028±0.3%	0.168±0.8%	0.049±0.4%
GPT-4o	1444 1169 1216	198 171 167	0.137 0.146 0.137	0.37 0.382 0.371	0.2 0.212 0.2
	1276±147	179±17	0.14±0.5%	0.374±0.7%	0.204±0.7%

can categorize the predicted triples into positive and negative as shown below: triple sets as follows:

$$\mathcal{T}_{predict}^{+} = \mathcal{T}_{predict} \cap \mathcal{T}_{test} \tag{2}$$

$$\mathcal{T}_{predict}^{-} = \mathcal{T}_{predict} - \mathcal{T}_{predict}^{+} \tag{3}$$

Following prior work [9], we chose Joint Precision (*JPrecision*), Squared Test Recall (*STRecall*), and TSP score ( $F_{TSP}$ ) as our three evaluation metrics to evaluate the performance of the proposed method. Under CWA, *JPrecision* is the percentage of correctly predicted triples in the prediction triples. *STRecall* is the percentage of correctly predicted triples in the test set, and the square operation is used considering the large number of triples in the test set. As the harmonic mean of *JPrecision* and *STRecall*,  $F_{TSP}$  effectively balances the two and can accurately reflect the overall performance of the model, especially when the data is imbalanced. The three metrics under CWA are calculated

$$JPrecision = \frac{|\mathcal{T}_{predict}^+|}{|\mathcal{T}_{predict}|} \tag{4}$$

$$STRecall = \left(\frac{|\mathcal{T}_{predict}^+|}{|\mathcal{T}_{test}|}\right)^{\frac{1}{2}}$$
(5)

$$F_{TSP} = 2 \times \frac{STRecall \times JPrecision}{STRecall + JPrecision}$$
(6)

# C. Results

Table II shows the statistics of the rules mined by GPT-3.5turbo and GPT-40 on the CFamily dataset, where the same rules generated by GPT-3.5-turbo and GPT-40 are marked in light gray. It can be seen that these rules are correct and match the relationships between the characters in the family. On the one hand, it can be seen that LLM can mine valid rules based only on the list of relations without giving information about the triples. On the other hand, the number of valid rules mined by LLM at one time is small, thus how to improve the number of valid rules is also a concern for future work.

Table III shows the individual and average results of experiments conducted three times on the CFamily dataset by using GPT-3.5-turbo and GPT-40 as LLMs. In the three experiments of GPT-3.5-turbo, the average number of predicted triples is 3403, and the average number of correctly predicted triples is 96. The average classification metrics are JPrecision = $0.028, STRecall = 0.168, F_{TSP} = 0.049$ . The fluctuation of each metric is extremely small, 0.3%, 0.8%, and 0.4% respectively. From the experimental results, it can be seen that the proposed model does not perform as well as expected on the test dataset. When employing GPT-40 to predict the missing triples, the average number of predicted triples and correctly predicted triples are 1276 and 179 respectively. The average classification metrics are JPrecision = 0.14,  $STRecall = 0.374, F_{TSP} = 0.204$ . The fluctuation of each metric is also small, 0.5%, 0.7%, and 0.7% respectively. It can be observed that employing GPT-40 can enhance the prediction outcome to some degree. This shows that the capability of LLM itself has a significant influence on the TSP task. However, both GPT models demonstrate relatively poor performance on the TSP task. Further analyzing the responses of LLMs, we consider that the poor experimental results may be attributed to the significant hallucination phenomenon generated by LLMs in the prediction process. To further elucidate this phenomenon, we will elaborate on a specific case in the next subsection.

## D. Case Study

Fig. 4 shows the specific reasoning process of LLM. As shown in the figure, the triples from the subgraph and a rule are taken as input to the LLM in the form of a prompt. Take the rule  $nephewOf(X,Y) \leftarrow$  $sonOf(X, Z_1) \wedge brotherOf(Z_1, Y)$  as an example, let r = $is\_nephew\_of, r_1 = is\_son\_of, r_2 = is\_brother\_of$ . We can observe that during LLM reasoning, one of the  $r_1$ related triples does not exist in the subgraph, and two of the  $r_2$ -related triples do not exist in the subgraph. These nonexistent triples are wrong triples generated by LLM, thus showing the very significant hallucination phenomenon of LLM in the reasoning process. This hallucination phenomenon is especially pronounced when we input all the triples of the subgraph into LLM. When only rule-related triples are input, the hallucination phenomenon is mitigated to some extent but still persists.

In conclusion, we can observe that when LLM needs to comply with a given large amount of factual knowledge to predict the missing triples, significant hallucinations occur, which is mainly manifested by 1) the triples used for reasoning do not really exist; and 2) the reasoning is not made exactly according to the given rule. These hallucinations may occur due to the following reasons: 1) LLM deals with natural language information that is usually unstructured, while the triple in KG is structured information with logical relationships. Therefore LLM may generate hallucination phenomena due to the lack of in-depth understanding of these structured relations. 2) The entities of the triple in CFamily exist in the form of encodings rather than specific person names in natural language, lacking semantic information in comparison. This may lead to the inability of LLM to accurately understand the roles and relations of the entities. 3) LLM relies on the current context for reasoning during generation. However, when a large number of facts are involved, the model may not be able to relate the facts correctly, leading to the generation of incorrect information.



Fig. 4. Illustration of the specific case used to demonstrate the hallucination phenomenon observed in the LLM-based TSP task.

#### VI. CONCLUSION

In this paper, we propose a new framework to explore the strengths and limitations of LLM in TSP tasks. Specifically, the KG relation list is first utilized to prompt LLM to mine useful rules. The KG is further divided into subgraphs and the rule-related triples in the subgraphs are extracted. The rule and triples are then utilized to prompt LLM to predict the missing triples. We conducted experiments on the relatively complete CFamily dataset. Experimental results indicate that when a Large Language Model (LLM) needs to follow a substantial amount of factual knowledge to predict missing triples, significant hallucination phenomena occur. We believe that the reason for this phenomenon may be related to the way information is stored in KG and LLM's dependence on context. In the future, we will improve the way of obtaining triples from subgraphs and the reasoning process of LLM to mitigate the illusion phenomenon. Meanwhile, we will further conduct experiments on more datasets.

## ACKNOWLEDGMENT

This work is founded by National Natural Science Foundation of China (NSFC62306276/NSFCU23B2055/NS FCU19B2027), Zhejiang Provincial Natural Science Foundation of China (No. LQ23F020017), Yongjiang Talent Introduction Programme (2022A-238-G), and Fundamental Research Funds for the Central Universities (226-2023-00138).

#### REFERENCES

- J. Z. Pan, G. Vetere, J. M. Gomez-Perez, and H. Wu, *Exploiting linked data and knowledge graphs in large organisations*. Springer, 2017.
- [2] S. Huang, Y. Wang, and X. Yu, "Design and implementation of oil and gas information on intelligent search engine based on knowledge graph," in *Journal of Physics: Conference Series*, vol. 1621, no. 1. IOP Publishing, 2020, p. 012010.
- [3] C.-M. Wong, F. Feng, W. Zhang, C.-M. Vong, H. Chen, Y. Zhang, P. He, H. Chen, K. Zhao, and H. Chen, "Improving conversational recommender system by pretraining billion-scale knowledge graph," in 2021 IEEE 37th International Conference on Data Engineering (ICDE). IEEE, 2021, pp. 2607–2612.
- [4] Z. Chen, Y. Huang, J. Chen, Y. Geng, Y. Fang, J. Z. Pan, N. Zhang, and W. Zhang, "Lako: Knowledge-driven visual question answering via late knowledge-to-text injection," in *Proceedings of the 11th International Joint Conference on Knowledge Graphs*, 2022, pp. 20–29.
- [5] S. V. Thambi and P. Reghu Raj, "A novel technique using graph neural networks and relevance scoring to improve the performance of knowledge graph-based question answering systems," *Journal of Intelligent Information Systems*, pp. 1–24, 2024.
- [6] K. Bollacker, C. Evans, P. Paritosh, T. Sturge, and J. Taylor, "Freebase: a collaboratively created graph database for structuring human knowledge," in *Proceedings of the 2008 ACM SIGMOD international conference on Management of data*, 2008, pp. 1247–1250.
- [7] C. Bizer, J. Lehmann, G. Kobilarov, S. Auer, C. Becker, R. Cyganiak, and S. Hellmann, "Dbpedia-a crystallization point for the web of data," *Journal of web semantics*, vol. 7, no. 3, pp. 154–165, 2009.
- [8] D. Vrandečić and M. Krötzsch, "Wikidata: a free collaborative knowledgebase," *Communications of the ACM*, vol. 57, no. 10, pp. 78–85, 2014.
- [9] W. Zhang, Y. Xu, P. Ye, Z. Huang, Z. Xu, J. Chen, J. Z. Pan, and H. Chen, "Start from zero: Triple set prediction for automatic knowledge graph completion," *IEEE Transactions on Knowledge and Data Engineering*, 2024.
- [10] R. OpenAI, "Gpt-4 technical report. arxiv 2303.08774," View in Article, vol. 2, no. 5, 2023.
- [11] L. Yao, J. Peng, C. Mao, and Y. Luo, "Exploring large language models for knowledge graph completion," arXiv preprint arXiv:2308.13916, 2023.
- [12] D. Li, Z. Tan, T. Chen, and H. Liu, "Contextualization distillation from large language model for knowledge graph completion," arXiv preprint arXiv:2402.01729, 2024.
- [13] Y. Zhang, Z. Chen, W. Zhang, and H. Chen, "Making large language models perform better in knowledge graph completion," arXiv preprint arXiv:2310.06671, 2023.
- [14] L. Luo, J. Ju, B. Xiong, Y.-F. Li, G. Haffari, and S. Pan, "Chatrule: Mining logical rules with large language models for knowledge graph reasoning," arXiv preprint arXiv:2309.01538, 2023.
- [15] Y. Zhu, X. Wang, J. Chen, S. Qiao, Y. Ou, Y. Yao, S. Deng, H. Chen, and N. Zhang, "Llms for knowledge graph construction and reasoning: Recent capabilities and future opportunities," *World Wide Web*, vol. 27, no. 5, p. 58, 2024.
- [16] S. Schoenmackers, J. Davis, O. Etzioni, and D. S. Weld, "Learning firstorder horn clauses from web text," in *Proceedings of the 2010 conference* on empirical methods in natural language processing, 2010, pp. 1088– 1098.
- [17] L. A. Galárraga, C. Teflioudi, K. Hose, and F. Suchanek, "Amie: association rule mining under incomplete evidence in ontological knowledge bases," in *Proceedings of the 22nd international conference on World Wide Web*, 2013, pp. 413–422.
- [18] L. Galárraga, C. Teflioudi, K. Hose, and F. M. Suchanek, "Fast rule mining in ontological knowledge bases with amie+," *The VLDB Journal*, vol. 24, no. 6, pp. 707–730, 2015.
- [19] A. Bordes, N. Usunier, A. Garcia-Duran, J. Weston, and O. Yakhnenko, "Translating embeddings for modeling multi-relational data," *Advances in neural information processing systems*, vol. 26, 2013.
- [20] Z. Wang, J. Zhang, J. Feng, and Z. Chen, "Knowledge graph embedding by translating on hyperplanes," in *Proceedings of the AAAI conference* on artificial intelligence, vol. 28, no. 1, 2014.
- [21] Z. Sun, Z.-H. Deng, J.-Y. Nie, and J. Tang, "Rotate: Knowledge graph embedding by relational rotation in complex space," *arXiv preprint* arXiv:1902.10197, 2019.

- [22] B. Yang, W.-t. Yih, X. He, J. Gao, and L. Deng, "Embedding entities and relations for learning and inference in knowledge bases," arXiv preprint arXiv:1412.6575, 2014.
- [23] M. Nickel, L. Rosasco, and T. Poggio, "Holographic embeddings of knowledge graphs," in *Proceedings of the AAAI conference on artificial intelligence*, vol. 30, no. 1, 2016.
- [24] S. M. Kazemi and D. Poole, "Simple embedding for link prediction in knowledge graphs," *Advances in neural information processing systems*, vol. 31, 2018.
- [25] T. Dettmers, P. Minervini, P. Stenetorp, and S. Riedel, "Convolutional 2d knowledge graph embeddings," in *Proceedings of the AAAI conference* on artificial intelligence, vol. 32, no. 1, 2018.
- [26] D. Q. Nguyen, T. D. Nguyen, D. Q. Nguyen, and D. Phung, "A novel embedding model for knowledge base completion based on convolutional neural network," arXiv preprint arXiv:1712.02121, 2017.
- [27] D. Q. Nguyen, T. Vu, T. D. Nguyen, D. Q. Nguyen, and D. Phung, "A capsule network-based embedding model for knowledge graph completion and search personalization," arXiv preprint arXiv:1808.04122, 2018.
- [28] M. Schlichtkrull, T. N. Kipf, P. Bloem, R. Van Den Berg, I. Titov, and M. Welling, "Modeling relational data with graph convolutional networks," in *The semantic web: 15th international conference, ESWC* 2018, Heraklion, Crete, Greece, June 3–7, 2018, proceedings 15. Springer, 2018, pp. 593–607.
- [29] S. Vashishth, S. Sanyal, V. Nitin, and P. Talukdar, "Compositionbased multi-relational graph convolutional networks," *arXiv preprint* arXiv:1911.03082, 2019.
- [30] R. Agrawal, "Fast algorithms for mining association rules." VLDB, 1994.
- [31] M. J. Zaki, S. Parthasarathy, M. Ogihara, W. Li *et al.*, "New algorithms for fast discovery of association rules." in *KDD*, vol. 97, 1997, pp. 283– 286.
- [32] D. Stepanova, M. H. Gad-Elrab, and V. T. Ho, "Rule induction and reasoning over knowledge graphs," *Reasoning Web. Learning, Uncertainty, Streaming, and Scalability: 14th International Summer School* 2018, Esch-sur-Alzette, Luxembourg, September 22–26, 2018, Tutorial Lectures 14, pp. 142–172, 2018.
- [33] S. Khan and M. Shaheen, "Wisrule: First cognitive algorithm of wise association rule mining," *Journal of Information Science*, vol. 50, no. 4, pp. 874–893, 2024.
- [34] J. Lajus, L. Galárraga, and F. Suchanek, "Fast and exact rule mining with amie 3," in *The Semantic Web: 17th International Conference, ESWC* 2020, Heraklion, Crete, Greece, May 31–June 4, 2020, Proceedings 17. Springer, 2020, pp. 36–52.
- [35] J. Wei, X. Wang, D. Schuurmans, M. Bosma, F. Xia, E. Chi, Q. V. Le, D. Zhou *et al.*, "Chain-of-thought prompting elicits reasoning in large language models," *Advances in neural information processing systems*, vol. 35, pp. 24 824–24 837, 2022.