

MPI-Rockstar: a Hybrid MPI and OpenMP Parallel Implementation of the Rockstar Halo finder

Tomoyuki Tokue¹, Tomoaki Ishiyama ^{*2}, Ken Osato^{3,4,5}, Satoshi Tanaka⁶, and Peter Behroozi⁷

¹Department of Applied and Cognitive Informatics, Division of Mathematics and Informatics, Graduate School of Science and Engineering, Chiba University, Chiba 263-8522, Japan

²Digital Transformation Enhancement Council, Chiba University, Chiba 263-8522, Japan

³Center for Frontier Science, Chiba University, Chiba 263-8522, Japan

⁴Department of Physics, Graduate School of Science, Chiba University, Chiba 263-8522, Japan

⁵Kavli Institute for the Physics and Mathematics of the Universe (WPI), The University of Tokyo, Kashiwa, Chiba 277-8583, Japan

⁶Centre for Gravitational Physics and Quantum Information, Yukawa Institute for Theoretical Physics, Kyoto University, Kyoto 606-8502, Japan

⁷Department of Astronomy, University of Arizona, AZ 85721, USA

Summary

According to the concordance cosmological theory, structure formation and evolution proceeds hierarchically in the Universe. Smaller-scale dark matter structures gravitationally collapse first everywhere in the Universe, then merge into larger-scale structures. Such dense gravitationally bound structures of dark matter are called halos. Halos can host smaller halos, so-called subhalos (or substructures). Cosmological N -body simulations are vital in understanding the formation and evolution of halos and subhalos. Halo/subhalo finders are a post-processing step to identify those dense structures in the particle dataset of cosmological N -body simulations.

MPI-Rockstar ¹ is a massively parallel halo finder based on the Rockstar ² phase-space temporal halo finder code (Behroozi et al., 2013), which is one of the most extensively used halo finding codes. Compared to the original code, parallelized by a primitive socket communication library, we parallelized it in a hybrid way using MPI and OpenMP, which is suitable for analysis on the hybrid shared and distributed memory environments of modern supercomputers. This

^{*}ishiyama@chiba-u.jp

¹<https://github.com/Tomoaki-Ishiyama/mpi-rockstar/>

²<https://bitbucket.org/gfcstanford/rockstar/>

implementation can easily handle the analysis of more than a trillion particles on more than 100,000 parallel processes, enabling the production of a huge dataset for the next generation of cosmological surveys.

Statement of need

Owing to the advance of supercomputing power and highly scalable parallel gravitational N -body codes (e.g., Ishiyama et al., 2009; Ishiyama et al., 2012; Potter et al., 2017; Wang et al., 2018; Garrison et al., 2021), the number of particles in recent massive cosmological simulations exceeds a trillion (e.g., Potter et al., 2017; Ishiyama et al., 2021; Wang et al., 2022), posing significant challenges for halo finding. Several halo finding algorithms have been suggested (Knebe et al., 2013), and some of their implementation are publicly available. (e.g., Knollmann & Knebe, 2009; Behroozi et al., 2013; Elahi et al., 2019; Springel et al., 2021) The computational performance of these implementations differs substantially, and they have not been uniformly tested yet on the large-scale hybrid shared and distributed memory environments of modern supercomputers. MPI-Rockstar addresses these issues and is designed to run on more than 100,000 parallel processes in a hybrid way using MPI and OpenMP. As new functions to the original Rockstar code, MPI-Rockstar supports HDF5 as an output format and can output additional halo properties such as the inertia tensor.

Acknowledgements

This work has been supported by IAAR Research Support Program in Chiba University Japan, MEXT/JSPS KAKENHI (Grant Number JP23H04002), MEXT as “Program for Promoting Researches on the Supercomputer Fugaku” (JP-MXP1020230406 and JPMXP1020230407), and JICFuS. Numerical computations were carried out on the supercomputer Fugaku provided by the RIKEN Center for Computational Science (Project ID: hp230173, and hp240184).

References

- Behroozi, P. S., Wechsler, R. H., & Wu, H.-Y. 2013, *Astrophys. J.*, 762, 109, doi: 10.1088/0004-637X/762/2/109
- Elahi, P. J., Cañas, R., Poulton, R. J. J., et al. 2019, *Publications of the Astronomical Society of Australia*, 36, e021, doi: 10.1017/pasa.2019.12
- Garrison, L. H., Eisenstein, D. J., Ferrer, D., Maksimova, N. A., & Pinto, P. A. 2021, *Mon. Not. R. Astron. Soc.*, 508, 575, doi: 10.1093/mnras/stab2482
- Ishiyama, T., Fukushige, T., & Makino, J. 2009, *Publ. of the Astron. Society of Japan*, 61, 1319, doi: 10.1093/pasj/61.6.1319
- Ishiyama, T., Nitadori, K., & Makino, J. 2012, in Proc. Int. Conf. High Performance Computing, Networking, Storage and Analysis, SC’12 (Los Alamitos, CA: IEEE Computer Society Press), 5:, (arXiv:1211.4406). <http://dl.acm.org/citation.cfm?id=2388996.2389003>

- Ishiyama, T., Prada, F., Klypin, A. A., et al. 2021, *Mon. Not. R. Astron. Soc.*, 506, 4210, doi: 10.1093/mnras/stab1755
- Knebe, A., Pearce, F. R., Lux, H., et al. 2013, *Mon. Not. R. Astron. Soc.*, 435, 1618, doi: 10.1093/mnras/stt1403
- Knollmann, S. R., & Knebe, A. 2009, *Astrophys. J.Supp.*, 182, 608, doi: 10.1088/0067-0049/182/2/608
- Potter, D., Stadel, J., & Teyssier, R. 2017, Computational Astrophysics and Cosmology, 4, 2, doi: 10.1186/s40668-017-0021-1
- Springel, V., Pakmor, R., Zier, O., & Reinecke, M. 2021, *Mon. Not. R. Astron. Soc.*, 506, 2871, doi: 10.1093/mnras/stab1855
- Wang, Q., Cao, Z.-Y., Gao, L., et al. 2018, Research in Astronomy and Astrophysics, 18, 062, doi: 10.1088/1674-4527/18/6/62
- Wang, Q., Gao, L., & Meng, C. 2022, *Mon. Not. R. Astron. Soc.*, 517, 6004, doi: 10.1093/mnras/stac3072