Structured Speaker-Deficiency Adaptation of Foundation Models for Dysarthric and Elderly Speech Recognition

Shujie Hu¹, Xurong Xie², Mengzhe Geng³, Jiajun Deng¹, Zengrui Jin¹, Tianzi Wang¹, Mingyu Cui¹

Guinan Li¹, Zhaoqing Li¹, Helen Meng¹, Xunying Liu¹

1 *The Chinese University of Hong Kong, Hong Kong SAR, China*

2 *Institute of Software, Chinese Academy of Sciences, Beijing, China*

³*National Research Council of Canada, Canada*

Abstract—Data-intensive fine-tuning of speech foundation models (SFMs) to scarce and diverse dysarthric and elderly speech leads to data bias and poor generalization to unseen speakers. This paper proposes novel structured speaker-deficiency adaptation approaches for SSL pretrained SFMs on such data. Speaker and speech deficiency invariant SFMs were constructed in their supervised adaptive fine-tuning stage to reduce undue bias to training data speakers, and serves as a more neutral and robust starting point for test time unsupervised adaptation. Speech variability attributed to speaker identity and speech impairment severity, or aging induced neurocognitive decline, are modelled using separate adapters that can be combined together to model any seen or unseen speaker. Experiments on the UASpeech dysarthric and Dementia-Bank Pitt elderly speech corpora suggest structured speaker-deficiency adaptation of HuBERT and Wav2vec2-conformer models consistently outperforms baseline SFMs using either: a) no adapters; b) global adapters shared among all speakers; or c) single attribute adapters modelling speaker or deficiency labels alone by statistically significant WER reductions up to 3.01% and 1.50% absolute (10.86% and 6.94% relative) on the two tasks respectively. The lowest published WER of 19.45% (49.34% on very low intelligibility, 33.17% on unseen words) is obtained on the UASpeech test set of 16 dysarthric speakers.

Index Terms—Foundation Model, Speaker Adaptation, Dysarthric Speech, Elderly Speech

I. INTRODUCTION

Despite the rapid progress of ASR technologies targeting normal and healthy users, their application to those suffering from speech disorders remains a challenging task to date [\[1\]](#page-4-0)–[\[8\]](#page-4-1). Neurocognitive disorders, such as Alzheimer's disease (AD), are often found among older adults and manifest themselves in speech and language deficiency such as weakened neuro-motor control in speech production and imprecise articulation [\[9\]](#page-4-2), [\[10\]](#page-4-3). ASR-based assistive technology plays a vital role in not only improving their quality of life and social inclusion, but also facilitating large-scale automatic early diagnosis of neurocognitive impairment and preventive care [\[4\]](#page-4-4), [\[11\]](#page-4-5)–[\[14\]](#page-4-6).

Elderly and dysarthric speech bring challenges on all fronts to current deep learning based ASR technologies predominantly targeting non-aged, healthy adult users: 1) large mismatch between such data and non-aged, healthy adult voices; 2) data scarcity [\[3\]](#page-4-7), [\[15\]](#page-4-8); and 3) data diversity including accent or gender, and speech deficiency brought by: 1) speech disorders such as dysarthria; and 2) aging induced neurocognitive decline [\[16\]](#page-4-9), [\[17\]](#page-4-10). For example, dysarthric speakers of very low speech intelligibility exhibit more discriminative patterns of articulatory imprecision, decreased volume and clarity, changes in pitch, increased dysfluencies and slower speaking rate, while those diagonalized with mid or high speech intelligibility are closer to normal speakers. Such diversity among dysarthric or elderly speakers hinders not only speaker-independent ASR system training or fine-tuning on such data, but also their fine-grained personalization to individual users' voices. This issue is even more challenging when fine-tuning self-supervised learning (SSL) speech foundation models (SFMs) [\[18\]](#page-4-11)–[\[20\]](#page-4-12) that contain a large number of parameters.

Recently, test time training [\[21\]](#page-4-13), [\[22\]](#page-4-14) has been successfully applied to large language models (LLMs) adaptation tasks. Such techniques are closely related to the test time unsupervised speaker adaptation techniques that were widely employed across generations of ASR systems [\[23\]](#page-4-15)–[\[26\]](#page-4-16) including both hybrid and end-to-end (E2E) models [\[3\]](#page-4-7), [\[27\]](#page-4-17). However, their application to foundation models for ASR tasks remains under explored to date.

Data-intensive supervised fine-tuning of speech foundation models to the highly scarce dysarthric and elderly speech training data rapidly leads to data bias and poor generalization to unseen speakers. In order to perform effective test time unsupervised adaptation of SSL models to arbitrary unseen speakers, it is vital to first construct a more speaker and speech deficiency invariant SSL model during their supervised fine-tuning stage to reduce the undue bias to training data speakers, and serves as a more neutral and robust starting point for test time unsupervised adaptation, akin to the use of well-established speaker adaptive training (SAT) [\[3\]](#page-4-7), [\[23\]](#page-4-15), [\[24\]](#page-4-18), [\[26\]](#page-4-16), [\[28\]](#page-4-19) approaches. Furthermore, SAT based supervised fine-tuning of SSL models using highly diverse dysarthric and elderly speech data of varying degrees of speech disorder severity and speaker level attributes, such gender and age [\[3\]](#page-4-7), [\[5\]](#page-4-20), [\[27\]](#page-4-17) requires their multifaceted sources of variability to be modelled using separate adapters in a structured manner.

To this end, novel structured speaker-deficiency adaptation approaches are proposed in this paper for SSL pre-trained speech foundation models. Speaker and speech deficiency invariant SFMs were constructed in their supervised adaptive fine-tuning stage (i.e., system training) to reduce undue bias to training data speakers, and serves as a more neutral and robust starting point for test time unsupervised adaptation. Speech variability attributed to speaker identity and speech impairment severity, or aging induced neurocognitive decline, are modelled using separate adapters that can be combined together to model any seen or unseen speaker.

Experiments on the benchmark UASpeech [\[29\]](#page-4-21) dysarthric and DementiaBank Pitt [\[30\]](#page-4-22) elderly speech corpora suggest structured speaker-deficiency adaptation of large HuBERT [\[20\]](#page-4-12) and Wav2vec2 conformer [\[18\]](#page-4-11) models consistently outperforms baseline SFMs using either: a) no adapters; b) global adapters shared among all speakers; or c) single attribute adapters modelling speaker or deficiency labels alone by statistically significant WER reductions up to 3.01% and 1.50% absolute (10.86% and 6.94% relative) on the two tasks respectively. The lowest published WERs of 19.45% (49.34% on very low intelligibility, 33.17% on unseen words) and 17.45% are obtained after applying the proposed structured speaker-deficiency adaptation approach on a stronger baseline SFM [\[15\]](#page-4-8), [\[31\]](#page-4-23) obtained using cross-system multi-pass rescoring.

The main contributions of the paper are summarized below:

1) To the best of our knowledge, this paper presents the first work to apply test time unsupervised adaptation to SFMs for dysarthric and

Fig. 1. Examples of SSL pre-trained SFM (grey box, sub-figure (a)) adaptation using either speaker identity alone via c) speaker-dependent LHUC, or d) structured speaker-deficiency adapters. The adapter can be inserted either 1) after the CNN encoder (sub-figure (a)); or 2) in a specific transformer block (sub-figure (b))."LN", "MHSA", "DP" and "FF" are layernorm, multi-head self-attention, dropout and feedforward modules. .

elderly speech recognition. In contrast, previous researches utilizing test time unsupervised adaptation were conducted on hybrid and endto-end (E2E) ASR systems [\[3\]](#page-4-7), [\[27\]](#page-4-17), while speaker adaptation on SSL SFM was performed in a supervised manner [\[32\]](#page-4-24).

2) This paper presents the first work to apply supervised adaptive finetuning on SFMs to produce a more neutral and robust starting point for test time unsupervised adaptation. In contrast, previous studies on this approach were conducted on hybrid and E2E ASR systems [\[3\]](#page-4-7), [\[5\]](#page-4-20), [\[27\]](#page-4-17).

3) This paper pioneers novel structured speaker-deficiency adaptation approaches for SFMs. In contrast, prior researches in this direction significantly differ from this work by either: a) using speaker identity alone in in-domain data trained non-SSL based ASR systems [\[3\]](#page-4-7), [\[5\]](#page-4-20), $[27]$, $[33]$ – $[35]$, or SSL foundation model adaptation $[32]$; or **b**) using speaker-deficiency information when adapting non-SSL, traditional hybrid TDNNs [\[36\]](#page-4-27).

4) The best performing structured speaker-deficiency adapted Hu-BERT produces the lowest published WER of 19.45% (49.34% on very low intelligibility, 33.17% on unseen words) on the benchmark UASpeech test set.

II. SSL PRE-TRAINED ASR MODELS

Speech SSL models such as Wav2vec2.0 [\[18\]](#page-4-11), HuBERT [\[20\]](#page-4-12), and WavLM [\[19\]](#page-4-28) share similar Transformer backbones with supervised models. For example, Wav2vec2.0 consists of three components, including 1) a multi-layer CNN-based feature encoder; 2) an L-layers transformer-based context network; and 3) a quantization module. In this paper, we fine-tune the pre-trained Wav2vec2.0 model and HuBERT model with a pure CTC decoder.

III. ADAPTER BASED TEST TIME UNSUPERVISED ADAPTATION

1. Adapter Architecture: LHUC/HUB adapters provide parameterefficient and compact representations of the variability among dysarthric or elderly speakers [\[3\]](#page-4-7), [\[25\]](#page-4-29), [\[27\]](#page-4-17), [\[37\]](#page-4-30). The key idea of LHUC adaptation is to use a speaker-dependent (SD) scaling vector to modify the amplitudes of activation outputs. Let $r^{l,s}$ denotes the SD parameters for speaker s in the l -th hidden layer, the hidden outputs adapted to the speaker s is given as $h^{l,s} = \xi(r^{l,s}) \odot h^l$. where $h^l \in \mathbb{R}^m$ is the hidden outputs of *l*-th layer, \odot denotes the Hadamard product operation, and $\xi(\cdot)$ is the element-wise $2 \times Sigmoid(\cdot)$ function. An example of incorporating LHUC into SSL pre-trained SFMs is shown in Fig. 1(c). HUB adaptation is similar to LHUC. Speaker-adapted hidden outputs can be given by $h^{l,s} = r^{l,s} + h^l$.

Residual Adapter Blocks (RAB) have been developed as a general parameter-efficient technique for pre-trained model fine-tuning [\[32\]](#page-4-24), [\[38\]](#page-4-31)–[\[40\]](#page-4-32). Let $f(\cdot; \Theta_{l,s})$ denote the residual adapter function for speaker s in the l -th layer, the adapted hidden outputs conditioned on the speaker are expressed by

$$
\boldsymbol{h}^{l,s} = f(\boldsymbol{h}^l; \boldsymbol{\Theta}_{l,s}) + \boldsymbol{h}^l,\tag{1}
$$

$$
f(\boldsymbol{h}^{l};\boldsymbol{\Theta}_{l,s}) = \text{LN}(\text{DP}(\boldsymbol{P}_{l,s}^{u}\zeta(\boldsymbol{P}_{l,s}^{d}\boldsymbol{h}^{l})))
$$
\n(2)

where $\Theta_{l,s}$ is the learnable SD parameters in the residual adapter. An RAB consists of a down-linear projection $\boldsymbol{P}^d_{l,s} \in \mathbb{R}^{k \times m}$, a GeLU activation function $\zeta(\cdot)$, an up-linear projection $P_{l,s}^u \in \mathbb{R}^{m \times k}$, a dropout operation $DP(\cdot)$ and a layer-norm operation $LN(\cdot)$.

Structured speaker-deficiency RAB can separately model the rich sources of heterogeneity attributed to speaker identity and speech deficiency labels. As shown in Fig. 1(d), the final adapted hidden outputs are given by

$$
\boldsymbol{h}^{l,sd} = f(\boldsymbol{h}^l; \boldsymbol{\Theta}_{l,sd}) + \boldsymbol{h}^l, \boldsymbol{h}^{l,sd,s} = f(\boldsymbol{h}^{l,sd}; \boldsymbol{\Theta}_{l,s}) + \boldsymbol{h}^{l,sd} \quad (3)
$$

where $\Theta_{l,sd}$ denotes the speech deficiency conditioned adapter parameters for speakers labelled with a particular speech deficiency "sd" in the *l*-th hidden layer.

2. Adapter Labels: To investigate adaptation labels at different fine-grained levels, several adapter labels are used during test time unsupervised adaptation, including a) global level label, i.e., all speakers are classified into one category; b) speech impairment severity, or aging induced neurocognitive decline (speech deficiency) labels; c) speaker labels; and d) structured speaker-deficiency labels. 3. Adapter Supervision and Estimation: The overall procedure of test time unsupervised adaptation of foundation models using structured speaker-deficiency adapters is shown in Fig. 2(iii). Let $\mathcal{D}^{sd,s} = \{X^{sd,s}, Y^{sd,s}\}\$ denote the data set for speaker s whose speech deficiency label is sd, where $X^{sd,s}$ and $Y^{sd,s}$ are the waveform and the corresponding supervision token sequences, respectively. Test time unsupervised adaptation is performed to speaker data initially without any speech transcription or speech deficiency labels provided. The speech deficiency labels of test data speakers are automatically predicted using the well-trained spectro-temporal embedding features based neural network classifiers [\[5\]](#page-4-20), [\[36\]](#page-4-27). The hypothesis supervision $\hat{\mathbf{Y}}^{sd,s}$ for adaptation is generated by initially decoding the test data using the baseline SSL foundation model finetuned to all the in-domain training data (Fig. 2(ii)). The parameters of speech deficiency conditioned adapter $\hat{\Theta}_{sd}$, and speaker identity dependent adapters, $\hat{\Theta}_s$, are estimated in turn using the CTC loss,

$$
\{\hat{\Theta}_{sd}\} = \underset{\{\Theta_{sd}\}}{\arg \min} \{\mathcal{L}_{CTC}(\mathcal{D}^{sd}; \Theta_{sd})\}
$$
(4)

$$
\{\hat{\Theta}_s\} = \underset{\{\Theta_s\}}{\text{arg min}} \{ \mathcal{L}_{CTC}(\mathcal{D}^{sd,s}; \hat{\Theta}_{sd}, \Theta_s) \} \tag{5}
$$

where \mathcal{D}^{sd} is the union of all the dysarthric or elderly speakers' data that are labelled with a speech deficiency level of "sd", and $\mathcal{D}^{sd,s}$ is the s speaker's data labelled with a speech deficiency level of " sd ".

IV. STRUCTURED SFM ADAPTATION

A. Structured SFM Supervised Adaptive Fine-tuning

Adaptive training (AT) [\[23\]](#page-4-15), [\[24\]](#page-4-18) is a well-established family of techniques that model heterogeneity in natural speech. By representing factors of speech variability, e.g. speaker identity, using separate parameters based on, e.g. MLLR, CMLLR, LHUC transforms or adapters, AT produces canonical models independent of both speaker identity and speech deficiency during the supervised training stage, which serves as a more neutral and robust starting point than standard non-AT models for test time unsupervised adaptation. Their effectiveness has been widely demonstrated across generations of

Fig. 2. Examples of i) adaptive training using structured speaker-deficiency adapters; ii) baseline fine-tuning; and iii) test time unsupervised adaptation using structured speaker-deficiency adapters. During adaptive training and test time adaptation, the parameters of the speech deficiency conditioned adapter and the speaker identity dependent adapter are estimated in turn in two stages.

ASR systems from HMM, hybrid DNN to end-to-end systems [\[23\]](#page-4-15)– [\[25\]](#page-4-29), [\[28\]](#page-4-19). In our paper, the proposed form of structured speakerdeficiency supervised adaptive fine-tuning (AFT), akin to the use of well-established adaptive training, enhances the speaker and speech deficiency invariance of SFMs.

The adapter architectures used during structured SFM supervised adaptive fine-tuning are also LHUC/HUB, RAB and structured speaker-deficiency RAB, while the adapter labels encompass speech deficiency labels, speaker level labels, and structured speakerdeficiency labels. The overall procedure of structured SFM supervised adaptive fine-tuning using speaker-deficiency adapters is shown in Fig. 2 (i). The supervision of supervised adaptive fine-tuning are ground truth speech transcript, and the speech deficiency and speaker identity conditioned adapters are optimized in turn and tightly integrated with the backbone foundation model parameters fine-tuned to multi-speaker in-domain training data.

B. Test Time Unsupervised Adaptation on AFT Model

The adapter architectures, adapter labels, and adapter supervision are identical to those described in Sec. III. After structured supervised AFT, the canonical foundation model is independent of both speaker identity and speech deficiency, providing a more neutral and robust starting point compared to standard non-AFT models.

V. EXPERIMENTS

A. Task Description

The UASpeech corpus [\[29\]](#page-4-21) is the largest publicly available dysarthric speech corpus consisting of 16 dysarthric and 13 control speakers, and contains 155 common words and 300 uncommon words. The entire corpus is further divided into 3 subset blocks per speaker. The same set of 155 common words is used in all three blocks, while the uncommon words in each block differ. The data

TABLE I

PERFORMANCE OF HUBERT SYSTEMS WITHOUT OR WITH STRUCTURED SPEAKER (SPK.) DEFICIENCY (DEFI.) ADAPTATION ON UASPEECH. LHUC OR RAB ARE INSERTED AT DIFFERENT LAYER POSITIONS (POS.), WHERE "0" STANDS FOR BEING AFTER THE CNN ENCODER (AS SHOWN IN FIG $1(A)$), WHILE OTHER NUMBERS DENOTE A POSITION IN THE x -TH TRANSFORMER BLOCK (AS SHOWN IN FIG 1(B)). "VL/L/M/H" REFERS TO INTELLIGIBILITY SUBGROUPS. "PARAM." IS THE NUMBER OF ADAPTER PARAMETERS. "STRU.", "ADA. ARC." AND "SUP." STAND FOR

"STRUCTURED", "ADAPTER ARCHITECTURE" AND "SUPERVISION".

from Block 1 and 3 of all the 29 speakers are used as the training set, while the data of Block 2 of all the 16 dysarthric speakers serves as the test set. After removing excessive silence and speed perturbation based data augmentation [\[41\]](#page-4-33), a total of 130.1 hours of audio data is used as the training set, while 9 hours of speech is used for evaluation. The DementiaBank Pitt [\[30\]](#page-4-22) corpus is the largest publicly available elderly speech corpus designed for speech-based Alzheimer's Disease (AD) diagnosis. It contains about 33 hours of audio recorded over AD assessment interviews between 292 elderly participants and clinical investigators. After silence stripping and data augmentation, the training data is increased to 58.9 hours, while the development and evaluation sets contain 2.5 hours and 0.6 hours of audio respectively. There is no overlapping between the elderly speakers in the training, development and evaluation sets. The test data word coverage rates of UASpeech and DementiaBank are 61% and 98.7%.

B. Experimental Setup

The pre-trained models on UASpeech and DementiaBank corpora are the large HuBERT model^{[1](#page-2-0)} and Wav2vec2-conformer model with relative position embeddings^{[2](#page-2-1)} respectively. They are selected as the strongest baseline foundation model for each task, following the prior work [\[15\]](#page-4-8). The bottleneck dimensionality of the deficiencyconditioned RAB is empirically set as 256 for both UASpeech and DementiaBank. While the bottleneck dimensionality of the speaker identity-conditioned RAB is set to 256 for UASpeech and 128 for DementiaBank. This difference is due to UASpeech having more speaker-level data (2025 seconds per speaker) compared to DementiaBank (76 seconds per speaker).

C. Implementation Issues & Ablation Studies

Two key implementation issues affecting the performance of both non-structured and structured SFM adaptation are investigated. These include: a) the position of the adapter; and b) the architecture of the adapter. From the ablation study results in Table I^3 I^3 , several trends can be observed: 1) Among all non-structured speaker-adapted or

¹huggingface.co/facebook/hubert-large-ls960-ft

²huggingface.co/facebook/wav2vec2-conformer-rel-pos-large-960h-ft

³The speech deficiency labels of the test set speakers are automatically predicted using the well-trained spectro-temporal embedding feature based neural network classifiers [\[5\]](#page-4-20), [\[36\]](#page-4-27), while test set speaker identity labels are provided during test-time unsupervised adaptation.

TABLE II

PERFORMANCE OF HUBERT AND WAV2VEC2-CONFORMER SYSTEMS CONSTRUCTED WITHOUT OR WITH STRUCTURED SPEAKER-DEFICIENCY ADAPTATION ON THE TEST SET OF UASPEECH DYSARTHRIC SPEECH, AS WELL AS DEVELOPMENT (DEV.) AND EVALUATION (EVAL.) SETS OF DEMENTIABANK PITT ELDERLY SPEECH RESPECTIVELY. "INV." AND "PAR." REFER TO CLINICAL INVESTIGATORS AND ELDERLY PARTICIPANTS. SYS.2∗, 9[∗] ARE THE UPPER BOUND OF SYS.2,9 RESPECTIVELY, WHICH USE THE GROUND TRUTH SPEECH TRANSCRIPT AS SUPERVISION DURING TEST TIME ADAPTATION. $\dagger,$ * and $^\Delta$ denote statistically significant (MAPSSWE [\[42\]](#page-4-34), α = 0.05) differences obtained against the baseline FINE-TUNED, NON-STRUCTURED SPEAKER OR DEFICIENCY ALONE ADAPTED ASR SYSTEMS (SYS. 1,5,7).

deficiency-adapted systems, inserting the LHUC and RAB adapters respectively after the CNN encoder and in the 2^{nd} Transformer block produces the best performance (Sys.2 vs. 3-6; Sys.9 vs. 8,10; Sys. 13 vs. 12). 2) The best-performing structured speaker-deficiency adapted system is obtained when both speaker and deficiency RAB adapters are located immediately after the CNN encoder (Sys.1[4](#page-3-0) vs. $15-17$)⁴.

D. Main Results On UASpeech Dysarthric Data

From the results in Table [II](#page-3-1) on UASpeech dataset, there are several trends can be found: 1) All non-structured speaker or deficiency alone adapted systems, and those using the proposed structured speaker-deficiency adaptation outperform the baseline in-domain multi-speaker data fine-tuned HuBERT and that using global (test set level) adapters (Sys.3-9 vs. 1,2).

2) Non-structured RAB-based speaker or deficiency alone adapted systems (highlighted in orange) outperform the baseline HuBERT with statistically significant WER reductions of 2.59% and 2.20% absolute (9.35% and 7.94% relative) respectively (Sys.5, 7 vs. 1).

3) The structured speaker-deficiency adapted system (highlighted in red) outperforms the baseline fine-tuned Large HuBERT model, as well as non-structured speaker or deficiency alone adapted systems by statistically significant WERs up to 3.01% absolute (10.86% relative, Sys.9 vs. 1,5,7).

4) Non-structured and structured SFM adaptive fine-tuning produce a more neutral and robust starting point than standard non-AFT models for test time unsupervised adaptation. It improves performance up to 1.79% absolute (7.24% relative, Sys.5,7,9 vs. 4,6,8).

5) After applying the proposed structured speaker-deficiency adaptation approach (Sys. 9A) on a stronger baseline SFM [\[15\]](#page-4-8), [\[31\]](#page-4-23) obtained using cross-system rescoring (Sys. 1A), the lowest published WER of 19.45% on all the 16 dysarthric speakers (49.34% on very low intelligibility, 33.17% on unseen words, highlighted in blue) is obtained. The performance improvements over the baseline in-domain data fine-tuned HuBERT (Sys. 9 vs 1) are also retained after crosssystem rescoring based system combination (Sys. 9A vs. 1A).

Finally, the performance of our best system (Sys. 9A, Table [II,](#page-3-1) in blue) is contrasted against recently published state-of-the-art results on UASpeech in Table [III.](#page-3-2) All the systems follow the same block-based training-evaluation protocol^{[5](#page-3-3)}.

⁵Block 1+3 data used in training, all the 16 dysarthric speakers of Block 2 for evaluation [\[1\]](#page-4-0), [\[29\]](#page-4-21), [\[43\]](#page-4-35), [\[44\]](#page-4-36).

TABLE III WERS OF PUBLISHED AND OUR BEST SYSTEM ON UASPEECH

System	VI.	All
Sheffield-2020 Fine-tuning CNN-TDNN speaker adaptation [45]	68.24	30.76
CUHK-2021 NAS DNN + Data Aug. + LHUC-SAT + AV fusion [3]	60.30	25.21
CUHK-2022 DNN + Data Aug. + LHUC-SAT + AUV fusion [8]	60.14	24.82
CUHK-2022 DNN + Data Aug. + SBE Adapt + LHUC-SAT [5]	59.30	25.05
BUT-2022 Wav2vec2.0 + fMLLR + xvectors [32]	57.72	22.83
Nagoya Univ.-2022 WavLM [46]	71.50	51.80
FAU-2022 Cross-lingual XLSR + Conformer [47]	62.00	26.10
CUHK-2023 Kaldi TDNN + VAE-GAN + LHUC-SAT [48]	57.31	27.78
CUHK-2024 HuBERT + sys. comb. [15]	50.70	20.56
HuBERT + structured adapt. + sys. comb. (Sys. 9A, Table II, ours)	49.34	19.45

E. Results On DementiaBank Elderly Speech

The following trends consistent with those found on the dysarthric UASpeech data in Table [II](#page-3-1) are also observed on DementiaBank (100% test set speakers unseen in training): 1) Structured speakerdeficiency adaptation (highlighted in red) outperforms all of the comparable speaker or deficiency alone adapted systems (Sys.9 vs. 3,5,7), and the baseline fine-tuned Wav2vec2-conformer system by statistically significant WER reductions of 1.50% absolute (6.94% relative, Sys.9 vs. 1). 2) After applying the proposed structured speaker-deficiency adaptation approach (Sys. 9A) on a stronger baseline SFM [\[15\]](#page-4-8), [\[31\]](#page-4-23) (Sys. 1A), a new state-of-the-art overall WER of 17.45% is obtained on the combined DementiaBank development and evaluation sets (highlighted in blue).

VI. CONCLUSION

This paper proposes novel structured speaker-deficiency adaptation approaches for SSL pre-trained SFMs on dysarthric and elderly speech data. Speaker and speech deficiency invariant SFMs were constructed in their supervised adaptive fine-tuning stage to reduce undue bias to training data speakers, and serves as a more neutral and robust starting point for test time unsupervised adaptation. Speech variability attributed to speaker identity and speech impairment severity, or aging induced neurocognitive decline, are modelled using separate adapters that can be combined together to model any seen or unseen speaker. Consistent performance improvements are obtained over the baseline fine-tuned HuBERT and Wav2vec2-conformer models by statistically significant WER reductions of 3.01% and 1.50% absolute (10.86% and 6.94% relative) on the benchmark UASpeech and DementiaBank Pitt test sets respectively. New state-of-the-art WERs are also obtained on both tasks. Future research will study the rapid and online adaptation of pre-trained ASR models for dysarthric and elderly speakers.

⁴This may be because the outputs of the lower positioned CNNs exhibit greater variability for structured adaptation to fully exploit, when compared with the outputs produced by the higher positioned Transformer blocks.

REFERENCES

- [1] S. Sehgal *et al.*, "Model adaptation and adaptive training for the recognition of dysarthric speech," in *SLPAT*, 2015.
- [2] F. Xiong *et al.*, "Deep learning of articulatory-based representations and applications for improving dysarthric speech recognition," in *ITG-Symposium*. VDE, 2018, pp. 1–5.
- [3] S. Liu et al., "Recent Progress in the CUHK Dysarthric Speech Recognition System," *TASLP*, vol. 29, pp. 2267–2281, 2021.
- [4] Z. Ye *et al.*, "Development of the CUHK Elderly speech recognition system for neurocognitive disorder detection using the dementiabank corpus," in *ICASSP*. IEEE, 2021, pp. 6433–6437.
- [5] M. Geng *et al.*, "Speaker adaptation using spectro-temporal deep features for dysarthric and elderly speech recognition," *TASLP*, vol. 30, pp. 2597– 2611, 2022.
- [6] Z. Yue *et al.*, "Acoustic Modelling From Raw Source and Filter Components for Dysarthric Speech Recognition," *TASLP*, vol. 30, pp. 2968–2980, 2022.
- [7] S. Hu *et al.*, "Exploiting Cross-Domain And Cross-Lingual Ultrasound Tongue Imaging Features For Elderly And Dysarthric Speech Recognition," in *INTERSPEECH*, 2023, pp. 2313–2317.
- [8] S. Hu, S. Liu *et al.*, "Exploiting Cross Domain Acoustic-to-articulatory Inverted Features for Disordered Speech Recognition," in *ICASSP*. IEEE, 2022, pp. 6747–6751.
- [9] A. König et al., "Fully automatic speech-based analysis of the semantic verbal fluency task," *Dementia and geriatric cognitive disorders*, 2018.
- [10] A. Association, "2019 Alzheimer's disease facts and figures," *Alzheimer's & dementia*, 2019.
- [11] C. P. Ferri *et al.*, "Global prevalence of dementia: a Delphi consensus study," *The lancet*, vol. 366, pp. 2112–2117, 2005.
- [12] F. Rudzicz *et al.*, "Speech recognition in Alzheimer's disease with personal assistive robots," in *SLPAT*, 2014, pp. 20–28.
- [13] L. Zhou *et al.*, "Speech Recognition in Alzheimer's Disease and in its Assessment." in *INTERSPEECH*, 2016, pp. 1948–1952.
- [14] B. Mirheidari *et al.*, "Dementia detection using automatic analysis of conversations," *Computer Speech & Language*, vol. 53, pp. 65–79, 2019.
- [15] S. Hu et al., "Self-Supervised ASR Models and Features for Dysarthric and Elderly Speech Recognition," *TASLP*, vol. 32, pp. 3561–3575, 2024.
- [16] I. Kodrasi and H. Bourlard, "Spectro-temporal sparsity characterization for dysarthric speech detection," *TASLP*, vol. 28, pp. 1210–1222, 2020.
- [17] B. L. Smith *et al.*, "Temporal characteristics of the speech of normal elderly adults," *JSLHR*, vol. 30, pp. 522–529, 1987.
- [18] A. Baevski et al., "wav2vec 2.0: A framework for self-supervised learning of speech representations," *Advances in NeuralIPS*, vol. 33, pp. 12 449–12 460, 2020.
- [19] S. Chen *et al.*, "Wavlm: Large-scale self-supervised pre-training for full stack speech processing," *JSTSP*, vol. 16, pp. 1505–1518, 2022.
- [20] W.-N. Hsu *et al.*, "Hubert: Self-supervised speech representation learning by masked prediction of hidden units," *TASLP*, vol. 29, pp. 3451–3460, 2021.
- [21] Y. Gandelsman et al., "Test-Time Training with Masked Autoencoders," in *NIPS*, A. H. Oh, A. Agarwal, D. Belgrave, and K. Cho, Eds., 2022. [Online]. Available:<https://openreview.net/forum?id=SHMi1b7sjXk>
- [22] Y. Sun *et al.*, "Learning to (learn at test time): Rnns with expressive hidden states," *arXiv preprint arXiv:2407.04620*, 2024.
- [23] T. Anastasakos et al., "A compact model for speaker-adaptive training," in *ICSLP*, vol. 2. IEEE, 1996, pp. 1137–1140.
- [24] M. J. Gales, "Maximum likelihood linear transformations for HMMbased speech recognition," *Computer speech & language*, vol. 12, no. 2, pp. 75–98, 1998.
- [25] P. Swietojanski *et al.*, "Learning hidden unit contributions for unsupervised acoustic model adaptation," *TASLP*, vol. 24, pp. 1450–1463, 2016.
- [26] X. Xie et al., "BLHUC: Bayesian Learning of Hidden Unit Contributions for Deep Neural Network Speaker Adaptation," in *ICASSP*, 2019, pp. 5711–5715.
- [27] M. Geng *et al.*, "On-the-Fly Feature Based Rapid Speaker Adaptation for Dysarthric and Elderly Speech Recognition," in *INTERSPEECH*, 2023, pp. 1753–1757.
- [28] J. Deng *et al.*, "Confidence score based speaker adaptation of conformer speech recognition systems," *TASLP*, vol. 31, pp. 1175–1190, 2023.
- [29] H. Kim et al., "Dysarthric speech database for universal access research," in *INTERSPEECH*, 2008, pp. 1741–1744.
- [30] J. T. Becker *et al.*, "The natural history of Alzheimer's disease: description of study cohort and accuracy of diagnosis," *Archives of neurology*, vol. 51, pp. 585–594, 1994.
- [31] S. Hu *et al.*, "Exploring Self-supervised Pre-trained ASR Models For Dysarthric and Elderly Speech Recognition," in *ICASSP*. IEEE, 2023, pp. 1–5.
- [32] M. K. Baskar *et al.*, "Speaker adaptation for Wav2vec2 based dysarthric ASR," in *INTERSPEECH*, 2022, pp. 3403–3407.
- [33] R. Takashima, T. Takiguchi, and Y. Ariki, "Two-Step Acoustic Model Adaptation for Dysarthric Speech Recognition," in *ICASSP*, 2020, pp. 6104–6108.
- [34] J. Shor et al., "Personalizing ASR for Dysarthric and Accented Speech with Limited Data," in *INTERSPEECH*, 2019, pp. 784–788.
- [35] J. Qi and H. V. hamme, "Parameter-efficient Dysarthric Speech Recognition Using Adapter Fusion and Householder Transformation," in *INTRESPEECH*, 2023, pp. 151–155.
- [36] M. Geng et al., "Use of Speech Impairment Severity for Dysarthric Speech Recognition," in *INTERSPEECH*, 2023, pp. 2328–2332.
- [37] O. Abdel-Hamid and H. Jiang, "Fast speaker adaptation of hybrid NN/HMM model for speech recognition based on discriminative learning of speaker code," in *ICASSP*. IEEE, 2013, pp. 7942–7946.
- [38] B. Thomas *et al.*, "Efficient adapter transfer of self-supervised speech models for automatic speech recognition," in *ICASSP*. IEEE, 2022, pp. 7102–7106.
- [39] R. Fan *et al.*, "Towards better domain adaptation for self-supervised models: A case study of child asr," *JSTSP*, vol. 16, no. 6, pp. 1242– 1252, 2022.
- [40] Z.-C. Chen et al., "Exploring Efficient-Tuning Methods in Self-Supervised Speech Models," in *SLT*, 2023, pp. 1120–1127.
- [41] M. Geng *et al.*, "Investigation of Data Augmentation Techniques for Disordered Speech Recognition." in *INTERSPEECH*, 2020, pp. 696– 700.
- [42] L. Gillick and S. J. Cox, "Some statistical issues in the comparison of speech recognition algorithms," in *ICASSP*. IEEE, 1989, pp. 532–535.
- [43] H. Christensen *et al.*, "Combining in-domain and out-of-domain speech data for automatic recognition of disordered speech." in *INTERSPEECH*, 2013, pp. 3642–3645.
- [44] F. Xiong *et al.*, "Phonetic analysis of dysarthric speech tempo and applications to robust personalised dysarthric speech recognition," in *ICASSP*. IEEE, 2019, pp. 5836–5840.
- [45] F. Xiong, J. Barker *et al.*, "Source domain data selection for improved transfer learning targeting dysarthric speech recognition," in *ICASSP*. IEEE, 2020, pp. 7424–7428.
- [46] L. P. Violeta, W. C. Huang, and T. Toda, "Investigating Self-supervised Pretraining Frameworks for Pathological Speech Recognition," in *IN-TERSPEECH*, 2022, pp. 41–45.
- [47] A. Hernandez et al., "Cross-lingual Self-Supervised Speech Representations for Improved Dysarthric Speech Recognition," in *INTERSPEECH*, 2022, pp. 51–55.
- [48] Z. Jin *et al.*, "Adversarial data augmentation using VAE-GAN for disordered speech recognition," in *ICASSP*, 2023, pp. 1–5.