Graphical Abstract

CoEvo: Continual Evolution of Symbolic Solutions Using Large Language Models

Ping Guo, Qingfu Zhang, Xi Lin

CoEvo: Continual Evolution of Symbolic Solutions Using Large Language Models

Ping Guo^a, Qingfu Zhang^{a,*}, Xi Lin^a

^aCity University of Hong Kong, 83 Tat Chee Avenue, Kowloon Tong, Hong Kong, China

Abstract

Large Language Models (LLMs) have emerged as transformative tools in artificial intelligence, capable of processing and understanding extensive human knowledge to enhance problem-solving across various domains. This paper explores the potential of LLMs to drive the discovery of symbolic solutions within scientific and engineering disciplines, where such solutions are crucial for advancing theoretical and practical applications. We propose a novel framework that utilizes LLMs in an evolutionary search methodology, augmented by a dynamic knowledge library that integrates and refines insights in an open-ended manner. This approach aims to tackle the dual challenges of efficiently navigating complex symbolic representation spaces and leveraging both existing and newly generated knowledge to foster open-ended innovation. By enabling LLMs to interact with and expand upon a knowledge library, we facilitate the continuous generation of novel solutions in diverse forms such as language, code, and mathematical expressions. Our experimental results demonstrate that this method not only enhances the efficiency of searching for symbolic solutions but also supports the ongoing discovery process, akin to human scientific endeavors. This study represents a first effort in conceptualizing the search for symbolic solutions as a lifelong, iterative process, marking a significant step towards harnessing AI in the perpetual pursuit of scientific and engineering breakthroughs. We have open-sourced our code and data, please visit https://github.com/pgg3/CoEvo for more information.

Keywords: Large Language Model, Evolutionary Algorithm, Continual Learning, Knowledge Discovery, Symbolic Solution

^{*}Corresponding Author: qingfu.zhang@cityu.edu.hk

1. Introduction

Large Language Models (LLMs) constitute a significant breakthrough in artificial intelligence (AI), demonstrating remarkable proficiency across various research domains [1, 2, 3]. Their capacity to process and comprehend a wide range of human knowledge significantly contributes to intricate problemsolving tasks. Initially,LLMs assist in extracting critical information from various contexts for inspiring innovative ideas among researchers [4, 5, 6]. Furthermore, recent advancements aim to endow LLMs with fully automated problem-solving capabilities, including operating as autonomous agents in physical environments [7], generating scoring heuristic functions [8, 9], executing automatic prompt engineering for jailbreak attacks [10, 11], and conducting autonomous machine learning [12, 13]. Given these advancements, we believe that LLMs can be deployed in a fully automated manner for developing symbolic solutions to complex systems.

Symbolic systems play a vital role in addressing numerous challenges across diverse scientific and engineering disciplines [14, 15, 16, 17]. In science, they facilitate knowledge transfer between related fields, promoting the development of mathematical models that can contribute to formulating new theories and hypotheses, thereby expediting scientific discovery [18, 19]. Similarly, in engineering, symbolic solutions and their foundational knowledge are instrumental in the design of complex systems. For instance, in circuit design, smaller modules are encapsulated as Intellectual Property (IP) blocks, each serving distinct and specialized functions. These blocks are then assembled to construct larger, more sophisticated systems [20, 21].

Expanding on these foundations, we suggest that the discovery of symbolic solutions significantly benefits from an open-ended process where solutions and foundational knowledge continually co-evolve, akin to the work of human scientists and engineers. As such, an endless process holds many possibilities for new symbolic solutions that contribute to both scientific and engineering domains. It involves endless exploration and adaptation, fostering the emergence of innovative ideas that may be unattainable through conventional methods [22]. In the field of artificial intelligence, open-ended exploration has led to breakthroughs by establishing environments in which algorithms endlessly generate and refine solutions without the constraints of specific, predefined goals [23, 24]. This paradigm not only accelerates

the development of complex systems but also mirrors the iterative essence of human creativity and scientific discovery, where each new discovery leads to further questions and explorations [25].

Despite these insights, no existing studies explicitly tackle the challenge of open-ended evolution and refinement of symbolic solutions. The primary obstacles hindering progress in this area are two-fold: 1) the difficulties of conducting efficient searches on the symbolic representation spaces, which are often NP-hard across multiple domains [26], and more crucially, 2) the absence of methodologies for leveraging existing knowledge and newly generated knowledge to guide the search. While there have been developments in evolutionary search algorithms for symbolic regression [27] and deep learning approaches [28, 29], these primarily address the former challenge in different encoding spaces and overlook the latter, which is vital for open-ended innovation.

This gap could potentially be bridged by employing LLMs, which inherently integrate baseline human knowledge [30]. However, even with the implementation of cutting-edge retrieval-augmented generation (RAG) techniques [31], an important question remains:

Can LLMs actually uncover new knowledge rather than merely replicate existing information? In addition, can LLMs summarize knowledge to support an open-ended search for symbolic solutions akin to human scientific endeavors?

In our study, we conceptualize the search for symbolic solutions as an endless, lifelong process, guided by both existing knowledge and the newly generated knowledge during the search. We propose an LLM-based evolutionary search methodology, augmented by a knowledge library that contains the summarized knowledge from the search process. Throughout this exploration, the LLM interacts with the knowledge library to create novel solutions in multiple spaces, including language, code, mathematical expressions, and logic expressions *etc.*. Our approach resolves the challenge of efficient search by navigating multiple search contexts, and our knowledge library serves as the first trial in answering the question of whether LLMs can discover new knowledge and apply it in an endless search for symbolic solutions. To the best of our knowledge, this represents the pioneering effort to view the discovery of symbolic solutions as a continual open-ended process.

Our contributions are as follows:

• We believe that finding symbolic solutions in domains such as scientific

discovery should be perceived as a continual open-ended process. We make a first attempt to extract knowledge and apply it in the endless search for symbolic solutions for scientific and engineering challenges.

- With this understanding, we propose a framework for harvesting and applying knowledge to search for symbolic solutions in multiple search spaces.
- Our extensive experimental outcomes demonstrate that incorporating the newly generated knowledge enables a lifetime of continual searching for symbolic solutions in scientific and engineering domains.

2. CoEvo

2.1. Overview

This section presents an overview of CoEvo, a framework specifically designed to support a continual open-ended search process for symbolic solutions to a myriad of problems, as illustrated in Figure 1. The CoEvo framework incorporates three distinct elements: 1) a versatile representation of solutions, 2) a tree-based knowledge discovery mechanism, and 3) an evolutionary search methodology equipped with a knowledge repository. Specifically, the framework first defines the solution to the task in a general style, allowing for different formats to enable search in different spaces. Secondly, for the generation of these solutions, we adopt a multi-phased reasoning process with the tree-based idea (knowledge pieces) search process. Finally, the solutions and the discovered ideas co-evolve through the evolutionary search process augmented by a knowledge repository.

2.2. Representations of Solutions.

For any given task, employing various solution formats can facilitate the concurrent exploration of multiple representation spaces. Prior research has demonstrated the effectiveness of conducting parallel searches across natural language and Python code spaces, particularly in code generation tasks [32, 8, 33]. To illustrate, we present examples of several representative formats:

• Natural Language: The basic concept of LLMs are built on the fundamental linguistic domain [34]. This domain is well within the operating capability of LLMs and is central to related research, such as the study of jailbreak attacks[10, 11]. Additionally, language's intimate connection to human intelligence has been noted [35, 36].



Figure 1: An overview of the CoEvo framework.

- Mathematical Formulas: A fundamental representation to convey mathematical functions and equations.
- Python Code: This format is selected because current LLMs are predominantly trained on Python code, boosting their code generation capabilities [37, 38]. Alternative coding languages, including C++ and Verilog, are also feasible in our method. Moreover, code representations facilitate the automatic evaluation of the task [8, 9].
- Logic Expression: A symbolic representation employed to describe complex relationships and regulations, particularly within digital circuits [39].

With these definitions of solution representations, our method can generate comprehensive solutions for a variety of tasks, rather than being restricted to symbolic solutions.

2.3. Tree-based Idea Search Process

To define our solution generation strategy, we first analyze the human problem-solving process as shown in Figure 2(a). Typically, humans generate initial ideas upon encountering a task, then validate these ideas through reasoning. Successful validation leads to implementation and subsequent feedback collection, which refines and iterates the approach.

This human-centric methodology aligns with two key insights from the LLM research domain: 1) the Reason-and-Act approach [7], which mirrors



(a) Human thinking process (b) CoEvo's thinking process.

Figure 2: The idea generation process of human and CoEvo. the iterative reasoning and action cycle, and 2) the multi-phased tree-based search process [40, 41], facilitating the exploration of diverse ideas..

Expanding on these insights, we propose a tree-based idea search process for task solution generation, as illustrated in Figure 2(b). The process initiates with the generation of a diverse set of N_0 initial ideas, serving as the root nodes of our tree structure. At each subsequent k-th level, N_k ideas are developed through direct inference based on the evaluator's feedback and existing ideas. This enhances the initial concepts and forming a network-like structure for deeper refinement.

For the tree-based search, we have opted not to implement an extensive sampling-branching process as outlined in [41] to conserve resources. However, our framework retains full compatibility with such extensions, allowing for future scalability.

At every level, ideas undergo implementation aided by explicit reasoning within the thought sections, articulated through various solution representations as defined in §2.2. The task evaluator plays a crucial role by assessing the viability and effectiveness of these ideas, providing crucial feedback that shapes further iterations. This iterative refinement ensures alignment with task requirements and feasibility.

By integrating these strategies, our approach not only replicates human problem-solving processes but also harnesses the computational capabilities of LLMs to explore a vast array of possibilities, significantly enhancing the potential for innovative solutions across various applications.

2.4. Knowledge Library-enhanced Evolution Process

To enable continual evolution and manage the ideas we have discovered, we adopt a knowledge library-enhanced evolution process for final solution generation, as shown in Figure 1. This process comprises two critical components: 1) the evolution process and 2) the knowledge library, each playing a pivotal role in the solution lifecycle.

2.4.1. Evolution Process

Our implementation of the evolution process adheres to the standard evolutionary steps: initialization, crossover, mutation, and population management.

Initialization. We initiate by randomly generating a set of N solutions as the initial population using the tree-based idea search process in §2.3.

Crossover. We employ two crossover operators—*positive-crossover* and *negative-crossover*. Positive-crossover promotes the generation of solutions similar to parent ideas, whereas negative-crossover fosters the creation of distinctly different solutions, enhancing solution diversity as validated in related research [32, 11, 8].

Mutation. Similarly, mutation of CoEvo is facilitated by *positive-mutation* and *negative-mutation* operators, designed to either reinforce or diverge from the existing solution traits.

Population Update. We maintain the top N solutions with the highest scores as the population for the next generation, ensuring a quality-driven evolution.

2.4.2. Knowledge Library

The knowledge library, as illustrated in Figure 3, is central to our continual evolution process. It interacts dynamically with the LLM during each phase of the evolution process, including initialization, crossover, mutation, tree-based idea search phase, enhancing the generation and refinement of ideas. Specifically, it involves three core designs: 1 idea summarization, 2idea management, and 3 idea reuse.

Idea summarization. Idea summarization occurs when solutions improve the score during the tree-based search and offspring generation processes. The LLM is asked to analyze the improved performance and store the effective idea into the knowledge library.

Idea management. The knowledge library is managed by another LLM, who is responsible to organize the knowledge library and retrieve the knowledge when needed. Specifically, it computes the sentence embeddings for the ideas and cluster them into different clusters. The clustering is done based on the cosine similarity of the sentence embeddings.



Figure 3: An illustration of the knowledge library with summarization and reuse in the evolutionary process and the tree-based idea search process.

Idea reuse. The knowledge library is used to retrieve the knowledge when needed in two modes *Random Reuse* and *Similarity-based Reuse*. When the LLM is generating new solutions, it needs to explore the search space to the largest extent, thus it is provided with random ideas from the knowledge library from each cluster for inspiration. However, when it is conducting tree-based idea search, it needs to explore the ideas that are related to the ideas in the previous level, thus similarity-based reuse is used. Similarity reuse involves calculate the distances from the current ideas to the ideas in the knowledge library and retrieve the ideas that are most similar to the current ideas.

3. Experiments

3.1. Experimental Setup

Backbone LLMs. In our experiments, we employ gpt-3.5-turbo and gpt-4o-mini as the backbone LLMs. The gpt-3.5-turbo model, as per OpenAI's documentation, has a knowledge cutoff of September 2021 [42]. In contrast, the gpt-4o-mini model's knowledge extends up to October 2023 [43]. Throughout this paper, the term gpt-4 is used interchangeably with gpt-4o-mini for brevity.

Benchmark and Datasets. The AI Feynman benchmark [44], consists of 120 physics problems and represents the current standard for evaluating symbolic regression methods in the discovery of scientific equations. However, employing this benchmark directly can result in mere rote recitation of information, a limitation highlighted in recent work [30]. Therefore, we

Table 1: Overall Performance

Table 1: O toran i cristinance									
Category	Method	Oscillation 1		Oscillation 2		E. coli growth		Stress-Strain	
		ID↓	$OOD \downarrow$	$ID\downarrow$	$OOD \downarrow$	$ID\downarrow$	$OOD \downarrow$	$ID\downarrow$	OOD↓
Evolutionary Search [*]	GPlearn ^[1]	0.0155	0.5567	0.7551	3.188	1.081	1.039	0.1063	0.4091
	PySR [45]	0.0009	0.3106	0.0002	0.0098	0.0376	1.0141	0.0331	0.1304
Deep Learning [*]	NeSymReS [48]	0.0047	0.5377	0.2488	0.6472	N/A ((d > 3)	0.7928	0.6377
	E2E [29]	0.0082	0.3722	0.1401	0.1911	0.6321	1.4467	0.2262	0.5867
	DSR [46]	0.0087	0.2454	0.0580	0.1945	0.9451	2.4291	0.3326	1.108
	uDSR [47]	0.0003	0.0007	0.0032	0.0015	0.3322	5.4584	0.0502	0.1761
LLM-based	LLM-SR (Mixtral) [*] [30]	7.89e-8	0.0002	0.0030	0.0291	0.0026	0.0037	0.0162	0.0946
	LLM-SR (GPT-3.5)* [30]	4.65e-7	0.0005	2.12e-7	<u>3.81e-5</u>	0.0214	0.0264	0.0210	0.0516
	LLM-SR (GPT-3.5, Reproduce) [30]	6.02e-9	0.0004	2.55e-7	3.03e-3	0.0207	0.0547	0.0017	0.0025
	CoEvo (Ours, GPT-3.5)	4.32e-9	8.71e-5	1.58e-10	1.32e-10	1.58e-9	1.21e-8	0.0020	0.0015
	CoEvo (Ours, GPT-40-mini)	1.28e-8	7.51e-5	2.98e-7	2.21e-4	0.0019	0.0107	0.0018	9.90e-4
*: Reported results from LLM-SR [30].									

[1]: https://gplearn.readthedocs.io/en/stable/

adopted the four problems introduced in [30] to evaluate the performance of our proposed method.

Baseline Algorithms. In our comparative analysis, we incorporate leading symbolic regression (SR) techniques in evolutionary search area, including GPlearn¹ and PySR [45]. Additionally, for deep learning-driven methods, our study encompasses DSR [46], uDSR [47], NeSymReS [48], and E2E [29]. Within the domain of LLM-based approaches, we feature LLM-SR, the most current advancement in LLM-driven symbolic regression.

The results of non-LLM based methods are directly reported from [30]. For LLM-based techniques, we permit up to 2,000 LLM queries, inclusive of all tree-based search endeavors and evolutionary operations, while excluding queries generated by summarization processes.

3.2. Overall Performance

The overall performance of various methods on problems is summarized in Table 1. Performance metrics are evaluated using the Normalized Mean Squared Error (NMSE), with lower values indicating superior performance.

Superior performance. Our approach consistently outperforms contemporary LLM-based regression methods across all tested benchmarks with two different LLM backbones. Notably, it achieves this with an equivalent or reduced number of queries, as shown in Figure 4.

Performance Comparison Between Backbones. Despite the more advanced capabilities of GPT-4o-mini compared to GPT-3.5, our findings indicate no significant performance disparity between them. This demonstrates

¹https://gplearn.readthedocs.io/en/stable/



Figure 4: The NMSE during the search process of our method and LLM-SR.



Figure 5: The ratio of the generated solutions that are valid during the search process. that our method effectively leverages GPT-3.5 to achieve results comparable to or better than those using the newer model.

Insights on Oscillation 2. In addressing the Oscillation 2 problem, our method achieves extremely low NMSE values. Further analysis reveals that applying temporal differentiation to velocity data is an effective solution, highlighting our approach's robustness. This finding, while validating our method's efficacy, also suggests potential issues with the benchmark's design. Future work may involve modifications to this benchmark to better test and validate symbolic regression methods.

3.3. Search Efficiency.

This section evaluates the search efficiency of our approaches compared to simple LLM queries by examining the historical NMSE on training data and the ratio of valid solutions found. These metrics illustrate the convergence behavior of the algorithms and the nature of solutions explored by different methods.

Convergence Figure 4 plots the historical NMSE across different benchmarks for both our methods and LLM-SR. While initial convergence rates are comparable, our methods demonstrate superior long-term efficiency, achieving lower NMSE values more consistently across iterations.

Exploration. The exploration capabilities of our methods compared to LLM-SR are depicted in Figure 5. Our approaches consistently generate a



Figure 6: The NMSE of the newly sampled solutions under the influence of the knowledge. higher ratio of valid solutions across all benchmarks. This improvement is attributed to two main factors: 1) the integration of tree-based reasoning and action processes, which enhances the generation and refinement of valid solutions, and 2) the employment of offspring operators that utilize existing solutions as starting points, thus increasing the likelihood of producing valid outcomes. These strategies contribute significantly to the robustness and effectiveness of our search process, particularly under complex problem conditions like those presented in the Oscillation 2 and Stress-Strain tests.

3.4. Knowledge Extraction and Application

This section evaluates the impact of knowledge on the quality of solutions generated by our models. We categorize the influence of knowledge into three types: 1 positive, 2 negative, and 3 neutral. The effects of these influences are depicted in Figure 6.

3.4.1. Positive Effect.

Significant improvements are observed in problems such as Oscillation 1, Oscillation 2, and E. coli growth, where the application of relevant knowledge leads to substantial reductions in error rates. To quantify these effects, we compare 50 solutions generated with and without specific knowledge inputs for Oscillation 1 and E. coli growth. The results, shown in Figure 7, indicate that solutions crafted with knowledge consistently outperform those without, exhibiting lower mean errors and reduced variability.

Knowledge and Search Space. In simpler scenarios like Oscillation 1, while knowledge aids in reducing error, it appears to restrict the exploration space, leading to a lower variance in solutions but not necessarily impairing the overall solution quality.

Better Knowledge v.s. Better Models In the context of the E. coli growth problem, superior knowledge proves more beneficial than advanced



Figure 7: The NMSE of the newly sampled solutions under the influence of the knowledge. model architectures. This observation underscores the importance of quality knowledge in enhancing model performance, as demonstrated by the distinct improvement in solutions when informed by more accurate knowledge.

Comprehension of Knowledge. Stronger models such as GPT-4o-mini show a greater sensitivity to the input knowledge compared to GPT-3.5, indicating that more advanced models can better leverage detailed and complex knowledge to improve performance.

3.4.2. Negative Effect.

The only observed negative impact occurs in the Oscillation 2 problem, where the inclusion of specific, misleading knowledge from numpy.gradient adversely affects the solutions. An analysis of the knowledge library during iterations 500 to 1500 confirms the presence of this detrimental knowledge (Figure 8).

3.4.3. Knowledge Pollution.

Figure 8 illustrates the pollution within the knowledge pool for Oscillation 2, where irrelevant or incorrect knowledge entries, such as those related to numpy.gradient, have accumulated. so that many useless knowledge for performance improvement are summarized in the pool false. This contamination significantly hampers the model's performance by steering the solution generation process towards less effective outcomes.



Figure 8: Pollution of knowledge

4. Conclusion

We proposed the idea of open-ended optimization process and conducted extensive experiments on four scientific benchmarks. The results have shown that with knowledge extracted, LLMs are able to conduct endless explorations over the solutions.

References

- [1] OpenAI, GPT-4 technical report, CoRR abs/2303.08774 (2023). arXiv:2303.08774.
- [2] F. Liu, Y. Yao, P. Guo, Z. Yang, Z. Zhao, X. Lin, X. Tong, M. Yuan, Z. Lu, Z. Wang, Q. Zhang, A systematic survey on large language models for algorithm design, CoRR abs/2410.14716 (2024). doi:10.48550/ ARXIV.2410.14716. arXiv:2410.14716.
- [3] T. Ifargan, L. Hafner, M. Kern, O. Alcalay, R. Kishony, Autonomous llm-driven research — from data to human-verifiable research papers, NEJM AI 0 (2024) AIoa2400555. doi:10.1056/AIoa2400555. arXiv:https://ai.nejm.org/doi/pdf/10.1056/AIoa2400555.
- [4] H. Wang, T. Fu, Y. Du, W. Gao, K. Huang, Z. Liu, P. Chandak, S. Liu, P. V. Katwyk, A. Deac, A. Anandkumar, K. Bergen, C. P. Gomes, S. Ho, P. Kohli, J. Lasenby, J. Leskovec, T. Liu, A. Manrai, D. S. Marks, B. Ramsundar, L. Song, J. Sun, J. Tang, P. Velickovic, M. Welling,

L. Zhang, C. W. Coley, Y. Bengio, M. Zitnik, Scientific discovery in the age of artificial intelligence, Nat. 620 (2023) 47–60.

- [5] Y. Zheng, H. Y. Koh, J. Ju, A. T. N. Nguyen, L. T. May, G. I. Webb, S. Pan, Large language models for scientific synthesis, inference and explanation, CoRR abs/2310.07984 (2023). URL: https://doi. org/10.48550/arXiv.2310.07984. doi:10.48550/ARXIV.2310.07984. arXiv:2310.07984.
- [6] Q. Wang, D. Downey, H. Ji, T. Hope, Scimon: Scientific inspiration machines optimized for novelty, in: L. Ku, A. Martins, V. Srikumar (Eds.), Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2024, Bangkok, Thailand, August 11-16, 2024, Association for Computational Linguistics, 2024, pp. 279–299. URL: https://doi.org/10.18653/v1/2024. acl-long.18. doi:10.18653/V1/2024.ACL-LONG.18.
- [7] S. Yao, J. Zhao, D. Yu, N. Du, I. Shafran, K. R. Narasimhan, Y. Cao, React: Synergizing reasoning and acting in language models, in: The Eleventh International Conference on Learning Representations, ICLR, OpenReview.net, 2023.
- [8] F. Liu, X. Tong, M. Yuan, X. Lin, F. Luo, Z. Wang, Z. Lu, Q. Zhang, Evolution of heuristics: Towards efficient automatic algorithm design using large language model, in: Forty-first International Conference on Machine Learning, (ICML), 2024.
- [9] B. Romera-Paredes, M. Barekatain, A. Novikov, M. Balog, M. P. Kumar, E. Dupont, F. J. R. Ruiz, J. S. Ellenberg, P. Wang, O. Fawzi, P. Kohli, A. Fawzi, Mathematical discoveries from program search with large language models, Nat. (2024).
- [10] X. Liu, N. Xu, M. Chen, C. Xiao, Autodan: Generating stealthy jailbreak prompts on aligned large language models, in: The Twelfth International Conference on Learning Representations, ICLR, OpenReview.net, 2024.
- [11] X. Liu, P. Li, E. Suh, Y. Vorobeychik, Z. Mao, S. Jha, P. McDaniel, H. Sun, B. Li, C. Xiao, Autodan-turbo: A lifelong agent for strategy self-exploration to jailbreak llms, CoRR (2024).

- [12] P. Guo, F. Liu, X. Lin, Q. Zhao, Q. Zhang, L-autoda: Large language models for automatically evolving decision-based adversarial attacks, in: Proceedings of the Genetic and Evolutionary Computation Conference Companion, GECCO, ACM, 2024.
- [13] S. Zhang, C. Gong, L. Wu, X. Liu, M. Zhou, Automl-gpt: Automatic machine learning with GPT, CoRR (2023). arXiv:2305.02499.
- [14] E. P. Wigner, The unreasonable effectiveness of mathematics in the natural sciences, in: Mathematics and science, World Scientific, 1990, pp. 291–306.
- [15] A. Newell, Physical symbol systems, Cogn. Sci. 4 (1980) 135–183.
- [16] J. R. Koza, Genetic programming as a means for programming computers by natural selection, Statistics and computing 4 (1994) 87–112.
- [17] G. Gielen, W. M. Sansen, Symbolic analysis for automated design of analog integrated circuits, volume 137, Springer Science & Business Media, 2012.
- [18] D. B. Lenat, Eurisko: a program that learns new heuristics and domain concepts: the nature of heuristics iii: program design and results, Artificial intelligence 21 (1983) 61–98.
- [19] M. Coccia, Probability of discoveries between research fields to explain scientific and technological change, Technology in Society 68 (2022) 101874.
- [20] S. D. Brown, Z. G. Vranesic, Fundamentals of digital logic with VHDL design, volume 70125910, McGraw-Hill New York, 2000.
- [21] W. Wolf, Modern VLSI design: system-on-chip design, Pearson Education, 2002.
- [22] K. O. Stanley, J. Lehman, L. Soros, Open-endedness: The last grand challenge you've never heard of, While open-endedness could be a force for discovering intelligence, it could also be a component of AI itself (2017).

- [23] J. Lehman, K. O. Stanley, Abandoning objectives: Evolution through the search for novelty alone, Evolutionary computation 19 (2011) 189– 223.
- [24] M. Faldor, J. Zhang, A. Cully, J. Clune, Omni-epic: Open-endedness via models of human notions of interestingness with environments programmed in code, 2024. URL: https://arxiv.org/abs/2405.15568. arXiv:2405.15568.
- [25] M. A. Boden, The creative mind: Myths and mechanisms, Routledge, 2004.
- [26] M. Virgolin, S. P. Pissis, Symbolic regression is np-hard, Trans. Mach. Learn. Res. 2022 (2022).
- [27] M. D. Cranmer, Interpretable machine learning for science with pysr and symbolic symbolic regression.jl, CoRR abs/2305.01582 (2023).
- [28] L. Biggio, T. Bendinelli, A. Neitz, A. Lucchi, G. Parascandolo, Neural symbolic regression that scales, in: Proceedings of the 38th International Conference on Machine Learning, ICML, Proceedings of Machine Learning Research, PMLR, 2021, pp. 936–945.
- [29] P. Kamienny, S. d'Ascoli, G. Lample, F. Charton, End-to-end symbolic regression with transformers, in: Advances in Neural Information Processing Systems 35: Annual Conference on Neural Information Processing Systems 2022, NeurIPS, 2022.
- [30] P. Shojaee, K. Meidani, S. Gupta, A. B. Farimani, C. K. Reddy, LLM-SR: scientific equation discovery via programming with large language models, CoRR abs/2404.18400 (2024). doi:10.48550/ARXIV. 2404.18400. arXiv:2404.18400.
- [31] Y. Huang, J. Huang, A survey on retrieval-augmented text generation for large language models, CoRR (2024).
- [32] E. Wang, F. Cassano, C. Wu, Y. Bai, W. Song, V. Nath, Z. Han, S. Hendryx, S. Yue, H. Zhang, Planning in natural language improves LLM search for code generation, CoRR (2024). doi:10.48550/ARXIV. 2409.03733. arXiv:2409.03733.

- [33] F. Liu, X. Tong, M. Yuan, X. Lin, F. Luo, Z. Wang, Z. Lu, Q. Zhang, Evolution of heuristics: Towards efficient automatic algorithm design using large language model, in: Forty-first International Conference on Machine Learning, ICML, OpenReview.net, 2024.
- [34] W. X. Zhao, K. Zhou, J. Li, T. Tang, X. Wang, Y. Hou, Y. Min, B. Zhang, J. Zhang, Z. Dong, Y. Du, C. Yang, Y. Chen, Z. Chen, J. Jiang, R. Ren, Y. Li, X. Tang, Z. Liu, P. Liu, J.-Y. Nie, J.-R. Wen, A survey of large language models, 2024. URL: https://arxiv.org/abs/ 2303.18223. arXiv:2303.18223.
- [35] M. Dascal, Why does language matter to artificial intelligence?, Minds and machines 2 (1992) 145–174.
- [36] I. Goldstein, S. Papert, Artificial intelligence, language, and the study of knowledge, Cognitive science 1 (1977) 84–123.
- [37] B. Roziere, J. Gehring, F. Gloeckle, S. Sootla, I. Gat, X. E. Tan, Y. Adi, J. Liu, R. Sauvestre, T. Remez, et al., Code llama: Open foundation models for code, arXiv preprint arXiv:2308.12950 (2023).
- [38] A. Dubey, A. Jauhri, A. Pandey, A. Kadian, A. Al-Dahle, A. Letman, A. Mathur, A. Schelten, A. Yang, A. Fan, et al., The llama 3 herd of models, arXiv preprint arXiv:2407.21783 (2024).
- [39] W. F. Clocksin, Logic programming and digital circuit analysis, The Journal of Logic Programming 4 (1987) 59–82.
- [40] J. Wei, X. Wang, D. Schuurmans, M. Bosma, F. Xia, E. Chi, Q. V. Le, D. Zhou, et al., Chain-of-thought prompting elicits reasoning in large language models, Advances in neural information processing systems 35 (2022) 24824–24837.
- [41] S. Yao, D. Yu, J. Zhao, I. Shafran, T. Griffiths, Y. Cao, K. Narasimhan, Tree of thoughts: Deliberate problem solving with large language models, Advances in Neural Information Processing Systems 36 (2024).
- [42] Models openai api, https://platform.openai.com/docs/models# gpt-3-5-turbo, ????. Accessed: 2024-12-23.

- [43] Models openai api, https://platform.openai.com/docs/models# gpt-4o-mini, ????. Accessed: 2024-12-23.
- [44] S. Udrescu, M. Tegmark, AI feynman: a physics-inspired method for symbolic regression, CoRR abs/1905.11481 (2019). arXiv:1905.11481.
- [45] M. D. Cranmer, Interpretable machine learning for science with pysr and symbolic regression.jl, CoRR abs/2305.01582 (2023). doi:10.48550/ ARXIV.2305.01582. arXiv:2305.01582.
- [46] B. K. Petersen, M. Landajuela, T. N. Mundhenk, C. P. Santiago, S. Kim, J. T. Kim, Deep symbolic regression: Recovering mathematical expressions from data via risk-seeking policy gradients, in: 9th International Conference on Learning Representations, ICLR, OpenReview.net, 2021.
- [47] M. Landajuela, C. S. Lee, J. Yang, R. Glatt, C. P. Santiago, I. Aravena, T. N. Mundhenk, G. Mulcahy, B. K. Petersen, A unified framework for deep symbolic regression, in: Advances in Neural Information Processing Systems 35: Annual Conference on Neural Information Processing Systems 2022, NeurIPS, 2022.
- [48] L. Biggio, T. Bendinelli, A. Neitz, A. Lucchi, G. Parascandolo, Neural symbolic regression that scales, in: Proceedings of the 38th International Conference on Machine Learning, ICML, volume 139 of *Proceedings of Machine Learning Research*, PMLR, 2021, pp. 936–945.