Dovetail: A CPU/GPU Heterogeneous Speculative Decoding for LLM inference

Libo Zhang^{*}, Zhaoning Zhang^{*†}, Baizhou Xu, Songzhu Mei, Dongsheng Li *National University of Defense Technology* Email: {zhanglibo, zhangzhaoning, xubaizhou23, sz.mei, dsli}@nudt.edu.cn

Abstract-Due to the high resource demands of Large Language Models (LLMs), achieving widespread deployment on consumer-grade devices presents significant challenges. Typically, personal or consumer-grade devices, including servers configured prior to the era of large-scale models, generally have relatively weak GPUs and relatively strong CPUs. However, most current methods primarily depend on GPUs for computation. Therefore, we propose Dovetail, an approach that deploys the draft model on the GPU to generate draft tokens while allowing the target model to perform parallel verification on the CPU, thereby improving the utilization of all available hardware resources and occupying less inter-device communication bandwidth. Accordingly, we have redesigned the draft model to better align with heterogeneous hardware characteristics. To this end, we implemented several optimizations: reducing the number of draft tokens to mitigate latency in parallel verification, increasing the depth of the draft model to enhance its predictive capacity, and introducing DGF (Dynamic Gating Fusion) to improve the integration of features and token embeddings. In the HumanEval benchmark, Dovetail achieved an inference speed of 5.86 tokens per second for LLaMA2-Chat-7B using 3GB of VRAM, representing an approximately 2.77x improvement over CPU-only inference. Furthermore, the inference speed was increased to 8 tokens per second when utilizing 7GB of VRAM.

Index Terms—Resource Constrained; Heterogeneous Architecture; Speculative Decoding; LLM Inference;

I. INTRODUCTION

In recent years, as the size of model parameters continues to increase, large language models (LLMs) [1], [2] have demonstrated remarkable performance improvements across various domains. Nevertheless, these advancements come with significant computational demands, which require high-end hardware. Consequently, there is a growing demand to enable the deployment of LLMs on personal or consumer-grade devices, including outdated servers from before the era of large-scale models.

We observed that these devices and small-scale servers are typically equipped with GPUs with limited memory capacity, which is insufficient to fully load LLMs. For instance, a 7B model with 16-bit precision requires approximately 14GB of memory solely to load its parameters, a memory demand that far exceeds the available capacity of consumer-grade GPUs, such as the NVIDIA RTX 2080 SUPER.

Currently, to enable inference without compromising model performance, the primary strategies include offloading and



Fig. 1: The inference latency speedup ratio of LLaMA2-Chat-7B was evaluated on MT-bench using an NVIDIA RTX 2080 SUPER, with the temperature set to 0. Vanilla represents the existing lossless inference method, while SD refers to the speculative decoding algorithm. Bars with the same color indicate the effect of applying the SD algorithm on top of the Vanilla method.

partial offloading. These methods store a portion of the model parameters in the host memory and dynamically load them onto the GPU as needed, or alternatively, execute computations directly on the CPU. As shown in Fig. 1, the offloading strategy, compared to performing inference entirely on the CPU, reduces the inference speed to approximately 0.45 times the original speed due to the high communication latency between the CPU and GPU. In contrast, partial offloading improves the inference speed to 1.68 times the original speed by exploiting lower communication latency. Nonetheless, the acceleration effect remains limited and is constrained by the GPU memory capacity: as the available GPU memory decreases, the acceleration effect gradually diminishes.

Speculative decoding [3], [4] is an emerging approach for accelerating LLM inference. This method utilizes a smaller model to generate multiple draft tokens, which are then verified in parallel by the target model, enabling multi-token generation per step for lossless acceleration. SpecExec adopts speculative decoding in offloading scenarios by designing a search algorithm to dynamically construct and expand draft trees, significantly increasing the average acceptance length and accelerating LLM inference. However, the algorithm does not fully utilize the available resources, exhibits significant communication latency, and is constrained by GPU memory capacity. Under the current testing environment, the algorithm requires a minimum of 5.9 GB of GPU memory, rendering it

^{*}Equal Contribution [†]Corresponding author

¹https://github.com/ddInference/Dovetail



Fig. 2: The architecture of Dovetail, highlighting a collaborative inference mode where the target model is deployed on the CPU, and the draft model is deployed on the GPU.

difficult to deploy effectively on devices with lower memory capacities.

Based on this, we propose Dovetail, a heterogeneous collaborative speculative decoding mechanism between the CPU and GPU, as shown in Fig. 2. In this setup, the draft model is independently deployed on the consumer-grade GPU, while the target model is executed on the CPU. Compared to offloading strategies, our method reduces the granularity of data transfer between the CPU and GPU from the Transformer block level to the token level, significantly reducing communication overhead. Compared to SpecExec, our method can efficiently operate on most consumer-grade GPUs, as the parameter size of the draft model ranges from 68M to 3B [5], [6].

As shown in Fig. 1, the speedup effect was only improved by 1.57 times when the speculative decoding algorithm was directly applied on the heterogeneous architecture. To further accelerate inference on heterogeneous architectures, we explored the characteristics of speculative decoding algorithms in such architectures and optimized the existing algorithm as follows: (1) By reducing the number of draft tokens, we linearly decreased the latency of parallel verification, effectively mitigating performance bottlenecks on low-end hardware. (2) Due to the significant increase in the latency of the target model, adopting larger draft models became feasible. Based on EAGLE-2 [7], we redesigned the draft model by introducing DGF (Dynamic Gating Fusion) to dynamically adjust the fusion weights between hidden states and token embeddings, avoiding information loss and imbalances in feature representation fusion. In addition, by extending the Transformer blocks in the draft model from a single block to multiple blocks, we significantly reduced the performance gap between the draft model and the target model, while effectively enhancing predictive performance and improving the average reception length.

Our main contributions are as follows:

 We propose a novel heterogeneous speculative decoding paradigm that leverages the characteristics of heterogeneous architectures and the features of speculative decoding. By deploying the verification stage of the target model on the CPU, this paradigm significantly



Fig. 3: A demonstration of Speculative Decoding

improves the utilization efficiency of existing hardware resources.

- We optimize the existing draft model for low-end hardware in heterogeneous architectures, achieving an improved balance between latency and performance.
- 3) We developed a system capable of achieving an inference speed of 4.62 to 5.86 tokens per second for LLaMA2-Chat-7B or similar models using only 3GB of VRAM, delivering a 2.25x performance improvement on MT-bench, as shown in Fig. 1. With 7GB of VRAM, the inference speed further increases to 6.5 to 8 tokens per second, achieving a 3.08x performance improvement on MT-bench.

II. PRELIMINARIES

The core idea of speculative decoding is to draft first and verify later. As shown in Fig. 3, the draft model generates multiple rounds of draft tokens autoregressively and organizes these tokens into a tree structure called the draft tree. The target model performs a single forward pass on the tokens in the draft tree to calculate their probabilities and uses speculative sampling [3], [4] to sequentially determine the acceptance of each token. If a token is rejected, the distribution is adjusted for resampling, and all subsequent tokens are discarded, ending the verification phase. Finally, the verified tokens are used as input for the next generation round, and this process is repeated until the generation is complete.

Speculative decoding is a very common optimization method for auto-regressive generative models. By verifying multiple tokens at once, it achieves higher parallelized computing. Following the theoretical model in MagicDec (Chen et al., 2024), we focus on the following two core questions: 1) What are the new characteristics of speculative decoding in a heterogeneous environment? 2) What else is there in the optimization space in a heterogeneous environment?

A. Effectiveness of Heterogeneous Speculative Decoding

In the current resource-constrained environment, common computing resources include various types and combinations of CPUs and small-scale GPU configurations, such as the combination of CPUs with discrete GPUs (dGPUs) or integrated GPUs (iGPUs) in personal devices, as well as the pairing of CPU with small GPU in server environments, which are not designed for AI purposes.

Mainstream approaches typically achieve LLM inference through parameter offloading. Given the characteristics of these computing resource configurations and speculative decoding, we propose a heterogeneous speculative decoding method to accelerate LLM inference. However, this method does not necessarily perform well across all combinations of main processor and accelerator. Thus, we present a stochastic analysis to reveal the correlation between hardware and computing combinations. Typically, main processors are designed for general purpose and relatively slow for GEMM computation, while accelerators are specialized for parallelized GEMM process.

Given a sequence of length S and batch size B, with a target model consisting of m Transformer blocks, a hidden dimension H, and a candidate draft token number γ , the average per-token decoding latency, based on the theoretical formula proposed by MagicDec [8] can be defined as:

$$T_{Avg}^{SD} = \frac{\gamma \cdot T_D + T_V(\gamma)}{\Omega(\gamma, \alpha)},\tag{1}$$

where α is the acceptance rate, and $\Omega(\gamma, \alpha)$ represents the number of tokens accepted in a single parallel verification. T_D denotes the time taken by the draft model to decode a single token, while $T_V(\gamma)$ represents the time required for the target model to perform parallel verification of γ tokens.

The offloading methods [9] are implemented using a parallel strategy of simultaneous computation and loading, which hides data loading time within computation time to optimize efficiency. The latency per token can be expressed as $T_{Offload}$.

To ensure that our proposed heterogeneous speculative decoding method demonstrates practical advantages, the following condition must be met:

$$T_{Avg}^{SD} < T_{Offload}, \tag{2}$$

This condition (2) indicates that the average latency per token for heterogeneous speculative decoding must be lower than that of the offloading method.

In a heterogeneous architecture, to evaluate the parallel verification time $T_V(\gamma)$ of the target model on the main processor, let T_c represent the computation time, and T_p represent the memory access time. These are defined as follows:

$$T_c = \frac{F}{P_c \cdot E_c}, \quad T_p = \frac{P}{B_m \cdot E_m}, \tag{3}$$

where F represents the computational cost of a single Transformer block, P is the parameter size, P_c denotes the peak computational performance of the main processor, E_c represents the computational efficiency, B_m is the memory bandwidth, and E_m is the memory utilization efficiency.

To account for the partial overlap of computational time and memory access time, the total time can be expressed as:

$$T_V(\gamma) = \max(T_c, T_p) + \beta \cdot \min(T_c, T_p), \qquad (4)$$



Fig. 4: Exploring the impact of average acceptance length and the parallel validation time of the target model on the speedup ratio. The speedup ratio is defined as the ratio of tokens generated per second by the target model using the EAGLE-2 algorithm on a heterogeneous architecture to the tokens generated per second by the target model running solely on a CPU.

where β ($0 \le \beta \le 1$) represents the overlap coefficient. A value of $\beta = 1$ indicates no overlap, while $\beta = 0$ indicates complete overlap.

The condition (2) can be further updated as follows:

$$\max(T_c, T_p) + \beta \cdot \min(T_c, T_p) < \Omega(\gamma, \alpha) \cdot \frac{P}{B_p \cdot E_p}, \quad (5)$$

where B_p is the PCIe bandwidth and E_p is the PCIe transmission efficiency.

Based on this analysis, when the performance of the main processor and the accelerator in a heterogeneous system is relatively balanced, heterogeneous speculative decoding can deliver superior efficiency. However, in scenarios where hardware resources are significantly imbalanced (the main processor has severely limited computational performance, and PCIe transmission bandwidth is high, e.g. currently mainstreaming CPU/GPU environment), the heterogeneous speculative decoding strategy may not be the optimal choice.

B. Factors Affecting Speculative Decoding Speedup

The speculative decoding algorithm aims to improve the inference speed of the target model. The time taken by the target model to decode a single token is T_T , while the time taken by the speculative decoding algorithm to decode a single token is T_{Avg}^{SD} . The performance analysis formula can be expressed as:

$$\frac{T_{Avg}^{SD}}{T_T} = \frac{1}{\Omega(\gamma, \alpha)} \left(\frac{\gamma \cdot T_D}{T_T} + \frac{T_V(\gamma)}{T_T} \right),\tag{6}$$

From (6), the key factors affecting the speedup are: the cost ratio between decoding a single token by the draft model and the target model T_D/T_T ; the cost ratio of verifying γ draft tokens in parallel to decoding a single token by the target model $T_V(\gamma)/T_T$; and the expected average acceptance length $\Omega(\gamma, \alpha)$. When both T_D/T_T and $T_V(\gamma)/T_T$ are



Fig. 5: The pipeline of heterogeneous collaborative speculative decoding depicts the computational procedure. In this context, N and M denote the number of layers in the target model and the draft model, respectively.

relatively small, and $\Omega(\gamma, \alpha)$ is large, the speedup effect is more pronounced. We conducted preliminary experiments and analysis by directly applying Eagle-2 to resource-constrained heterogeneous architectures. The experimental results show that compared to high-end hardware, the value of T_D/T_T becomes closer to zero, $\Omega(\gamma, \alpha)$ remains unchanged, but the lower parallelism [10] of the CPU causes $T_V(\gamma)/T_T$ to increase significantly, ultimately reducing the overall speedup effect.

The significant increase in $T_V(\gamma)$ shifts the primary bottleneck of heterogeneous speculative decoding to the parallel verification process of the target model. While reducing the number of draft tokens can effectively decrease $T_V(\gamma)$, it also shortens $\Omega(\gamma, \alpha)$, which may negatively affect overall inference speed. Thus, achieving a balance between these two factors is crucial. As illustrated in Fig. 4, reducing the number of draft tokens results in a linear decrease in verification latency. Despite the resulting reduction in the expected generation length, the overall inference speed improves due to the reduction in verification delay. Consequently, appropriately reducing the number of draft tokens can effectively mitigate the primary bottleneck caused by increased verification time.

As $T_V(\gamma)$ decreases while remaining constant, the primary bottleneck in heterogeneous speculative decoding shifts from $T_V(\gamma)$ to $\Omega(\gamma, \alpha)$. However, achieving a higher α is often associated with an increase in T_D . DSD [11] demonstrates that as the parameter size of the draft model grows, $\Omega(\gamma, \alpha)$ also increases. Despite this, the overall inference speed initially improves and subsequently declines, primarily due to the continuous rise in T_D . In heterogeneous architectures, compared to high-end hardware, the increase in T_T is significantly more pronounced than that of T_D , leading to a marked reduction in T_D/T_T . This disparity allows for the deployment of draft models with larger parameter sizes, which improves α , extends $\Omega(\gamma, \alpha)$, and ultimately enhancing overall inference speed.

Based on the above analysis, to further improve the performance of heterogeneous speculative decoding, $T_V(\gamma)$ can be linearly reduced by decreasing γ . Meanwhile, draft models with larger parameter sizes can be utilized to enhance α ,



Fig. 6: Schematic diagram of the DGF. hidden state represents the second-totop hidden state in the target LLM, "||" denotes concatenation, " σ " represents the sigmoid function, and "x" denotes the multiplication mechanism.

thereby increasing $\Omega(\gamma,\alpha)$ and optimizing overall performance.

III. METHOD

This section introduces methods for accelerating LLM inference under resource-constrained conditions using speculative decoding, the effective integration of information at different levels by the DGF module, and the strategy of reducing distribution differences between the draft and target models by increasing the parameter size of the draft model.

A. CPU/GPU Heterogeneous Architecture

Dovetail deploys the draft model on the GPU and the target model on the CPU, effectively utilizing the strengths of heterogeneous computing architectures.

As illustrated in Fig. 5, the target model processes the input prompt to generate the hidden states required by the draft model and transfers them along with the tokens to the GPU for inference. The draft model dynamically constructs the draft tree through multiple rounds of autoregressive decoding. During each round, it computes the cumulative product of token probabilities along the paths from the root to each node, which is used as the global acceptance probability. The top-k tokens are then selected for expansion, and this process continues until the tree is fully constructed.

Once completed, the tree nodes are reordered, and the top- γ tokens with the highest global acceptance probabilities are selected as candidates and sent to the CPU-based target model for parallel validation. The target model performs a single forward pass to compute the logits of the candidate tokens and applies the speculative sampling algorithm to determine which tokens to accept. The accepted tokens are returned to the GPU-based draft model for the next round of draft tree generation.

Compared to offloading strategies, the token-level exchange strategy significantly reduces the data transfer overhead between the GPU and CPU, avoiding frequent large-scale parameter transfers. Moreover, in contrast to deploying both the draft and target models on the CPU, this heterogeneous architecture substantially decreases the inference latency of the draft model, thereby accelerating the overall inference process.

B. Dynamic Gated Fusion

In EAGLE-2, prior to inference with the draft model, it is necessary to fuse the input hidden state and token embedding to address the inherent uncertainty of the hidden state. The current approach involves simply concatenates the hidden state and token embedding, followed by a single-layer linear transformation to map the concatenated representation to the dimensionality of the hidden state, thereby achieving their fusion. However, this method has certain limitations. First, the straightforward concatenation and linear transformation may lead the model to overly rely on the linear transformation of the concatenated features, potentially neglecting deeper interactions between the hidden state and token embedding. Second, the fixed linear layer lacks flexibility in handling features from two different sources, as it fails to dynamically adjust the fusion process according to the specific context. Since the linear layer treats all inputs uniformly, it may not adequately emphasize critical input information, resulting in suboptimal fusion performance.

To address these limitations, we propose the Dynamic Gated Fusion (DGF) module, inspired by dynamic weight allocation techniques used in multimodal feature fusion [12]. As illustrated in Fig. 6, the DGF module begins by applying linear transformations to the hidden state and token embedding, producing feature representations h_1 and h_2 , respectively. These two features are then concatenated into a joint feature vector. A linear layer, followed by a sigmoid activation function, is used to generate a gating value that determines the contribution ratio of h_1 and h_2 . Finally, h_1 and h_2 are weighted according to the gating value and summed to produce the fused feature representation, effectively capturing the interactions between the two features.

Unlike the method that applies linear transformation after concatenation, the advantage of DGF lies in its ability to adaptively regulate the interaction strength between the hidden state and token embedding and dynamically adjust the ratio of information fusion based on different input scenarios. This mechanism not only enhances the model's expressive power in complex scenarios but also effectively reduces the risk of information loss or imbalance in fusion that may arise from global linear transformations.

C. Multiple Transformer Blocks

In high-performance hardware environments, the latency of the draft model is often the primary bottleneck affecting the speedup ratio of speculative decoding algorithms. Consequently, designing the draft model requires a careful tradeoff between parameter size and prediction accuracy. Typically, the draft model is designed with a smaller parameter size, often corresponding to a single Transformer block from the target model, enabling significant inference acceleration on high-performance hardware. However, in resource-constrained heterogeneous architectures, directly adopting existing draft models often results in suboptimal performance. As discussed in Section II-B, the increased parallel verification time of the target model introduces opportunities for further optimization of the draft model.

Although DGF effectively integrates information across different levels to enhance the performance of the draft model, the draft model's capacity is limited by its single-Transformerblock architecture. This limitation hinders its ability to learn the deep abstract features of the target model and align with its feature distribution, thereby constraining prediction accuracy. To address this issue, we extend the draft model from a single Transformer block to a multi-block architecture comprising M Transformer blocks, as illustrated in Fig. 5, significantly increasing the model's parameter size. The addition of multiple blocks greatly enhances the draft model's nonlinear representational capacity, enabling it to more accurately approximate the complex representational space of the target model. Furthermore, this extension allows the model to more effectively capture and align with the target model's feature distribution, resulting in improved prediction accuracy, extended average acceptance length, and accelerated overall inference.

However, in a heterogeneous architecture, increasing the number of Transformer blocks in the draft model beyond a certain point leads to computation latency becoming a major bottleneck. In our experiments, we set the value of M to 4, with a detailed analysis and justification provided in Section IV-B2.

IV. EXPERIMENTS

Hardware: The experiment was conducted in a low-end hardware environment: Intel Xeon Silver 4214R processor with 24 physical cores and 128GB of RAM. NVIDIA GeForce RTX 2080 SUPER with 8GB VRAM connected to the host memory via PCIe Gen 3x16 interface. To simulate a scenario with imbalanced performance between the main processor and accelerator: Intel Xeon Silver 4310 processor with 24 physical cores and 128GB of RAM. NVIDIA GeForce RTX 3090 with 24GB VRAM connected to the host memory via PCIe Gen 4x16 interface.

Models: During the evaluation, we employed LLaMA2chat-7B as the target model. This series also offers several smaller models with fewer parameters that can serve as draft models, such as TinyLlama-1.1B and ShearedLlama-1.3B.

Tasks: To comprehensively evaluate the model's performance across various tasks, we covered multi-turn dialogue, code generation, mathematical reasoning, and instruction execution tasks. Specifically, the following datasets were used in the evaluation: MT-bench [12] for dialogue tasks, HumanEval [13] for code generation, GSM8K [14] for mathematical reasoning, and the Alpaca dataset [15] for instruction-following tasks.

Training: We trained the draft model on the ShareGPT dataset, where the configuration of the draft model under the Dovetail framework was defined with M ranging from 1 to 6. The training process utilized four NVIDIA A800 80G GPUs with a batch size of 16, employing mixed precision training

TABLE I: A comparison of speedup ratios and average acceptance length τ for different methods on heterogeneous architectures with GeForce RTX 2080 SUPER, where L2 represents LLaMA2-Chat.

Model	Method	MT-bench		HumanEval		GSM8K		Alpaca		Mean	
		Speedup	τ	Speedup	au	Speedup	au	Speedup	τ	Speedup	au
Temperature = 0											
L2 7B	Vanilla EAGLE-2	1.62x	4.75	1.90x	5.61	1.63x	4.97	1.54x	4.65	1.67x	5.00
	ShearedLlama-1.3B	1.80x	4.75	2.10x	5.48	1.69x	4.41	1.68x	4.47	1.82x	4.78
	TinyLlama-1.1B	1.89x	4.89	2.17x	5.70	1.69x	4.38	1.69x	4.57	1.86x	4.88
	EAGLE-2	1.99x	3.95	2.32x	4.69	1.99x	4.01	1.93x	3.83	2.06x	4.12
	Ours	2.25x	4.73	2.77x	5.90	2.20x	4.71	2.17x	4.62	2.35x	4.99
Temperature = 1											
L2 7B	Vanilla EAGLE-2	1.54x	4.49	1.77x	5.23	1.63x	4.90	1.50x	4.41	1.61x	4.76
	ShearedLlama-1.3B	1.69x	4.37	1.87x	4.83	1.71x	4.52	1.61x	4.21	1.72x	4.48
	TinyLlama-1.1B	1.78x	4.53	1.94x	5.00	1.66x	4.35	1.67x	4.33	1.76x	4.55
	EAGLE-2	1.88x	3.67	2.14x	4.25	1.96x	3.98	1.81x	3.60	1.95x	3.89
	Ours	2.12x	4.38	2.49x	5.34	2.16x	4.68	2.02x	4.24	2.20x	4.66

TABLE II: Speedup ratios of different methods at temperature = 0, using LLaMA2-Chat-7B as the target model, with PM (peak memory) in GB. The number of tokens generated per second is denoted as t/s.

Method	MT-	bench		HumanEval					
	Speedup	τ	PM	Speedup	τ	PM			
GeForce RTX 2080 SUPER									
CPU-only	1x(2.14t/s)	-	-	1x(2.12t/s)	-	-			
Offload	0.45x	-	7.44	-	-	-			
SpecExec	2.36x	7.43	7.14	2.98x	10.10	7.32			
Dovetail	3.08x	4.61	7.40	3.78x	5.90	7.44			
GeForce RTX 3090									
CPU-only	1x(2.35t/s)	-	-	1x(2.34t/s)	-	-			
Offload	0.83x	-	7.44	-	-	-			
SpecExec	3.95x	7.38	7.14	4.92x	10.05	7.32			
Dovetail	4.05x	4.60	7.40	4.99x	5.91	7.44			

(bf16). The AdamW optimizer was used, with momentum parameters set as $\beta_1 = 0.9$ and $\beta_2 = 0.95$. The model was trained for 50 epochs, and when M = 6, the training process was completed within approximately 4 to 5 days. To ensure a fair comparison, the EAGLE model was retrained under identical conditions, providing a consistent experimental baseline.

Metrics: Given that our approach achieves lossless acceleration, the focus of evaluation was on the acceleration performance of the target LLM. To this end, we selected the average acceptance length τ and speedup ratio as the primary metrics.

In the experimental process, for the tree-based decoding setup, we used a maximum width of 10, a depth of 7, and a maximum validated token count of 16. Regarding model precision, the target model on the CPU used 32-bit weights, while the draft model on the GPU employed 16-bit weights. Our current method has limitations when processing long texts, primarily due to insufficient CPU parallelism, which results in higher latency for generating the first token.

A. Result

Table I presents the average acceptance length and speedup ratio for various methods. Vanilla EAGLE-2 refers to the direct

application of the EAGLE-2 algorithm on a heterogeneous architecture using 60 draft tokens, while other methods utilize 16 draft tokens. Despite performance variations under different temperature settings, the overall trends remain consistent. As shown in Table I, the draft model optimized for the heterogeneous architecture consistently outperforms Vanilla EAGLE-2 across all tasks. By reducing the number of draft tokens to 16, EAGLE-2 significantly reduced the time required for parallel validation and adapted more effectively to the heterogeneous architecture. Although this adjustment resulted in a decrease in average acceptance length, the average speedup ratio increased from 1.67x to 2.06x, leading to a significant improvement in inference efficiency. Further optimization of our approach achieved the best acceleration performance across all tasks. At T = 0, the speedup ranged from 2.17x to 2.77x, with the average acceptance length nearly matching that of the Vanilla EAGLE-2.

A straightforward approach to increasing the parameter size of the draft model is to employ smaller models from the same series as the draft model. These smaller models, sharing the same tokenizer with the target model and trained through similar processes, exhibit behavioral characteristics closely aligned with the target model, thereby increasing the number of accepted draft tokens. As shown in Table I, while models such as TinyLlama-1.1B and ShearedLlama-1.3B significantly improve the average acceptance length, their higher draft latency offsets the acceleration gains achieved through the increased acceptance length in heterogeneous architectures. This leads to suboptimal overall acceleration performance, only marginally better than directly applying EAGLE-2. In contrast, Dovetail achieves an average acceptance length of 4.99 across four tasks, surpassing the performance of smaller models from the same series while maintaining lower draft latency. This balance enables Dovetail to achieve optimal performance across all tasks.

In Table I, the peak memory consumption for Dovetailrelated experiments is 2.95GB. When the memory capacity of consumer-grade GPUs exceeds 3GB, certain layers of the

TABLE III: Ablation experiment results on a heterogeneous architecture using GeForce RTX 2080 SUPER, with the temperature set to 0 for LLaMA2-Chat-7B. Lparameters denotes the model's learnable parameters. w/o both indicates that neither DGF nor additional layers are used, w/ DGF indicates that only DGF is used, and w/ DGF + m indicates that DGF is used along with the addition of m Transformer blocks.

Method	Lparameters	MT-bench		HumanEval		
		Speedup	τ	Speedup	au	
w/o both	0.22B	1.99x	3.95	2.32x	4.69	
w/ DGF	0.25B	2.05x	4.06	2.42x	4.89	
w/ DGF + 1	0.44B	2.13x	4.31	2.62x	5.38	
w/ DGF + 2	0.63B	2.21x	4.53	2.72x	5.65	
w/ DGF + 3	0.81B	2.23x	4.62	2.74x	5.82	
w/ DGF + 4	1.00B	2.25x	4.73	2.77x	5.90	
w/ DGF + 5	1.19B	2.26x	4.83	2.75x	5.98	

target model can be loaded onto the GPU to achieve further acceleration. As shown in Table II, SpecExec and Dovetail achieve optimal performance with 128 and 16 draft tokens, respectively. Although SpecExec has a significantly larger average acceptance length compared to Dovetail, the speedup ratio of Dovetail is superior. Notably, as shown in Table I, Dovetail, using only 2.95GB of memory, achieves a speedup ratio only slightly lower than that of SpecExec, which utilizes 7.14GB. This is primarily due to the considerable communication latency inherent in the offload method, coupled with the fact that SpecExec constructs a significantly larger draft tree than Dovetail. This results in increased time consumption during the drafting phase, partially offsetting the acceleration benefits gained from the increased average acceptance length.

When CPU performance changes but with only a small improvement, while GPU performance improves significantly, this configuration can be used to simulate scenarios where there is an imbalance between CPU and GPU performance. As shown in Table II, this imbalance is reflected in the fact that, with improved GPU performance, the enhanced PCIe bandwidth significantly improves the performance of the Offload method, increasing its speedup ratio from 0.45x on the GeForce RTX 2080 SUPER to 0.83x on the GeForce RTX 3090. However, this also results in the Dovetail method on the GeForce RTX 3090 achieving a smaller speedup improvement relative to SpecExec compared to the GeForce RTX 2080 SUPER. Nevertheless, the speedup ratio of Dovetail remains superior to that of SpecExec, demonstrating excellent adaptability, particularly in scenarios where GPU performance is not significantly better than CPU performance or when GPU memory is more limited. Dovetail still delivers noticeable performance advantages in many cases.

B. Ablation Study

We conducted an ablation study on the LLaMA2-Chat-7B model using MT-bench and HumanEval to explore the impact of DGF, and multiple transformer blocks on model's performance.

1) Dynamic Gating Fusion: To validate the effectiveness of DGF, we conducted a comparative analysis against a baseline method from EAGLE-2, in which token embeddings are

linearly combined with hidden states. As shown in Table III, the results demonstrate that incorporating DGF significantly improves both the average acceptance length and speedup ratio on the MT-bench and HumanEval datasets. These findings highlight the ability of DGF to effectively leverage input information from multiple sources and dynamically adjust the contribution of each source, enabling more efficient and adaptive feature fusion.

2) Multiple Transformer Blocks: To evaluate the impact of the draft model's parameter scale on inference speed, we gradually increased the number of Transformer blocks in the draft model from 1 to 6. As shown in Table III, increasing the number of Transformer blocks from 1 to 5 led to a gradual improvement in prediction accuracy, which in turn resulted in a corresponding increase in average acceptance length and a steady rise in the speedup ratio. This indicates that increasing the number of Transformer blocks enables the model to capture more complex features, thereby aligning the draft model's feature distribution more closely with that of the target model. However, when the number of Transformer blocks reached 6, while both the average acceptance length and speedup ratio improved significantly on the MT-bench dataset, the speedup ratio on the HumanEval dataset slightly decreased despite a marked improvement in average acceptance length. This phenomenon can be attributed to the fact that, at this stage, the inference time during the draft phase becomes the primary bottleneck. The additional parameters significantly increase the draft computation time, which offsets the acceleration benefits gained from the improved average acceptance length.

This experiment underscores the importance of balancing model depth and inference speed when designing draft models. Excessive Transformer blocks significantly increase computational overhead, which can adversely affect real-time inference efficiency. Consequently, carefully optimizing the depth of draft model is essential for achieving an optimal trade-off between model performance and efficiency.

V. RELATED WORK

A. Heterogeneous Architecture

Since the introduction of the Transformer [16], its variants have become the dominant architecture for LLMs. However, as the parameter size increases, the inference process is constrained by the memory capacity of accelerators. To address this challenge, researchers have proposed various model compression techniques, including quantization [17]-[21], pruning [22]–[24], and knowledge distillation [25]–[27], to reduce model size. However, these methods often come at the cost of decreased generation quality. Moreover, even with reduced model size, the models can still be too large to run on consumer-grade GPUs. To enable lossless inference, offloading or partial offloading strategies can be employed. Offloading stores model parameters that exceed GPU capacity in CPU memory and dynamically loads them onto the GPU as needed. However, during single-batch inference, more than 99.5% of the time is spent on data transfer between the GPU and CPU [24], significantly increasing latency. In contrast, partial offloading [28] stores parameters exceeding GPU capacity in CPU memory, performs computations on the CPU, and transfers intermediate results to the GPU for subsequent processing. While partial offloading alleviates memory bandwidth constraints, its performance remains limited by the computational capacity of the CPU and the memory capacity of the GPU.

In heterogeneous architectures, the presence of accelerators allows for leveraging the advantages of multiple computational resources for model inference. Model compression techniques typically focus on fully utilizing accelerator performance, often with limited consideration of output quality. In contrast, offloading and partial offloading strategies combine the performance of accelerators with the memory and computational capabilities of CPUs to achieve lossless output quality, although their acceleration efficiency is generally suboptimal. To address this issue, PowerInfer [24] leverages the locality characteristics of LLM inference by predicting hot neurons to be computed on the GPU, while delegating cold neurons to the CPU. This approach effectively utilizes the advantages of heterogeneous architectures to significantly improve inference speed. Similarly, KTransformers [29] focuses on sparse Mixture of Experts (MoE) models, employing a heterogeneous computing strategy: non-shared components (sparse MoE matrices) are placed on the CPU to conserve GPU memory, while shared dense components are computed on the GPU. This method maximizes hardware resource utilization through heterogeneous computing, enabling efficient inference in resource-constrained environments.

B. Speculative Decoding

Speculative decoding is an emerging approach that focuses on enhancing decoding efficiency, achieving lossless acceleration, and is orthogonal to other methods. The speculative decoding algorithm fundamentally adopts a draft-then-verify paradigm [30], a concept initially applied in Blockwise Decoding [31]. Speculative Decoding [32] was the first to formally introduce the term 'Speculative Decoding', establishing the draft-then-verify process as a paradigm for accelerating autoregressive decoding. Later, Speculative Sampling [3], [4] extended this paradigm to non-greedy sampling scenarios. As a result, subsequent research on speculative inference has centered around this paradigm.

1) Obtaining Draft Tokens: For certain target models [1], [33], smaller models from the same series can be directly used as draft models [3] without requiring additional training or modification. When small models from the same series are unavailable, the draft model must be trained from scratch, or draft models or draft tokens can be derived from the target model. Draft models can be obtained from target models using knowledge distillation [34] or quantization [5], or by incorporating early exit mechanisms [35] and layer-skipping techniques [36] to conclude the inference process earlier, thus generating draft tokens.Additionally, non-autoregressive or autoregressive prediction heads [7], [37] can be incorporated into the target model to generate draft tokens. A draft model



Fig. 7: A depiction of the Dovetail joint in Chinese carpentry, which also inspired the name of our method. It represents that the seamless integration of this heterogeneous architecture.

can also be composed of multiple smaller models, leveraging a staged [38] or cascaded approach [39] to generate draft tokens

2) Organizing Draft Tokens: In early studies [3], [4], the draft model sampled only one draft token per step and used a chain structure. To increase average acceptance length, later studies [5], [37]proposed sampling multiple draft tokens per step and organizing them in a predefined tree structure. However, static tree structures do not consider contextual information. Studies [7], [9]have suggested dynamically constructing a draft tree based on the cumulative confidence of tokens in their context.

3) Verifying Draft Tokens: Early studies [32], [40] strictly required that draft tokens match the greedy decoding output of the target model exactly. Later, speculative sampling [3], [4] adopted nucleus sampling and theoretically demonstrated that this criterion preserves the same output distribution as the target LLM, also achieving lossless acceleration. To further enhance acceleration, some studies [32], [41] have proposed moderately relaxing the verification criteria to increase the acceptance rate of draft tokens.Judge decoding [42] can determine whether to accept a draft token directly based on its token embedding, without relying on logits.

VI. CONCLUSION

In this paper, we propose Dovetail, a lossless acceleration method that incorporates speculative decoding to accelerate target model inference under resource-constrained conditions. By introducing theoretical formulas, we analyze under which combination of CPU and GPU this method can effectively improve performance. Based on the characteristics of lowend hardware, Dovetail reduces the number of draft tokens, resulting in a linear reduction in the latency of parallel verification. Additionally, it utilizes DGF to efficiently integrate information from multiple sources. The parameter size of the draft model is also increased to enhance prediction accuracy, thereby achieving a higher speedup ratio. We evaluate Dovetail on multiple datasets and compare it with existing lossless acceleration methods. The experimental results demonstrate that Dovetail consistently achieves the highest speedup ratio across all benchmarks.

Although the proposed method has achieved relatively superior performance, achieving optimal inference speed in resource-constrained environments still needs more effect. Due to the limitations of CPU parallelism, inference methods face challenges when dealing with long text scenarios because the delay in the pre-filling stage is relatively large. This is a task that needs to be addressed in the future.

REFERENCES

- H. Touvron, T. Lavril, G. Izacard, X. Martinet, M.-A. Lachaux, T. Lacroix, B. Rozière, N. Goyal, E. Hambro, F. Azhar *et al.*, "Llama: Open and efficient foundation language models," *arXiv preprint arXiv:2302.13971*, 2023.
- [2] J. Achiam, S. Adler, S. Agarwal, L. Ahmad, I. Akkaya, F. L. Aleman, D. Almeida, J. Altenschmidt, S. Altman, S. Anadkat *et al.*, "Gpt-4 technical report," *arXiv preprint arXiv:2303.08774*, 2023.
- [3] Y. Leviathan, M. Kalman, and Y. Matias, "Fast inference from transformers via speculative decoding," in *International Conference on Machine Learning*. PMLR, 2023, pp. 19274–19286.
- [4] C. Chen, S. Borgeaud, G. Irving, J.-B. Lespiau, L. Sifre, and J. Jumper, "Accelerating large language model decoding with speculative sampling," arXiv preprint arXiv:2302.01318, 2023.
- [5] X. Miao, G. Oliaro, Z. Zhang, X. Cheng, Z. Wang, Z. Zhang, R. Y. Y. Wong, A. Zhu, L. Yang, X. Shi *et al.*, "Specinfer: Accelerating generative large language model serving with tree-based speculative inference and verification," *arXiv preprint arXiv:2305.09781*, 2023.
- [6] M. Xia, T. Gao, Z. Zeng, and D. Chen, "Sheared llama: Accelerating language model pre-training via structured pruning," arXiv preprint arXiv:2310.06694, 2023.
- [7] Y. Li, F. Wei, C. Zhang, and H. Zhang, "Eagle-2: Faster inference of language models with dynamic draft trees," *arXiv preprint arXiv:2406.16858*, 2024.
- [8] J. Chen, V. Tiwari, R. Sadhukhan, Z. Chen, J. Shi, I. E.-H. Yen, and B. Chen, "Magicdec: Breaking the latency-throughput tradeoff for long context generation with speculative decoding," *arXiv preprint* arXiv:2408.11049, 2024.
- [9] R. Svirschevski, A. May, Z. Chen, B. Chen, Z. Jia, and M. Ryabinin, "Specexec: Massively parallel speculative decoding for interactive llm inference on consumer devices," arXiv preprint arXiv:2406.02532, 2024.
- [10] L. Yin, Y. Zhang, Z. Zhang, Y. Peng, and P. Zhao, "Parax: Boosting deep learning for big data analytics on many-core cpus," *Proceedings* of the VLDB Endowment, vol. 14, no. 6, pp. 864–877, 2021.
- [11] M. Yan, S. Agarwal, and S. Venkataraman, "Decoding speculative decoding," arXiv preprint arXiv:2402.01528, 2024.
- [12] J. Arevalo, T. Solorio, M. Montes-y Gómez, and F. A. González, "Gated multimodal units for information fusion," *arXiv preprint* arXiv:1702.01992, 2017.
- [13] M. Chen, J. Tworek, H. Jun, Q. Yuan, H. P. D. O. Pinto, J. Kaplan, H. Edwards, Y. Burda, N. Joseph, G. Brockman *et al.*, "Evaluating large language models trained on code," *arXiv preprint arXiv:2107.03374*, 2021.
- [14] K. Cobbe, V. Kosaraju, M. Bavarian, M. Chen, H. Jun, L. Kaiser, M. Plappert, J. Tworek, J. Hilton, R. Nakano *et al.*, "Training verifiers to solve math word problems," *arXiv preprint arXiv:2110.14168*, 2021.
- [15] R. Taori, I. Gulrajani, T. Zhang, Y. Dubois, X. Li, C. Guestrin, P. Liang, and T. B. Hashimoto, "Stanford alpaca: An instruction-following llama model," 2023.
- [16] A. Vaswani, "Attention is all you need," Advances in Neural Information Processing Systems, 2017.
- [17] I. Hubara, M. Courbariaux, D. Soudry, R. El-Yaniv, and Y. Bengio, "Quantized neural networks: Training neural networks with low precision weights and activations," *Journal of Machine Learning Research*, vol. 18, no. 187, pp. 1–30, 2018.
- [18] T. Dettmers, M. Lewis, Y. Belkada, and L. Zettlemoyer, "Llm.int8(): 8bit matrix multiplication for transformers at scale," *arXiv e-prints*, 2022.
- [19] G. Xiao, J. Lin, M. Seznec, H. Wu, J. Demouth, and S. Han, "Smoothquant: Accurate and efficient post-training quantization for large language models," in *International Conference on Machine Learning*. PMLR, 2023, pp. 38 087–38 099.
- [20] E. Frantar, S. Ashkboos, T. Hoefler, and D. Alistarh, "Gptq: Accurate post-training quantization for generative pre-trained transformers," *arXiv* preprint arXiv:2210.17323, 2022.
- [21] Z. Liu, C. Zhao, I. Fedorov, B. Soran, D. Choudhary, R. Krishnamoorthi, V. Chandra, Y. Tian, and T. Blankevoort, "Spinquant–llm quantization with learned rotations," arXiv preprint arXiv:2405.16406, 2024.
- [22] T. Gale, E. Elsen, and S. Hooker, "The state of sparsity in deep neural networks," arXiv preprint arXiv:1902.09574, 2019.
- [23] Z. Liu, J. Wang, T. Dao, T. Zhou, B. Yuan, Z. Song, A. Shrivastava, C. Zhang, Y. Tian, C. Re *et al.*, "Deja vu: Contextual sparsity for efficient llms at inference time," in *International Conference on Machine Learning*. PMLR, 2023, pp. 22137–22176.

- [24] Y. Song, Z. Mi, H. Xie, and H. Chen, "Powerinfer: Fast large language model serving with a consumer-grade gpu," arXiv preprint arXiv:2312.12456, 2023.
- [25] V. Sanh, L. Debut, J. Chaumond, and T. Wolf, "Distilbert, a distilled version of bert: Smaller, faster, cheaper and lighter. arxiv 2019," arXiv preprint arXiv:1910.01108, 2019.
- [26] L. Tu, R. Y. Pang, S. Wiseman, and K. Gimpel, "Engine: Energy-based inference networks for non-autoregressive machine translation," arXiv preprint arXiv:2005.00850, 2020.
- [27] Y. Wen, Z. Li, W. Du, and L. Mou, "f-divergence minimization for sequence-level knowledge distillation," arXiv preprint arXiv:2307.15190, 2023.
- [28] G. Gerganov, "ggerganov/llama.cpp: Port of facebook's llama model in c/c++," https://github.com/ggerganov/llama.cpp, 2023.
- [29] KVCache.AI, "kvcache-ai/ktransformers: A flexible framework for experiencing cutting-edge llm inference optimizations," https://github.com/ kvcache-ai/ktransformers, 2024.
- [30] H. Xia, Z. Yang, Q. Dong, P. Wang, Y. Li, T. Ge, T. Liu, W. Li, and Z. Sui, "Unlocking efficiency in large language model inference: A comprehensive survey of speculative decoding," arXiv preprint arXiv:2401.07851, 2024.
- [31] M. Stern, N. Shazeer, and J. Uszkoreit, "Blockwise parallel decoding for deep autoregressive models," *Advances in Neural Information Processing Systems*, vol. 31, 2018.
- [32] H. Xia, T. Ge, P. Wang, S.-Q. Chen, F. Wei, and Z. Sui, "Speculative decoding: Exploiting speculative execution for accelerating seq2seq generation," in *Findings of the Association for Computational Linguistics: EMNLP 2023*, 2023, pp. 3909–3925.
- [33] A. Yang, B. Yang, B. Hui, B. Zheng, B. Yu, C. Zhou, C. Li, C. Li, D. Liu, F. Huang *et al.*, "Qwen2 technical report," *arXiv preprint* arXiv:2407.10671, 2024.
- [34] Y. Zhou, K. Lyu, A. S. Rawat, A. K. Menon, A. Rostamizadeh, S. Kumar, J.-F. Kagy, and R. Agarwal, "Distillspec: Improving speculative decoding via knowledge distillation," *arXiv preprint arXiv:2310.08461*, 2023.
- [35] Z. Zeng, Y. Hong, H. Dai, H. Zhuang, and C. Chen, "Consistentee: A consistent and hardness-guided early exiting method for accelerating language models inference," in *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 38, no. 17, 2024, pp. 19506–19514.
- [36] J. Zhang, J. Wang, H. Li, L. Shou, K. Chen, G. Chen, and S. Mehrotra, "Draft & verify: Lossless large language model acceleration via selfspeculative decoding," arXiv preprint arXiv:2309.08168, 2023.
- [37] T. Cai, Y. Li, Z. Geng, H. Peng, J. D. Lee, D. Chen, and T. Dao, "Medusa: Simple Ilm inference acceleration framework with multiple decoding heads," *arXiv preprint arXiv:2401.10774*, 2024.
- [38] B. Spector and C. Re, "Accelerating llm inference with staged speculative decoding," arXiv preprint arXiv:2308.04623, 2023.
- [39] Z. Chen, X. Yang, J. Lin, C. Sun, K. C.-C. Chang, and J. Huang, "Cascade speculative drafting for even faster llm inference," arXiv preprint arXiv:2312.11462, 2023.
- [40] M. Stern, W. Chan, J. Kiros, and J. Uszkoreit, "Insertion transformer: Flexible sequence generation via insertion operations," in *International Conference on Machine Learning*. PMLR, 2019, pp. 5976–5985.
- [41] S. Kim, K. Mangalam, S. Moon, J. Malik, M. W. Mahoney, A. Gholami, and K. Keutzer, "Speculative decoding with big little decoder," *Advances* in Neural Information Processing Systems, vol. 36, 2024.
- [42] Anonymous, "Judge decoding: Faster speculative sampling requires going beyond model alignment," in *Submitted to The Thirteenth International Conference on Learning Representations*, 2024, under review. [Online]. Available: https://openreview.net/forum?id=mtSSFiqW6y