Blue laser induced bright red fluorescence in hot cesium vapor

Armen Sargsyan, Anahit Gogyan† , and David Sarkisyan

Institute for Physical Research, National Academy of Sciences of Armenia, Gitavan-2, 0204 Ashtarak, Armenia

† Corr. author: agogyan@gmail.com

Abstract: We have observed laser-induced fluorescence using 456 nm laser radiation, resonant with the $6S_{1/2}$ -7P_{3/2} transition in Cs atoms. It includes red emission lines in the range of 580-730 nm and a prominent line at 852 nm corresponding to the $6P_{3/2}$ - $6S_{1/2}$ transition. A T-shaped all-sapphire cell with a length of 1 cm, containing Cs atomic vapor and capable of being heated up to 500◦C, was used. The laser-induced fluorescence (LIF) power at 852 nm was investigated as a function of the cell temperature. The maximum LIF power was achieved at 130◦C, while a significant decrease was observed around 300◦C. At 130◦C, the Doppler-broadened LIF spectrum at 852 nm exhibited self-conversion, resulting in the formation of two distinct peaks within the spectrum. The LIF power at 852 nm was also studied as a function of the 456 nm radiation power. The Cs cell demonstrated potential as an efficient optical filter and down-converter, effectively transforming 456 nm radiation into 852 nm radiation.

Keywords: laser-induced fluorescence; hot cesium vapor; down-converter

1 Introduction

In [\[1\]](#page-5-0), it was experimentally demonstrated that blue laser radiation could be successfully used for wireless underwater communication in free space over a range of 36 kilometers in the Yellow Sea. Particularly, blue laser radiation at 456 nm exhibits a relatively small absorption coefficient of 0.01 m−¹ in certain ocean waters [\[2\]](#page-5-1). Therefore, it is crucial to study the conditions for effective detection and manipulation of blue radiation conversion. By registering 852 nm laser-induced fluorescence (LIF), it is possible to completely suppress 456 nm radiation, enabling a cesium (Cs) vapor cell to serve as an optical filter [\[3\]](#page-5-2), [\[4\]](#page-5-3).

Currently, the Cs atom transitions $6S_{1/2} \rightarrow 7P_{1/2,3/2}$ (D_{1,2} lines) at wavelengths 459 nm and 456 nm, respectively, are actively being studied. Nonlinear magneto-optical resonances observed in the fluorescence to the ground state from the $7P_{3/2}$ level, populated directly by 456 nm laser radiation, were investigated in $[5]$. The Cs D_2 transition was theoretically analyzed in [\[6\]](#page-5-5) and compared with the D_1 transition ($\lambda = 459$ nm). In [\[7\]](#page-5-6), the D_2 line transition was studied using the saturated absorption (SA) technique, allowing for sub-Doppler spectroscopy. The same technique was applied to examine the D_1 transition [\[8\]](#page-6-0).

Figure 1: A homemade T-shaped 1-cm long all-sapphire cell containing Cs atomic vapor, housed within a heater. An ECDL laser with a spectral linewidth of approximately 0.4 MHz, a beam diameter of 2 mm, and tunable around $\lambda = 456$ nm was used for resonant excitation of the $6S_{1/2} \rightarrow 7P_{3/2}$ transitions in Cs atoms. Fluorescence signal at 852 nm is registered with a photodetector.

Population inversion between the $7S_{1/2}$ and $6P_{3/2}$ levels of Cs in a thermal cesium cell, achieved using a 455.5 nm pumping laser, and the subsequent laser generation at 1470 nm were demonstrated in [\[9\]](#page-6-1). Moreover, by using 456 nm radiation in combination with additional 1070 nm radiation, high-lying Rydberg levels such as $32S_{1/2}$ can be explored, as shown in [\[4\]](#page-5-3). A bichromatic pumping scheme with 852- and 917-nm lasers excites Cs atoms to the $6D_{5/2}$ level, followed by cascaded decay, resulting in coherent 456 nm blue laser generation under phasematching conditions [\[10\]](#page-6-2), [\[11\]](#page-6-3). Generation of polychromatic and collimated light at 456 nm, 459 nm, and 761 nm via two-photon excitation of the $6S_{1/2} \rightarrow 8S_{1/2}$ transition with two infrared pump lasers at 852 nm and 795 nm is demonstrated in [\[12\]](#page-6-4), [\[13\]](#page-6-5). It is noteworthy that [\[10\]](#page-6-2) mentions that 456 nm generation via two-photon excitation of the $6S_{1/2} \rightarrow 6D_{5/2}$ transition may be more advantageous than using two-photon excitation of the $6S_{1/2} \rightarrow 8S_{1/2}$ transition.

In this work, laser radiation at 456 nm, which is in resonance with the $6S_{1/2} \rightarrow 7P_{3/2}$ transition, generates bright red laser-induced fluorescence and a strong 852 nm line corresponding to the $6S_{1/2} \rightarrow 6P_{3/2}$ transition. In contrast to some of the aforementioned works, this study demonstrates a straightforward scheme for converting blue radiation into red using only a single 456 nm laser, without requiring the use of two lasers.

An all-sapphire cell (ASC) of 1-cm length containing Cs atomic vapor and capable of being heated up to 500° C is utilized [\[14\]](#page-6-6). The LIF power of 852 nm radiation is studied as a function of the cell temperature, reaching a maximum at 130◦C and strongly decreasing around 300◦C. Meanwhile, LIF at 890 nm corresponding to the $6S_{1/2} \rightarrow 6P_{1/2}$ transition is detected with three times less power. The LIF intensity increases nearly linearly with 456 nm laser power up to 100 mW, achieving a conversion efficiency of 1%. Using 456 nm radiation in resonance with the $6S_{1/2} \rightarrow 7P_{3/2}$ transition, the dependence of bright red LIF and 852 nm LIF on ASC temperature and laser intensity is thoroughly investigated.

The next section presents the experimental details and analyzes the obtained results, while

Figure 2: Energy level diagram of atomic cesium, highlighting the states relevant to this study. The excitation of the $6S_{1/2} \rightarrow 7P_{3/2}$ transition occurs at 456 nm. LIF is observed at 456 nm, 894 nm, and 852 nm.

Figure 3: Excitation of the $6S_{1/2} \rightarrow 7P_{3/2}$ transition using 100 mW of 456 nm radiation. A strong LIF of bright red color, consisting of several prominent lines in the range of 580–730 nm and at 852 nm, is detected using a conventional photo camera. The left image corresponds to the ASC temperature of $\sim 100^{\circ}$ C, while the right image corresponds to $\sim 130^{\circ}$ C. The bright white spot at the center of the red region is due to the saturation of the photo camera's sensitivity.

the Conclusion summarizes the findings.

2 Experimental Procedures and Results

Experiment

A part of the experimental setup is sketched in Fig. 1. A tunable external-cavity diode laser with a spectral linewidth of ∼0.4 MHz, beam diameter of 2 mm, and tunable around $\lambda = 456$ nm was used for the resonant excitation of the $6S_{1/2} \rightarrow 7P_{3/2}$ transitions of Cs atoms. The laser beam was directed normally to the windows of a homemade T-shaped 1-cm-long ASC containing Cs atomic vapor, as shown in Fig. 1.

The specially designed oven consists of two heaters: one for the cell body and another for the side-arm (reservoir) containing Cs metal vapors. Due to its original construction, the pressure of the Cs atomic vapor is determined by the temperature at the boundary of the Cs

Figure 4: (a) Dependence of LIF power at 852 nm as a function of ASC temperature. (b) LIF power at 852 nm as a function of incident radiation intensity at 456 nm, measured at an ASC temperature of 130 ◦C.

metal column in the side-arm. The oven has three openings: two for laser transmission and one for LIF detection in a direction perpendicular to the laser propagation.

The atomic Cs levels and the wavelengths of transitions produced by the 456 nm laser are shown in Fig. 2. The 456 nm radiation effectively populates the $7P_{3/2}$ level (energy ${\sim}21{,}950$ ${\rm cm^{-1}}),$ from which the Cs atom absorbs another 456 nm photon, leading to ionization. Subsequent recombination results in the Cs atom occupying higher energy levels, which, through cascade spontaneous emission, predominantly populate the $6P_{3/2}$ level [\[3\]](#page-5-2), [\[4\]](#page-5-3). Narrowband interference filters were used to select LIF at 456 nm, 852 nm, or 894 nm. The power of these radiations was measured by a power meter and recorded with a photodiode FD-24K and a four-channel Tektronix TDS2014B oscilloscope.

Results

A strong LIF of bright red color, consisting of several intense red lines in the range of 580– 730 nm and the 852 nm line, was observed at ASC temperatures of ∼100 ◦C and ∼130 ◦C (Fig. 3, left and right panels). These were detected using a conventional photo camera. The Cs vapor densities were $N = 1.6 \times 10^{13}$ cm⁻³ and $N = 8 \times 10^{13}$ cm⁻³, respectively. Notably, when the 456 nm radiation was detuned by 300 MHz from the $6S_{1/2} \rightarrow 7P_{3/2}$ transition, the red LIF disappeared. This makes it convenient to visually ensure resonance of the laser frequency with the $6S_{1/2} \rightarrow 7P_{3/2}$ transition by maximizing the brightness of the red radiation, which is clearly visible to the naked eye even from several meters away.Notably, blue fluorescence at 456 nm is also observed in the emitted fluorescence light.

The dependence of LIF power at 852 nm on ASC temperature is shown in Fig. 4(a). The maximum power was achieved at 130◦C, while at higher temperatures it decreased. Recalculating the total 852 nm power emitted into 4π steradians (i.e., spontaneously emitted in all directions) indicates a conversion efficiency of the 456 nm radiation power of ∼1%. The dependence of the LIF power at 852 nm on 456 nm radiation intensity at 130° C is shown in Fig. 4(b).

The spectrum of 852 nm radiation in the side direction, recorded using a photodiode and an oscilloscope, is shown in Fig. 5. Note that the sensitivity of the photodiode at 852 nm is seven times greater than at 456 nm, an additional benefit of the 456 nm \rightarrow 852 nm conversion. Curve (i)

Figure 5: Fluorescence spectra of cesium under different conditions. Curve (i): Sub-Doppler reference fluorescence spectrum of the Cs D₂ line ($F_g = 3 \rightarrow F_e = 2, 3, 4$ transitions) obtained using a Cs nanocell heated to 100 \degree C with an atomic vapor column thickness of $L = 850$ nm. Curve (ii): Doppler-broadened fluorescence spectrum at 852 nm recorded at 100◦C. Curve (iii): Doppler-broadened fluorescence spectrum at 852 nm recorded at 130◦C, demonstrating selfconversion and forming two peaks inside the spectrum.

shows a sub-Doppler reference fluorescence spectrum of the Cs D_2 line $F_g = 3 \rightarrow F_e = 2, 3, 4$ transitions obtained with a Cs nanocell heated to $100\degree C$, with an atomic vapor column thickness of $L = 850$ nm [\[15\]](#page-6-7), [\[16\]](#page-6-8). Curve (ii) shows the 852 nm Doppler-broadened fluorescence spectrum at 100◦C with a narrowband interference filter at 852 nm, and Curve (iii) shows the spectrum at 130◦C.

The broadened fluorescence spectrum at 852 nm demonstrates self-conversion, forming two peaks within the spectrum. The fluorescence dip at the spectrum center is due to absorption while passing through the atomic vapor column $(L = 0.5 \text{ cm})$ before exiting the cell. The absorption is approximately $\exp(-\sigma NL)$ [\[17\]](#page-6-9), where $\sigma = 10^{-11}$ cm² is the Cs absorption cross-section at the exact $6S \to 6P_{3/2}$ transition, N is the Cs density, and L is the vapor column length. Here, $\sigma NL \sim 400$, although this value might be smaller by an order of magnitude, as many Cs atoms are in excited states when using 456 nm excitation [\[9\]](#page-6-1). Note that ∼8% LIF efficiency is observed for 456 nm radiation.

3 Conclusion

Using 456 nm laser radiation resonant with the $6S_{1/2} \rightarrow 7P_{3/2}$ transition of Cs atoms and a T-shaped ASC containing Cs atomic vapor (capable of being heated up to 500 ◦C), a bright LIF was observed at red lines (in the range of 580–730 nm) and at the 852 nm line $(6P_{3/2} \rightarrow 6S_{1/2})$ transition). The dependence of LIF power at 852 nm on ASC temperature was studied, with a maximum power achieved at 130 ◦C, which significantly decreased at ∼300 ◦C. LIF at the 894 nm transition (D_1) line) was also detected, but with approximately three times less power.

At 130 ◦C, the Doppler-broadened LIF at 852 nm demonstrated self-conversion, forming two peaks in the spectrum. This behavior was attributed to Cs vapor absorption as the radiation propagated toward the exit of the ASC. The 852 nm LIF power exhibited a nearly linear dependence on the 456 nm laser intensity, up to 100 mW. The ASC was repeatedly heated to 300 °C and higher without any darkening caused by the interaction of hot Cs vapors, in contrast to glass cells, where darkening occurs at temperatures above 150 °C [\[14\]](#page-6-6). Recalculating the total 852 nm power, which is spontaneously emitted in all directions, revealed a down-conversion efficiency of 456 nm \rightarrow 852 nm of ∼1%. Furthermore, at the input to the photodetector, the 456 nm radiation could be completely suppressed, indicating that the ASC could serve as an efficient 456 nm \rightarrow 852 nm optical filter and down-converter.

To achieve exact resonance of the 456 nm laser with the $6S_{1/2} \rightarrow 7P_{3/2}$ transition, a simple and practical method is to visually maximize the brightness of the red radiation, which is clearly visible to the naked eye even from several meters away. This process, illustrated in Fig. 3, provides an excellent demonstration of the frequency down-conversion effect for students. For simplicity, a Cs glass cell heated to 130 °C could be used for this demonstration.

Credit Authorship Contribution Statement

Armen Sargsyan: Investigation, Writing – review and editing, Funding acquisition.

Anahit Gogyan: Formal analysis, Software.

David Sarkisyan: Writing – original draft, Writing – review and editing, Supervision, Funding acquisition.

Funding

This work was supported by the Higher Education and Science Committee of the Republic of Armenia under the research project N 22IRF-06 and project N 1-6/23-I/IPR.

References

- [1] L. Ji, J. Gao, A.-L. Yang, et al., "Towards quantum communications in free-space seawater," Optics Express, vol. 25, p. 19 795, 2017.
- [2] B. Wozniak and J. Dera, Light Absorption in Sea Water. Springer Science Business Media, LLC, 2007.
- [3] J. Huennekens, Z. Wu, and T. Walker, "Ionization. excitation of high-lying atomic states and molecular fluorescence in cs vapor excited at 455.7 and 459.4 nm," Phys. Rev. A, vol. 31, p. 196, 1985.
- [4] A. Urvoy, Diploma thesis, 2011. [Online]. Available: [http://pi5.uni-stuttgart.de.](http://pi5.uni-stuttgart.de)
- [5] M. Auzinsh, R. Ferber, F. Gahbauer, A. Jarmola, L. Kalvans, and A. Atvars, "Cascade coherence transfer and magneto-optical resonances at 455 nm excitation of cesium," Optics Communications, vol. 284, p. 2863, 2011.
- [6] A. Damitz, G. Toh, E. Putney, C. Tanner, and D. Elliott, "Measurement of the radial matrix elements for the transitions in cesium," *Phys. Rev. A*, vol. 99, p. 062 510, 2019.
- [7] W. Williams, M. Herd, and W. Hawkins, "Spectroscopic study of the 7p1/2 and 7p3/2 states in cesium-133," Laser Physics Letters, vol. 15, p. 095 702, 2018.
- [8] E. Klinger, A. Mursa, C. Rivera-Aguilar, R. Vicarini, and N. Boudot, "Sub-doppler spectroscopy of the cs atom $6s1/2$ -7p1/2 transition at 459 nm in a microfabricated vapor cell," Optics Letters, vol. 49, p. 1953, 2024.
- [9] W. YanFei, W. DongYing, Z. TongGang, et al., "Realization of population inversion between 7s1/2 and 6p3/2 levels of cesium for four-level active optical clock," Science China, Physics Mechanics & Astronomy, vol. 56, p. 1107, 2013.
- [10] S. Kargapol'tsev, V. Velichansky, A. Yarovitsky, A. Taichenachev, and V. Yudin, "Optical cascade pumping of the 7p3/2 level in cesium atoms," Quantum Electronics, vol. 35, p. 591, 2005.
- [11] G. Ge, T. Li, Z. Guoqing, et al., "Generation of coherent blue light via bichromatic pumping in cesium vapor," Frontiers of Physics, vol. 18, p. 42 302, 2023.
- [12] B. Yang, J. Fan, J. Xu, L. Zheng, W. Huang, and H. Zhou, "Polychromatic and collimated lights generated by nondegenerate four-wave mixing in cesium vapor," Optics Express, vol. 32, p. 3492, 2024.
- [13] B. Yang, J. Xu, J. Fan, and H. Zhou, "Frequency characteristics of collimated blue light generated by four-wave mixing in cesium vapor," Optics Letters, vol. 49, p. 3846, 2024.
- [14] D. Sarkisyan, U. Hinze, L. Meyer, and B. Wellegehausen, "Efficient cw sodium dimer raman laser operation in a high-temperature sapphire cell," *Applied Physics B*, vol. 70, pp. 351– 354, 2000.
- [15] J. Keaveney, A. Sargsyan, U. Krohn, D. Sarkisyan, I. Hughes, and C. Adams, "Cooperative lamb shift in an atomic vapor layer of nanometer thickness," *Phys. Rev. Lett.*, vol. 108, p. 173 601, 2012.
- [16] A. Sargsyan, A. Tonoyan, R. Momier, C. Leroy, and D. Sarkisyan, "Formation of strongly shifted eit resonances using "forbidden" transitions of cesium," J. Quant. Spectrosc. Radiat. Transf., vol. 272, p. 107 780, 2023.
- [17] W. Demtroder, Laser Spectroscopy: Basic Concepts and Instrumentation. Springer Science & Business Media, 2002.