Exploiting Domain-Specific Parallel Data on Multilingual Language Models for Low-resource Language Translation

Surangika Ranathunga^a, Shravan Nayak[‡], Shih-Ting Cindy Huang[§], Yanke Mao [§], Tong Su[§], Yun-Hsiang Ray Chan[§], Songchen Yuan[§], Anthony Rinaldi[§], Annie En-Shiun Lee^{†§}

[†]Mila – Quebec AI Institutes, [§]University of Toronto, [†]OntarioTech University

> ^aSchool of Mathematical and Computational Sciences, Massey University, Albany, 0632, Auckland, New Zealand

Abstract

Neural Machine Translation (NMT) systems built on multilingual sequenceto-sequence Language Models (msLMs) fail to deliver expected results when the amount of parallel data for a language, as well as the language's representation in the model are limited. This restricts the capabilities of domainspecific NMT systems for low-resource languages (LRLs). As a solution, parallel data from auxiliary domains can be used either to fine-tune or to further pre-train the msLM. We present an evaluation of the effectiveness of these two techniques in the context of domain-specific LRL-NMT. We also explore the impact of domain divergence on NMT model performance. We recommend several strategies for utilizing auxiliary parallel data in building domain-specific NMT models for LRLs.

Keywords: Neural Machine Translation, Domain divergence, multilingual Language Models, domain adaptation

1. Introduction

The need to rapidly develop translation systems to disseminate information during pandemics, natural disasters, and other major events justifies

Preprint submitted to Natural Language Processing

Email address: s.ranathunga@massey.ac.nz (Surangika Ranathunga)

the need to build domain-specific Neural Machine Translation (NMT) systems with any and all available parallel data. This is particularly true for low-resource languages (LRLs) that do not possess large amounts of parallel data for any single domain [1]. Therefore, when building a domain-specific NMT model for a given LRL pair, we face two possible scenarios: the considered (target, aka test) domain does not have any parallel data to be used in training, or it has a little amount of parallel data. In both cases, it is possible to make use of parallel data available for the same language pair, but in different (auxiliary) domains. This is not an unrealistic assumption according to Tiedemann [2], hundreds of languages have parallel data from more than one domain.

Multilingual sequence-to-sequence Language Models (msLMs) such as mBART [3] have been shown to outperform vanilla Transformer models for the LRL-NMT task [4, 5, 6]. There are two possible ways to exploit auxiliary domain parallel data in building domain-specific LRL-NMT systems on top of msLMs: to further pre-train the msLM with self-supervised training objectives (**continuous pre-training**) [7] or to **fine-tune** the msLM with the NMT objective.

As shown in Figure 1, there are different ways to use auxiliary domain data in fine-tuning. These can be categorized as single-stage fine-tuning (FT) and Intermediate Task Transfer Learning (ITTL). Similarly, we can introduce another categorization based on the data availability of the target domain. In-domain refers to the case whether target domain has some parallel data for model training. Out-domain refers to the case where there is no such parallel data for the target domain. Note that out-domain testing scenario can be considered as zero-shot testing with respect to the target domain.

Variations of single-stage FT are: 1) single domain (vanilla) FT, where the msLM is fine-tuned once with data from one domain, and 2) multidomain FT, where the msLM is fine-tuned once with data from multiple domains. In vanilla FT, if the target domain has parallel data, this data is used for fine-tuning (in-domain case). In multi-domain FT, when the target domain has parallel data (in-domain case), it is combined with auxiliary domain data. In ITTL, the msLM is fine-tuned with an intermediate task, before fine-tuning with the final task. It also has two variations: singledomain ITTL, where the intermediate task has data from one auxiliary domain, and multi-domain ITTL, where the intermediate task has data from multiple domains. In both cases, the final task (i.e. stage¹) fine-tuning is done using data from a single domain. If target domain has parallel data (in-domain case), the final task always uses this data. In the in-domain case, target domain data is also combined with auxiliary domain data in intermediate stage of multi-domain ITTL.

Currently, there is no comparative study on the impact of continuous pre-training and fine-tuning techniques when auxiliary domain data is used. Determining the method that best exploits auxiliary domain parallel data is beneficial for LRL-NMT researchers who are unable to run extensive experiments due to limited computational resources. Lee et al. [6] and Adelani et al. [8] identified that domain divergence in parallel datasets affects NMT performance. However, they did not conduct a detailed investigation into the impact of this factor. Khiu et al. [9] and our previous work [10] evaluated the

¹We use the term stage interchangeably with task, i.e. final task or final stage, and intermediate task or intermediate stage.



Figure 1: Fine-tuning Strategies. (a) Vanilla FT (b) Mixed-domain FT (c) Single-domain ITTL (d) Multi-domain ITTL. *D*- set of all domain-specific datasets per language pair. d_i , d_j , d_k - domain-specific datasets.

impact of domain divergence only in the case of single domain ITTL. Given the above shortcomings, this paper intends to answer the following questions related to domain-specific LRL-NMT systems built on top of msLMs:

- 1. Should we use auxiliary domain parallel data for fine-tuning, continuous pre-training, or for both?
- 2. What is the impact of domain divergence between different parallel data sets on different FT setups?

In order to answer these questions, we conducted an extensive set of experiments with the aforementioned FT techniques as well as the bitext denoising pre-training technique [11]. We considered the LRLs Sinhala (SI), Tamil (TA), Kannada (KA), and Gujarati (GU) as well as Hindi (HI) for English-centric NMT. We report results for the case where the target domain has some parallel data for training (in-domain) and where the target domain has no parallel data (out-domain). We quantify the impact of domain divergence using Jenson-Shanon Divergence (JSD).

Based on our analysis, we make the following observations in using parallel data from auxiliary domains when building NMT systems on top of msLMs for LRL pairs:

- When the parallel data set size is small (less than 50k, in our experiments), pre-training with bitext denoising yields no gains for both inand out-domain setups.
- Multi-domain ITTL is the best for in-domain, but this utility diminishes when target dataset size increases. For out-domain, the best strategy depends on the domain relatedness and the size of parallel corpora.
- For both in- and out-domain setups, simply combining data from multiple domains does not help in ITTL, mainly due to the divergence between the domains they belong to.

2. Related Work

2.1. ITTL on msLMs for NMT

ITTL has roots in Transfer Learning, which has been extensively explored for NMT with vanilla Transformer models. However, as mentioned earlier, for LRLs, NMT systems built on top of msLMs outperform these traditional NMT techniques. Thus we do not discuss these techniques.

ITTL [12, 13, 14] refers to fine-tuning a pre-trained language model with the intermediate task(s), before fine-tuning on the final task. It has been extensively experimented with encoder-based LLMs such as BERT [12, 15], and has shown promising results even for LRLs [16].

With respect to ITTL for NMT, the closest to our work is Adelani et al. [8]. Similar to us, they explored single-domain ITTL and multi-domain ITTL, as well as multi-domain FT. However, they only considered the scenario where the auxiliary task has a large amount of data, while the target task has only a small amount of data. Moreover, they only used religious and news data and tested only for the in-domain setup. They did not quantify the impact of domain divergence. Our prior work [10] and Khiu et al. [9] considered only single-domain ITTL. However, they considered both in- and out-domain test setups and investigated the impact of domain divergence. Verma et al. [17] experimented with single-domain ITTL and multilingual ITTL (data from the same domain but in multiple languages). They found that the former is better, but did not quantify the impact of domain divergence.

2.2. Pre-training msLMs with Parallel Data

Reid and Artetxe [7] augmented the existing denoising objective in mBART with three new objectives: replace words in the noised sequence with a bilingual dictionary, predict the reference translation instead of the input sequence (bitext denoising), and a combination of the two. Kale et al. [18] used four denoising objective functions on mT5: translation language modeling, standard NMT, denoised NMT and denoised NMT with language model (LM). Chi et al. [19] used three cross-lingual objective functions on mT5: machine translation, translation pair span corruption, and translation span corruption. However, the latter two research did not consider the NMT task.

3. Methodology

The baseline for all our experiments is fine-tuning the msLM once with data from one domain (vanilla FT or single-domain FT). In the in-domain setup, this dataset comes from the target domain.

For continuous pre-training, we experimented with two of the Reid and Artetxe's pre-training objective functions: bitext de-noising with auxiliary domain parallel data *with and without* monolingual denoising [11]. For monolingual denoising, we used the source and target side of the parallel data separately and did not use additional monolingual data as done by Reid and Artetxe [11], because our objective is only to exploit the use of parallel data. We also excluded their dictionary denoising, as many LRLs still do not have sufficient bilingual dictionaries [20]. Once msLM is pre-trained with Reid and Artetxe's objective functions [11], we continue with vanilla FT with the NMT objective function.

We use the four FT strategies shown in Figure 1, and we formally define them as follows: Let D be the set of all domains where there is parallel data available for model training, for a considered language pair. $d_k \notin D$ is a domain for which there is no training data, but only test data is available. In the single-domain FT (vanilla FT) baseline (Figure 1(a)), the model is only fine-tuned with data from one domain $d_j \in D$. In the in-domain case, both fine-tuning and testing is done using data from domain $d_i \in D$. In the out-domain case, fine-tuning uses data from d_i , but testing is done on domain d_k . In **multi-domain FT** (Figure 1(b)), the model is fine-tuned with data from multiple domains $\forall d_i \in D$. In the in-domain case, this includes data from the target domain d_i as well. In the out-domain case, this trained model is tested on the unseen target domain d_k . In single-domain ITTL (Figure 1(c)), msLM is first fine-tuned with data of domain $d_i \in D$. This is the *intermediate task*, which is also called the *first stage*. Next, this finetuned model is further fine-tuned with data from domain $d_i \in D$. This is the second and last $stage^2$. In the in-domain case, testing will be done on the same domain d_i . In out-domain case, testing will be done on the unseen domain d_k . In **multi-domain ITTL** (Figure 1(d)), msLM is first fine-tuned with data from multiple domains in D. This model is further fine-tuned with $d_i \in D$, which is the target domain. In the in-domain case, data of d_i is included in the intermediate stage, as well as in the final stage. Similar to previous setups, in the out-domain case, testing will be done on the unseen domain d_k

4. Experimental Setting

Our experiment setup is inspired from our previous work [10] and we

²The model can always be fine-tuned in more stages if there is data from different domains. However, we do not consider this option due to lack of computational resources.

Lang.	Family	Script	Joshi class	mBART coverage in Tokens (M)
EN	Indo European	Latin	5	55608
HI	Indo Aryan	Devanagari	4	1715
GU	Indo Aryan	Gujarati	1	140
KN	Dravidian	Kannada	1	_
SI	Indo Aryan	Sinhala	1	243
ТА	Dravidian	Tamil	3	595

Table 1: Language details. Smaller the Joshi et al. [23] class value, more low-resource the language is (source [10]).

follow the same choices for msLM, languages, datasets, etc.

msLM: We used mBART, as previous research showed it outperformed mT5 [10]. Translation-specific models such as NLLB [21] were omitted, because they cannot be further pre-trained.

Languages: We selected the LRL GU, KN, SI, TA along with EN and HI (see Table 1). KN is not included in mBART and is at a disadvantage compared to other languages [22]. To fine-tune mBART for KN, we used related language fine-tuning strategy [6] with Telugu.

Datasets: We used both open-domain (CC) and domain-specific (Bible, Gvt, PMI) corpora (see Table 3). Each language has parallel data from three domains. The rather small FLORES dataset is used for out-domain testing only. Bible is the only domain-specific corpus with data for all our languages. The PMI and Gvt corpora are mutually exclusive in our experiments. Therefore, when describing results, we use PMI/Gvt to denote that we use one of these corpora for the considered experiment. Unlike PMI/Gvt and Bible, CC is larger, even for LRLs. However, it is a web-mined corpus, and is considered noisy [24, 25]. For multi-domain experiments, we randomly shuffled the training data from different domains.

Evaluation Metrics: We used SentencePiece BLEU (spBLEU) that was used in FLORES-101 evaluation benchmark [26].

Domain Divergence: We used Jenson-Shanon Divergence (JSD) to quantify domain divergence. Kashyap et al. [27] showed that JSD is a very reliable measure to analyze the performance of a model in a new domain. JSD values between our parallel corpora are given in Table 2.

Test set specifications are in Table 3. Further details on the data sets,

Dataset	Gvt test	FLORES test	Bib test	PMI test
Gvt train	0.10	0.40	0.58	-
CC train	0.40	0.41	0.52	0.44
Bib train	0.56	0.47	0.10	0.53
PMI train	-	0.33	0.52	0.15

Table 2: JS divergence between train and test domains (source [10])

model training, evaluation metrics (including spBLEU signature), and JSD calculation are given in Appendix A. We carried out experiments across techniques, languages, and domains for all EN-XX pairs. XX-EN experiments were carried out for SI and KN only to keep the number of experiments at a manageable level.

Dataset	Domain	Languages	Train Size	Test Size
FLORES-101	Open	HI, GU, KA, TA	-	1k
Floresv1	Open	SI	-	1k
CCAligned (CC)	Open	ALL	100k	1k
Government (Gvt)	Administrative	SI, TA	50k	1k
PMIndia (PMI)	News	HI	50k	1k
		GU, KA	25k	1k
Web-scraped Bible	Religious	ALL	25k	1k

Table 3: Data set statistics (source [10])

5. Results and Discussion

5.1. Pre-training with Bi-text Denoising

Three languages were selected for experiments, considering their representation in mBART (Table 1): KN-not included in mBART, SI- 243M tokens and HI- 1757M tokens. We tested for data sizes 1k, 10k, and 25k from individual domains and report the average results. Table 4³ shows that neither of the pre-training techniques was able to surpass the results of vanilla FT on mBART, except in two cases. Even in those two cases, continually pretrained mBART shows only marginal gains over original mBART.

³see Appendix Appendix B for raw results

Interestingly, additional pre-training performed worst for Kannada, which is unseen during the original pretraining of mBART. These results imply that bitext denoising is not a suitable strategy for utilizing auxiliary domain parallel data when the data size is small. Reid and Artetxe [11] reported results might improve if additional monolingual data is incorporated in large quantities; however, this is outside the scope of our research and we leave this for future research. Since pre-training only with parallel data did not yield satisfactory results for vanilla FT, we did not carry out further experiments combining pre-training and ITTL.

5.2. Impact of Data Set Size and Domain Divergence on FT and ITTL

In these experiments, we varied the data set size of both the intermediate and final stages. The smallest size is 1k (termed "small") and the maximum size is 25k (termed "large")⁴, where 25k is the largest common size across all three domains (see Table 3). Note that we reused the experiments results of single ITTL of our previous research [10]. For clarity, we used a selected set of EN-XX experiment results for our discussion; full results for EN-XX and XX-EN are in Appendix Appendix C.

To identify the best-performing technique under different data setups, we analyzed the results with respect to dataset sizes of the intermediate (IM) and final (FI) stages in the following four combinations (recall that Adelani et al. [8] considered only the large-small data setup): 1) **small-small** (IM data 1k - TD data 1k); 2) **large-small** (IM data 25k - TD data 1k); 3) **small-large** (IM data 1k - TD data 25k); 4) **large-large** (IM data 25k - TD data 25k).

5.2.1. In-Domain Test Case

In-domain results are reported in Tables 5-8. In this setup, we consider either PMI/Gvt or Bible as the target domain. Baseline results are reported by training mBART with the target domain, and testing with the same. In ITTF experiments, the second stage of fine-tuning is done using this target domain data. In each table, the best technique appears in bold, the second best appears in italic. Worst is grayed out.

⁴These terms for dataset sizes are simply relative. In Ranathunga et al.'s [28], even 25k parallel data is considered an extremely small data setup. However, the maximum data size we can use is bound by domain data availability.

small-small. According to Table 5, multi-domain ITTL is the best-performing technique. However, on average, its gains over the second-best technique (multi-domain FT, which uses less compute) is less than 1 spBLEU. Hence, under limited computing resources, multi-domain FT the best option.

large-small. Comparing Table 6 against Table 5 (small-small setup), increasing the intermediate task size from 1k to 25k is consistently beneficial. In this data setup, multi-domain ITTL performs better than the other two

Longuago	ou	ıt domain	in domain					
Language	bitex	bitex+mono	bitex	bitex+mono				
KA	-0.2	-0.6	-0.8	-0.6				
SI	-0.2	-0.4	-0.5	0.3				
HI	-0.2	-0.5	0.3	-0.4				

Table 4: Average difference of NMT results between continuously pre-trained mBART and original mBART

Language	Interi	nediat Final	e task - task - 1	- PMI/Gvt Bible	Intermediate task - Bible Final task - PMI/Gvt						
	Single ITTL	Multi FT	Multi ITTL	Baseline	Single ITTL	Multi FT	Multi ITTL	Baseline			
SI	17.2	16.7	16.7	17.0	20.9	21.4	22.3	20.2			
ТА	11.0	14.5	15.0	9.3	19.9	18.9	20.1	18.6			
GU	13.0	13.3	13.2	12.9	18.8	19.4	20.1	20.9			
HI	15.5	15.0	15.7	14.0	18.3	18.5	19.3	18.2			
KA	9.4	9.1	8.9	8.2	5.9	6.2	6.6	6.5			
Avg	13.2	13.7	13.9	12.3	16.8	16.9	17.7	16.9			

Table 5: In-domain results. Intermediate task-1k, final task-1k.

Language	Inter	mediate Final	e task - task - E	PMI/Gvt Bible	Intermediate task - Bible Final task - PMI/Gvt				Intermediate task - CC Final task - PMI/Gvt				Intermediate task - CC Final task - Bible			
	Single ITTL	Multi FT	Multi ITTL	Baseline	Single ITTL	Multi FT	Multi ITTL	Baseline	Single ITTL	Multi FT	Multi ITTL	Baseline	Single ITTL	Multi FT	Multi ITTL	Baseline
SI	18.9	19.4	19.4	17.0	22.1	19.8	24.5	20.2	24.1	23.7	25.8	20.2	19.3	17.4	18.8	17.0
TA	13.4	13.5	14.5	9.3	18.3	18.3	19.7	18.6	20.0	20.0	21.0	18.6	14.5	14.9	16.4	9.3
GU	14.3	14.6	15.1	12.9	19.9	20.5	21.5	20.9	23.8	24.3	24.6	20.9	13.9	13.3	15.4	12.9
HI	15.3	15.9	16.7	14.0	18.7	18.1	19.2	18.2	20.0	20.8	21.1	18.2	16.1	16.2	16.3	14.0
KA	12.7	12.8	13.8	8.2	12.9	12.5	15.5	6.5	12.9	13.8	14.8	6.5	9.6	9.6	10.0	8.2
Avg	14.9	15.2	15.9	12.3	18.4	17.8	20.1	16.9	20.2	20.5	21.5	16.9	14.7	14.3	15.4	12.3

Table 6: In-domain results. Intermediate task - 25k, final task - 1k.

Language	Inter	mediat Final	e task task -	- PMI/Gvt Bible	Intermediate task - Bible Final task - PMI/Gvt						
	Single ITTL	Multi FT	Multi ITTL	Baseline	Single ITTL	Multi FT	Multi ITTL	Baseline			
SI	37.6	37.7	38.2	37.9	45.0	43.8	45.3	44.7			
TA	30.5	30.9	30.7	31.0	37.1	37.7	38.1	36.8			
GU	27.3	27.8	27.7	27.8	38.0	37.8	37.8	37.9			
HI	31.5	31.7	31.2	31.4	35.1	35.3	34.9	35.2			
KA	27.0	27.4	27.6	27.8	33.8	33.8	34	33.6			
Avg	30.8	31.1	31.1	31.2	37.8	37.7	38.0	37.6			

Table 7: In-domain results. Intermediate task-1k, final task-25k.

Language	Inter	mediate Final	e task - task - E	PMI/Gvt Bible	Intermediate task - Bible Final task - PMI/Gvt				In 1	ntermeo Final ta	liate ta sk - PN	sk - CC II/Gvt	Intermediate task - CC Final task - Bible			
	Single ITTL	Multi FT	Multi ITTL	Baseline	Single ITTL	Multi FT	Multi ITTL	Baseline	Single ITTL	Multi FT	Multi ITTL	Baseline	Single ITTL	Multi FT	Multi ITTL	Baseline
SI	38.1	37.9	37.9	37.9	44.2	43.7	44.0	44.7	44.4	43.9	44.7	44.7	37.9	38.0	37.9	37.9
TA	30.9	30.4	30.7	31.0	37.2	37.0	38.2	36.8	37.2	37.7	37.9	36.8	30.8	30.6	30.7	31.0
GU	27.4	27.7	28.2	27.8	37.6	37.7	37.6	37.9	38.3		37.6	37.9	26.9	27.8	27.9	27.8
HI	31.6	31.4	31.4	31.4	34.4	35.1	35.1	35.2	35.5	35.4	35.3		31.5	31.4	31.1	31.4
KA	27.5	26.2	27.2	27.8	32.8	32.7	34.4	33.6	34.3		33.7	33.6	27.3	26.5	27.4	27.8
Avg	31.1	30.7	31.1	31.2	37.2	37.2	37.9	37.6	37.9	37.6	37.8	37.6	30.9	30.9	31.0	31.2

Table 8: In-domain results. Intermediate task - 25k, final task - 25k.

techniques (more than 1 average spBLEU gains except in one experiment) irrespective of the domain differences, thus confirming Adelani et al.'s [8] observations (see Section 2.1).

small-large and large-large. According to Tables 7 and 8, when there are 25k sentences from the target domain, none of the techniques managed to significantly outperform vanilla FT baseline, thus questioning the benefit of auxiliary domain data.

The above observations are supported by Figure 2 as well ⁵. Note that the line corresponding to 0k in the graphs is the vanilla FT baseline. When the target (final) task size is less than 10k, all three techniques are effective over the vanilla FT baseline, but to varying degrees. However, as the target task data set size increases, their results converge to baseline. Even using 100k CC data was not able to make gains in performance when the target

 $^{^{5}}$ Graphs for all the experiments are in Appendix D



(a) Method - single-domain ITTL. Intermediate dataset - CC, Final dataset - PMI/Gvt, Test dataset - PMI/Gvt.



(b) Method - multi-domain FT. Intermediate dataset - CC, Final dataset - PMI/Gvt, Test dataset - PMI/Gvt.



(c) Method - multi-domain ITTL. Intermediate dataset - CC, Final dataset - PMI/Gvt, Test dataset - PMI/Gvt.

Figure 2: In-domain testing for different methods.

domain data set is at least 25k. Thus our results emphasize that Adelani et al.'s [8] observations do not always hold, and it is important to consider the size of the datasets.

An important observation is the results for KA, which is unseen in mBART. Adding an intermediate task with 1k auxiliary data only results in a less than 1 spBLEU gain for this language in the small-small data setup. However, when adding 25k auxiliary data at the intermediate stage results in a significant gain (5.9 spBLEU on average) resulting in the largest gain amongst the languages.

5.2.2. Out-domain Test Case

We use the results for the FLORES test set to explain our observations in Tables 9-12. In ITTL experiments, either PMI/Gvt or Bible is used as the final stage of fine-tuning. PMI/Gvt, Bible, and/or CC are used at the inter-

Language	Inter	mediat Final	e task - task - I	- PMI/Gvt Bible	Intermediate task - Bible Final task - PMI/Gvt						
	Single ITTL	Multi FT	Multi ITTL	Baseline	Single ITTL	Multi FT	Multi ITTL	Baseline			
SI	2.4	4.4	4.3	0.9	4.9	4.4	4.5	3.9			
ТА	2.2	3.7	3.6	0.7	3.9	3.7	3.9	2.6			
GU	6.0	7.8	7.9	2.2	8.3	7.8	8.1	7.3			
HI	4.8	8.0	7.6	2.6	8.4	8.0	8.2	7.1			
KA	0.5	1.1	1.1	0.3	1.0	1.1	1.2	1.0			
Avg	3.2	5.0	4.9	1.3	5.3	5.0	5.2	4.4			

Table 9: Out-domain results. Intermediate task-1k, final task-1k.

Language	Inter	rmediat Final	e task - task - B	PMI/Gvt Sible	Intermediate task - Bible Final task - PMI/Gvt						
	Single ITTL	Multi FT	Multi ITTL	Baseline	Single ITTL	Multi FT	Multi ITTL	Baseline			
SI	1.9	4.6	2.8	1.9	11.3	11.3	11.3	11.2			
ТА	2.2	3.8	2.9	2.1	9.5	9.5	9.8	9.0			
GU	5.2	9.4	9.0	4.4	20.2	19.8	20.0	19.8			
HI	3.4	6.9	6.5	3.2	16.9	17.4	17.8	17.3			
KA	2.3	3.9	3.2	2.2	14.0	14.5	14.5	14.1			
Avg	3.0	5.7	4.9	2.8	14.4	14.5	14.7	14.3			

Table 10: Out-domain results. Intermediate task-1k, final task-25k

Language	Inter	mediat Final	e task - task - E	PMI/Gvt Bible	Intermediate task - Bible Final task - PMI/Gvt				Intermediate task - CC Final task - PMI/Gvt				Intermediate task - CC Final task - Bible			
	Single ITTL	Multi FT	Multi ITTL	Baseline	Single ITTL	Multi FT	Multi ITTL	Baseline	Single ITTL	Multi FT	Multi ITTL	Baseline	Single ITTL	Multi FT	Multi ITTL	Baseline
SI	7.9	11.3	11.3	0.9	5.8	4.2	5.6	3.9	8.9	9.7	10.6	3.9	3.5	8.8	8.4	0.9
TA	5.4	9.4	8.7	0.7	4.9	3.8	4.3	2.6	10.1	12.2	12.4	2.6	7.2	10.8	10.6	0.7
GU	15.3	19.8	19.7	2.2	10.5	9.3	10.2	7.3	16.8	16.1	16.5	7.3	9.6	12.2	11.9	2.2
HI	12.8	17.1	17.1		8.8	7.1	8.2	7.1	13.3	16.3	16.0	7.1	7.1	14.9	14.9	
KA	7.6	14.3	13.7	0.3	4.5	4.4	5.1	1.0	4.5	4.7	5.6	1.0	0.9	1.7	1.9	0.3
Avg	9.8	14.4	14.1	1.34	6.9	5.8	6.7	4.4	10.7	11.8	12.2	4.4	5.7	9.7	9.5	1.3

Table 11: Out-domain results. Intermediate task - 25k, final task - 1k.

mediate stage⁶. Here, baseline refers to vanilla FT with the dataset used for

⁶Unlike domain-specific datasets s.a Bible, CC corpus is larger even for LRLs. Thus we do not run 1k setup for CC.

Language	Language Final task - Bible					Intermediate task - Bible Final task - PMI/Gvt				Intermediate task - CC Final task - PMI/Gvt				Intermediate task - CC Final task - Bible			
	Single ITTL	Multi FT	Multi ITTL	Baseline	Single ITTL	Multi FT	Multi ITTL	Baseline	Single ITTL	Multi FT	Multi ITTL	Baseline	Single ITTL	Multi FT	Multi ITTL	Baseline	
SI	2.4	11.6	11.5	1.9	11.9	9.9	10.5	11.2	12.1	14.1	13.3	11.2	2.0	9.5	8.8	1.9	
TA	2.8	9.9	6.6	2.1	10.0	11.5	11.8	9.0	11.1	14.8	14.7	9.0	2.9	11.0	6.1	2.1	
GU	8.0	20.8	20.0	4.4	20.5	20.8	20.6	19.8	21.5	23.7	24.1	19.8	5.6	13.3	14.6	4.4	
HI	4.3	17.6	16.5	3.2	18.4	17.2	18.0	17.3	18.3	21.5	21.3	17.3	3.8	14.5	12.6	3.2	
KA	3.2	14.3	8.6	2.2	14.2	14.3	15.5	14.1	15.0	16.6	16.2	14.1	2.4	4.2	3.1	2.2	
Avg	4.1	14.8	12.6	2.8	15.0	14.7	15.2	14.2	15.6	18.1	17.9	14.3	3.3	10.5	9.0	2.8	

Table 12: Out-domain results. Intermediate task - 25k, final task - 25k.

the final task (e.g. if Bible is used as the final task in the ITTL experiments, baseline refers to vanilla FT with Bible and testing with FLORES).

Unlike in the in-domain test case, in the out-domain test case, there exists a large impact of domain divergence. To begin with, vanilla FT baseline performs significantly better (average gain 11.5 BLEU) when PMI/Gvt is used for fine-tuning, compared to using Bible. This observation can be explained with the domain divergence results in Table 2, where the divergence between FLORES and Bible (0.47) is higher than that between FLORES and PMI/Gvt (0.33/0.4).

Similarly, for all four data size setups, the best results from both the ITTL strategies are reported when a domain more closer to FLORES is used in final stage fine-tuning. The best result is reported when both the intermediate dataset and the final dataset are from domains closer to the target domain (e.g. CC and PMI/Gvt).

The impact of domain divergence is visible in Figure 3 as well. For example, in single-domain ITTL in Figure 3b, results for FLORES decrease to baseline when Bible dataset size increases in the final stage. In contrast, in Figure 3a, when PMI/Gvt is used in the final stage, results for FLORES mostly increase when PMI/Gvt size increases.

For all four data size setups, all three techniques are better than the vanilla FT baseline, but in varying degrees. In order to further explain this observation, we calculated the correlation (R^2) between JSD (of the final stage dataset and test set) and the corresponding spBLEU score. We see that the average R^2 is 0.78 for the baseline, while the same is 0.57, 0.20 and 0.59 for single-domain ITTL, multi-domain ITTL and multi-domain FT (respectively). This indicates that, compared to the vanilla FT baseline, domain divergence is less correlated to the performance when auxiliary domain data is used.

Overall, both multi-domain ITTL and multi-domain FT are better than



(a) Method - single-domain ITTL. Intermediate dataset - CC, final dataset - PMI/Gvt, test set - FLORES.



(b) Method - single-domain ITTL. Intermediate dataset - PMI/Gvt, final dataset - Bible, test set - FLORES.





(d) Method - multi-domain ITTL. Intermediate dataset - CC, final dataset - PMI/Gvt, test set - FLORES.

Figure 3: Out-domain testing for different methods.

single-domain ITTL, except in two cases. However, the results difference between multi-domain ITTL and multi-domain FT is marginal. In fact, in more than half of the experiments reported in Tables 9-12, multi-domain ITTL underperforms multi-domain FT. Our summary results also show that the variance of performance for multi-domain FT and multi-domain ITTL is 17.2 and 28.00 (respectively). The higher variance of multi-domain ITTL indicates that the final stage fine-tuning in the multi-domain ITTL model is more susceptible to domain divergence compared to multi-domain FT.

6. Ablation Study

6.1. Impact of Up-sampling

In both small-large and large-small dataset setups, one dataset size is significantly smaller than the other. In order to dilute the impact of size difference, we up-sampled⁷ the smaller data set to match with the larger dataset. For this experiment, we used CC (the largest dataset) and Bible, and experimented with three languages. As shown in Table 13, we do not see any gains from upsampling.

Mathad	$\mathbf{C}\mathbf{C}$	Bible		hi			ka		:	si	
Method	Size	Size	FLORES	Bible	PMI	FLORES	Bible	PMI	FLORES	Bible	\mathbf{Gvt}
	951-	1k	-6.8	0.6	-4.4	-1.3	-0.6	-0.9	-4.2	0.2	-7.5
M.1+;	ZOK	10k	-1.8	0.3	-1.8	-0.8	0.4	-0.5	-1.5	0.2	-2.9
FT		1k	-13.1	1.2	-9.2	-3.8	3.9	-2.5	-8.5	1.3	-13.6
I' 1	100k	10k	-7.9	0.6	-5.2	-0.7	6.0	-0.6	-4.8	1.1	-7.9
		25k	-4.9	0.3	-3.4	-1.4	2.7	-0.7	-2.7	1.4	-2.6
	951-	1k	-7.1	0.5	-4.7	-1.5	-0.4	-0.9	-3.9	-0.9	-7.2
M.1+;	ZOK	10k	-1.6	0.2	-1.6	-0.4	0.3	-0.1	-1.7	-0.1	-3.2
IVIUIUI		1k	-14	0.6	-9.5	-4.8	-0.1	-2.9	-9.1	0.1	-13.8
1111	100k	10k	-8.1	0.6	-5.7	-0.6	0.2	0.0	-2.0	-0.6	-1.7
		25k	2.1	-0.7	1.6	0.2	1.2	-0.2	0.5	0.9	0.8

Table 13: Performance diff with/without minority class upsampling. Grey text - upsampling under-perform.

6.2. Mixing more than two domains

All our previous experiments involved only two domains. In order to investigate the impact of combining multiple domains, we mixed data from CC, Bible, and PMI/Gvt separately for SI and KA. As seen in Tables 14 and 15, the inclusion of an extra domain during training does not consistently improve performance due to domain divergence.

In multi-domain FT (Table 14), when testing on FLORES, combining Bible with CC+PMI/Gvt yielded inferior results. A similar observation holds

 $^{^7\}mathrm{random}$ oversampling (https://t.ly/MLrhd), we use the term up-sampling to mean oversampling

Multi Domaina	Domain Sizo]	KA		5	SI	
Wulti-Domains	Domain Size	FLORES	Bible	\mathbf{PMI}	FLORES	Bible	\mathbf{Gvt}
CC+Bible	25k + 25k	4.2	26.5	2.1	9.5	38.0	16.6
CC+PMI/Gvt	25k+25k	16.6	1.1	33.5	14.1	2.7	43.9
$\rm CC+PMI/Gvt+Bible$	$25\mathrm{k}{+}25\mathrm{k}{+}25\mathrm{k}$	14.5	25.1	31.9	13.6	37.2	43.5

Table 14: The spBLEU score for Multi-domain FT with different domain combinationfor KA and SI.

Intermediat	e Task	Final S	tage		ka			si	
Multi-Domains	Domain Size	Domain	Size	FLORES	Bible	PMI	FLORES	Bible	\mathbf{Gvt}
CC+Bible	25k+25k	Bible	951-	3.1	27.4	1.4	8.8	37.9	15.6
CC+PMI/Gvt+Bible	$25\mathrm{k}{+}25\mathrm{k}{+}25\mathrm{k}$	Dible	ZJK	7.0	27.8	14.4	9.1	37.6	34.3
Impro	ovement	Į.		3.9	0.4	13.0	0.3	-0.3	18.7
CC+PMI/Gvt	25k+25k	DMI/Cut	95k	16.2	1.8	33.7	13.3	2.3	44.7
CC+PMI/Gvt+Bible	$25\mathrm{k}{+}25\mathrm{k}{+}25\mathrm{k}$	I MI/GVt	20K	16.6	19.8	34.3	13.8	31.0	45.0
Impro	ovement	1		0.4	18.0	0.6	0.5	28.7	0.3

Table 15: spBLEU score for Multi-domain ITTL with different domain combinations for KA and SI. Last row shows the improvement of using three domains.

for the in-domain test case—adding Bible to CC+PMI/Gvt drops the result on PMI/Gvt.

In multi-domain ITTL (Table 15), when testing on FLORES, adding PMI/Gvt to CC+Bible significantly improves the results, but adding Bible to CC+PMI/Gvt yields marginal gains. Similarly, in the in-domain case, adding PMI/Gvt to CC+Bible does not increase the result on Bible, and adding Bible to CC+PMI/Gvt does not increase the result on PMI/Gvt.

7. Conclusions

The optimal way of using auxiliary domain parallel data to build domainspecific LRL-NMT systems on msLMs was an under-explored problem. We presented the first comparative study of two ways to utilize this parallel data—fine-tuning and additional pre-training. Based on our experiments, we are able to provide a set of observations, which will assist NMT researchers in selecting the optimal way to use data from auxiliary domains, without having to run extensive sets of experiments. In the future, we plan to experiment with multilingual FT and ITTL, as well as multilingual and multi-domain FT and ITTL. It would also be worthwhile to explore new pre-training objectives on parallel data as well.

Appendix A. Experiment Setup

Appendix A.1. Corpus Details (from [10])

PMIndia corpus (PMI). [29] is a multi-way parallel corpus of 14 languages (13 Indian languages, plus English). The data set contains Indian Prime Minister's speeches extracted from the Prime Minister of India website⁸.

Government corpus (Gvt). [30] is a multi-way parallel corpus for Sinhala, Tamil, and English. This is a manually curated data set. It consists of data from official government documents (annual reports, committee reports, government institutional websites, and acts of the Parliament).

Bible corpus. We scrape Bible data from web⁹ and then automatically align the sentences (at verse level) using the scripts provided by Nayak et al. [10] This curated multi-way parallel corpus has 25k parallel sentences in KN, GU, HI, TA. Note that Sinhala was scraped from a different website, thus has different content¹⁰.

CCAligned (CC). is an automatically sentence-aligned (bi-text mined) corpus based on the CommonCrawl.

FLORES-101. [26] is a multi-way parallel corpus. The source is English Wikipedia, which has been manually translated into 101 languages. Data comes from a variety of topics and domains, thus can be considered opendomain. We use FLORESv1 [31] for Sinhala since it is not present in FLORES-101.

Appendix A.2. Model Training

Our implementation is based on the Fairseq library. All experiments are run with seed 222. We used an Nvidia Volta of 32 GPU RAM.

Training details are as follows: number of epochs =3, learning rate = $3 \cdot 10^{-5}$, dropout = 0.3, attention dropout = 0.1, and a batch size = 32 for training and evaluation.

⁸https://www.pmindia.gov.in/en/

⁹Sinhala: https://www.wordproject.org/bibles/si/index.htm; and others: https://ebible.org/download.php

¹⁰We will be releasing the scripts to create the corpus on acceptance of the paper.

Appendix A.3. Evaluation Metric

spBLEU calculates the BLEU score for the text tokenized using the sentence-piece sub-word model, which has been trained for all the 101 languages in FLORES-101 data set (including the languages (except KN) considered in our experiments). Furthermore, Goyal et al. [26] showed that spBLEU functions similarly to BLEU and has a strong correlation with the Chrf++ metric. [32] ¹¹. The sacreBLEU signature for pre-training with bi-text denoising is: nrefs:1—case:mixed—eff:no—tok:

spm-flores—smooth:none—version:2.1.0. The sacreBLEU signature for Singledomain ITTL is: nrefs:

1—case:mixed—eff:no—tok:spm-flores—smooth:none—version:2.2.1.

The signature for Multi-domain ITTL is: nrefs:1—case:mixed—eff:no—tok:flores101—smooth:none—version:2.3.1.

Appendix A.4. Jenson-Shannon Divergence

Jenson-Shannon Divergence (JSD) is calculated between two distributions P and Q using the formula given below:

$$JSD(P||Q) = \frac{1}{2}KL(P||M) + \frac{1}{2}KL(Q||M)$$

Here, M represents an equally weighted sum of the two distributions (i.e., $M = \frac{1}{2}P + \frac{1}{2}Q$). $KL(\cdot||\cdot)$ represents the Kullback–Leibler divergence. JSD ranges from 0 to 1 - lower the value, more similar the distributions are.

Divergence is calculated between each pair of train and test sets, for a given language pair. These language-specific values are then averaged to obtain a similarity score independent of the target language.

Following our previous work [10], each corpus was first tokenized (times and numbers were also converted into the tokens <TIME> and <NUMBER>, respectively) using the NLTK package,¹³ and stopwords were removed. The resulting corpora were transformed into a (discrete) frequency distribution over all word tokens. The frequency distributions of each train and test set are then compared using the formula above.

 $^{^{11}}$ We use the official implementation provided in the sacreBLEU library 12 [33] 13 https://www.nltk.org/

Pro training Sot	Pro training	Pro training Sot Siz	o Fino tuning	Set Fine tuning Set Size		ka			si			hi	-
1 re-training Set	1 re-training	1 le-training Set Siz	e rme-tuning	Set Fille-tuning Set Size	FLORES	Bible	PMI	FLORES	Bible	Gvt	FLORES	Bible	e PMI
	Lieure	25k		25k	1.0	0.0	0.6	8.5	1.9	14.1	12.3	5.0	11.3
00	bitext	100k	00	100k	6.2	0.1	4.5	15.4	4.1	26.4	22.7	6.8	17.8
00	1.5.7.1.1.1	25k	00	25k	0.5	0.0	0.4	8.4	1.8	13.3	14.0	5.4	11.9
	bitext + monolignual	100k		100k	5.8	0.2	4.1	14.6	4.1	25.9	22.9	6.9	18.4
	Literat	1k		1k	0.5	0.1	3.7	3.7	0.5	19.5	6.5	1.4	17.3
	bitext	10k		10k	9.6	1.1	28.9	8.8	0.9	39.7	14	2.2	31.7
		25k		25k	14.3	1.9	34.3	10.8	1.1	44.9	17.2	3	35.6
DMI/CL		50k	DM //C	50k	N/A	N/A	N/A	12.2	1.3	48.7	19.1	3.3	37.2
PMI/Gvt	1.5.7.1.1.1	1k	PMI/Gvt	1k	0.5	0.1	3.3	3.2	0.4	21.2	7.1	1.7	18.6
	bitext + monoiinguai	10k		10k	9.1	0.9	29.1	8.3	0.8	38.3	14	2.4	31.8
		25k		25k	12.8	1.6	33.8	10.7	1.1	44.5	17.2	3	35.6
		50k		50k	N/A	N/A	N/A	11.7	1.3	49.2	18.7	3.3	36.8
		1k		1k	0.3	6.7	0.2	0.7	12.6	1.1	2.4	15.9	2.1
	bitext	10k		10k	1.5	21.9	0.6	1.8	33.7	0.8	2.9	26.9	2.2
D:11		25k	D11	25k	2.1	28	0.8	1.6	38	0.7	3	31.6	2.1
Bible		1k	Bible	1k	0.3	7.4	0.2	0.8	17.9	1.2	0.9	10.5	1.2
	bitext + monolignual	10k		10k	1.3	22.4	0.6	1.8	33.9	0.8	2.9	26.8	2
		25k		25k	1.8	28	0.7	1.7	37.9	0.7	2.7	31.4	1.9

Appendix B. Pre-training results

Table B.16: Results (spBLEU) for pre-training with bi-text denoising.

Appendix C. Tabular Results for Individual Techniques

Appendix C.1. Result Tables for EN-XX

D1	D1 siz	e D2	D2 size		ka			\mathbf{gu}			hi			si			ta	
51	DI			FLORE	S Bible	e PMI	FLORE	S Bible	$e \mathbf{PMI}$	FLOR	RES Bible	e PMI	FLOR	ES Bible	e Gvt	FLOR	ES Bibl	e Gvt
			1k	4.5	0.4	12.9	16.8	3.6	23.8	13.3	3.6	20	8.9	1.7	24.1	10.1	5.9	20.0
	951		10k	12.4	1.6	30.5	19.4	4.6	34.7	16.6	3.3	31.8	10.6	1.9	39.2	9.8	3.6	33.4
	ZJK		25k	15.0	1.9	34.3	21.5	5.1	38.3	18.3	3.3	35.5	12.1	1.9	44.4	11.1	3.3	37.2
00		DMI/C	50k	N/A	N/A	N/A	N/A	N/A	N/A	19.9	3.8	37.0	12.8	2.0	49.7	12.1	2.8	40.1
CC		PMI/GV	^l 1k	10.2	1.1	16.2	20.9	3.7	26.0	22.1	6.1	24.0	16.3	4.6	31.0	20.3	9.4	23.9
	1001-		10k	14.6	1.8	30.3	22.5	5.2	35.1	20.3	4.9	32.5	15.2	4.1	41.4	15.4	6.2	34.1
	100K		25k	16.3	2.1	34.1	22.9	5.4	38.5	21.4	4.4	35.2	15.2	3.6	44.3	15.0	5.0	37.6
			50k	N/A	N/A	N/A	N/A	N/A	N/A	22.5	4.4	37.0	15.2	3.5	48.7	14.9	4.5	40.5
			1k	0.9	9.6	0.7	9.6	13.9	8.5	7.1	16.1	6.8	3.5	19.3	6.2	7.2	14.5	6.7
	25k		10k	2.1	23.1	0.9	6.6	23.7	5.1	4.0	26.4	3.0	2.2	33.5	2.2	3.0	26.1	2.5
CC		Dible	25k	2.4	27.3	1	5.6	26.9	4.1	3.8	31.5	2.4	2.0	37.9	1.0	2.9	30.8	1.6
CC		Dible	1k	4.1	11.2	2.3	14.6	13.3	11.9	16.9	16.5	14.5	11.0	20.1	19.0	17.2	16.3	15.3
	100k		10k	2.8	22.9	1.4	8.3	24.2	6.9	6.6	26.8	5.5	3.9	33.4	5.4	5.9	26.2	6.0
			25k	2.8	27.4	1.2	6.9	27.8	5.4	4.8	31.7	3.3	3.0	37.9	2.6	4.2	31.0	3.2
			1k	0.5	9.4	1.0	6.0	13.0	15.6	4.8	15.5	11.4	2.4	17.2	13.1	2.2	11.0	13.7
	1k		10k	1.7	22.0	0.9	5.1	24.2	6.6	3.3	27.2	2.9	1.9	34.1	3.2	2.3	26.3	3.7
			25k	2.3	27.0	1.1	5.2	27.3	5.1	3.4	31.5	2.5	1.9	37.6	1.8	2.2	30.5	2.7
			1k	4.2	12.4	12.9	11.8	14.7	26.3	10.2	15.8	24.7	5.3	17.5	29.8	3.8	13.6	23.3
	10k		10k	2.8	23.1	2.9	7.4	24.2	13.6	5.1	26.9	8.9	2.2	32.4	8.0	2.6	25.8	8.1
DMI/C-		D:11-	25k	2.9	27.1	2.1	6.5	27.7	9.1	4.2	31.5	4.6	2.1	37.8	4.4	2.5	30.6	4.8
PMI/GV	L	Dible	1k	7.6	12.7	21.3	15.3	14.3	31.8	12.8	15.3	29.3	7.9	18.9	36.7	5.4	13.4	28.4
	25k		10k	3.7	23.1	6.1	9.7	23.9	20.1	6.0	27.0	12.8	3.3	33.1	14.5	3.2	24.8	13.8
			25k	3.2	27.5	2.8	8.0	27.4	13.4	4.3	31.6	6.4	2.4	38.1	6.5	2.8	30.9	7.3
			1k	N/A	N/A	N/A	N/A	N/A	N/A	14.7	16.0	31.3	8.4	19.2	40.5	6.9	13.7	32.5
	50k		10k	N/A	N/A	N/A	N/A	N/A	N/A	6.7	26.7	15.8	4.3	33.5	17.8	3.8	25.0	17.3
			25k	N/A	N/A	N/A	N/A	N/A	N/A	4.8	31.8	8.2	3.0	37.3	8.6	3.3	30.5	9.8
			1k	1.0	1.6	5.9	8.3	9.6	18.8	8.4	8.6	18.3	4.9	10.3	20.9	3.9	6.1	19.9
	11.		10k	10.0	1.7	28.5	17.3	7.5	34.5	14.7	5.3	31.4	9.3	5.5	38.6	7.0	4.6	32.7
	IK		25k	14.0	2.0	33.8	20.2	6.8	38.0	16.9	4.7	35.1	11.3	3.5	45.0	9.5	3.0	37.1
			50k	N/A	N/A	N/A	N/A	N/A	N/A	19.1	4.9	37.2	12.3	3.5	49.5	11.2	2.6	40.7
			1k	4.0	12.0	12.8	10.3	19.4	20.2	9.1	20.1	19.2	6.1	25.1	22.4	4.8	19.3	18.9
D:11.	101-	DMI/C-	10k	11.4	6.0	29.7	18.1	13.9	34.8	15.4	14.2	31.4	10.0	15.1	39.3	7.9	12.2	33.2
Dible	10K	PMI/GV	^t 25k	14.3	4.3	34.2	20.5	12.0	37.9	17.9	10.8	34.7	11.8	12.2	44.2	9.9	10.2	37.3
			50k	N/A	N/A	N/A	N/A	N/A	N/A	19.9	10.1	36.7	12.7	9.3	49.0	11.6	8.5	39.8
			1k	4.5	16.3	12.9	10.5	22.6	19.9	8.8	23.9	18.7	5.8	28.7	22.1	4.9	24.3	18.3
	951-		10k	11.6	8.4	29.8	17.8	17.4	33.7	15.4	17.2	31.2	10.0	19.6	39.1	8.0	14.9	33.6
	ZOK		25k	14.2	6.5	32.8	20.5	14.7	37.6	18.4	15.2	34.4	11.9	14.9	44.2	10.0	13.2	37.2
			50k	N/A	N/A	N/A	N/A	N/A	N/A	20	12.7	36.8	12.9	12.7	48.6	11.2	11.4	39.9

Table C.17: Results (spBLEU) for single-domain ITTL. Here D1 refers to Domain 1 and D2 refers to Domain 2.

D1 + D2	D1 + D2 size		ka			$\mathbf{g}\mathbf{u}$			hi			si			\mathbf{ta}	
51 52	DI Di olio	FLOR	ES Bible	e PMI	FLOR	ES Bibl	e PMI	FLOR	tes Bibl	e PMI	FLOR	RES Bibl	e Gvt	FLOI	RES Bibl	e Gvt
	25k + 1k	4.7	0.0	13.8	16.1	2.1	24.3	16.3	5.6	20.8	9.7	1.9	23.7	12.2	6.6	20.0
	25k + 10k	13.6	0.4	30.0	22.2	3.4	34.4	19.4	5.9	31.2	12.2	2.4	37.9	13.1	7.0	32.7
	25k + 25k	16.6	1.1	33.5	23.7	5.1	37.5	21.5	6.4	35.4	14.1	2.7	43.9	14.8	7.5	37.7
CC + DML/C-+	25k + 50k	N/A	N/A	N/A	N/A	N/A	N/A	22.9	6.6	36.9	14.9	2.8	47.9	15.3	7.4	40.0
CC + PMI/Gvt	100k + 1k	6.1	0.2	11.1	15.8	1.6	24.9	23.9	7.2	23.6	15.5	4.5	30.4	18.7	9.3	21.4
	100k + 10k	12.7	0.7	25.1	22.4	3.7	33.4	26.1	7.4	31.8	16.7	4.9	38.7	19.0	9.8	31.6
	100k + 25k	15.0	1.0	29.8	23.5	5.0	36.8	26.9	7.5	35.2	17.3	4.6	43.2	19.6	9.4	35.3
	100k+50k	N/A	N/A	N/A	N/A	N/A	N/A	27.1	7.8	36.3	17.6	4.4	45.7	19.9	8.8	37.5
	25k + 1k	1.7	9.6	1.2	12.2	13.3	8.2	14.9	16.2	12.2	8.8	17.4	14.8	10.8	14.9	8.9
	25k + 10k	3.6	22.4	2.0	12.8	23.9	10.7	14.8	27.0	12.6	9.8	33.1	16.9	11.3	26.1	9.4
00 . 011	25k + 25k	4.2	26.5	2.1	13.3	27.8	11.5	14.5	31.4	11.9	9.5	38	16.6	11.0	30.6	9.5
CC + Bible	100k + 1k	4.3	7.3	2.9	12.1	13.1	11.2	23.9	16.4	19.0	15.4	18.8	26.8	18.7	16.0	17.0
	100k + 10k	4.1	16.7	2.8	12.9	22.2	12.6	24.1	27.0	19.1	15.4	31.9	27.4	18.8	24.5	17.1
	100k+25k	5.8	22.6	3.5	11.9	25.0	10.2	23.8	30.6	19.3	15.4	35.7	26.8	18.1	28.3	16.2
	1k + 1k	1.1	9.1	6.2	7.7	13.1	19.4	8.0	15.0	18.5	4.4	18.5	21.4	3.7	14.5	18.9
	1k + 10k	3.7	22.7	11.8	8.8	23.8	20.3	7.5	26.7	18.1	4.9	33.4	22.4	3.9	25.1	17.4
	1k + 25k	4.4	27.8	12.5	9.3	27.6	20.5	7.1	30.8	18.1	4.2	36.6	19.8	3.8	30.9	18.3
	10k + 1k	11.2	12.6	29.3	17.2	14.2	34.0	15.0	16.7	31.0	9.1	19.4	39.3	7.5	14.9	33.7
	10k + 10k	11.9	22.8	29.3	17.9	24.2	34.1	14.7	27.2	30.5	9.5	33.8	39.0	7.9	25.9	33.0
	10k + 25k	11.8	27.3	29.3	18.2	27.8	34.2	14.5	31.1	30.8	9.4	37.5	38.5	7.6	30.4	33.0
PMI/Gvt + Bible (1st)	25k + 1k	14.5	13.0	33.8	19.8	15.0	37.8	17.4	16.5	35.3	11.3	19.2	43.8	9.5	14.7	37.7
	25k + 10k	14.9	23.0	33.7	20.9	24.1	37.4	17.4	27.2	35.6	11.9	33.8	44.9	9.9	25.9	37.3
	25k + 25k	14.3	26.2	32.7	20.8	27.7	37.7	17.2	31.4	35.1	11.5	37.7	43.7	9.9	30.4	37.0
	50k + 1k	N/A	N/A	N/A	N/A	N/A	N/A	19.4	17.2	37.4	12.4	20.0	48.6	11.2	14.1	40.1
	50k + 10k	N/A	N/A	N/A	N/A	N/A	N/A	20.1	26.8	37.1	12.7	33.4	48.2	11.3	25.6	39.7
	50k + 25k	N/A	N/A	N/A	N/A	N/A	N/A	19.2	31.0	36.2	12.6	37.4	46.9	11.2	29.5	39.4
	1k + 1k	1.1	9.1	6.2	7.9	13.3	19.2	8.0	15.0	18.5	4.3	16.7	19.5	3.7	14.5	18.9
	1k + 10k	3.2	22.2	10.8	9.2	24.2	21.0	7.7	27.0	18.5	4.8	33.7	22.7	3.6	24.6	16.9
	1k + 25k	3.9	27.4	11.3	9.4	27.8	21.2	6.9	31.7	18.2	4.6	37.7	22.3	3.8	30.9	18.3
	10k + 1k	10.1	11.6	28.7	16.7	14.1	33.3	15.0	16.7	31.0	8.8	18.1	37.2	7.3	13.9	32.1
	10k + 10k	11.5	22.8	29.1	17.9	24.2	34.1	14.7	27.2	31.0	9.1	32.4	37.8	7.7	25.4	32.3
	10k + 25k	11.7	27.0	28.9	18.2	27.8	34.2	14.6	31.6	31.2	9.3	38.2	39.3	7.6	30.7	33.1
PMI/Gvt + Bible (2nd)	25k + 1k	14.3	12.8	33.5	19.8	14.6	37.6	17.1	15.9	34.8	11.3	19.4	43.4	9.4	13.5	36.1
	25k + 10k	14.8	23.1	33.6	20.9	24.4	37.3	17.4	27.2	35.6	11.8	33.2	43.8	9.9	25.9	37.3
	25k + 25k	14.3	26.2	32.7	20.8	27.7	37.7	17.6	31.4	35.1	11.6	37.9	44.3	9.9	30.4	37.0
	50k + 1k	N/A	N/A	N/A	N/A	N/A	N/A	18.8	15.6	36.7	12.4	18.1	45.8	11.1	13.7	39.7
	50k + 10k	N/A	N/A	N/A	N/A	N/A	N/A	19.8	26.7	36.8	12.7	33.4	48.2	11.3	25.8	40.0
	50k + 25k	N/A	N/A	N/A	N/A	N/A	N/A	19.2	30.5	36.9	12.6	37.4	46.9	11.2	29.5	39.4

Table C.18: Results (spBLEU) for multi-domain FT. Here D1 refers to Domain 1 and D2 refers to Domain 2. The experiment for PMI/Gvt+Bible ran twice.

D1 + D2	D1 + D2 si	zeD2	D2 size		ka			$\mathbf{g}\mathbf{u}$			hi			si			$_{\mathrm{ta}}$	
				FLORE	S Bible	$e \mathbf{PMI}$	FLOF	RES Bible	PMI	FLOF	RES Bibl	e PMI	FLOR	ES Bibl	e Gvt	FLOI	ES Bible	e Gvt
	25k + 1k		1k	5.6	0.1	14.8	16.5	2.2	24.6	16.0	5.6	21.1	10.6	2.2	25.8	12.4	6.7	21
	25k + 10k		10k	13.7	0.4	30.4	21.7	4.7	34.7	19.3	5.9	31.2	12.7	2.8	39.2	13.4	7.1	33.1
	25k + 25k		25k	16.2	1.8	33.7	24.1	5.3	37.6	21.3	6.2	35.3	13.3	2.3	44.7	14.7	7.4	37.9
CC + PMI/Crt	25k + 50k	DMI/Cut	50k	N/A	N/A	N/A	N/A	N/A	N/A	22.9	6.6	36.7	14.4	2.7	49.3	13.6	6.1	40.7
CC + FMI/GVC	100k + 1k	FMI/GVU	1k	10.0	0.6	17.8	21.9	4.0	26.8	24.1	7.0	25.7	16.9	4.8	32.6	21.1	9.9	24.2
	100k + 10k		10k	15.0	2.1	30.4	24.7	5.6	35.4	25.2	7.3	32.6	17.7	5.4	40.0	18.3	8.5	34.3
	100k + 25k		25k	17.1	2.2	34.1	24.9	5.9	38.2	25.8	6.9	35.4	17.5	5.0	45.2	17.0	7.1	38.1
	100k+50k		50k	N/A	N/A	N/A	N/A	N/A	N/A	25.2	6.4	37.2	16.9	4.7	48.5	17.0	6.5	41.1
	25k + 1k		1k	1.9	10.0	1.2	11.9	15.4	10.0	14.9	16.3	12.3	8.4	18.8	14.5	10.6	16.4	8.8
	25k + 10k		10k	3.1	22.7	1.6	14.6	24.6	11.9	13.9	27.3	11.8	9.3	33.7	16.1	10.2	26.4	9.1
00 - D11	25k + 25k	D:11	25k	3.1	27.4	1.4	14.6	27.9	12.6	12.6	31.1	10.7	8.8	37.9	15.6	6.1	30.7	6.7
CC + Bible	100k + 1k	Bible	1k	5.4	11.8	3.3	15.3	14.7	15.1	23.8	17.3	18.7	15.6	20.4	26.3	19.3	17.4	17.1
	100k + 10k		10k	3.7	22.9	1.7	17.3	23.9	14.8	24.0	27.2	18.9	11.3	34.2	18.7	12.9	26.3	12.7
	100k+25k		25k	3.6	27.1	1.7	11.0	27.9	9.1	14.1	31.6	12.2	9.1	37.4	15.7	9.8	30.1	9.8
	11. 11.	Bible	1k	1.1	8.9	6.1	7.9	13.2	19.4	7.6	15.7	18.2	4.3	16.7	19.4	3.6	15.0	19.1
	1K + 1K	PMI/Gvt	1k	1.2	8.6	6.6	8.1	13.0	20.1	8.2	14.9	19.3	4.5	18.3	22.3	3.9	12.0	20.1
	11 . 101	Bible	10k	2.6	22.6	7.6	9.5	24.1	21.0	6.9	27.2	18.1	4.3	34.1	21.4	3.0	25.7	13.3
	1K + 10K	PMI/Gvt	1k	4.0	21.7	13.7	8.9	23.8	20.3	8.3	26.3	19.5	5.2	33.2	23.1	4.4	25.0	20.0
	11 . 051	Bible	25k	3.2	27.6	5.6	9.0	27.7	19.7	6.9	31.2	17.2	2.8	38.2	14.1	2.9	30.7	12.6
	1k + 25k	PMI/Gvt	1k	5.1	25.6	15.5	10.2	27.2	21.5	8.2	30.1	19.2	5.6	35.6	24.5	4.3	30.2	19.7
	101 - 11	Bible	1k	9.3	12.7	26.8	16.7	14.5	33.5	14.8	16.6	31.0	8.4	19.5	37.0	7.2	14.1	32.1
	10k + 1k	PMI/Gvt	10k	11.4	12.2	29.3	16.9	13.2	34.1	15.0	16.3	31.6	9.2	20.1	39.1	7.3	14.8	33.9
	101 - 101	Bible	10k	9.6	23.4	25.9	17.0	24.3	33.7	14.3	27.5	30.5	6.6	33.2	31.7	7.0	25.8	31.6
	10k + 10k	PMI/Gvt	10k	12.0	22.4	29.4	17.7	23.1	34.2	15.4	27.2	31.5	9.6	33.8	39.1	7.7	25.6	33.2
	101 . 051	Bible	25k	7.1	27.6	17.0	17.1	27.9	33.1	13.5	31.2	30.2	9.1	37.9	39.0	5.0	30.6	25.8
D) ((() D))	10k + 25k	PMI/Gvt	10k	12.2	26.0	29.5	18.5	27.6	34.6	14.9	31.1	31.8	9.7	37.1	39.7	8.0	29.9	33.6
PMI/Gvt + Bibl	e 071 - 11	Bible	1k	13.7	13.8	32.7	19.7	15.1	37.4	17.1	16.7	34.8	11.3	19.4	43.4	8.7	14.5	36.1
	20K + 1K	PMI/Gvt	25k	14.5	12.9	34.0	20.0	14.0	37.8	17.8	15.4	34.9	11.3	15.4	45.3	9.8	14.7	38.1
	071 . 101	Bible	10k	13.9	23.1	32.3	20.2	24.7	36.5	17.2	27.5	35.0	11.0	33.8	43.2	8.8	26.3	36.5
	25k + 10k	PMI/Gvt	25k	14.7	20.8	33.7	21.2	23.1	37.8	17.7	26.8	35.4	11.7	32.8	44.8	9.9	25.7	37.3
		Bible	25k	8.6	27.2	20.0	20.0	28.2	36.5	16.5	31.4	34.3	11.5	37.9	44.4	6.6	30.7	29.5
	25k + 25k	PMI/Gvt	25k	15.5	21.4	34.4	20.6	25.0	37.6	18.0	29.5	35.1	11.8	35.7	44.0	10.5	25.3	38.2
		Bible	1k	N/A	N/A	N/A	N/A	N/A	N/A	18.0	17.6	36.5	11.9	20.1	45.5	10.1	14.8	39.5
	50k + 1k	PMI/Gvt	50k	N/A	N/A	N/A	N/A	N/A	N/A	19.9	16.8	36.9	12.3	16.5	48.6	10.7	11.4	40.8
		Bible	10k	N/A	N/A	N/A	N/A	N/A	N/A	15.7	27.5	32.6	12.2	34.3	47.4	10.3	26.0	39.2
	50k + 10k	PMI/Gvt	50k	N/A	N/A	N/A	N/A	N/A	N/A	20.0	26.7	37.0	12.8	26.5	48.9	11.5	20.8	40.7
		Bible	25k	N/A	N/A	N/A	N/A	N/A	N/A	18.0	30.8	35.9	8.1	38.0	35.9	7.1	30.5	31.4
	50k + 25k	PMI/Gvt	50k	N/A	N/A	N/A	N/A	N/A	N/A	19.8	26.6	37.3	12.8	29.9	48.5	11.6	23.9	40.5
		(111								10.0	20.0	51.5		20.0	10.0	++	20.0	10.0

Table C.19: Results (spBLEU) for multi-domain ITTL. Here D1 refers to Domain 1 and D2 refers to Domain 2.

D1	D1 size D	2	D2 size		ka			$\mathbf{g}\mathbf{u}$			hi			si			ta	
DI	DI SIZE D	-	D2 Size	FLORE	S Bible	\mathbf{PMI}	FLORE	ES Bible	$e \mathbf{PMI}$	FLOR	ES Bible	PMI	FLOR	ES Bible	\mathbf{Gvt}	FLOR	ES Bibl	e Gvt
	25k		1k	0.2	-0.4	0.9	-0.7	-1.5	0.5	3.0	2.0	0.8	0.8	0.2	-0.4	2.1	0.7	0.0
	25k		10k	1.2	-1.2	-0.5	2.8	-1.2	-0.3	2.8	2.6	-0.6	1.6	0.5	-1.3	3.3	3.4	-0.7
	25k		25k	1.6	-0.8	-0.8	2.2	0.0	-0.8	3.2	3.1	-0.1	2.0	0.8	-0.5	3.7	4.2	0.5
CC	25k p	ML/Cyt	50k	N/A	N/A	N/A	N/A	N/A	N/A	3.2	2.8	-0.1	2.1	0.8	-1.8	3.2	4.6	-0.1
00	100k r 1	MI/GVU	1k	-4.1	-0.9	-5.1	-5.1	-2.1	-1.1	3.0	1.1	-0.4	-0.8	-0.1	-0.6	-1.6	-0.1	-2.5
	100k		10k	-1.9	-1.1	-5.2	-0.1	-1.5	-1.7	1.8	2.5	-0.7	1.5	0.8	-2.7	3.6	3.6	-2.5
	100k		25k	-1.3	-1.1	-4.3	0.6	-0.4	-1.7	5.8	3.1	0.0	2.1	1.0	-1.1	4.6	4.4	-2.3
	100k		50k	N/A	N/A	N/A	N/A	N/A	N/A	4.6	3.4	-0.7	2.4	0.9	-3.0	5.0	4.3	-3.0
	25k		1k	0/8	0.0	0.5	2.6	-0.6	-0.3	7.8	0.1	5.4	5.3	-1.9	8.6	3.6	0.4	2.2
	25k		10k	1.5	-0.7	1.1	6.2	0.2	5.6	10.8	0.6	9.6	7.6	-0.4	14.7	8.3	0.0	6.9
CC	25k p	ible	25k	1.8	-0.8	1.1	7.7	0.9	7.4	10.7	-0.1	9.5	7.5	0.1	15.6	8.1	-0.2	7.9
00	100k D	IDIe	1k	0.2	-3.9	0.6	-2.5	-0.2	-0.7	7.0	-0.1	4.5	4.4	-1.3	7.8	1.5	-0.3	1.7
	100k		10k	1.3	-6.2	1.4	4.6	-2.0	5.7	17.5	0.2	13.6	11.5	-1.5	22.0	12.9	-1.7	11.1
	100k		25k	3.0	-4.8	2.3	5.0	-2.8	4.8	19.0	-1.1	16.0	12.4	-2.2	24.2	13.9	-2.7	13.0
	1k		1k	0.6	-0.3	5.2	1.7	0.1	3.8	3.2	-0.5	7.1	2.0	1.3	8.3	1.5	3.5	5.2
	1k		10k	2.0	0.7	10.9	3.7	-0.4	13.7	4.2	-0.5	15.2	3.0	-0.7	19.2	1.6	-1.2	13.7
	1k		25k	2.1	0.8	11.4	4.1	0.3	15.4	3.7	-0.7	15.6	2.3	-1.0	18.0	1.6	0.4	15.6
	10k		1k	7.0	0.2	16.4	5.4	-0.5	7.7	4.8	0.9	6.3	3.8	1.9	9.5	3.7	1.3	10.4
	10k		10k	9.1	-0.3	26.4	10.5	0.0	20.5	9.6	0.3	21.6	7.3	1.4	31.0	5.3	0.1	24.9
PML/Cyd	10k B	iblo	25k	8.9	0.2	27.2	11.7	0.1	25.1	10.3	-0.4	26.2	7.3	-0.3	34.1	5.1	-0.2	28.2
1 1011/070	25k D	IDIC	1k	6.9	0.3	12.5	4.5	0.7	6.0	4.6	1.2	6.0	3.4	0.3	7.1	4.1	1.3	9.3
	25k		10k	11.2	-0.1	27.6	11.2	0.2	17.3	11.4	0.2	22.8	8.6	0.7	30.4	6.7	1.1	23.5
	25k		25k	11.1	-1.3	29.9	12.8	0.3	24.3	12.9	-0.2	28.7	9.1	-0.4	37.2	7.1	-0.5	29.7
	50k		1k	N/A	N/A	N/A	N/A	N/A	N/A	4.7	1.2	6.1	4.0	0.8	8.1	4.3	0.4	7.6
	50k		10k	N/A	N/A	N/A	N/A	N/A	N/A	13.4	0.1	21.3	8.4	-0.1	30.4	7.5	0.6	22.4
	50k		25k	N/A	N/A	N/A	N/A	N/A	N/A	14.4	-0.8	28.0	9.6	0.1	38.3	7.9	-1.0	29.6
	1k		1k	0.1	7.5	0.3	-0.4	3.7	0.4	-0.4	6.4	0.2	-0.6	6.4	-1.4	-0.2	8.4	-1.0
	1k		10k	0.1	9.9	0.2	-0.6	6.6	-1.2	0.3	11.4	-0.4	-0.5	12.6	-1.4	0.3	9.3	-0.6
	1k		25k	0.3	10.8	-0.3	-0.4	7.8	-0.4	0.2	11.2	-0.3	0.0	15.9	-1.6	-0.1	10.5	-1.0
	1k		50k	N/A	N/A	N/A	N/A	N/A	N/A	-0.3	10.7	-0.5	0.1	14.6	-3.7	-0.1	11.1	-1.0
	10k		1k	-0.8	10.2	-2	-1.1	4.8	0.8	-1.4	6.9	-0.7	-1.3	8.6	0.3	-1.2	5.3	-2.0
Biblo	10k p	MI/Cut	10k	0.1	16.8	-0.6	-0.2	10.3	-0.7	-0.7	13.0	-0.4	-0.9	17.3	-1.5	-0.2	13.2	-0.9
DIDIE	10k 1	wii/ Gvt	25k	0.5	18.8	-0.6	0.4	12.4	-0.6	-0.5	16.4	0.9	0.0	21.0	-0.4	0.0	15.7	0.0
	10k		50k	N/A	N/A	N/A	N/A	N/A	N/A	-0.1	16.6	0.1	0.0	24.1	-0.8	-0.3	17.3	0.2
	25k		1k	-0.6	11.1	-1.6	-1.1	5.2	1.3	-1.9	7.8	-0.5	-1.2	9.0	0.2	-1.1	6.6	0.0
	25k		10k	0.1	18.6	-0.9	-2.3	15.8	-3.7	-0.8	14.4	0.0	-0.7	18.6	0.2	-0.4	15.8	-0.5
	25k		25k	0.1	19.7	-0.1	0.3	13.0	0.1	-0.8	16.2	0.7	-0.3	23.0	0.1	-0.1	17.2	-0.2
	25k		50k	N/A	N/A	N/A	N/A	N/A	N/A	-0.8	17.8	0.1	-0.3	24.7	-1.7	0.0	18.1	-0.5

Table C.20: Difference in spBLEU scores between multi-domain FT and single-domain ITTL. The baseline was single-domain ITTL. Here D1 refers to Domain 1 and D2 refers to Domain 2. For multi-domain FT D1 and D2 were combined and fine-tuned.

	Sta	age 1		Stag	e 2		ka			$\mathbf{g}\mathbf{u}$			hi			si			ta	
D1	D1 size	$\ge D2$	D2 size	D	D siz	e FLORES	Bible	PMI	FLOR	ES Bible	PM	FLOR	ES Bible	PM	FLC	RES Bibl	Gv	FLOF	ES Bibl	e Gvt
	25k		1k		1k	0.9	0.1	1.0	0.4	0.1	0.3	0.9	0.3	2.1	0.2	0.1	1.0	-0.3	0.0	0.3
	25k		10k		10k	0.1	0.0	0.4	-0.5	1.3	0.3	0.5	0.4	1.3	0.3	0.1	0.4	-0.1	0.0	0.0
	25k		25k		25k	-0.4	0.7	0.2	0.4	0.2	0.1	-0.8	-0.4	0.8	-0.1	-0.1	0.2	-0.2	-0.2	-0.1
CC	25k	PMI/Gv	50k	PMI/Gyt	50k	N/A	N/A	N/A	N/A	N/A	N/A	-0.5	-0.1	1.4	-1.7	-1.3	0.7	0.0	0.0	0.0
00	100k	1 311/07	1k	1 111/010	1k	3.9	0.4	6.7	6.1	2.4	1.9	1.4	0.3	2.2	2.4	0.6	2.8	0.2	-0.2	2.1
	100k		10k		10k	2.3	1.4	5.3	2.3	1.9	2.0	1.0	0.5	1.3	-0.7	-1.3	2.7	-0.9	-0.1	0.8
	100k		25k		25k	2.1	1.2	4.3	1.4	0.9	1.4	0.2	0.4	2.0	-2.6	-2.3	2.8	-1.1	-0.6	0.2
	100k		50k		50k	N/A	N/A	N/A	N/A	N/A	N/A	-0.7	0.3	2.8	-2.9	-2.3	3.6	-1.9	-1.4	0.9
	25k		1k		1k	0.2	0.4	0.0	-0.3	2.1	1.8	-0.4	1.4	-0.3	-0.2	1.5	-0.1	0.0	0.1	0.1
	25k		10k		10k	-0.5	0.3	-0.4	1.8	0.7	1.2	-0.5	0.6	-0.8	-1.1	0.3	-0.3	-0.9	0.3	-0.8
CC	25k	Bible	25k	Bible	25k	-1.1	0.9	-0.7	1.3	0.1	1.1	-0.7	-0.1	-1.0	-4.9	0.1	-2.8	-1.9	-0.3	-1.2
00	100k	Dibie	1k	Dible	1k	1.1	4.5	0.4	3.2	1.6	3.9	0.2	1.6	-0.5	0.6	1.4	0.1	-0.1	0.9	-0.3
	100k		10k		10k	-0.4	6.2	-1.1	4.4	1.7	2.2	-4.1	2.3	-8.7	-5.9	1.8	-4.4	-0.1	0.2	-0.2
	100k		25k		25k	-2.2	4.5	-1.8	-0.9	2.9	-1.1	-6.3	1.7	-11.1	-8.3	1.8	-6.4	-9.7	1.0	-7.1
	11.		11.	Bible	1k	0.0	-0.2	-0.1	0.0	-0.1	0.2	0.0	0.0	-0.1	-0.1	0.5	0.2	-0.4	0.7	-0.3
	1K		IK	PMI/Gvt	1k	0.1	-0.5	0.4	0.4	-0.1	0.7	0.1	-0.2	0.9	0.2	-2.5	1.2	0.2	-0.1	0.8
	11.		101.	Bible	10k	-0.6	0.4	-3.2	0.3	-0.1	0.0	-0.5	0.4	-1.3	-0.6	1.1	-3.6	-0.8	0.2	-0.4
	IK		10K	PMI/Gvt	1k	0.3	-1.0	1.9	0.1	0.0	0.0	0.3	-0.2	0.7	0.5	-0.1	2.6	0.8	-0.4	1.4
	11-		251	Bible	25k	-0.7	0.2	-5.7	-0.4	-0.1	-1.5	-1.8	0.5	-8.2	-0.9	-0.2	-5.7	-0.4	-0.5	-1.0
	IK		20K	PMI/Gvt	1k	0.7	-2.2	3.0	0.9	-0.4	1.0	1.4	-1.0	4.7	0.5	-0.7	1.4	1.1	-0.7	1.1
	10k		1k	Bible	1k	-0.8	1.1	-1.9	0.0	0.4	0.2	-0.4	1.4	-0.2	-0.1	0.2	0.0	-0.2	-0.1	0.0
	101			PMI/Gvt	10k	0.2	-0.4	0.0	-0.3	-1.0	0.1	0.1	0.7	-0.2	-0.2	-0.1	0.2	0.0	-0.4	0.6
	10k		10k	Bible	10k	-1.9	0.6	-3.2	-0.9	0.1	-0.4	-2.5	0.8	-6.1	-0.7	0.4	-0.7	-0.4	0.3	-0.5
				PMI/Gvt	10k	0.1	-0.4	0.1	-0.2	-1.1	0.1	0.1	0.0	0.1	-0.2	-0.3	0.2	0.7	0.0	1.0
	10k		25k	Bible	25k	-4.6	0.6	-11.9	-1.1	0.1	-1.1	-0.2	-0.3	-0.3	-2.6	-0.1	-7.3	-1.1	-0.4	-1.0
PMI/Gvt		Bible		PMI/Gvt	10k	0.4	-1.3	0.2	0.3	-0.2	0.4	0.3	-0.4	1.2	0.4	-0.5	0.6	0.4	0.0	1.0
	051		11.	Bible	1k	-0.6	1.0	-0.8	-0.1	0.5	-0.2	0.0	0.0	0.0	-0.7	1.0	0.0	0.0	0.8	0.0
	ZJK		1 K	PMI/Gvt	25k	0.0	-0.1	0.2	0.2	-1.0	0.0	0.0	-3.8	1.5	0.3	0.0	0.4	0.4	-1.1	-0.4
				Bible	10k	-0.9	0.0	-1.3	-0.7	0.3	-0.8	-0.8	0.6	-0.6	-1.1	0.4	-0.8	-0.2	0.3	-0.6
	25k		10k	PMI/Gvt	25k	-0.2	-2.2	0.0	0.3	-1.0	0.4	-0.2	-1.0	-0.1	0.0	-0.2	0.0	0.3	-0.4	-0.2
				Bible	25k	-5.7	1.0	-127	-0.8	0.5	-1.2	-0.1	0.0	0.1	-33	0.3	-75	-11	0.0	-0.8
	25k		25k	PMI/Gvt	25k 25k	1.2	-1.8	1 7	-0.2	-2.7	-0.1	0.1	-2.0	0.1	-0.0	-5.1	1.0	0.8	-1.0	-0.8
				Bible	1k	N/A	N/A	N/Δ	N/Δ	N/A	N/Δ	-0.5	2.0	-0.3	-1.0	1.1	-0.2	-0.8	2.0	-0.2
	50k		1k	PMI/Gvt	50k	N/A	N/A	N/A	N/A	N/A	N/A	-0.1	-3.5	0.0	-0.5	-2.7	0.7	0.5	-0.4	-0.5
												0.1			0.0	2.1		0.0		0.0
	50k		10k	Bible	10k	N/A	N/A	N/A	N/A	N/A	N/A	-0.5	0.9	-0.8	-1.0	0.2	-0.8	-4.1	0.8	-4.2
				PMI/Gvt	50k	N/A	N/A	N/A	N/A	N/A	N/A	0.1	-6.9	0.7	0.2	-4.8	1.0	-0.1	-0.1	-0.1
	501		051	Bible	25k	N/A	N/A	N/A	N/A	N/A	N/A	-4.5	0.6	-11.0	-4.1	1.0	-0.8	-1.2	0.3	-1.0
	OOK		ZOK	PMI/Gvt	50k	N/A	N/A	N/A	N/A	N/A	N/A	0.2	-7.5	1.6	0.4	-5.6	1.1	0.6	-4.4	1.1

Table C.21: Difference in spBLEU scores between multi-domain FT and multi-domain ITTL. The baseline was multi-domain FT. Here D1 refers to Domain 1 in stage 1 and D2 refers to Domain 2 in stage 1, while D refers to Domain in stage 2 for multi-domain

ITTL. D1 and D2 were combined in stage 1 and multi-domain FT was only fine-tuned in stage 1.

 D1	D1 size	D2	D2 size		ka	L		gu	L		h	i		si	l		ta	
51	DISEC	22	D2 Size	F	В	Р	F	в	Р	F	в	Р	F	в	G	F	в	G
	25k		1k	1.1	-0.3	1.9	-0.3	-1.4	0.8	2.7	2.0	1.1	1.7	0.5	1.7	2.3	0.8	1.0
	25k		10k	1.3	-1.2	-0.1	2.3	0.1	0.0	2.7	2.6	-0.6	2.1	0.9	0.0	3.6	3.5	-0.3
	25k		25k	1.2	-0.1	-0.6	2.6	0.2	-0.7	3.0	2.9	-0.2	1.2	0.4	0.3	3.6	4.1	0.7
CC	25k	DMI/Cart	50k	N/A	N/A	N/A	N/A	N/A	N/A	3.0	2.8	-0.3	1.6	0.7	-0.4	1.5	3.3	0.6
	100k	r m/Gvt	1k	-0.2	-0.5	1.6	1.0	0.3	0.8	2.0	0.9	1.7	0.6	0.2	1.6	0.8	0.5	0.3
	100k		10k	0.4	0.3	0.1	2.2	0.4	0.3	4.9	2.4	0.1	2.5	1.3	-1.4	2.9	2.3	0.2
	100k		25k	0.8	0.1	0.0	2.0	0.5	-0.3	4.4	2.5	0.2	2.3	1.4	0.9	2.0	2.1	0.5
	100k		50k	N/A	N/A	N/A	N/A	N/A	N/A	2.7	2.0	0.2	1.7	1.2	-0.2	2.1	2.0	0.6
	25k		1k	1.0	0.4	0.5	2.3	1.5	1.5	7.8	0.2	5.5	4.9	-0.5	8.3	3.4	1.9	2.1
	25k		10k	1.0	-0.4	0.7	8.0	0.9	6.8	9.9	0.9	8.8	7.1	0.2	13.9	7.2	0.3	6.6
CC	25k	Bible	25k	0.7	0.1	0.4	9.0	1.0	8.5	8.8	-0.4	8.3	6.8	0.0	14.6	3.2	-0.1	5.1
00	100k	Dible	1k	1.3	0.6	1.0	0.7	1.4	3.2	6.9	0.8	4.2	4.6	0.3	7.3	2.1	1.1	1.8
	100k		10k	0.9	0.0	0.3	9.0	-0.3	7.9	17.4	0.4	13.4	7.4	0.8	13.3	7.0	0.1	6.7
	100k		25k	0.8	-0.3	0.5	4.1	0.1	3.7	9.3	-0.1	8.9	6.1	-0.5	13.1	5.6	-0.9	6.6
	1k		1k	0.6	-0.5	5.1	1.9	0.2	3.8	2.8	0.2	6.8	1.9	-0.5	6.3	1.4	4.0	5.4
	1k		10k	0.9	0.6	6.7	4.4	-0.1	14.4	3.6	0.0	15.2	2.4	0.0	18.2	0.7	-0.6	9.6
	1k		25k	0.9	0.6	4.5	3.8	0.4	14.6	3.1	-0.3	14.7	0.9	0.6	12.3	0.7	0.2	9.9
	10k		1k	5.1	0.3	13.9	4.9	-0.2	7.2	4.6	0.8	6.3	3.1	2.0	7.2	3.4	0.5	8.8
	10k		10k	6.8	0.3	23.0	9.6	0.1	20.1	9.2	0.6	21.6	4.4	0.8	23.7	4.4	0.0	23.5
PMI/Cwt	10k	Bible	25k	4.2	0.5	14.9	10.6	0.2	24.0	9.3	-0.3	25.6	7.0	0.1	34.6	2.5	0.0	21.0
1 111/000	25k	DIDIE	1k	6.1	1.1	11.4	4.4	0.8	5.6	4.3	1.4	5.5	3.4	0.5	6.7	3.3	1.1	7.7
	25k		10k	10.2	0.0	26.2	10.5	0.8	16.4	11.2	0.5	22.2	7.7	0.7	28.7	5.6	1.5	22.7
	25k		25k	5.4	-0.3	17.2	12.0	0.8	23.1	12.2	-0.2	27.9	9.1	-0.2	37.9	3.8	-0.2	22.2
	50k		1k	N/A	N/A	N/A	N/A	N/A	N/A	3.3	1.6	5.2	3.5	0.9	5.0	3.2	1.1	7.0
	50k		10k	N/A	. N/A	. N/A	N/A	N/A	N/A	9.0	0.8	16.8	7.9	0.8	29.6	6.5	1.0	21.9
	50k		25k	N/A	N/A	N/A	N/A	N/A	N/A	13.2	-1	27.7	5.1	0.7	27.3	3.8	0.0	21.6
	1k		1k	0.2	7.0	0.7	-0.2	3.4	1.3	-0.4	6.4	0.2	-0.4	8.0	1.4	0.0	5.9	0.2
	1k		10k	1.4	10.5	0.8	-0.4	5.7	-0.4	0.3	11.4	-0.4	-0.1	14.6	0.5	0.3	10.2	1.2
	1k		25k	0.5	10.9	0.2	-0.2	7.2	-0.2	0.5	11.8	30.2	0.0	11.9	0.3	0.3	11.7	1.0
	1k		50k	N/A	. N/A	. N/A	N/A	N/A	N/A	0.3	12.3	0.2	0.0	13.0	-0.9	-0.5	8.8	0.1
	10k		1k	0.0	9.7	0.9	-1.4	4.4	0.1	-1.6	6.6	-1.1	-0.9	8.1	0.7	-0.4	5.7	1.1
Bible	10k	PMI/Cart	10k	0.6	16.4	-0.3	-0.4	9.2	-0.6	-0.7	13.0	0.9-	-0.4	18.7	-0.2	-0.2	13.4	0.0
DIDIE	10k	1 1/11/0/0	25k	0.4	16.5	-0.5	0.7	11.1	-0.1	-0.5	16.4	0.9	-0.1	20.6	0.6	0.0	15.5	0.0
	10k		50k	N/A	N/A	N/A	N/A	N/A	N/A	0.2	16.7	0.4	0.1	17.2	-0.1	-0.1	12.3	0.9
	25k		1k	0.6	9.3	2.6	-0.3	4.6	1.6	-1.7	6.9	-0.6	-0.2	6.9	2.4	-0.6	5.9	1.4
	25k		10k	0.6	17.6	-0.3	0.7	10.2	0.9	-0.9	13.9	0-0.4	-0.3	17.5	0.6	0.0	15.0	0.0
	25k		25k	1.3	14.9	1.6	0.1	10.3	0.0	-1.2	16.2	2.0.7	-0.1	20.8	-0.2	0.5	12.1	1.0
	25k		50k	N/A	N/A	N/A	N/A	N/A	N/A	-0.8	18.3	8-0.6	-0.1	17.2	-0.1	0.4	12.5	0.6

Table C.22: Difference in spBLEU scores between multi-domain ITTL and single-domain
ITTL. Here D1 refers to Domain 1 and D2 refers to Domain 2. For multi-domain ITTL
D1 and D2 were combined and fine-tuned and then further fine-tuned on
D2.FLORES=F Bible=B PMI=P Gvt=G

Fine-tuning Set	Fine-tuning Set size		ka			\mathbf{si}			hi	
r me-tuning Set	The-tuning bet size	FLOR	ES Bible	e PMI	FLOR	ES Bibl	e Gvt	FLOR	ES Bibl	e PMI
CC	25k	0.9	0.0	0.5	8.1	1.7	13.2	12.4	4.4	11.2
	100k	4.7	0.2	3.7	14.8	4.1	26.1	21.9	6.7	17.2
	1k	1.0	0.1	6.5	3.9	0.5	20.2	7.1	1.5	18.2
	10k	10.4	1.3	29.4	8.8	1.0	38.2	14.7	2.6	31.4
PMI/Gvt	25k	14.1	1.7	33.6	11.2	1.2	44.7	17.3	2.9	35.2
	50k	N/A	N/A	N/A	12.4	1.6	49.5	19.0	3.4	37.0
	1k	0.3	8.2	0.2	0.9	17.0	1.3	2.6	14.0	2.3
Bible	10k	1.6	22.6	0.7	1.8	33.3	0.8	2.9	26.9	2.2
	25k	2.2	27.8	0.9	1.9	37.9	0.9	3.2	31.4	2.0

Table C.23: Results (spBLEU) for vanilla fine-tuning.

D1	D1 size	D2	D2 size	ka			si			
				FLORE	ES Bible	e PMI	FLOR	ES Bible	e Gvt	
CC	0k		1k 10k 25k	$0.0 \\ 0.9 \\ 1.4$	$0.8 \\ 19.0 \\ 28.5$	$0.0 \\ 0.6 \\ 1.1$	$2.4 \\ 2.5 \\ 2.5$	$13.8 \\ 30.3 \\ 35.1$	1.8 1.4 1.1	
	25k	Bible	1k 10k 25k	$0.7 \\ 1.4 \\ 1.6$	$2.2 \\ 22.2 \\ 28.5$	$0.4 \\ 0.9 \\ 1.2$	$6.1 \\ 3.2 \\ 3.0$	$15.3 \\ 31.1 \\ 35.4$	$9.4 \\ 2.4 \\ 1.4$	
	100k		1k 10k 25k	5.1 2.7 2.2	10.7 23.8 29.0	4.4 2.1 1.7	$9.4 \\ 4.1 \\ 3.6$	$17.0 \\ 31.1 \\ 35.3$	16.9 4.2 2.2	

Appendix C.2. Result Tables for XX-EN

Table C.24: Results (spBLEU) for single-domain ITTL from other languages to English.Here D1 refers to Domain 1 and D2 refers to Domain 2.

$D1 \perp D2$	D1 + D2 size	D2	D2 size	ka			si		
				FLORES	5 Bible	PMI	FLORES	Bible	Gvt
	$\begin{array}{l} 25k + 1k \\ 25k + 10k \\ 25k + 25k \end{array}$		1k 10k 25k	0.5 2.5 2.8	3.1 22.7 28.2	0.5 1.7 1.9	9.7 8.8 8.1	$16.3 \\ 30.0 \\ 34.9$	$13.5 \\ 13.4 \\ 13.0$
CC + Bible	$\begin{array}{l} 100k + 1k \\ 100k + 10k \\ 100k + 25k \end{array}$	Bible	1k 10k 25k	$0.6 \\ 1.4 \\ 3.4$	$6.3 \\ 22.4 \\ 26.1$	$0.7 \\ 1.9 \\ 3.4$	13.9 14.0 13.4	17.5 30.1 33.3	$21.3 \\ 21.6 \\ 20.7$

Table C.25: Results (spBLEU) for multi-domain FT from other languages to English.Here D1 refers to Domain 1 and D2 refers to Domain 2.

$D1 \perp D2$	D1 + D2 size	D2	D2 size	ka			si		
				FLORES	5 Bible	$e \mathbf{PMI}$	FLORES	Bible	Gvt
	25k + 1k 25k + 10k 25k + 25k		1k 10k 25k	0.6 2.7 2.4	3 23.5 28.2	0.5 2 1.6	9.7 7.1 5.8	$17 \\ 31.2 \\ 35.4$	$13.5 \\ 11.7 \\ 8.9$
CC + Bible	100k + 1k 100k + 10k 100k + 25k	Bible	1k 10k 25k	5.4 4.2 3.2	9.8 24.5 29.4	4.8 3.2 2.5	$14 \\ 11.4 \\ 5.5$	$18.3 \\ 30.8 \\ 35.7$	21.3 20.2 7.3

Table C.26: Results (spBLEU) for multi-domain ITTL from other languages to English.Here D1 refers to Domain 1 and D2 refers to Domain 2.

Appendix D. Graphical Results of Performance

Appendix D.1. Single-domain ITTL Performance Plots



(a) Single-domain ITTL where CC is used as Stage 1 data set, and Bible is used as Stage 2 data set. The spBLEU scores correspond to the test on Bible test set.



(b) Single-domain ITTL where CC is used as Stage 1 data set, and PMI/Gvt is used as Stage 2 data set. The spBLEU scores correspond to the test on the PMI/Gvt test set.



(c) Single-domain ITTL where PMI/Gvt is used as Stage 1 data set, and Bible is used as Stage 2 data set. The spBLEU scores correspond to the test on Bible test set.



(d) Single-domain ITTL where Bible is used as Stage 1 data set, and PMI/Gvt is used as Stage 2 data set. The spBLEU scores correspond to the test on the PMI/Gvt test set.

Figure D.4: Single-domain ITTL results on in-domain cases.



(a) Single-domain ITTL where CC is used as Stage 1 data set, and Bible is used as Stage 2 data set. The spBLEU scores correspond to the test on the FLORES test set.



(b) Single-domain ITTL where CC is used as Stage 1 data set, and PMI/Gvt is used as Stage 2 data set. The spBLEU scores correspond to the test on the FLORES test set.



(c) Single-domain ITTL where PMI/Gvt is used as Stage 1 data set, and Bible is used as Stage 2 data set. The spBLEU scores correspond to the test on the FLORES test set.



(d) Single-domain ITTL where Bible is used as Stage 1 data set, and PMI/Gvt is used as Stage 2 data set. The spBLEU scores correspond to the test on the FLORES test set.



(e) Single-domain ITTL where CC is used as Stage 1 data set, and Bible is used as Stage 2 data set. The spBLEU scores correspond to the test on the PMI/Gvt test set.



(f) Single-domain ITTL where CC is used as Stage 1 data set, and PMI/Gvt is used as Stage 2 data set. The spBLEU scores correspond to the test on Bible test set.

Figure D.5: Single-domain ITTL results for out-domain cases.



(a) Multi-domain FT where a mix of CC and PMI/Gvt are used are used to fine-tune the model. The spBLEU scores correspond to the test on the PMI/Gvt test set.



(b) Multi-domain FT where a mix of CC and Bible are used to fine-tune the model. The spBLEU scores correspond to the test on Bible test set.



(c) Multi-domain FT where a mix of PMI/Gvt and Bible are used to fine-tune the model. The spBLEU scores correspond to the test on the PMI/Gvt test set.



(d) Multi-domain FT where a mix of PMI/Gvt and Bible are used to fine-tune the model. The spBLEU scores correspond to the test on Bible test set.

Figure D.6: Results for multi-domain FT for in-domain cases.



(a) Multi-domain FT where a mix of CC and PMI/Gvt are used to fine-tune the model. The spBLEU scores correspond to the test on the FLORES test set.



(b) Multi-domain FT where a mix of CC and PMI/Gvt are used to fine-tune the model. The spBLEU scores correspond to the test on Bible test set.



(c) Multi-domain FT where a mix of CC and Bible are used to fine-tune the model. The spBLEU scores correspond to the test on the FLORES test set.



(d) Multi-domain FT where a mix of CC and Bible are used to fine-tune the model. The spBLEU scores correspond to the test on the PMI/Gvt test set.



(e) Multi-domain FT where a mix of PMI/Gvt and Bible are used to fine-tune the model. The spBLEU scores correspond to the test on the FLORES test set.

Figure D.7: Results for multi-domain FT for out-domain cases.





(d) Multi-domain ITTL where a mix of PMI/Gvt and Bible are used as Stage 1 data set and Bible is used as Stage 2 data set. The spBLEU scores correspond to the test on Bible test set.

Figure D.8: Results for multi-domain ITTL for in-domain cases.



(a) Multi-domain ITTL where a mix of CC and PMI/Gvt is used as Stage 1 data set, and PMI/Gvt is used as Stage 2 data set. The spBLEU scores correspond to the test on the FLORES test set.



(b) Multi-domain ITTL where a mix of CC and PMI/Gvt is used as Stage 1 data set, and PMI/Gvt is used as Stage 2 data set. The spBLEU scores correspond to the test on Bible test set.



(c) Multi-domain ITTL where a mix of CC and Bible are used as Stage 1 data set, and Bible is used as Stage 2 data set. The spBLEU scores correspond to the test on the FLORES test set.



(d) Multi-domain ITTL where a mix of CC and Bible is used as Stage 1 data set, and Bible is used as Stage 2 data set. The spBLEU scores correspond to the test on the PMI/Gvt test set.



(e) Multi-domain ITTL where a mix of Bible and PMI/Gvt is used as Stage 1 data set, and Bible is used as Stage 2 data set. The spBLEU scores correspond to the test on the FLORES test set.



(f) Multi-domain ITTL where a mix of Bible and PMI/Gvt is used as Stage 1 data set, and PMI/Gvt is used as Stage 2 data set. The spBLEU scores correspond to the test on the FLORES test set.

Figure D.9: Results for Multi-dônain ITTL for out-domain cases.

References

- Z. Zhou, A. Waibel, Family of origin and family of choice: Massively parallel lexiconized iterative pretraining for severely low resource text-based translation, in: Proceedings of the Third Workshop on Computational Typology and Multilingual NLP, 2021, pp. 67–80.
- [2] J. Tiedemann, Parallel data, tools and interfaces in opus, in: Proceedings of the Eighth International Conference on Language Resources and Evaluation (LREC'12), 2012, pp. 2214–2218.
- [3] Y. Tang, C. Tran, X. Li, P.-J. Chen, N. Goyal, V. Chaudhary, J. Gu, A. Fan, Multilingual translation from denoising pre-training, in: Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021, 2021, pp. 3450–3466.
- [4] L. Madaan, S. Sharma, P. Singla, Transfer learning for related languages: Submissions to the WMT20 similar language translation task, in: Proceedings of the Fifth Conference on Machine Translation, Association for Computational Linguistics, Online, 2020, pp. 402–408. URL https://aclanthology.org/2020.wmt-1.46
- [5] S. Thillainathan, S. Ranathunga, S. Jayasena, Fine-tuning selfsupervised multilingual sequence-to-sequence models for extremely lowresource NMT, in: 2021 Moratuwa Engineering Research Conference (MERCon), 2021, pp. 432–437. doi:10.1109/MERCon52712.2021. 9525720.
- [6] E.-S. Lee, S. Thillainathan, S. Nayak, S. Ranathunga, D. Adelani, R. Su, A. McCarthy, Pre-trained multilingual sequence-to-sequence models: A hope for low-resource language translation?, in: Findings of the Association for Computational Linguistics: ACL 2022, Association for Computational Linguistics, Dublin, Ireland, 2022, pp. 58–67. doi:10.18653/v1/2022.findings-acl.6. URL https://aclanthology.org/2022.findings-acl.6
- [7] M. Reid, M. Artetxe, Paradise: Exploiting parallel data for multilingual sequence-to-sequence pretraining, arXiv preprint arXiv:2108.01887 (2021).

- [8] D. I. Adelani, J. O. Alabi, A. Fan, J. Kreutzer, X. Shen, M. Reid, D. Ruiter, D. Klakow, P. Nabende, E. Chang, et al., A few thousand translations go a long way! leveraging pre-trained models for african news translation, arXiv preprint arXiv:2205.02022 (2022).
- [9] E. Khiu, H. Toossi, J. Liu, J. Li, D. Anugraha, J. Flores, L. Roman, A. S. Doğruöz, E.-S. Lee, Predicting machine translation performance on low-resource languages: The role of domain similarity, in: Findings of the Association for Computational Linguistics: EACL 2024, 2024, pp. 1474–1486.
- [10] S. Nayak, S. Ranathunga, S. Thillainathan, R. Hung, A. Rinaldi, Y. Wang, J. Mackey, A. Ho, E.-S. A. Lee, Leveraging auxiliary domain parallel data in intermediate task fine-tuning for low-resource translation, arXiv preprint arXiv:2306.01382 (2023).
- [11] M. Reid, M. Artetxe, PARADISE: Exploiting parallel data for multilingual sequence-to-sequence pretraining, in: Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Association for Computational Linguistics, Seattle, United States, 2022, pp. 800–810. doi:10.18653/v1/2022.naacl-main.58. URL https://aclanthology.org/2022.naacl-main.58
- [12] J. Phang, T. Févry, S. R. Bowman, Sentence encoders on stilts: Supplementary training on intermediate labeled-data tasks, arXiv preprint arXiv:1811.01088 (2018).
- [13] Y. Pruksachatkun, J. Phang, H. Liu, P. M. Htut, X. Zhang, R. Y. Pang, C. Vania, K. Kann, S. R. Bowman, Intermediate-task transfer learning with pretrained models for natural language understanding: When and why does it work?, arXiv preprint arXiv:2005.00628 (2020).
- [14] S. Park, C. Caragea, Scientific keyphrase identification and classification by pre-trained language models intermediate task transfer learning, in: Proceedings of the 28th International Conference on Computational Linguistics, 2020, pp. 5409–5419.
- [15] N. Moghe, M. Steedman, A. Birch, Cross-lingual intermediate finetuning improves dialogue state tracking, in: Proceedings of the 2021

Conference on Empirical Methods in Natural Language Processing, 2021, pp. 1137–1150.

- [16] V. Dhananjaya, S. Ranathunga, S. Jayasena, Lexicon-based fine-tuning of multilingual language models for low-resource language sentiment analysis, CAAI Transactions on Intelligence Technology (2024).
- [17] N. Verma, K. Murray, K. Duh, Strategies for adapting multilingual pretraining for domain-specific machine translation, in: Proceedings of the 15th biennial conference of the Association for Machine Translation in the Americas (Volume 1: Research Track), 2022, pp. 31–44.
- [18] M. Kale, A. Siddhant, R. Al-Rfou, L. Xue, N. Constant, M. Johnson, nmt5-is parallel data still relevant for pre-training massively multilingual language models?, in: Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 2: Short Papers), 2021, pp. 683–691.
- [19] Z. Chi, L. Dong, S. Ma, S. Huang, S. Singhal, X.-L. Mao, H.-Y. Huang, X. Song, F. Wei, mt6: Multilingual pretrained text-to-text transformer with translation pairs, in: Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing, 2021, pp. 1671–1683.
- [20] A. Liyanage, S. Ranathunga, S. Jayasena, Bilingual lexical induction for sinhala-english using cross lingual embedding spaces, in: 2021 Moratuwa Engineering Research Conference (MERCon), IEEE, 2021, pp. 579–584.
- [21] M. R. Costa-jussà, J. Cross, O. Çelebi, M. Elbayad, K. Heafield, K. Heffernan, E. Kalbassi, J. Lam, D. Licht, J. Maillard, et al., No language left behind: Scaling human-centered machine translation, arXiv preprint arXiv:2207.04672 (2022).
- [22] S. Ranathunga, N. de Silva, Some languages are more equal than others: Probing deeper into the linguistic disparity in the nlp world, arXiv preprint arXiv:2210.08523 (2022).
- [23] P. Joshi, S. Santy, A. Budhiraja, K. Bali, M. Choudhury, The state and fate of linguistic diversity and inclusion in the NLP world, in: Proceedings of the 58th Annual Meeting of the Association for Computational

Linguistics, Association for Computational Linguistics, Online, 2020, pp. 6282-6293. doi:10.18653/v1/2020.acl-main.560. URL https://aclanthology.org/2020.acl-main.560

- [24] J. Kreutzer, I. Caswell, L. Wang, A. Wahab, D. van Esch, N. Ulzii-Orshikh, A. Tapo, N. Subramani, A. Sokolov, C. Sikasote, M. Setyawan, S. Sarin, S. Samb, B. Sagot, C. Rivera, A. Rios, I. Papadimitriou, S. Osei, P. O. Suarez, I. Orife, K. Ogueji, A. N. Rubungo, T. Q. Nguyen, M. Müller, A. Müller, S. H. Muhammad, N. Muhammad, A. Mnyakeni, J. Mirzakhalov, T. Matangira, C. Leong, N. Lawson, S. Kudugunta, Y. Jernite, M. Jenny, O. Firat, B. F. P. Dossou, S. Dlamini, N. de Silva, S. Çabuk Ballı, S. Biderman, A. Battisti, A. Baruwa, A. Bapna, P. Baljekar, I. A. Azime, A. Awokoya, D. Ataman, O. Ahia, O. Ahia, S. Agrawal, M. Adeyemi, Quality at a glance: An audit of web-crawled multilingual datasets, Transactions of the Association for Computational Linguistics 10 (2022) 50–72.
 URL https://aclanthology.org/2022.tacl-1.4
- [25] S. Ranathunga, N. De Silva, V. Menan, A. Fernando, C. Rathnayake, Quality does matter: A detailed look at the quality and utility of webmined parallel corpora, in: Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers), 2024, pp. 860–880.
- [26] N. Goyal, C. Gao, V. Chaudhary, P.-J. Chen, G. Wenzek, D. Ju, S. Krishnan, M. Ranzato, F. Guzmán, A. Fan, The Flores-101 evaluation benchmark for low-resource and multilingual machine translation, Transactions of the Association for Computational Linguistics 10 (2022) 522–538.

URL https://aclanthology.org/2022.tacl-1.30

[27] A. Ramesh Kashyap, D. Hazarika, M.-Y. Kan, R. Zimmermann, Domain divergences: A survey and empirical analysis, in: Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Association for Computational Linguistics, Online, 2021, pp. 1830–1849. doi:10. 18653/v1/2021.naacl-main.147.

URL https://aclanthology.org/2021.naacl-main.147

- [28] S. Ranathunga, E.-S. A. Lee, M. P. Skenduli, R. Shekhar, M. Alam, R. Kaur, Neural machine translation for low-resource languages: A survey, arXiv preprint arXiv:2106.15115 (2021).
- [29] B. Haddow, F. Kirefu, Pmindia–a collection of parallel corpora of languages of india, arXiv preprint arXiv:2001.09907 (2020).
- [30] A. Fernando, S. Ranathunga, G. Dias, Data augmentation and terminology integration for domain-specific sinhala-english-tamil statistical machine translation, arXiv preprint arXiv:2011.02821 (2020).
- [31] F. Guzmán, P.-J. Chen, M. Ott, J. Pino, G. Lample, P. Koehn, V. Chaudhary, M. Ranzato, The flores evaluation datasets for lowresource machine translation: Nepali–english and sinhala–english, in: Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP), 2019, pp. 6098–6111.
- [32] M. Popović, chrF++: words helping character n-grams, in: Proceedings of the Second Conference on Machine Translation, Association for Computational Linguistics, Copenhagen, Denmark, 2017, pp. 612-618. doi:10.18653/v1/W17-4770. URL https://aclanthology.org/W17-4770
- [33] M. Post, A call for clarity in reporting BLEU scores, in: Proceedings of the Third Conference on Machine Translation: Research Papers, Association for Computational Linguistics, Brussels, Belgium, 2018, pp. 186–191. doi:10.18653/v1/W18-6319.
 URL https://aclanthology.org/W18-6319