Multi-population Differential Evolution for RSS based Cooperative Localization in Wireless Sensor Networks with Limited Communication Range

Lismer Andres Caceres Najarro, Iickho Song, Fellow, IEEE, Muhammad Salman, and Kiseon Kim, Senior Member, IEEE

Abstract—This paper presents a novel approach to deal with the cooperative localization problem in wireless sensor networks based on received signal strength measurements. In cooperative scenarios, the cost function of the localization problem becomes increasingly nonlinear and nonconvex due to the heightened interaction between sensor nodes, making the estimation of the positions of the target nodes more challenging. Although most of existing cooperative localization algorithms assure acceptable localization accuracy, their computational complexity increases dramatically, which may restrict their applicability. To reduce the computational complexity and provide competitive localization accuracy at the same time, we propose a localization algorithm based on the differential evolution with multiple populations, opposite-based learning, redirection, and anchoring. In this work, the cooperative localization cost function is split into several simpler cost functions, each of which accounts only for one individual target node. Then, each cost function is solved by a dedicated population of the proposed algorithm. In addition, an enhanced version of the proposed algorithm which incorporates the population midpoint scheme for further improvement in the localization accuracy is devised. Simulation results demonstrate that the proposed algorithms provide comparative localization accuracy with much lower computational complexity compared with the state-of-the-art algorithms.

Index Terms—Centralized, cooperative, localization, multiple population, differential evolution, received signal strength (RSS).

I. INTRODUCTION

The attention to wireless sensor networks (WSNs) has been increasing in recent years. This is mainly because WSNs allow the installation of a large number of small, lowpower sensor nodes in an area of interest (AOI) for a wide range of applications such as monitoring, tracking, smart cities,

K. Kim is with the School of Electrical Engineering and Computer Science, Gwangju Institute of Science and Technology, Gwangju 61005 Republic of Korea. Email: kskim@gist.ac.kr

M.Salman is with College of Electrical & Mechanical Engineering, National University of Sciences and Technology, Islamabad, Pakistan. Email: msalman@ceme.nust.edu.pk

I. Song is with the School of Electrical Engineering, Korea Advanced Institute of Science and Technology, Daejeon 34141 Republic of Korea. Email: i.song@ieee.org

This work was supported by the National Research Foundation of Korea under Grant NRF-2021R1IIA1A01041257, in part by the project titled "Development of Automatic Identification Monitoring System for Fishing Gears", funded by the Ministry of Oceans and Fisheries, Korea, and in part by the University of Science and Technology of China Visiting Professor International under Grant No. 2022BVT04, and by the research fund from Chosun University, 2024, for which the authors wish to express their appreciation. autonomous vehicles, and smart farming [1]. Furthermore, it is expected that the applicability of WSNs will continuously increase due to the rise of new technologies such as 6G [2] and cheaper prices of sensor nodes [3]. Normally, WSNs consist of several anchor nodes (ANs) and target nodes (TNs): the ANs can be static or dynamic and are usually aware of their own positions. In contrast, the TNs are sensor nodes with an unknown position that need to be estimated.

The estimation of the locations of the TNs is of great importance for any application of WSNs. In the literature there exist several techniques for estimating the unknown positions of the TNs, which can be grouped into centralized or decentralized approaches [1]. Although we focus our attention on centralized approaches in this work, the proposed algorithm can be easily implemented in a distributed manner also. The locations of TNs are commonly found via (a combination of) signal related measurements such as received signal strength (RSS) [4], time of arrival (TOA) [5], angle of arrival (AOA) [6], and channel state information (CSI) [7]. Among these common measurements, RSS is preferred due to the fact that most of the commercial sensor nodes readily provide the RSS information, and thus additional hardware/software is not required as in the case of the other measurements. This allows an easier implementation of the RSS-based localization with low hardware complexity and low cost. For these reasons, in this work, we utilize RSS measurements to find the locations of several TNs in a cooperative manner.

In contrast to the noncooperative localization, the cooperative localization uses signal related measurements obtained in both ANs and TNs. This increases the information about the TNs, which leads to an improvement in the localization accuracy, especially in sparse WSNs [1]. The improvement in the localization accuracy is possible at the cost of increased complexity of the maximum likelihood (ML) cost function [8]. Such highly complex ML cost function results in a more challenging optimization problem that cannot be handled by standard optimization techniques. A possible way to solve this problem is to employ iterative techniques. Although iterative techniques can be used for solving the cooperative localization problem, they generally require initial guess points that usually restrict their applicability. To avoid this requirement and guarantee convergence in some extent, convex optimization [9] has recently attracted considerable attention for solving the cooperative localization problem.

Techniques based on semidefinite programming (SDP) and second order cone programming (SOCP) have been

L. A. Caceres Najarro is with the Department of Computer Science of Chosun University, Gwangju 61452 Republic of Korea. Email: andrescn@chosun.ac.kr

shown to outperform several existing techniques based on the first/second derivative and linearization methods. For instance, under the assumption of low noise, the cooperative localization problem was relaxed using convex relaxation techniques based on SDP [10]. Similar relaxation was adopted in [11] based on SOCP when the cooperative localization problem was formulated under weighted least square criterion. In addition to the approaches in [10] and [11], the log-normal RSS measurement model was transformed into an equivalent multiplicative model in [12]. The cooperative ML estimator was approximated by a nonconvex estimator using the relative error criterion [13], which was then relaxed based on SDP techniques. Recently, biased RSS measurements were considered for formulating the cooperative localization problem, which was then relaxed based on SDP [14]. More recently, the cooperative localization cost function was converted into invariant convex function for reducing the computational complexity, which was then solved by the gradient descent algorithm [15]. Although the approach in [15] is computationally more efficient, it provides a lower localization accuracy than that in [14]. Certainly, the algorithms based on SDP and SOCP provide a reasonable localization accuracy, but, unfortunately, they suffer from a high computational complexity restricting their applicability.

In this paper, to reduce the computational complexity and provide a competitive localization accuracy at the same time, we investigate an alternative optimization technique based on a novel variant of the differential evolution (DE) [16]. Unlike the aforementioned cooperative localization algorithms, we first reformulate the cooperative localization problem under the multi-objective optimization framework. To do so, the cost function of the ML formulation of the cooperative localization problem is cast into several objective functions that are optimized separately. Although evolutionary algorithms with a single population may solve the cooperative localization problem, a multi-population evolutionary algorithm based on the DE is proposed to avoid the curse of dimensionality [17]. The proposed algorithm also takes advantage of the oppositionbased learning (OBL) [18, 19] and adaptive redirection [20] for better search capability and redirection of the individuals, respectively. Additionally, we exploit the connectivity information inferred from the interaction between sensor nodes for a better initialization and guiding of the individuals towards the positions of the TNs. To be precise, the connectivity information is exploited for generating the initial populations by generating pseudo-random individuals that are close to the ANs. Furthermore, a new process called anchoring is devised for guiding the individuals through the evolution process of all the populations.

The rest of this paper is organized as follows. In Section II, we present the RSS measurement model, the ML estimator, and the multi-objective framework for the cooperative localization problem. In Section III, the proposed approach is described in detail. The simulation results for several localization scenarios are presented in Section IV, where the proposed approach is compared with the state-of-the-art algorithms. The computational complexity is also analyzed in this section. Finally, concluding remarks are provided in Section V.

II. SYSTEM MODEL

This section introduces the cooperative localization problem based on RSS measurements, and presents the reformulation of the cooperative localization problem under the umbrella of multi-objective optimization framework.

A. Cooperative Localization

Let us consider a centralized WSN in the two-dimensional space \mathbb{R}^2 with N ANs and M TNs having the same communication, where $M \gg N$. The extension to the three dimensional space should be straightforward. We say that a pair of two sensors with positions p_1 and p_2 in \mathbb{R}^2 are directly connected or have a direct connection if only if

$$\|\boldsymbol{p}_1 - \boldsymbol{p}_2\| \le R,\tag{1}$$

where $\|\cdot\|$ and R denote the \mathcal{L}_2 norm and the communication range of the sensor nodes, respectively. If (1) does not hold, then we say the sensor nodes are indirectly connected or have an indirect connection. In an indirect connection, the two sensor nodes require relay node(s) to communicate each other since they are not within their communication range. We assume, due to a hardware limitation or limited communication range, it is not possible to have a fully connected network: in other words, only part of the TNs are directly connected to the ANs. In this situation, the cooperation between sensor nodes is necessary and is required to compensate for the deficiency in the number of ANs for an accurate estimation of the positions of TNs. This means that the TNs will also conduct RSS measurements and participate actively as pseudo ANs in the localization process.

The positions of the *n*-th AN and the *m*-th TN are denoted by $\mathbf{s}_n = [s_{n,1}, s_{n,2}], n \in \mathcal{N}$ and $\mathbf{x}_m = [x_{m,1}, x_{m,2}], m \in \mathcal{M}$, where $\mathcal{N} = \{1, 2, \dots, N\}$ and $\mathcal{M} = \{N+1, N+2, \dots, N+M\}$ represent the set of indices of the ANs and TNs, respectively. To find the positions of TNs in a cooperative manner, RSS measurements are conducted in both the TNs and ANs. Note that the RSS measurements can only be taken between sensor nodes with positions satisfying (1). Thus, we define two sets $\mathcal{A}_m = \{n : ||\mathbf{s}_n - \mathbf{x}_m|| \leq R, n \in \mathcal{N}\}$ and $\mathcal{B}_m = \{k : ||\mathbf{x}_k - \mathbf{x}_m|| \leq R, k \in \mathcal{M}\}$ that contain the indices of the anchor nodes and target nodes, respectively, directly connected to the *m*-th TN for $m \in \mathcal{M}$. The information contained in the sets \mathcal{A}_m and \mathcal{B}_m will be used later in Section III in the generation of the initial population and anchoring processes of the proposed technique.

The path loss between the n-th AN (TN) and the m-th TN in decibel [10, 15] can be formulated as

$$L_{nm} = L_0 + 10\gamma \log_{10} d_{nm} + v_{nm} \tag{2}$$

for $m \in \mathcal{M}$ and $n \in \mathcal{A}_m \cup \mathcal{B}_m$, where L_0 denotes the path loss at the reference distance assumed to be 1 m as in the literature [11, 12, 15], γ is the path loss exponent, v_{nm} represents the log-shadowing noise modeled as a zero-mean Gaussian random variable with variance $\sigma_{v_{nm}}^2$, and d_{nm} is the Euclidean distance between the *n*-th and *m*-th sensor nodes, i.e., for $m \in \mathcal{M}$, $d_{nm} = ||\mathbf{s}_n - \mathbf{x}_m||$ when $n \in \mathcal{N}$ and $d_{nm} = ||\mathbf{x}_n - \mathbf{x}_m||$ when $n \in \mathcal{M}$.

Let us denote by $\boldsymbol{X} = [\boldsymbol{x}_{N+1}^T, \boldsymbol{x}_{N+2}^T, \cdots, \boldsymbol{x}_{N+M}^T] \in \mathbb{R}^{2 \times M}$ the vector of all the unknown positions of the TNs. Then, from (2) the ML estimator of \boldsymbol{X} for cooperative RSS based localization can be obtained as

$$\hat{\boldsymbol{X}} = \arg\min_{\boldsymbol{X}} \sum_{m \in \mathcal{M}} \sum_{n \in \mathcal{A}_m \cup \mathcal{B}_m} \frac{(P_{nm} - 10\gamma \log_{10} d_{nm})^2}{\sigma_{v_{nm}}^2}, (3)$$

where $P_{nm} = L_{nm} - L_0$. The cost function of (3) is highly nonlinear, multimodal, and nonconvex: this is the reason why most of the state-of-the-art algorithms solve an approximation of the ML formulation.

B. Multiobjective Formulation

The cooperative localization problem can be viewed as a dynamic optimization problem, and can be reformulated under the multi-objective optimization framework [21]. To do so, we first note that (3) can be rewritten as

$$\hat{\boldsymbol{X}} = \arg\min_{\boldsymbol{X}} \sum_{m=N+1}^{N+M} f_m(\boldsymbol{x}_m), \qquad (4)$$

where

$$f_m(\boldsymbol{x}_m) = \sum_{n \in \mathcal{A}_m \cup \mathcal{B}_m} \frac{1}{\sigma_{v_{nm}}^2} (P_{nm} - 10\gamma \log_{10} d_{nm})^2 \quad (5)$$

is the cost function corresponding to the *m*-th TN for $m \in \mathcal{M}$. To align with the multi-objective optimization framework, each TN's cost function is treated as a separate objective, allowing simultaneous minimization of individual cost function as

$$\hat{\boldsymbol{X}} = \underset{\boldsymbol{X}}{\operatorname{arg\,min}} \{ f_{N+1} \left(\boldsymbol{x}_{N+1} \right), f_{N+2} \left(\boldsymbol{x}_{N+2} \right), \\ \cdots, f_{N+M} \left(\boldsymbol{x}_{N+M} \right) \}.$$
(6)

This strategy is expected to enhance the localization accuracy by optimizing each position of the TNs while considering the interactions among them.

III. PROPOSED LOCALIZATION ALGORITHM

For solving (6), we propose a multiple population DE combined with OBL, adaptive redirection, and an additional process called anchoring. The OBL in the proposed method, is used in the initialization process in order to generate better individuals closer to the global optimum. In the meantime, the adaptive redirection is to assure that the individuals are located inside the solution space

$$\mathbf{Z} = \{(z_1, z_2) : a_1 \le z_1 \le b_1, a_2 \le z_2 \le b_2\},$$
(7)

also called the area of interest (AOI), where a_d and b_d denote, respectively, the lower and upper bound of the AOI for d = 1, 2. The process anchoring guides the individuals through the evolution process toward the global optimum by using the connectivity information contained in the sets A_m and B_m .

Fig. 1 shows the flow chart of the main components of the proposed algorithm. The proposed algorithm generates as many populations as the number M of the TNs. The *m*-th population is dedicated to solve the cost function $f_m(\mathbf{x}_m)$ for $m \in \mathcal{M}$. The sharing matrix serves as a crucial link between the populations, storing and updating the estimated



Fig. 1. Flow chart of the proposed algorithm for the cooperative localization in WSNs.

positions of all TNs at each generation. This matrix facilitates the sharing of the estimates of the positions of the TNs among the populations, ensuring collaborative information exchange. More details on the sharing matrix will be described later when we present the pseudo code of the proposed algorithm.

A. Processes of the Proposed Algorithm

Commonly, standard evolutionary algorithms such as the DE start the generation of individuals randomly. In the proposed algorithm, on the other hand, a pseudo random initialization by using connectivity information between ANs and TNs is devised. In essence, if a TN is directly connected to one or more ANs, the individuals of the corresponding population will be generated by taking into account the positions of the ANs to which the TN is directly connected. By doing so, it is expected that the initial population will be closer to the global minima, resulting in a faster convergence of the proposed algorithm.

Let us denote the *m*-th population, a collection of *L* individuals, in the *g*-th generation by $\{I_l^{g,m}\}_{l=1}^L$ for $g = 1, 2, \dots, G$ and $m = 1, 2, \dots, M$. Each individual $I_l^{g,m}$ is a two-dimensional vector $[I_{l,1}^{g,m}, I_{l,2}^{g,m}]$, with $I_{l,1}^{g,m}$ and $I_{l,2}^{g,m}$ called genes, and is a candidate estimate of the *m*-th unknown position \boldsymbol{x}_m .

1) Generation of initial populations: The initial *m*-th population $\{I_l^{1,m}\}_{l=1}^{L}$ is selected taking the best *L* vectors among $\{I_l^{+,m}\}_{l=1}^{L}$ and $\{I_l^{-,m}\}_{l=1}^{L}$ for $m = 1, 2, \cdots, M$, which are created as pseudo-random vectors

$$T_{l,d}^{+,m} = \begin{cases} a_d + r \left(b_d - a_d \right), & \text{if } \delta = 0, \\ R_d + \frac{1}{|\mathcal{A}_m|} \sum_{n \in \mathcal{A}_m} s_{n,d}, & \text{if } \delta = 1, \end{cases}$$
(8)

and their opposite

1

$$I_{l,d}^{-,m} = \begin{cases} a_d + b_d - I_{l,d}^{+,m}, & \text{if } \delta = 0, \\ \frac{2}{|\mathcal{A}_m|} \sum_{n \in \mathcal{A}_m} s_{n,d} - I_{l,d}^{+,m}, & \text{if } \delta = 1, \end{cases}$$
(9)

using the OBL scheme [18], respectively, where $\delta = 1$ when the *m*-th TN is directly connected to one or more ANs and $\delta = 0$ otherwise, $R_d = \frac{rR}{|\mathcal{A}_m|} \cos(\theta)$ and $R_d = \frac{rR}{|\mathcal{A}_m|} \sin(\theta)$ when d = 1 and d = 2, respectively, *r* is the product of two uniformly distributed random variables on [0, 1], θ is a random variable uniformly distributed on $[0, 2\pi]$, and $|\cdot|$ denotes the cardinality of a set.

Once the initial populations are generated, five processes, namely, mutation, crossover, anchoring, adaptive redirection, and selection are conducted recursively for each of the M populations.

2) *Mutation:* The *l*-th mutant of the *m*-th population is generated from the combination of three individuals at the g-th generation as

$$\tilde{\boldsymbol{I}}_{l}^{g,m} = \boldsymbol{I}_{k}^{g,m} + \alpha \left(\boldsymbol{I}_{p}^{g,m} - \boldsymbol{I}_{q}^{g,m} \right).$$
(10)

In (10) α is the scaling factor determining the diversity and convergence speed with the value normally between 0.4 and 1 [22]. The indices k, p, and q of the three individuals are randomly selected in such a way that they are different from each other.

3) *Crossover:* Once the mutation process is completed, a trial individual $\breve{I}_{l}^{g,m} = \left[\breve{I}_{l,1}^{g,m}, \breve{I}_{l,2}^{g,m}\right]$ is created as

$$\check{I}_{l,d}^{g,m} = \begin{cases} \tilde{I}_{l,d}^{g,m}, & \text{if } c_l \le p_C, \\ I_{l,d}^{g,m}, & \text{if } c_l > p_C \end{cases}$$
(11)

by mating the mutated vector $\tilde{I}_l^{g,m}$ and the target vector $I_l^{g,m}$ for $l = 1, 2, \dots, L$, where c_l is a uniformly distributed random variable on [0, 1] and $p_C \in [0, 1]$ represents the crossover probability.

4) Anchoring: In an evolutionary algorithm, the trial individuals are commonly blindly generated: i.e., a trial individual is generated without any information. In contrast, in the proposed algorithm, the connectivity information contained in the sets $\{A_m\}$ and $\{B_m\}$ is used to guide the individuals toward the positions of TNs. The guidance is provided by anchoring the individuals with respect to the positions of the ANs and/or TNs to which the *m*-th TN is directly connected. Specifically, the *m*-th anchored population $\{\vec{I}_l^{g,m} = [\vec{I}_{l,1}^{g,m}, \vec{I}_{l,2}^{g,m}]\}_{l=1}^L$ is obtained from the trial population $\{\vec{I}_l^{g,m}\}_{l=1}^L$ as

$$\ddot{I}_{l,d}^{g,m} = \begin{cases} \check{I}_{l,d}^{g,m}, & \text{if } C_N = C_M = 0, \\ \frac{\dot{I}_{l,d}^{g,m} \cdot C_N + \ddot{I}_{l,d}^{g,m} \cdot C_M}{C_N + C_M}, & \text{otherwise,} \end{cases}$$
(12)

where C_N and C_M are binary parameters: $C_N = 0$ if the trial individual $\check{I}_l^{g,m}$ satisfy (1) for direct connection with respect to the positions of the ANs the *m*-th TN is connected to, otherwise $C_N = 1$. Similarly, $C_M = 0$ if the trial individual $\check{I}_l^{g,m}$ satisfy the condition (1) for direct connection with respect to the positions of the TNs the *m*-th TN is connected to, otherwise $C_M = 1$. The terms

$$\dot{I}_{l,d}^{g,m} = R_d + \frac{1}{|\mathcal{A}_m|} \sum_{n \in \mathcal{A}_m} s_{n,d} \tag{13}$$

and

$$\ddot{R}_{l,d}^{g,m} = R_d + \frac{1}{|\mathcal{B}_m|} \sum_{k \in \mathcal{B}_m} \hat{x}_{k,d}^{g-1}$$
 (14)

represent anchored vectors relative to the positions of the ANs and TNs, respectively. In addition, $\hat{x}_{k}^{g-1} = \begin{bmatrix} \hat{x}_{k,1}^{g-1}, \hat{x}_{k,2}^{g-1} \end{bmatrix}$ denotes the best estimate of the *k*-th TN with direct connection to the *m*-th TN, obtained at the (g-1)-th generation.

5) Adaptive redirection: Due to the random generation of the populations and the mutation process, some individuals may be out of the solution space Z affecting negatively the evolution process. To avoid this situation, the adaptive redirection process introduced in [20] is employed. The adaptive redirection process uses efficiently the information contained in the population to guide the individuals. To be specific, to assure that the genes of individuals are always within the solution space Z, the redirected population $\left\{ I_{l}^{g,m} = \left[I_{l,1}^{g,m}, I_{l,2}^{g,m} \right] \right\}_{l=1}^{L}$ is obtained as

for d = 1, 2 from the anchored population $\{ \boldsymbol{I}_{l}^{g,m} \}_{l=1}^{L}$, where β_{d} is a uniformly distributed random variable on [0, 1] and

$$a_{d}^{g,m} = \min_{I_{l,d}^{g,m}} \left(\left\{ I_{l,d}^{g,m} \right\}_{l=1}^{L} \right)$$
(16)

and

$$b_{d}^{g,m} = \max_{I_{l,d}^{g,m}} \left(\left\{ I_{l,d}^{g,m} \right\}_{l=1}^{L} \right)$$
(17)

denote the lower and upper bounds, respectively, of the area of redirection at the g-th generation of the m-th population.

6) Selection: At each iteration g, the proposed algorithm selects the individual with the lowest fitness value as

$$\boldsymbol{I}_{l,m}^{g+1} = \arg\min_{\boldsymbol{I}_{l}^{g,m}, \boldsymbol{f}_{l}^{g,m}} \left\{ f_{m} \left(\boldsymbol{I}_{l}^{g,m} \right), f_{m} \left(\boldsymbol{I}_{l}^{g,m} \right) \right\}, \qquad (18)$$

among the target individual $I_l^{g,m}$ and the redirected individual $I_l^{g,m}$. Note that the populations are updated only if the redirected individual is better than the target individual.

After all M populations evolve during G generations by passing through the five processes explained above, the best individual of the m-th population is selected as the best estimation of the m-th TN as

$$\hat{\boldsymbol{x}}_{m} = \operatorname*{arg\,min}_{\boldsymbol{I}_{l}^{G,m}} \left\{ f_{m} \left(\boldsymbol{I}_{l}^{G,m} \right) \right\}_{l=1}^{L}$$
(19)

for $m \in \mathcal{M}$. Then, the estimate of the M TNs $\hat{X} = [\hat{x}_{N+1}^T, \hat{x}_{N+2}^T, \cdots, \hat{x}_{N+M}^T]$ is presented.

Here, we incorporate the population midpoint scheme [23], which was demonstrated to improve the performance of the standard DE in a simple and elegant way [24]. The population midpoint scheme creates a midpoint individual $\bar{I}^g = [\bar{I}^g_1, \bar{I}^g_2]$ by calculating the average over a population $\{I^g_l\}_{l=1}^L$ as

$$\bar{\boldsymbol{I}}^g = \frac{1}{L} \sum_{l=1}^{L} \boldsymbol{I}_l^g, \qquad (20)$$

where $I_l^g = \left[I_{l,1}^g, I_{l,2}^g\right]$ represents an individual in the population.

The midpoint individual has been proven statistically that it is better than any individual in the population [23]. Although the midpoint scheme can be used at any stage of the evolution process, it has been demonstrated in [24] that a consistent improvement can be obtained when the population midpoint scheme is employed after G generations. Consequently, we employ the midpoint scheme at the end of the evolution process for each of the populations. In other words, the estimated position of the m-th TN is obtained as

$$\hat{x}_m = \frac{1}{L} \sum_{l=1}^{L} I_l^{G,m}.$$
 (21)

Note that in contrast to (19), instead of taking the best individual, we take the individual obtained through the population midpoint scheme as the estimate of the m-th TN.

The pseudo code of the proposed algorithm is presented in Algorithm 1. Here, $\hat{X}^g = [\hat{x}^g_{N+1}, \hat{x}^g_{N+2}, \cdots, \hat{x}^g_{N+M}]$ is the sharing matrix in which the estimates of the positions of all TNs at the *g*-th generation are stored and updated. This matrix is used for evaluating the cost function and anchoring (12) the individuals in each population. Note that this matrix is fully updated generation by generation, and acts as a link between the populations.

IV. EXPERIMENTATION AND PERFORMANCE ANALYSIS

In this section, results from numerical simulations are presented to show the performance of the proposed algorithms for solving the cooperative localization problem. We assume an area of 100 m \times 100 m with nine fixed ANs located at (0,0), (0,50), (0,100), (50,100), (50,50), (50,0), (100,100),(100, 50), and (0, 100). The RSS measurements are generated using the propagation model (2) with a path loss $L_0 = 40$ dB, path loss exponent $\gamma = 3$, and the standard deviations of the log-shadowing noise fixed to be the same for both connections AN-TN and AN-TN, i.e., $\sigma_{v_{nm}} = \sigma$. For the proposed algorithms, we assume a population size L = 10, scaling factor $\alpha = 0.9$, crossover probability $p_C = 0.9$, lower bounds $a_1 = a_2 = 0$, upper bounds $b_1 = b_2 = 100$, and maximum number of generation G = 50. It should be mentioned that these values were obtained after extensive preliminary experiments and are in line with those used in [20, 25].

For comparing the performance of the proposed algorithms, the performances of the SDP [10], SDP1 [12], and SOCP [11] Algorithm 1: Pseudo code of the proposed algorithm to estimate the positions of M TNs.

Input : ML cost function (5), RSS measurements, number N of ANs, number M of TNs, communication range R, population size L, scaling factor α , crossover probability p_C , maximum number G of generations, lower bounds a_1 and a_2 , and upper bounds b_1 and b_2 **Output:** Estimated positions of the *M* TNs 1 Initialize the populations according to (8) and (9); 2 while $q \leq G$ do Select the best individual from each population and 3 set the sharing matrix $\hat{oldsymbol{X}}^g = \left[\hat{oldsymbol{x}}^g_{N+1}, \hat{oldsymbol{x}}^g_{N+2}, \cdots, \hat{oldsymbol{x}}^g_{N+M}
ight]$ as the initial estimation of the M TNs; 4 for $m = 1; m \le M; m = m + 1$ do 5 for l = 1; l <= L; l = l + 1 do 6 Create mutant individuals with (10); 7 Generate trial individuals via (11); 8 Obtain anchored individuals via (12); 9 Redirect the anchored individuals according 10 to (15): Select the best individual according to (18); 11 12 end Update the *m*-th vector in \hat{X}^{g} ; 13 end 14 Increase q = q + 1; 15 16 end 17 Return the estimated positions of the M TNs;

approaches are taken into consideration here. The algorithms of these approaches are all implemented in Matlab. For the algorithms based on SDP and SOCP, we use the well-known package CVX [9], where the solver is SeDuMi [26]. In addition to these algorithms, we have included the solution of the ML (ML-true) obtained through the function slqnonlin of Matlab, for which the real positions of the TNs was assumed as the initial guessing positions to provide the actual lower bound on the localization error. The function slqnonlin employs the Levenverg Marquart optimization to solve the problem at hand.

The normalized root mean square error (NRMSE) defined as

NRMSE =
$$\sqrt{\frac{1}{MM_C} \sum_{i=1}^{M_C} \sum_{m=1}^{M} \|\boldsymbol{x}_{mi} - \hat{\boldsymbol{x}}_{mi}\|}$$
 (22)

is used as the performance metric, where M_C is the number of Monte Carlo runs, and x_{mi} and \hat{x}_{mi} denote the real and estimated positions, respectively, of the *m*-th TN at the *i*-th run.

A. Influence of the Number of Target Nodes

The performance of the proposed algorithms is first evaluated when the number M of TNs varies in the area of interest. Fig. 2 illustrates the NRMSE values as a function of



Fig. 2. NRMSE versus number of target nodes.

the number of TNs when the connectivity range and standard deviation of the log-shadowing noise are set to R = 40 m and $\sigma = 4$ dB, respectively. In general, it is observed that the localization accuracy of all algorithms improves as the number of TNs increases, as expected, due to the increased information from the TNs. The proposed algorithms provide the best and most consistent localization accuracy, following the ML-true algorithm. Specifically, the proposed algorithms demonstrate a larger advantage over the SDP, SDP-1, and SOCP when the number of TNs is smaller. Additionally, the proposed algorithm using the population midpoint scheme achieves better localization accuracy than the proposed algorithm with the best individual selection among the two proposed algorithms.

B. Influence of the Noise Variance

The performance of the algorithms is now evaluated at different levels of log-shadowing noise to investigate their effectiveness. Specifically, we considered a scenario with M =30 TNs and a connectivity range of R = 40 m for all sensor nodes. Fig 3 shows the localization accuracy of the algorithms considered when the standard deviation of the log-shadowing noise varies from 1 to 6 dB. As expected, it is observed that the performance of the algorithms deteriorates as the standard deviation increases. However, such trend is less prominent for the proposed algorithms. This figure also shows that the proposed algorithms provide the least localization accuracy for low values of the standard deviation of the log-shadowing noise, the proposed algorithms outperform considerably the other algorithms at high values of the standard deviation of the noise. For instance, at $\sigma = 6$ dB, the proposed algorithm provides a localization improvement of around 23%, 18%, and 18% with respect to the SDP, SDP1, and SOCP, respectively. Similarly, the enhanced proposed algorithm (Proposed-1) improves the localization accuracy by roughly 26%, 22%, and 22% with respect to the SDP, SDP1, and SOCP, respectively.

C. Influence of the Connectivity Range

Cooperative localization is a crucial aspect of WSNs and requires careful consideration of several parameters, including



Fig. 3. NRMSE versus standard deviation of the log-shadowing noise.



Fig. 4. NRMSE versus connectivity range.

the connectivity range. However, increasing the connectivity range can lead to higher energy consumption, which can significantly reduce the life span of sensor nodes. Consequently, investigating the localization accuracy as a function of the connectivity range is of great important.

To investigate the impact of the connectivity range, we consider 30 TNs and a standard deviation $\sigma = 4$ dB of the log-shadowing noise. Fig. 4 shows the NRMSE when the connectivity range R varies from 40 to 90 m. It is observed that, as R increases, the NRMSE decreases for all the algorithms. This is because a larger R allows more connections among sensor nodes, increasing the number of RSS measurements. Interestingly, the proposed algorithms provide the best performance when the connectivity range is smaller and have comparable localization accuracy at higher values of the connectivity range. This suggests that the proposed algorithms using connectivity information have a higher impact when the connectivity range values are smaller.

D. Computational Complexity

In cooperative localization, the computational complexity of an algorithm is also a crucial factor that should be taken

TABLE I Comparison of Theoretical Computational Complexity of Several Algorithms

Algorithm	Complexity
Proposed	$O\left(2GL\left(M^2+M\left(N-1\right)\right)\right)$
SDP [10]	$O\left(\sqrt{2}M^{0.5}\left(4M^4\left(N+\frac{M}{2}\right)^2\right)\right)$
SDP1 [12]	$O\left(M^{0.5}\left(4M^4\left(N+\frac{M}{2}\right)^2\right) ight)$
SOCP [11]	$O\left(M^{0.5}\left(4M^4\left(N+\frac{M}{2}\right)^2\right) ight)$

into account alongside the localization accuracy. In fact, there exists often a trade-off between these two, and a balance needs to be targeted between achieving a higher localization accuracy and lower computational complexity. An algorithm with high computational complexity may not be suitable for real-time processing and can limit its practical applicability. Conversely, reducing the computational complexity of an algorithm can enhance its applicability, particularly in real-time scenarios. Thus, in this section, we examine and compare the computational complexity of the algorithms under consideration.

The Big-O notation is used to describe the theoretical complexity of the algorithms. In the calculation of the complexity of the algorithms, minor terms are typically neglected, and only the dominant terms are considered. In our particular case, the dominant terms are the maximum number G of iterations, the number L of individuals per population, the number M of TNs, and the number N of ANs. Table I presents the theoretical computational complexity for the algorithms discussed in the previous section. It is noteworthy that the theoretical complexity of the proposed algorithms have an order of N and M^2 with regards to the number N of ANs and number M of TNs, respectively. In contrast, the other algorithms used for comparison are of the order of N^2 and $M^{6.5}$. Thus, it is expected that the proposed algorithms will have a lower running computational time, especially when the numbers of TNs and/or ANs are high. This statement will be demonstrated shortly.

Assuming R = 40 m, G = 50, L = 10, N = 9, and varying the number M of TNs from 10 to 90, measurements of the real computational time are secured. Fig. 5 shows the average of the computational time of all the algorithms in a log scale. This figure shows the proposed algorithms are the least demanding among all the algorithms compared. This result is in accordance with the theoretical complexity presented in Table I. Additionally, the figure also shows that both proposed algorithms have practically the same computational time.

E. Discussion

The comparison of the proposed algorithms have been performed with several variations of the cooperative localization scenario such as number of TNs, standard deviation of the logshadowing noise, and connectivity range. In such variation of the cooperative localization problem, the proposed algorithms provide significant improvement of the localization accuracy



Fig. 5. Average running time versus number of target nodes (CPU: Intel (R) Core (TM) i5-6600 3.30 GHz. RAM: 16.0 GB.).

under high level of noise, limited connectivity range, and small number of TNs. These results suggest the proposed algorithms are well suited for sparse deployment of WSNs. In WSNs with a large number of sensor nodes, the proposed algorithms are expected to provide equal or only marginal gain in the localization accuracy with respect to the other algorithms, especially with respect to those based on the SOCP.

With regard to the computational complexity, we demonstrated, theoretically and experimentally, that the proposed algorithms require the least computational complexity. This result implies a better trade-off between computational complexity and accuracy of the proposed algorithms. Additionally, it is worth mentioning that the proposed algorithms provide similar computational complexity in the localization accuracy gain obtained by incorporating the population midpoint scheme comes at free cost. Thus, a proper incorporation of the population midpoint scheme in any evolutionary algorithm is highly recommendable.

V. CONCLUSION

In this paper, we developed an algorithm and an enhanced version of it based on differential evolution with opposition based learning, adapting redirection, anchoring, and population midpoint scheme. The proposed algorithms are for addressing the high non-linearity, nonconvexity, and multi-modality of the cooperative localization problem in wireless sensor networks with limited communication range. We also reformulated the problem under the multi-objective framework, where the cost function of the cooperative localization is split into several small cost functions that accounts only for a target node. The proposed algorithms, which employ as many populations as the number of target nodes, have been compared with state-of-the-art algorithms based on semidefinite programming and second order cone programming. Results from various simulations conducted under different scenarios indicate that the proposed algorithms offer a notable enhancement in localization accuracy compared to alternative methods. This improvement is particularly evident in scenarios characterized by a limited number of anchor nodes, high levels of noise, and a restricted connectivity range. Importantly, the proposed algorithms demonstrate comparable localization accuracy to other methods in alternative scenarios. Additionally, the computational complexity of the proposed algorithms is the least demanding among the algorithms compared. These results imply the robustness and computational efficiency of the proposed algorithms for sparse wireless sensor networks applications with limited communication range and computational power.

ACKNOWLEDGEMENT

This research was supported in part by the Basic Science Research Program through the National Research Foundation of Korea (NRF), funded by the Ministry of Education under the grant numbers NRF-2020R1A4A1018774 and NRF-2021M3A9E4080780, and by the Program of International Visiting Professor of the University of Science and Technology of China under Grant 2022BVT04, and by the research fund from Chosun University, 2024.

REFERENCES

- L. A. Caceres-Najarro, I. Song, and K. Kim, "Fundamental limitations and state-of-the-art solutions for target node localization in WSNs: A review," *IEEE Sensors J.*, vol. 22, no. 24, pp. 23661–23682, Dec. 2022.
- [2] M. Z. Chowdhury, M. Shahjalal, S. Ahmed, and Y. M. Jang, "6G wireless communication systems: Applications, requirements, technologies, challenges, and research directions," *IEEE Open J. Commun. Soc.*, vol. 1, pp. 957–975, July 2020.
- [3] S. Yinbiao, K. Lee, P. Lanctot, F. Jianbin, H. Hao, B. Chow, and J. P. Desbenoit, "Internet of things: Wireless sensor networks," *Int. Electrotechnical Commission* - *White Paper*, pp. 1–78, 2014.
- [4] A. Zanella, "Best practice in RSS measurements and ranging," *IEEE Commun. Surveys, Tuts.*, vol. 18, no. 4, pp. 2662–2686, 4th Quart. 2016.
- [5] W. Wu, G. Wang, and K. Ho, "Multistatic localization by differential time delays and time differences of arrival in the absence of transmitter position," *IEEE Trans. Aerosp.*, *Electron. Syst.*, vol. 59, no. 5, pp. 7020–7034, Oct. 2023.
- [6] S. L. Shih, C. K. Wen, S. Jin, and K. K. Wong, "Angleof-arrival estimation with practical phone antenna configurations," *IEEE Internet Things J.*, vol. 10, no. 22, pp. 20006–20020, Nov. 2023.
- [7] X. Tian, S. Zhu, S. Xiong, B. Jiang, Y. Yang, and X. Wang, "Performance analysis of Wi-Fi indoor localization with channel state information," *IEEE Trans. Mobile Comput.*, vol. 18, no. 8, pp. 1870–1884, Aug. 2019.
- [8] S. M. Kay, Fundamentals of Statistical Signal Processing. Upper Saddle River, NJ: Prentice Hall PTR, 1993.
- [9] S. Boyd and L. Vandenberghe, *Convex Optimization*. Cambridge, UK, Cambridge University Press, 2004.
- [10] S. Tomic, M. Beko, and R. Dinis, "RSS-based localization in wireless sensor networks using convex relaxation:

Noncooperative and cooperative schemes," *IEEE Trans.* Veh. Technol., vol. 64, no. 5, pp. 2037–2050, May 2015.

- [11] S. Chang, Y. Li, H. Wang, W. Hu, and Y. Wu, "RSSbased cooperative localization in wireless sensor networks via second-order cone relaxation," *IEEE Access*, vol. 6, pp. 54097–54105, Sep. 2018.
- [12] Z. Wang, H. Zhang, T. Lu, and T. A. Gulliver, "Cooperative RSS-based localization in wireless sensor networks using relative error estimation and semidefinite programming," *IEEE Trans. Veh. Technol.*, vol. 68, no. 1, pp. 483–497, Jan. 2019.
- [13] K. Chen, S. Guo, Y. Lin, and Z. Ying, "Least absolute relative error estimation," *J. Amer. Statist. Assoc.*, vol. 105, no. 491, pp. 1104–1112, Sep. 2010.
- [14] Q. Wang, Z. Duan, and F. Li, "Semidefinite programming for wireless cooperative localization using biased RSS measurements," *IEEE Commun. Lett.*, vol. 26, no. 6, pp. 1278–1282, June 2022.
- [15] B. Mukhopadhyay, S. Srirangarajan, and S. Kar, "Invex relaxation based cooperative localization using RSS measurements," *IEEE Trans. Commun.*, vol. 70, no. 8, pp. 5482–5497, Aug. 2022.
- [16] R. Storn and K. Price, "Differential evolution A simple and efficient heuristic for global optimization over continuous spaces," *IEEE J. Global Optimization*, vol. 11, no. 4, pp. 341–359, Dec. 1997.
- [17] S. Chen, A. Bolufé-Röhler, J. Montgomery, W. Zhang, and T. Hendtlass, "Using average-fitness based selection to combat the curse of dimensionality," in *IEEE Congr. Evol. Comput.*, Padua, Italy, pp. 1–8, July 2022.
- [18] H. R. Tizhoosh, "Opposition-based learning: A new scheme for machine intelligence," in *Proc. Int. Conf. Comput.*, Vienna, Austria, pp. 695–701, Nov. 2005.
- [19] Z. Seif and M. B. Ahmadi, "An opposition-based algorithm for function optimization," *Eng. Appl. Artificial Intell.*, vol. 37, pp. 293–306, Jan. 2015.
- [20] L. A. Caceres-Najarro, I. Song, and K. Kim, "Differential evolution with opposition and redirection for source localization using RSS measurements in wireless sensor networks," *IEEE Trans. Autom. Sci., Eng.*, vol. 17, no. 4, pp. 1736–1747, Oct. 2020.
- [21] Z. Fei, B. Li, S. Yang, C. Xing, H. Chen, and L. Hanzo, "A survey of multi-objective optimization in wireless sensor networks: Metrics, algorithms, and open problems," *IEEE Commun. Surveys, Tuts.*, vol. 19, no. 1, pp. 550– 586, 1st Quart. 2017.
- [22] J. Rökkönen, S. Kukkonen, and K. V. Price, "Realparameter optimization with differential evolution," in *Proc. Congr. Evol. Comput.*, Edinburgh, Scotland, pp. 506–513, Sep. 2005.
- [23] J. Arabas and R. Biedrzycki, "Improving evolutionary algorithms in a continuous domain by monitoring the population midpoint," *IEEE Trans. Evol. Comput.*, vol. 21, no. 5, pp. 807–812, Oct. 2017.
- [24] L. A. Caceres-Najarro, I. Song, A. Dadlani, and K. Kim, "Population midpoint-based differential evolution for localization in wireless sensor networks," in *Proc. IEEE Globecom Workshops*, Rio de Janeiro, Brazil, pp. 335–

340, Dec. 2022.

- [25] L. A. Caceres-Najarro, I. Song, S. Tomic, and K. Kim, "Fast localization with unknown transmit power and path-loss exponent in WSNs based on RSS measurements," *IEEE Commun. Lett.*, vol. 24, no. 12, pp. 2756– 2760, Dec. 2020.
- [26] I. Polik, "Addendum to the SeDuMi user guide version 1.1," in http://sedumi.ie.lehigh.edu/?page_id=58, June 2005.