Convex Data-Driven Contraction With Riemannian Metrics

Andreas Oliveira

Jian Zheng

Mario Sznaier

Abstract—The growing complexity of dynamical systems and advances in data collection necessitates robust data-driven control strategies without explicit system identification and robust synthesis. Data-driven stability has been explored in linear and nonlinear systems, often by turning the problem into a linear or positive semidefinite program. This paper focuses on a new emerging property called contractivity, which refers to the exponential convergence of all system trajectories toward each other under a specified metric. Data-driven closed loop contractivity has been studied for the case of the 2-norm and assuming nonlinearities are lipschitz bounded in subsets of \mathbb{R}^n . We extend the analysis by considering Riemannian metrics for polynomial dynamics. The key to our derivation is to leverage the convex criteria for closed-loop contraction developed in [20] and duality results to efficiently check infinite dimensional membership constraints. Numerical examples demonstrate the effectiveness of the proposed method for both linear and nonlinear systems, highlighting its potential for robust data-driven contraction.

Index Terms—Control Theory, Contraction, Data-driven control, Nonlinear control

I. INTRODUCTION

The growing complexity of dynamical systems and our enhanced ability to collect accurate measurements necessitates the development of robust control strategies derived purely from data. Traditional model-based approaches are to perform system identification and design a robust control law on the identified system. However, for nonlinear systems, system identification can be particularly challenging, and the robustness of these methods often relies on classical techniques, such as Lyapunov stability, an extensive review on this topic can be found in [23].

In response, new data-driven methodologies that bypass the identification step and go directly to the control design have been developed. Pioneering work in this space includes virtual feedback tuning [8] and iterative feedback tuning [9], which have demonstrated success in solving tracking problems. Similarly, there has been a great effort in certifying stability in a data-driven fashion. In the context of Linear Time-Invariant (LTI) systems if one can create a quadratic Lyapunov function compatible with data then that is a necessary and sufficient condition for stability. There are still many challenges associated with this task: dealing with rank deficient data, noise, or switched linear systems. Notable contributions in the LTI data driven stabilization include [3], [4], [21], [22], [12].

Stabilizing nonlinear systems can be treated like an LTI problem if one chooses to do it locally. That is one estimates the Jacobian of the system around a point and locally stabilizes that system, this is the main idea in data-driven approaches for nonlinear systems seen in [16], [5], Global stability for nonlinear systems is a much harder problem. Without assuming some form of nonlinearity the problem of verifying stability certificates becomes intractable furthermore, methods like quadratic Lyapunov functions are no longer guaranteed to exist as is the case for LTI systems. To address these difficulties, [11] assumed systems were polynomial and resorted to finding a data-driven density function so that the resulting problem was transformed into linear programs. Similarly, in [14], a positive semidefinite program is derived by using quadratic-like Lyapunov to ensure closed-loop stability of polynomial nonlinear systems.

This paper focuses on deriving data-driven control strategies for a different property that has seen increased interest, namely contractivity. Contractive systems were brought to the spotlight of controls research in [19] and [1]. A comprehensive treatment of the subject is given in the book [7]. Informally, contractive systems are those where the distance between different trajectories, measured in a suitable chosen metric, tends to zero exponentially fast, regardless of the initial conditions. Furthermore, if a system contains a fixed point and is contractive then the fixed point is globally asymptotically stable. Contractive systems enjoy many other useful properties: invariance under bounded noise, entrainment to periodic forcing, and boundedness in the infinite horizon.

Closed loop contraction in a model-based setting was first studied in [20]. The convex criteria developed there will be the basis of our data-driven results. Several methods have been built on top of this original framework to improve its computational efficiency, notably neural network-based contraction metrics [10], [25], [26]. The core idea is to use a neural network to specify a contraction metric, then stochastically minimize a matrix inequality as a function of the metric and a dataset of trajectories. To prove robustness of the above usually requires the assumption of independent and identically distributed samples of trajectories. Hence guaranteeing the contraction holds over the entire domain of interest can only be given probabilistically. Additionally, as is often the case with Neural Network optimization problems, being stuck in local minima can never be prevented. Therefore, we seek to define a robust data-driven method that will guarantee contractivity over the entire domain of interest.

Recent work on robust data-driven contraction has been

This work was partially supported by NSF grants ECCS-1808381 and CNS-2038493, AFOSR grant FA9550-19-1-0005, ONR grant N00014-21-1-2431 and DHS grant 22STESE0001-02-00. The authors are with the Robust Systems Lab, ECE Department, Northeastern University, Boston, MA 02115. (e-mails: {franciscodemelooli.a,zheng.jian1}@northeastern.edu, msznaier@coe.neu.edu)

explored in [27] and [17]. The first approach builds on the insightful discovery that for certain contractive dynamical systems there exists a lifting via Koopman operators that maps to an LTI system specified by a Hurwitz matrix. Finding the lifting amounts to finding functions that solve a PDE and hence the space of solutions may not be finite or compact. However, if one assumes certain basis functions for the lifting then the problem of finding a contraction metric amounts to a system identification that is bilinear, non-convex and requires the identified system to be Hurwitz. In general, this is NPhard but using certain relaxations the problem was solved efficiently. The second paper is more closely aligned with ours. There authors seek a feedback controller that makes all systems compatible with observed data contractive with respect to weighted quadratic metrics. The key point is that the Demidovich condition for a quadratic metric can be made linear in relation to the feedback controller. Furthermore, it can be transformed into a semi-definite program if one assumes noiseless measurements and Lipschitz-bounded nonlinearities in the subspace considered. In this paper, we generalize these results by considering noisy measurements, potentially unbounded polynomial nonlinearities and non-quadratic metrics. Rather, we search for contraction metrics in the space of Riemannian metrics defined by polynomials. The main idea of our method is to leverage the convex criteria developed in [20] and duality results akin to the work in [11] to construct a metric and a control law that enforces a nonlinear semidefinite condition to be true.

The paper is organized as follows: Section II provides the definitions and theorems that will be used throughout the paper, along with the problem definition. Section III presents a sufficient condition that solves the problem exploiting Lagrange duality. Section IV develops a tractable relaxation of the dual optimization problem. Section V illustrates these results with numerical examples. Finally, Section VI presents conclusions and directions for future researach.

II. PRELIMINARIES

A. Notation

$\mathbb{R}^n, (\mathbb{R}^n_+)$	n-tuples of real and non-negative reals
$1,0,\mathbf{I}$	vector/matrix of all 1s, 0s, identity matrix
$ x _{\infty}$	ℓ_{∞} -norm of vector x
$ x _{2}$	ℓ_2 -norm of vector x
X^T	the transpose of X
$x \succeq 0$	x is element-wise non-negative
S_n^{++}	the set of symmetric positive definite matrices
$X\succeq 0$	X is positive semi-definite
$X \succ 0$	X is positive definite
$f\in C^d$	the d^{th} derivative of f exists and is continuous
$\operatorname{vec}(X)$	vectorization of matrix X along columns
\otimes	matrix Kronecker product

B. Kronecker Product Property

The following property of Kronecker product [15] will be used in the paper:

$$\operatorname{vec}(B^T X^T A^T) = (A \otimes B^T) \operatorname{vec}(X^T).$$
(1)

C. Contractions

The idea behind contraction is to show that the distance between trajectories decreases exponentially. The choice of metric one considers is crucial, as systems can have trajectories that exponentially converge to a single trajectory under only one metric, an example can be found in section C of [1].

Following the presentation of [13], we provide some intuition of how this can be formalized and then give a definition. Consider $f \in C^1(\mathbb{R}^n)$ and define the ODE:

$$\dot{x}(t) = f(x). \tag{2}$$

Let $\psi : \mathbb{R}_+ \times \mathbb{R}^n \to \mathbb{R}^n$ be the flow operator of the ODE such that its derivative with respect to time satisfies (2) and $\psi(0, x) = x$ (an initial value condition). The goal is to bound

$$l(t) = d(\psi(t, x), \psi(t, y))$$
(3)

where d(.,.) is a distance, by exploiting the structure of $\frac{\partial l(t)}{\partial t}$. Consider a metric tensor $M(x) \in C^1(\mathbb{R}^n) \to S_n^{++}$ and the associated Riemannian metric $\langle \delta_1, \delta_2 \rangle_x \doteq \delta_1^T M(x) \delta_2$. In this context, a suitable choice for l(t) is the length of a geodesic between $\psi(t,x), \psi(t,y) \in \mathbb{R}^n$. Next, given a C^1 curve γ : $[0,1] \to \mathbb{R}^n$ such that $\gamma(0) = x, \gamma(1) = y$, define $l(t,\gamma)$ as:

$$l(t,\gamma) \doteq \int_0^1 L(t,\gamma,s)ds \tag{4}$$

where:

$$L(t,\gamma,s) = \left(\frac{\partial}{\partial s}\psi^T(t,\gamma(s))M(\phi(t,\gamma(s)))\frac{\partial}{\partial s}\psi(t,\gamma(s))\right)^{\frac{1}{2}}.$$
(5)

Assuming $l(t, \gamma) \in C^2$ and hence satisfies the Leibniz differentiation rule we have that:

$$\frac{\partial l(t,\gamma)}{\partial t} = \int_0^1 \frac{1}{2L(t,\gamma,s)} \frac{\partial}{\partial s} \psi^T(t,\gamma(s)) C(t,\psi(t,\gamma(s))) \frac{\partial}{\partial s} \psi(t,\gamma(s)) ds$$
(6)

where $C(t,x) = \frac{\partial f(x)}{\partial x}^T M(x) + M(x) \frac{\partial f(x)}{\partial x} + \dot{M}(x)$ and $\dot{M}(x) = \sum_{i=1}^n \frac{\partial M(x)}{\partial x_i} f(x)^T e_i$ where e_i is the *i*th basis vector in \mathbb{R}^n . Hence

$$C(t,x) \preceq -2\lambda M(x) \Rightarrow \frac{\partial l(t,\gamma)}{\partial t} \leq -\lambda l(t,\gamma)$$
 (7)

which implies $l(t, \gamma) \leq e^{-\lambda t} l(0, \gamma)$. Since l(t) was defined to be the length of the geodesic between $\psi(t, x), \psi(t, y)$, we have that $l(t) \leq l(t, \gamma)$ for any γ and hence $l(t) \leq e^{-\lambda t} l(0)$ (assuming the geodesic exists). Therefore, the matrix inequality (7) is sufficient to guarantee exponential convergence of any initial value problem leading to the formal definition:

Definition: [19] We consider a system **contractive** with respect

to \mathbb{R}^n if $\exists M \in C^1(\mathbb{R}^n) \to S_n^{++}$ and a real number $\lambda > 0$ such that the following matrix inequality holds for $\forall x \in \mathbb{R}^n$:

$$\frac{\partial f(x)}{\partial x}^{T} M(x) + M(x) \frac{\partial f(x)}{\partial x} + \dot{M}(x) \prec -2\lambda M(x).$$
(8)

As indicated above and as shown in [19] any system of the form $\dot{x} = f(t, x)$ that is contractive, satisfies for any two solutions $\psi(t, x), \psi(t, y)$:

$$d(\psi(t,x),\psi(t,y)) \le e^{-\lambda t} d(x,y) \tag{9}$$

which implies that all solutions have bounded norm over the infinite horizon.

D. The Data-Driven Contraction Problem

In this paper, we will consider continuous-time controlaffine polynomial system of the form

$$\dot{x} = f(x) + Gu = F\phi(x) + Gu \tag{10}$$

where $x \in \mathbb{R}^n$ and $u \in \mathbb{R}^m$ are state and control, f is a polynomial up to certain degree, $\phi(x)$ represents a vector of monomials of x and F, G are constant matrices.

For example,

$$f(x) = \begin{bmatrix} 3x_2 - x_1^2 \\ x_2 \end{bmatrix} = \begin{bmatrix} 3 & -1 \\ 1 & 0 \end{bmatrix} \begin{bmatrix} x_2 \\ x_1^2 \end{bmatrix} = F\phi(x).$$
(11)

Assume that T noisy measurements of $\{\dot{x}, x, u\}$ satisfying:

$$\dot{x}[i] = f(x[i]) + Gu[i] + \eta[i], \|\eta[i]\|_{\infty} \le \epsilon, \forall i = 1, ..., T$$
(12)

are available. Here the ℓ_{∞} bounded noise η models, for instance, process disturbances or the error incurred when approximating \dot{x} by finite differences.

Definition 1. The consistency set \mathcal{P}_1 of the system (10) is the set of all F compatible with the observations (12), e.g.

$$\mathcal{P}_1 \doteq \{F \colon \|F\phi(x[i]) + Gu[i] - \dot{x}[i]\|_{\infty} \le \epsilon, \ i = 1, ..., T\}$$
(13)

Problem 1. Given noisy data $\{\dot{x}, x, u\}$ generated by a system of form (10), with a known G, find smooth M(x) and state feedback control law u(x) such that for all $F \in \mathcal{P}_1$, the closed-loop system is contractive under the metric induced by M.

Remark 1. The case where G is a potentially unknown polynomial function of x can be reduced to the problem above by filtering the control action with known dynamics and absorbing the unknown G(x) into f(x), e.g.:

$$\begin{bmatrix} \dot{x} \\ \dot{u} \end{bmatrix} = \begin{bmatrix} f(x) + G(x)u \\ 0 \end{bmatrix} + \begin{bmatrix} 0 \\ I \end{bmatrix} v \tag{14}$$

III. DATA-DRIVEN CONTRACTION CONTROL

The goal of this section is to establish tractable conditions for finding a (differential) data-driven control law that renders all systems in \mathcal{P}_1 contractive. This will be accomplished by recasting the problem into a robust optimization problem.

A. Robust Optimization Reformulation

Begin by rewriting the consistency set as

$$\mathcal{P}_1 \doteq \{F \colon \operatorname{Tr}(F\Phi_{i,k}^{\pm}) \le d_{i,k}^{\pm}, \,\forall i, k\}$$
(15)

where

$$\Phi_{i,k}^{\pm} = \left[\mathbf{0}, ..., \pm \phi(x[i]), ..., \mathbf{0}\right], \ d_{i,k}^{\pm} = \epsilon \pm (\dot{x}[i] - Gu[i]).$$
(16)

For example, for $x[i] \in \mathbb{R}^2$ and a single measurement, we have

$$\Phi_{1,1}^{\pm} = \begin{bmatrix} \pm \phi(x[1]) & \mathbf{0} \end{bmatrix}, \quad d_{1,1} = \epsilon \pm (\dot{x}_1[1] - Gu[1]) \\ \Phi_{1,2}^{\pm} = \begin{bmatrix} \mathbf{0} & \pm \phi(x[1]) \end{bmatrix}, \quad d_{1,2} = \epsilon \pm (\dot{x}_2[1] - Gu[1]).$$
(17)

In the sequel the \pm superscript in $\Phi_{i,k}^{\pm}$ and $d_{i,k}^{\pm}$ is omitted to keep the notation cleaner.

For systems of the form (10), the contraction condition (8) becomes:

$$\dot{M}(x) + (F\frac{\partial\phi}{\partial x} + G\frac{\partial u(x)}{\partial x})^T M(x)$$

$$+ M(x) (F\frac{\partial\phi}{\partial x} + G\frac{\partial u(x)}{\partial x}) \prec -2\lambda M(x)$$
(18)

Using the change of variable $W = M^{-1}$ and leveraging Proposition 2 in [20], the differential control law $\frac{\partial u(x)}{\partial x} = -\frac{1}{2}\rho(x)G^TW^{-1}(x)$ renders the closed loop system contractive if there exists $W(x) \in S_n^{++}$ and a function $\rho(x)$ such that $\forall x \in \mathbb{R}^n$ (we omit (x) for brevity hereafter):

$$-\dot{W} + W(F\frac{\partial\phi}{\partial x})^T + (F\frac{\partial\phi}{\partial x})W + 2\lambda W - \rho GG^T \prec 0$$
(19)

and

$$\sum_{j} \frac{\partial W(x)}{\partial x_j} (Ge_i)_j = 0, \forall i = 1, ..., n$$
(20)

where e_i is the *ith* basis vector in \mathbb{R}^n . For the future, condition (20) is abbreviated as $\partial_G W(x) = 0$.

In terms of (15), (19) and (20), Problem 1 can be reformulated as:

Problem 2. Find $W \in S_n^{++}$ and ρ such that (19)-(20) hold for all F satisfying (15).

B. Solution via Duality

In principle, Problem 2 can be reduced to a sequence of SDPs by exploiting Scherer's Positivstellesatz [24]. However, this approach is practically limited to relatively small, low-order systems due to the very poor scaling properties of the resulting SDP with respect to the size of F and W. To avoid this difficulty, in this paper, we will pursue a duality-based approach to obtain an equivalent condition that does not involve F.

Assume for now that x is fixed and hence ρ and W are constant. Scalarizing (19) leads to the following equivalent condition:

$$y^{T}(W\partial\phi^{T}F^{T} + F\partial\phi W - \dot{W} + 2\lambda W - \rho GG^{T})y < 0$$

$$\forall \|y\|_{2} = 1 \text{ and all } F \text{ such that } \mathbf{Tr}(F\Phi_{i,k}) \leq d_{i,k}.$$
(21)

This condition can be reduced to an SDP via Putinar's Positivstellenzats in y and the elements of F. However, as before, this leads to problems with poor scaling properties. Rather than pursuing this approach, we will enforce (21) by computing

$$p^{*}(y, W, \rho) = \max_{F} y^{T}(W\partial\phi^{T}F^{T} + F\partial\phi W - \dot{W} + 2\lambda W - \rho G G^{T})y \qquad (22)$$

subject to: $d_{i,k} - \operatorname{Tr}(F\Phi_{i,k}) \ge 0.$

and finding W(x) and $\rho(x)$ such that $p^*(y, W, \rho) < 0$ for all $\|y\|_2 = 1$.

Theorem 1. A metric tensor $W(x) \in C^1(\mathbb{R}^n) \to S_n^{++}$ and a function $\rho(x)$ solve Problem 2 if there exists non-negative functions $\mu_{i,k}(x, y)$ such that:

$$y^{T}(-2\lambda W + \rho GG^{T})y - \sum_{i,k} [\mu(x,y)d]_{i,k} > 0$$
 (23a)

for all
$$\|y\|_2 = 1$$

 $\operatorname{vec}(-2\partial\phi Wyy^T + \Sigma_{i,k}\mu_{i,k}\Phi_{i,k})^T$
(23b)

$$+ \Sigma_i Tr(\frac{\partial W}{\partial x_i} y y^T) (e_i^T \otimes \phi^T) = 0$$

$$\partial W(x)_G = 0$$
(23c)

$$\mu_{i,k}(x,y) \ge 0, W(x) \succ 0$$
(23d)

Moreover, if the consistency set \mathcal{P}_1 has a non-empty interior, then the condition is also necessary.

Proof. The Lagrangian of (22) for fixed y, W, ρ is given by:

$$L(F, \mu_{i,k}) = \sum_{ik} \mu_{ik} (d_{ik} - \operatorname{Tr}(F\Phi_{i,k})) +$$

$$y^{T} (W \partial \phi^{T} F^{T} + F \partial \phi W - \dot{W} + 2\lambda W - \rho G G^{T}) y =$$

$$\operatorname{Tr} \left\{ F \left(2\partial \phi W y y^{T} - \sum_{i,k} \mu_{i,k} \Phi_{i,k} \right) \right\} -$$

$$\operatorname{Tr} \left\{ \left(\dot{W} - 2\lambda W + \rho G G^{T} \right) y y^{T} \right\} + \sum_{i,k} \mu_{i,k} d_{i,k}.$$
(24)

Expanding \dot{W} by leveraging (23c) and (1) yields:

$$\dot{W} = \sum_{i} \frac{\partial W}{\partial x_{i}} (\phi^{T} F^{T}) e_{i} =$$

$$\sum_{i} \frac{\partial W}{\partial x_{i}} (e_{i}^{T} \otimes \phi^{T}) vec(F^{T}).$$
(25)

Using the former identity and the fact that $Tr(AB) = vec(B)^T vec(A^T)$ the Lagrangian becomes:

$$L(F, \mu_{i,k}) = \operatorname{vec}(2\partial\phi Wyy^T - \Sigma_{i,k}\mu_{i,k}\Phi_{i,k})^T\operatorname{vec}(F^T) - \Sigma_i \operatorname{Tr}(\frac{\partial W}{\partial x_i}yy^T)(e_i^T \otimes \phi^T)\operatorname{vec}(F^T) + \operatorname{Tr}((2\lambda W - \rho GG^T)yy^T) + \Sigma_{i,k}\mu_{i,k}d_{i,k}.$$
(26)

Notice that $L(F, \mu_{i,k})$ is affine in F therefore the dual function:

$$g(\mu_{i,k}) = \sup_{F} L(F,\mu_{i,k}) \tag{27}$$

is finite only if (23b) holds. Therefore:

$$g(\mu_{i,k}) = \begin{cases} \operatorname{Tr} \left\{ (2\lambda W - \rho G G^T) y y^T \right\} + \sum_{i,k} [\mu d]_{i,k} \\ \text{if (23b) holds and} \\ \infty \text{ otherwise} \end{cases}$$
(28)

Hence, if there exists non-negative multipliers $\mu_{i,k}(x,y) \ge 0$ satisfying (23), $g(\mu_{i,k}) < 0$. From weak duality [6] it follows that $p^*(y, W, \rho) < 0$ for all $||y||_2 = 1, W(x), \rho(x)$ such that $x \in \mathbb{R}^n$. Thus (19)-(20) hold for all F satisfying (15). Moreover, if the consistency set \mathcal{P}_1 has a non-empty interior, then (22) is a linear program in F which now satisfies Slater's condition at each $y, W(x), \rho(x)$. Hence strong duality holds and $p^*(y, W, \rho) = g^*(\mu_{i,k})$. Thus (23) is also necessary. \Box

Corollary 1. The differential feedback control law $\frac{\partial u}{\partial x} = -\frac{1}{2}\rho(x)G^T M(x)$ renders all systems in \mathcal{P}_1 contractive.

IV. TRACTABLE RELAXATIONS

From Theorem 1 it follows that Problem 2 reduces to a feasibility problem in $W(x) \in S_n^{++}, \mu_{ik}(x, y) \in \mathbb{R}_+$, and $\rho(x)$. However, searching for a matrix function $W(x) \succ 0$ is generically intractable. To avoid this problem we will restrict the search to SoS matrices, that is $W(x) = (\Psi \otimes \mathbf{I})^T Q(\Psi \otimes \mathbf{I})$ where $Q \succ 0$ and Ψ is a basis of monomials per [24]. Similarly, to guarantee that $\mu_{i,k} \ge 0$ and (23a), the search is performed for $\mu_{i,k}$ belonging to the set of sum of squares polynomials. Finally, we will also restrict ρ to be a sum of squares a semi-algebraic optimization over W, μ , and ρ that satisfy the linear constraints in (23). In turn, by using standard SoS tools, this problem can be solved by solving a sequence of SDPs.

It is important to get an understanding of the computational complexity before presenting the examples. Assume the system dimension is n, the highest degree in ϕ is p, the highest degree in W is 2q and T data samples were collected. As discussed $W(x) = (\Psi \otimes \mathbf{I})^T Q(\Psi \otimes \mathbf{I})$ where Ψ is the vector of all monomials up to degree q of the system state. Hence the size of the Gram matrix Q is $n\binom{n+q}{q} \times n\binom{n+q}{q}$.

Furthermore, based on the set \mathcal{P}_1 and the number of data samples T, there are 2nT SOS functions $\mu_{i,k}$ each of which should have degree in x at least 2q + p - 1 and degree 2 in y. Thus, the associated Gram matrices have dimension $n_G \times n_G$ with $n_G \approx (n+1) \left(\frac{p-1}{2} + q + n\right)$.

On the other hand, enforcing (19) directly through Scherer's Psatz in the indeterminate $x \in \mathbb{R}^n$ and $F \in \mathbb{R}^{nm}$, involves an $n \times n$ SoS matrix in (n + nm) variables. Assuming polynomials of order 2q in W(x) and n_F in F the corresponding Gram matrix will have dimension $n_S \times n_S$ where $n_S \approx n \left(\frac{p-1}{2} + q+n\right) \binom{nm+n_F}{n_F}$. In summary, finding higher-order metrics comes at the cost of combinatorial complexity in the size of the positive semidefinite matrix constraints. However, exploiting duality mitigates the growth of the largest Gram

matrix, as compared to straight application of Scherer's Psatz, when m > 1, even when choosing $n_F = 1$. Additionally, while increasing the number of data samples can shrink the consistency set \mathcal{P}_1 it increases the amount of SOS functions $\mu_{i,k}$ needed.

V. NUMERICAL EXAMPLES

To decrease numerical errors and computational complexity, the following examples assume the basis function ϕ is known. Additionally due to the limitations of numerical solvers in handling zero equality constraints as required in (23b) and $\partial W_G = 0$, we adopt the heuristic that any polynomial coefficient smaller than 10^{-5} in W, ρ is set to 0. Each data driven problem is solved with 40 points coming from four distinct trajectories and the noise level is assumed to be $\|\epsilon\|_{\infty} = \frac{1}{20} \max_i(|\dot{x}[i]|)$.

A. Linear System

First, we validate our results in a linear system. Consider the system given by:

$$\dot{x} = \begin{bmatrix} 0.4285 & -0.4298\\ 0.4018 & 1.3036 \end{bmatrix} x + \begin{bmatrix} -0.7826 & 0.7731\\ -0.5110 & 0.0339 \end{bmatrix} u.$$
(29)

If $u = [0,0]^T$ the above is unstable with eigenvalues at 0.7291, 1.0030. The objective is to find a controller u and metric tensor W that ensures the system is contractive from data observations. Contractivity for linear systems is equivalent to exponential stability [1], so ideally the optimization problem would produce a constant positive definite matrix W and scalar ρ that makes the system contractive. As expected the results are:

$$W = \begin{bmatrix} 1.9710 & 0.1994 \\ 0.1994 & 0.0290 \end{bmatrix}, \rho = 82.3555.$$
(30)

In order to test this in the underlying dynamical system one needs to define u(x) from $\frac{\partial u(x)}{\partial x} = -\frac{1}{2}\rho G^T W$. Following [18], but simplifying the control input to track the origin:

$$u(x) = \int_0^1 -\frac{1}{2}\rho(\gamma(s))G^T W(\gamma(s))^{-1} \frac{\partial\gamma(s)}{\partial s} ds \qquad (31)$$

where $\gamma : [0,1] \to \mathbb{R}^2, \gamma(0) = [0,0]^T, \gamma(1) = x$ is the geodesic under the norm induced by W, which if constant implies $\gamma(s) = sx$ (i.e the straight line connecting x and (0,0)). Since both ρ, W are constant we have that the feedback controller that makes the system contractive is $u(x) = -\frac{1}{2}\rho G^T W^{-1}x$.

B. Nonlinear Examples

We alter the system referenced in [2] such that it is no longer open-loop contractive and it has a control input:

$$\begin{bmatrix} \dot{x}_1\\ \dot{x}_2 \end{bmatrix} = \begin{bmatrix} -x_2 - \frac{3}{2}x_1^2 - \frac{1}{2}x_1^3\\ 3x_1 + x_2 \end{bmatrix} + \begin{bmatrix} 1 & 0\\ 0 & 1 \end{bmatrix} u.$$
(32)

Ten random trajectories under zero control input are shown below:



Fig. 1. Progression of coordinate x_1 for ten different trajectories of (32)



Fig. 2. Progression of coordinate x_2 for ten different trajectories of (32)

Running the same optimization program on (32) results in:

$$W = \begin{bmatrix} 0.1302 & -0.0101 \\ -0.0101 & 1.8698 \end{bmatrix}, \quad (33)$$

$$\rho = 97.9804 - 0.2792x_1 + 96.7093x_1^2 + 96.8508x_2^2.$$

Doing the same as in the linear example, define u per (31). Since W is constant $\gamma(s) = sx$, but now ρ is a nonlinear function of x so there isn't a simple expression for u(x) and we resort to numerically integrating (31) at every ODE step. Creating 10 random initial value conditions and simulating their evolution under the resulting non-autonomous system yields:



Fig. 3. Progression of coordinate of x_1 for ten different trajectories of (32)



Fig. 4. Progression of coordinate of x_2 for ten different trajectories of (32)

which validates the control input u found based on the metric tensor W.

To demonstrate the need for a nonlinear contraction metric, let's draw from the example in [20]:

$$\begin{bmatrix} \dot{x}_1\\ \dot{x}_2\\ \dot{x}_3 \end{bmatrix} = \begin{bmatrix} -x_1 + x_3\\ -x_2 - 2x_1x_3 + x_3\\ -x_2 \end{bmatrix} + \begin{bmatrix} 0\\ 0\\ 1 \end{bmatrix} u.$$
(34)

and this time with a lower noise level of $\|\epsilon\|_{\infty} = \frac{1}{50} \max_i(|\dot{x}[i]|)$. Collecting the same amount of data points as before and running the optimization program, the following contraction metric W and ρ are found that make the closed-loop system contractive (only the (1,1)th entry of W, denoted as $W_{1,1}(x)$ is shown for the sake of brevity):

$$W_{1,1}(x) = 0.0147 + 0.0052x_1 + 0.0020x_2 + 0.1193x_1^2 + 0.0063x_1x_2 + 0.0258x_2^2 \rho(x) = 1 - 0.0910x_1 + 0.01404x_2 - 0.0031x_3 - 0.4266x_1x_3 + 151.76085x_1^2 + 0.6901x_1x_2 + 152.6700x_2^2 + 0.4565x_2x_3 + 150.5090x_3^2.$$
(35)

VI. CONCLUSION

We study the problem of finding a metric and state feedback controller that renders all systems compatible with noisy experimental data contractive. Previous works on this problem have considered the case of searching for weighted 2-norms that render a sector-bounded nonlinear system compatible with data contractive [17]. Our approach extends this by considering polynomial systems in unbounded domains and searching for Riemannian metrics. The key to our formulation lies in leveraging the convex criteria developed in [20] and applying duality to turn an infinite-dimensional set-membership constraint into an equivalent convex finite dimensional optimization. The problem can be solved efficiently for low dimensional systems and low order metric tensor W but remains challenging as the system dimension and tensor order increase, due to its combinatorial complexity. Future work seeks to address this complexity by using alternative characterizations of contractivity based on matrix log norms [7].

REFERENCES

- Zahra Aminzare and Eduardo D. Sontag. Contraction methods for nonlinear systems: A brief introduction and some open problems. In 53rd IEEE Conference on Decision and Control, pages 3835–3847, 2014.
- [2] Erin M. Aylward, Pablo A. Parrilo, and Jean-Jacques E. Slotine. Stability and robustness analysis of nonlinear systems via contraction metrics and sos programming. *Automatica*, 44(8):2163–2170, August 2008.
- [3] Julian Berberich, Anne Koch, Carsten W. Scherer, and Frank Allgöwer. Robust data-driven state-feedback design. In 2020 American Control Conference (ACC), pages 1532–1538, 2020.
- [4] Julian Berberich, Johannes Köhler, Matthias A. Müller, and Frank Allgöwer. Data-driven model predictive control with stability and robustness guarantees. *IEEE Transactions on Automatic Control*, 66(4):1702– 1717, 2021.
- [5] Gianluca Bontempi and Mauro Birattari. From linearization to lazy learning: A survey of divide-and-conquer techniques for nonlinear control (invited paper). *International Journal of Computational Cognition*, 3, 01 2004.
- [6] Stephen Boyd and Lieven Vandenberghe. Convex optimization. Cambridge university press, 2004.
- [7] F. Bullo. Contraction Theory for Dynamical Systems. Kindle Direct Publishing, 1.2 edition, 2024.
- [8] M.C. Campi and S.M. Savaresi. Virtual reference feedback tuning for non-linear systems. In *Proceedings of the 44th IEEE Conference on Decision and Control*, pages 6608–6613, 2005.
- [9] M.C. Campi and S.M. Savaresi. Direct nonlinear control design: the virtual reference feedback tuning (vrft) approach. *IEEE Transactions* on Automatic Control, 51(1):14–27, 2006.
- [10] Glen Chou, Necmiye Ozay, and Dmitry Berenson. Model error propagation via learned contraction metrics for safe feedback motion planning of unknown systems, 2022.
- [11] Tianyu Dai and Mario Sznaier. A semi-algebraic optimization approach to data-driven control of continuous-time nonlinear systems. *IEEE Control Systems Letters*, 5(2):487–492, 2020.
- [12] Tianyu Dai, Mario Sznaier, and Biel Roig Solvas. Data-driven quadratic stabilization of continuous lti systems**this work was supported in part by nsf grants cns-1646121, cmmi-1638234, iis-1814631 and eccs-1808381; afosr grant fa9550-19-1-0005; and the alert dhs center of excellence under award number 2013-st-061-ed0001. *IFAC-PapersOnLine*, 53(2):3965–3970, 2020. 21st IFAC World Congress.
- [13] Peter Giesl, Sigurdur Hafstein, and Christoph Kawan. Review on contraction analysis and computation of contraction metrics, 2022.
- [14] Meichen Guo, Claudio De Persis, and Pietro Tesi. Learning control for polynomial systems using sum of squares relaxations. In 2020 59th IEEE Conference on Decision and Control (CDC), pages 2436–2441, 2020.
- [15] Roger A. Horn and Charles R. Johnson. *Matrix Analysis*. Cambridge University Press, 1985.
- [16] Zhongsheng Hou and Shangtai Jin. Data-driven model-free adaptive control for a class of mimo nonlinear discrete-time systems. *IEEE* transactions on neural networks / a publication of the IEEE Neural Networks Council, 22:2173–88, 11 2011.
- [17] Zhongjie Hu, Claudio De Persis, and Pietro Tesi. Enforcing contraction via data, 2024.
- [18] Karen Leung and Ian R. Manchester. Nonlinear stabilization via control contraction metrics: a pseudospectral approach for computing geodesics, 2017.
- [19] WINFRIED LOHMILLER and JEAN-JACQUES E. SLOTINE. On contraction analysis for non-linear systems. *Automatica*, 34(6):683–696, 1998.
- [20] Ian R Manchester and Jean-Jacques E Slotine. Control contraction metrics: Convex and intrinsic criteria for nonlinear feedback design. *IEEE Transactions on Automatic Control*, 62(6):3046–3053, 2017.
- [21] Claudio De Persis and Pietro Tesi. Formulas for data-driven control: Stabilization, optimality and robustness, 2019.
- [22] Claudio De Persis and Pietro Tesi. Low-complexity learning of linear quadratic regulators from noisy data, 2020.
- [23] Ricardo S. Sanchez-Pena and Mario Sznaier. Robust Systems Theory and Applications. John Wiley & Sons, Inc., USA, 1st edition, 1998.
- [24] C. W. Scherer and C. W. J. Hol. Matrix sum-of-squares relaxations for robust semi-definite programs. *Mathematical Programming*, 107(1):189– 211, 2006.

- [25] Dawei Sun, Susmit Jha, and Chuchu Fan. Learning certified control using contraction metric, 2020.
- [26] Hiroyasu Tsukamoto and Soon-Jo Chung. Neural contraction metrics for robust estimation and control: A convex optimization approach. *IEEE Control Systems Letters*, 5(1):211–216, January 2021.
 [27] Bowen Yi and Ian R. Manchester. On the equivalence of contraction and koopman approaches for nonlinear stability and control, 2023.