Enhancing Table Recognition with Vision LLMs: A Benchmark and Neighbor-Guided Toolchain Reasoner

Yitong Zhou 1 , Mingyue Cheng 1 , Qingyang Mao 1 , Qi Liu 1 , Feiyang Xu 2 , Xin Li 2 , Enhong Chen 1

¹State Key Laboratory of Cognitive Intelligence, University of Science and Technology of China, Hefei, China, ² Artificial Intelligence Research Institute, iFLYTEK Co., Ltd, Hefei, China

{yitong.zhou,maoqy0503}@mail.ustc.edu.cn,{mycheng,qiliuql,cheneh,leexin}@ustc.edu.cn,fyxu2@iflytek.com

Abstract

Pre-trained foundation models have recently significantly progressed in structured table understanding and reasoning. However, despite advancements in areas such as table semantic understanding and table question answering, recognizing the structure and content of unstructured tables using Vision Large Language Models (VLLMs) remains under-explored. In this work, we address this research gap by employing VLLMs in a training-free reasoning paradigm. First, we design a benchmark with various hierarchical dimensions relevant to table recognition. Subsequently, we conduct in-depth evaluations using pre-trained VLLMs, finding that lowquality image input is a significant bottleneck in the recognition process. Drawing inspiration from these findings, we propose the Neighbor-Guided Toolchain Reasoner (NGTR) framework, which is characterized by integrating multiple lightweight models for low-level visual processing operations aimed at mitigating issues with low-quality input images. Specifically, we utilize a neighbor retrieval mechanism to guide the generation of multiple tool invocation plans, transferring tool selection experiences from similar neighbors to the given input, thereby facilitating suitable tool selection. Additionally, we introduce a reflection module to supervise the tool invocation process. Extensive experiments on public table recognition datasets demonstrate that our approach significantly enhances the recognition capabilities of the vanilla VLLMs. We believe that the designed benchmark and the proposed NGTR framework could provide an alternative solution in table recognition 1 1 .

Keywords

Vision Large Language Models, Table Recognition, Tool Invocation

ACM Reference Format:

Yitong Zhou¹, Mingyue Cheng¹, Qingyang Mao¹, Qi Liu¹, Feiyang Xu², Xin Li², Enhong Chen¹. 2018. Enhancing Table Recognition with Vision LLMs: A Benchmark and Neighbor-Guided Toolchain Reasoner. In Proceedings of Make sure to enter the correct conference title from your rights confirmation emai (Conference acronym 'XX). ACM, New York, NY, USA, [14](#page-13-0) pages. [https:](https://doi.org/XXXXXXX.XXXXXXX) [//doi.org/XXXXXXX.XXXXXXX](https://doi.org/XXXXXXX.XXXXXXX)

Conference acronym 'XX, June 03–05, 2018, Woodstock, NY

1 Introduction

Tables are ubiquitous for organizing and communicating structured information across diverse domains, ranging from scientific literature and business reports to web pages and financial documents [\[1,](#page-8-0) [2\]](#page-8-1). They encapsulate a wealth of information essential for numerous applications, such as knowledge discovery, decision support, and data-driven analytics [\[3,](#page-8-2) [4\]](#page-8-3). In the context of intelligent table applications, one fundamental yet challenging task is table recognition [\[5\]](#page-8-4): converting image-based table representations into structured digital formats. Over the years, substantial efforts [\[6\]](#page-8-5) have been made to tackle this problem, introducing various approaches to address challenges such as segmentation techniques and object detection methods.

Recently, the advent of Large Language Models (LLMs) [\[7\]](#page-8-6) and Vision Large Language Models (VLLMs) [\[8\]](#page-8-7) has revolutionized natural language processing and computer vision, respectively. For LLMs, their ability to process serialized data has facilitated numerous tabular data mining tasks, such as table-to-text generation [\[9](#page-8-8)[–11\]](#page-8-9), table question answering [\[12–](#page-8-10)[14\]](#page-8-11), and table semantic understanding [\[15–](#page-8-12)[17\]](#page-8-13). Meanwhile, several VLLM-based methods have emerged to bypass traditional OCR pipelines for visual table analysis and understanding [\[18,](#page-8-14) [19\]](#page-8-15).

Despite these advancements, our investigation reveals a noticeable gap: the application of VLLMs to table recognition remains underexplored. This task serves as a foundational building block for table-related applications. Some existing work [\[20,](#page-8-16) [21\]](#page-8-17) has focused on pre-training or fine-tuning VLLMs to accomplish this task. However, Fine-tuning VLLMs for specific tasks is often computationally expensive and risks catastrophic forgetting of general capabilities. To address this, we focus on leveraging a prompt-based paradigm for table recognition using pre-trained VLLMs, exploring a generative approach without requiring additional fine-tuning. Recognizing the absence of dedicated benchmarks in this domain, we design an evaluation framework based on a hierarchical design philosophy [\[22–](#page-8-18)[24\]](#page-8-19), comprising recognition tasks for table recognition. Through extensive evaluations, we identify a critical bottleneck: low-quality input images significantly hinder the table recognition

 $^1\rm{Our}$ code is open-sourced and available at<https://github.com/lqzxt/NGTR>

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

[©] 2018 Copyright held by the owner/author(s). Publication rights licensed to ACM. ACM ISBN 978-1-4503-XXXX-X/18/06 <https://doi.org/XXXXXXX.XXXXXXX>

capabilities of the evaluated VLLMs. This is understandable given the various characteristics associated with different table styles.

To overcome this limitation, we propose the Neighbor-Guided Toolchain Reasoner (NGTR) framework with the goal of effective table recognition. One of the main characteristics of the NGTR framework is that it integrates the capacity of lightweight models and the strategy of retrieval-augmented generation to enhance input image quality and guide structured data recognition. Specifically, we propose a preprocessing toolkit equipped with various lightweight models designed to enhance input image quality. For each input instance, we retrieve a similar neighbor from the training data, and the experience gained from these neighbors is used to inform the guidance for the generation of tool invocation plans. This experience based guidance helps select and integrate suitable tools for the given input. Furthermore, we incorporate a reflection-driven tool selection module at each step of tool invocation to iteratively refine table recognition outputs. This enables VLLMs to produce higher-quality structured data.

To validate the effectiveness of the proposed NGTR framework, we conduct extensive experiments on multiple public table recognition datasets. The key observations are as follows: (1) Our NGTR framework significantly enhances the table recognition performance of naive VLLM-based approaches; (2) While VLLMs achieve competitive accuracy on specific datasets compared to traditional models, a noticeable performance gap remains in favor of traditional models. Nonetheless, we have preliminarily revealed the performance boundaries of VLLMs in several representative table recognition datasets. As is shown in Figure [1,](#page-0-1) the VLLM-based table recognition approach demonstrates the capability for universal modeling. This method facilitates a paradigm shift in design objectives from a model-centric to a data-centric focus, presenting significant potential for further exploration. We hope this work will inspire more research efforts in the future.

In summary, the contributions of this paper are as follows:

- We pioneer the exploration of VLLM-based table recognition tasks by introducing a comprehensive benchmark with hierarchical evaluation settings.
- We propose the NGTR framework to address critical bottlenecks in table recognition, such as low-quality input images.
- We conduct extensive experiments to report the promising performance and potential of VLLMs for table recognition, along with interesting observations that highlight areas for future research.

2 Related Work

Table Recognition. Earlier table recognition (TR) methods predominantly rely on heuristic rules [\[25–](#page-8-20)[27\]](#page-8-21) or statistical learning techniques [\[28,](#page-8-22) [29\]](#page-8-23), which were generally effective on simple and standard structured tables. However, these approaches rely heavily on handcrafted features or implicit rules and show limited generalization ability. In the era of deep learning, numerous studies have made impressive progress in handling more intricate and heterogeneous table structures. Top-down methods [\[30–](#page-8-24)[33\]](#page-8-25) first predict table lines and boundaries to infer the overall structure, and then locate cells based on row-column intersections. Bottom-up methods [\[2,](#page-8-1) [34,](#page-8-26) [35\]](#page-8-27) first identify table cells with object detection models

[\[36,](#page-8-28) [37\]](#page-8-29), and then predict the cell relations to organize the rowcolumn structures to form the overall tables. These methods follow an explicit two-stage learning paradigm with relatively strong transferability and explainability, yet the risks of ambiguous contents and boundless structures may cause unstable and incorrect predictions.

Recently, sequence-based methods [\[38](#page-8-30)[–41\]](#page-8-31) have been widely explored to directly generate markup sequence defining structures with specific decoders. Although these approaches require a massive of training data and computing resources, they have demonstrated substantial potential to unify visual-text parsing tasks [\[42\]](#page-8-32).

Large Language Models. In recent years, LLMs have made significant progress in the field of natural language processing. In particular, LLMs such as GPT [\[43\]](#page-8-33) and Llama [\[44\]](#page-8-34) have demonstrated exceptional performance in tasks such as multi-task learning [\[45\]](#page-8-35), zero-shot learning [\[46\]](#page-9-0), and text generation [\[47\]](#page-9-1). These models have not only broken through the limitations of traditional technologies in generating natural language text, but have also shown capabilities in reasoning [\[48](#page-9-2)[–50\]](#page-9-3) and planning [\[51,](#page-9-4) [52\]](#page-9-5). Meanwhile, VLLMs combine the capabilities of visual and language understanding, enabling LLMs to process visual information. For multimodal understanding scenarios (e.g., scene text recognition [\[53\]](#page-9-6), visual question answering [\[54\]](#page-9-7)), VLLMs have been widely validated as effective [\[55](#page-9-8)[–57\]](#page-9-9). With continuous progress in text-rich scenarios, some studies [\[18,](#page-8-14) [20,](#page-8-16) [58\]](#page-9-10) have also focused on enabling VLLMs to handle multimodal table understanding tasks.

Despite their promising success in a wide range of domains, VLLMs applied to table recognition remain under-evaluated and under-explored. Our study presents a comprehensive benchmark for VLLM-based table recognition evaluation. Subsequently, we propose a novel framework to address the bottleneck of VLLMs, thereby enhancing their capabilities in table recognition.

3 Problem Definition and Proposed Benchmark 3.1 Problem Definition

We employ the generation paradigm of VLLMs to address the table recognition (TR) task, which is formulated as a format mapping problem from images to sequences. Formally, given a TR dataset $\mathcal{D} = \{ (I^i, H^i) \}_{i=1}^n$ with *n* samples, we predict the corresponding structured form H^i for each table image I^i . Specifically, we provide the image table I^i along with a prompt P as input to the VLLMs, which generates the structured data form $\hat{H}^i = \text{VLLM}(P, I^i)$.

3.2 Benchmark Evaluation Setup

This section proposes an evaluation benchmark for TR based on VLLMs, outlining the hierarchical recognition tasks to assess their performance and the evaluation setup, including the recognition tasks and VLLMs being evaluated. Details of the evaluation metrics and datasets are discussed in Section [5.1.](#page-5-0)

3.2.1 Recognition Task Design. We design several hierarchical recognition tasks to conduct a more in-depth assessment of VLLMs' table recognition capability. In addition to the general table recognition task, we extend our approach by designing recognition tasks that focus on the structural composition of the table, including the cell-level, row-level, column-level, and global table-level. This hierarchical recognition tasks design comprehensively assesses VLLM's

Granularity	Recognition Task	Description				
Table-level	Visual Table Size	Get the number of rows and columns.				
	Detection					
Row-level	Row Index-based					
	Data Recognition	Get the content list of a specific row.				
Column-level	Column Index-based					
	Data Recognition	Get the content list of a specific column.				
	Merged Cell	Get contents of all merged cells.				
	Detection					
Cell-level	Content-based	Get the location of specific cell content.				
	Cell recognition					
	Index-based	Get the cell content of specific location.				
	Cell Recognition					

Table 1: Descriptions of the proposed hierarchical recognition tasks.

table recognition capability at different levels. Table [1](#page-2-0) presents the details of the hierarchical recognition tasks.

Cell-level. We evaluate the cell-level recognition capability of VLLMs within three specific recognition tasks. Merged cell detection task aims to recognize cells that span multiple rows or columns in the table. Formally, given an image I , this task aims to recognize ${c_1, c_2, \ldots, c_n}$ that represents the textual content of all merged cells in the table. Content/index-based cell recognition tasks evaluate the structural and content recognition capabilities of VLLMs, which are crucial for assessing whether VLLMs could perform well in fine-grained table recognition. Formally, define an image I , the cell content c , and the cell's row and column indices (R, C) . The Content-based cell recognition task identifies the logical location (R, C) of the target cell, and the index-based cell recognition task extracts the content of the target cell $c_{(R,C)}$.

Row/Column-level. We evaluate the row/column-level recognition capability of VLLMs within two specific recognition tasks. Row/column index-based data recognition tasks are designed to assess whether VLLMs can accurately identify row/column elements. Formally, given a table image I with specific cell's row index R or column index C , the VLLMs are required to return the entire row content $[c_{(R,1)}, c_{(R,2)}, \ldots]$ or the column content $[c_{(1,C)}, c_{(2,C)}, \ldots]$.

Table-level. We evaluate the overall table-level recognition capability of VLLMs. The visual table size detection recognition task is designed to evaluate whether VLLMs can accurately determine the number of rows and columns in a table, assessing their comprehension of the global structural information.

3.2.2 Baselines. In this study, we evaluate the performance of six VLLMs. For open-source VLLMs, we select Phi-3.5-Vision-Instruct (Phi) and Llama-3.2-90B-Vision-Instruct (Llama) for evaluation. For closed-source VLLMs, we evaluat GPT-4o-mini (GPT-mini), Qwen-VL-Max (Qwen), GPT-4o (GPT) and Gemini-1.5-Pro (Gemini). The specific details of VLLM can be found in the appendix [D.](#page-11-0)

3.3 Benchmark Evaluation Results

Comprehensive evaluations of hierarchical structural recognition tasks are presented in Figure [2.](#page-2-1) The results show that, among all the VLLMs we selected, GPT and Gemini demonstrate the strongest performance, consistently outperforming the other VLLMs. Furthermore, open-source Llama demonstrates a significant performance

A Benchmark and Neighbor-Guided Toolchain Reasoner Conference acronym 'XX, June 03-05, 2018, Woodstock, NY

Figure 2: Experimental results of VLLMs for the proposed hierarchical tasks. The tasks evaluated include the following: merged cell detection (MCD), content/index-based cell recognition (CCR, ICR), index-based row/column data recognition (IRDR, ICDR), and visual table size detection (VTSD).

gap compared to the closed-source VLLMs. We give some highlights associated with the benchmark results as follows:

Figure 3: Row-column sensitivity analysis of VLLMs on designed hierarchical tasks. The left figure uses Gemini, and the right figure uses GPT.

Row-column Sensitivity Analysis. We found that all models show inconsistent performance between row/column-related tasks. To mitigate the influence of uneven distributions of rows and columns in the original data leading to varying difficulty levels, we further refine the experimental results by selecting samples where the difference between the number of rows and columns does not exceed three. The refined results are presented in Figure [3.](#page-2-2) The results of row-column sensitivity analysis experiments show that the accuracy for the column-related tasks is higher than for the row-related tasks, suggesting that VLLMs prefer to process column-structured information.

We believe this phenomenon is because columns usually contain more substantial attribute information, allowing VLLMs to locate columns more accurately. Rows tend to have higher similarities, so VLLMs faces more significant challenges locating rows or completing row-related tasks. The differences between rows and columns in visual table size detection further verify this view.

Image Quality Analysis. We conduct in-depth experiments and analysis on the TR task. Detailed experimental results and analysis are presented in Section [5.](#page-5-1) The results demonstrate that significant bottlenecks remain despite existing VLLMs achieving competitive

Table 2: Specific description of the challenges and scenarios in low-quality image inputs.

Challenge	Scenario	Description			
	Blur	The image is out of focus, with details			
Visual		appearing smeared or indistinct.			
	Underexposure	The image is too dark, which may			
Conditions		cause the content to be unclear.			
	Overexposure	The image is overly bright, losing			
		detail in some regions.			
	Unclear	The image's table borders are faint,			
Table	Borders	blending into the background.			
Border	Missing	The table is without expected			
Quality	Borders	borders or separators.			
	Thickened	The table borders are thickened.			
	Borders				
Geometric	Tilt 20°	The image is tilted at 20° angle.			
Deformation	Tilt 40°	The image is tilted at 40° angle.			

performance on the TR task. Using simple prompts, the publicly available VLLMs performs relatively well on the SciTSR dataset with higher image quality, scoring only 4.38 TEDS points lower than the leading baseline models. However, when processing the PubTabNet dataset with lower image quality, the performance gap widens significantly, reaching 13.63 TEDS points. This phenomenon indicates that the quality of the input image is a key bottleneck limiting the performance of VLLMs. Section [3.4](#page-3-0) provides a more in-depth analysis of this bottleneck.

3.4 Bottleneck Analysis

In this section, we further investigate the performance of VLLMs under varying image quality conditions and assess their visual robustness to these conditions through empirical analysis.

3.4.1 Experimental Setup. To comprehensively evaluate the visual robustness of VLLM, we focus on three distinct visual challenges: the image quality challenge, the table border quality challenge, and the geometric deformation challenge. Specifically, We randomly selected 1,000 samples from the SciTSR [\[59\]](#page-9-11) test set for our experiments and configure our image types according to these challenges. Details of these challenges are provided in Table [2.](#page-3-1)

Visual Conditions. Visual conditions is a key factor affecting the accuracy of VLLMs in table recognition. To assess it, we systematically analyze the performance of VLLMs under various visual conditions across three scenarios: blur, underexposure, and overexposure. These analyses demonstrate the robustness of VLLMs in handling impaired visual conditions.

Table Border Quality. Table borders indicate structural information and are critical for parsing tasks. We evaluate the impact of border visibility and completeness on table recognition performance by considering scenarios including unclear table borders and missing borders. Additionally, we explore the effect of border changes in the table by thickened table borders.

Geometric Deformation. Geometric deformation caused by viewing angles or operations can disrupt the geometric consistency of tables, which is common in visual table parsing, especially when

Figure 4: Evaluation results of bottleneck scenarios: abbreviations UE (Underexposure), OE (Overexposure), MB (Missing Borders), UB (Unclear Borders), TB (Thickened Borders).

tables are scanned or photographed. We evaluated the robustness of VLLMs against geometric deformations by testing them under tilt conditions of 20° and excessive tilt conditions of 40°.

3.4.2 Discussion and Analysis. Figure [4](#page-3-2) shows the detailed experimental results. We observe that blurring and overexposure can lead to loss of text information in table images and inaccurate fine-grained text recognition, thus negatively impacting the performance of table content recognition. In contrast, underexposure has little effect on table recognition performance. Moreover, VLLM demonstrates limited efficacy when processing skewed tables, resulting in a substantial decrease in accuracy under such conditions.

Although table borders are often considered essential for conveying structured information, modifications such as fading or removing these borders have minimal impact on the performance of VLLMs in TR tasks. This result suggests that VLLMs do not heavily rely on borders in TR. VLLMs only pay slight attention to the structural information the borders provide when thickening. Structural information provided by the borders.

4 Neighbor-Guided Toolchain Reasoner

Through our in-depth analysis of VLLMs' performance on benchmark tasks and bottleneck analysis, we have identified that the quality of the input image emerges as a critical factor that constrains the performance of these VLLMs. Consequently, improving input image quality is essential for enhancing VLLMs' capability to recognize and interpret structured image data more effectively. To address this bottleneck, we propose the NGTR framework.

4.1 Model Overview

NGTR enhances input image quality by applying various tool combinations tailored to scenarios such as low resolution, overexposure, and noise interference, among others. To select a suitable combination of tools, we employ a similarity-based neighbor retrieval module to obtain samples that resemble each input instance. These samples guide the generation of multiple tool invocation plans. Subsequently, the tool invocation experience learning module executes each toolchain plan and generates the corresponding structured data based on the neighbor samples. It evaluates the effectiveness of different plans to select a relatively better plan. In the final processing stage, we utilize a reflection-driven tool selection module. This module integrates iterative tool invocation and dynamic feedback to refine the processing flow. The optimized image resulting from this process is subsequently input into the VLLMs, which utilize Enhancing Table Recognition with Vision LLMs:

A Benchmark and Neighbor-Guided Toolchain Reasoner Conference acronym 'XX, June 03–05, 2018, Woodstock, NY

Figure 5: Illustration of a pipeline for table image preprocessing leveraging a toolkit of lightweight vision models.

Table 3: Specific descriptions of built tools in the toolkit.

Tool	Descriptions
Border En- hancement	The border enhancement tool improves the legibility of tables and their structures by thickening the border lines in the image. This process enhances the structural information features of tabular data.
Image Upscaling	Image upscaling optimize image resolution to improve visual quality. This technique is commonly employed to repair and enhance blurry images.
Noise Reduction	The noise reduction tool enhances image quality by adjusting brightness and contrast to mitigate noise interference and underexposure issues.
Binarization	The binarization tool converts images to black and white, highlighting key features for easier extraction.
Detection and Cropping	This tool identifies table regions within an image and crops them into independent segments. It is particularly suitable for processing images of tables embedded in complex backgrounds.

their powerful reasoning capabilities to generate the structured data representation of the table.

4.2 Toolkit Preparation

Inspired by the conclusions of the Bottleneck Analysis (Section [3.4\)](#page-3-0), we employ five distinct tools to address various scenarios and potential issues that may arise in the table recognition task. These tools are shown in Table [3.](#page-4-0) By combining different tools, NGTR effectively addresses various challenging situations. For example, when the table border is faint, the VLLMs can invoke the border enhancement tool to strengthen the structural information by thickening the table border. Similarly, when the table occupies only a portion of the image, the VLLMs can invoke the table detection and cropping tool to identify and crop the relevant table area, thereby reducing noise interference.

4.3 Similarity-based Neighbor Retrieval

Neighbor retrieval methods enable VLLMs to retrieve similar neighbor samples, providing richer contextual information. In the NGTR framework, we hypothesize that images with similar features exhibit similar results after being processed by the same image preprocessing toolchain. Consequently, the processing results of neighbor samples could guide the selection of a potentially optimal toolchain for test samples. We first retrieve images that are similar to the target task images from a sample set (a subset of the training data containing 100 samples). Subsequently, we employ a prompting template to leverage the VLLM's planning capabilities to generate tool invocation plans. The retrieval process can be formally described as follows:

Retrieval(
$$
I^{\text{test}}, \mathcal{D}', f
$$
) = arg max $\left[f\left(I^{\text{test}}, I^i\right) \right]_{i=1}^{|\mathcal{D}'|}$, (1)

where I^{test} represents an image from the test set, D' denotes a subset of the training dataset, and f is the similarity measurement function. In this paper, we combine the ORB (Oriented FAST and Rotated BRIEF) algorithm with the Hamming distance as f to measure the similarity between images. Specifically, the feature vectors are first extracted using the ORB algorithm for the task image and a candidate example image. Subsequently, the Hamming distance between the feature vectors of the two images is calculated as a measure of similarity. Then, we guide the VLLMs to generate multiple tool invocation plans for the image. The generation process can be formally expressed as follows:

$$
VLLM(\mathcal{T}, \mathcal{N}(I^{\text{test}})) \to \{p_1, p_2, \dots, p_n\},\tag{2}
$$

where $\mathcal T$ represents the description information set of all available image preprocessing tools, including their functions, applicable scenarios, invocation identifiers, and other relevant details; $\mathcal{N}(I^\mathsf{test})$ denotes the neighbor image samples of the test sample I^test , along with their associated features, retrieved from the training set; and $\{p_1, p_2, \ldots, p_n\}$ represents the generated candidate set of plans, which are then used to select an appropriate tool invocation plan.

4.4 Tool Invocation Experience Learning

In this module, we follow a sequential workflow to evaluate the multiple tool invocation plans. First, we execute each tool invocation plan generated by the previous module to obtain multiple processed images:

$$
I_{p_i} = f_{p_i}(I), \quad i \in \{1, 2, \dots, n\},\tag{3}
$$

where f_{p_i} denotes the image preprocessing process corresponding to the tool invocation plan p_i . Next, we use a simple prompt template to instruct VLLMs to generate an markup sequence.

$$
\hat{H}_{P_i} = \text{VLLM}(I_{P_i}, P),\tag{4}
$$

where P represents the prompt to instruct VLLMs generation.

Subsequently, we evaluate the prediction results based on the example labels. The evaluation process employs the tree edit distancebased similarity (TEDS) metrics to quantify the accuracy of the VLLMs output. The specific details of TEDS can be found in the appendix [E.](#page-11-1) By following this process, we calculate a quantitative score for each toolchain, enabling selection of a suitable plan.

4.5 Reflection-driven Tool Selection

Although the tool invocation experience learning module provides a high-quality plan, mindlessly applying the tool invocation plan to new samples may result in the loss of critical information in the image, thereby affecting the accuracy of the final result. To address this, we introduce the reflection-driven tool selection module during the execution phase to refine the processing flow, reduce information loss, and thereby improve recognition accuracy. The formalized expression of the reflection module is as follows:

Let $I^{(t-1)}$ denote the image before the t-th operation and $I^{(t)}$ denote the image after the t -th operation. The VLLMs computes a decision value $\gamma^{(t)}$ to determine whether to accept the operation:

$$
\gamma^{(t)} = \text{reflect}(I^{(t-1)}, I^{(t)}), \tag{5}
$$

where $\gamma^{(t)}$ is a binary decision indicating the quality change between the before and after images. The function $\text{reflect}(\cdot)$ evaluates the difference in quality. If $\gamma^{(t)} = 1$, the operation is considered successful; otherwise, if $\gamma^{(t)} = 0$, the operation is rejected, and the process proceeds to the next step.

This step-by-step module enhances the interaction between the VLLMs and the target image, ensuring the accuracy of the final task outcome. More importantly, introducing this module enables downstream researchers and developers to flexibly customize and expand the toolkit without worrying about the impact of poorly performing expanded tools on the final results, thereby significantly improving the versatility and transferability of our framework. In the last step, we use a simple prompt template to instruct VLLM to generate a markup sequence and obtain the result of table recognition.

5 Experiments

5.1 Experimental Setup

5.1.1 Datasets. In this study, we utilize three widely-used table recognition datasets: SciTSR [\[59\]](#page-9-11), PubTabNet [\[38\]](#page-8-30), and WTW [\[60\]](#page-9-12), each offering unique characteristics and challenges, as shown in Table [4.](#page-5-2) SciTSR is a dataset comprising tables extracted from the scientific literature, and the image quality in this dataset is relatively high. In contrast, the image resolution of PubTabNet is 72 pixels per inch, and its overall image quality is relatively low. WTW contains

Table 4: Characteristics of selected table recognition datasets.

Dataset	Tables	Source	Markup Sequence Annotations	Textual Annotations	Year
SciTSR	15K	ArXiv	\times		2019
PubTabNet	568K	PubMed			2020
WTW	14.6K	Wild Scenarios	×	×	2021

images collected from the wild, introducing a variety of extreme cases, such as tilt, blur, and table curvature, which significantly increase the task's difficulty. These datasets encompass diverse table types as well as various unique visual challenges, providing a robust foundation for benchmarking in this study.

5.1.2 Baselines. We select six Vision Large Language Models (VLLMs), including Phi, Llama, GPT-mini, Qwen, GPT, and Gemini, as baseline models for comparison. These models' selection and implementation details are described in appendix [D.](#page-11-0) Additionally, we select three representative deep learning-based methods as baselines for comparison: EDD [\[38\]](#page-8-30) based on sequence modeling, LGPMA [\[34\]](#page-8-26) based on cell bounding box detection, and LORE [\[35\]](#page-8-27) based on cell point center detection.

5.1.3 Evaluation Metrics. As for the evaluation metrics of TR, we use a similarity metric based on Tree-Edit Distance (TEDS) [\[38\]](#page-8-30) and the structure-aware TEDS-Struct metric. The specific details of TEDS can be found in the appendix [E.](#page-11-1) We employ two evaluation metrics for the hierarchical tasks described in Section [3.2.1:](#page-1-0) accuracy (ACC) and micro-averaged F1 score (F1-score). Specifically, ACC is used to evaluate cell-level tasks (excluding merged cell detection) and table-level tasks; the F1-score is utilized for row- and columnlevel tasks and merged cell detection.

5.1.4 Implementation Details. For the PubTabNet dataset, since the test set labels are not public, we choose to use the validation set for evaluation. We randomly select 1,500 images from the validation set of PubTabNet as research samples. The experimental results show that the EDD and LGPMA baseline model's performance on this sample is consistent with its initial reported results, which shows that our sampling is well-representative. For the SciTSR and WTW datasets, we use their complete test sets for evaluation. Since the WTW dataset does not provide content information for table recognition, we do not report its TEDS scores.

For LORE, since it is mainly aimed at table structure recognition but not table content recognition, we only report its performance scores for table structure recognition. As for EDD, since its model training requires a large amount of end-to-end annotated data, and SciTSR and WTW lack corresponding labeled data, its performance on these datasets has not been evaluated. For LGPMA, since the model relies on table content for training and the WTW dataset does not provide table content labels, we did not evaluate its performance on the WTW dataset.

5.2 Main Results Analysis

Tables [5](#page-6-0) show our benchmark results on the table recognition and table structure recognition tasks. Based on the experimental results, we draw the following insights:

5.2.1 Performance Analysis of NGTR. As shown in Table [5,](#page-6-0) the experimental results compare our NGTR framework with baseline

Table 5: Performance comparison of methods on the SciTSR, PubTabNet, and WTW datasets. "-" indicates the method's lack of results (specific reasons are provided in the implementation details). Best scores in the lightweight OCR model category are highlighted in blue, while best scores in the prompt tuning in VLLMs category are highlighted in green.

methods. We use GPT and Gemini, which performs well in benchmark tests, as the framework backbone. The main results show that our framework achieves significant performance improvements on the PubTabNet dataset, mainly attributed to our framework's enhanced VLLMs robustness when dealing with low-quality inputs. On the SciTSR dataset, our framework also outperforms all VLLMs baselines, further verifying our framework's effectiveness.

In the WTW dataset, our method and all VLLM-based baselines demonstrate suboptimal performance compared to traditional lightweight baseline methods. However, despite these challenges, our approach significantly enhances the effectiveness of VLLMs, suggesting that our framework imparts a degree of robustness to VLLMs in complex environments. Nevertheless, it highlights persistent challenges that remain difficult to address in VLLMs. Section [5.2.4](#page-6-1) presents a more detailed analysis of VLLMs performance on the WTW dataset.

5.2.2 Open-source and Proprietary VLLMs. The advanced opensource VLLMs demonstrate capabilities comparable to proprietary VLLMs in this task. As a representative of open-source VLLMs, Llama exhibits outstanding performance, particularly in the table structure evaluation task (TEDS-Struct) on the PubTabNet dataset. Llama achieves a relatively better result, surpassing GPT by 2.73 points and Gemini by 2.36 points. These results confirm the exceptional performance of Llama but also underscore the potential of open-source VLLMs for further research.

5.2.3 Model Scale. We observe that lightweight VLLMs face significant performance limitations in specific tasks. For instance, Phi, a lightweight VLLM with a parameter size of 4.2B, demonstrates consistently low performance across all evaluations. While another lightweight VLLM, GPT-mini, achieves commendable results on the simpler SciTSR dataset, its performance declined significantly on the more challenging PubTabNet dataset, dropping 33% and 21% in TEDS and TEDS-Struct metrics, respectively.

We attribute this phenomenon to two key factors. First, the TR task requires VLLMs to possess fine-grained detection capabilities and the ability to accurately recognize and extract structured information—a difficult challenge. Due to their relatively small parameter sizes and limited computational power, lightweight VLLMs struggle to achieve the required recognition accuracy and input robustness. Second, the TR task demands the generation of accurate markup sequence representations of tables, imposing stringent requirements on the VLLMs' generation capabilities. We observe

that lightweight VLLMs often fail to produce parsable markup sequences after multiple attempts, mainly when tasked with complex scenarios such as large, intricate tables or ambiguous image inputs. This limitation significantly reduces their final performance scores, a phenomenon not observed in larger-scale VLLMs.

5.2.4 WTW Dataset: A Challenge for VLLMs. Table [5](#page-6-0) presents the experimental results on the WTW dataset. These results indicate that prompt tuning based VLLMs methods still exhibit significant gaps compared to traditional lightweight OCR methods, highlighting the challenges VLLMs face when processing datasets with wild scenarios. An in-depth analysis of the experimental findings reveals that the WTW dataset primarily emphasizes table structure information. Performance declines notably when processing tables with numerous empty cells, unevenly distributed text, skewed, rotated, or densely packed text. Further analysis of the outputs suggests that VLLMs tend to ignore cells lacking semantic content. While this behavior helps avoid processing irrelevant data, it also limits their ability to effectively capture the structural information of tables with many blank cells.

In conjunction with the analysis of table borders in Section [3.4,](#page-3-0) we speculate that VLLMs primarily rely on cell content and its logical position in the image when completing the table recognition task, with relatively limited use of table border information. This dependence restricts the performance of VLLMs in recognizing complex table structures to some extent.

Table 6: Ablation study results on key components of the proposed framework. "EXP" denotes the tool invocation experience learning module, while "REF" represents the reflectiondriven tool selection module.

5.3 Ablation Study w.r.t Key Components

The results of our ablation experiments on the NGTR framework are shown in Table [6.](#page-6-2) We randomly select 1,000 images from the SciTSR dataset for ablation studies. We ablate two key components:

(right) on performance.

tool invocation experience learning and reflection-driven tool selection module. Note that we do not ablate the toolkit, as it is the foundational module of our framework and cannot be removed. The results highlight the critical contributions of these components to the overall performance of the NGTR framework.

Effectiveness of Tool Invocation Experience Learning. To evaluate the effectiveness of VLLMs in optimizing toolchains using neighbor samples, we performed an ablation study by removing the tool invocation experience learning module. In this experiment, we only prompted VLLMs to generate a tool invocation plan and applied it directly to the test samples. Without the tool invocation experience learning module, the experimental results showed that while the VLLMs was able to generate a valid tool invocation plan, the lack of effective validation of the generated plan led to a significant performance decline. This further validates the critical role of the tool invocation experience learning module in improving the NGTR framework performance.

Effectiveness of Reflection-driven Tool Selection. To evaluate the effectiveness of introducing the reflection-driven tool selection module for stepwise backtracking validation in the final execution stage, we ablate this module. We apply all the tools in the toolchain to the task images in a single pass, using them as input for the generation stage. Experimental results show that, without the reflection module for stepwise backtracking validation, VLLMs cannot effectively supervise the processing procedure, which may lead to the incorporation of unsuitable tools for the current sample, thereby affecting performance. This performance drop is mainly reflected in the reduction of the TEDS indicator, which may be due to the loss of text details caused by the incorrect noise reduction and binarization application.

5.4 Tool Invocation Analysis

To further investigate the NGTR framework's preferences in tool invocation, we calculated the tool usage rates for each test dataset (i.e., the proportion of samples that invoke a particular tool among all samples where tools are invoked). The results are presented in Table [7.](#page-7-0) As shown, there are notable differences in the frequency of tool usage rates across different datasets.

On the PubTabNet dataset, the NGTR framework exhibits a marked preference for the image upscaling tool. This preference is consistent with this dataset's overall lower image quality characteristic, as improving image resolution can better support subsequent table recognition tasks. For the SciTSR and WTW datasets, the border enhancement tool is invoked more frequently. These two datasets primarily feature tables with complete borders, and enhancing border features enables VLLM to recognize the table structure information more accurately. Moreover, the detection

PORT AND REAL PROPERTY OF A SUBSEX 2015 IN PROPERTY ISSUED ASSESSED ASSESSED. The marking the dataset where each tool is most frequently used. $\begin{array}{c|c} \text{\#} & \text{\#} \end{array}$ the percentage of samples using each tool, with bold values **100 TEDS TEDS-STRAGE TABLE 7: Tool invocation preference analysis. Values show**

Binarization	Noise Reduction	Detection and Cropping
4.40	15.64	64.39
3.70	20.64	54.23
6.65	15.46	82.93

and cropping tool has the highest invocation rate on the WTW dataset, which aligns with the dataset's characteristics in the wild scenarios. In such images, tables often occupy only a portion of the frame or appear displaced, making this tool effective in locating and extracting the target areas. In summary, the experimental results demonstrate that the NGTR framework adaptively selects appropriate image processing tools based on the characteristics of different datasets, thereby fully showcasing its flexible planning capabilities in cross-dataset scenarios.

5.5 Hyperparameter Sensitivity Analysis

The NGTR framework contains two core parameters: the maximum length of the toolchain execution plan L and the number of plans generated each time N . Based on GPT, Experimental results on the SciTSR dataset are presented in Figures [6.](#page-7-1)

Our experimental results indicate that a moderate toolchain length achieves an adequate balance between complexity and performance, as excessive toolchain length increases combinatorial complexity and limits processing performance, thereby affecting the framework's ability to generate high-quality solutions. Similarly, generating a moderate number of execution plans effectively balances solution quality and generation efficiency, whereas generating too few or too many plans slightly reduces performance. Therefore, a moderate toolchain length and number of execution plans can balance complexity and performance well, providing valuable guidance for the tool invocation.

6 Conclusion and Limitation

This paper addressed the under-explored challenge of table recognition using VLLMs in a training-free reasoning paradigm. We proposed the NGTR framework, which enhanced input image quality through lightweight models and neighbor-guided tool invocation strategies. Extensive experiments demonstrated that NGTR significantly improved VLLM-based table recognition performance, addressing critical bottlenecks such as low-quality input images. This work not only established a benchmark for table recognition but also highlighted the potential of VLLMs in advancing table understanding, paving the way for future research and applications.

Despite the strengths of our framework, we acknowledge several limitations that warrant further investigation. Firstly, its performance depends on the underlying toolkit. Secondly, when the available set of neighbor candidates does not sufficiently cover a wide range of scenarios, selecting inappropriate neighbors may lead to suboptimal performance. Nevertheless, we believe the NGTR framework demonstrates strong generalizability, serving as a versatile approach for tool invocation for various domains.

Enhancing Table Recognition with Vision LLMs:

A Benchmark and Neighbor-Guided Toolchain Reasoner Conference acronym 'XX, June 03-05, 2018, Woodstock, NY

References

- [1] Shuo Zhang and Krisztian Balog. Web table extraction, retrieval, and augmentation: A survey. ACM Transactions on Intelligent Systems and Technology (TIST), 11(2):1–35, 2020.
- [2] Xinyi Zheng, Douglas Burdick, Lucian Popa, Xu Zhong, and Nancy Xin Ru Wang. Global table extractor (gte): A framework for joint table identification and cell structure recognition using visual context. In Proceedings of the IEEE/CVF winter conference on applications of computer vision, pages 697–706, 2021.
- [3] Ravid Shwartz-Ziv and Amitai Armon. Tabular data: Deep learning is not all you need. Information Fusion, 81:84–90, 2022.
- [4] Jiahao Wang, Mingyue Cheng, Qingyang Mao, Qi Liu, Feiyang Xu, Xin Li, and Enhong Chen. Tabletime: Reformulating time series classification as zero-shot table understanding via large language models. arXiv preprint arXiv:2411.15737, 2024.
- [5] Richard Zanibbi, Dorothea Blostein, and James R Cordy. A survey of table recognition: Models, observations, transformations, and inferences. Document Analysis and Recognition, 7:1–16, 2004.
- [6] Mahmoud Salaheldin Kasem, Abdelrahman Abdallah, Alexander Berendeyev, Ebrahem Elkady, Mohamed Mahmoud, Mahmoud Abdalla, Mohamed Hamada, Sebastiano Vascon, Daniyar Nurseitov, and Islam Taj-Eddin. Deep learning for table detection and structure recognition: A survey. ACM Computing Surveys, 56(12):1–41, 2024.
- [7] Yupeng Chang, Xu Wang, Jindong Wang, Yuan Wu, Linyi Yang, Kaijie Zhu, Hao Chen, Xiaoyuan Yi, Cunxiang Wang, Yidong Wang, et al. A survey on evaluation of large language models. ACM Transactions on Intelligent Systems and Technology, $15(3):1-45$, 2024.
- [8] Shukang Yin, Chaoyou Fu, Sirui Zhao, Ke Li, Xing Sun, Tong Xu, and Enhong Chen. A survey on multimodal large language models. National Science Review, page nwae403, 2024.
- [9] Tianyu Liu, Kexiang Wang, Lei Sha, Baobao Chang, and Zhifang Sui. Table-totext generation by structure-aware seq2seq learning. In Proceedings of the AAAI conference on artificial intelligence, volume 32, 2018.
- [10] Zhoujun Cheng, Haoyu Dong, Zhiruo Wang, Ran Jia, Jiaqi Guo, Yan Gao, Shi Han, Jian-Guang Lou, and Dongmei Zhang. Hitab: A hierarchical table dataset for question answering and natural language generation. arXiv preprint arXiv:2108.06712, 2021.
- [11] Zhixin Guo, Mingxuan Yan, Jiexing Qi, Jianping Zhou, Ziwei He, Guanjie Zheng, Xinbing Wang, and Chenghu Zhou. Adapting knowledge for few-shot tableto-text generation. IEEE/ACM Transactions on Audio, Speech, and Language Processing, 2024.
- [12] Zilong Wang, Hao Zhang, Chun-Liang Li, Julian Martin Eisenschlos, Vincent Perot, Zifeng Wang, Lesly Miculicich, Yasuhisa Fujii, Jingbo Shang, Chen-Yu Lee, et al. Chain-of-table: Evolving tables in the reasoning chain for table understanding. arXiv preprint arXiv:2401.04398, 2024.
- [13] Dawei Gao, Haibin Wang, Yaliang Li, Xiuyu Sun, Yichen Qian, Bolin Ding, and Jingren Zhou. Text-to-sql empowered by large language models: A benchmark evaluation. arXiv preprint arXiv:2308.15363, 2023.
- [14] Qingyang Mao, Qi Liu, Zhi Li, Mingyue Cheng, Zheng Zhang, and Rui Li. Potable: Programming standardly on table-based reasoning like a human analyst. arXiv preprint arXiv:2412.04272, 2024.
- [15] Xiang Deng, Huan Sun, Alyssa Lees, You Wu, and Cong Yu. Turl: Table understanding through representation learning. ACM SIGMOD Record, 51(1):33–40, 2022.
- [16] Benjamin Feuer, Yurong Liu, Chinmay Hegde, and Juliana Freire. Archetype: A novel framework for open-source column type annotation using large language models. arXiv preprint arXiv:2310.18208, 2023.
- [17] Mohamed Trabelsi, Jin Cao, and Jeff Heflin. Semantic labeling using a deep contextualized language model. arXiv preprint arXiv:2010.16037, 2020.
- [18] Mingyu Zheng, Xinwei Feng, Qingyi Si, Qiaoqiao She, Zheng Lin, Wenbin Jiang, and Weiping Wang. Multimodal table understanding, 2024.
- [19] Anwen Hu, Haiyang Xu, Jiabo Ye, Ming Yan, Liang Zhang, Bo Zhang, Chen Li, Ji Zhang, Qin Jin, Fei Huang, et al. mplug-docowl 1.5: Unified structure learning for ocr-free document understanding. arXiv preprint arXiv:2403.12895, 2024.
- [20] Leiyuan Chen, Chengsong Huang, Xiaoqing Zheng, Jinshu Lin, and Xuan-Jing Huang. Tablevlm: Multi-modal pre-training for table structure recognition. In Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 2437–2449, 2023.
- [21] Yiming Zhang, Yaping Zhang, Lu Xiang, and Yu Zhou. Multi-modal attention based on 2d structured sequence for table recognition. In Chinese Conference on Pattern Recognition and Computer Vision (PRCV), pages 378–391. Springer, 2024.
- [22] Yuan Sui, Mengyu Zhou, Mingjie Zhou, Shi Han, and Dongmei Zhang. Table meets llm: Can large language models understand structured table data? a benchmark and empirical study. In Proceedings of the 17th ACM International Conference on Web Search and Data Mining, pages 645–654, 2024.
- [23] Mingyue Cheng, Qi Liu, Zhiding Liu, Zhi Li, Yucong Luo, and Enhong Chen. Formertime: Hierarchical multi-scale representations for multivariate time series classification. In Proceedings of the ACM Web Conference 2023, pages 1437–1445,

2023.

- [24] Zhiding Liu, Jiqian Yang, Mingyue Cheng, Yucong Luo, and Zhi Li. Generative pretrained hierarchical transformer for time series forecasting. In Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining, pages 2003–2013, 2024.
- [25] Katsuhiko Itonori. Table structure recognition based on textblock arrangement and ruled line position. In Proceedings of 2nd International Conference on Document Analysis and Recognition (ICDAR'93), pages 765–768. IEEE, 1993.
- [26] Thomas Kieninger and Andreas Dengel. The t-recs table recognition and analysis system. In Document Analysis Systems: Theory and Practice: Third IAPR Workshop, DAS'98 Nagano, Japan, November 4–6, 1998 Selected Papers 3, pages 255–270. Springer, 1999.
- [27] Alexey Shigarov, Andrey Mikhailov, and Andrey Altaev. Configurable table structure recognition in untagged pdf documents. In Proceedings of the 2016 ACM symposium on document engineering, pages 119–122, 2016.
- [28] Hwee Tou Ng, Chung Yong Lim, and Jessica Li Teng Koo. Learning to recognize tables in free text. In Proceedings of the 37th Annual Meeting of the Association for Computational Linguistics, pages 443–450, 1999.
- [29] Yalin Wang, Ihsin T Phillips, and Robert M Haralick. Table structure understanding and its performance evaluation. Pattern recognition, 37(7):1479–1497, 2004.
- [30] Sebastian Schreiber, Stefan Agne, Ivo Wolf, Andreas Dengel, and Sheraz Ahmed. Deepdesrt: Deep learning for detection and structure recognition of tables in document images. In 2017 14th IAPR international conference on document analysis and recognition (ICDAR), volume 1, pages 1162–1167. IEEE, 2017.
- [31] Shoaib Ahmed Siddiqui, Imran Ali Fateh, Syed Tahseen Raza Rizvi, Andreas Dengel, and Sheraz Ahmed. Deeptabstr: Deep learning based table structure recognition. In 2019 international conference on document analysis and recognition (ICDAR), pages 1403–1409. IEEE, 2019.
- [32] Chixiang Ma, Weihong Lin, Lei Sun, and Qiang Huo. Robust table detection and structure recognition from heterogeneous document images. Pattern Recognition, 133:109006, 2023.
- [33] Chunxia Qin, Zhenrong Zhang, Pengfei Hu, Chenyu Liu, Jiefeng Ma, and Jun Du. Semv3: A fast and robust approach to table separation line detection. \emph{arXiv} preprint arXiv:2405.11862, 2024.
- [34] Liang Qiao, Zaisheng Li, Zhanzhan Cheng, Peng Zhang, Shiliang Pu, Yi Niu, Wenqi Ren, Wenming Tan, and Fei Wu. Lgpma: Complicated table structure recognition with local and global pyramid mask alignment. In International conference on document analysis and recognition, pages 99–114. Springer, 2021.
- [35] Hangdi Xing, Feiyu Gao, Rujiao Long, Jiajun Bu, Qi Zheng, Liangcheng Li, Cong Yao, and Zhi Yu. Lore: logical location regression network for table structure recognition. In Proceedings of the AAAI Conference on Artificial Intelligence, volume 37, pages 2992–3000, 2023.
- [36] Shaoqing Ren, Kaiming He, Ross Girshick, and Jian Sun. Faster r-cnn: Towards real-time object detection with region proposal networks. IEEE transactions on pattern analysis and machine intelligence, 39(6):1137–1149, 2016.
- [37] Nicolas Carion, Francisco Massa, Gabriel Synnaeve, Nicolas Usunier, Alexander Kirillov, and Sergey Zagoruyko. End-to-end object detection with transformers. In European conference on computer vision, pages 213–229. Springer, 2020.
- [38] Xu Zhong, Elaheh ShafieiBavani, and Antonio Jimeno Yepes. Image-based table recognition: data, model, and evaluation. In European conference on computer vision, pages 564–580. Springer, 2020.
- [39] Devashish Prasad, Ayan Gadpal, Kshitij Kapadni, Manish Visave, and Kavita Sultanpure. Cascadetabnet: An approach for end to end table detection and structure recognition from image-based documents. In Proceedings of the IEEE/CVF conference on computer vision and pattern recognition workshops, pages 572–573, 2020.
- [40] Ahmed Nassar, Nikolaos Livathinos, Maksym Lysak, and Peter Staar. Tableformer: Table structure understanding with transformers. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 4614–4623, 2022.
- [41] Yongshuai Huang, Ning Lu, Dapeng Chen, Yibo Li, Zecheng Xie, Shenggao Zhu, Liangcai Gao, and Wei Peng. Improving table structure recognition with visual-alignment sequential coordinate modeling. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 11134–11143, 2023.
- [42] Jianqiang Wan, Sibo Song, Wenwen Yu, Yuliang Liu, Wenqing Cheng, Fei Huang, Xiang Bai, Cong Yao, and Zhibo Yang. Omniparser: A unified framework for text spotting key information extraction and table recognition. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 15641–15653, 2024.
- [43] Alec Radford. Improving language understanding by generative pre-training. 2018.
- [44] Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and efficient foundation language models. arXiv preprint arXiv:2302.13971, 2023.
- [45] Shijie Chen, Yu Zhang, and Qiang Yang. Multi-task learning in natural language processing: An overview. ACM Computing Surveys, 56(12):1–32, 2024.
- [46] Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. Large language models are zero-shot reasoners. Advances in neural information processing systems, 35:22199–22213, 2022.
- [47] Junyi Li, Tianyi Tang, Wayne Xin Zhao, Jian-Yun Nie, and Ji-Rong Wen. Pretrained language models for text generation: A survey. ACM Computing Surveys, 56(9):1–39, 2024.
- [48] Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. Chain-of-thought prompting elicits reasoning in large language models. Advances in neural information processing systems , 35:24824–24837, 2022.
- [49] Mingyue Cheng, Yiheng Chen, Qi Liu, Zhiding Liu, and Yucong Luo. Advancing time series classification with multimodal language modeling. arXiv preprint arXiv:2403.12371, 2024.
- [50] Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. Advances in Neural Information Processing Systems, 36, 2024.
- [51] Lin Guan, Karthik Valmeekam, Sarath Sreedharan, and Subbarao Kambhampati. Leveraging pre-trained large language models to construct and utilize world models for model-based task planning. Advances in Neural Information Processing Systems, 36:79081–79094, 2023.
- [52] Zhibin Gou, Zhihong Shao, Yeyun Gong, Yelong Shen, Yujiu Yang, Nan Duan, and Weizhu Chen. Critic: Large language models can self-correct with tool-interactive critiquing. arXiv preprint arXiv:2305.11738, 2023.
- [53] Kai Wang, Boris Babenko, and Serge Belongie. End-to-end scene text recognition. In 2011 International conference on computer vision, pages 1457–1464. IEEE, 2011.
- [54] Stanislaw Antol, Aishwarya Agrawal, Jiasen Lu, Margaret Mitchell, Dhruv Batra, C Lawrence Zitnick, and Devi Parikh. Vqa: Visual question answering. In Proceedings of the IEEE international conference on computer vision, pages 2425– 2433, 2015.
- [55] Jiaxian Guo, Junnan Li, Dongxu Li, Anthony Meng Huat Tiong, Boyang Li, Dacheng Tao, and Steven Hoi. From images to textual prompts: Zero-shot visual question answering with frozen large language models. In Proceedings of the IEEE/CVF conference on computer vision and pattern recognition, pages 10867– 10877, 2023.
- [56] Jiabo Ye, Anwen Hu, Haiyang Xu, Qinghao Ye, Ming Yan, Guohai Xu, Chenliang Li, Junfeng Tian, Qi Qian, Ji Zhang, et al. Ureader: Universal ocr-free visuallysituated language understanding with multimodal large language model. In Findings of the Association for Computational Linguistics: EMNLP 2023, pages 2841–2858, 2023.
- [57] Yuliang Liu, Biao Yang, Qiang Liu, Zhang Li, Zhiyin Ma, Shuo Zhang, and Xiang Bai. Textmonkey: An ocr-free large multimodal model for understanding document. arXiv preprint arXiv:2403.04473, 2024.
- [58] Weichao Zhao, Hao Feng, Qi Liu, Jingqun Tang, Shu Wei, Binghong Wu, Lei Liao, Yongjie Ye, Hao Liu, Wengang Zhou, et al. Tabpedia: Towards comprehensive visual table understanding with concept synergy. arXiv preprint arXiv:2406.01326, 2024.
- [59] Zewen Chi, Heyan Huang, Heng-Da Xu, Houjin Yu, Wanxuan Yin, and Xian-Ling Mao. Complicated table structure recognition. arXiv preprint arXiv:1908.04729, 2019.
- [60] Rujiao Long, Wen Wang, Nan Xue, Feiyu Gao, Zhibo Yang, Yongpan Wang, and Gui-Song Xia. Parsing table structures in the wild. In Proceedings of the IEEE/CVF International Conference on Computer Vision, pages 944–952, 2021.

Appendix

A Logical to Markup Sequence Conversion

Since the baseline methods (including LORE and LGPMA) output logical structures representing cell information, they cannot be directly used for the calculation of TEDS metrics. To address this, we use the following pseudocode to convert the logical structure into markup sequence format.

We divide the entire conversion process into two stages. In the first stage, we perform a preliminary preprocessing of the logical location information, associating the logical positions with the corresponding cell content and storing them in a tabular data matrix. The detailed implementation is shown in Algorithm [1.](#page-10-0)

In the second stage, we traverse the tabular data matrix row by row, gradually converting the stored logical information and cell content into a markup sequence, ultimately generating the output. The specific implementation is detailed in Algorithm [2.](#page-10-1)

B Study of Table Size

In this section, we analyze the scale of the tables involved in the benchmark evaluations. We quantify the size of tables in the SciTSR and PubTabNet datasets by counting the number of cells in each table. Furthermore, this section presents experiments designed to evaluate the impact of table size on table recognition performance. GPT is selected as a representative of VLLMs for these experiments, with the distribution details and experimental results illustrated in Figure [7.](#page-10-2) In small scale tables, the model demonstrates stable performance on both the SciTSR and PubTabNet datasets. However, as the table size increased, the model's performance experienced a moderate decline. This indicates that larger tables introduce longer context lengths, thereby affecting the VLLMs' TR task performance.

Figure 7: Table size distribution and its impact on TR performance in SciTSR (left) and PubTabNet (right) Datasets

Specifically, statistical analysis shows that all tables involved in the experiments do not exceed the VLLMs' context window after being encoded into markup sequence. The largest table occupies only 10K tokens of context when encoded as an markup sequence, while all VLLMs possess context windows of at least 128K tokens. However, it is important to note that generating well formed markup sequence poses certain challenges to the model's capabilities. Therefore, when tables are huge and have complex structures, some VLLMs with weaker generative abilities may encounter issues generating parseable markup sequence results, even though the 128K context window is not exceeded.

C Case Study

Figure [8](#page-11-2) presents a case study that showcases evaluation samples from the PubTabNet dataset and analyzes the table recognition results using the traditional OCR models LORE and VLLM. The input table image lacks clear row borders, making it challenging for traditional OCR models to locate specific cells accurately. However, VLLM effectively comprehends the hierarchical structure of the table, thereby producing correct recognition results. This case highlights the advantages of VLLM in semantically rich table recognition tasks, demonstrating its superior adaptability and robustness compared to traditional OCR models.

However, relying on the understanding of the table's hierarchical structure to perform table recognition tasks can also have negative consequences in certain scenarios. As illustrated in Figure [9,](#page-11-3) we analyzed the results of using VLLM for table recognition on evaluation samples from the SCITSR dataset. The results indicate that the output of VLLM in table recognition significantly deviates from the correct answers, particularly in the placement of the "Linear" and "Kernel" cells in the table. Specifically, VLLM tends to misidentify "Linear" and "Kernel" as belonging to the first row of the table, treating them as subheaders, even though these cells are located in the table's upper-left corner. This phenomenon may stem from Conference acronym 'XX, June 03–05, 2018, Woodstock, NY Zhou et al. 2018, 2018, 2018, 2018, 2020

Figure 8: A case study is conducted using an evaluation sample from PubTabNet

									Image Input
LINEAR	PCA		$LPP*$	DNE	LFDA	SELF		SS-DNE	SS-LFDA
Lavornupp	$72.8{\pm}.6$		$83.7{\pm}.6$	$77.9{\pm}.7$	74 ± 1.0	$77.8{\pm}.5$		$84.5 \pm .6^{80}$	$84.9{\pm}.4^{95}$
BALANCE	$57 + 2.2$		$80 + 1.3$	$86.4{\pm}.5$	$87.9 \pm .3$	$87.2 \pm .4$		$88.2{\pm}.5^{99}$	$86.3{\pm}.6$
BCI	$49.5{\pm}.5$		$54.9{\pm}.5$	$53.1{\pm}.7$	$67.9 + .5$	$67.6 + .6$		$63.1{\pm}.5^{99}$	$67.5{\pm}.6$
USPS	$91.4 \pm .3$		$75.7{\pm}.3$	$91.1 \pm .3$	$89.3 \pm .4$	$92.2 \pm .3$		$92.2 \pm .4^{95}$	$91.6{\pm}.3$
M-EYALE	$69.4{\pm}.4$		$84.1{\pm}.4$	$92.3{\pm}.4$	$95.4 \pm .3$	$94.3{\pm}.2$		$93.5{\pm}.4^{95}$	$95.7 + .2$
KERNEL	\overline{PCA}		$LPP*$	DNE	LFDA	SELF		SS-DNE	SS-LFDA
LONOSPHERE	$79.8{\pm}.4$		$89.7{\pm}.5$	$78.7{\pm}.9$	$81.3{\pm}.7$	$81.1 \pm .5$		$93.6{\pm}.2^{99}$	$93.7 \pm .3^{99}$
BALANCE	$42.5 \pm .3$		$46.9{\pm}.5$	$84.0{\pm}.7$	$87.8{\pm}.7$	$79 + 1.6$		$86.5{\pm}.7^{99}$	$87.7{\pm}.9$
BCI	$49.7{\pm}.5$		$54.5 \pm .4$	$51.6{\pm}.6$	$51.0 + .8$	$52.4 \pm .6$		$57.6{\pm}.2^{99}$	$57.0 \pm .4^{99}$
USPS	$91.1 \pm .3$		$81.5 \pm .6$	$91.4 \pm .4$	$91.2 \pm .4$	$92.7 + .3$		$92.3{\pm}.3^{95}$	$91.9{\pm}.3$
M-EYALE	$66.3{\pm}.3$		$81.9{\pm}.5$	$91.2 \pm .3$	$89.1 \pm .5$	$85.8 \pm .6$		$91.2{\pm}.3$	$94.3{\pm}.3^{99}$
									VLLM Output
				Linear					
	Dataset	PCA	$LPP*$	DNE	LFDA	SELF		SS-DNE SS-LFDA	
	tonosphere 7 2.8±6 83.7±6			77.7 ± 7				$74\pm1.077.8\pm584.5\pm68084.9\pm495$	
	Balance		$57 \pm 2.280 \pm 1.3$	86.4 ± 5			$ 87.9 \pm 3 87.2 \pm 4 88.2 \pm 5 99 $	86.3 ± 6	
	BCI		$49.5 \pm 5.54.9 \pm 5$	53.1 ± 7			$67.9 \pm 567.6 \pm 763.1 \pm 599$	67.3 ± 5	
	Usps	$69.4 \pm 3.84.1 \pm 4$	$91.4 \pm 3.75.7 \pm 3$	91.3 ± 4			$92.1 \pm 592.3 \pm 292.2 \pm 495$	91.3 ± 2 95.7 ± 2	
	M-Eyale			Kernel			92.3±4 95.4±3 94.3±2 93.5±4 ⁹⁵		
	Dataset	PCA	LPP*	DNE	LFDA	SELF		SS-DNE SS-LFDA	
	tonosphere 7 9.8±4 89.7±2			$78.7 + 9$				$81.3 \pm 781.1 \pm 593.6 \pm 29993.7 \pm 139$	
	Balance	$42.5 \pm 3 \times 46.9 \pm 2$		65.8 ± 7			87.0±879±1.686.5±799	87.7 ± 2	
	BCI		$49.7 \pm 5.54.5 \pm 4$	$51.0 + 8$				67.9±552.4±857.6±2 ⁹⁹ 57.0±4 ⁹⁹	
	Usps						91.1±381.5±6 91.2±3 92.7±392.7±392.3±3 ⁹⁵ 91.9±4		

Figure 9: A case study is conducted using an evaluation sample from SciTSR

VLLMs' excessive reliance on contextual cues, causing the model to be misled by its own reasoning or interpretation mechanisms when encountering atypical table structures, thereby resulting in erroneous hierarchical structural information recognition results.

D Parameter Settings of VLLMs

We report the parameter settings of six VLLMs. For open-source VLLMs, we select Phi-3.5-Vision-Instruct 2 2 (Phi) and Llama-3.2-90B-Vision-Instruct^{[3](#page-11-5)} (Llama) for evaluation. For closed-source VLLMs, we evaluate GPT-[4](#page-11-6)0-mini⁴ (GPT-mini), Qwen-VL-Max^{[5](#page-11-7)} (Qwen), GPT-40 6 6 (GPT) and Gemini-1.5-Pro 7 7 (Gemini). Specifically, when generating multiple tool invocation plans, we set the temperature parameter to 0.8 to encourage the generation of more diverse tool invocation plans. For other experiments, the temperature parameter was kept at 0 to ensure the stability of the experimental results. Additionally, the top p parameter was set to 0.2, and the n_samples parameter was set to 1.

E Details of TEDS Metric

TEDS is designed to measure the similarity between two tree structures. Specifically, TEDS is used to calculate the similarity between the HTML tree of the real tag and the HTML tree of the predicted tag. When applying the TEDS metric, the HTML table format must first be converted into a tree structure. The similarity is then calculated using the following formula:

$$
TEDS(T_a, T_b) = 1 - \frac{\text{EditDist}(T_a, T_b)}{\max(|T_a|, |T_b|)},
$$
\n(6)

where T_a and T_b represent the tree structures of the tables in HTML format. Edit $\mathrm{Dist}(T_a,T_b)$ denotes the tree-edit distance, and $|T|$ refers to the number of nodes in tree T . Additionally, we adopted a modified version of TEDS, referred to as TEDS-Struct. TEDS-Struct is designed to assess the accuracy of table structure recognition without considering the specific results generated by the table content.

Prompt 10: Simplified prompt template for VLLMs on table recognition tasks.

F Implementation Details of Benchmark

We present two prompt templates designed to guide VLLM in generating markup sequence outputs for TR tasks in Figures [10](#page-11-10) and [11.](#page-12-0) Prompt 1 is a simplified template that facilitates the execution of TR tasks by VLLM. In contrast, Prompt 2 introduces the concept of Chain-of-Thought by explicitly planning the table recognition process for VLLM. In our experiments, the more complex Prompt 2 achieved a slight improvement in TR tasks performance. However, since our benchmark evaluation aims to reflect VLLM's recognition capabilities more directly, we employ Prompt 1 as the prompt template in all experiments.

 2 <https://azure.microsoft.com/en-us/products/phi/>

 3 <https://www.llama.com/> $\,$

 4 <https://openai.com/index/gpt-4o-mini-advancing-cost-efficient-intelligence/>

⁵<https://qwenlm.github.io/blog/qwen-vl/>

⁶<https://openai.com/index/hello-gpt-4o/>

⁷<https://deepmind.google/technologies/gemini/pro/>

Figure 11: Chain-of-Thought prompt template for VLLMs on table recognition tasks.

Figures [12-](#page-12-1)[17](#page-13-1) illustrate the prompt templates designed for our benchmark evaluation of hierarchical evaluation tasks. Each template corresponds to a specific hierarchical task, as detailed below:

- Visual Table Size Detection Task. (Figure [12\)](#page-12-1)
- Merged Cell Detection Task. (Figure [13\)](#page-12-2)
- Content-based Cell Recognition Task. (Figure [14\)](#page-12-3)
- Index-based Cell Recognition Task. (Figure [15\)](#page-12-4)
- Row Index-based Data Recognition Task. (Figure [16\)](#page-13-2)
- Column Index-based Data Recognition Task. (Figure [17\)](#page-13-1)

Figure 12: Prompt template for VLLMs on visual table size detection task.

Figure 13: Prompt template on merged cell detection task.

Answer:

Figure 14: Prompt template for VLLMs on content-based cell recognition task.

Figure 15: Prompt template for VLLMs on index-based cell recognition task.

Conference acronym 'XX, June 03–05, 2018, Woodstock, NY Zhou et al. 2018, 2018, 2018, 2018, 2020

Answer:

Figure 16: Prompt template for VLLMs on row index-based data recognition task.

Answer:

Figure 17: Prompt template for VLLMs on column indexbased data recognition task.

Figure 18: Prompt template for generating multiple tool invocation plans in the NGTR framework

Prompt 4.2 Instruction: You are an expert in identifying information. You will be given two images **Output Format: Answer:** below. Now you need to analyze which of the two image contains more information. {image_1}, {image_2} The first image is the image before processing, and the second image is the image after processing. If you think that the image has not lost any information before and after processing, then choose the second image. ```json { "chain_of_thought": "Your thought process for making this choice.", "choice": 1 or 2 } $\ddot{}$

Figure 19: Prompt template for the reflection-driven tool utilization module in the NGTR framework

G Implementation Details of NGTR

Figure [18](#page-13-3) illustrates the prompt template utilized by our proposed NGTR framework for generating multiple tool invocation plans. By inputting the target image along with its tool descriptions and identifiers, we leverage the planning capabilities of VLLM to produce several tool invocation plans for subsequent modules. This module encompasses two adjustable hyperparameters: the maximum length ${\cal L}$ of the toolchain execution plan and the number N of plans generated per iteration.

Figure [19](#page-13-4) illustrates the prompt template employed by the NGTR framework within the reflection-driven tool utilization module. By inputting both the pre-processed and post-processed images, we could leverage the discriminative capabilities of VLLM to select the image with superior quality. This selection process enables the further optimization of tool invocation strategies, thereby minimizing the loss of image information caused by inappropriate tool usage.