

Efficient Multi-Task Inferencing with a Shared Backbone and Lightweight Task-Specific Adapters for Automatic Scoring

Ehsan Latif

EHSAN.LATIF@UGA.EDU

Xiaoming Zhai*

XIAOMING.ZHAI@UGA.EDU

AI4STEM Education Center, University of Georgia, Athens, GA, 30602

Abstract

The integration of Artificial Intelligence (AI) in education requires scalable and efficient frameworks that balance performance, adaptability, and cost. This paper addresses these needs by proposing a shared backbone model architecture enhanced with lightweight LoRA adapters for task-specific fine-tuning, targeting the automated scoring of student responses across 27 mutually exclusive tasks. By achieving competitive performance (average QWK of 0.848 compared to 0.888 for fully fine-tuned models) while reducing GPU memory consumption by 60% and inference latency by 40%, the framework demonstrates significant efficiency gains. This approach aligns with the workshop's focus on improving language models for educational tasks, creating responsible innovations for cost-sensitive deployment, and supporting educators by streamlining assessment workflows. The findings underscore the potential of scalable AI to enhance learning outcomes while maintaining fairness and transparency in automated scoring systems.

Keywords: Multi-task learning, Efficient inference, LoRA adapters, Automatic Scoring, and Scalability in AI deployment

1. Introduction

The deployment of machine learning models in resource-constrained online learning environments presents significant challenges, especially when addressing problems requiring multiple distinct models. Such scenarios often involve high operational costs and time-intensive deployment processes, as observed in domains such as automated scoring of student responses in education (Latif et al., 2024a; Zhai et al., 2022). In educational contexts, recent advancements in natural language processing (NLP) and large language models (LLMs) like BERT (Devlin et al., 2018) and its domain-specific variants (e.g., SciBERT, G-BERT) have enabled more accurate automated scoring (Liu et al., 2023; Latif et al., 2023). However, these solutions often fail to adequately balance scalability, cost, and domain specificity, necessitating the development of specialized, efficient frameworks.

Preliminary efforts such as G-SciEdBERT (Latif et al., 2024b) demonstrate the efficacy of contextualized LLMs in addressing these limitations for specific use cases like German science education. Despite improvements in scoring accuracy, deploying multiple task-specific models in large-scale applications remains costly and inefficient. Existing research (Zhang et al., 2023) highlights the value of parameter-efficient fine-tuning methods, such as LoRA (Low-Rank Adaptation), which can reduce the computational overhead without compromising performance.

* Corresponding author

This paper proposes a unified framework leveraging pre-trained LLMs with lightweight task-specific components, such as LoRA adapters or classification heads, to address these challenges. The framework focuses on efficiently fine-tuning and deploying a single shared backbone model across multiple distinct tasks. Our approach not only minimizes deployment costs but also enables faster adaptation to new tasks.

Below are the key contribution of the paper:

1. We present a scalable inferencing framework using LoRA adapters and classification heads to efficiently address 27 mutually exclusive tasks while leveraging a single pre-trained model.
2. We demonstrate significant cost savings and reduced deployment times compared to traditional task-specific models.
3. We provide an empirical analysis of our framework’s performance across diverse tasks, highlighting its adaptability and efficiency.

The proposed framework aligns with the goals of resource-efficient AI for education and other cost-sensitive domains, contributing to ongoing advancements in parameter-efficient fine-tuning and automated scoring systems.

2. Proposed Framework

Deploying 27 distinct models for mutually exclusive tasks is both cost- and resource-intensive. To address this, we propose a unified inferencing framework that leverages a single pre-trained backbone model with task-specific lightweight modules, such as Low-Rank Adaptation (LoRA) layers and fine-tuned classification heads. This approach ensures efficient scalability, cost savings, and adaptability across tasks.

The proposed framework consists of three key components:

- **Shared Backbone Model:** A single pre-trained transformer model (G-SciEdBERT (Latif et al., 2024b)) serves as the shared backbone to extract generalizable features from input data.
- **Task-Specific Modules:** Lightweight LoRA adapters (Hu et al., 2023) or fine-tuned classification heads are attached to the shared backbone to specialize in each task.
- **Dynamic Inference Orchestration:** A mechanism to dynamically load task-specific modules during inference, enabling efficient memory utilization.

Instead of fine-tuning the entire backbone model for each task, we adopt LoRA, which updates only a small number of task-specific parameters. LoRA decomposes the parameter update matrix into two low-rank matrices:

$$\Delta W = A \cdot B, \quad \text{where } A \in \mathbb{R}^{d \times r}, B \in \mathbb{R}^{r \times k}. \quad (1)$$

Here, d and k are the dimensions of the original weight matrix W , and r is the rank of the decomposition, typically much smaller than d or k . This reduces the number of trainable parameters while preserving task performance.

The updated weight matrix W' is computed as:

$$W' = W + \Delta W = W + A \cdot B. \quad (2)$$

This approach ensures efficient adaptation to each task while retaining the pre-trained backbone’s knowledge.

Each task T_i is associated with a unique LoRA adapter or classification head, which specializes the shared backbone for task-specific predictions. The task-specific classification head applies a softmax function over the output logits z :

$$P(y|x) = \text{softmax}(z), \quad z = W_h \cdot h + b_h, \quad (3)$$

where h is the output embedding from the backbone model, W_h and b_h are the parameters of the classification head.

During inference, the framework dynamically loads only the required task-specific module, minimizing memory usage and computational overhead. The workflow is as follows:

1. Input x is passed through the shared backbone to extract generalized features h .
2. Based on the task identifier, the corresponding LoRA adapter or classification head is loaded.
3. The task-specific module processes h to generate predictions $P(y|x)$.

This framework offers several advantages including *Scalability*: A single backbone supports multiple tasks, significantly reducing the deployment footprint. *Efficiency*: LoRA adapters minimize memory usage and computational cost during fine-tuning and inference. *Adaptability*: The modular design facilitates rapid adaptation to new tasks by fine-tuning only the task-specific modules, similar to (Latif and Zhai, 2024b,a).

The framework is implemented using the Hugging Face Transformers library (Wolf et al., 2020), leveraging its support for LoRA adapters and task-specific head fine-tuning. Deployment is orchestrated via ONNX Runtime to enable dynamic loading of task-specific modules. This approach ensures low-latency inference across diverse tasks.

The training objective combines the backbone’s pre-trained knowledge with task-specific fine-tuning. For each task T_i , the objective is to minimize the cross-entropy loss:

$$\mathcal{L}_{CE} = - \sum_{j=1}^N \sum_{k=1}^C y_{j,k} \log \hat{y}_{j,k}, \quad (4)$$

where $y_{j,k}$ is the ground-truth probability for class k of instance j , and $\hat{y}_{j,k}$ is the predicted probability.

Regularization is applied to prevent overfitting:

$$\mathcal{L} = \mathcal{L}_{CE} + \lambda \|\Delta W\|_F^2, \quad (5)$$

where λ controls the regularization strength, and $\|\cdot\|_F$ denotes the Frobenius norm.

Our framework will be validated on 27 mutually exclusive tasks, with metrics such as quadratic weighted kappa (QWK) and F1-score used to assess performance improvements over traditional multi-model deployments.

3. Dataset Details

The dataset for this study is derived from the Programme for International Student Assessment (PISA), an international large-scale assessment led by the Organisation for Economic Co-operation and Development (OECD). Specifically, we utilized data from the German PISA 2015 ([Organisation for Economic Co-operation and Development, 2016](#)), which assess scientific literacy among 15-year-old students.

Our analysis focuses on constructed response items, which include both short (approximately one sentence) and extended (up to five sentences) responses. The average response length is 20 words, with scores ranging from 0 to 5. Responses were scored as part of the original PISA iterations, ensuring high-quality human annotations. To ensure fairness, the coding process was designed to be unbiased with respect to student ethnicity, race, or gender.

For this study we used responses to 27 items from PISA 2015 were utilized for fine-tuning task-specific modules. Approximately 1,000 human-scored responses per item were available, facilitating effective adaptation to task-specific requirements. This dataset ensures a robust foundation for training and validating our proposed framework, offering diverse examples of student writing and high-quality scoring annotations.

4. Experimentation

This section outlines the implementation details, experimental setup, and evaluation metrics employed to validate the proposed framework.

4.1. Implementation Details

The framework was implemented using the Hugging Face Transformers library ([Wolf et al., 2020](#)) for model management, fine-tuning, and inference. Pre-training and fine-tuning processes were conducted on an NVIDIA RTX A6000 GPU with 48 GB of memory.

We have pre-trained Backbone Model similar to G-SciEdBERT ([Latif et al., 2024b](#)). The backbone model was initialized using the pre-trained BERT model tailored for the German language (G-BERT ([Chan et al., 2020](#))). A domain-specific corpus of 30,000 German science assessment responses was used for pre-training. Responses were tokenized using the WordPiece tokenizer with a vocabulary size of 30,000 tokens. The masked language modeling (MLM) objective was employed, masking 15% of input tokens for prediction. The model was trained for 10 epochs with a batch size of 32 and a learning rate of 5×10^{-5} , optimized using the Adam optimizer. To ensure robust training, gradient clipping with a maximum norm of 1.0 and learning rate warm-up over the first 10% of training steps were applied.

Fine-tuning was conducted on task-specific LoRA adapters or classification heads for each of the 27 mutually exclusive tasks. LoRA was configured with a rank of 8 and an alpha of 16. Training data for fine-tuning consisted of approximately 1,000 responses per task, split into 80% training, 10% validation, and 10% testing datasets. Cross-entropy loss was minimized during fine-tuning with the same optimizer and hyperparameter settings as pre-training. Each task-specific module was fine-tuned for 5 epochs. Early stopping was implemented based on validation loss, with a patience of 2 epochs.

4.2. Experimental Setup

The evaluation was conducted on the dataset described in Section 3, focusing on the following:

- **Tasks:** Each of the 27 mutually exclusive tasks corresponds to a unique item or set of items from the dataset.
- **Baseline Models:** The framework’s performance was compared against fully fine-tuned G-SciEdBERT models, where separate G-SciEdBERT instances were fine-tuned for each task.
- **Evaluation Metrics:** Quadratic Weighted Kappa (QWK) was used as the primary evaluation metric, as it measures the agreement between human-annotated and model-predicted scores while accounting for chance agreement. Secondary metrics included accuracy, F1-score, and inference latency.

A simulated production environment was set up where requests for predictions were sent to the model framework. Dynamic module loading was tested by sequentially switching between tasks, with adapters or classification heads loaded on demand. Latency measurements were collected, comparing the proposed framework’s dynamic setup against traditional full-model loading approaches.

The pre-trained backbone was frozen during fine-tuning to isolate the effects of task-specific modules. Each task was trained and validated independently to assess the framework’s modularity and scalability. Predictions on the test set were compared with human-annotated scores to compute QWK and secondary metrics. Paired t-tests were conducted to compare QWK scores across tasks between the proposed framework and baseline models. A significance level of $p < 0.05$ was adopted to validate observed improvements.

GPU memory usage and inference latency were logged during both training and inference phases to validate the efficiency of LoRA adapters. The memory footprint of the proposed framework was compared against that of traditional fine-tuned models.

5. Results

The proposed framework was evaluated on 27 mutually exclusive tasks, with performance compared to the baseline models fully fine-tuned for each task. This section presents the evaluation results in terms of accuracy, Quadratic Weighted Kappa (QWK), and inference efficiency.

Table 1 summarizes the Quadratic Weighted Kappa (QWK) scores for selected tasks and the average performance across all 27 tasks. While the fully fine-tuned G-SciEdBERT model achieves slightly higher QWK scores (average: 0.888), the proposed framework maintains competitive accuracy (average: 0.848), with a relative reduction of only 4.5%. For individual tasks, the difference in QWK ranges between 0.01 and 0.03, demonstrating that the proposed framework delivers comparable performance.

Inference Efficiency: The proposed framework demonstrated significant reductions in memory usage and inference latency. The shared backbone reduced GPU memory consumption by approximately 60% compared to loading full models for each task. Task-switching

overhead was minimized to under 50 milliseconds due to dynamic module loading, enabling real-time predictions in practical scenarios.

Although the proposed framework achieves slightly lower QWK scores than the fully fine-tuned G-SciEdBERT models, the trade-offs are justified in scenarios where deployment cost and efficiency are critical. For instance; tasks with fewer labels (e.g., binary classification) exhibit negligible differences in QWK, as shown for tasks S268Q02 and S269Q01. Additionally, tasks with more complex scoring rubrics (e.g., S131Q02) still retain competitive accuracy, with a maximum QWK difference of only 0.03.

Table 1: Performance Comparison Between Fully Fine-Tuned G-SciEdBERT and Proposed Framework on Selected Tasks.

Item	Samples (n)		Labels	Accuracy as QWK	
	Training Samples	Testing Samples		G-SciBERT	Proposed
S131Q02	487	122	5	0.852	0.821
S131Q04	478	120	5	0.825	0.816
S268Q02	446	112	2	0.893	0.874
S269Q01	508	127	2	0.953	0.934
S269Q03	500	126	4	0.802	0.796
Average (27)	598	150	2-5	0.888	0.848

The results highlight the proposed framework’s practical advantages such as comparable accuracy with a slight reduction in QWK (average 4.5% decrease), substantial gains in efficiency, including reduced memory usage, faster inference, and lower deployment costs, and scalability across multiple tasks with minimal resource overhead, enabling real-world applicability in cost-sensitive scenarios.

6. Conclusion

This paper presents a novel inferencing framework for automatic scoring on resource-constrained online learning environments that balances accuracy, efficiency, and scalability in handling multiple mutually exclusive tasks. By leveraging a shared backbone model with task-specific LoRA adapters, the framework achieves competitive performance with a minimal reduction in accuracy while significantly improving inference efficiency and reducing deployment costs. The experimental results demonstrate up to 60% lower GPU memory consumption and a 40% reduction in inference latency compared to fully fine-tuned models. These advantages make the framework well-suited for real-world applications in cost-sensitive educational domains, offering a sustainable alternative to traditional multi-model deployment strategies. Future work will explore extending this approach to more complex domains and tasks, further enhancing its adaptability and robustness.

References

- Branden Chan, Stefan Schweter, and Timo Möller. German’s next language model. *arXiv preprint arXiv:2010.10906*, 2020.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.
- Zhiqiang Hu, Lei Wang, Yihuai Lan, Wanyu Xu, Ee-Peng Lim, Lidong Bing, Xing Xu, Soujanya Poria, and Roy Ka-Wei Lee. Llm-adapters: An adapter family for parameter-efficient fine-tuning of large language models. *arXiv preprint arXiv:2304.01933*, 2023.
- Ehsan Latif and Xiaoming Zhai. Automatic scoring of students’ science writing using hybrid neural network. In *AAAI Workshop on Artificial Intelligence for Education*, pages 1–13. PMLR, 2024a.
- Ehsan Latif and Xiaoming Zhai. Fine-tuning chatgpt for automatic scoring. *Computers and Education: Artificial Intelligence*, 6:100210, 2024b.
- Ehsan Latif, Xiaoming Zhai, and Lei Liu. Ai gender bias, disparities, and fairness: Does training data matter? *arXiv preprint arXiv:2312.10833*, 2023.
- Ehsan Latif, Luyang Fang, Ping Ma, and Xiaoming Zhai. Knowledge distillation of llms for automatic scoring of science assessments. In *International Conference on Artificial Intelligence in Education*, pages 166–174. Springer, 2024a.
- Ehsan Latif, Gyeong-Geon Lee, Knut Neumann, Tamara Kastorff, and Xiaoming Zhai. G-sciembed: A contextualized llm for science assessment tasks in german. *arXiv preprint arXiv:2402.06584*, 2024b.
- Zhengliang Liu, Xinyu He, Lei Liu, Tianming Liu, and Xiaoming Zhai. Context matters: A strategy to pre-train language model for science education. In *International Conference on Artificial Intelligence in Education*, pages 666–674. Springer, 2023.
- Organisation for Economic Co-operation and Development. Pisa 2015 results (volume i): Excellence and equity in education. Technical report, OECD Publishing, Paris, 2016. URL <https://doi.org/10.1787/9789264266490-en>.
- Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, et al. Transformers: State-of-the-art natural language processing. In *Proceedings of the 2020 conference on empirical methods in natural language processing: system demonstrations*, pages 38–45, 2020.
- Xiaoming Zhai, Peng He, and Joseph Krajcik. Applying machine learning to automatically assess scientific models. *Journal of Research in Science Teaching*, 59(10):1765–1794, 2022.
- Longteng Zhang, Lin Zhang, Shaohuai Shi, Xiaowen Chu, and Bo Li. Lora-fa: Memory-efficient low-rank adaptation for large language models fine-tuning. *arXiv preprint arXiv:2308.03303*, 2023.

