arXiv:2412.21071v1 [quant-ph] 30 Dec 2024

Investigating layer-selective transfer learning of QAOA parameters for Max-Cut problem

Francesco Aldo Venturelli^{1,3}, Sreetama Das^{2,4}, Filippo Caruso^{2,3,4}

¹Department of Engineering, University Pompeu Fabra, Tànger, 122-140, 08018, Barcelona, Spain

²Istituto Nazionale di Ottica del Consiglio Nazionale delle Ricerche (CNR-INO), I-50019 Sesto Fiorentino, Italy

³Department of Physics and Astronomy, University of Florence, Via Sansone 1, Sesto Fiorentino, I-50019, Italy

⁴European Laboratory for Non-Linear Spectroscopy (LENS),

University of Florence, Via Nello Carrara 1, Sesto Fiorentino, I-50019, Italy

Quantum approximate optimization algorithm (QAOA) is a variational quantum algorithm (VQA) ideal for noisy intermediate-scale quantum (NISQ) processors, and is highly successful for solving combinatorial optimization problems (COPs). It has been observed that the optimal variational parameters obtained from one instance of a COP can be transferred to another instance, producing sufficiently satisfactory solutions for the latter. In this context, a suitable method for further improving the solution is to fine-tune a subset of the transferred parameters. We numerically explore the role of optimizing individual QAOA layers in improving the approximate solution of the Max-Cut problem after parameter transfer. We also investigate the trade-off between a good approximation and the required optimization time when optimizing transferred QAOA parameters. These studies show that optimizing a subset of layers can be more effective at a lower time-cost compared to optimizing all layers.

I. INTRODUCTION

Combinatorial optimization problems (COPs) represent a large class of optimization problems relevant in a plethora of real-world scenarios, some examples being the traveling salesman problem, minimum vertex covering, graph coloring, knapsack problem, etc. Due to the non-deterministic polynomial-time (NP) hardness of these problems, finding an optimal solution is very challenging for a classical exact or heuristic algorithm. Specifically, the complexity of searching the optimal solution(s) among feasible ones could exponentially increase as the problem scale grows [1]. With the inception of quantum computation, and the evidence of inherent quantum advantages absent in classical computation, significant interest has been focused towards developing quantum algorithms with the final goal of surpassing their classical counterparts. The quantum approximate optimization algorithm (OAOA), aimed at solving COPs, was first proposed in Ref. [2]. It is well known that the solution of a COP can be encoded in the ground state of a classical cost Hamiltonian H_c [3] which represents the instance of the problem itself. The QAOA works by variationally preparing an approximation of the ground state of H_c . It has been established that QAOA provides certain quantum advantages over classical algorithms [2, 4–8] for certain classes of COPs.

The QAOA algorithm lies within the large class of circuitbased quantum learning algorithms, known as variational quantum algorithms (VQAs) [9, 10], which are ideal to implement in noisy intermediate-scale quantum (NISQ) devices. In VQA, the parameters $(\vec{\theta} = \{\theta_1, \theta_2, .., \theta_k\})$ of a quantum circuit $U(\vec{\theta})$ are iteratively updated using a classical optimization routine until the state $|\psi\rangle$ prepared by $U(\vec{\theta})$ minimizes the expectation value $\langle \psi | H_c | \psi \rangle$ of the Hamiltonian H_c , i.e. the system's energy. In particular for QAOA, $U(\vec{\theta})$ is composed by alternately applying two unitary operators generated from H_c and another 'mixer' Hamiltonian H_m . A *p*-layer QAOA has in total k = 2p such unitary applications and trainable parameters. We discuss the architecture in more detail in the next section. The approximate solution obtained from a finitedepth QAOA approaches the true solution as $p \rightarrow \infty$. With an increasing number of qubits, one needs a higher p to obtain a good approximate solution. However, training a variational circuit of large size and depth may suffer from local minima [11] and is prone to the Barren plateau problem [12] in which the variance of the gradient of the cost function vanishes. To avoid these bottlenecks, several works have emphasized the importance of choosing certain underlying structure of the parameters as well as an efficient parameter initialization [13–16].

Another efficient technique to circumvent the trainability issue is to leverage the good transferability of OAOA parameters, which is based on the observation that the optimum parameters for one instance of a particular COP result in good quality solutions for other instances of that COP [17–21]. It has been observed that the parameter transferability is maintained even between different COPs [22]. Thus, one can transfer the optimized QAOA parameters from one particular instance with a smaller problem size to the QAOA circuits corresponding to newer target instances with higher problem sizes, skipping the resource-extensive optimization process for the latter. In spite of this advantage, a thorough look at previous works suggests that the transferability of parameters is reduced with growing difference in size between the optimized instance and the target instance [21–23]. Thus, another practical approach is to use the transferred parameters as the initial parameters, followed by optimizing all of them to get a reasonably good solution. The optimization time in this approach will be less than the time required for self-optimization of the target instance starting from random initial parameters.

In this work, we propose and explore a novel QAOA transfer learning regime in which we optimize only a small subset of all layers following the parameter transfer. The motivation of this approach is to significantly reduce the optimization time compared to optimizing all layers, as well as to investigate if selectively optimizing some of the layers can lead to a better performance than optimizing the others. The approximation ratio obtained from this approach is evidently lower than that obtained by optimizing all layers, with the benefit of a shorter optimization time. As a measure of the trade-off between the approximation ratio and the optimization time, we calculate the ratio of the above two quantities, and we find that the ratio is significantly higher for layer selective transfer learning.

II. METHODS

A. Quantum approximate optimization algorithm

QAOA can be interpreted as a trotterized quantum annealing (QA) algorithm, facilitated by a classical optimization routine. Similarly to QA, the time evolution in QAOA is generated by two Hamiltonians, namely the cost Hamiltonian H_c and the mixer Hamiltonian H_m . H_c encodes the COP to be solved. It is diagonal in the computational basis, and the ground state is the solution of the COP. However, H_m is not diagonal in the computational basis. The initial state of QAOA is an eigenstate $|\Psi_0\rangle$ of H_m . The most frequently used mixer Hamiltonian is

$$H_m = \sum_{i=0}^{N-1} \sigma^X,\tag{1}$$

with the corresponding initial state $|\Psi_0\rangle = |+\rangle^{\otimes N}$ for N qubits. However, depending on the particular COP and the knowledge of a feasible solution set, it may be prudent to use other mixer Hamiltonians [5, 24–26]. To construct the variational ansatz, one alternately applies the unitaries $e^{-i\gamma_i H_c}$ and $e^{-i\beta_i H_m}$ to $|\Psi_0\rangle$, where $\{\gamma_i, \beta_i\}$ are the durations for which these two unitaries act in the *i*th layer. The former introduces phases between different basis states of the initial state, while the latter creates interference between them. After applying p such layers, the final state is

$$|\Psi\rangle = e^{-\mathrm{i}\beta_p H_m} e^{-\mathrm{i}\gamma_p H_c} \dots e^{-\mathrm{i}\beta_1 H_m} e^{-\mathrm{i}\gamma_1 H_c} |\Psi_0\rangle.$$
(2)

After each circuit simulation, one measures the expectation value $\langle H_c \rangle$ of the cost Hamiltonian, and it is minimized by repetitively updating γ 's and β 's using a classical optimization routine, which can be gradient-based or gradient-free. The performance of QAOA is evaluated using the Approximation Ratio r defined as,

$$r = \langle H_c \rangle / E_{min},\tag{3}$$

where E_{min} the energy of the true ground state of H_C . Upon completion of the optimization process, $|\psi\rangle$ is a superposition of computational basis states, from which one can sample the solution state with high probability by projectively measuring all the qubits. For certain classes of COPs, the QAOA circuit with depth p = 1 is guaranteed to find the solution with ~ 69% approximation ratio [2]. The output state $|\psi\rangle$ approaches the true solution as $p \to \infty$ in which limit r = 1. In general, it is not clear how many layers one must optimize in order to guarantee a desired value of r.

B. Max-Cut

The maximum cut or Max-Cut refers to labeling the nodes of a graph into two groups in such a way that the total number of graph edges connecting two nodes from different groups is maximized. Solving Max-Cut for unweighted graphs is equivalent to finding the ground state of the Hamiltonian

$$H_c = -\sum_{\langle i,j\rangle \in S} \sigma_i^Z \sigma_j^Z , \qquad (4)$$

where $\langle i, j \rangle$ denotes an edge connecting the i^{th} and j^{th} node, and S is the set of all edges.

For weighted graphs, the Max-Cut problem can be mapped to the Hamiltonian

$$H_C = -\sum_{\langle i,j\rangle \in S} J_{ij} \sigma_i^Z \sigma_j^Z.$$
 (5)

Here σ_i^Z is Pauli-Z matrix acting on i^{th} qubit, and $J_{ij} > 0$ are edge weights randomly generated from uniform distribution.

C. Transferability of QAOA parameters

In Ref. [17], a concentration behavior of the QAOA cost function corresponding to the Max-Cut problem was heuristically and numerically observed for 3-regular graphs. In detail, for a fixed depth p of the QAOA circuit and in the limit of large number of qubits N, the cost function landscape and the optimum parameter values have very little dependence on the particular chosen instance of the Max-Cut problem. Thus, the optimum parameter values for different instances concentrate in the same region of the parameter space. For nonisomorphic and unweighted graphs, similar observations were reported in Ref. [27]. The concentration phenomena and the scaling of the parameters were analytically demonstrated in [23]. These observations lead to "parameter transfer" i.e. optimizing QAOA parameters for one instance (donor graph) and then transferring them to the QAOA circuit for a different instance (acceptor graph), without optimizing them further for the latter. Many other works studied in detail the effectiveness of the optimum parameter transfer for smaller problem size, between graphs with varying topological properties, for weighted Max-Cut problem, and even between instances of different COPs [18–22].

While the above studies imply that the parameter transfer results in an approximation ratio close to that obtained by selfoptimization, this statement may not strongly hold when considering small size graphs, and transfer between graphs with large difference in size. Indeed, as we observe from Ref. [23], for certain layers, $\{\gamma_i, \beta_i\}$ vary significantly with N, when N is of the order of a few tens. The results of Ref. [21] show that when transferring parameters between different graphs with same N, a high difference in edge probability between them may result in sampling a wrong solution state for the acceptor graph. The study in Ref. [22] shows a poor transferability between different COPs for higher values of N. These observations suggest that an additional optimization should be



FIG. 1: A schematic diagram of the layer-selective transfer learning scheme of QAOA for Max-Cut problem.

performed starting from the transferred parameters, to finetune them to the optimal solution. The time for the additional optimization, though being less than the time for selfoptimization, can be further reduced if we selectively finetune the parameters corresponding to only some of the layers instead of all layers. In Fig. 1, we schematically present this layer-selective optimization scheme. In the following section, we describe our methodologies and numerical observations for studying this layer-selective optimization of QAOA for Max-Cut problem.

III. RESULTS

We compare the following two optimization schemes.

- 1. **Full transfer:** We transfer optimized QAOA parameters for a fixed maxcut instance of a donor graph to the QAOA circuits for solving other acceptor graph instances and calculate the approximation ratios obtained for the latter.
- 2. *k*-layer optimization with transferred initial parameters: In this new scheme proposed by us, following the full transfer of parameters, we use them as the initial parameters and we further optimize only k(< l) number of layers.

As the measure of optimization time τ , we use the number of iterations required to reach a desired convergence of the cost function. In all cases, we stop the optimization cycle when the change in the cost function is less than 0.0001 for three consecutive iterations. In some cases, we present a comparison of approximation ratio obtained from the above two schemes with the all-layer-optimization scheme. The latter refers to the scenario in which all layers are optimized starting from the transferred parameters.

For all of the above schemes and for each number of nodes, we randomly generate 20 connected and unweighted graphs from the Erdos-Renyi distribution with edge probability 0.6. These graphs construct the set of acceptor graphs. We conduct each experiment using a 5-layer QAOA circuit. To generate the set of parameters to be transferred in tasks 1 and 2 described above, we use an 8-node donor graph configuration generated using a fixed seed and perform selfoptimization starting from random initial parameters with a 5-layer QAOA. An 8-node graph represents a moderate size within the range of nodes chosen for our numerical simulations. As such, it may help optimize smaller graphs by exploring a broader range of complex paths. For higher-node graphs, however, this initial configuration may lack sufficient complexity, which is why we incorporate an additional optimization step. We use Pennylane [28] quantum simulator to build the circuits. We use Adagrad optimizer from Optax [29] which is a gradient-based iterative optimizer.

To begin with, we investigate the improvement in the approximation ratio when any one of all five layers is optimized following the parameter transfer. We experiment with acceptor graphs having 12, 16 and 18 nodes. In Fig. 2, we show the results only for 12 and 18 nodes, each case with two different 8-node donor graphs. For majority of instances, we observe that training the first two layers as well as the last two layers improves the approximation ratio, whereas training the third layer has negligible effect. The same behaviour is observed for 16-node instances (though not shown in this manuscript). In particular, for all three cases, training the second layer alone ensures an improvement of approximation ratio. This improvement is most pronounced for 18 nodes. A grid search of $\langle H_c \rangle$ in the $\{\gamma_i, \beta_i\}$ plane for each i = 1, 2, ..., 5 shows that the minimum value of $\langle H_c \rangle$ is lower in $\{\gamma_2, \beta_2\}$ plane compared to the four other energy planes, which explains the best value of r obtained for the second layer. To check the single layer optimization with respect to a different number of total



FIG. 2: Approximation ratio r obtained from full parameter transfer, as well as from optimizing each of the layers individually for (a) 12 node instances and (b) 18 node instances. The horizontal axis shows the seed values using which 20 random graphs were generated.

Each of the subfigures shows two cases corresponding to two different 8-node donor graphs. All cases correspond to p = 5.

layers, in Fig. 3, we show the approximation ratio when using p = 7 layers for 12 node graphs. In this case as well, optimizing the second layer alone shows maximum improvement.

Next, we optimize two or three layers among all five layers. Motivated from our observations in Fig. 2, we choose to optimize the first two or three layers exclusively. A comparative analysis of this optimization scheme with respect to other schemes is presented in Fig. 4. For 12 node graphs, there are a few Max-Cut instances for which the parameter transfer results in a significantly low approximation ratio, the difference to all-layer-optimization being at least 10%. Such instances occur more frequently for 18 node graphs, which projects the poor transferability between donor and acceptor graphs with large difference in size. The figures also show that optimizing



FIG. 3: Approximation ratio r obtained from full parameter transfer, as well as from optimizing each of the layers individually for 12-node instances and p = 7.



FIG. 4: A comparison between approximation ratios obtained from full parameter transfer, as well as from optimizing the second layer alone, the first two layers, first three layers, and from optimizing all layers for (a) 12-node graph instance and (b) 16-node graph instance.

a small number of layers fails to reach an approximation ratio close to that obtained from all-layer-optimization. While optimizing the second layer alone results in an improvement of approximation ratio, the additional improvement resulting from optimizing two or three layers is not substantial.

We further investigate the trade-off between the approximation ratio r and the optimization time τ . In Fig. 5(a) and (b), we show the average values of these two quantities with

varying numbers of nodes. The averaging is done over 40 instances. We calculate the difference δr between the approximation ratio obtained from a particular optimization scheme and that obtained from full transfer of parameters. We divide it by the corresponding optimization time, and average this ratio $\delta r/\tau$ over 40 randomly generated acceptor graphs. We plot the averged ratio in Fig. 5(c), which shows that the time-efficiency trade-off is highest when optimizing the



FIG. 5: (a) Average of approximation ratio r, (b) average of optimization time, and (c) average of $\delta r/\tau$ for some of the optimization schemes presented in Fig. 4 and for a range of number of nodes.



FIG. 6: (a) Approximation ratio r for full transfer, as well as optimizing each layer individually for 16-node weighted graphs.
(b) Approximation ratios obtained from full parameter transfer, as well as from optimizing the second layer alone, the first two layers, and from optimizing all layers for 16 node weighted graphs.

second layer alone. The efficiency of 2-layers and 3-layers optimization begin to surpass the all-layer-optimization only when the number of nodes is sufficiently high. Thus, the *self-optimization* scheme for larger graphs is very costly in terms of optimization time, while introducing sub-optimization is much more efficient even though a percentage in the approxi-

mation ratio is lost.

Finally, we investigate the above scenarios for weighted graphs. For each instance, we randomly generate the edge weights. In Fig. 6(a), we compare individual single-layer optimization with the full parameter transfer, which again shows highest improvement for optimizing the first two QAOA lay-

ers. The observations from Fig. 6(b) again imply that optimizing first two layers results in very little improvement over optimizing the second layer alone. However, all transfer learning schemes have significantly lower approximation ratio compared to all-layer optimization. Thus for weighted graphs, sampling the correct solution may necessarily require optimizing all layers post parameter transfer.

IV. CONCLUSION

The QAOA algorithm has established itself as a promising method for solving COPs such as unweighted and weighted MaxCut. The costly optimization process of QAOA layers for large problem size can be bypassed by using the good transferability of parameters between different problem instances. In the present work, we have explored a new approach of layerselective optimization of QAOA parameters after the parameter transfer. We collected the optimized set of parameters from a donor graph and used them in the same QAOA circuit applied to other larger acceptor graphs of the order of 16 or 18 nodes. Following this, we propose to optimize a subset of klayers, rather than the whole set of p layers, with a consequent reduction in terms of the total number of steps, and hence the time taken by the optimizer to achieve the solution. Our study also highlighted the different contributions arising from each single layer of the circuit, and showed that the optimization of a specific layer can give higher or lower approximation ratio values, implying different significance of individual layers. In particular, the numerical results suggest that optimizing the second layer alone corresponds to the highest ratio between approximation quality and the required optimization time. These observations can lead to new insights towards understanding how the QAOA works and how to set up efficient and powerful QAOA-based algorithms. The next step could be to test the validity of our results on real quantum processors and on larger graphs with the aim of opening new ways to efficiently implement a pipeline to assess COPs via quantum machine learning.

ACKNOWLEDGMENTS

This work was supported by the European Commission's Horizon Europe Framework Programme under the Research and Innovation Action GA n. 101070546–MUQUABIS, by the European Defence Agency under the project Q-LAMPS Contract No B PRJ- RT-989, and by the MUR Progetti di Ricerca di Rilevante Interesse Nazionale (PRIN) Bando 2022 - project n. 20227HSE83 – ThAI-MIA funded by the European Union - Next Generation EU.

- C. Zhang, Y. Wu, Y. Ma, W. Song, Z. Le, Z. Cao, and J. Zhang, A review on learning to solve combinatorial optimisation problems in manufacturing, IET Collaborative Intelligent Manufacturing 5, e12072 (2023).
- [2] E. Farhi, J. Goldstone, and S. Gutmann, A quantum approximate optimization algorithm (2014), arXiv:1411.4028 [quantph].
- [3] A. Lucas, Ising formulations of many np problems, Frontiers in Physics 2, 10.3389/fphy.2014.00005 (2014).
- [4] E. Farhi and A. W. Harrow, Quantum supremacy through the quantum approximate optimization algorithm (2019), arXiv:1602.07674 [quant-ph].
- [5] S. Hadfield, Z. Wang, B. O'Gorman, E. G. Rieffel, D. Venturelli, and R. Biswas, From the quantum approximate optimization algorithm to a quantum alternating operator ansatz, Algorithms 12, 34 (2019).
- [6] D. Lykov, J. Wurtz, C. Poole, M. Saffman, T. Noel, and Y. Alexeev, Sampling frequency thresholds for the quantum advantage of the quantum approximate optimization algorithm, npj Quantum Information 9, 73 (2023).
- [7] R. Shaydulin, C. Li, S. Chakrabarti, M. DeCross, D. Herman, N. Kumar, J. Larson, D. Lykov, P. Minssen, Y. Sun, Y. Alexeev, J. M. Dreiling, J. P. Gaebler, T. M. Gatterman, J. A. Gerber, K. Gilmore, D. Gresh, N. Hewitt, C. V. Horst, S. Hu, J. Johansen, M. Matheny, T. Mengle, M. Mills, S. A. Moses, B. Neyenhuis, P. Siegfried, R. Yalovetzky, and M. Pistoia, Evidence of scaling advantage for the quantum approximate optimization algorithm on a classically intractable problem, Science Advances 10, eadm6761 (2024), https://www.science.org/doi/pdf/10.1126/sciadv.adm6761.

- [8] K. Blekos, D. Brand, A. Ceschini, C.-H. Chou, R.-H. Li, K. Pandya, and A. Summer, A review on quantum approximate optimization algorithm and its variants, Physics Reports 1068, 1 (2024), a review on Quantum Approximate Optimization Algorithm and its variants.
- [9] A. Peruzzo, J. McClean, P. Shadbolt, M.-H. Yung, X.-Q. Zhou, P. J. Love, A. Aspuru-Guzik, and J. L. O'Brien, A variational eigenvalue solver on a photonic quantum processor, Nature Communications 5, 4213 (2014).
- [10] J. R. McClean, J. Romero, R. Babbush, and A. Aspuru-Guzik, The theory of variational hybrid quantum-classical algorithms, New Journal of Physics 18, 023023 (2016).
- [11] E. R. Anschuetz and B. T. Kiani, Quantum variational algorithms are swamped with traps, Nature Communications 13, 7760 (2022).
- [12] J. R. McClean, S. Boixo, V. N. Smelyanskiy, R. Babbush, and H. Neven, Barren plateaus in quantum neural network training landscapes, Nature Communications 9, 4812 (2018).
- [13] L. Zhou, S.-T. Wang, S. Choi, H. Pichler, and M. D. Lukin, Quantum approximate optimization algorithm: Performance, mechanism, and implementation on near-term devices, Phys. Rev. X 10, 021067 (2020).
- [14] M. Streif and M. Leib, Training the quantum approximate optimization algorithm without access to a quantum processing unit, Quantum Science and Technology 5, 034008 (2020).
- [15] Quantum annealing initialization of the quantum approximate optimization algorithm, Quantum **5**, 491 (2021).
- [16] X. Lee, Y. Saito, D. Cai, and N. Asai, Parameters fixing strategy for quantum approximate optimization algorithm, in 2021 IEEE International Conference on Quantum Computing and Engineering (QCE) (2021) pp. 10–16.

- [17] F. G. S. L. Brandao, M. Broughton, E. Farhi, S. Gutmann, and H. Neven, For fixed control parameters the quantum approximate optimization algorithm's objective function value concentrates for typical instances (2018), arXiv:1812.04170 [quantph].
- [18] A. Galda, X. Liu, D. Lykov, Y. Alexeev, and I. Safro, Transferability of optimal qaoa parameters between random graphs, in 2021 IEEE International Conference on Quantum Computing and Engineering (QCE) (2021) pp. 171–180.
- [19] A. Galda, E. Gupta, J. Falla, X. Liu, D. Lykov, Y. Alexeev, and I. Safro, Similarity-based parameter transferability in the quantum approximate optimization algorithm (2023), arXiv:2307.05420 [quant-ph].
- [20] R. Shaydulin, P. C. Lotshaw, J. Larson, J. Ostrowski, and T. S. Humble, Parameter transfer for quantum approximate optimization of weighted maxcut, ACM Transactions on Quantum Computing 4, 10.1145/3584706 (2023).
- [21] R. Sakai, H. Matsuyama, W.-H. Tam, Y. Yamashiro, and K. Fujii, Linearly simplified qaoa parameters and transferability (2024), arXiv:2405.00655 [quant-ph].
- [22] J. A. Montanez-Barrera, D. Willsch, and K. Michielsen, Transfer learning of optimal qaoa parameters in combinatorial optimization (2024), arXiv:2402.05549 [quant-ph].
- [23] V. Akshay, D. Rabinovich, E. Campos, and J. Biamonte, Parameter concentrations in quantum approximate optimization, Phys. Rev. A 104, L010401 (2021).
- [24] Z. Wang, N. C. Rubin, J. M. Dominy, and E. G. Rieffel, xy mixers: Analytical and numerical results for the quantum alternating operator ansatz, Phys. Rev. A 101, 012320 (2020).
- [25] J. Cook, S. Eidenbenz, and A. Bärtschi, The quantum alternating operator ansatz on maximum k-vertex cover, in 2020 IEEE International Conference on Quantum Computing and Engineering (QCE) (2020) pp. 83–92.

- [26] A. Bärtschi and S. Eidenbenz, Grover mixers for qaoa: Shifting complexity from mixer design to state preparation, in 2020 IEEE International Conference on Quantum Computing and Engineering (QCE) (2020) pp. 72–82.
- [27] P. C. Lotshaw, T. S. Humble, R. Herrman, J. Ostrowski, and G. Siopsis, Empirical performance bounds for quantum approximate optimization, Quantum Information Processing 20, 403 (2021).
- [28] V. Bergholm, J. Izaac, M. Schuld, C. Gogolin, S. Ahmed, V. Ajith, M. S. Alam, G. Alonso-Linaje, B. AkashNarayanan, A. Asadi, J. M. Arrazola, U. Azad, S. Banning, C. Blank, T. R. Bromley, B. A. Cordier, J. Ceroni, A. Delgado, O. D. Matteo, A. Dusko, T. Garg, D. Guala, A. Hayes, R. Hill, A. Ijaz, T. Isacsson, D. Ittah, S. Jahangiri, P. Jain, E. Jiang, A. Khandelwal, K. Kottmann, R. A. Lang, C. Lee, T. Loke, A. Lowe, K. McKiernan, J. J. Meyer, J. A. Montañez-Barrera, R. Moyard, Z. Niu, L. J. O'Riordan, S. Oud, A. Panigrahi, C.-Y. Park, D. Polatajko, N. Quesada, C. Roberts, N. Sá, I. Schoch, B. Shi, S. Shu, S. Sim, A. Singh, I. Strandberg, J. Soni, A. Száva, S. Thabet, R. A. Vargas-Hernández, T. Vincent, N. Vitucci, M. Weber, D. Wierichs, R. Wiersema, M. Willmann, V. Wong, S. Zhang, and N. Killoran, Pennylane: Automatic differentiation of hybrid quantum-classical computations (2022), arXiv:1811.04968 [quant-ph].
- [29] DeepMind, I. Babuschkin, K. Baumli, A. Bell, S. Bhupatiraju, J. Bruce, P. Buchlovsky, D. Budden, T. Cai, A. Clark, I. Danihelka, A. Dedieu, C. Fantacci, J. Godwin, C. Jones, R. Hemsley, T. Hennigan, M. Hessel, S. Hou, S. Kapturowski, T. Keck, I. Kemaev, M. King, M. Kunesch, L. Martens, H. Merzic, V. Mikulik, T. Norman, G. Papamakarios, J. Quan, R. Ring, F. Ruiz, A. Sanchez, L. Sartran, R. Schneider, E. Sezener, S. Spencer, S. Srinivasan, M. Stanojević, W. Stokowiec, L. Wang, G. Zhou, and F. Viola, The DeepMind JAX Ecosystem (2020).