On Parallel External-Memory Bidirectional Search

Lior Siag^a, Shahaf S. Shperberg^{a,*}, Ariel Felner^a and Nathan R. Sturtevant^{b,c}

^aBen-Gurion University of the Negev ^bUniversity of Alberta, Department of Computing Science ^cAlberta Machine Intelligence Institute (Amii)

Abstract. Parallelization and External Memory (PEM) techniques have significantly enhanced the capabilities of search algorithms when solving large-scale problems. Previous research on PEM has primarily centered on unidirectional algorithms, with only one publication on bidirectional PEM that focuses on the meet-in-the-middle (MM) algorithm. Building upon this foundation, this paper presents a framework that integrates both uni- and bi-directional best-first search algorithms into this framework. We then develop a PEM variant of the state-of-the-art bidirectional heuristic search (BiHS) algorithm BAE* (PEM-BAE*). As previous work on BiHS did not focus on scaling problem sizes, this work enables us to evaluate bidirectional algorithms on hard problems. Empirical evaluation shows that PEM-BAE* outperforms the PEM variants of A* and the MM algorithm, as well as a parallel variant of IDA*. These findings mark a significant milestone, revealing that bidirectional search algorithms clearly outperform unidirectional search algorithms across several domains, even when equipped with state-of-the-art heuristics.

1 Introduction

A* [11] and its many variants are commonly used to optimally solve combinatorial and pathfinding problems. However, as these problems often involve state spaces of exponential size, practical limitations in terms of time and memory resources hinder the ability of these algorithms to tackle large instances, particularly when the scale of the problem increases (e.g., more variables, larger graphs, etc.). Thus, an important line of research in heuristic search is harnessing hardware capabilities to overcome these limitations. Parallelizing various components of the search process across multiple threads can lead to a significant reduction in running time. Similarly, exploiting external memory, such as large disks, allows algorithms to scale the size of OPEN and CLOSED lists, substantially increasing the size of problems that can be solved [6, 8, 9, 14, 23].

Orthogonally, recent research has focused on *bidirectional heuristic search* (BiHS) algorithms, which have been shown to outperform unidirectional search (UniHS) methods [1, 5, 31, 33], on some problems, but the majority of these results are on relatively small problems or with weakened heuristics. It has been conjectured [3] that bidirectional search does not perform well with strong heuristics, and it is unclear whether these results will scale to the largest problems. Thus, our aim is to scale bidirectional search algorithms to significantly larger problems and stronger heuristics.

The intersection of parallel and external memory (PEM) and BiHS has only been explored in the context of the meet-in-the-middle

(MM) algorithm [13], yielding a variant called PEMM [35]. However, utilizing recent advancements in BiHS algorithms necessitates a framework for seamlessly converting both recent and future BiHS algorithms into corresponding PEM variants.

This paper builds upon previous research in parallel and externalmemory search [35] to unify and explore how parallel computing and external memory utilization impact BiHS. In the interest of broad accessibility, we introduce a flexible framework capable of integrating any UniHS or BiHS algorithm into the PEM paradigm. Additionally, using this framework, we successfully integrate the state-of-the-art BiHS algorithm BAE^{*} [27], which relies on a consistent heuristic, resulting in a variant called PEM-BAE^{*}.

We empirically compare PEM-BAE* against PEM variants of A* (PEM-A*), reverse A* (PEM-rA*), and MM (PEMM) on 15-and 24tile puzzles and random 20-disk 4-Peg Towers of Hanoi problems. In addition, we compare PEM-BAE* to a parallel variant of IDA*, called AIDA* [26], as well as its reversed version. Our results confirm that PEM-BAE* significantly outperforms the other algorithms as problem complexity increases. This superiority of PEM-BAE* is evident not only with weak heuristics, as previously demonstrated for BAE*, but also persists when utilizing strong heuristics on large problems. This highlights that a BiHS algorithm stands as the stateof-the-art approach for addressing multiple challenging problems.

2 Background and Definitions

Research on bidirectional heuristic search (BiHS) has spanned several decades, dating back to the work of Pohl [25]. Recently, a new theoretical understanding emerged regarding the necessary nodes for expansion during the search [7, 29], sparking a series of algorithms that find optimal [1, 4, 5, 31], near-optimal [2], and memory-efficient solutions [32]. Other research has delved into algorithm comparisons [1, 30, 33] and explored the potential advantages of BiHS over Unidirectional search (UniHS) [37].

The focus of this paper is on two algorithms: MM, the first algorithm to be integrated with parallel external-memory search, and BAE*, chosen due to its superior performance. BAE* and other BiHS algorithms have demonstrated strong performance, surpassing their UniHS counterparts, on small problems with relatively weak heuristics. Some have suggested that, as the scale of problems increase, BiHS algorithms can maintain their dominance over UniHS algorithms, even when stronger heuristics are employed [1, 34, 37]. Others have conjectured that bidirectional search will not perform well on problems with strong heuristics [3]. This paper evaluates these conjectures by constructing a PEM variant of BAE* capable of solv-

^{*} Email: shperbsh@bgu.ac.il

ing large problems with state-of-the-art heuristics.

2.1 BiHS: Definitions and Algorithms

In BiHS, the aim is to find a least-cost path, of cost C^{*}, between *start* and *goal* in a given graph G. dist(x, y) denotes the shortest distance between x and y, so $dist(start, goal) = C^*$. BiHS executes a forward search (F) from *start* and a backward search (B) from *goal* until the two searches meet. BiHS algorithms typically maintain two open lists OPEN_F and OPEN_B for the forward and backward searches, respectively. Each node is associated with a g-value, an h-value, and an f-value (g_F, h_F, f_F and g_B, h_B, f_B for the forward and backward searches). Given a direction D (either F or B), we use f_D, g_D and h_D to indicate f-, g-, and h-values in direction D.

The g-value of a state s is cost of the best path discovered to s, and f-value of a state is the sum of its g- and h- values. Most BiHS algorithms consider the two front-to-end heuristic functions [15] $h_F(s)$ and $h_B(s)$ which respectively estimate dist(s, goal) and dist(start, s) for all $s \in G$. h_F is forward admissible iff $h_F(s) \leq$ dist(s, goal) for all s in G and is forward consistent iff $h_F(s) \leq$ $dist(s, s') + h_F(s')$ for all s and s' in G. Backward admissibility and consistency are defined analogously.

BiHS algorithms mainly differ in their node- and directionselection strategies and other termination criteria. We next describe MM and BAE^{*}, both implemented in this paper.

Meet in the middle (MM). MM [13] is a BiHS algorithm ensuring that the search frontiers *meet in the middle*. In MM, nodes n in OPEN_D are prioritized by:

$$pr_D(n) = \max(f_D(n), 2g_D(n)) \tag{1}$$

MM expands the node with minimal priority, PrMin on both OPEN_F and OPEN_B. MM halts the search once the following two conditions are met: (1) the same node n is found on both OPEN lists; (2) the cost of the path from *start* to *goal* through n is $\leq LB_{\text{MM}}$ where LB_{MM} is a lower bound on C^* that is computed as follows:

$$LB_{\rm MM} = \max(PrMin, fMin_F, fMin_B, gMin_F + gMin_B)$$
⁽²⁾

where $fMin_F$ ($fMin_B$) and $gMin_F$ ($gMin_B$), are the minimal fand g-values in OPEN_F (OPEN_B), respectively. Sturtevant and Chen [35] provided a PEM variant of MM (PEMM). Our framework below is an extension of PEMM.

BAE*. Most algorithms (e.g., MM) only assume that the heuristics used are admissible. BAE^{*} [27, 1] (and the identical algorithm DIBBS [28]) are BiHS algorithms that specifically assume that both h_F and h_B are consistent and thus exploit this fact. Let $d_F(n) = g_F(n) - h_B(n)$, the *difference* between the actual forward cost n (from *start*) and its heuristic estimation to *start*. This indicates the *heuristic error* for node n (as $h_F(n)$ is a possibly inaccurate estimation of $g_B(n)$). Likewise, $d_B(m) = g_B(m) - h_F(m)$. BAE^{*} orders nodes in OPEN_F according to

$$b_F(n) = f_F(n) + d_F(n) \tag{3}$$

 $b_F(n)$ adds the heuristic error $d_F(n)$ to $f_F(n)$ to indicate that the opposite search using $h_B(n)$ will underestimate by $d_F(n)$. Likewise, $b_B(m) = f_B(m) + d_B(m)$ is used to order nodes in OPEN_B. At every expansion cycle, BAE* chooses a search direction D and expands a node with minimal b_D -value. Additionally, BAE* terminates once the same state n is found on both OPEN lists and the cost of the path from *start* to *goal* through n is $\leq LB_B$ where LB_B , is a the following lower bound on C^* (known as the *b*-bound):

$$LB_B = (bMin_F + bMin_B)/2 \tag{4}$$

where $bMin_D$ is the minimal *b*-value in OPEN_D.

Given a consistent heuristic, BAE^{*} was proven to return an optimal solution. b(n) is more informed than other priority functions (as it also considers d(n)), and was shown to outperform common unidirectional and bidirectional algorithms [1, 33] on relatively simple domains. These included the 15-puzzle with the Manhattan Distance heuristic, the 12-disk 4-peg Towers of Hanoi Problem, grid benchmark problems, and the pancake puzzle with a weakened GAP heuristic. While BAE^{*} stands as a state-of-the-art BiHS algorithm, it has not been tested on large sliding-tile or Towers of Hanoi problems, or with large pattern database heuristics. In this paper, we develop PEM-BAE^{*}, a PEM version of BAE^{*}, which is able to scale to far larger problems and heuristics.

2.2 Parallel External-Memory Search

External Memory Search structures a search such that the maximum size of a problem solved scales according to the size of the disk, instead of available RAM [24]. These algorithms are often paired with parallel search methods, as techniques to minimize random I/O often group states together, allowing parallel processing.

Two classes of external memory search appear in the literature. One class aims to perform a complete breadth-first search of a state space, employed for verifying state space properties [18] or building large heuristics [14]. These approaches maintain information about every state on disk, loading portions of the data into memory for expansion and duplicate detection. Another class of algorithms, including External A* [9] and search with structured duplicate detection [40, 41], is used to solve large problem instances. In these algorithms, OPEN is stored explicitly on disk, and CLOSED may or may not be stored, depending on the properties of the state space [22].

Both classes aim to reduce I/O operations to disk, e.g., by delaying operations like duplicate detection until many states can be processed in parallel [17], and dividing the state space up into smaller buckets of states [9, 12, 19, 36, 38] which are stored together on disk, and then loaded and expanded together. When duplicate states all hash into the same bucket, it reduces the complexity of checking for duplicate. Hash-based duplicate detection [18] and sorting-based duplicate detection has been delayed, load them into memory, and remove duplicate susing hash tables or sorting, respectively. Structured duplicate detection [40] structures the state space so that all successor buckets can be loaded into memory for immediate duplicate detection.

External memory search has often relied on exponential-growing state-spaces with unit costs to ensure sufficient states are available to efficiently process in parallel. Notably, algorithms like PEDAL [12] have extended these approaches to non-unit-cost problems.

3 The PEM-BiHS Framework

We next introduce a high-level framework called *Parallel External Memory Bidirectional Heuristic Search* (PEM-BiHS), into which both BiHS and UniHS can be seamlessly integrated. PEM-BiHS is designed to efficiently solve very large problem instances. Leveraging parallelization capabilities along with using external memory, PEM-BiHS utilizes the foundations laid by algorithms such as

Algorithm 1 PEM-BiHS General Framework						
1:	1: procedure PEM-BIHS (start, goal)					
2:	$U \leftarrow \infty, LB \leftarrow \text{ComputeLowerBound}()$					
3:	$OPEN_F$, $OPEN_B$, $CLOSED_F$, $CLOSED_B \leftarrow \emptyset$					
4:	Push(<i>start</i> , OPEN _F) \triangleright create bucket and record					
5:	$Push(goal, OPEN_B)$					
6:	while $OPEN_F \neq \emptyset \land OPEN_B \neq \emptyset \land U > LB$ do					
7:	$D \leftarrow \text{ChooseDirection}()$					
8:	$b \leftarrow \text{ChooseNextBucket}(\text{OPEN}_{D})$					
9:	ParallelReadBucket(b, D) \triangleright including In-Bucket DD					
10:	RemoveDuplicates(b, CLOSED _D)					
11:	CheckForSolution($U, b, OPEN_{\overline{D}}$)					
12:	ParallelExpandBucket(b, OPEN _D)					
13:	WriteToClosed(b, CLOSED _D)					
14:	$LB \leftarrow \text{ComputeLowerBound}()$					
15:	return U					

PEMM, PEDAL, External A*, and structured duplicate detection and exploits further parallelization opportunities.

We begin with a high-level description of PEM-BiHS together with the pseudo-code presented in Algorithm 1, which builds on [35], followed by a detailed description of algorithmic components. PEM-BiHS initializes an OPEN and CLOSED list for each direction (line 3). These lists do not explicitly store search nodes; instead, they maintain references to files (buckets) that contain the corresponding nodes. PEM-BiHS employs the following stages:

Halting condition (line 6): During each expansion cycle, PEM-BiHS evaluates the cost U of the current incumbent solution in comparison to the calculated lower bound LB, derived from the nodes within the open lists. If $U \leq LB$ or one of the open lists is empty, PEM-BiHS halts and returns the current solution cost (or infinity if no solution was found). Otherwise, the search continues.

Choosing direction and bucket for expansion (line 7–8): next, PEM-BiHS chooses the search direction D (UniHS always chooses the forward side) as well as a bucket from OPEN_D to be expanded.

Retrieving the bucket (line 9): Next PEM-BiHS performs parallel reading of the file containing the bucket from external memory into the internal memory (RAM). This stage involves eliminating duplicate states within the bucket.

Duplicate Detection (DD) (line 10): PEM-BiHS then eliminates duplicates nodes with other buckets in CLOSED_D.

Solution Detection (line 11): PEM-BiHS checks whether a new solution was found.

Expansion (line 12 detailed in Algorithm 2): Nodes from memory are concurrently expanded, generating children. These children are then written to their respective buckets (creating new ones if needed, and their references are inserted into OPEN_D).

Writing to disk (line 13): Finally, the expanded nodes are written to disk, creating a new duplicate-free bucket. A reference to this bucket is inserted into CLOSED.

We next turn to provide an in-depth description of different algorithmic components of PEM-BiHS.

3.1 State-space Representation

Typically, states are represented using high-level structures for convenient programming. In the context of combinatorial puzzles (e.g., the 15- and 24-puzzles), states are commonly stored as an array, with each cell's value corresponding to the label of the object it holds. To pack these states into files, an additional encoding/decoding mechanism is required for converting states into bits and decoding them. These decodings aim to minimize memory consumption and reduce I/O time. For example, in the 24-puzzle practical implementations often use 8 bits (byte) to represent the identity of each tile demanding 200 bits (8 × 25). Leveraging bit manipulation allows compression to 125 bits (5 bits are enough to store the identity of a tile). Furthermore, recognizing that a state is a permutation of 0-24 enables to use only $\lceil \log_2(25!) \rceil = 84$ bits, e.g., using the Lehmer encoding, which maps each permutation to a unique integer in the range $\{1 \dots 25!\}$.

3.2 Bucket Structure

Nodes are grouped into buckets based on pre-determined attributes or *identifiers*. E.g., in the context of External A*, a bucket groups nodes with identical g- and h-values (e.g., all nodes n with g(n) = 3and h(n) = 4 belong to the 3-4-bucket). In PEMM, a bucket groups nodes with identical priority (pr(n), as defined for MM) as well as identical g-value. Alternatively, a hash value of a state, obtained by applying a hashing function to divide the set of states into a fixed number of values, can also serve as a property for defining a bucket.

Importantly, PEM-BiHS assumes that an entire bucket can fit into memory (in addition to a fixed-sized cache used to store successors before flushing them to disk, as detailed in Section 3.7). Therefore, bucket identifiers may not allow too many nodes to be mapped into a single bucket, although adaptive methods have been used to dynamically adapt bucket sizes [39]. Buckets are then written to files and loaded into memory as needed.

In PEM-BiHS, OPEN and CLOSED are maintained inside main memory. They store bucket *records*, which include the bucket identifiers and a link to the file containing the bucket. During an expansion cycle, a bucket record from OPEN is chosen for expansion. That bucket's file is then loaded into memory. Different algorithms within PEM-BiHS will choose different buckets as described next.

3.3 Direction, Prioritization, and Lower-bound

Selecting direction (line 7 in Algorithm 1). Numerous strategies can be employed for direction selection in BiHS. Three prevalent strategies appear in the BiHS literature: i) choosing the direction with minimal priority (as employed by MM), ii) alternating between search directions, and iii) Pohl's cardinality criterion, which chooses the direction with the smaller open-list. Naturally, UniHS algorithms consistently choose the same direction.

Prioritizing buckets (line 8). Selecting the next node to expand is the essence of any search algorithm. PEM-BiHS allows the use of any priority function, under the restriction that the priority function must induce a total order among buckets based on the bucket identifiers. Thus, a bucket is chosen by comparing bucket identifiers within OPEN. For example, in the implementation of a PEM variant of A^* using this framework (denoted as PEM- A^*), the bucket identifier includes the *g*- and *h*-values of nodes.

It is well known that the priority function influences the number of nodes expanded. For example, A^* prioritizes nodes based on lower *f*-values, and often adds a second prioritization criterion ("tiebreaking" between nodes that share the same *f*-value), which prefers nodes with higher *g*-value (and thus lower *h*-value). This "higher-*g*first" tie-breaking typically reduces the number of expanded nodes compared to "lower-*g*-first", particularly in domains with unit edge costs. Nevertheless, in standard A^* , different tie-breaking policies usually expand states at the same rate (nodes per second). By contrast, in the context of PEM-BiHS, tie-breaking policies can also significantly affect the node expansion rate. If PEM-A* breaks ties according to lower-q-first, once a q-h-bucket is expanded, new nodes will never be added to it, due to the monotonically increasing nature of q-values. By contrast, when using a higher-q-first policy, nodes can be added to the bucket after its expansion. Consequently, the same bucket can be selected for expansion multiple times, up to a number that scales quadratically with the total number of buckets, instead of only once. Thus, while using the lower-g-first tie-breaking may result in more expansions when compared to higher-g-first, the gains from minimizing the costly I/O operations by the lower-g-first tie-breaking make it a more resource-effective strategy. We have validated this in an empirical study on the 15-puzzle problem with a PDB heuristic (see details in Section 5). PEM-A* with the lowerq-first policy expanded 4.4 times more nodes than the higher-q-first policy (616,758 vs. 2,724,974), but still was able to run four times faster (7.8 vs 32 seconds).

Computing Lower-bound (line 14). Different lower-bounds may be employed by PEM-BiHS algorithms [33]. For instance, A^* uses the minimal *f*-value in the open list as a lower bound on the solution cost, MM uses LB_{MM} (Eq. 2) and BAE^{*} uses LB_B (Eq. 4). These and other bounds can be plugged into our framework.

3.4 Reading Buckets

In prior PEM search studies, the process of reading a bucket (file) was carried out sequentially, influenced by the constraints of Hard Disk Drives (HDDs). Concurrent threads accessing the same file on HDDs could lead to performance degradation. However, the recent, popular Solid-State Drives (SSDs) not only provide faster memory access but also benefit from parallelized reading. Therefore, PEM-BiHS further optimizes performance by parallelizing the reading process. To parallelize the reading of a bucket, PEM-BiHS distributes the file containing the bucket equally among multiple threads. In our experiments, this resulted in a twofold speed-up compared to sequential reading. Subsequently, each thread reads states from the disk and decodes them into their in-memory state representation (See Section 3.1).

3.5 In-bucket Duplicate Detection

To minimize I/O operations, the elimination of duplicates is delayed until a bucket is chosen for expansion. Duplicate nodes may arise within the same bucket when a state is discovered via different paths. Additionally, duplicates can occur within closed buckets if the state has already been expanded with a lower g-value, or within other open buckets if states have been discovered with the same g-value. Notably, if the bucket identifiers include the g-value, other open buckets cannot contain duplicates of the same state with the same g-value, and can be disregarded for duplicate detection. During the reading phase, we manage in-bucket duplicate detection. However, to minimize I/O, we postpone duplicate detection within the closed list (as discussed in Section 3.6) until after all nodes have been read.

Similar to hash-based delayed duplicate detection (DDD) [17, 18], when loading a bucket into memory, its nodes are placed into a hash table based on their states using a perfect hash function, and duplicates are ignored if their cell is already filled. Unlike the work of Korf [18], PEM-BiHS allows multiple threads to read from the same bucket concurrently. To support this, each unique hash value is paired with a mutex. Once the reading and in-bucket duplicate detection is done, all threads are synchronized.

Algorithm 2 Parallel Bucket expansion pseudo-code				
1: procedure PARALLELEXPANDBUCKET(<i>b</i> , <i>D</i>)				
2:	$cache \leftarrow \emptyset$			
3:	for every state s in b do			
4:	if current thread should expand s then			
5:	for each successor s_i of s do			
6:	$sb \leftarrow \text{GetBucketOfNode}(s_i)$			
7:	if <i>sb</i> not in OPEN _D then			
8:	AddBucket(OPEN _D , sb)			
9:	AddState(cache _{sb} , s_i)			
10:	if cache _{sb} is full then			
11:	FlushToDisk(cache _{sb}) \triangleright Also locks	sb		
12:	if cache is not empty then			
13:	FlushToDisk(cache)			

3.6 Duplicate Detection against CLOSED

To identify and eliminate duplicates of in-memory nodes with respect to nodes stored in closed buckets (line 10), a scanning process is initiated which reads relevant buckets (in small increments) and compares them against the in-memory nodes. With *Delayed Duplicate Detection* [17], each bucket is associated with a hash value and exclusively contains states assigned that particular value by a hash function. As a result, the scanning process is confined to closed buckets sharing the same hash value as the state of the node under consideration. For instance, if a node's state has a hash value of 5, only buckets associated with the hash value 5 are relevant and considered for duplicate detection.

In PEM-BiHS, the determination of the relevant buckets for scanning relies on the identifiers that define them. If the bucket records include hash values of states, a similar approach to Korf [17] can be employed. Alternatively, if the bucket record contains the h_D -value of states, for direction D, as an identifier, only buckets with the same h_D -value need to be scanned. Therefore, if a bucket record contains both the h_F -value and the h_B -value, the scanning process is limited to buckets that possess identical values for both h_F and h_B .

In addition, with unit edge-cost undirected graphs, (where edges can be followed in both ways) there are three cases for finding duplicates of a node generated at level x. (1) A parent p at level x - 2generates a child node n at level x-1. The child node n generates its parent again at level x. (2) Consider a cycle of even length k which was first explored by the search at the ancestor node a at level 0. The farthest node of this cycle will be seen twice at level x = k/2 from two parents which are at level x - 1. (3) Consider a cycle with odd length k. Here, the two nodes farthest from a will be generated at level $y = \lfloor k/2 \rfloor$ and each will generate the other at level x = y + 1. Note that duplicates only occur as a result of a cycle, and a cycle can be either even or odd. Thus, when generating node n with g(n) = xwe only need to check buckets with g-values of x - 2, x, and x - 1, for these three cases, respectively. Consequently, using the g-value as an identifier could significantly reduce the number of buckets that need to be scanned. This approach optimizes the duplicate detection process based on the available information in the bucket records.

3.7 Parallel Node Expansion

The process of parallel bucket expansion (line 12) is outlined in Algorithm 2. To enable parallel expansion, each thread is allocated an equal portion of the nodes. Newly generated nodes are inserted into a dedicated successor cache for each thread. Each cache is divided into smaller arrays, where each array corresponds to a specific bucket record. This avoids the necessity of immediately writing each new successor to the file, thereby minimizing I/O operations.¹ The framework supports reopenings by adding a new bucket with the same identifier to OPEN and merging it with the corresponding CLOSED bucket after its expansion. In our evaluation, we used consistent heuristics, so we did not encounter any reopenings. Once an array reaches its capacity, all its nodes are flushed into the disk, generating new buckets on disks as well as new bucket records in OPEN if necessary. To prevent simultaneous writes to the same file and maintain data integrity, each bucket record is linked to a mutex, which is locked when a thread writes to a bucket. This design maintains data integrity and allows concurrent writing.

Note that bucket expansion and delayed solution detection in this framework (see Section 3.8) can occur concurrently with separate threads, as delayed solution detection is only concerned with the nodes that are about to be expanded, which are already loaded into memory and will not change due to the expansion.

3.8 Solution Detection

There are two approaches for solution detection (Algorithm 1, line 11): *immediate solution detection* (ISD) and *delayed solution detection* (DSD). In ISD, solutions are identified upon generation of a node n. This involves a query to the open list of the opposite frontier to check for the existence of a node with the same state as the newly generated node n. This is trivially implemented in UniHS, as it only entails checking if the state of n is the goal. Similarly, in standard BiHS, when the open lists are stored in memory, ISD can be efficiently performed using a hash table or a direct-access table where each item can be accessed in constant time.

However, when buckets are stored on disk, ISD can lead to frequent I/O calls every time a node is generated or when the cache of generated nodes is filled. Therefore, PEM-BiHS employs DSD as suggested by Sturtevant and Chen [35]. In DSD, solutions are identified during the expansion phase once all states of the bucket that was chosen to be expanded are already loaded into memory and stored in a hash table. Following that, closed buckets from the opposite direction are loaded in segments and compared against the hash table of expanded nodes in an effort to identify a solution. It's important to highlight that only relevant buckets need to be loaded; for instance, if the identifiers of the bucket corresponding to the same h-values need to be considered. We note again that when the expansion and solution detection are done, all threads are synchronized.

It is important to acknowledge that the benefits of DSD come with certain trade-offs. First, since solutions are detected at a later stage, some nodes might be expanded which could have been avoided with ISD. Furthermore, search bounds leveraging information across the minimal edge cost (often denoted as ϵ) cannot be employed with DSD. This limitation arises because these bounds rely on ISD to improve the lower bound (*LB*) on the solution cost (we refer the reader to Sturtevant and Chen [35] for more details).

4 Parallel External-Memory BAE*

We next describe the implementation details needed for obtaining a PEM variant of the BAE* algorithm (PEM-BAE*).

Direction, Prioritization, and Lower-bound. The prioritization of buckets relies on the BAE* priority function (Eq.3). The lower bound

is determined by the *b*-bound (Eq.4). Additionally, the direction selection policy alternates between directions; a seemingly simplistic approach that has proven to be as effective as more intricate policies [1]. In PEM, this means that the two search sides take turns in loading buckets into memory and expanding them.

Bucket Structure. In PEM-BAE*, we classify nodes into buckets based on their q_D -, h_F -, and h_B -values. This bucket structure offers several advantages. First, it encapsulates all the essential information needed for computing the BAE* priority function. Consequently, during each expansion cycle, only a single bucket needs to be loaded into memory, enhancing efficiency. Second, the *g*-value, serving as one of the bucket identifiers, can sometimes further reduce the number of closed buckets scanned during duplicate detection (as discussed in Section 3.6). Finally, as the classification is based on three values, the resulting buckets tend to remain relatively small. Notably, when buckets become too large for memory, a hash value can be introduced as an additional identifier but such a scenario did not arise in our experiments. A possible limitation of this approach is the potential for significant imbalances in the distribution of nodes across buckets. This bucket size imbalance could impede runtime performance, as we explore in our experiments below. Solution Detection. PEM-BAE* uses DSD.

5 Experimental Results

We performed experiments with PEM-BiHS on the 15- and 24sliding-tile puzzles (STP) and 4-peg Towers of Hanoi (ToH4). All experiments were executed on 2 Intel Xeon Gold 6248R Processor 24-Core 3.0GHz, 192 GB of 3200MHz DDR4 RAM, and 100TB SSD for the external memory. By default, all parallel algorithms were assessed utilizing all 96 available virtual threads (with 48 physical cores). Nevertheless, we have also conducted an ablation study to investigate algorithm performance while varying the number of threads.

We tested the following algorithms besides PEM-BAE*. First, we instantiated both A* and MM within the PEM-BiHS framework, resulting in PEM-A* and PEMM, respectively. Similarly to A*, PEM-A* consistently expands nodes in the forward direction, employs the minimal f-value in OPEN as a lower bound for the solution cost(LB), and expands a g-h bucket with the minimal f-value during each expansion cycle. PEM-A* uses the low-g-first tie-breaking as detailed in Section 3.3. PEM-A* incorporates ISD, checking for solution upon node generation, where the PEM-BAE* and PEMM employ DSD, checking for solutions before node expansions. As BiHS search algorithms explore from both the *goal* and the *start* states, it is crucial to ensure that any potential advantage is not merely a consequence of asymmetries, which causes the search tree from one side to be much smaller. Such asymmetries could also be leveraged in a unidirectional search from goal to start. To address this concern, we executed a reverse variant of PEM-A*, denoted as PEM-rA*, where the search is conducted from *goal* to *start*.

PEMM uses the direction-selection, lower-bound, and prioritizations of MM while using the lower-*g*-first tie-breaking. PEMM uses the *g*-value and priority value (Eq. 1) as bucket identifiers. As a BiHS, PEMM adopts DSD as part of its operational strategy.

For comparison, we have also implemented Asynchronous Parallel IDA* (AIDA*), [26]). AIDA* is a parallelized adaptation of IDA* which conducts a breadth-first search to a predetermined depth. The resulting frontier is subsequently distributed among all threads. Additionally, we've evaluated the reverse version of AIDA*, referred to as rAIDA*. Lastly, we evaluated the standard versions of A* and

¹ One may perform a DD inside this cache array. This will have a marginal effect on the overall performance.





5.1 15-Puzzle

We first experimented on Korf's 100 random instances of the 15puzzle [16]. This domain is relatively compact (13^{10} states) and could be solved without external memory. However, its size enables a comprehensive comparison of all algorithms across different heuristics before moving to larger domains. For heuristics, we used Manhattan Distance (labeled MD) and a 3-4-4-4 additive pattern database [10]) (labeled PDB). To construct the PDB, we divided the puzzle into four squares, one for each corner, with each pattern also including the blank. The average runtime (in seconds) and the number of node expansions are presented in Table 1 (top).

Naturally, using the PDB heuristic substantially reduced both the time and node expansions for all algorithms when compared to using the MD heuristic. The AIDA* variants expanded the largest number of nodes but exhibited the fastest overall runtime. Due to their DFS nature, the AIDA* variants do not store nodes in memory, let alone external memory, nor do they involve sorting nodes, as typically done by best-first search algorithms. Thus, they have the smallest time overhead per node in comparison with all other algorithms. Among the PEM algorithms, both BiHS algorithms outperformed the UniHS algorithms in terms of node expansions and runtime, when using the MD heuristic. Notably, PEM-BAE* significantly outperformed all PEM or iterative deepening algorithms in terms of node expansions by an order of magnitude. This finding is consistent with prior studies that compared BAE* to A* [1, 33], underscoring the advantages of harnessing the consistency of heuristics, as demonstrated by the performance of both A^* and BAE^* as presented in the table. Even when employing the PDB heuristic, PEM-BAE* maintained a significant edge over all other PEM or iterative deepening algorithms in terms of node expansions. However, it exhibited slower runtime than



PHNguké 2andTPEAN6A4*resultate the first environmed radiation startion s5.5. Furthermore, despite its parallelism, PEM-BAE* was slower than both A* and BAE* when using the PDB heuristic. As anticipated, in scenarios where the problems are relatively simple to solve, the overhead incurred by utilizing external memory and parallelization serves to decelerate the search process rather than expedite it.

Table 1 (bottom) provides results on the ten most difficult instances (with largest solution cost). In these instances, the superiority of PEM-BAE* is more pronounced in terms of node expansions, and it also outperforms PEM-A* and PEM-rA* in terms of runtime. Additionally, PEM-BAE* outperformed both AIDA* and rAIDA* with MD. Although PEM-BAE* was still slower than AIDA* and rAIDA* with PDB heuristic, the performance gap is comparatively narrower.

As the problems become more challenging or, conversely, when the heuristic weakens, the performance of PEM-BAE* improves relative to other algorithms. This is demonstrated next on the 24-Puzzle, marking the first evaluation of BiHS algorithms for this large domain.

5.2 24-Puzzle

We experimented with the 50 24-puzzle problems of Korf and Felner [21], using a 6+6+6+6 additive PDB heuristic coupled with its reflection about the main diagonal [10]. Given the immense size of these 24-puzzle problems and the extensive computation time they demand, assessing all algorithms becomes impractical. Moreover, the memory demands for tackling these problems are substantial, making it impractical to execute standard (in-memory) A* and BAE* algorithms. Thus, we compared PEM-BiHS with the AIDA* variants. Figure 1 illustrates the runtime (left) and the number of expanded nodes (right) for each instance. Instances are sorted solution length in ascending order, which roughly indicates the problem's difficulty. For instances with the same solution length, we averaged the results. The plot legends also display the average runtime and expansions for each algorithm across all instances, shown in parentheses.

In general, PEM-BAE^{*} performs the best in both node expansions and runtime. On average, PEM-BAE^{*} expands only 4.4% of the nodes expanded by AIDA^{*} and runs 4.5 times faster. These findings align with the observed trend in the 15-puzzle, indicating that on challenging problems, PEM-BAE^{*} outperforms UniHS algorithms even when equipped with state-of-the-art (or near state-of-the-art) heuristics. The average disk space consumption of PEM-BAE^{*} for the 5x5 STP instances was 653GB, with a peak of 4TB. This underscores the impracticality of employing in-memory algorithms (such as A^{*} and BAE^{*}) for tackling these challenging problems.

5.3 4-peg Towers of Hanoi

In TOH4, we examined 20 random start and goal pairs with 20 disks, utilizing a 16+4 additive PDB heuristic [10]. In this domain, numerous cycles exist, posing a challenge for algorithms that lack duplicate detection, as already noted by Felner et al. [10]. This issue is



Figure 3. Distribution of node expansions **Figure 4.** Avg. runtime as a function of number **Figure 5.** Avg. nodes expanded per second; ^{*H*} indicates the hard instance with solution length of 184 of threads in 24-Puzzle hard instance in STP.

so severe that neither AIDA* nor rAIDA* could solve a single problem even after running for days. Consequently, we only compared PEM-BAE*, PEM-A*, PEM-rA*, and PEM-MM.

The results, presented in Figure 2, highlight a significant performance gap between PEM-BAE* and the other algorithms. On average, PEM-BAE* runs 7 times faster than its UniHS counterparts and expands a factor of 12.9 fewer nodes. Notably, PEMM was approximately 1.17 times slower than both PEM-A* and PEM-rA*, and it expanded more nodes than both of them.

5.4 Analyzing Previous Conjectures

In a previous analysis of bidirectional search [3], it was suggested that in a unidirectional search "if the majority [of nodes] are expanded at shallower depth than the solution midpoint $[C^*/2]$ then [...] a bidirectional heuristic search would expand more nodes than a unidirectional heuristic search.". The analysis for this claim predates our current understanding of BiHS. But, since we have the data it is worthwhile to evaluate the validity of this claim.

In this context, in our experiments we found that in 19 of 20 Towers of Hanoi instances and all 15-puzzle instances when using the PDB, the unidirectional algorithm (PEM-A^{*}) expanded the majority of states prior to the solution midpoint. Yet, in all of these problems PEM-BAE^{*} expanded fewer node than PEM-A^{*}. Thus, the previous analysis does not hold for PEM-BAE^{*} on these problems. This analysis for a representative ToH4 instance is presented in Figure 3. It is a matter for future work to analyze these claims in more depth and to consider whether or how to revise them to be more accurate.

5.5 Analyzing Expansion-per-second Ratios

The Table in Figure 5 presents the number of nodes expanded per second (NPS) by different PEM algorithms on the domains in which all PEM algorithms were evaluated, namely 15-STP and TOH4. While these algorithms differ in how they choose their search direction, decide on which bucket to expand, and terminate the search, these differences are not expected to significantly impact NPS. Two factors, however, have the potential to affect NPS. First, BiHS algorithms perform DSD, while UniHS algorithms perform ISD. DSD generally requires more computational effort, though a profiling analysis revealed that this additional time was negligible. Second, differences in bucket structure can affect the number of buckets and their sizes, affecting the I/O time of the algorithms. The results show significant variations in NPS among the algorithms. Despite its relative strength in nodes and in time, PEM-BAE* exhibited the worst (smallest) NPS overall, suggesting that an alternative bucket structure might further improve its advantages over the other algorithms.

5.6 Ablation Study on the Number of Threads

To assess the thread utilization of PEM-BAE^{*}, we compare its performance against AIDA^{*} on the 24-STP while varying number of threads. Specifically, we conducted experiments using 1, 16, 32, 48, 64, 80, and 96 (virtual) threads on a subset of problems (problems 4, 36, 45, 48) with an intermediate solution cost, $C^* = 100$.

Figure 4 shows average runtimes for various thread configurations, with a logarithmic *y*-axis. As observed previously, PEM-BAE* surpasses AIDA* performance with 96 threads and consistently outperforms it across varying thread counts. As anticipated, adding more threads yields diminishing returns. PEM-BAE* reduced its runtime by a factor of 11 when transitioning from 1 thread to 16 threads, whereas AIDA* improved by a factor of 7. Beyond 16 threads, runtime reduction becomes smaller, decreasing only by a factor of 2 for both algorithms when transitioning from 16 to 96 threads. This reduced gain can be attributed to memory access required for obtaining heuristic values, imbalanced subtrees and last-layer expansions for AIDA*, constrained I/O parallelization (relative to the thread count), imbalanced bucket sizes, and locking overhead for PEM-BiHS.

6 Conclusions and Future Work

We presented PEM-BiHS, a parallel external-memory (PEM) BiHS framework for single-target search in undirected, uniformly weighted search graphs, which was used to create a PEM variant of BAE* (PEM-BAE*). Our empirical evaluations show that PEM-BAE* outperforms UniHS algorithms both in runtime and node expansions, even with well-informed heuristics. These findings challenge the conjecture put forth by Barker and Korf [3], suggesting that BiHS algorithms would not significantly surpass UniHS or bidirectional brute-force search. Further theoretical study is necessary to analyze our results in relation to this conjecture, as well as to other theoretical comparisons between BiHS and UniHS algorithms [13, 37].

Future research could also address NPS differences among algorithms by exploring dynamic bucket sizes and other approaches that relax the best-first assumption, aiming to achieve more balanced buckets [12].

Acknowledgements

This work was supported by the Israel Science Foundation (ISF) grant #909/23 awarded to Shahaf Shperberg and Ariel Felner, by Israel's Ministry of Innovation, Science and Technology (MOST) grant #1001706842, awarded to Shahaf Shperberg, and by United States-Israel Binational Science Foundation (BSF) grant #2021643 awarded to Ariel Felner. This work was also partially funded by the Canada CIFAR AI Chairs Program. We acknowledge the support of

the National Sciences and Engineering Research Council of Canada (NSERC).

References

- V. Alcázar, P. J. Riddle, and M. Barley. A unifying view on individual bounds and heuristic inaccuracies in bidirectional search. In *The Thirty-Fourth Conference on Artificial Intelligence, AAAI 2020*, pages 2327– 2334, 2020.
- [2] D. Atzmon, S. S. Shperberg, N. Sabah, A. Felner, and N. R. Sturtevant. W-restrained bidirectional bounded-suboptimal heuristic search. In Proceedings of the Thirty-Third International Conference on Automated Planning and Scheduling, July 8-13, 2023, Prague, Czech Republic, pages 26–30, 2023.
- [3] J. K. Barker and R. E. Korf. Limitations of front-to-end bidirectional heuristic search. In Proceedings of the Twenty-Ninth Conference on Artificial Intelligence, AAAI, pages 1086–1092, 2015.
- [4] M. W. Barley, P. J. Riddle, C. L. López, S. Dobson, and I. Pohl. GBFHS: A generalized breadth-first heuristic search algorithm. In Proceedings of the Eleventh International Symposium on Combinatorial Search, SOCS, pages 28–36, 2018.
- [5] J. Chen, R. C. Holte, S. Zilles, and N. R. Sturtevant. Front-to-end bidirectional heuristic search with near-optimal node expansions. In Proceedings of the Twenty-Sixth International Joint Conference on Artificial Intelligence, IJCAI, pages 489–495, 2017.
- [6] R. Döbbelin, T. Schütt, and A. Reinefeld. Building large compressed PDBs for the sliding tile puzzle. In Computer Games: Workshop on Computer Games, CGW 2013, Held in Conjunction with the 23rd International Conference on Artificial Intelligence, IJCAI 2013, Beijing, China, August 3, 2013, Revised Selected Papers 2, pages 16–27. Springer, 2014.
- [7] J. Eckerle, J. Chen, N. R. Sturtevant, S. Zilles, and R. C. Holte. Sufficient conditions for node expansion in bidirectional heuristic search. In Proceedings of the Twenty-Seventh International Conference on Automated Planning and Scheduling, ICAPS, pages 79–87, 2017.
- [8] S. Edelkamp and S. Schrödl. *Heuristic Search Theory and Applica*tions, chapter Distributed Search. Academic Press, 2012.
- [9] S. Edelkamp, S. Jabbar, and S. Schrödl. External A*. In Annual Conference on Artificial Intelligence, pages 226–240. Springer, 2004.
- [10] A. Felner, R. E. Korf, and S. Hanan. Additive pattern database heuristics. J. Artif. Intell. Res., 22:279–318, 2004.
- [11] P. E. Hart, N. J. Nilsson, and B. Raphael. A Formal Basis for the Heuristic Determination of Minimum Cost Paths. *IEEE transactions on Systems Science and Cybernetics*, 4(2):100–107, 1968.
- [12] M. Hatem, E. Burns, and W. Ruml. Solving large problems with heuristic search: General-purpose parallel external-memory search. *Journal* of Artificial Intelligence Research, 62:233–268, 2018.
- [13] R. C. Holte, A. Felner, G. Sharon, N. R. Sturtevant, and J. Chen. MM: A bidirectional search algorithm that is guaranteed to meet in the middle. *Artif. Intell.*, 252:232–266, 2017.
- [14] S. Hu and N. R. Sturtevant. Direction-optimizing breadth-first search with external memory storage. *International Joint Conference on Artificial Intelligence (IJCAI)*, pages 1258–1264, 2019. URL https: //webdocs.cs.ualberta.ca/~nathanst/papers/DEBFS.pdf.
- [15] H. Kaindl and G. Kainz. Bidirectional heuristic search reconsidered. J. Artif. Intell. Res., 7:283–317, 1997.
- [16] R. É. Korf. Depth-first iterative-deepening: An optimal admissible tree search. Artif. Intell., 27(1):97–109, 1985.
- [17] R. E. Korf. Best-first frontier search with delayed duplicate detection. In Proceedings of the Nineteenth National Conference on Artificial Intelligence, AAAI, pages 650–657, 2004.
- [18] R. E. Korf. Linear-time disk-based implicit graph search. Journal of the ACM (JACM), 55(6):1–40, 2008.
- [19] R. E. Korf. Minimizing disk I/O in two-bit breadth-first search. In Proceedings of the Twenty-Third AAAI Conference on Artificial Intelligence, AAAI, pages 317–324, 2008.
- [20] R. E. Korf. Comparing search algorithms using sorting and hashing on disk and in memory. In *IJCAI*, pages 610–616, 2016.
- [21] R. E. Korf and A. Felner. Disjoint pattern database heuristics. Artif. Intell., 134(1-2):9–22, 2002.
- [22] R. E. Korf, W. Zhang, I. Thayer, and H. Hohwald. Frontier search. Journal of the ACM, 52(5):715–748, 2005.
- [23] D. Kunkle and G. Cooperman. Twenty-six moves suffice for rubik's cube. In Proceedings of the 2007 international symposium on Symbolic and algebraic computation, pages 235–242, 2007.
- [24] D. Kunkle and G. Cooperman. Solving rubik's cube: disk is the new RAM. Communications of the ACM, 51(4):31–33, 2008.

- [25] I. Pohl. Bi-directional search. Machine intelligence, 6:127-140, 1971.
- [26] A. Reinefeld and V. Schnecke. Work-load balancing in highly parallel depth-first search. In *Proceedings of IEEE scalable high performance computing conference*, pages 773–780. IEEE, 1994.
- [27] S. K. Sadhukhan. Bidirectional heuristic search based on error estimate. *CSI Journal of Computing*, 2(1-2):S1, 2013.
- [28] E. C. Sewell and S. H. Jacobson. Dynamically improved bounds bidirectional search. Artif. Intell., 291:103405, 2021.
- [29] E. Shaham, A. Felner, J. Chen, and N. R. Sturtevant. The minimal set of states that must be expanded in a front-to-end bidirectional search. In *Proceedings of the Tenth International Symposium on Combinatorial Search, SOCS*, pages 82–90, 2017.
- [30] S. S. Shperberg and A. Felner. On the differences and similarities of fMM and GBFHS. In *Proceedings of the Thirteenth International Symposium on Combinatorial Search, SOCS*, pages 66–74, 2020.
- [31] S. S. Shperberg, A. Felner, N. R. Sturtevant, S. E. Shimony, and A. Hayoun. Enriching non-parametric bidirectional search algorithms. In *The Thirty-Third AAAI Conference on Artificial Intelligence, AAAI*, pages 2379–2386, 2019.
- [32] S. S. Shperberg, S. Danishevski, A. Felner, and N. R. Sturtevant. Iterative-deepening bidirectional heuristic search with restricted memory. In *Proceedings of the Thirty-First International Conference on Automated Planning and Scheduling, ICAPS*, pages 331–339, 2021.
- [33] L. Siag, S. Shperberg, A. Felner, and N. Sturtevant. Front-to-end bidirectional heuristic search with consistent heuristics: enumerating and evaluating algorithms and bounds. In *Proceedings of the Thirty-Second International Joint Conference on Artificial Intelligence, IJCAI*, pages 5631–5638, 2023.
- [34] L. Siag, S. Shperberg, A. Felner, and N. R. Sturtevant. Comparing frontto-front and front-to-end heuristics in bidirectional search. In *Proceedings of the International Symposium on Combinatorial Search, SoCS*, volume 16, pages 158–162, 2023.
- [35] N. R. Sturtevant and J. Chen. External memory bidirectional search. In Proceedings of the Twenty-Fifth International Joint Conference on Artificial Intelligence, IJCAI, pages 676–682, 2016.
- [36] N. R. Sturtevant and M. J. Rutherford. Minimizing writes in parallel external memory search. In *IJCAI*, pages 666–673. IJCAI/AAAI, 2013.
- [37] N. R. Sturtevant, S. S. Shperberg, A. Felner, and J. Chen. Predicting the effectiveness of bidirectional heuristic search. In *ICAPS*, pages 281– 290. AAAI Press, 2020.
- [38] Á. Torralba, V. Alcázar, P. Kissmann, and S. Edelkamp. Efficient symbolic search for cost-optimal planning. *Artif. Intell.*, 242:52–79, 2017.
- [39] R. Zhou and E. Hansen. Dynamic state-space partitioning in externalmemory graph search. In *Proceedings of the International Conference* on Automated Planning and Scheduling, volume 21, pages 290–297, 2011.
- [40] R. Zhou and E. A. Hansen. Structured duplicate detection in externalmemory graph search. In *Proceedings of the Nineteenth National Conference on Artificial Intelligence, AAAI*, pages 683–689, 2004.
- [41] R. Zhou and E. A. Hansen. Parallel structured duplicate detection. In AAAI, pages 1217–1224, 2007.

A Code

The code of the paper was uploaded to GitHub and can be found here: https://github.com/SPL-BGU/PEM-BiHS

B Results Tables

Tables 2, 3, and 4 present the full results summarized in the paper for 24-Sliding Tile Puzzle and 4-Peg Towers of Hanoi respectivley. The 24-STP instances match the instances described in Table 2 of Korf [21]. The ToH instances correspond to random ones generated (a full list appears in the code repo). The columns include the following: instance number, the algorithm executed, the number of nodes expanded, the number of nodes generated, time in seconds, and the solution cost.

Instance	Algorithm	Expanded	Generated	Elapsed	Solution
0	PEM-BAE*	69,230,832	220,879,373	48	95
0	AIDA*	703,361,151	2,230,288,795	60	95
0	rAIDA*	298,891,181	962,050,469	21	95
1	PEM-BAE*	4,268,907,890	13,630,651,253	1,994	96
1	AIDA*	106,013,766,980	341,876,855,982	15,411	96
1	rAIDA*	11,115,669,857	35,192,151,412	1,383	96
2	PEM-BAE*	1,881,452,125	6,079,830,316	870	97
2	AIDA*	15,497,174,429	50,045,721,079	2,207	97
2	rAIDA*	118,194,520,400	386,919,173,185	8,559	97
3	PEM-BAE*	486,925,192	1,564,458,403	241	98
3	AIDA*	10,499,950,390	34,166,927,429	916	98
3	rAIDA*	8,355,167,278	26,527,013,652	647	98
4	PEM-BAE*	562,259,551	1,784,446,623	266	100
4	AIDA*	6,251,407,352	19,828,603,739	429	100
4	rAIDA*	4,829,480,771	15,612,945,465	404	100
5	PEM-BAE*	3,060,348,563	9,778,084,836	1,408	101
5	AIDA*	39,804,885,473	127,574,030,552	4,617	101
3	TAIDA*	2 6 4 5 6 6 5 6 2 0	402,272,005,008	1,343	101
6	PEM-DAE*	2,043,003,030	6,465,295,970 272 142 756 065	6.424	104
6	rAIDA*	60 732 574 150	272,142,750,905	5.088	104
7	PEM-BAE*	6 341 150 974	20 222 934 040	2 922	104
7	AIDA*	25 961 585 022	82 385 607 008	6 254	108
7	rAIDA*	133.373.261.394	427.651.175.162	13,143	108
8	PEM-BAE*	27 212 933 333	86 599 962 301	13 504	113
8	AIDA*	776.302.510.731	2.460.969.417.979	59,157	113
8	rAIDA*	1,779,553,689,438	5.629.539.624.191	189,967	113
9	PEM-BAE*	84.643.679.974	268,176,125,953	47,688	114
9	AIDA*	1,063,877,057,715	3,330,671,280,447	91,349	114
9	rAIDA*	6,341,997,459,809	19,959,427,954,921	409,236	114
10	PEM-BAE*	22,043,034,863	70,424,617,713	10,265	106
10	AIDA*	1,790,268,187,428	5,712,762,291,643	163,722	106
10	rAIDA*	338,961,713,914	1,064,576,618,761	25,734	106
11	PEM-BAE*	7,166,972,315	22,552,629,538	3,292	109
11	AIDA*	163,240,926,083	513,056,203,546	15,620	109
11	rAIDA*	17,864,928,517	55,236,406,222	1,047	109
12	PEM-BAE*	810,360,812	2,560,814,092	372	101
12	AIDA*	3,326,240,519	10,389,525,447	261	101
12	rAIDA*	5,363,614,647	17,014,790,519	562	101
13	PEM-BAE*	15,722,616,097	50,530,082,815	7,416	111
13	AIDA*	610,358,362,103	1,974,350,435,375	73,723	111
13	rAIDA*	237,342,857,210	748,028,335,178	17,874	111
14	PEM-BAE*	6,546,441,457	21,088,442,538	3,245	103
14	AIDA*	121,/32,030,000	394,521,427,843	13,083	103
14	TAIDA*	90,099,314,702	1 640 287 410	0,081	105
15	PEM-DAE*	2 210 852 570	7 100 620 820	230	90
15	rAIDA*	12 104 008 103	30 207 380 078	1 1 1 1 8	90
15	DEM BAE*	21 572 731 051	67 876 835 431	0 703	100
16		431 775 179 640	1 355 237 512 487	47 360	109
16	rAIDA*	210 983 589 712	655 921 859 058	14 793	109
17	PEM-BAE*	39.843.274.192	126.680.194.817	18,998	110
17	AIDA*	442,310,527,540	1.398,526,796,413	31.757	110
17	rAIDA*	2,374,565,687,766	7,512,383,106.222	186,946	110
18	PEM-BAE*	10,121,572,991	31,893,504.326	4,404	106
18	AIDA*	132,965,680,106	413,222,129,725	9,021	106
18	rAIDA*	76,199,307,271	241,731,795,548	4,883	106
19	PEM-BAE*	1,334,088,442	4,267,729,893	584	92
19	AIDA*	67,664,490,886	215,174,841,090	6,093	92
19	rAIDA*	1.110.753.209	3.615.804.097	83	92

Table 2.24-STP Instances 0-20

Instance	Algorithm	Expanded	Generated	Elapsed	Solution
20	PEM-BAE*	9,527,278,036	30,356,569,236	4,188	103
20	AIDA*	565,380,369,670	1,795,962,930,341	38,295	103
20	rAIDA*	78,458,996,064	249,254,041,120	4,581	103
21	PEM-BAE*	214,615,450	686,779,942	110	95
21	AIDA*	963,175,022	3,112,348,975	78	95
21	rAIDA*	1,135,413,445	3,640,912,326	70	95
22	PEM-BAE*	4,029,225,810	12,910,448,751	1,734	104
22	AIDA*	80,547,390,480	257,197,389,109	11,128	104
22	rAIDA*	18.303.074.822	58,970,515,060	1.181	104
23	PEM-BAE*	8 301 166 057	26 225 686 035	3 704	107
23		169 310 755 886	530 726 996 648	21 803	107
23	rAIDA*	109,510,755,000	632 052 577 237	13 028	107
23	DEM DAE*	65 909 216	214 250 822	15,920	81
24	FEWI-DAE	224 092 920	214,239,022	47	01
24	AIDA	2,34,062,629	11 210 (02 000	470	01
24	rAIDA*	3,415,426,809	11,218,683,998	4/8	81
25	PEM-BAE*	3,002,690,414	9,462,022,810	1,245	105
25	AIDA*	4,776,563,020	14,967,139,880	370	105
25	rAIDA*	13,621,337,969	42,579,832,339	791	105
26	PEM-BAE*	1,043,423,515	3,322,959,911	468	99
26	AIDA*	20,621,200,744	66,416,950,731	2,212	99
26	rAIDA*	3,463,364,779	10,900,612,650	221	99
27	PEM-BAE*	352,497,075	1,125,759,542	165	98
27	AIDA*	623,798,323	2,005,600,613	44	98
27	rAIDA*	3,597,787,376	11,382,223,685	234	98
28	PEM-BAE*	547,971,940	1,764,505,585	264	88
28	AIDA*	3,786,487,784	12.224.161.369	254	88
28	rAIDA*	8.692.306.706	27,879,346,477	584	88
29	PEM-BAE*	335 757 077	1 077 689 262	172	92
20	AIDA*	581 364 286	1,854,619,108	90	02
29	rAIDA*	2 696 888 415	8 740 333 614	328	92
30	DEM DAE*	2,020,000,413	7 141 272 421	1 014	92
30	rewi-BAE*	2,229,244,202	106.007.242.215	1,014	99
30	AIDA*	33,327,387,471	106,997,263,315	2,511	99
30	rAIDA*	131,207,748,664	417,547,549,017	9,892	99
31	PEM-BAE*	165,410,379	534,243,911	97	97
31	AIDA*	943,787,432	3,057,123,999	81	97
31	rAIDA*	24,385,419,169	79,050,507,238	1,682	97
32	PEM-BAE*	35,763,541,684	115,037,007,664	16,898	106
32	AIDA*	312,137,711,728	997,185,135,000	29,195	106
32	rAIDA*	2,491,371,346,301	7,990,457,375,484	234,616	106
33	PEM-BAE*	8,414,844,647	26,920,078,806	3,792	102
33	AIDA*	46.451.633.545	147.871.894.613	3.886	102
33	rAIDA*	182.236.486.186	581,410,425,737	14.892	102
34	PEM-BAE*	1 741 485 012	5 583 334 380	760	98
34		40 024 395 290	128 437 310 919	4 911	98
24	rAIDA*	5 277 202 444	16 961 902 050	225	08
25	DEM DAE*	140.062.216	451 722 001	94	00
33	PENI-DAE*	140,002,510	451,725,901	64	90
35	AIDA*	499,903,906	1,001,017,848	62	90
33	TAIDA*	541,595,075	1,097,795,800	23	90
36	PEM-BAE*	495,304,641	1,594,666,052	240	100
36	AIDA*	2,698,159,455	8,677,615,693	222	100
36	rAIDA*	20,062,621,118	64,712,694,760	1,516	100
37	PEM-BAE*	42,448,377	133,974,933	36	96
37	AIDA*	176,088,934	555,352,440	14	96
37	rAIDA*	215,908,715	681,002,670	19	96
38	PEM-BAE*	14,628,451,144	46,816,491,293	6,456	104
38	AIDA*	240,449,464,103	771,787,649,108	21,090	104
38	rAIDA*	297,309,206,780	952,751,563,739	16,566	104
39	PEM-BAE*	15.247.477	49.575.653	21	82
39	AIDA*	16.659.387	54,193,955	2	82
39	rAIDA*	23,765,362	77.316.278	3	82
40	PEM-BAE*	665 359 298	2 111 896 270	305	106
40	AIDA*	27 310 752 272	87 441 169 355	2 350	106
40	rAIDA*	3 356 750 072	10 588 713 001	2,550	100
41	PEM_RAE*	9 18/ 707 007	20 102 002 221	4 300	100
41	AIDA*	1/13/1/2 100 702	450 500 270 007	4,500	108
41	rAIDA*	248 400 162 021	787 805 271 124	20 400	108
41	DEM DAE*	2 260 156 617	10 562 674 994	1 446	108
42	AIDA*	42 701 120 701	10,000,074,004	1,440	104
42	AIDA*	42,/01,129,/81	101 670 000 260	5,105	104
42	rAIDA*	01,0/5,010,8/8	191,070,808,269	5,384	104
43	PEM-BAE*	27,655,526	86,783,847	26	93
43	AIDA*	424,991,002	1,342,993,964	87	93
43	rAIDA*	41,147,319	128,315,339	6	93
44	PEM-BAE*	2,564,119,144	8,196,575,888	1,117	101
44	AIDA*	27,292,984,883	86,492,573,883	3,107	101
44	rAIDA*	12,585,530,174	40,235,026,931	757	101
45	PEM-BAE*	3,343,626,420	10,731,780,830	1,479	100
45	AIDA*	40,044,217,948	128,274,186,070	8,035	100
45	rAIDA*	127,779,500,497	411,479,697,811	10,877	100
46	PEM-BAE*	352,424,217	1,137,139,590	179	92
46	AIDA*	9,865,063.039	31,738,097.602	1,534	92
46	rAIDA*	521.478.728	1,689.254.936	49	92
47	PEM-BAE*	17.429 341 353	55,807 506 350	8 030	107
47	AIDA*	283,715 030 330	911.965 768 598	21 557	107
47	rAIDA*	243,995 327 026	773,713 951 124	14.068	107
48	PEM-RAF*	2 791 739 131	8 937 517 9/2	1 180	100
48		45 208 243 509	144 973 407 202	4 080	100
+0	rAIDA*	45,208,245,508	84 645 054 660	4,089	100
+0	DEM DAE*	20,404,070,323	04,043,934,009	1,070	100
49	rewi-BAE*	44,000,338,130	141,194,804,106	20,222	113
49	AIDA*	2,233,230,313,124	1,127,089,799,036	25 202	113
47	TAIDA"	344,477,410,329	1,077,370,140,431	20,595	113

 Table 3.
 24-STP Instances 20-50

Instance	Algorithm	Expanded	Generated	Elapsed	Solution
0	PEM-BAE*	11,402,376	68,414,256	167	127
0	PEM-MM	113,477,535	680,865,200	369	127
0	PEM-A*	96,251,817	577,510,898	111	127
1	PEM-IA ⁺ PEM-BAE*	25 775 736	154 654 416	200	127
1	PEM-MM	351.046.537	2.106.279.222	567	134
1	PEM-A*	363,462,637	2,180,775,804	403	134
1	PEM-rA*	331,575,951	1,989,455,675	365	134
2	PEM-BAE*	221,402,494	1,328,413,066	680	196
2	PEM-MM	3,065,812,530	18,394,856,344	3,566	196
2	PEM-A*	2,266,947,910	13,001,008,477	2,756	196
3	PEM-BAE*	875 748 652	5 254 491 321	1 407	226
3	PEM-MM	17.627.193.887	105.763.116.151	19.716	226
3	PEM-A*	15,257,726,280	91,546,318,447	19,595	226
3	PEM-rA*	18,694,559,963	112,167,326,767	24,084	226
4	PEM-BAE*	427,190,546	2,563,142,872	908	210
4	PEM-MM	7,205,812,198	43,234,848,104	7,584	210
4	PEM-A* DEM +A*	4,005,098,179	24,034,172,187	4,700	210
5	PEM-BAF*	146 546 097	879 276 416	480	194
5	PEM-MM	2,690,832,340	16,144,991,560	3.020	194
5	PEM-A*	1,662,774,594	9,976,645,755	1,956	194
5	PEM-rA*	1,720,710,614	10,324,262,888	1,978	194
6	PEM-BAE*	396,001,541	2,376,007,755	796	209
6	PEM-MM	6,952,068,090	41,712,369,788	7,319	209
6	PEM-A*	5,467,395,121	32,804,351,175	0,/51	209
7	PEM-IA ⁺	302 449 443	1 814 603 233	4,237	209
7	PEM-MM	5 473 929 538	32 843 536 479	5 812	208
7	PEM-A*	3,668,644,117	22,011,830,694	4,426	208
7	PEM-rA*	3,530,151,234	21,180,889,797	4,241	208
8	PEM-BAE*	879,254,053	5,275,495,463	1,486	231
8	PEM-MM	11,786,153,720	70,716,724,653	13,013	231
8	PEM-A*	8,556,073,364	51,336,276,445	10,663	231
0	PEM-BAE*	37 081 001	227 801 045	260	155
9	PEM-MM	481 198 567	2 887 191 276	802	155
9	PEM-A*	448,034,637	2,688,207,607	510	155
9	PEM-rA*	228,474,350	1,370,846,061	252	155
10	PEM-BAE*	154,672,578	928,035,264	532	184
10	PEM-MM	2,283,285,317	13,699,688,562	2,700	184
10	PEM-A*	1,896,591,734	6 401 553 672	2,275	184
10	PEM-BAF*	173 190 498	1 039 142 833	513	104
11	PEM-MM	3.476.195.799	20.857.156.385	3.788	190
11	PEM-A*	2,013,246,081	12,079,473,280	2,399	190
11	PEM-rA*	2,087,343,968	12,524,048,476	2,480	190
12	PEM-BAE*	490,313,689	2,941,880,692	929	209
12	PEM-MM	6,302,878,412	37,817,233,326	6,695	209
12	PEM-A* DEM +A*	3,279,998,033	31,0/9,902,790	0,541	209
12	PEM-BAE*	265 428 652	1 592 570 397	648	190
13	PEM-MM	4,039,716,079	24,238,274,622	4,363	190
13	PEM-A*	3,480,192,849	20,881,150,573	4,176	190
13	PEM-rA*	2,753,420,297	16,520,494,513	3,287	190
14	PEM-BAE*	19,924,463	119,546,778	155	133
14	PEM-MM	243,416,450	1,460,498,700	440	133
14	PEM-rA*	175 698 215	1 054 189 290	198	133
15	PEM-BAE*	218.669.651	1.312.017.745	644	195
15	PEM-MM	3,229,210,445	19,375,253,326	3,640	194
15	PEM-A*	1,998,734,210	11,992,404,448	2,348	194
15	PEM-rA*	2,039,686,344	12,238,108,147	2,436	194
16	PEM-BAE*	229,045,224	1,374,271,197	634	189
16	PEM-MM	3,788,714,202	22,732,279,620	4,095	189
16	PEM-rA*	2 821 803 598	20,043,710,783	4,140	189
17	PEM-BAE*	54,740.919	328,445,513	348	177
17	PEM-MM	952,740,416	5,716,442,305	1,374	177
17	PEM-A*	669,377,980	4,016,267,799	758	177
17	PEM-rA*	563,424,177	3,380,544,791	629	177
18	PEM-BAE*	367,828,352	2,206,969,889	822	201
18	PEM-MM DEM A*	7,145,353,473	42,872,111,738	7,391	201
10	reivi-A* PEM-ra*	6 231 287 375	42,733,831,340	0,709 7 587	201 201
19	PEM-BAE*	604,182.452	3.625.082.948	1.065	219
19	PEM-MM	11,314,109,761	67,884,576,473	12,139	219
19	PEM-A*	6,979,257,042	41,875,500,224	8,643	219
19	PEM-rA*	9,368,016,548	56,208,049,256	11,771	219

 Table 4.
 TOH Instances