AdvAnchor: Enhancing Diffusion Model Unlearning with Adversarial Anchors

Mengnan Zhao, Lihe Zhang, Xingyi Yang, Tianhang Zheng, Baocai Yin

Abstract

Security concerns surrounding text-to-image diffusion models have driven researchers to unlearn inappropriate concepts through fine-tuning. Recent fine-tuning methods typically align the prediction distributions of unsafe prompts with those of predefined text anchors. However, these techniques exhibit a considerable performance trade-off between eliminating undesirable concepts and preserving other concepts. In this paper, we systematically analyze the impact of diverse text anchors on unlearning performance. Guided by this analysis, we propose AdvAnchor, a novel approach that generates adversarial anchors to alleviate the trade-off issue. These adversarial anchors are crafted to closely resemble the embeddings of undesirable concepts to maintain overall model performance, while selectively excluding defining attributes of these concepts for effective erasure. Extensive experiments demonstrate that AdvAnchor outperforms state-of-the-art methods. Our code is publicly available at https://anonymous.4open. science/r/AdvAnchor.

1. Introduction

Text-guided diffusion models (DMs) have garnered significant interest in the research community for their ability to generate high-fidelity images [14, 39] and their widespread applications like medical image reconstruction [20, 42], creative arts [24], and material generation [2, 22, 43]. However, these models also encounter critical security concerns, such as harmful content generation [30] and potential copyright infringement [34]. Furthermore, retraining safe DMs is challenging due to the extensive data cleaning, the high training resource consumption, and the unpredictable effects of training data on model predictions.

To remove unsafe behaviors from DMs without retraining, researchers are increasingly exploring Machine Unlearning (MU) techniques. A prominent MU approach directly fine-tunes the weights of pre-trained DMs [8], often by minimizing the prediction differences between text anchors (pre-defined target prompts) and prompts containing unsafe concepts [9, 44]. For instance, to erase the '*Van Gogh*' style, Abconcept [23] adjusts the cross-attention



Figure 1. Overview of the proposed AdvAnchor. To construct adversarial anchors, tiny adversarial perturbations that greatly affect the generation performance of DMs on '*Van Gogh*' are added to the embeddings of '*Van Gogh*'. θ_{op} is fine-tuned by aligning the prediction distributions of e_{ori} with those of e_{anchor} .

module weights in DMs to enhance prediction consistency between predefined prompt pairs, such as "A picture of a painting" and "A picture of a *Van Gogh's* painting".

While recent MU methods effectively erase undesirable concepts from pre-trained DMs, they often significantly compromise the overall generation quality of models. For instance, after erasing the '*Cezanne*' style with Abconcept, the model struggles to yield images in the styles of '*Van Gogh*' or '*Picasso*'. Inspired by prior works [8, 21] that utilize different anchors to fine-tune model weights, we naturally raise a key question: *How does anchor selection influence DM unlearning, and could performance be enhanced through improved anchor crafting*?

To answer this question, we conduct a systematic experimental analysis on the impact of anchors in DM unlearning. Our findings have twofold: 1) Anchors that closely resemble the undesirable concept are more effective in preserving overall model performance; 2) Effective erasure occurs when anchors omit the defining attributes of the undesirable concept. Namely, for effective erasure with minimal impact on model performance, ideal anchors should approximate the undesirable concept yet exclude its defining attributes.

Based on our analyses and prior studies (tiny adversar-

ial perturbations can substantially affect model predictions [10, 48]), we introduce AdvAnchor, a simple yet effective adversarial anchoring method for DMs. AdvAnchor creates adversarial anchors by adding crafted universal perturbations to the embeddings of undesirable concepts. These perturbations, guided by the proposed similarity losses and optimization strategies, aim to degrade the generation quality of undesirable concepts across any visual input, thereby removing defining attributes of these concepts. Notably, the adversarial anchors are versatile and can be integrated into various MU techniques, such as the alignment mechanism in Abconcept. The AdvAnchor pipeline is shown in Fig. 1.

Our contributions are three-fold: (1) We conduct a systematic analysis of anchor impact on DM unlearning, revealing that for effective concept erasure with minimal impact on model performance, ideal anchors should maintain semantic similarity to the undesirable concept while excluding its defining attributes. (2) Based on this insight, we propose AdvAnchor, a simple yet effective method that generates adversarial anchors using designed loss constraints and optimization strategies. (3) Extensive experiments demonstrate that AdvAnchor significantly enhances both erasure and preservation performance in DM unlearning.

2. Related work

Recent advancements in text-to-image generation [31, 50], especially with the emergence of DMs [32, 33], have drastically improved the quality of high-resolution image generation [19, 37]. However, these developments also raise security issues [38], such as the dissemination of NSFW materials [25, 40] and copyright infringement [36]. To mitigate these risks, the MU fine-tuning technique [4, 7, 11] has been proposed to eliminate specific concepts from pretrained models. In this work, we focus on the DM unlearning task. Figure 2 illustrates the denoising process in textguided DMs, which consists of two-steps: introducing noise to convert the data distribution into a Gaussian distribution, followed by denoising to restore the original distribution.

Several advanced MU techniques have been developed for DMs. For instance, Forget-Me-Not [44] eliminates undesirable concepts by decreasing the attention map values associated with these concepts. GEOM [25] introduces implicit concept erasure, focusing on removing concepts that cannot be controlled through pre-defined text prompts. P4D [6] and UnlearnDiff [46] evaluate the robustness of unlearning approaches by generating adversarial text prompts [47]. Receler [18] improves the erasing robustness by introducing an adversarial learning strategy, *i.e.*, expanding the training data with adversarial soft prompts.

Particularly, depending on whether the network structure is modified, DM unlearning techniques can be categorized into adaptor-based and adaptor-free approaches. The former modifies the DM structure by introducing adaptor lay-



Figure 2. The denoising process of text-guided DMs. a) the encoder converts the input noise into latent representations \boldsymbol{x}_{T} ; b) the denoiser iteratively removes the predicted noise $\boldsymbol{\epsilon}_{t \in [1,N]}$ from latent representations \boldsymbol{x}_{t}^{c} ; c) the decoder reconstructs the image from the denoised representations \boldsymbol{x}_{0}^{c} .

ers, learning only their weights. For instance, SPM [27] constructs lightweight one-dimensional adapters [6, 29] and MACE [26] integrates multiple non-interfering LoRA modules [17]. In contrast, the latter directly updates the module weights in original DMs. For example, ESD [8] and Abconcept [23] fine-tune cross-attention modules, while SepME [49] restricts weight modifications to image-independent layers. Our approach follows the adaptor-free paradigm, *i.e.*, fine-tuning the cross-attention modules of DMs.

In this paradigm, researchers generally align the prediction distributions for undesirable concepts with those for predefined anchors. For instance, SDD [21] employs an empty prompt as the anchor for all undesirable concepts. Abconcept utilizes broader concepts compared to undesirable concepts as anchors. ESD uses both the undesirable concept and the empty prompt to create anchors. UCE [9] generates anchors based on a weighted combination of various text prompts, aiming to address generation bias. Allbut-one [15] presents a Prompt-to-Prompt erasing technique that employs the highest and lowest embedding values of target prompts [5] to construct anchors. Unlike these methods that combine predefined text prompts to build anchors, this paper systematically explores the anchor impact on unlearning performance and introduces adversarial anchors.

3. Proposed method

In this section, we first explore the impact of anchors on DM unlearning. Then, we introduce the proposed AdvAnchor.

3.1. Impact of various anchors on DM unlearning

We follow previous unlearning approaches [8, 21] to conduct this research, *i.e.*, the undesirable concept c_u is erased from DMs by minimizing the prediction difference between p_u and p_{anchor} . Here, p_u is a prompt containing c_u and p_{anchor} denotes a target prompt.

$$\min_{\boldsymbol{\theta}_{op}} \mathcal{L}_{op} = \|f_{de}(\boldsymbol{x}_t, \boldsymbol{e}_{pu}; \boldsymbol{\theta}_{op}) - f_{de}(\boldsymbol{x}_t, \boldsymbol{e}_{anchor}; \boldsymbol{\theta}_{ori})\|_2,$$
(1)

where θ_{op} denotes the optimizable model weights for unlearning. $f_{de}(\cdot)$ means the denoiser in Fig. 2. x_t represents



Figure 3. Impact of using various types of words as anchors (p_{anchor}^{word}) on DM unlearning.

the latent representations of inputs at the timestamp t, which can be obtained through either the diffusion process [8] or the sampling process [23]. e_{pu} and e_{anchor} are text embeddings of prompts p_u and p_{anchor} , respectively. θ_{ori} refers to the fixed weights of original models. $\|\cdot\|_2$ is the ℓ_2 norm.

3.1.1. Anchors

We use various types of p_u and p_{anchor} , detailed as follows:

1) Each anchor is designated as a word, denoted p_{anchor}^{word} , with $p_u = c_u$. ChatGPT [1] is used to determine the anchor for c_u , with potential input prompts structured as follows:

- The closest type to c_u ;
- The type imitated by c_u ;
- The parent class of c_u ;
- The type least similar to c_u .

2) We embed p_{anchor}^{word} and c_u into a masked sentence to construct p_{anchor}^{mask} and p_u , respectively. For instance, when removing an artist style from DMs, p_{anchor}^{mask} and p_u can be denoted as "A picture of a $\{p_{anchor}^{word}\}$'s painting" and "A picture of a $\{c_u\}$'s painting", respectively.

3) We prepend a same long sentence to p_{anchor}^{word} and c_u , to construct p_{anchor}^{long} and p_u , respectively. For example, when erasing the 'Van Gogh' style, the prompt for ChatGPT to generate this long sentence might be:

- Provide a long sentence that describes an artistic style except for 'Van Gogh'.

4) We utilize a descriptive sentence as an anchor, called as $p_{\text{anchor}}^{\text{desc}}$, and $p_{\text{u}} = c_{\text{u}}$. For instance, when erasing an object

category, the prompt for ChatGPT may be

 $p_{anchor}^{desc_1}$: Provide a sentence that describes the morphological features of p_{anchor}^{word} . This sentence should include the common attributes between p_{anchor}^{word} and c_u .

 $p_{anchor}^{desc.2}$: { $p_{anchor}^{desc.1}$ }, while excluding defining features of c_u .

3.1.2. Settings

Evaluation metrics. 1) We use Fréchet Inception Distance (FID) [13] to measure the distance between images generated with the undesirable concept and the corresponding anchor; 2) Accuracy (ACC): For object classification, we use a pre-trained ResNet50 [12]. For style classification, we finetune the fully connected layer of a pre-trained ResNet18 [12] on a dataset generated by original DMs. This dataset includes a blank prompt and nine artist styles: *Cezanne, Van Gogh, Picasso, Jackson Pollock, Caravaggio, Keith Haring, Kelly McKernan, Tyler Edlin*, and *Kilian Eng*.

Evaluation data. 1) Erasure: Generate 1,000 images per undesirable concept, with 200 seeds per concept and 5 images per seed. 2) Object preservation: Generate 1,859 images with prompts from 1,000 categories in the ImageNet dataset¹. 3) Style preservation: Generate 2,000 images with the retained styles as prompts (excluding the erased one), with 50 seeds per style and 5 images per seed.

Others. Under identical settings, models from multiple fine-tuning processes exhibit notable performance variation.

https://github.com/rohitgandikota/erasing



Figure 4. Ablation studies on the length of the shared sentence between p_{anchor} and p_u in DM unlearning.

Hence, we report the average evaluation results over three independent fine-tuning runs for each undesirable concept.

3.1.3. Observations

The observations are as follows:

- -01 A higher similarity between p_{anchor}^{word} and c_u often results in better preservation performance, as shown in Fig. 3.
- -o2 A longer shared sentence between p_{anchor} and p_u generally leads to better preservation performance, as demonstrated in Fig. 4, which compares the results for p_{anchor} set to p^{word}_{anchor}, p^{mask}_{anchor}, and p^{long}_{anchor}.
 -o3 Unlearning with p^{desc.2}_{anchor} usually achieves superior era-
- -o3 Unlearning with $p_{anchor}^{desc.2}$ usually achieves superior erasure and preservation performance than other variants, as illustrated in Fig. 5.

Additional experiments supporting these observations are provided in the Appendix. We can conclude that:

- To preserve overall model performance, e_{anchor} and e_{pu} should retain high similarity (Observations o1 and o2).
- Undesirable concepts can be erased by excluding their defining attributes from anchors (Observation o3).

3.2. Proposed AdvAnchor

Inspired by prior studies that tiny adversarial perturbations can significantly affect model predictions [28, 41], and by our conclusions, we propose AdvAnchor to generate adversarial anchors for DM unlearning. Specifically, as the text space is discrete, AdvAnchor fine-tunes the undesirable concept c_u in the embedding space to generate adversarial anchors e_{anchor}^{adv} . The *i*-th feature element of e_{anchor}^{adv} is expressed as

$$e_{\text{anchor},i}^{\text{adv}} = \begin{cases} e_{\text{pu},i} + e_{\text{adv}} & \text{if } e_{\text{pu},i} = e_{\text{u}} \\ e_{\text{pu},i} & \text{otherwise}, \end{cases}$$

where e_{pu} and e_u denote the text embeddings of p_u and c_u , respectively. Since e_u remains fixed during erasure, we designate e_{adv} as a universal perturbation.

To exclude defining attributes of undesirable concepts from e_{anchor}^{adv} , given the ground truth images x_{gt} of undesirable concepts and the random noise z, we produce e_{adv} by

$$\max_{\boldsymbol{e}_{\text{adv}}} \|f_{\text{DM}}(\boldsymbol{z}, \boldsymbol{e}_{\text{anchor}}^{\text{adv}}; \boldsymbol{\theta}_{\text{ori}}) - \boldsymbol{x}_{\text{gt}}\|_{2}, \quad (2)$$

where f_{DM} denotes a pre-trained DM with fixed weights θ_{ori} . Eq. (2) aims to degrade the generation quality of undesirable concepts across any visual input. To influence the full denoising process with e_{adv} , we reformulate Eq. (2) as:

$$\max_{\boldsymbol{e}_{adv}} [\mathcal{L}_{adv}(f_{de}(\boldsymbol{x}_t, \boldsymbol{e}_{anchor}^{adv}; \boldsymbol{\theta}_{ori}), f_{de}(\boldsymbol{x}_t, \boldsymbol{e}_{pu}; \boldsymbol{\theta}_{ori}))], \quad (3)$$

where $f_{de}(\boldsymbol{x}_t, \boldsymbol{e}_{pu}; \boldsymbol{\theta}_{ori})$ acts as the pseudo target. We design two functions for \mathcal{L}_{adv} : \mathcal{L}_{adv1} , which measures the cosine similarity between model predictions for $\boldsymbol{e}_{adv}^{adv}$ and \boldsymbol{e}_{pu} ,

$$\max_{\boldsymbol{e}_{adv}} [-\cos(f_{de}(\boldsymbol{x}_t, \boldsymbol{e}_{anchor}^{adv}, \boldsymbol{\theta}_{ori}), f_{de}(\boldsymbol{x}_t, \boldsymbol{e}_{pu}, \boldsymbol{\theta}_{ori}))],$$



Figure 5. Comparative experiments using p_{anchor}^{word} and p_{anchor}^{desc}

and \mathcal{L}_{adv2} , which measures the similarity between generation changes $g_c(\cdot)$ caused by e_{anchor}^{adv} and e_{pu} :

$$egin{aligned} &\max_{oldsymbol{e}_{ ext{adv}}}[-\cos(g_c(oldsymbol{e}_{ ext{anchor}}),g_c(oldsymbol{e}_{ ext{pu}}))], \ &g_c(oldsymbol{e}) = f_{ ext{de}}(oldsymbol{x}_t,oldsymbol{e},oldsymbol{ heta}_{ ext{orig}}) - f_{ ext{de}}(oldsymbol{x}_t,oldsymbol{e}_{ ext{orig}},oldsymbol{ heta}_{ ext{orig}}). \end{aligned}$$

Inspired by vector orthogonality, we set $\mathcal{L}_{adv}(\cdot) = 0$ as the stopping criterion for optimizing e_{adv} . The generated e_{anchor}^{adv} can be easily integrated into various unlearning techniques by replacing predefined anchors, such as e_{anchor} in Eq. (1). Furthermore, we design alternating, sequential, and cyclical optimization strategies to update θ_{op} and e_{adv} :

- Alternating optimization: We alternately update e_{adv} and θ_{op} with various inputs. For each input x_t , we stop optimizing e_{adv} in Eq. (3) when $\mathcal{L}_{adv}(\cdot) = 0$, and then finetune θ_{op} using the current e_{adv} and x_t .
- Sequential optimization: We first construct the final e_{adv} using various inputs, and then fine-tune θ_{op} with the final e_{adv} across these inputs. Each input is *repeatedly* used to update e_{adv} until the stopping criterion is met.
- *Cyclical optimization:* In contrast to sequential optimization, each input is revisited in *cycles* to update e_{adv} until the stopping criterion is met.

Algorithm 1 presents the details of AdvAnchor using the alternating optimization strategy.

4. Experiments

4.1. Experimental Details

Following existing works [8, 21], we conduct experiments using Stable Diffusion [33]. By default, we utilize the stable-diffusion-v-1-4 version. The Adam optimizer is used with a learning rate of 1e-5 for optimizing θ_{op} , and 1e-4 for adjusting e_{adv} . For constructing adversarial anchors, we apply the alternating optimization strategy with a maximum of 30 iterations (S = 30). For DM unlearning, only the cross-attention module weights are fine-tuned, with the unlearning step set to 50, requiring two RTX 3090 GPUs. λ is set to 10. The evaluation metrics include FID, ACC, and Learned Perceptual Image Patch Similarity (LPIPS) [45].

4.2. Unlearning Evaluation

For style and object unlearning, we produce 250 images per evaluation concept, utilizing 50 seeds per concept and generating 5 images per seed.

Style unlearning. We evaluate various unlearning methods on nine artist styles described in Section 3.1.2, erasing each style individually and assessing preservation performance across the remaining styles.

The comparative results are shown in Tab. 1, with the following key observations: 1) AdvAnchor effectively eliminates undesirable styles. For instance, with \mathcal{L}_{adv1} , AdvAn-

Table 1. Comparative results on style unlearning. $c_{0\sim8}$ represent nine artist styles in Section 3.1.2. We evaluate both erasure (FID⁺/ACC⁺/LPIPS⁺) and preservation (FID⁺/ACC⁺/LPIPS⁺) performance. The red digits — **digit**₁, <u>digit</u>₂, and <u>digit</u>₃ — indicate the best, second-best, and third-best erasure results, respectively. Similarly, the blue digits highlight best results for preservation performance.

	0	RI	SDD	[21]	All-but-	one [15]	ESI	D [8]	AbConc	ept [23]	Ours()	\mathcal{L}_{adv1})	Ours(1	\mathcal{L}_{adv2})
	Erase	Preserve	Erase	Preserve	Erase	Preserve	Erase	Preserve	Erase	Preserve	Erase	Preserve	Erase	Preserve
c0	0/98.0/0	0/99.4/0	282.1/1.20/.402	108.5/87.8/.214	251.2/9.60/.371	103.6/91.2/.209	320.3/0/.494	140.6/73.7/.278	213.4/18.8/.339	115.0/85.1/.207	404.8/0/.385	96.4/94.3/.158	261.6/22.0/.320	84.9/96.2/.141
c_1	0/97.6/0	0/99.4/0	255.3/12.4/.427	95.2/95.8/.178	234.2/12.8/.445	97.9/95.6/.183	278.4/4.80/.518	117.1/84.8/.220	246.7/34.8/.410	75.7/96.9/.109	404.5/34.0/.522	113.0/96.0/.165	256.0/31.2/.411	70.6/97.5/.090
c_2	0/99.6/0	0/99.2/0	240.1/1.20/.422	105.7/90.4/.189	261.0/0/.385	109.2/92.4/.189	291.9/0/.494	149.2/71.4/.249	231.7/0.40/.356	98.7/89.7/.157	452.0/0/.519	145.0/92.6/.181	253.7/0/.380	96.6/91.2/.174
c_3	0/99.6/0	0/99.2/0	424.5/4.40/.580	91.6/93.7/.192	345.9/21.2/.414	88.1/95.2/.188	469.9/0/.731	103.2/86.6/.229	317.0/5.60/.447	69.4/97.0/.118	585.3/0/.386	108.8/94.8/.210	338.4/5.20/.436	70.6/95.8/.128
c_4	0/99.6/0	0/99.2/0	302.9/0.80/.358	98.5/94.0/.171	290.8/19.2/.298	100.5/95.2/.182	321.3/1.60/.366	110.6/92.9/.186	243.9/17.2/.306	80.6/95.5/.122	509.4/0/.600	123.3/90.9/.188	283.1/11.6/.297	74.6/95.9/.117
c_5	0/98.8/0	0/99.3/0	258.8/6.40/.605	96.5/94.3/.164	238.5/9.20/.566	94.8/96.6/.151	295.6/0.40/.635	102.4/91.6/.169	271.2/2.80/.621	79.0/95.4/.105	309.0/0/.598	97.2/94.0/.160	276.4/0/.648	74.4/94.9/.097
c_{6}	0/100.0/0	0/99.0/0	242.2/1.60/.367	99.8/93.2/.187	254.7/2.80/.433	99.7/95.3/.193	286.6/0/.482	107.6/93.9/.189	174.7/10.8/.301	72.6/96.4/.105	333.5/0/.438	96.5/92.4/.169	276.0/0/.363	73.1/97.1/.104
c_7	0/100.0/0	0/99.0/0	266.4/3.20/.369	92.9/94.7/.189	325.4/4.00/.337	91.9/95.7/.176	286.2/0.40/.364	98.3/94.0/.202	247.7/19.6/.291	68.9/96.3/.116	381.5/0/.396	95.1/94.7/.184	313.0/5.60/.325	67.0/96.1/.113
c_8	0/99.6/0	0/99.4/0	196.7/96.4/.305	89.5/98.6/.181	177.1/41.2/.339	88.7/96.2/.175	240.9/18.0/.340	97.8/94.8/.189	220.9/78.0/.279	67.3/95.7/.111	376.5/4.00/.432	87.8/97.0/.176	262.1/16.4/.303	67.0/97.6/.095
Avg	0/99.2/0	0/99.2/0	274.3/14.2/.426	97.6/93.6/.185	264.3/13.3/.399	97.2/ <u>94.8</u> /.183	<u>310.1</u> / 2.80/.492	114.1/87.1/.212	240.8/20.9/.372	<u>80.8</u> /94.2/ <u>.128</u>	417.4 / <u>4.2</u> /.475	107.0/94.1/.177	280.0/10.2/.387	75.4/95.8/.118

Algorithm 1: AdvAnchor.

Input: The training dataset \mathcal{D} ; noise schedule $\bar{\alpha}_t$; denoiser $f_{de}(\cdot; \cdot)$; original DM weights θ_{ori} ; optimizable weights for unlearning θ_{op} ; maximum iteration S; and prompt p_u with undesirable concept c_u . e_{pu} , e_u , and e_{\emptyset} are embeddings of p_u , c_u , and c_{\emptyset} , respectively.

Output: The fine-tuned model weights θ_{op} .

1 Randomly initialize a universal variable e_{adv} ;

2 for $x_0 \in \mathcal{D}$ do

- 3 Randomly select a sampling step t;
- 4 | $\boldsymbol{x}_t = \sqrt{\bar{\alpha}_t} \boldsymbol{x}_0 + \sqrt{1 \bar{\alpha}_t} \boldsymbol{\epsilon}, \boldsymbol{\epsilon} \in \mathcal{N}(0, \mathbf{I});$
- 5 $\boldsymbol{\epsilon}_{pu} = f_{de}(\boldsymbol{x}_t, \boldsymbol{e}_{pu}; \boldsymbol{\theta}_{ori}); \boldsymbol{\epsilon}_{\emptyset} = f_{de}(\boldsymbol{x}_t, \boldsymbol{e}_{\emptyset}; \boldsymbol{\theta}_{ori});$
- 6 /*Generating adversarial anchors.*/
- for $j \in [1, S]$ do 7 $e_{\text{anchor},i}^{\text{adv}} = \begin{cases} e_{\text{pu},i} + e_{\text{adv}} & \text{if } e_{\text{pu},i} \text{ is } e_{\text{u}} \\ e_{\text{pu},i} & \text{otherwise}; \end{cases}$ 8 $\boldsymbol{\epsilon}_{\text{anchor}} = f_{\text{de}}(\boldsymbol{x}_t, \boldsymbol{e}_{\text{anchor}}^{\text{adv}}; \boldsymbol{\theta}_{\text{ori}});$ 9 $\max_{\boldsymbol{e}_{adv}} \mathcal{L}_{adv}(\cdot)$ in Eq. (3); 10 if $\mathcal{L}_{adv} \leq 0$ then 11 break; 12 13 end end 14 /*Concept unlearning.*/ 15 $e_{\text{anchor}} = e_{\text{anchor}}^{\text{adv}};$ Calculate \mathcal{L}_{op} in Eq. (1); 16 17 $\mathcal{L}_{\text{reg}} = \lambda \cdot \| f_{\text{de}}(\boldsymbol{x}_t, \boldsymbol{e}_{\emptyset}; \boldsymbol{\theta}_{\text{op}}) - f_{\text{de}}(\boldsymbol{x}_t, \boldsymbol{e}_{\emptyset}; \boldsymbol{\theta}_{\text{ori}}) \|_2$ 18 $\min_{\boldsymbol{\theta}_{op}} [\mathcal{L}_{op} + \mathcal{L}_{reg}];$ 19 20 end

chor increases the average FID/LPIPS values for undesirable styles from 0/0 to 417.4/0.408, while decreasing their average ACC from 99.2 to 4.22. 2) AdvAnchor with \mathcal{L}_{adv1} shows superior erasure performance and comparable preservation performance compared to existing approaches. 3) AdvAnchor with \mathcal{L}_{adv2} exhibits optimal model preservation performance while maintaining comparable erasure effectiveness to previous techniques. 4) Erasing different styles affects the generation quality of retained styles to varying extents. For instance, erasing the '*Cezanne*' style greatly influences the generation performance for '*Van Gogh*', '*Jackson Pollock*', and '*Caravaggio*', whereas erasing the '*Keith Haring*' style has minimal effect on retained styles. 5) The difficulty of erasing different styles also varies. For example, AdvAnchor with \mathcal{L}_{adv1} can reduce the classification accuracy of most undesirable styles to 0%. However, erasing the '*Van Gogh*' style remains challenging.

Object unlearning. We use category names from Imagenette [16] as prompts to evaluate object unlearning [8, 21]. The '*Cassette Player*' category is excluded due to the low accuracy of the classification network on images of this category. It can be observed from Tab. 2 that AdvAnchor shows excellent erasure and preservation abilities in object unlearning. Notably, in terms of preservation performance, DM unlearning affects styles more significantly than objects. For instance, using AdvAnchor with \mathcal{L}_{adv2} , the average FID for retained styles is 75.5 (see Tab. 1), while for retained objects it is 23.8 (see Tab. 2). Fig. 6 provides visual examples illustrating the effectiveness of AdvAnchor in both object and style unlearning.

Explicit content removal. We then show the efficacy of AdvAnchor in erasing exposed content by removing the word 'nudity'. For erasure evaluation, we generate 4,073 images using unlearned DMs with I2P prompts [35] and count the number of images exposing body parts. The original DM yields 815 sensitive images across 8 classes, classified by Nudenet [3]. To asses preservation performance, 1,859 images are produced with prompts from ImageNet.

The results are presented in Fig. 8, with the following key observations: 1) AdvAnchor with \mathcal{L}_{adv1} outperforms \mathcal{L}_{adv2} in erasing exposed content, likely due to the higher initial value of \mathcal{L}_{adv1} , which strengthens the adversarial anchors. 2) Compared to other methods, AdvAnchor with \mathcal{L}_{adv1} achieves the optimal erasure capability and the superior preservation performance in terms of ACC, while maintaining competitive FID and LPIPS scores. Visual examples of AdvAnchor on 'nudity' unlearning are shown in Fig. 7.

Unlearning other I2P categories. Using I2P categories

Table 2. Comparative results on object unlearning. $c_{0\sim9}$ represent the object categories '*Chain Saw*', '*Church*', '*Gas Pump*', '*Tench*', '*Garbage Truck*', '*English Springer*', '*Golf Ball*', '*Parachute*', '*French Horn*', respectively. We evaluate both erasure (FID⁺/ACC⁺/LPIPS⁺) and preservation (FID⁺/ACC⁺/LPIPS⁺) performance. The red digits — **digit**₁, **digit**₂, and **digit**₃ — indicate the best, second-best, and third-best erasure results, respectively. Similarly, the blue digits highlight best results for preservation performance.

	0	RI	SDD	[21]	All-but-	one [15]	ESD	[8]	AbConc	ept [23]	Ours()	\mathcal{L}_{adv1})	Ours(2	\mathcal{L}_{adv2})
	Erase	Preserve	Erase	Preserve	Erase	Preserve	Erase	Preserve	Erase	Preserve	Erase	Preserve	Erase	Preserve
c_0	0/88.8/0	0/90.7/0	295.1/22.8/.322	24.5/84.3/.189	331.3/0/.402	25.0/86.0/.185	319.3/4.40/.367	26.1/81.6/.198	240.0/14.0/.303	21.6/80.5/.147	488.1/0/.615	23.4/89.1/.182	362.6/0/.373	18.7/84.9/.213
c_1	0/82.8/0	0/91.5/0	221.6/32.4/.403	32.8/82.3/.200	183.6/26.8/.355	30.4/82.6/.187	179.6/18.4/.394	36.4/78.9/.215	190.5/33.6/.366	25.0/84.0/.117	320.4/10.8/.426	29.7/85.0/.182	211.9/33.6/.360	22.9/83.8/.109
c_2	0/77.6/0	0/92.1/0	200.6/10.8/.390	29.2/89.3/.182	205.8/12.0/.411	29.7/86.1/.177	265.6/1.20/.470	35.5/84.4/.207	199.8/16.4/.358	23.6/88.3/.107	391.5/0/.587	29.9/86.8/.169	204.3/18.4/.378	22.3/87.6/.101
c_3	0/86.8/0	0/91.0/0	232.1/5.20/.461	32.6/84.1/.195	236.6/2.00/.423	30.2/83.2/.195	256.2/5.60/.484	29.5/84.2/.190	205.4/4.40/.386	22.1/85.5/.103	202.9/1.20/.460	31.4/86.1/.188	205.6/4.80/.384	27.0/83.4/.140
c_4	0/90.0/0	0/90.6/0	241.6/42.0/.373	29.3/82.5/.175	152.7/22.4/.297	29.9/84.5/.183	208.2/18.8/.398	31.9/82.0/.194	165.3/25.2/.330	24.2/82.9/.112	392.8/10.4/.484	36.7/86.0/.190	185.4/24.8/.320	23.2/84.0/.108
c_5	0/94.8/0	0/90.0/0	249.4/4.40/.359	28.8/83.6/.187	187.8/17.8/.358	32.2/81.2/.207	369.9/1.20/.430	32.8/82.6/.211	198.8/12.0/.344	24.7/81.3/.126	377.5/0/.555	28.6/86.8/.186	319.4/4.40/.386	22.9/82.7/.113
c_6	0/98.0/0	0/89.6/0	313.6/40/.464	33.9/81.8/.195	303.1/6.00/.408	29.8/82.8/.181	311.8/3.20/.486	33.6/79.0/.200	426.9/0.80/.409	33.1/76.7/.159	477.0/2.40/.437	29.5/84.8/.172	470.9/0.80/.415	26.8/79.4/.126
c_7	0/95.6/0	0/89.9/0	236.3/22.0/.468	30.9/82.4/.188	216.6/18.6/.455	30.2/83.0/.206	320.5/0/.543	35.7/81.8/.215	195.2/24.8/.449	24.9/83.9/.125	336.0/3.20/.526	31.3/83.1/.184	182.8/37.6/.411	24.6/80.5/.111
c_8	0/100.0/0	0/89.3/0	382.5/0/.455	31.9/80.1/.178	341.0/4.40/.411	31.4/80.2/.187	408.0/0/.480	41.6/74.7/.201	320.5/20/.415	27.7/79.5/.125	433.9/0/.489	30.1/83.6/.171	357.6/0.40/.443	27.4/79.9/.128
Avg	0/90.5/0	0/90.5/0	263.6/20.0/.411	30.4/ <u>83.4</u> /.188	239.8/12.2/.391	29.9/83.3/.190	293.2/5.87/.450	33.7/81.0/.203	238.0/16.8/.373	25.2/82.5/.125	380.0/3.11/.509	30.1/85.7/.180	277.8/18.3/.386	24.0 /82.9/ <u>.128</u>



Figure 6. Visual examples of AdvAnchor in style (top two rows) and object (bottom two rows) unlearning.

as prompts, we train an 8-class classifier with a pre-trained ResNet18: seven unsafe classes from I2P (1,000 samples for each class) and one safe class (7,000 ImageNet samples), achieving 92.8% classification accuracy. Preservation performance is evaluated using ImageNet prompts. The results presented in Tab. 3 show that AdvAnchor achieves optimal performance in both erasure and preservation.

Others. For explicit content removal, the Appendix presents ablation studies that incorporate various unsafe categories from NudeNet, rather than relying solely on the term 'nudity.' Moreover, the Appendix includes experiments conducted on other versions of Stable Diffusion, and across various tasks such as facial identity unlearning.

4.3. Ablation Studies

Impact of optimization strategy on AdvAnchor: We compare different optimization strategies for nudity un-



Figure 7. Visual examples of AdvAnchor on 'nudity' unlearning.

learning, with the results shown in Tab. 4. Considering both erasure and preservation performance, the alternating optimization strategy with \mathcal{L}_{adv1} emerges as the optimal choice.

Impact of hyperparameter S on AdvAnchor. We use the alternating optimization strategy in this research, varying S from 20 to 50 in increments of 10. Experimental re-



Figure 8. Comparative results on 'nudity' unlearning. We report the best (first row) and average (second row) metric values across three runs. 'E' and 'P' are the erasure \downarrow and preservation performance, respectively. The preservation metrics include FID \downarrow , ACC \uparrow , and LPIPS \downarrow .

Table 3. Comparative experiments on I2P categories. We evaluate erasure (ACC \downarrow) and preservation performance (FID \downarrow /ACC \uparrow /LPIPS \downarrow).

I2P		Hate		Violence	;	Self-Harm		Shocking	Ill	egal activity	I	Iarassment		AVG
Metrics	Erase	Preserve												
ORI	92.4	0.00/54.7/.00	76.4	0.00/54.7/.00	96.0	0.00/54.7/.00	92.0	0.00/54.7/.00	96.4	0.00/54.7/.00	97.2	0.00/54.7/.00	91.7	0.00/54.7/.00
AbConcept [23]	54.4	22.4/50.8/.190	15.6	22.4/50.0/.190	52.0	22.0/50.3/.181	97.2	22.7/51.0/.193	85.6	22.2/52.3/.186	76.0	21.9/53.1/.187	63.5	22.3 /51.3/.188
ESD [8]	34.0	23.1/50.5/.189	33.2	22.9/50.6/.196	2.00	23.6/50.6/.205	78.4	22.4/51.5/.193	90.8	22.6/51.2/.193	84.4	22.1/52.7/.184	53.8	22.8/51.2/.193
All-but-one [15]	54.0	23.0/50.9/.187	14.8	23.3/50.4/.201	32.4	23.8/51.0/.210	95.2	22.1/52.6/.187	76.8	23.5/50.9/.197	86.0	22.4/52.2/.185	59.9	23.0/51.3/.195
AdvAnchor	19.6	22.8/53.2/.179	0.0	22.5/54.8/.180	0.0	22.4/55.6/.183	3.20	23.9/54.5/.195	1.98	24.1/54.3/.196	0.0	22.4/53.7/.179	4.13	23.0/ 54.4/.185

Table 4. Ablation study on optimization strategies in AdvAnchor. We report average metric values over three runs. 'Erasure' indicates the count of images exposing body parts, while 'Preservation' includes FID \downarrow /ACC \uparrow /LPIPS \downarrow as evaluation metrics. S = 40.

AdvAnchor	Strategies	Erasure \downarrow	Preservation
	Alternating	107	23.4/53.8/0.188
\mathcal{L}_{adv1}	Sequential	102.7	24.9/53.7/0.197
	Cyclical	66	25.6/52.4/0.200
	Alternating	238.3	22.6/51.7/0.189
\mathcal{L}_{adv2}	Sequential	227	22.2/52.7/0.185
	Cyclical	280.3	22.2 /52.1/ 0.185

sults are presented in Tab. 5. For AdvAnchor with \mathcal{L}_{adv1} , increasing *S* notably improves erasure performance but reduces preservation performance. In contrast, modifying *S* has minimal effect on AdvAnchor with \mathcal{L}_{adv2} , as \mathcal{L}_{adv2} quickly meets the stopping criterion, making further adjustments to *S* largely ineffective.

5. Conclusions

In this paper, we address the performance trade-off issue in DM unlearning by exploring the influence of anchor selection. Our analysis reveals that ideal anchors should exclude defining attributes specific to undesirable concepts while reTable 5. Ablation study on hyperparameter S. We report average metric values over three runs. 'Erasure' indicates the count of images exposing body parts, while 'Preservation' includes $FID\downarrow/ACC\uparrow/LPIPS\downarrow$ as evaluation metrics.

	AdvAnchor	S	Erasure ↓	Preservation
		20	204.7	22.7 /53.3/0.189
	C	30	126.3	23.7/53.2/0.195
	\mathcal{L}_{adv1}	40	107	23.4/53.8/ 0.188
		50	95.3	25.0/ 54.2 /0.199
-		20	234.3	22.4/52.2/0.186
	C	30	199.3	22.7/51.2/0.196
	\mathcal{L}_{adv2}	40	238.3	22.6/51.7/0.189
		50	220.7	23.7/51.6/0.188

maining close to these concepts. To this end, we propose AdvAnchor, which yields adversarial anchors using specifically designed loss constraints and optimization strategies. Experimental results demonstrate that AdvAnchor effectively removes undesirable concepts while preserving the generative quality of DMs for retained concepts.

References

 Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023. 3

- [2] Mohamed Akrout, Bálint Gyepesi, Péter Holló, Adrienn Poór, Blága Kincső, Stephen Solis, Katrina Cirone, Jeremy Kawahara, Dekker Slade, Latif Abid, et al. Diffusionbased data augmentation for skin disease classification: Impact across original medical datasets to fully synthetic images. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 99–109. Springer, 2023. 1
- [3] P Bedapudi. Nudenet: Neural nets for nudity classification, detection and selective censoring, 2019. 6
- [4] Lucas Bourtoule, Varun Chandrasekaran, Christopher A Choquette-Choo, Hengrui Jia, Adelin Travers, Baiwu Zhang, David Lie, and Nicolas Papernot. Machine unlearning. In *IEEE Sympo. on Security and Privacy*, pages 141–159. IEEE, 2021. 2
- [5] Manuel Brack, Felix Friedrich, Dominik Hintersdorf, Lukas Struppek, Patrick Schramowski, and Kristian Kersting. Sega: Instructing text-to-image models using semantic guidance. *Adv. Neural Inform. Process. Syst.*, 36, 2024. 2
- [6] Zhi-Yi Chin, Chieh-Ming Jiang, Ching-Chun Huang, Pin-Yu Chen, and Wei-Chen Chiu. Prompting4debugging: Redteaming text-to-image diffusion models by finding problematic prompts. arXiv preprint arXiv:2309.06135, 2023. 2
- [7] Rishav Chourasia and Neil Shah. Forget unlearning: Towards true data-deletion in machine learning. In *International Conference on Machine Learning*, pages 6028–6073.
 PMLR, 2023. 2
- [8] Rohit Gandikota, Joanna Materzynska, Jaden Fiotto-Kaufman, and David Bau. Erasing concepts from diffusion models. In *Int. Conf. Comput. Vis.*, 2023. 1, 2, 3, 5, 6, 7, 8
- [9] Rohit Gandikota, Hadas Orgad, Yonatan Belinkov, Joanna Materzyńska, and David Bau. Unified concept editing in diffusion models. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 5111–5120, 2024. 1, 2
- [10] Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. arXiv preprint arXiv:1412.6572, 2014. 2
- [11] Varun Gupta, Christopher Jung, Seth Neel, Aaron Roth, Saeed Sharifi-Malvajerdi, and Chris Waites. Adaptive machine unlearning. Adv. Neural Inform. Process. Syst., 34: 16319–16330, 2021. 2
- [12] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In Proceedings of the IEEE conference on computer vision and pattern recognition, pages 770–778, 2016. 3
- [13] Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. Adv. Neural Inform. Process. Syst., 30, 2017. 3
- [14] Jonathan Ho and Tim Salimans. Classifier-free diffusion guidance. arXiv preprint arXiv:2207.12598, 2022. 1
- [15] Seunghoo Hong, Juhun Lee, and Simon S Woo. All but one: Surgical concept erasing with model preservation in text-toimage diffusion models. *arXiv preprint arXiv:2312.12807*, 2023. 2, 6, 7, 8

- [16] Jeremy Howard and Sylvain Gugger. Fastai: A layered api for deep learning. *Information*, 11(2):108, 2020. 6
- [17] Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models. arXiv preprint arXiv:2106.09685, 2021. 2
- [18] Chi-Pin Huang, Kai-Po Chang, Chung-Ting Tsai, Yung-Hsuan Lai, and Yu-Chiang Frank Wang. Receler: Reliable concept erasing of text-to-image diffusion models via lightweight erasers. *arXiv preprint arXiv:2311.17717*, 2023.
 2
- [19] Bahjat Kawar, Shiran Zada, Oran Lang, Omer Tov, Huiwen Chang, Tali Dekel, Inbar Mosseri, and Michal Irani. Imagic: Text-based real image editing with diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6007–6017, 2023. 2
- [20] Amirhossein Kazerouni, Ehsan Khodapanah Aghdam, Moein Heidari, Reza Azad, Mohsen Fayyaz, Ilker Hacihaliloglu, and Dorit Merhof. Diffusion models for medical image analysis: A comprehensive survey. arXiv preprint arXiv:2211.07804, 2022. 1
- [21] Sanghyun Kim, Seohyeon Jung, Balhae Kim, Moonseok Choi, Jinwoo Shin, and Juho Lee. Towards safe selfdistillation of internet-scale text-to-image diffusion models. *arXiv preprint arXiv:2307.05977*, 2023. 1, 2, 5, 6, 7
- [22] Diederik Kingma and Ruiqi Gao. Understanding diffusion objectives as the elbo with simple data augmentation. Adv. Neural Inform. Process. Syst., 36, 2024. 1
- [23] Nupur Kumari, Bingliang Zhang, Sheng-Yu Wang, Eli Shechtman, Richard Zhang, and Jun-Yan Zhu. Ablating concepts in text-to-image diffusion models. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2023. 1, 2, 3, 6, 7, 8
- [24] Yixiao Li, Yifan Yu, Chen Liang, Pengcheng He, Nikos Karampatziakis, Weizhu Chen, and Tuo Zhao. Loftq: Lorafine-tuning-aware quantization for large language models. *arXiv preprint arXiv:2310.08659*, 2023. 1
- [25] Zhili Liu, Kai Chen, Yifan Zhang, Jianhua Han, Lanqing Hong, Hang Xu, Zhenguo Li, Dit-Yan Yeung, and James Kwok. Geom-erasing: Geometry-driven removal of implicit concept in diffusion models. arXiv preprint arXiv:2310.05873, 2023. 2
- [26] Shilin Lu, Zilan Wang, Leyang Li, Yanzhu Liu, and Adams Wai-Kin Kong. Mace: Mass concept erasure in diffusion models. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 6430– 6440, 2024. 2
- [27] Mengyao Lyu, Yuhong Yang, Haiwen Hong, Hui Chen, Xuan Jin, Yuan He, Hui Xue, Jungong Han, and Guiguang Ding. One-dimensional adapter to rule them all: Concepts, diffusion models and erasing applications. arXiv preprint arXiv:2312.16145, 2023. 2
- [28] Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. arXiv preprint arXiv:1706.06083, 2017. 4
- [29] Ninareh Mehrabi, Palash Goyal, Christophe Dupuy, Qian Hu, Shalini Ghosh, Richard Zemel, Kai-Wei Chang, Aram

Galstyan, and Rahul Gupta. Flirt: Feedback loop in-context red teaming. *arXiv preprint arXiv:2308.04265*, 2023. 2

- [30] Yiting Qu, Xinyue Shen, Xinlei He, Michael Backes, Savvas Zannettou, and Yang Zhang. Unsafe diffusion: On the generation of unsafe images and hateful memes from text-to-image models. In *Proceedings of the 2023 ACM SIGSAC Conference on Computer and Communications Security*, pages 3403–3417, 2023. 1
- [31] Aditya Ramesh, Mikhail Pavlov, Gabriel Goh, Scott Gray, Chelsea Voss, Alec Radford, Mark Chen, and Ilya Sutskever. Zero-shot text-to-image generation. In *International Conference on Machine Learning*, pages 8821–8831. PMLR, 2021.
 2
- [32] Aditya Ramesh, Prafulla Dhariwal, Alex Nichol, Casey Chu, and Mark Chen. Hierarchical text-conditional image generation with clip latents. *arXiv preprint arXiv:2204.06125*, 1 (2):3, 2022. 2
- [33] Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In Proceedings of the IEEE/CVF conference on computer vision and pattern recognition, pages 10684–10695, 2022. 2, 5
- [34] Pamela Samuelson. Generative ai meets copyright. *Science*, 381(6654):158–161, 2023. 1
- [35] Patrick Schramowski, Manuel Brack, Björn Deiseroth, and Kristian Kersting. Safe latent diffusion: Mitigating inappropriate degeneration in diffusion models. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 22522–22531, 2023. 6
- [36] Shawn Shan, Jenna Cryan, Emily Wenger, Haitao Zheng, Rana Hanocka, and Ben Y Zhao. Glaze: Protecting artists from style mimicry by text-to-image models. *arXiv preprint arXiv:2302.04222*, 2023. 2
- [37] C Shivashankar and Shane Miller. Semantic data augmentation with generative models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 863–873, 2023. 2
- [38] Gowthami Somepalli, Vasu Singla, Micah Goldblum, Jonas Geiping, and Tom Goldstein. Diffusion art or digital forgery? investigating data replication in diffusion models. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 6048–6058, 2023. 2
- [39] Jiaming Song, Chenlin Meng, and Stefano Ermon. Denoising diffusion implicit models. arXiv preprint arXiv:2010.02502, 2020. 1
- [40] Yu-Lin Tsai, Chia-Yi Hsu, Chulin Xie, Chih-Hsun Lin, Jia-You Chen, Bo Li, Pin-Yu Chen, Chia-Mu Yu, and Chun-Ying Huang. Ring-a-bell! how reliable are concept removal methods for diffusion models? arXiv preprint arXiv:2310.10012, 2023. 2
- [41] Haotian Xue, Alexandre Araujo, Bin Hu, and Yongxin Chen. Diffusion-based adversarial sample generation for improved stealthiness and controllability. *Adv. Neural Inform. Process. Syst.*, 36, 2024. 4
- [42] Ling Yang, Zhilong Zhang, Yang Song, Shenda Hong, Runsheng Xu, Yue Zhao, Wentao Zhang, Bin Cui, and Ming-Hsuan Yang. Diffusion models: A comprehensive survey of

methods and applications. *ACM Computing Surveys*, 56(4): 1–39, 2023. 1

- [43] Xinyi Yu, Guanbin Li, Wei Lou, Siqi Liu, Xiang Wan, Yan Chen, and Haofeng Li. Diffusion-based data augmentation for nuclei image segmentation. In *International Conference* on Medical Image Computing and Computer-Assisted Intervention, pages 592–602. Springer, 2023. 1
- [44] Eric Zhang, Kai Wang, Xingqian Xu, Zhangyang Wang, and Humphrey Shi. Forget-me-not: Learning to forget in text-toimage diffusion models. arXiv preprint arXiv:2303.17591, 2023. 1, 2
- [45] Richard Zhang, Phillip Isola, Alexei A Efros, Eli Shechtman, and Oliver Wang. The unreasonable effectiveness of deep features as a perceptual metric. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 586–595, 2018. 5
- [46] Yimeng Zhang, Jinghan Jia, Xin Chen, Aochuan Chen, Yihua Zhang, Jiancheng Liu, Ke Ding, and Sijia Liu. To generate or not? safety-driven unlearned diffusion models are still easy to generate unsafe images... for now. arXiv preprint arXiv:2310.11868, 2023. 2
- [47] Yihua Zhang, Yimeng Zhang, Yuguang Yao, Jinghan Jia, Jiancheng Liu, Xiaoming Liu, and Sijia Liu. Unlearncanvas: A stylized image dataset to benchmark machine unlearning for diffusion models. arXiv preprint arXiv:2402.11846, 2024. 2
- [48] Mengnan Zhao, Lihe Zhang, Wei Wang, Yuqiu Kong, and Baocai Yin. Adversarial attacks on scene graph generation. *IEEE Transactions on Information Forensics and Security*, 2024. 2
- [49] Mengnan Zhao, Lihe Zhang, Tianhang Zheng, Yuqiu Kong, and Baocai Yin. Separable multi-concept erasure from diffusion models. arXiv preprint arXiv:2402.05947, 2024. 2
- [50] Yufan Zhou, Ruiyi Zhang, Changyou Chen, Chunyuan Li, Chris Tensmeyer, Tong Yu, Jiuxiang Gu, Jinhui Xu, and Tong Sun. Towards language-free training for text-to-image generation. In *Proceedings of the IEEE/CVF Conference* on Computer Vision and Pattern Recognition, pages 17907– 17917, 2022. 2