Efficient Human-in-the-Loop Active Learning: A Novel Framework for Data Labeling in AI Systems

Yiran Huang, Jian-Feng Yang^{*} School of Statistics and Data Science, LPMC & KLMDASR, Nankai University, Tianjin300071, China

and

Haoda Fu

University of North Carolina at Chapel Hill

January 3, 2025

Abstract

Modern AI algorithms require labeled data. In real world, majority of data are unlabeled. Labeling the data are costly. this is particularly true for some areas requiring special skills, such as reading radiology images by physicians. To most efficiently use expert's time for the data labeling, one promising approach is human-in-the-loop active learning algorithm. In this work, we propose a novel active learning framework with significant potential for application in modern AI systems. Unlike the traditional active learning methods, which only focus on determining which data point should be labeled, our framework also introduces an innovative perspective on incorporating different query scheme. We propose a model to integrate the information from different types of queries. Based on this model, our active learning frame can automatically determine how the next question is queried. We further developed a data driven exploration and exploitation framework into our active learning method. This method can be embedded in numerous active learning algorithms. Through simulations on five real-world datasets, including a highly complex real image task, our proposed active learning framework exhibits higher accuracy and lower loss compared to other methods.

Keywords: Active learning; Data labeling; Entropy; Exploration and exploitation; Full and partial information; Multiple questions

^{*}The authors gratefully acknowledge the National Natural Science Foundation of China (Grant No.12271270).

1 Introduction

A diverse range of AI systems have emerged for practical applications. Large language models, such as Generative Pre-trained Transformers (GPT) (Vaswani et al., 2017; Radford et al., 2018), demonstrated exceptional capabilities in natural language processing tasks, including understanding, generating and interpreting human language. Similarly, reinforcement learning models have also been successfully applied in real-world scenarios. such as autonomous driving (Kiran et al., 2021). These models are data-hungry, requiring significant amount labeled data for effective training. For a thorough overview of the data requirements across different models, see Zhao et al. (2023). This poses challenges in data collection, large-scale data labeling and data quality enhancement. Across various scientific domains like language processing, reinforcement learning, medical image field and speech recognition, there are a substantial volume of unlabeled data and a relatively small amount of annotated data (Budd et al., 2021; Zhu and Goldberg, 2022). It is prohibitive for traditional supervised model training, especially for deep learning models, because labelong a significant portion of data can be impractical. For instance, there is a large pool of unannotated pathological images, but only a small number of them have been diagnosed. Increasing the labeled images to a high level is unrealistic because clinical diagnosis for images can be expensive. One of the solutions to this dilemma is human-in-the-loop active learning algorithms. Active learning is a process in which humans interact with computers to enhance the efficiency of machine learning. It aims to identify the most informative unlabeled data and entrust them to oracle experts for labeling. The high quality of the newly labeled data enhances the efficiency of machine learning. Consequently, the demand for sample size sharply declines to an affordable level. Criteria from different perspectives are used to recognize informative data, including uncertainty-based method (Settles and

Craven, 2008; Nguyen et al., 2022), diversity-based method (Zhdanov, 2019), density-based method (Xu et al., 2007), cluster-based method (Wang et al., 2017), disagreement-based method (Cohn et al., 1994; Hanneke, 2011; Hanneke and Yang, 2019), etc. Additionally, Hsu and Lin (2015) proposed assembling a few criteria simultaneously and assigning scores to these criteria by an algorithm inspired by the bandit problem. Konyushkova et al. (2017) suggested learning active learning criteria directly from the data. This paper focuses on the uncertainty-based method because it is one of the most prevalent active learning schemes and is available under most models.

The most uncertain data will be deemed as the most informative because, intuitively, ambiguous data sits on the margin of classes and querying them helps the machine identify the class boundaries rapidly. Different models use different methods to measure uncertainty. Distance-based models mainly use distance to depict uncertainty. For example, in support vector machine model (Kremer et al., 2014), the point closest to the classification boundary is deemed the most uncertain and thus the most informative. Probabilistic models utilize the predicted probabilities of classes to reflect uncertainty. Entropy, introduced by Shannon (1948), is highly recommended as it is related to the likelihood function and integrates the uncertainty level of each class into one index. During active learning, the machine builds the model with labeled data and calculates the entropies of the unlabeled data. The one with the highest entropy is then queried.

Except for sampling the most informative data, some algorithms may allocate some budgets to querying less informative data because the model is likely to be inaccurate during the early stages of active learning, which may misrecognize the information of each datum. It is a trade-off called exploration and exploitation. Exploration tends to gather information from areas with limited knowledge, while exploitation is obsessed with the informative area identified by the current model, see for example Ren et al. (2021).

Traditional active learning methods focus primarily on which data to query but often neglect how to label the data. That is, traditional methods merely concentrate on data quality while overlooking the labeling process itself. Motivated by this limitation, we aim to develop a method that addresses both the challenges of data labeling and quality enhancement by considering various perspectives on labeling data. Specifically, traditional modeling methods assume the information for each point is either full or none. In other words, we either know the exact label or have no information for a given point. Most active learning algorithms only query one question, "what is the class of the datum?". The difference among algorithms lies in their information measurements. In a wide range of areas, it is possible to query one innovative question to a batch of data simultaneously. This is not the same as batch active learning, where the same question "what is the class of the datum?" is repeatedly asked for each point in a batch (Hoi et al., 2006; Sener and Savarese, 2017; Zhdanov, 2019; Ash et al., 2019). For example, it is possible to select several data and query the question, "are all of these data from a specific class?" or "is any of these data from a specific class?". The two questions are meaningful in practical fields. In epidemiological testing, doctors are required to conduct pathological tests to determine whether the patient is suffering from a disease and to identify the disease. By collecting the samples of several patients and querying "does any of these patients suffer from a specific illness?", experimenters can mix several samples and conduct a single laboratory test, as demonstrated in Hogan et al. (2020) and Song et al. (2022). If the test result is positive, then the answer to the question is yes; otherwise, it is no. The benefits of querying these innovative questions are threefold. (1) The cost of querying these questions may be much less than querying "what is the class of the datum?". In the given example, the question we

queried needs only one experiment, while the question "what is the disease of the patient?" must conduct each experiment sequentially until a medical test yields a positive result or all test results are negative. (2) Querying these questions can obtain information for several points in one iteration, though it may be partial information. Suppose we inquire "are all of these points from a specific class?". If the answer is yes, we then possess full information about them because their labels are all known. Nevertheless, if the answer is no, we only obtain partial information about them. (3) These questions can efficiently explore the sample space because a single question can include data from many regions.

In certain research domains, datasets may contain multiple labels, as discussed in ?. This paper focuses on the scenarios where each data point has exactly one label. The paper introduces a method to construct a probabilistic model using information gathered from various questions, including both full and partial information. The logistic and neural network models are considered. Additionally, the paper proposes a novel uncertainty-based active learning method using entropy, which automatically selects both the question and the data to be queried. Alongside the active learning criterion, a heuristic data-driven exploration and exploitation frame is proposed. The frame can be embedded cleverly in a large number of active learning algorithms. The basic idea of the frame is to automatically remove data that are likely to contain redundant information based on distance before each active learning iteration. Traditional metrics like the Euclidean or Mahalanobis metric may not adequately capture distances, particularly when dealing with highly non-linear and high dimensional data, such as image data. Furthermore, these two distance metrics are unsupervised. To address this, we introduce a model-guided distance metric within the frame which can accommodate a broad class of models. This model-guided distance metric updates whenever the model is revised.

The paper is organized as follows. Section 2 introduces the background of the active learning problem and some related notations. Section 3 elaborates the method for integrating both full and partial information as well as active learning with multiple questions. The exploration and exploitation frame is also shown. Section 4 establishes a theoretical foundation to validate the proposed method from the perspective of the probability of unexpected answers. Section 5 provides our active learning method based on five real datasets simulations. Section 6 concludes the paper and brings some insights for future studies. All proofs are deferred to the supplementary material.

2 Background and Notation

The size of full data in the pool is assumed to be N, where each data point $x_i \in \mathbb{R}^p$ has a label $y_i \in \{1, 2, ..., L\}$, or say each x_i is from class y_i , for $i \in 1, 2, ..., N$. The full data is denoted by $D_{full} = \{(x_i, y_i)\}_{i=1}^N$. While most labels in D_{full} are unknown, we adopt this notation for convenience. By the basic assumption of active learning, let D_0 , with a size n_0 , represent a small fraction of D_{full} as annotated data. We further denote by $D_{full}^x = \{x_i\}_{i=1}^N$ all points without their labels from D_{full} , and D_0^x is similarly defined. Though most labels in D_{full} are unknown, D_{full}^x is fully observed. Predicting the label yfor a point x requires building some metrics or models. Metric learning aims to find an adequate positive semi-definite matrix $A \in \mathbb{R}^{p \times p}$ to define a quadratic form distance such that points from the same class are close to each other and points from different classes are far away, see, for example, Xing et al. (2002), Yang et al. (2012) and Deng et al. (2023). The metric learning utilizes the pairwise constraints between any two points from D_0^x to learn the optimal metric. The label of $x \in D_{full}^x$ can be predicted according to the learned distance between x and each point in D_0^x . However, when the dimension p is high, the method is not stable. Additionally, the metric learning frame also fails to realize our aim of querying multiple questions. The paper focuses on the probabilistic model approach. The probabilistic model can be written as $p(\cdot; \theta) : \mathbb{R}^p \to \mathbb{R}^L$, where the *c*th entry, $p_c(x; \theta)$, represents the probability of *x* from class *c*. The method also needs to define a proper loss function $l : \mathbb{R}^L \times \{1, 2, \ldots, L\} \to \mathbb{R}^+$ so that the model parameters can be estimated by minimizing the loss function:

$$\hat{\theta} = \arg\min_{\theta} \frac{1}{n_0} \sum_{i=1}^{n_0} l(p(x_i; \theta), y_i).$$

For a given $x \in \mathbb{R}^p$, the model predicts its label by $\hat{y} = \arg \max_{c \in \{1,2,\dots,L\}} p_c(x;\hat{\theta})$.

Typically, the prediction accuracy of the model built by the initial training set is unsatisfactory, which makes active learning necessary. Most active learning methods can be summarized in Algorithm 1. The most "informative" point is selected using the crite-

Algorithm 1: Traditional active learning Data: D_0 and D_{full}^x

Result: probabilistic model $p(\cdot, \hat{\theta})$.

- (1) Build model $p(\cdot; \hat{\theta})$ based on D_0 ;
- (2) while Budget enough do
- (3) Select $x \in D_{full}^x$ based on criterion $AL(p(x;\hat{\theta}));$
- (4) Query the label y for x and add (x, y) into D_0 ;
- (5) Rebuild model $p(\cdot; \hat{\theta})$ based on D_0
- (6) end

rion $AL(\cdot)$, such as Fisher information considered in Hoi et al. (2006) and Sourati et al. (2017), least confidence reviewed in Settles (2012) and entropy introduced before. Fisher information is associated with traditional statistics theory and performs well under low dimensional cases, although it requires a parametric model and suffers from the curse of dimension. Least confidence identifies the point with the lowest predicted probability for its most possible class, but it discards the information of the remaining probabilities. Entropy, derived from information theory, incorporates the uncertainty of each class and concludes them into one index. It is expressed as

$$En(p(x;\hat{\theta})) = -\sum_{c=1}^{L} p_c(x;\hat{\theta}) \log[p_c(x;\hat{\theta})].$$
(1)

The traditional active learning method only queries one question, "what is the class of x?". The paper considers an innovative scenario where multiple questions are available to be inquired, allowing data to be labeled from different perspectives. Some of these questions may involve more than one point, which can efficiently explore the input space. We use the uppercase letter Q to denote the general form of how a question is queried, while the lowercase letter q refers to a specific query. For example, assume a question Q is of the form "are x_1, x_2 from the class c?". We can query the question Q several times with different choices of points x_1, x_2 and class c. Given two specific points x_{i_1}, x_{i_2} and class c = 1, if we queried "are points x_{i_1}, x_{i_2} from class 1?" and the feedback is yes, we can represent the gathered information as $q = [(x_{i_1}, x_{i_2}), c = 1]$ and a = 1. Formally, besides the question "what is the class of x?", there are K extra questions, Q_1, \ldots, Q_K . All possible answers for question Q_k are contained in the set A_k . The question point q_k for question Q_k contains all the necessary information to formulate q_k as a specific question, such as the points and class in the previous example. Suppose we have queried question Q_k for n_k times, where each question point and the corresponding answer are q_{ki} and a_{ki} , respectively, for $i = 1, \ldots, n_k$. We use the notation $D_k = \{(q_{ki}, a_{ki})\}_{i=1}^{n_k}$ to denote the information gained by such a question. Without loss of generality, we always assume the question "what is the class of x?" to be question 0, and its corresponding D_0 coincides with the training set described earlier. Throughout the paper, we focus on three types of questions shown in

Table 1. By setting different m values, we can create multiple questions.

Question	Answer set	Probability
"What is the class of x ?"	$\{1,\ldots,L\}$	$Pr(ans = c) = p_c(x)$
"Are all of x_1, x_2, \ldots, x_m from class c ?"	$\{0, 1\}$	$Pr(ans = 1) = \prod_{i=1}^{n} p_c(x_i)$
"Is any of x_1, x_2, \ldots, x_m from class c ?"	$\{0, 1\}$	$Pr(ans = 0) = \prod_{i=1}^{n} (1 - p_c(x_i))$

Table 1: Questions considered in the paper

3 Method

As shown in Table 1, probability is the best bridge to connect different questions to the true labels. When the probabilities of classes are known, or at least can be predicted, the probabilities of answers to any question can be calculated or predicted. Consider a loss function $l_k(\cdot, \cdot)$ for each question Q_k and then apply them to all information in $D = \{D_0, D_1, \ldots, D_K\}$ by

$$l(D,\theta) = \frac{1}{\sum_{k=0}^{K} n_i} \sum_{k=0}^{K} \sum_{i=1}^{n_k} l_k(\hat{P}r(ans|q_{ki},\theta), a_{ki}),$$
(2)

where $\hat{P}r(ans|q_{ki},\theta)$ is an $|A_k|$ length vector of estimated probabilities of answers under the model $p(\cdot;\theta)$ and $|A_k|$ is the size of the answer set A_k . For instance, for the question "are all of x_{i_1}, \ldots, x_{i_m} from class c?", the first and second entries of $\hat{P}r(ans|q_{ki},\theta)$ are $1 - \prod_{j=1}^m p_c(x_{i_j};\theta)$ and $\prod_{j=1}^m p_c(x_{i_j};\theta)$, respectively. The estimated parameter $\hat{\theta}$ can be obtained by minimizing the loss $l(D,\theta)$. The selection of the loss function is not arbitrary. A wise choice would be cross-entropy loss, expressed as

$$l_k(\hat{P}r(ans|q_{ki},\theta),a_{ki}) = -\sum_{a\in A_k} \mathbf{1}(a_{ki}=a)\log[\hat{P}r(ans=a|q_{ki},\theta)].$$
(3)

Firstly, it is equivalent to the negative log-likelihood function. Secondly, it provides a more reasonable connection between different questions and the probabilities of classes than other loss functions. In detail, if we inquire "are all of x_{i_1}, \ldots, x_{i_m} from class c?" and the answer is yes, then the loss will be

$$-\log[\hat{P}r(ans=1|q_{ki},\theta)] = -\sum_{j=1}^{m}\log[p_c(x_{i_j};\theta)],$$

which happens to be the sum of losses for data (x_{i_j}, y_{i_j}) for j = 1, ..., m. If we query "is any of $x_{i_1}, ..., x_{i_m}$ from class c?" and the feedback is no, then the loss will be

$$-\log[\hat{P}r(ans = 0|q_{ki}, \theta)] = -\sum_{j=1}^{m}\log[1 - p_c(x_{i_j}; \theta)],$$

which is equivalent to the sum of losses for "is x_{i_j} from class c?" with the answer no for all $j = 1, \ldots, m$. Therefore, the cross-entropy loss in (3) used hereafter makes sense.

3.1 Active learning method

The main concept behind active learning is to identify the most uncertain data, i.e., to find the question q_k with a high expected loss, as determined by

$$E(l_k(\hat{P}r(ans|q_k,\theta),a_k)) = -\sum_{a \in A_k} Pr(ans=a|q_k) \log[\hat{P}r(ans=a|q_k,\theta)].$$
(4)

This is estimated by substituting the predicted probability, resulting in the entropy:

$$En(\hat{P}r(ans|q_k,\theta)) = -\sum_{a \in A_k} \hat{P}r(ans = a|q_k,\theta) \log[\hat{P}r(ans = a|q_k,\theta)].$$
(5)

As discussed in Section 2, entropy is one of the criteria used to measure the information of a point. We use it as an active learning criterion. In our frame, active learning is divided into two parts. The first part determines what is the best q_k to be queried for question Q_k with fixed k, and the second part decides which question Q_k should be queried. To solve these, we introduce the cost for each question Q_k , $cost_k$. Without loss of generality, we always assume $cost_0 = 1$. The optimal question point q_k for Q_k is determined by

$$q_k^{opt} = \arg\max_{q_k} En(\hat{P}r(ans|q_k, \theta)).$$

This can be approximated by the random exchanging algorithms. To determine which Q_k to be queried, we utilize both entropy and cost,

$$k^{opt} = \arg \max_{k \in \{0,1,\dots,K\}} \frac{En(\hat{P}r(ans|q_k^{opt},\theta))}{g(cost_k)} + \xi_k,\tag{6}$$

where g is an increasing function with g(0) = 0 and ξ_k 's are identically and independently distributed around 0 with small scales. Based on our simulation experience, $g(x) = x^{2/3}$ appears to be a relatively good choice. The ξ_k 's are random values to provide chances to all informative questions with comparable high performances.

3.2 Exploration and exploitation method

When the model is not accurate enough, the discrepancies between the predicted probabilities and the true probabilities can be large, resulting in a big gap between estimated loss and true loss. At this time, it may waste the budget to focus on exploiting the uncertain area. To mitigate the risks, the machine should expand its knowledge to unexplored areas. To achieve this, we introduce the distance function d, whose specific form will be introduced at the end of the subsection. Recall the definition of D_{full}^x and $D = \{D_0, D_1, \ldots, D_K\}$. Similarly, we define $D^x = \bigcup_{k=0}^K D_k^x$. For any $x \in D_{full}^x$, define its distance to D^x as

$$d(x, D^x) = \min_{x' \in D^x} d(x, x').$$

A small $d(x, D^x)$ implies that some information has been gained in the neighbor of x. Therefore, to explore the sample space, we should consider the x with a large $d(x, D^x)$.

Once we have explored the sample space to some extent, we should shift our focus to exploitation, although deciding when that moment comes can be challenging. We present a data-driven exploration and exploitation frame, which employs distance as the key to gradually shift the focus from exploration to exploitation. Given a sequence of distance thresholds $d_1 > d_2 > \cdots > d_S = 0$ and a proportion threshold ρ , in each active learning iteration, we screen out points close to D^x and consider the rest of the points as the candidate set. This is achieved by finding $D^x_{can}(s) = \{x \in D^x_{full} : d(x, D^x) > d_s\}$ for $s = 1, \ldots, S$. Then, we find the minimum s such that $|D_{can}^{x}(s)| > \rho N$ where $|D_{can}^{x}(s)|$ is the number of points within $D_{can}^{x}(s)$. In other words, we require at least ρ proportion of data available to be chosen. Figure 1 exhibits a visual example. The red triangles are points in D^x . In the first panel, the blue dashed circles have a radius of d_1 , and the black dots represent candidate points in $D_{can}^{x}(1)$. The blue squares are excluded since they are too close to D^x . The second panel shows that some of the black dots in the first panel are selected to be queried. The blue dashed circles with radiuses d_1 are also plotted in the second panel. However, these circles cover too many points such that the size of $D^x_{can}(1)$ is less than ρN . Therefore, in the third panel, the radius is reduced to d_2 and the size of $D_{can}^{x}(2)$ is once again greater than ρN . In the fourth panel, the active learning algorithm continues querying a question within $D_{can}^{x}(2)$. This exploration and exploitation frame is maintained throughout the active learning algorithm until the budget is exhausted.



Figure 1: Illustration of exploration and exploitation frame.

The distance thresholds are hard-to-decide parameters. We present a data-driven method for selecting the distance thresholds. We first gather all pairwise distances within D_{full}^x and obtain its 5th percent quantile as d_1 . By setting $d_S = 0$, we generate d_2, \ldots, d_S using an arithmetic sequence. In the simulation, we set S = 6. The only rest hyperparameter ρ controls the tendency between exploration and exploitation. Larger ρ encourages exploitation more. An extreme example is when ρ approximate 1, the candidate set will always be $D_{full}^x - D^x$.

The last problem of the frame is determining the appropriate distance metric. While the Euclidean distance or the Mahalanobis distance are viable options, they are unsupervised. That is, they do not leverage any information provided by the labels. Introducing a supervised distance metric is crucial since the input space may not provide a suitable metric, especially in the field of image data. For a wide range of probabilistic models, the probability is generated by a "softmax" operation,

$$p_c(x;\theta) = \frac{\exp\{h_c(x;\theta)\}}{\sum_{l=1}^L \exp\{h_l(x;\theta)\}}.$$
(7)

For example, the logistic model set $h_c(x;\theta) = \theta_c^T x + \theta_{0c}$ with $\theta = (\theta_0^T, \theta_1^T, \theta_2^T, \dots, \theta_L^T)^T$. In the neural network model, $h_c(\cdot;\theta)$ is a highly complex function created by numerous hidden layers. Under such models, we can use the feature space, $h(x;\theta) = (h_1(x;\theta), \dots, h_L(x;\theta))$, to define a model-guided distance

$$d(x, x'; \theta) = d_2(h(x; \theta), h(x'; \theta)),$$
(8)

where d_2 is the Euclidean distance.

3.3 Some remarks

The entire procedure, including active learning as well as exploration and exploitation, is organized in Algorithm 2. The exploration and exploitation frame is flexible and can be embedded in many active learning algorithms because the frame is screening out redundant points. To make it, one simply needs to switch Step (4) to other active learning criteria.

A	Algorithm 2: New frame of active learning with exploration and exploitation					
	Data: budget B , ρ , D_{full}^x , D_k and $cost_k$ for $k = 0, 1, \ldots, K$.					
	Result: probabilistic model $p(\cdot, \hat{\theta})$.					
(1)	Build $p(\cdot; \hat{\theta})$ based on all D_k by minimizing Equation (2); Set $b = 0$;					
(2) while $B \ge b + \min\{cost_k\}$ do						
(3)	Generate distance thresholds $d_1 > \cdots > d_S = 0$ based on distance function (8).					
	Find out minimum s such that $ D_{can}^{x}(s) > \rho N;$					
(4)	Consider all questions Q_k satisfying $b + cost_k \leq B$. Obtain k^{opt} and					
	corresponding $q_{k^{opt}}^{opt}$ within $D_{can}^{x}(s)$ based on Equation (6) by random					
	exchanging algorithm. Query $q_{k^{opt}}^{opt}$ and obtain $(q_{k^{opt}}^{opt}, a_{k^{opt}}^{opt})$. Add $(q_{k^{opt}}^{opt}, a_{k^{opt}}^{opt})$					
	into $D_{k^{opt}}$, set $n_{k^{opt}} \leftarrow n_{k^{opt}} + 1$ and $b \leftarrow b + cost_{k^{opt}}$;					
(5)	Rebuild $p(\cdot; \hat{\theta})$ based on all D_k by minimizing Equation (2).					

(6) end

We also provide some more discussion on the proposed active learning algorithm. For convenience, we refer to the three types of questions by "Class", "All" and "Any", which will also be employed in the later Section 5. The maximum entropies for the three questions are $\log L$, $\log 2$ and $\log 2$, respectively. Consider the case where the costs are all under moderate scales. At the initial stage of active learning, the machine favors the question "Class" because the entropy of the question at this time can be large, even approaching $\log L$. It corresponds to our intuition because the "Class" question can provide more information than others when the model is inaccurate. When the model becomes more confident and accurate, the machine tends to "All" or "Any" questions. For instance, when the most uncertain point x has predicted class probabilities $(\hat{p}_1(x), \hat{p}_2(x), \dots, \hat{p}_L(x)) =$ (0.5, 0.45, ..., 0), it is almost for sure that point x is either from class 1 or 2. Though querying the "Class" question can obtain its true label, inquiring "is x from class 1?" can be more budget-efficient. For another example, when the model is highly confident and accurate, say arg max_c $p_c(x) > 0.9$ for all x, querying "Class" can rarely obtain unexpected answers, making the active learning inefficient. Alternatively, if we inquire about the "All" or "Any" question, the predicted probability of the answer can rapidly decrease approximately to 0.5 by the factorial. In conclusion, despite the "Class" question being a robust and optimal option when the model is inaccurate, it is overly cautious when the model is confident. The "All" and "Any" questions bring some risks of obtaining partial information, but they provide information for a batch of data at a very low cost.

4 Theory

Some theoretical supports for both the proposed entropy-based active learning frame and the exploration and exploitation frame are provided in this section. Let $\mathcal{X} \subset \mathbb{R}^p$ be the input space. Assume the joint distribution of the input point X with its label Y to be F(X,Y). We also assume that the form of the model follows the "softmax" structure. Let \mathcal{H}_0 be the set of measurable functions mapping \mathcal{X} into \mathbb{R}^L . For any $h \in \mathcal{H}_0$, the predicted probability of label c for x is

$$p_c^h(x) = \frac{\exp\{h_c(x)\}}{\sum_{l=1}^L \exp\{h_l(x)\}}$$

We refer to $h \in \mathcal{H}_0$ as a model or a score. Working under the entire \mathcal{H}_0 is impractical. We assume a subset $\mathcal{H} \subset \mathcal{H}_0$ which contains functions with a given uniform bound Δ . Furthermore, we define a subset of \mathcal{H} by \mathcal{H}' , representing the set of functions under consideration. For example, by restricting a specific structure, the newly defined subset is $\mathcal{H}' = \{h(\cdot; \theta) \in \mathcal{H}\}$. We denote the entropy of x under model h by En(h, x). We further define the distribution for En(h, X) as $F_E^h(En)$ where $X \sim F(X)$. We first provide some assumptions that may be used in the following theory.

A1
$$F(y|x) = 1$$
 or 0.

A2 For any $h \in \mathcal{H}$, $h_c(x) \in [-\Delta, \Delta]$ for all $c = 1, \ldots, L$.

A3 For any $0 < En \leq \log 2$ and $h \in \mathcal{H}'$, there is a function F_E such that $F_E^h(En) \geq F_E(En)$.

Assumption A1 requires the label for input x to be deterministic, which is common in machine learning. Assumption A2 requires the scores to be bounded. As the predicted probability is derived by exponentiating the scores, even a small Δ can yield a wide range of probabilities. For example, with L = 5 and $\Delta = 5$, the predicted probability of a class roughly spans from 10^{-5} to 0.9998. Assumption A3 assumes a uniform lower bound function for all entropy distributions within \mathcal{H}' . This suggests that the scores under consideration must not be too ambiguous across \mathcal{X} . Indeed, most points will exhibit small entropies when the model is sufficiently confident.

Proposition 1. For any model $h \in \mathcal{H}_0$, suppose the true label for x is y. Then the entropy is within the range

$$\left[-p_y^h(x)\log[p_y^h(x)] - [1 - p_y^h(x)]\log[1 - p_y^h(x)], -p_y^h(x)\log[p_y^h(x)] - [1 - p_y^h(x)]\log\left(\frac{1 - p_y^h(x)}{L - 1}\right)\right].$$

The bounds are shown in the first panel of Figure 2 with black solid lines. If the entropy for a point is large, the predicted probability of the true label will consistently be low, as shown by the blue dotted line. For a low-entropy point, the predicted probability for the true label can be either low or high, as shown by the red dashed line. When the predicted probability of the true label is high, the model prediction aligns with reality. However, when the predicted probability is small, the model is overconfident, and querying such a point will yield an unexpected answer. We aim to demonstrate that when the model is accurate enough, querying low-entropy points can only yield unexpected answers with low probability.



Figure 2: Illustrations of Proposition 1, Corollary 1 and Theorem 3.

Define $\phi(\cdot)$ to be the inverse function of $-x \log(x) - (1-x) \log(1-x)$ over [0, 1/2]. Let $\mathcal{R}(\mathcal{H}') = E_F[\sup_{h \in \mathcal{H}'} |n^{-1} \sum_{i=1}^n \xi_i l(h, X_i, Y_i)|]$ be the Rademacher complexity over n independent identical distributed samples, where ξ_i are identically and independently sampled with a probability of 1/2 to be 1 and 1/2 to be -1.

Theorem 1. Under assumption A1-A3, the model $\hat{h} \in \mathcal{H}'$ is built by minimizing

$$\frac{1}{n}\sum_{i=1}^{n}l(h,X_i,Y_i),$$

where (X_i, Y_i) 's are identically and independently distributed by F(X, Y) for i = 1, ..., n. Given $En < \log 2$, for any $0 < \delta < 1/2$, we have

$$P\{p_Y^{\hat{h}}(X) \leqslant \phi(En(\hat{h},X)) | En(\hat{h},X) \leqslant En\} \leqslant \left\{\frac{\epsilon(n,\delta,\Delta)}{-\log[\phi(En)]F_E(En)} \wedge 1\right\} (1-2\delta) + 2\delta,$$

where $b = 2\Delta + \log L$ and

$$\epsilon(n,\delta,\Delta) = 2\mathcal{R}(\mathcal{H}') + \sqrt{\frac{2}{n}\log\frac{1}{\delta}}b + \exp\left\{-\frac{2n\delta^2}{b^2}\right\} + (L-1)\exp(-2\Delta).$$

Controlling the Rademacher complexity towards any sample space and model space can be hard. We present a simplified conclusion by directly assuming the expected loss.

Corollary 1. Under assumption A1, suppose model \hat{h} satisfies $E_F[l(\hat{h}, X, Y)] = \epsilon$. Given $En < \log 2$, we have

$$P\{p_Y^{\hat{h}}(X) \leqslant \phi(En(\hat{h},X)) | En(\hat{h},X) \leqslant En\} \leqslant \frac{\epsilon}{-\log[\phi(En)]F_E^{\hat{h}}(En)} \wedge 1.$$

The proof of Corollary 1 directly follows from the proof of Theorem 1. The two results indicate that the probability of an unexpected answer conditioned on querying a lowentropy point can be bounded. An example for Corollary 1 is shown in the second panel of Figure 2, with $\epsilon = 0.1$ and $F_E^{\hat{h}}(En) \ge En + 0.05$. Theories suggest that we should query points with large entropies because the chance of observing misclassified points within low-entropy areas is small.

The previous results provide some theoretical supports for querying the question "what is the class of x?". We now investigate the theories for our proposed frame that is capable of querying multiple questions. The sampling scheme for the question point should be modeldependent. We partition input space \mathcal{X} into several disjoint parts and use the model to guide a question point $[(x_{i_1}, \ldots, x_{i_m}), c]$ sampling strategy. The strategy will obtain the expected answer with high probability but shares some similarities with the proposed entropy-based method. We firstly separate the input space to three parts: high-confident area, low-confident area and uncertain area, denoted by $\hat{A}(h) = \{x \in \mathcal{X} : \max_c p_c^h(x) \ge$ $1 - \delta_m\}, \bar{A}(h) = \{x \in \mathcal{X} : \max_c p_c^h(x) \in [\max\{1/L, 1 - (1/2)^{1/m}\}, 1 - \delta_m)\}$ and $\tilde{A}(h) =$ $\mathcal{X} - \hat{A}(h) - \bar{A}(h)$ respectively, where $\delta_m \leq 1 - (1/2)^{1/m}$. We further denote $\hat{A}_c(h) =$ $\hat{A}(h) \cap \{x : \arg\max_l p_l^h(x) = c\}$ as the area with high confidence predicted to be class cand $\bar{A}_c(h)$ can be defined similarly.

We use model h to guide a question sampling strategy such that the entropy of each

question point will be small. To begin, we sample a random value ξ by $P(\xi = all) = \pi_1$ and $P(\xi = any) = \pi_2$, with $\pi_1 + \pi_2 = 1$. If ξ is all, we sample c with probability $F(\hat{A}_c(h))/F(\hat{A}(h))$, then sample x_{i_1}, \ldots, x_{i_m} identically and independently from $\mathbf{1}\{X \in \hat{A}_c(h)\}F(X)/F(\hat{A}_c(h))$, and query "are all of x_{i_1}, \ldots, x_{i_m} from class c?"; if ξ is any, we sample c with probability $F(\bar{A}_c(h))/F(\bar{A}(h))$, then sample x_{i_1}, \ldots, x_{i_m} identically and independently from $\mathbf{1}\{X \in \bar{A}_c(h)\}F(X)/F(\bar{A}_c(h))$, and query "is any of x_{i_1}, \ldots, x_{i_m} from class c?". With the sampling approach, when we inquire "are all of x_{i_1}, \ldots, x_{i_m} from c?", we can expect the answer yes; likewise, when we ask "is any of x_{i_1}, \ldots, x_{i_m} from c?", we can also anticipate the answer yes. The area $\tilde{A}(h)$ is left. This area is highly ambiguous according to model h and it is more sensible to query the question "what is the class of x?" within this region.

Theorem 2. Under assumption A1, suppose the model \hat{h} has average loss $\epsilon = E_F[l(\hat{h}, X, Y)]$. For the query strategy shown above, we have

$$\begin{split} &P(\{q:\arg\max\hat{P}r(ans|q)=a\})\\ \geqslant &\pi_1 \bigg[1 - \frac{\epsilon + \log(1-\delta_m)[1-F(\hat{A}(\hat{h}))]}{-\log(\delta_m)F(\hat{A}(\hat{h}))}\bigg]^m + \pi_2 \bigg[1 - \frac{\epsilon + \log(1-\delta_m)F(\bar{A}(\hat{h}))}{[\log(1-\delta_m) - \log(l_m)]F(\bar{A}(\hat{h}))}\bigg]^m,\\ &where \ l_m = 1 - \max\{1/L, 1 - (1/2)^{1/m}\}. \end{split}$$

We further consider a set of m's values $\mathcal{M} \subset \mathbb{N}^+$. Assume that the probability of each m being sampled is π'_m , with $\sum_{m \in \mathcal{M}} \pi'_m = 1$. Denote the set of the high-confident area under m as $\hat{A}(h, m)$, and similar notation can be defined for other sets.

Corollary 2. Under assumption A1, suppose the model \hat{h} has average loss $\epsilon = E_F[l(\hat{h}, X, Y)]$. Let $\pi_1(m) = F(\hat{A}(\hat{h}, m))/(F(\hat{A}(\hat{h}, m)) + F(\bar{A}(\hat{h}, m)))$ and $\pi_2(m) = 1 - \pi_1(m)$. Then we have

$$P(\{q : \arg \max \hat{P}r(ans|q) = a\})$$

$$\geq \sum_{m \in \mathcal{M}} \pi'_m \left[1 - \frac{\epsilon + \log(1 - \delta_m)[1 - F(\hat{A}(\hat{h}, m))]}{-\log(\delta_m)[F(\hat{A}(\hat{h}, m)) + F(\bar{A}(\hat{h}, m))]} - \frac{\epsilon + \log(1 - \delta_m)F(\bar{A}(\hat{h}, m))}{[\log(1 - \delta_m) - \log(l_m)][F(\hat{A}(\hat{h}, m)) + F(\bar{A}(\hat{h}, m))]} \right]^m.$$

The proof of Corollary 2 directly follows from Jensen's inequality. Theorem 2 and Corollary 2 depict that when the model \hat{h} provides accurate predictions, the probability of obtaining the expected answer will be high under the given question querying scheme. Because when \hat{h} performs well, ϵ will be small and $F(\hat{A}(\hat{h})) + F(\bar{A}(\hat{h}))$ tends to be 1. The two results indicate that we can design a safe scheme by sampling low-entropy question points such that the probability of obtaining the expected answer is high. In active learning, we should identify the most informative question point instead of the one with the expected answer. However, the entropy-based sampling strategy is similar to the sampling scheme. When querying "are all of x_{i_1}, \ldots, x_{i_m} from c?", the proposed active learning frame will not be restricted on $\hat{A}(\hat{h})$, but it may also find several x_{i_j} 's from $\bar{A}(\hat{h})$ to adjust the uncertainty to the highest level. Analogously, when querying "is any of x_{i_1}, \ldots, x_{i_m} from c?", the active learning frame may also find several x_{i_j} 's from $\hat{A}(\hat{h})$ to adjust the uncertainty.

The last part of our proposed frame is the exploration and exploitation frame. In conclusion, entropy can be highly sensitive to the model-guided distance, resulting in highentropy points that are not necessarily far from low-entropy area.

Theorem 3. For a given point x and a given model h, let $l_0 = \arg \max_l h_l(x)$ and $\delta =$

 $h_{l_0}(x) - \max_{l \neq l_0} h_l(x)$ satisfying $\delta e^{\delta} \ge (L-3)/e$. Define two functions

$$\phi_1(x) = -\frac{e^x}{e^x + (L-1)} \log\left(\frac{e^x}{e^x + (L-1)}\right) - \frac{L-1}{e^x + (L-1)} \log\left(\frac{1}{e^x + (L-1)}\right),$$

$$\phi_2(x) = -\frac{e^x}{e^x + 1} \log\left(\frac{e^x}{e^x + 1}\right) - \frac{1}{e^x + 1} \log\left(\frac{1}{e^x + 1}\right).$$

Consider a new point x' such that $d(x, x'; h) = d_2(h(x), h(x')) = d \leq \delta$ and $(\delta - d)e^{\delta - d} \geq (L - 3)/e$. We have

$$\phi_2(\delta) \leq En(h, x) \leq \phi_1(\delta) \text{ and } \phi_2(\delta + d) \leq En(h, x') \leq \phi_1(\delta - d).$$

The δ in Theorem 3 describes the gap between the two highest scores. The upper bound ϕ_1 can approach $\log(L)$ even when the score gap is relatively small. See the example with L = 10 in the third panel of Figure 2 where the black solid lines are bounds for entropy over the gap and the red dashed line is the value $\log(L)$. Consider $x \in D^x$ whose score gap is not too large. Though the entropy of x can be small, the entropy upper bounds of its nearby points can still be relatively high. In addition, from the proof of the theorem, the upper bound can be attained, which makes it possible that a queried point has uncertain neighbor areas not far away. With the exploration and exploitation frame, points near x are filtered out from the candidate set, forcing the model to query points far away from x. As active learning goes on, the distance threshold d_s decreases, gradually opening the access to exploiting the neighbor of x.

5 Simulation

The section presents simulations of the proposed active learning method along with the exploration and exploitation frame using several distinct models and five real-world datasets. Our frame with multiple questions available is compared with two typical traditional methods. The first method repeatedly queries "what is the class of x?" with x obtained by entropy criterion. The second method also queries "what is the class of x?" each time with x obtained randomly. The exploration and exploitation frame can also be embedded in the two traditional methods. The multiple questions available under our proposed method are displayed in Table 2.

Table 2: Questions available for each dataset (number of dataset). Class, All and Any are short for "what is the class of x?", "are all of x_1, \ldots, x_m from class c?" and "is any of x_1, \ldots, x_m from class c?", respectively.

Question	m, cost (1)	m, cost (2)	m, cost (3)	m, cost (4)	m, cost (5)
Class	1, 1	1, 1	1, 1	1, 1	1, 1
All	1, 0.18	1, 0.25	1, 0.23	1, 0.23	1, 0.21
All	2, 0.18	2, 0.25	2, 0.235	2, 0.235	2, 0.215
All			5, 0.24	5, 0.24	3, 0.22
Any	2, 0.2	2, 0.25	2, 0.235	2, 0.235	2, 0.215
Any			5, 0.24	5, 0.24	3, 0.22

5.1 Logistic model

We will start by illustrating the logistic model using two real-world datasets. The first dataset, MEU-Mobile, consists of 71 features of phone users. The aim is to identify users based on these features. The dataset involves 56 users who each repeated typing 51 times. We randomly sample 12 users in each simulation, resulting in 12 classes with 612 samples. The second is a pre-processed handwriting digits dataset from the UC Irvine machine learning repository¹ with 5620 images depicting digits 0 to 9. The images are originally of

¹https://archive.ics.uci.edu/dataset/80

size 32×32 from NIST. Each image is divided into 8×8 blocks, with each block a 4×4 matrix. The image is compressed into size 8×8 by counting the pixels of each block.

The budgets for the first and second datasets are 110 and 120, respectively. Initially, we randomly sample 3L points and query their classes. These samples constitute D_0 . Then we set $D_k = \{\emptyset\}$ for k > 0 and begin each active learning algorithm.

We also compare our method to the "ideal" active learning process. As shown in Algorithm 2 and Equation (5), our method utilizes entropy to choose question Q_k as well as q_k . Nevertheless, the ideal criterion substitutes entropy in Equation (5) with cross-entropy shown in Equation (4). In the simulation, we first use a substantial amount of data to train the optimal model. We treat the predicted probability of the optimal model as the true probability p(x), enabling the calculation of Equation (4) during active learning. We then use Equation (5) to obtain q_k^{opt} for each k and find k^{opt} by substituting the entropy within Equation (6) by the cross-entropy in Equation (4). This "ideal" method is not viable in the real world, as the true probabilities are unknown. The comparison aims to demonstrate whether our method using predicted probabilities can match or even surpass the method using true probabilities.

Figures 3 and 4 display the outcomes of active learning processes, with different methods represented by different colors. Dashed curves correspond to active learning methods without the exploration and exploitation frame, while solid curves represent those with the frame. The horizontal dotted line indicates the optimal. Our proposed active learning method demonstrates rapid accuracy improvement at the initial stages. Compared to traditional methods, our method exhibits superior accuracy increment rates at the outset and achieves higher accuracy when the budget is exhausted. The "ideal" process initially provides more outstanding performance as it can measure the differences between the predicted probabilities and the true probabilities precisely. Our method keeps up with or even surpasses the "ideal" process when the budget used is approximately 80 and 120 in the two datasets, respectively. The inclusion or exclusion of the exploration and exploitation frame only yields minimal impact on performance under our active learning method. However, this frame enhances the accuracies of the two traditional active learning methods. The reason is that our proposed method's capability to query questions involving multiple points enables automatic exploration of the input space, even without the exploration and exploitation frame. By contrast, the two traditional methods only gain information from a single point in each iteration. Excluding the exploration and exploitation frame reduces the chance of querying points in areas with less knowledges. Similar conclusions apply to the cross-entropy over true labels shown in the right panels of the two figures.

5.2 Neural network model

When facing a high-dimensional, non-linear dataset, the logistic model fails to capture the features of the data. In such cases, the neural network model is a better alternative. The model is constructed by a great deal of hidden layers and nodes. As the hidden layers go deeper, this model captures increasingly abstract features. The number of nodes in the final layer equals the number of classes. A "softmax" operator is used in the last layer, as described in Equation (7), to ensure that the model's outputs are probabilities.

The third dataset is the urban land cover dataset containing 675 multi-scale remote sensing images. The dataset has been preprocessed into 147 features. The dataset includes nine objects: trees, grass, soil, concrete, asphalt, buildings, cars, pools and shadows. The fourth dataset is the frequently used MNIST handwriting digits dataset. It contains 70000 28×28 images of numbers 0 to 9. To ease the computational burden, we randomly sample



Figure 3: Accuracy and the sum of cross-entropy of active learning for the first dataset. Pro, En and Ra indicate the proposed active learning method and the two traditional active learning methods mentioned at the beginning of Section 5 respectively. If "dis" is added, then the exploration and exploitation frame is taken into consideration. IdealAL is the "ideal" active learning process and "Optimal" is the optimal model trained by an extensive set of data.

7000 samples as full data in each simulation. We use an artificial neural network model (ANN) for the third dataset and a convolution neural network model (CNN) for the fourth dataset. The detailed structures of the two models are in the Section S2 in supplementary material.

The budget for the third and the fourth datasets are 150 and 90, respectively. Initially, we randomly sample 4L points for the third dataset and 2L points for the fourth dataset and query their classes. The remaining procedures remain consistent with those in the previous subsection.



Figure 4: Accuracy and sum of cross-entropy of active learning for the second dataset.

The results of the two data sets are shown in Figures 5 and 6, respectively, with the same notations. The conclusion is similar to before. In the urban land cover example, the proposed method outperforms the "ideal" process when the budget reaches about 50. However, the "ideal" process is far beyond the two traditional methods. In the fourth dataset, the optimal model trained with 1000 samples achieves an accuracy exceeding 95%. Remarkably, our method achieves almost the same accuracy with a budget of only 90. The performance of the proposed method and the two traditional methods are akin at the beginning of the process. Our method exhibits a remarkable superiority improvement rate over the traditional methods when the budget is around 20. It suggests that bringing more question options to the machine indeed speeds up the improvement of accuracy and cross-entropy. As for the exploration and exploitation frame, the conclusion is similar to before. The improvement over the traditional active learning method is considerable. Another observation is that, in the case of image data, with the help of exploration and exploitation

frame, the random method performs nearly as well as the traditional entropy-based method without the frame. It indicates that users can incorporate the exploration and exploitation frame even when the proposed active learning criterion is not available.



Figure 5: Accuracy and sum of cross-entropy of active learning for the third dataset.

5.3 Transfer learning

The fifth dataset utilized is an animal image set sourced from Kaggle², which contains a total of 26179 images categorized into ten classes: dog, cat, horse, spyder, butterfly, chicken, sheep, cow, squirrel and elephant. During preprocessing, we excluded 51 images with fewer than three color channels and resized the remaining images to dimensions of (3, 224, 224) using bilinear interpolation. The data was then randomly split into two sets. The first set, D_{full} , has 60% of data and is designated for active learning. The remaining 40% constitutes the second set, which is considered incoming data after active learning and

²https://www.kaggle.com/datasets/alessiocorrado99/animals10



Figure 6: Accuracy and sum of cross-entropy of active learning for the fourth dataset. is used to assess the model's ability to classify data outside the D_{full} pool.

We consider a more complex model to use transfer learning by utilizing the ResNet50 model (He et al., 2016). We truncate ResNet50 at its third last layer and add a global average pooling layer followed by two fully connected layers, as shown in the supplementary material. Notably, we froze the parameters in the first seven blocks of ResNet50, keeping them untrainable, while the parameters in the subsequent layers were set to be trainable.

To begin with, we randomly sample 200 images to train the model. The active learning process is divided into two stages due to the initial model's high level of uncertainty. If our proposed method was used from the start, the model would continuously query "what is the class of x" for an extend period. The first stage of active learning consistently queries "what is the class of x?" and the point x is selected by the traditional entropy-based method without the exploration and exploitation frame. The second stage considers different query strategies, including our proposed method and the two traditional methods,

and the results are compared in this stage. The budgets for the two stages of active learning are 300 and 450, respectively. To further alleviate the computational burden and minimize the iterations of interaction between human experts and computers, batch active learning is employed. Specifically, we delay proceeding step (5) in Algorithm 2 until steps (3) and (4) have been repeated for five budgets. The simulation repeats 30 times.

Figure 7 depicts the outcomes of active learning. The optimal model uses 80% of full data and achieves an accuracy over 98%, which exceeds the range of the plot. The advantage of our method is not significant when the budget is below 100 due to the model's lack of confidence, with the majority of queried questions being of the type "what is the class of x?". However, as the budget used increases, our method demonstrates superior performance over both traditional methods. The benefit of the exploration and exploitation frame in the simulation is not evident because the exploration and exploitation frame mainly improves the performance at the onset of active learning.



Figure 7: Accuracy and sum of cross-entropy of active learning for the fifth dataset.

Recall that the data is divided into two sets, with the second set being the newly incoming data. The prediction results over the newly incoming data are presented in Table 3. Our proposed method still shows superiority in accuracy over the other two methods. Additionally, incorporating the exploration and exploitation frame can slightly reduce the loss for all active learning methods.

Table 3: Prediction on newly incoming data.

	ideal	Pro+dis	Pro	En+dis	En	Ra+dis	Ra	optimal
Accuracy	0.9444	0.9355	0.9334	0.927	0.9271	0.9262	0.9214	0.9589
Cross-entropy	3433	3742	3815	3840	3972	3730	4160	1746

6 Concluding Remarks

In this paper, we address the classification active learning problems from a novel perspective on how the data are labeled. Three main contributions are as follows. First, we propose a method to effectively integrate full and partial information for model building by utilizing probabilities as a key bridge to connect the partial information. The method is applicable to all probabilistic models trained by minimizing the loss function. Secondly, we propose an innovative active learning method tailored for classification tasks. The proposed active learning method considers multiple questions and selects questions based on an index related to both entropy and cost. Thirdly, we propose an exploration and exploitation frame that can be embedded in any active learning criterion by screening points with redundant information using a data-driven approach and automatically selecting the distance threshold. Besides, we also propose a model-guided distance applicable to a broad range of models, including logistic and neural network models. The model-guided distance metric updates during the process of active learning and provides an accurate distance metric when the model is accurate enough. Simulation results indicate that the performance of the proposed method is superior to traditional methods over models. The exploration and exploitation frame significantly enhances traditional methods.

The paper focuses on the case of probabilistic models. The application of active learning with multiple questions in other cases, such as metric learning, is still unknown. One challenge is quantifying partial information, for which a naive approach involves using a Gaussian distribution. Nevertheless, the Gaussian assumption may not always hold in various scenarios, and addressing this issue is a topic for future research. On the other hand, a prerequisite condition for the paper is that the class number is known and fixed. Previous studies have focused on this aspect. For example, as discussed in Sun et al. (2016) and Mohamad et al. (2018), classes in stream data may evolve, with old classes vanishing and new ones arising. Consequently, the model should be capable of identifying and addressing these dynamic situations. Another prerequisite condition in the paper is that experts are oracles, which may be violated in some real cases such as misdiagnosis. Lastly, the number of classes in the dataset is relatively small compared to the sample size. A potential research direction is to investigate scenarios with a substantial class size.

References

Ash, J. T., Zhang, C., Krishnamurthy, A., Langford, J., and Agarwal, A. (2019), "Deep batch active learning by diverse, uncertain gradient lower bounds," *arXiv:1906.03671*.

Budd, S., Robinson, E. C., and Kainz, B. (2021), "A survey on active learning and

human-in-the-loop deep learning for medical image analysis," *Medical Image Analysis*, 71, 102062.

- Cohn, D., Atlas, L., and Ladner, R. (1994), "Improving generalization with active learning," Machine Learning, 15, 201–221.
- Deng, Y., Yuan, Y., Fu, H., and Qu, A. (2023), "Query-augmented active metric learning," Journal of the American Statistical Association, 118, 1862–1875.
- Hanneke, S. (2011), "Rates of convergence in active learning," The Annals of Statistics, 39, 333–361.
- Hanneke, S., and Yang, L. (2019), "Surrogate losses in passive and active learning," *Electronic Journal of Statistics*, 13, 4646 4708.
- He, K., Zhang, X., Ren, S., and Sun, J. (2016), "Deep residual learning for image recognition," in Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition, pp. 770–778.
- Hogan, C. A., Sahoo, M. K., and Pinsky, B. A. (2020), "Sample pooling as a strategy to detect community transmission of SARS-CoV-2," *The Journal of the American Medical Association*, 323, 1967–1969.
- Hoi, S. C. H., Jin, R., Zhu, J., and Lyu, M. R. (2006), "Batch mode active learning and its application to medical image classification," in *Proceedings of the 23rd International Conference on Machine Learning*, New York, NY, USA: Association for Computing Machinery, ICML '06, pp. 417–424.
- Hsu, W.-N., and Lin, H.-T. (2015), "Active Learning by Learning," *Proceedings of the* AAAI Conference on Artificial Intelligence, 29, 2659–2665.

- Kiran, B. R., Sobh, I., Talpaert, V., Mannion, P., Al Sallab, A. A., Yogamani, S., and Pérez, P. (2021), "Deep reinforcement learning for autonomous driving: A survey," *IEEE Transactions on Intelligent Transportation Systems*, 23, 4909–4926.
- Konyushkova, K., Sznitman, R., and Fua, P. (2017), "Learning active learning from data," Advances in Neural Information Processing Systems, 30, 4228–4238.
- Kremer, J., Steenstrup Pedersen, K., and Igel, C. (2014), "Active learning with support vector machines," Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery, 4, 313–326.
- Mohamad, S., Sayed-Mouchaweh, M., and Bouchachia, A. (2018), "Active learning for classifying data streams with unknown number of classes," *Neural Networks*, 98, 1–15.
- Nguyen, V.-L., Shaker, M. H., and Hüllermeier, E. (2022), "How to measure uncertainty in uncertainty sampling for active learning," *Machine Learning*, 111, 89–122.
- Radford, A., Narasimhan, K., Salimans, T., and Sutskever, I. (2018), "Improving language understanding by generative pre-training," *OpenAI*.
- Ren, P., Xiao, Y., Chang, X., Huang, P.-Y., Li, Z., Gupta, B. B., Chen, X., and Wang, X. (2021), "A survey of deep active learning," ACM Computing Surveys (CSUR), 54, 1–40.
- Sener, O., and Savarese, S. (2017), "Active learning for convolutional neural networks: A core-set approach," *arXiv preprint arXiv:1708.00489*.
- Settles, B. (2012), Active Learning, Synthesis Lectures on Artificial Intelligence and Machine Learning, Cham: Springer.
- Settles, B., and Craven, M. (2008), "An analysis of active learning strategies for sequence

labeling tasks," in Proceedings of the 2008 Conference on Empirical Methods in Natural Language Processing, pp. 1070–1079.

- Shannon, C. E. (1948), "A mathematical theory of communication," The Bell System Technical Journal, 27, 379–423.
- Song, Y., Wang, X., Xiao, Y., and Wang, H. (2022), "A review of pooled-sample strategy:Does complexity lead to better performance?" *View*, 3, 20210005.
- Sourati, J., Akcakaya, M., Leen, T. K., Erdogmus, D., and Dy, J. G. (2017), "Asymptotic analysis of objectives based on fisher information in active learning," *Journal of Machine Learning Research*, 18, 1–41.
- Sun, Y., Tang, K., Minku, L. L., Wang, S., and Yao, X. (2016), "Online ensemble learning of data streams with gradually evolved classes," *IEEE Transactions on Knowledge and Data Engineering*, 28, 1532–1545.
- Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, L., and Polosukhin, I. (2017), "Attention is all you need," Advances in Neural Information Processing Systems.
- Wang, M., Min, F., Zhang, Z.-H., and Wu, Y.-X. (2017), "Active learning through density clustering," *Expert Systems with Applications*, 85, 305–317.
- Xing, E., Jordan, M., Russell, S. J., and Ng, A. (2002), "Distance metric learning with application to clustering with side-information," Advances in Neural Information Processing Systems, 15, 521–528.
- Xu, Z., Akella, R., and Zhang, Y. (2007), "Incorporating diversity and density in active learning for relevance feedback," in *Advances in Information Retrieval: 29th European*

Conference on IR Research, ECIR 2007, Rome, Italy, April 2-5, 2007. Proceedings 29, Springer, pp. 246–257.

- Yang, L., Jin, R., and Sukthankar, R. (2012), "Bayesian active distance metric learning," arXiv:1206.5283.
- Zhao, W. X., Zhou, K., Li, J., Tang, T., Wang, X., Hou, Y., Min, Y., Zhang, B., Zhang, J., Dong, Z. et al. (2023), "A survey of large language models," arXiv preprint arXiv:2303.18223.
- Zhdanov, F. (2019), "Diverse mini-batch active learning," arXiv:1901.05954.
- Zhu, X., and Goldberg, A. B. (2022), *Introduction to semi-supervised learning*, Springer Nature.