MCP-Solver: Integrating Language Models with Constraint Programming Systems

Stefan Szeider

Algorithms and Complexity Group TU Wien, Vienna, Austria www.ac.tuwien.ac.at/people/szeider/

Abstract

While Large Language Models (LLMs) perform exceptionally well at natural language tasks, they often struggle with precise formal reasoning and the rigorous specification of problems. We present MCP-Solver, a prototype implementation of the Model Context Protocol that demonstrates the potential for systematic integration between LLMs and constraint programming systems. Our implementation provides interfaces for the creation, editing, and validation of a constraint model. Through an item-based editing approach with integrated validation, the system ensures model consistency at every modification step and enables structured iterative refinement. The system handles concurrent solving sessions and maintains a persistent knowledge base of modeling insights. Initial experiments suggest that this integration can effectively combine LLMs' natural language understanding with constraint-solving capabilities. Our open-source implementation is proof of concept for integrating formal reasoning systems with LLMs through standardized protocols. While further research is needed to establish comprehensive formal guarantees, this work takes a first step toward principled integration of natural language processing with constraint-based reasoning.

1 Introduction

Large Language Models (LLMs) have demonstrated remarkable capabilities across diverse natural language tasks yet exhibit fundamental limitations in logical reasoning and formal problem specification. Recent studies have established that LLMs struggle with complex reasoning chains, backtracking from failed solution attempts, and maintaining precise quantifier relationships [8]. These limitations are particularly evident in mathematical and logical problem-solving contexts, where LLMs often fail to provide reliable formal specifications despite their fluency in natural language descriptions [16].

Researchers have tackled LLMs' limitations by pairing them with specialized formal systems. Some integrate theorem provers into the reasoning pipeline, while others connect LLMs to calculators or verification tools. Integrating theorem provers [20] represents one promising direction, while other approaches leverage external calculators and verification frameworks. A breakthrough came with Wei et al.'s [18] demonstration that chain-ofthought prompting can unlock complex reasoning capabilities in large language models. Further advancing the field, Drori et al. [5] showcased the power of combining LLMs with scientific computing libraries, while Betz et al. [2] contributed valuable insights through their work on procedural reasoning networks for understanding physical systems. However, these solutions often need custom integration work for each reasoning system, limiting their broader applicability. The Model Context Protocol (MCP) introduces a universal standard for connecting LLMs with external systems, offering a principled solution to this integration challenge [1]. Since its launch by Anthropic, developers have created hundreds of MCP servers¹, establishing MCP as a key framework for AI integration. The protocol provides a flexible yet rigorous architecture where data and computational capabilities can be exposed through standardized servers while AI applications connect as clients to access these resources. McGuinness [9] provides an in-depth analysis of this architectural approach and its practical implications. The protocol has gained broad adoption, with companies like Block and Apollo implementing MCP in production and development platforms like Zed, Replit, Codeium, and Sourcegraph integrating it into their workflows. Anthropic has accelerated adoption by providing prebuilt MCP servers for popular enterprise systems like Google Drive, Slack, GitHub, Git, Postgres, and Puppeteer². While MCP shows promise as a standard for systematic interaction between informal natural language processing and formal computational systems, its success depends on industry support and solutions for security, scalability, and compatibility across platforms.

We present the first application of MCP to bridge the gap between LLMs and *Constraint Programming* (CP) systems, specifically focusing on integration with MiniZinc, a widely adopted constraint modeling language. Our implementation provides a precise interface for transforming natural language specifications into formal constraint models, validating these models, and verifying solutions. This bridges the fundamental reasoning limitations of LLMs with the formal guarantees provided by constraint solvers.

Our open-source implementation demonstrates the practical viability of this approach, offering tools for model submission, parameter management, solution retrieval, and interactive refinement. The system maintains a solver state, handles concurrent solving sessions, and provides detailed feedback for model validation and solution verification. This implementation is a prototype for integrating formal reasoning systems with LLMs through the MCP standard.

The contributions of this paper include (i) a formal specification of the MCP-based integration between LLMs and constraint solvers, (ii) a complete implementation demonstrating the practical viability of this approach, and (iii) an analysis of the complementary capabilities enabled by this integration. We argue that this work represents a significant step toward more reliable and verifiable LLM-based problem-solving systems.

2 Related Work

Recent research has linked large language models (LLMs) with constraint solving through different approaches. Curtis et al. [4] created PRoC3S, which uses a two-stage architecture for robotics planning—an LLM generates parameterized skill sequences that go through continuous constraint satisfaction. For program synthesis, Jha et al. [6] built a counterexample-guided framework that combines an LLM synthesizer with an SMT solver verifier to strengthen correctness guarantees. SATLM by Ye et al. [21] translates natural language into logical formulas suitable for SAT solving. Pan et al. [14] developed LOGIC-LM as a complete pipeline from LLM through symbolic solver to interpreter. Wu et al. [19] created Lemur, which provides a task-agnostic LLM framework for program synthesis.

Kambhampati et al. [7] established theoretical foundations for LLM-Modulo frameworks that pair LLMs with external verifiers. For constraint solving specifically, Régin et al. [15] built GenCP, which integrates LLMs into the domain generation of constraint solvers for text tasks. Voboril et al. [17] focused on real-time constraint solving by creating StreamLLM

¹https://glama.ai/mcp/servers, https://mcp.so, https://mcp-get.com

²https://www.anthropic.com/news/model-context-protocol

to generate constraint streamliners. In automated modeling, Michailidis et al. [11] demonstrated how pre-trained LLMs can transform textual problem descriptions into executable Constraint Programming specifications using retrieval-augmented in-context learning.

While these approaches demonstrate the benefits of combining LLMs with constraint solving, they typically implement fixed pipelines or tight integration for specific use cases. In contrast, MCP Solver provides a flexible protocol-based architecture that enables iterative interaction and supports a broader range of applications through its standardized tool interface.

While prior work has demonstrated various approaches to combining LLMs with constraint solvers, these solutions typically implement fixed integration patterns optimized for specific use cases. In contrast, our MCP Solver takes a more flexible approach by implementing the standardized Model Context Protocol, enabling dynamic interaction patterns between LLMs and constraint-solving capabilities. This protocol-based architecture allows for iterative refinement of constraint models through natural language interaction while maintaining solver integrity. The following sections detail our implementation's core components and design principles, showing how this flexibility is achieved without sacrificing reliability or formal guarantees.

3 System Overview

3.1 Code and Technical Description

The MCP Solver is available as an open-source project at:

```
https://github.com/szeider/mcp-solver
```

The implementation requires Python 3.9 or higher and MiniZinc with the Chuffed solver. The system supports macOS, Windows, and Linux platforms, though Linux users currently need an alternative to the Claude Desktop app. The server can be installed via standard Python package management tools, and configuration is handled through JSON files in platform-specific locations. Documentation includes installation instructions, configuration guides, and example usage. The project follows MCP's protocol specifications for tool interfaces and messaging, ensuring compatibility with any MCP-compliant client.

3.2 Design Principles

The MCP Solver addresses three key challenges in integrating LLMs with constraint solvers: maintaining solver integrity, managing model state, and providing effective tool interfaces.

Our asynchronous model management keeps modification and solving operations strictly separate. A validation step precedes each change to the model, maintaining its consistency. We handle solver timeouts and resource cleanup through a robust session management system.

Knowledge accumulation occurs through a file-backed memo system that maintains solver insights between sessions, creating a growing knowledge base of successful modeling patterns and providing structured error recovery suggestions.

The MCP Solver connects three key components (Figure 1): the Claude Desktop app as the MCP client, the MCP Solver as the server, and MiniZinc [13] as the constraintsolving backend. The client enables LLMs like Claude to interact with constraint models through natural language, while the server manages these interactions and translates them into MiniZinc operations using its Python API. MiniZinc then compiles these models into FlatZinc specifications that can be processed by a constraint solver.



Figure 1: System architecture of the MCP Solver showing the interaction between the The systemLLM, MCP Client, and the solver components. The MCP Client exposes eight standardized tools to interface with the MCP Solver, which coordinates between MiniZinc's constraint-solving capabilities and a persistent knowledge base.

The server supports all solvers compatible with MiniZinc, with Chuffed [3] as the default solver. The Python MiniZinc library [12] manages model validation, solver configuration, and solution extraction.

A system prompt guides the LLM's interaction with the solver by providing key information about tools, model structure, and validation rules. This allows the LLM to function as a constraint modeling assistant that can effectively translate natural language specifications into valid MiniZinc models while maintaining best practices and supporting iterative refinement.

The system prompt is still under construction and evolves based on practical experience. When specific instructions in the knowledge base are essential for reliable operation, we migrate them to the system prompt. This iterative refinement of the prompt reflects our growing understanding of optimally structure LLM interaction with constraint-solving capabilities.

3.3 MCP tools

The MCP Solver implements these core operations as *"tools"* adhering to the MCP specification [10]:

- get_model: View the current model with numbered items
- add_item: Add new item at a specific index
- delete_item: Delete item at index
- replace_item: Replace item at index
- clear_model: Reset model
- solve_model: Execute with Chuffed solver

- get_solution: Get solution variable value with array indices
- get_solve_time: Get execution timing
- get_memo: Access knowledge base
- edit_memo: Update knowledge base

The server implements MCP's request-response protocol with validation and error handling. Model modification has transitioned from line-based to item-based editing for improved robustness. The memo system maintains solution insights between sessions, enabling knowledge accumulation from past modeling experiences.

3.4 Model Management

The system implements an item-based model management approach through four complementary tools: get_model, add_item, delete_item, and replace_item. get_model enables inspection of the current model state with numbered items, while the editing tools provide atomic operations for model modification.

The item-based editing approach ensures model validity by integrating validation into every modification operation. Each proposed change triggers Python MiniZinc's complete validation chain: syntax parsing, type checking, and instantiation verification. Changes are only applied if validation succeeds, maintaining the invariant that the current model is always in a valid state (see Figure 2). This approach eliminates the possibility of accumulated inconsistencies that could arise in line-based editing.



Figure 2: Example for MCP Solver's item-based model editing with validation. Each modification is validated before being applied, maintaining model consistency. Numbers indicate item indices.

Each operation returns the current model with numbered items in truncated form, ensuring consistent tracking. This granular modification capability enables LLMs to refine models by iteratively adding constraints, modifying objective functions, or adjusting parameter declarations based on solver feedback. "The validation system provides detailed diagnostic information, enabling precise error reporting and allowing LLMs to perform targeted refinements.

The continuous validation during editing lets LLMs explore modeling approaches freely while preserving the model's integrity.

The system maintains the solver session state, including the current model, solution cache, and performance statistics. It implements proper resource cleanup through async context managers, particularly for handling solver process termination. The implementation coordinates model updates, solving operations, and solution retrieval while maintaining thread safety for concurrent operations.

3.5 Persistent Knowledge Base

The memo system maintains a growing knowledge base of solving and modeling insights that persist between sessions in a text file that can be periodically reviewed and curated. The LLM automatically records successful modeling strategies and solutions to complex problems. Users also contribute to this knowledge collection by prompting the LLM to document specific insights. The get_memo and edit_memo tools provide access to this growing knowledge base through a line-based editing interface.

4 Preliminary Experimental Evaluation

We evaluated the MCP Solver on various natural problems stated in natural language to assess its flexibility, robustness, and interaction patterns. While these experiments are not rigorous benchmarks, they provide valuable insights into the system's practical capabilities.

We tested the system on several dozen problems covering different constraint programming paradigms. These included pure satisfaction problems (e.g., casting constraints), optimization problems (e.g., Traveling Salesperson Problem), and parameter exploration (e.g., N-Queens with varying board sizes). The appendix provides detailed transcripts of representative examples that demonstrate different aspects of the system:

- The casting example shows how the LLM effectively translates complex logical conditions into boolean constraints.
- The TSP example demonstrates both optimization modeling and model adaptation when new constraints arise (blocked road)
- The N-Queens example illustrates parameter exploration while maintaining model structure

Current implementation restricts solving times to a few seconds, which suffices for moderately sized problems but may require modifications for larger instances. While the memo system successfully captures modeling insights when prompted, autonomous knowledge base updates by the LLM were rare, suggesting room for improvement in the system prompt to encourage more proactive knowledge accumulation.

5 Conclusion

The MCP Solver demonstrates that protocol-based integration of LLMs with constraint solvers offers significant advantages over fixed pipeline approaches. The flexible architecture enables dynamic problem refinement, where solutions can trigger new constraints and model adjustments based on user feedback. This adaptability is particularly valuable during the exploratory phase of constraint modeling, where problem specifications often evolve through iteration.

Our preliminary experiments demonstrate that the MCP Solver effectively combines natural language understanding with constraint modeling capabilities. The system shows particular strength in iterative model refinement and error recovery through natural dialogue, though some aspects, like autonomous knowledge accumulation could benefit from further development.

While the system effectively bridges LLM capabilities with constraint solving, some reliability challenges remain. LLMs occasionally misinterpret solver outputs or make translation errors. Although the current verification mechanisms generally catch and correct these issues, more rigorous system prompts and validation procedures could improve reliability. The balance between flexibility and reliability represents an ongoing challenge in LLM-solver integration.

Our work points to several promising research directions: Adding SAT solvers and minimal unsatisfiable subset analysis would broaden the system's scope. The reliability of results could benefit from more sophisticated verification methods without sacrificing the system's flexibility. The observed self-reflection capabilities of LLMs also suggest new possibilities for interactive modeling.

An inspiring direction lies in leveraging the broader MCP ecosystem. With hundreds of existing MCP services available, rich opportunities exist for creating more comprehensive problem-solving environments. Instance data could be seamlessly imported from databases or online spreadsheets through database MCP servers, while visualization servers could provide interactive result analysis. This interoperability with the broader MCP ecosystem enables the creation of sophisticated end-to-end workflows that combine constraint solving with data access, preprocessing, and result visualization.

The MCP Solver represents a significant step toward integrating natural language understanding with constraint programming, demonstrating that protocol-based architectures can effectively combine the strengths of both domains while maintaining the system flexibility. The broader MCP ecosystem opens up possibilities for building more sophisticated constraint-solving applications.

A Appendix: Case Studies

Here are a few transcripts of chat conversations. We used Claude Desktop app (version 0.7.7) and Claude Sonnet 3.5, and MCP Server (version 2.0.0).

A.1 Casting

This is based on an example by George Johnson (NYT, July 13, 1999).

User

Suppose that a theatrical director feels obligated to cast either his ingenue, Actress Alvarez, or his nephew, Actor Cohen, in a production. But Miss Alvarez won't be in a play with Mr. Cohen (her former lover), and she demands that the cast include her new flame, Actor Davenport. The producer, with her own favors to repay, insists that Actor Branislavsky have a part. But Mr. Branislavsky won't be in any play with Miss Alvarez or Mr. Davenport. Can the director cast the play?

Let me model this casting problem using MiniZinc. We'll use boolean variables to represent whether each actor is cast.

MCP clear_model

Model cleared

MCP add_item (multiple)

```
var bool: alvarez;
var bool: cohen;
var bool: branislavsky;
var bool: davenport;
constraint alvarez \/ cohen;
constraint not (alvarez \/ cohen); constraint alvarez \-
davenport; constraint branislavsky;
constraint not (branislavsky \/ alvarez);
constraint not (branislavsky \/ davenport);
solve satisfy;
```

MCP solve_model

{'status': 'SAT', 'solution': Solution(alvarez=False, cohen=True, branislavsky=True, davenport=False, _checker=''), 'solve_time': 0.0}

LLM

The problem has a solution: cast Cohen and Branislavsky, but not Alvarez or Davenport. Let's verify:

- 1. Either Alvarez or Cohen must be cast \checkmark (Cohen is cast)
- 2. Alvarez and Cohen can't both be cast \checkmark (only Cohen is cast)
- 3. If Alvarez is cast, Davenport must be cast \checkmark (Alvarez isn't cast)
- 4. Branislavsky must be cast \checkmark (Branislavsky is cast)
- 5. Branislavsky won't work with Alvarez \checkmark (Alvarez isn't cast)
- 6. Branislavsky won't work with Davenport \checkmark (Davenport isn't cast)

The director can cast the play with Cohen and Branislavsky.

A.2 Traveling Salesperson

This example shows how the same model can be re-used with different parameter settings, and how solving times are compared.

| <u></u> | Use | r | | | | | | | | | | |
|---------|---|-----|-----|-----|-----|-----|-----|-----|-----|-----|---|--|
| | A saleswoman based in Vienna needs to plan her upcoming tour through Austria, visiting each province capital once. Help find the shortest route. Distances in km: $1 = $ Vienna, $2 = $ St. Pölten, $3 = $ Eisenstadt, $4 = $ Linz, $5 = $ Graz, $6 = $ Klagenfurt, $7 = $ Salzburg, $8 = $ Innsbruck, $9 = $ Bregenz | | | | | | | | | | | |
| | | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | | |
| | 1 | 0 | 65 | 60 | 184 | 195 | 319 | 299 | 478 | 631 | | |
| | 2 | 65 | 0 | 125 | 119 | 130 | 254 | 234 | 413 | 566 | | |
| | 3 | 60 | 125 | 0 | 184 | 157 | 281 | 261 | 440 | 593 | | |
| | 4 | 184 | 119 | 184 | 0 | 208 | 252 | 136 | 315 | 468 | | |
| | 5 | 195 | 130 | 157 | 208 | 0 | 136 | 280 | 459 | 629 | | |
| | 6 | 319 | 254 | 281 | 252 | 136 | 0 | 217 | 391 | 566 | | |
| | 7 | 299 | 234 | 261 | 136 | 280 | 217 | 0 | 188 | 343 | | |
| | 8 | 478 | 413 | 440 | 315 | 459 | 391 | 188 | 0 | 157 | | |
| | 9 | 631 | 566 | 593 | 468 | 629 | 566 | 343 | 157 | 0 | | |
| | | | | | | | | | | | , | |

I'll model this as a Traveling Salesperson Problem using a circuit constraint.

MCP add_item (multiple)

```
include "globals.mzn";
int: n = 9;
array[1..n,1..n] of int: dist =
[| 0, 65, 60,184,195,319,299,478,631
 | 65, 0,125,119,130,254,234,413,566
 60,125, 0,184,157,281,261,440,593
 |184,119,184, 0,208,252,136,315,468
 |195,130,157,208, 0,136,280,459,629
 319,254,281,252,136, 0,217,391,566
 299,234,261,136,280,217, 0,188,343
 478,413,440,315,459,391,188, 0,157
 |631,566,593,468,629,566,343,157, 0|];
array[1..n] of var 1..n: succ;
var int: total_dist = sum(i in 1..n)(dist[i,succ[i]]);
constraint circuit(succ);
solve minimize total_dist;
```

Optimal route found: Vienna \rightarrow St. Pölten \rightarrow Linz \rightarrow Salzburg \rightarrow Bregenz \rightarrow Innsbruck \rightarrow Klagenfurt \rightarrow Graz \rightarrow Eisenstadt \rightarrow Vienna Total distance: 1,564 km Route verification:

- Each city visited exactly once: \checkmark (circuit constraint)
- Distance calculation correct: \checkmark
- Starting/ending in Vienna (city 1): \checkmark

User

Assume the road between Vienna and Eisenstadt is blocked, what is now the shortest tour?

LLM

I'll modify the distance matrix to make the Vienna-Eisenstadt route impossible (infinite distance).

MCP edit_model

```
array[1..n,1..n] of int: dist =
[| 0, 65,9999,184,195,319,299,478,631
| 65, 0,125,119,130,254,234,413,566
|9999,125, 0,184,157,281,261,440,593
|184,119,184, 0,208,252,136,315,468
|195,130,157,208, 0,136,280,459,629
|319,254,281,252,136, 0,217,391,566
|299,234,261,136,280,217, 0,188,343
|478,413,440,315,459,391,188, 0,157
|631,566,593,468,629,566,343,157, 0|];
```

LLM

Optimal route: Vienna \rightarrow Linz \rightarrow St. Pölten \rightarrow Salzburg \rightarrow Bregenz \rightarrow Innsbruck \rightarrow Klagenfurt \rightarrow Graz \rightarrow Eisenstadt \rightarrow Vienna Total distance: 1,694 km (+130 km compared to unblocked route)

A.3 N-Queens

This example shows how the same model can be solved with different parameter values, and the solving times can be obtained.

User

Check whether you can place n Queens on an nxn chessboard. Try n=10,20,30,40 and compare the solving times

Let me create a model for the N-Queens problem and test different sizes.

MCP clear_model

Model cleared

MCP add_item (multiple)

```
int: n = 10;
array[1..n] of var 1..n: queens;
constraint alldifferent(queens);
constraint alldifferent([queens[i] + i | i in 1..n]);
constraint alldifferent([queens[i] - i | i in 1..n]);
solve satisfy;
```

LLM

Testing n=10:

MCP solve_model

```
{'status': 'SAT',
'solution': Solution(queens=[3,6,9,1,8,4,2,7,5,10],_checker=''),
'solve_time': 0.001}
```

LLM

Testing n=20:

MCP edit_model

int: n = 20;

MCP solve_model

```
{'status': 'SAT', 'solution': Solution(
queens=[4,18,16,11,13,1,3,19,8,12,17,2,10,15,6,14,9,7,5,20],
_checker=''), 'solve_time': 0.005}
```

LLM

Testing n=30:

```
MCP \texttt{ edit\_model}
```

int: n = 30;

 $MCP \texttt{ solve_model}$

```
{'status': 'SAT', 'solution': Solution(
queens=[17,23,9,18,2,13,8,1,24,21,6,22,11,26,
5,25,19,14,10,3,29,27,15,4,12,20,16,7,28,30], _checker=''),
'solve_time': 0.04}
```

LLM

Testing n=40:

MCP edit_model

int: n = 40;

MCP solve_model

```
{'status': 'SAT', 'solution': Solution(
queens=[12,34,23,8,20,31,15,27,18,33,5,2,26,10,16,32,4,11,14,3,
9,25,28,30,35,6,1,17,21,37,13,29,24,19,7,22,39,36,38,40],
_checker=''), 'solve_time': 0.043}
```

LLM

Solve times comparison: n=10: 0.001s n=20: 0.005s n=30: 0.040s n=40: 0.043s Solutions exist for all tested board sizes. Time complexity increases non-linearly but remains manageable up to n=40.

A.4 Timetabling

This example showcases a timetabling problem. As a follow up question, the user asks for a more balanced schedule.

User

We need to schedule 6 courses in a university department. Each course has different requirements - some need labs, some need computer rooms, and a few need 2 consecutive time slots instead of just one. We have 4 rooms with different equipment and sizes, and 4 time slots (9am-4pm).

User

Specifically:

- 3 courses need lab access (one also requires computers)
- 3 courses need computer rooms
- 2 courses are "double-length" needing 2 slots
- Student groups range from 15 to 45 students
- Room capacities range from 30 to 50 students

The goal is to find a feasible schedule where everyone gets the room they need when they need it.

LLM

Let me help create a model for this scheduling problem. I'll formulate it step by step.

MCP clear_model

MCP add_item (multiple)

```
int: n_courses = 6;
int: n_rooms = 4;
int: n_slots = 4;
array[1..n_rooms] of int: room_capacity = [30, 35, 45, 50];
array[1..n_courses] of int: course_size = [15, 30, 35, 40, 45, 25];
array[1..n_rooms] of bool:
    has_lab = [true, true, false, false];
array[1..n_rooms] of bool:
    has_computers = [false, true, true, true];
array[1..n_courses] of bool:
    needs_lab = [true, true, true, false, false, false];
array[1..n_courses] of bool:
    needs_computers = [false, true, false, true, true, true];
array[1..n_courses] of bool:
    needs_computers = [false, true, false, true, true, true];
array[1..n_courses] of bool:
    is_double = [true, false, true, false, false, false];
```

LLM

Now let's define our decision variables:

MCP add_item (multiple)

```
array[1..n_courses, 1..n_slots] of var bool: schedule;
array[1..n_courses, 1..n_rooms] of var bool: room_assignment;
```

Let's add constraints:

MCP add_item (multiple)

```
constraint forall(c in 1..n_courses)(sum(s in 1..n_slots)
     (schedule[c,s]) = if is_double[c] then 2 else 1 endif);
constraint forall(c in 1..n_courses)(sum(r in 1..n_rooms)
     (room_assignment[c,r]) = 1);
constraint forall(s in 1..n_slots, r in 1..n_rooms)
     (sum(c in 1...n_courses)
          (schedule[c,s] * room_assignment[c,r]) \leq 1);
constraint forall(c in 1..n_courses where is_double[c])(
    forall(s in 1..._slots-1)(schedule[c,s] = 1 \rightarrow
schedule[c,s+1] = 1));
constraint forall(c in 1..n_courses, r in 1..n_rooms)(
  <code>room_assignment[c,r] = 1 \rightarrow (</code>
    (needs_lab[c] \leq has_lab[r]) \wedge
    (needs_computers[c] \leq has_computers[r]) \wedge
    (course_size[c] < room_capacity[r])</pre>
  )
);
solve satisfy;
```

LLM

Let's solve it:

```
MCP solve_model
```

```
{'status': 'SAT', 'solution': Solution(schedule=
[[False, False, True, True],
 [False, True, False, False],
 [False, False, True, False],
 [False, False, True, False],
 [False, False, False, True]],
room_assignment=
[[True, False, False, False],
 [False, True, False, False],
 [False, False, False, True],
 [False, False, True, False],
 [False, False, True, False],
 [False, False, False, True]], _checker=''), 'solve_time': 0.002}
```

A solution has been found! Let me interpret it:

- Course 1 (double length, needs lab): Room 1, Slots 3-4
- Course 2 (needs lab + computers): Room 2, Slot 2
- Course 3 (double length, needs lab): Room 2, Slots 3-4
- Course 4 (needs computers): Room 4, Slot 3
- Course 5 (needs computers): Room 3, Slot 4
- Course 6 (needs computers): Room 4, Slot 4

This solution satisfies all constraints:

- Double-length courses are scheduled in consecutive slots
- Room capacities match course sizes
- Lab and computer requirements are met
- No room is double-booked
- Each course gets its required number of slots

User

Give me the timetable please.

LLM

Timetable based on the solution: Timeslots: 1 (9am): -2 (10am): C2 in Room 2 3 (11am): C1 in Room 1, C3 in Room 2, C4 in Room 4 4 (12pm): C1 in Room 1, C3 in Room 2, C5 in Room 3, C6 in Room 4 Room assignments: Room 1 (Lab): C1 (15 students) Room 2 (Lab+Computers): C2 (30 students), C3 (35 students) Room 3 (Computers): C5 (45 students)

Room 4 (Computers): C4 (40 students), C6 (25 students)

User

Can you make it more balanced, that for each time slots a similar number of courses are scheduled?

Let me add a constraint to balance the load across time slots and rerun the model.

```
MCP add_item
```

```
constraint forall(s1,s2 in 1..n_slots)(
   abs(sum(c in 1..n_courses)(schedule[c,s1]) -
        sum(c in 1..n_courses)(schedule[c,s2])) < 1
);</pre>
```

```
MCP solve_model
```

```
{'status': 'SAT', 'solution': Solution(schedule=
[[False, False, True, True],
[True, False, False, False],
[False, False, True, True],
[False, True, False, False],
[False, True, False, False],
[True, False, False, False]],
room_assignment=
[[True, False, False, False],
[False, True, False, False],
[False, True, False, False],
[False, False, True, False],
[False, False, True, False],
[False, False, False, True],
[False, False, False, True]], _checker=''), 'solve_time': 0.002}
```

LLM

New timetable: Slot 1 (9am): C2 in Room 2, C6 in Room 4 Slot 2 (10am): C4 in Room 3, C5 in Room 4 Slot 3 (11am): C1 in Room 1, C3 in Room 2 Slot 4 (12pm): C1 in Room 1, C3 in Room 2

Each slot now has either 2 courses (balancing double-length courses across slots).

User

Check that all constraints are still satisfied.

Let me verify all constraints: Room Resources:

- C1 (lab needed) \rightarrow Room 1 (has lab) \checkmark
- C2 (lab+computers) \rightarrow Room 2 (has lab+computers) \checkmark
- C3 (lab needed) \rightarrow Room 2 (has lab+computers) \checkmark
- C4 (computers) \rightarrow Room 3 (has computers) \checkmark
- C5 (computers) \rightarrow Room 4 (has computers) \checkmark
- C6 (computers) \rightarrow Room 4 (has computers) \checkmark

Room Capacities:

- Room 1 (30) > C1 (15) \checkmark
- Room 2 (35) > C2,3 (30,35) \checkmark
- Room 3 (45) > C4 (40) \checkmark
- Room 4 (50) > C5,6 (45,25) \checkmark

Double-length courses:

- C1: Slots 3-4 consecutive \checkmark
- C3: Slots 3-4 consecutive \checkmark

No room conflicts:

• Each room has max 1 course per slot \checkmark

Load balancing:

- Slot 1: 2 courses
- Slot 2: 2 courses
- Slot 3: 2 courses
- Slot 4: 2 courses

Perfect balance achieved \checkmark All constraints are satisfied.

References

- [1] Anthropic. Model context protocol: A standard for AI system integration. https: //modelcontextprotocol.io, 2023. Accessed: 2024-03-15.
- [2] G. Betz, K. Richardson, and M. A. Musen. Procedural reasoning networks for understanding mechanisms in physical systems. arXiv preprint arXiv:2110.00088, 2021.

- [3] G. Chu. Chuffed: A lazy clause generation solver. In Proceedings of the Workshop on Constraint Modelling and Reformulation, 2011.
- [4] A. Curtis, N. Kumar, J. Cao, T. Lozano-Pérez, and L. P. Kaelbling. Trust the PRoC3S: Solving long-horizon robotics problems with llms and constraint satisfaction. In *Proceedings of the Conference on Robot Learning (CoRL)*, 2024.
- [5] I. Drori, L. Kates, Y. Katz, K. Sinha, J. Zou, Y. Shen, Y. Guo, J. Lepert, X. Cheng, C. B. Bruss, et al. Integrating large language models with scientific computing libraries. arXiv preprint arXiv:2306.08999, 2023.
- [6] S. K. Jha, S. Jha, P. Lincoln, N. D. Bastian, A. Velasquez, R. Ewetz, and S. Neema. Counterexample guided inductive synthesis using large language models and satisfiability solving. In *MILCOM 2023 - 2023 IEEE Military Communications Conference*, pages 944–949. IEEE, 2023.
- [7] S. Kambhampati et al. LLMs can't plan, but can help planning in LLM-modulo frameworks. In Proceedings of the 41st International Conference on Machine Learning (ICML), 2024.
- [8] J. Lee, T. Le, J. Chen, and D. Lee. Do language models plagiarize? In Y. Ding, J. Tang, J. F. Sequeda, L. Aroyo, C. Castillo, and G. Houben, editors, *Proceedings of the ACM Web Conference 2023, WWW 2023, Austin, TX, USA, 30 April 2023 - 4 May 2023*, pages 3637–3647. ACM, 2023.
- [9] P. McGuinness. Model context protocol changes AI integration, 2024.
- [10] MCP Working Group. Machine-client protocol (MCP) specification, 2023. Available online at https://spec.modelcontextprotocol.io/specification/.
- [11] K. Michailidis, D. Tsouros, and T. Guns. Constraint modelling with LLMs using in-context learning. In *Proceedings of the 30th International Conference on Principles* and Practice of Constraint Programming, CP 2024, pages 20:1–20:16. Schloss Dagstuhl– Leibniz-Zentrum fuer Informatik, 2024.
- [12] MiniZinc Team. Python MiniZinc: Python bindings for the MiniZinc API, 2021. Available online at https://pypi.org/project/minizinc/.
- [13] N. Nethercote, P. J. Stuckey, R. Becket, S. Brand, G. J. Duck, and G. Tack. MiniZinc: An open-source tool for constraint modeling and solving. *Constraints*, 15(2):123–145, 2010.
- [14] L. Pan, A. Albalak, X. Wang, and W. Y. Wang. LOGIC-LM: Empowering large language models with symbolic solvers for faithful logical reasoning. In *Proceedings of* the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP), 2023.
- [15] F. Régin, E. D. Maria, and A. Bonlarron. Combining constraint programming reasoning with large language model predictions. In *Proceedings of the 30th International Conference on Principles and Practice of Constraint Programming (CP)*, 2024.
- [16] S. Sharma and B. Sodhi. Calculating originality of llm assisted source code. arXiv preprint arXiv:2307.04492, 2023.
- [17] F. Voboril, V. P. Ramaswamy, and S. Szeider. Realtime generation of streamliners with large language models. arXiv preprint arXiv:2408.10268, 2024.

- [18] J. Wei, X. Wang, D. Schuurmans, M. Bosma, B. Ichter, F. Xia, E. Chi, Q. Le, and D. Zhou. Chain-of-thought prompting elicits reasoning in large language models. In Advances in Neural Information Processing Systems, volume 35, pages 24824–24837, 2022.
- [19] H. Wu, C. Barrett, and N. Narodytska. Lemur: Integrating large language models in automated program verification. In *The 3rd Workshop on Mathematical Reasoning and* AI at NeurIPS'23, 2023.
- [20] R. Yamauchi, S. Sonoda, A. Sannai, and W. Kumagai. LPML: LLM-prompting markup language for mathematical reasoning, 2023.
- [21] Y. Ye et al. SATLM: satisfiability-aided language models using declarative prompting. In Advances in Neural Information Processing Systems (NeurIPS), 2023.