Enabling New HDLs with Agents

Mark Zakharov, Farzaneh Rabiei Kashanaki, Jose Renau Department of Computer Science and Engineering University of California, Santa Cruz {mzakharo, frabieik, renau}@ucsc.edu

January 3, 2025

arXiv:2501.00642v1 [cs.AR] 31 Dec 2024

Abstract

Large Language Models (LLMs) based agents are transforming the programming language landscape by facilitating learning for beginners, enabling code generation, and optimizing documentation workflows. Hardware Description Languages (HDLs), with their smaller user community, stand to benefit significantly from the application of LLMs as tools for learning new HDLs. This paper investigates the challenges and solutions of enabling LLMs for HDLs, particularly for HDLs that LLMs have not been previously trained on.

This work introduces HDLAgent, an AI agent optimized for LLMs with limited knowledge of various HDLs. It significantly enhances off-the-shelf LLMs. For example, PyRTL's success rate improves from zero to 35% with Mixtral 8x7B, and Chisel's success rate increases from zero to 59% with GPT-3.5-turbo-0125. HDLAgent offers an LLM-neutral framework to accelerate the adoption and growth of HDL user bases in the era of agentic LLMs.

1 Introduction

Recent advancements in Large Language Models (LLMs), such as OpenAI's GPT, Google's Gemini, and Mistral AI's Mixtral are transforming the programming landscape. These models assist newcomers by providing intelligent assistance, generating code snippets, and offering context-aware suggestions, thereby significantly lowering the barriers to entry into programming.

However, LLMs currently offer limited support for niche Hardware Description Languages (HDLs), which often form specialized communities. Despite the ubiquity of Verilog¹, emerging languages like Chisel3 [6], PyRTL [8], and DSLX [13] illustrate the need for LLMs to adapt to new HDLs. The lack of training data for these languages means that existing LLMs underperform, creating a disincentive for developing new HDLs.

Additionally, many high-performance LLMs are closed-source, limiting their adaptability. Enhancing LLM capabilities without waiting for lengthy training cycles is crucial. Effective integration of LLMs with emerging HDLs would not only facilitate their adoption but also prevent LLMs from becoming barriers to innovation in hardware design.

To address these challenges, we propose a new LLM-neutral AI agent, **HDLAgent**, that incorporates state-of-the-art AI coding agent techniques, specifically adapted to support multiple HDLs with limited LLM support. This addresses the challenge of generating accurate and functional code in HDLs that have proven difficult for existing LLMs.

AI agents [49] typically involve multiple workflow steps, including LLM prompts and interactions with external tools. Techniques such as self-reflection like Chain-of-Thought (CoT) [36], memory enhancement through Retrieval Augmented Generation (RAG), and error minimization through grounding are commonly utilized. These techniques help improve the responses of LLMs by refining their input data and correcting syntax/semantics errors.

Although AI agents share these common workflow steps, they need to be adapted to the specific problem. HDLAgent incorporates state-of-the-art AI coding agent techniques in self-reflection and grounding using compiler errors, though these concepts are similar to existing coding LLM works. The novelty in HDLAgent lies in its approach to memory steps. We propose:

• Creating an HDL description summary to enable knowledge transfer between Verilog and the new HDL.

 $^{^1{\}rm The}$ original Verilog was designed in 1983, and modern versions like System-Verilog are semantically compatible with it.

- Generating few-shot learning examples that enrich the HDL description summary.
- Enhancing grounding messages from compile errors to rectify them.

Additional contributions are the LLM performance evaluation across multiple HDLs, and propose changes in the HDLs to better support LLMs.

HDLAgent succeeds where plain LLMs consistently fail. For instance, using HDLAgent with Mix-8x7B yields a 44% success rate when writing Chisel, compared to just 3% of tests passing without HDLAgent. Other LLMs, like GPT-3.50, improve from a 3% success rate for DSLX to 48% with HDLAgent. HDLAgent also benefits LLMs with Verilog; for Mix-8x22B, the success rate increases from 13% to 53%.

In summary, the key contributions of this paper are:

- HDLAgent Development: Introduction of HDLAgent, enhancing LLM performance in code generation for underrepresented HDLs.
- Comprehensive Evaluation: Detailed evaluations show HDLAgent boosts Chisel code success from 3% to 44%, and over 90% for concise code samples across all HDLs.
- HDL Enhancement Proposals: Strategic modifications to HDL designs are suggested to guide future developments in HDL and compiler technologies.
- **Practical Impact and Adoption:** Our approach bridges significant gaps in applying LLMs to hardware design, simplifying the adoption of new HDLs and boosting developer productivity.

2 Related Work

To adapt to a new language, there are two potentially complementary approaches to improve LLM output: fine-tuning and Agents. These techniques can be iteratively combined to develop Agents that produce even better results.

Fine-tuning is the process of adjusting the parameters of an LLM on a specific dataset or task to improve its performance. Thus, fine-tuning can be applied to optimize an LLM for a new language. RTL-Coder [21] fine-tunes a 7B Mistral model with GPTgenerated synthetic Verilog data. In contrast, HD-LAgent uses off-the-shelf LLMs without fine-tuning. The advantage of avoiding fine-tuning is that many commercial flows do not allow it, and it is not a trivial problem for languages with a very small set of examples.

URIAL [18] bypasses the need for fine-tuning by enriching prompts with illustrative examples. These prompts resemble the few-shot format used by HD-LAgent, incorporating both format and examples. While URIAL has shown effectiveness in circumventing the need for instruction alignment, HDLAgent further illustrates the possibility of learning previously unknown languages.

Agents [49] iterate through LLMs using three main techniques to improve performance: self-reflection, memory, and grounding.

Self-reflection techniques use a sequence of interactions with the LLM instead of a simple question/answer format. In this work, we call self-reflection to chaining LLMs prompts to other LLMs. CoT [36] is an example of self-reflection. Lumos [43] uses CoT to enable simpler LLMs to outperform more advanced ones. These studies highlight significant progress in this rapidly evolving field. Recent works [39] propose an optimization method to find the best prompt.

Memory techniques such as few-shot in-context learning [19, 5] and RAG [17] use instructions, supplemental information, and relevant examples to enhance efficiency. Various methods exist for constructing prompts with extended context. One such technique, querying an embedding database to augment the context, is known as Retrieval Augmented Generation (RAG).

Grounding involves verifying or checking the LLM's response using an external tool. While this is not always feasible, in code generation, a compiler or testbench can validate and identify issues with the LLM-generated response. This may trigger further iteration with the LLM.

Agents with self-reflection, memory, and grounding have been applied to improve code generation. If we ignore the HDL target, and focus on generic programming languages like Python or C++, several works [29, 48] show that errors can be fixed by grounding the generated code against compiler or testbench feedback. Intervenor [34] proposes an Agent that successfully leverages compiler feedback. Other recent works [24, 9, 34, 23, 25, 38, 45, 12, 26] propose Agents to iterate over testbench results to fix sematic errors in code.

VerilogCoder [47] introduces an autonomous coding approach using graph-based planning for synthesizing Verilog code from specifications. It combines a traditional LLM with a novel AST-based waveform tracing tool to refine the generated code. This tool traces the expected signal flow within the AST representation of Verilog, improving both the accuracy and reliability of the generated code. VerilogCoder has been shown to significantly reduce errors in synthesizable code by anticipating and correcting logical flaws before compilation.

The paper "Towards LLM-Powered Verilog RTL Assistant: Self-Verification and Self-Correction" [16] discusses a framework that employs LLMs to not only generate but also verify and correct RTL designs in Verilog. This system uses a self-verification method that incorporates runtime feedback to iteratively refine the Verilog code, effectively decreasing the cycle time between code generation and testing. It represents a shift towards fully autonomous RTL design, promising to streamline the Verilog development process significantly.

Besides CoT, some notable self-reflection techniques for code generation include: Self-planning [15] proposes a planning stage or self-reflection before code generation; Self-Debug [7] proposes how to improve code generation by generating explanations in the intermediate steps; ChatCoder [35] uses selfreflection to paraphrase and elaborate on the initial question.

Early work [31, 30, 40] with LLMs and Verilog avoids using Agents because LLMs like GPT-4 are already reasonably trained for Verilog. Several AIbased chip design competitions [10, 11] required designs implemented in Verilog. Looking at the top performers, they tend to use GPT-4 and focus on combinational modules where the top level module IO is fully specified. In all the cases, the humanin-the-loop guides the LLM to fix problems with the generated code and iterate over the testbench results.

The same AI coding Agent concepts of self-reflection, memory, and grounding can be applied to Verilog. Concurrent works include AutoChip [32], RTLFixer [33], and HDLDebugger [42].

AutoChip [32] uses testbench feedback to ground the generated Verilog. It is similar to Self-Edit [45] and Self-Repair [26], but with a focus on Verilog. AutoChip focuses on simulation errors, which is not included in HDLAgent but is a potential extension.

RTLFixer [33] uses ReAct [41] for self-reflection and compiler errors for grounding. RTLFixer utilizes human-generated explanations for various error messages, whereas HDLAgent uses previous examples of errors and their respective fixes. Unlike RTLFixer, which targets only Verilog, HDLAgent provides different error/fix strategies for each HDL.

HDLDebugger [42] fine-tunes CodeLlama to fix code generation, rather than to generate better Verilog, as RTLCoder does. HDLDebugger uses compiler error messages to ground the generation and applies this to the fine-tuned CodeLlama to fix the code. HDLDebugger represents a different approach that, when available (publication expected in August 2024), could be applied to HDLAgent for fixing compiler errors. However, it will require fine-tuning for each HDL. From the provisional paper, HDLDebugger does not seem to apply self-reflection.

For benchmarking, we use HDLEval [44] and VerilogEval [20] when possible. Both HDLEval and VerilogEval include several tests derived from HDL-Bits [3]. HDLBits is a website with problems and tests designed to teach students the basics of Verilog. These tests are simple and exemplify the types of questions a person learning a new HDL might have. Examples include outputs with a few lines of code, such as how to rotate an input value.

HDLEval [44] includes HDL-neutral tests, incorporating simple tests from HDLBits as well as tests from the Efabless LLM competition. Importantly, it categorizes tests into combinational and pipelining. This distinction is crucial because some languages, like DSLX, do not support unrestricted pipelining, allowing only combinational tests to be used.

VerilogEval [20] and RTLLM [22] propose test sets to evaluate only Verilog designs. VerilogEval consists of two sets of problems: Human and Machine. The Human category includes tests generated by humans, while the Machine category comprises tests translated into English from existing Verilog code using GPT-3.5. RTLLM features a different set of problems divided into arithmetic and logic. Both works use simulation for testing correctness and evaluate only Verilog code. RTLLM claims that the tests could be used for languages like Chisel, but the paper lacks explanations as how to address issues with matching Chisel-generated IOs.

3 HDLAgent

HDLAgent is an AI Agent (refer to Section 2) specifically tailored for adapting cutting-edge AI coding techniques to Hardware Description Languages (HDLs). This adaptation is crucial for HDLs that are not typically included in the training data of Large Language Models (LLMs).

LLMs demonstrate proficiency in transfer learning [27, 46]. HDLAgent exploits this capability, enabling LLMs to handle HDLs with limited training data. By facilitating the transfer of knowledge from well-known HDLs, such as Verilog, to new HDLs such as PyRTL, HDLAgent empowers the LLM to adapt its understanding of familiar programming languages to target languages. This process mirrors human learning mechanisms [28].



Figure 1: HDLAgent flow leveraging compiler feedback.

As illustrated in Figure 1, HDLAgent addresses the critical challenge of limited HDL-specific knowledge. It employs two primary memory components to bridge this gap: the "main context" and the "compiler context". The "main context" (described in Section 3.1) offers a succinct summary of HDLs along with targeted examples. The "compiler context" (Section 3.2) enhances code generation by integrating compiler feedback, grounding the output within practical and executable constraints.



Figure 2: HDLAgent Main and Compiler context prompt components.

3.1 Main Context

The "main context" in HDLAgent serves to inform the LLM about the specific HDL in use. Figure 2 illustrates this main context, which comprises four key elements: HDL description, few-shot examples, Prefix, and Suffix.

The HDL description provides a concise summary of the HDL, tailored to the LLM's familiarity with the language. While our evaluation demonstrates that the HDL description can be optimized for each LLM, we opt for simplicity by selecting the description that performs best with Mix-8x7B and GPT-3.5n. This choice is motivated by these LLMs' lower proficiency in HDLs such as Chisel, DSLX, and PyRTL. It is worth noting that the HDL description proves less beneficial only when the LLM already excels in a given HDL, such as Verilog. Such few-shot are crucial, especially in HDLs with unique syntaxes, helping LLMs avoid common pitfalls.

The prefix and suffix in the main context serve as navigational aids for the LLM, directing the model's attention to the task at hand and setting boundaries for its output. The prefix introduces the problem in the HDL's language, while the suffix provides specific instructions to ensure the output adheres strictly to HDL syntax, avoiding unnecessary English explanations and maintaining consistency in output formats.

Interestingly, even for LLMs capable of processing entire HDL reference manuals within their context window, utilizing a summary enhances both success rate and token efficiency. Our evaluation clearly demonstrates a significant improvement in success rates when employing an HDL description. The intuition is that focusing on the Verilog differences is more important than providing a lengthy description of the language.

Since including a complete tutorial is neither practical nor advantageous for the evaluated LLMs, we use an HDL description summary instead. To generate these summaries, we leverage LLMs with large context windows, specifically GPT-4 and GPro-1.0, to condense the HDL reference manuals.

For PyRTL and Chisel, our evaluation revealed that the most effective prompt was generated by GPT-4 using the following instruction: "PyRTL is a Hardware Description Language with the following reference documentation and tutorial. Create documentation useful for LLMs trying to generate PyRTL code. The generated documentation should include code snippets and highlight any language syntax that is atypical for HDLs."

For DSLX, the optimal summary was produced by GPro-1.0 using a similar prompt, with the addition of "Be concise and avoid examples with similar syntax." at the end. This minor variation in the prompt yielded the best results.

Complementing the HDL description, the "main context" provides few-shot examples to illustrate common HDL operations and potential areas of confusion. These examples cover bit operations, reductions, loops, multiplexing, and a multiply-add block. While the HDL Description can include some examples, it is important to cover these basic operations with simple examples, as LLMs tend to revert to incorrect syntax.

The bit operations example demonstrates simple bit manipulation and concatenation, while the reduction example showcases a basic NOR reduction over a given input. Loops can be particularly confusing in some HDLs. For instance, in DSLX, all variables are immutable, but loops have a special syntax for accumulator variables. Including an example like the one in Listing 3 in the HDL context helps address cases where the LLM needs to create a loop.

The Prefix follows the few-shot examples, briefly directing the original Question with a statement such as the following for DSLX: "The following statements describe the problem to be addressed in DSLX."

The Suffix, appended after the question, serves to limit the scope of the problem and provide specific instructions. It includes directives like "respond with valid program syntax only, without additional English explanations" and tailors HDL input and output formats. Handling I/Os is crucial, especially for HDLs with multiple output options, necessitating instructions to maintain output integrity and naming consistency. For DSLX, the Suffix includes directives like "do not split the outputs into individual bits" and "variables assigned to the output struct should have the same name as the struct fields." This Suffix concept is essential even when using Verilog, as it can employ interfaces, structs, or plain Verilog-2001 syntax.

The HDLAgent Suffix facilitates interfacing between different HDLs and Verilog. However, maintaining consistent naming conventions and common syntax remains a critical issue that the Suffix must address, even in single-HDL use cases.

3.2 Compiler Context

HDLAgent's compiler context employs an iterative approach to rectify inaccurately generated HDL code. This process grounds the LLM-generated code by providing feedback on potential errors or hallucinations. Before submitting the LLM output to the compiler, HDLAgent identifies the code section. This step is crucial, as LLMs may generate English explanations despite explicit instructions to avoid them.

When the generated program fails compilation, producing a compiler error, HDLAgent constructs a query (illustrated in Figure 2). This query begins with the "main context," disregarding any non-code responses. It then incorporates the latest code snippet, followed by a statement indicating "the previous code has the following compile error," succeeded by the specific compiler error message. If HDLAgent possesses an example fix for addressing the compiler error, it appends this "sample fix" to the context.

The sample fix methodology is analogous to RTL-Fixer [33], which provides explanations for resolving Verilog error messages. HDLAgent extends this concept to cover multiple HDLs, elucidating the special syntax requirements of a given HDL when necessary.

HDLAgent presents the entire latest code snippet in its query. We experimented with a method inspired by CWhy [4], which focuses on a few lines of code surrounding the compiler error message. While this approach worked for some LLMs like GPT-4, it proved less effective with others. Although this delta approach reduces token usage, it led to increased error rates, prompting us to exclude it from our evaluation. As LLMs continue to evolve, this approach may warrant reconsideration in future iterations.

3.3 **Prompt Optimizations**

Besides the previous main and compiler context there are also several subtle but important optimizations:

- Placing the prompt after the context achieves better results [14].
- HDLAgent approach avoids the chat-like history with all the previous code generations and fixes. Keeping the original question iteration but not the compiler error fixes achieves better results [32]. We did a quick test with HDLAgent and DSLX. Avoiding a history with all the error fixes had a 5% improvement in GPT-4 and a 27% in Mix-8x7B.
- Most LLMs generate code snippets in quoted sections, but not always. Even worse, it is common to write English explanations even thought the prompt explicitly asks to just write code. To address this, for each language we have a filter/detector that removes English and finds code boundaries. For example in Verilog it allows preprocessor directives and code between module and endmodule. Without this, some smaller LLMs fail very frequently.

3.4 LLM Cost

Our approach approximates LLM cost by the number of tokens utilized, serving as a practical proxy for monetary cost and compute resources required. As context length increases, so do the costs and computational demands.

While token usage offers a simple metric for gauging efficiency, our primary focus remains on balancing accuracy with cost-efficiency. This approach necessitates a judicious use of context and iteration, ensuring that each interaction with the LLM is as productive as possible. Future studies could investigate efficiency metrics like error rate \times tokens. A crucial aspect to consider is the "stateless" nature of LLMs, where each call requires a complete context. APIs like OpenAI and Mixtral lack a "chat-like" interface that accumulates context across queries, unlike GPro-1.0, which can retain context. Depending on the cost model for LLMs like GPro-1.0, retaining history may be more efficient. However, the context length of GPro-1.0 is insufficient for handling multiple iterations. Therefore, in this work, we flush the history and disregard cost models, considering only total token usage after all HDLAgent iterations.

4 Setup

Table 1 lists all the languages used in the evaluation and the compiler versions used by this paper. When a date is provided it corresponds to the top-of-tree version at that given month. For Quality of Results (QoR), we use Yosys synthesis results.

Table 1: Language Tools and Versions

Language	Tool	Version
Verilog	Yosys	0.35
Chisel	FIRRTL	3.5.0-RC2
PyRTL	PyRTL compiler	0.10.2
DSLX	XLS	3/2024

Table 2: LLMs used in the evaluation

LLM	Version	Date	Context
GPT-4	gpt-4-1106-preview	4/23	128000 •
GPT-3.5n	gpt-3.5-turbo-0125	9/21	16385
GPT-3.5o	gpt-3.5-turbo-1106	9/21	16385
GPro-1.0	gemini-1.0-pro-001	2/24	32720
Mix-8x7B	Mixtral-8x7B-instruct	12/23	32768
Mix-8x22B	Mixtral-8x22B-v0.1	3/24	32768 •

Table 2 shows the LLMs used. Many LLMs, including GPT-3.50, are not deterministic. They have produced differing outcomes for the same example under identical prompt conditions. OpenAI recently proposed a new API to address this issue, providing a seed, but this solution still needs to be fully implemented across all LLMs. For fair evaluation, we avoid the deterministic settings and perform 1, 5, or 10 runs depending on the top@k parameter.

5 Evaluation

5.1 Overall Results

To comprehensively assess HDLAgent's performance across various LLMs, we evaluate each HDL (Chisel, PyRTL, DSLX, and Verilog) against four benchmark tests: VH (VerilogEval-Human), VM (VerilogEval-Machine), HC (HDLEval-Comb), and HP (HDLEval-Pipe).

While VerilogEval tests comprise several Verilogspecific questions, they do not fully demonstrate the potential of the LLM/HDLAgent combination as effectively as HDLEval (HC, HP). This is primarily due to VerilogEval's inclusion of Verilog-specific instructions in some tests, such as implementing a D latch using an "always" block. Such tests are not suitable for evaluating languages other than Verilog. Consequently, we utilize VH and VM primarily for Verilog or as a reference point, while focusing our evaluation on HDLEval (HC and HP).

The results are broken down into five key components to delineate the incremental benefits provided by HDLAgent:

- *Base*: Represents the baseline performance of an LLM without HDLAgent enhancements but includes basic I/O formatting and general code generation guidelines.
- *Description*: Adds a concise HDL Description to the LLM context, improving specificity (see Section 3.1 for details).
- *Few-shot*: Adds language-specific few-shot examples. Section 5.2 provides further insights on the HDL Description and few-shot context selection.
- *Compile*: Incorporates compiler feedback with up to eight iterations to refine the generated code, optimizing accuracy (justification for the number of iterations is in Section 5.3).
- Fixes: Performs the same iterations as Compile, but for each iteration, provides a suggestion alongside a generic example on how to address the specific compiler error.

Chisel (Figure 3), a Scala-based HDL, presents a unique challenge and opportunity. Most LLMs are familiar with Scala but have limited knowledge of Chisel. While several LLMs demonstrate familiarity with its basic syntax, only GPT-4 initially performs adequately with Chisel (52% success rate). All other LLMs exhibit a mere 3% success rate or less.



Figure 3: HDLAgent improves Chisel across all LLMs.

Both the "main context" (comprising Description and Few-shot components) and the "compiler context" (including Compile and Fixes elements) provide substantial benefits, underscoring the necessity of all these components. Notably, with HDLAgent, GPT-3.50 and GPT-3.5n outperform even high-performing LLMs like GPT-4 in its baseline state. Furthermore, HDLAgent significantly enhances GPT-4's performance, elevating its success rate to 72%.

Examining the average performance across all LLMs reveals that each component of HDLAgent contributes significantly to the overall improvement. This underscores the comprehensive and synergistic nature of HDLAgent's approach to enhancing LLM performance in Chisel code generation.



Figure 4: HDLAgent improves PyRTL across all LLMs.

PyRTL (Figure 4), a Python-based Domain Specific Language (DSL), presents challenges similar to those of Chisel. OpenAI's LLMs (GPT-4, GPT-3.5n, GPT-3.50) demonstrate some capability in passing several tests without HDLAgent (Base) due to the strong baseline performance in Python; however, their success rates for PyRTL remain low, ranging from 27% to 40%. When HDLAgent is implemented, these success rates significantly improve, increasing to a range of 44% to 60%. As observed in the Chisel evaluation, HDLAgent's performance boost stems from multiple factors.

Mirroring the Chisel results, all components of HD-LAgent prove important for PyRTL, with the "compiler context" (Compile + Fixes) playing a particularly crucial role. This heightened importance of the compiler iterations for both PyRTL and Chisel can be attributed to their nature as DSLs and therefore their error message generation. Using the PyRTL or Chisel compiler error messages, HDLAgent iterates to fix the code. Since the baseline LLM knows the language, it can interpret the compiler error messages and iterate to fix mistakes.

LLMs often confuse the syntax of DSL host languages (Python for PyRTL, Scala for Chisel) with HDL-specific syntaxes. The HDL Description significantly aids compiler iterations in rectifying these mistakes, demonstrating synergy between the Description and Compile passes. Although not shown in the Figure, enabling only the Compile pass without the HDL Description and Few-Shot examples yields substantially lower overall improvement. This issue could be mitigated if PyRTL or Chisel compilers generated errors that clarified the distinction between base languages and DSLs, perhaps by providing a single few-shot example.



Figure 5: HDLAgent improves DSLX HDLEval-Comb across all LLMs.

DSLX (Figure 5), a Rust-like language, presents unique challenges for implementing a Rust-like syntax that it is not fully compatible with Rust. Due to its limitations on arbitrary pipelining, DSLX cannot be evaluated against HDLEval-Pipe and performs poorly with VerilogEval. While GPT-4 demonstrates some DSLX knowledge, HDLAgent significantly enhances results across all LLMs.

Unlike Chisel and PyRTL, DSLX is not a DSL. Consequently, the "main context" (*HDL Description* + *Few-Shot*) emerges as the primary factor in HD-LAgent's improvement. Explaining the Rust-like syntax and providing examples proves more crucial than grounding results with compile errors.

This shift in importance from compiler feedback

to Description stems from DSLX's unique syntax. While it resembles Rust, not all Rust syntax is valid in DSLX. In contrast, Chisel and PyRTL accept all Scala and Python syntax, respectively. Without clear guidance on DSLX's specific syntax, LLMs struggle to generate correct code.



Figure 6: Verilog succeeds across benchmarks and LLMs .

Verilog (Figure 6) demonstrates the best overall performance in the *Base* condition (without HDLA-gent), as expected due to extensive training with Verilog syntax. It is also the only fair case for VerilogEval use. HDLAgent minimally impacts models already proficient in Verilog but significantly enhances Mix-8x7B and Mix-8x22B, which have some Verilog knowledge, illustrating effective knowledge transfer even with limited Verilog familiarity.

Compiler iterations provide little benefit in error recovery for Verilog. This is due to LLMs' higher proficiency in Verilog syntax. Manually analyzing the HC results, only 5 out of 134 tests showed Verilog syntax errors, with just one potentially benefiting from improved error messaging. As a result, using Slang [2] instead of Yosys [37] did not improve results for GPT-3.50 despite producing more descriptive error messages.

Unexpectedly, Mix-8x22B underperforms Mix-8x7B, possibly due to difficulties in following directions. An "instruct" model might yield better results, but we retained the non-instruct model for its insights into HDLAgent's impact across LLMs.

HDLAgent successfully enables LLMs to use new HDLs. Comparing GPT-3.50 and GPT-3.5n across HDLs shows consistent relative performance regardless of the LLM used. For example, with GPT-4, Verilog achieves a 76% success rate, while PyRTL, the lowest, reaches 60%. This pattern holds across all tested LLMs. Even the worst-performing LLM (Mix-8x22B) achieves a 53% success rate with Verilog and 28% with PyRTL, a significant improvement from the zero success rates many LLMs had without HDLAgent.

5.2 HDLAgent Context Insights

This section offers insights into the selection of HDL Description and few-shot context. One straightforward approach is to utilize the full reference manual directly for the specific language. While this is feasible for models with large context windows such as GPT-4, Mix-8x7B, and GPro-1.0, it generally proves less effective than employing a summarized HDL description. For instance, using a full reference instead of a summary yields no change in results for GPro-1.0, but reduces the success rate from 77% to 66% for GPT-4, and from 59% to 33% for Mix-8x7B. These findings indicate that future LLMs need to improve their handling of lengthy contexts, as all evaluated models struggle with this aspect. Nevertheless, even if the LLMs improve, it is still advantageous to use smaller summary context because it reduces the LLM cost.

Figure 7 shows the DSLX, PyRTL, and Chisel success rate as different reference manuals are summarized for HDLAgent. Each bar shows a different LLM reference summarization prompt (Section 3.1) sorted by accuracy. The breakdown is the contribution of the few-shot examples and the HDL description. Interestingly, adding Few-shot always improves results, and removing HDL Description and just keeping few-shot examples is a reasonable alternative. In some HDL/LLM combinations like Chisel/GPT-3.5n, using either Few-shot or Description works. For other combinations like DSLX/Mix-8x7B, HDL Description helps but Few-shot is necessary. Optimal results require both Few-shot and HDL Description.

5.3 Pass Sensitivity

Top@k is a popular method that measures how results can be improved by generating multiple attempts. A k=5 means that when 5 LLM tries are used, at least one has the correct code generation. Table 3 shows tests passed for HDLEval-Comb for multiple LLMs and multiple top@k values (1,5,10). Due to space, only the HDLEval-Comb results are shown.

Less popular HDLs benefit more from higher top@k values. For example, DSLX shows a 1.22 to 2.08 times improvement in test pass rates from top@1 to top@10. Verilog has between 1.16 and 1.45 times. This discrepancy is likely because the LLM, unfamiliar with the language, starts from an incorrect baseline and struggles to correct errors through compiler feedback. Not being able to recover is very rare in Verilog but over 10% of the DSLX tests have this problem. The higher the top@k, the easier it is to avoid. Once the code compiles correctly, the failure



Figure 7: HDL description and few-shot help LLMs to improve results.

rate for all the HDLs is comparable. This means that if a future HDLAgent improved the iterations or selected better starting points, it could further improve results.



Figure 8: GPro-1.0 converges in a few iterations.

Figure 8 provides further insights into the top@k results, illustrating the increase in accuracy as HD-LAgent iterates with the compiler for GPro-1.0 across various HDLs. We selected GPro-1.0 for this analysis as it requires more iterations to converge compared to other LLMs. While Verilog converges rapidly, other HDLs necessitate 6 to 8 iterations for convergence. Additional iterations beyond this point do not improve the success rate, but altering the starting point, such as using top@5, does enhance results. Overall, 8 iterations further fails to improve success rates while incurring higher token usage.

When employing top@5 and 8 iterations (Table 3), HDLAgent-supported HDLs (Chisel, PyRTL, DSLX) perform equal to or better than the same LLM with Verilog (Base). This finding represents a key contribution of the paper, demonstrating that HD-LAgent effectively enables the use of less popular, community-developed HDLs.



Figure 9: LLM and HDL affect total HDLAgent execution time.

5.4 Time and QoR

Execution time is a crucial metric for any AI Agent. It refers to the time HDLAgent requires to generate a response, not the quality of results (QoR). Figure 9 presents a boxplot of execution times for HDLEval-Comb across different LLMs, encompassing both successful and failed tests. All languages except Verilog undergo a translation process to Verilog, adding overhead. In HDLAgent, the execution time is a function of $\frac{tokens}{second}$, the number of iterations, and external compiler speed.

Among the HDLs, Chisel stands out as the main outlier, with approximately 2/3 of the execution time consumed by the FIRRTL compiler generating Verilog. GPT-4 exhibits faster performance due to fewer errors and consequently fewer iterations. PyRTL and DSLX also show slower performance than Verilog, partly due to additional iterations.

Comparing LLMs, GPT-3.5n and GPT-3.5o generally demonstrate faster overall performance, combining fewer error iterations with rapid result generation. External $\frac{tokens}{second}$ benchmarking [1] indicates that GPro-1.0 is approximately 30% faster than GPT-3.5n and four times faster than GPT-4. However, HDLA-

		Verilog		Chisel			PyRTL		DSLX				
		k=1	k=5	k=10	k=1	k=5	k=10	k=1	k=5	k=10	k=1	k=5	k=10
GPT-4	Base HDLAgent	97 97	$\begin{array}{c} 103 \\ 109 \end{array}$	111 111	69 97	$\frac{88}{103}$	92 107	$53 \\ 81$	79 92	85 98	46 86	79 100	$85 \\ 104$
GPT-3.5n	Base HDLAgent	71 78	96 93	100 98	0 80	$\frac{5}{97}$	9 100	$\frac{36}{59}$	63 79	67 88	$ 15 \\ 55 $	$32 \\ 80$	41 88
GPT-3.50	Base HDLAgent	$\begin{vmatrix} 64 \\ 79 \end{vmatrix}$	93 92	99 100	$\frac{1}{79}$	$\begin{array}{c} 6\\91 \end{array}$	14 99	37 70	60 78	71 89	$\begin{array}{c} 4\\ 65\end{array}$	$\begin{array}{c} 19\\ 86 \end{array}$	$25 \\ 91$
GPro-1.0	Base HDLAgent	66 77	97 96	105 99	$\frac{1}{49}$	$\frac{5}{84}$	12 88	$\frac{6}{38}$	$\begin{array}{c} 17 \\ 66 \end{array}$	31 77	$\begin{array}{c} 0\\ 48 \end{array}$	$\begin{array}{c} 0\\74\end{array}$	$\begin{array}{c} 0\\ 82 \end{array}$
Mix-8x7B	Base HDLAgent	$\begin{vmatrix} 16 \\ 66 \end{vmatrix}$	39 86	50 95	$\begin{array}{c} 4 \\ 60 \end{array}$	12 80	17 86	$\begin{array}{c} 0\\ 48 \end{array}$	$\frac{1}{71}$	$2 \\ 82$	$\begin{array}{c} 0\\ 38 \end{array}$	$\begin{array}{c} 0\\72\end{array}$	0 79
Mix-8x22B	Base HDLAgent	18 72	$\begin{array}{c} 65\\ 96 \end{array}$	78 101	$\frac{2}{35}$	12 79	18 89	$2 \\ 39$	8 67	13 72	$\begin{array}{c} 0\\ 47\end{array}$	0 75	6 81

Table 3: top@k results for HDLEval-Comb for different LLMs with just a Base query or with HDLAgent.

gent results differ due to variations in iterations and speed.



Figure 10: QoR is consistent across LLMs but different across HDLs.

Quality of Results (QoR) is paramount in hardware generation. The tests in HDLEval are relatively small (under 500 LoC of equivalent Verilog), with many being purely combinational. Consequently, frequency or power QoR metrics are not relevant. Instead, we quantify QoR as the ratio of gates used compared to the best known implementation for each module request.

Figure 10 illustrates the gate count ratio relative to the optimal implementation. A ratio of 1 indicates optimal gate count, while 2 signifies double the optimal count. An interesting observation is that for many designs, we used the generated code as the optimal result. The hand-generated reference Verilog for HDLEval often turned out to be less optimal.

Figure 10 only includes successful runs using HD-LAgent with HDLEval-Comb. The plot reveals significant QoR variation compared to the best implementations. Typically, averages are skewed by one or two outliers. For example, in PyRTL generated by Mix-8x7B, the average gate count ratio is 1.63, but drops to 1.12 when two outliers are removed. This suggests that LLMs occasionally generate highly inefficient code, but such instances are infrequent.

A second observation indicates that GPT-4 may appear to underperform; however, this is partly due to its ability to successfully implement larger and more complex designs that are difficult to optimize, which affects the overall results. A third observation is that the efficiency of code generated by various LLMs is generally comparable. Among these, DSLX appears to be the most efficient, albeit by a slim margin. In DSLX generated by GPT-4, 80% of the produced code achieves the optimal 1:1 ratio. This suggests that an efficient compiler like XLS, combined with a popular syntax, can yield superior results for generated HDL code.

5.5 Usefulness Insights

HDLAgent significantly improves the LLM performance across all LLMs and HDLs, but in some cases like DSLX, the average HDLEval-Comb performance is around 60%. This can be interpreted as not good enough because it fails many times.

This section provides more insights in which tests pass and fail. HDLEval-Comb comprises 134 tests, with some being relatively small, containing only a few lines of code, while others are significantly more extensive. HDLEval is designed to encompass a range of tests, from straightforward to complex.

The output program complexity provides key insights in current LLM and HDLAgent limitations. The best proxy for complexity is not the input problem itself, but the lines of code (LoC) required to implement such a problem in a specific language (Verilog in this case).



Figure 11: Even with best LLM (GPT-4), performance degrades as Lines of Code for generated output increases.

Figure 11 illustrates the success rate for HDLEval-Comb using GPT-4 across four different problem sizes: under 25 LoC, 25-50 LoC, 50-75 LoC, and over 75 LoC of equivalent Verilog. A clear degradation in performance is evident as the required code size increases.

As demonstrated in Section 5.1, GPT-4 is the bestperforming LLM with HDLAgent, achieving average success rates of 72% for Chisel, 60% for PyRTL, 64% for DSLX, and 76% for Verilog. Figure 11 reveals that for small problems, HDLAgent performs consistently across all HDLs, with over 90% success rate. Conversely, for large problems exceeding 75 LoC, all HDLs, excluding Chisel, have a consistently low 20% success rate. The performance difference between HDLAgent and Verilog is most pronounced in medium-sized problems ranging from 25 to 75 LoC.

As previously mentioned, most of the errors are semantic. Interestingly, for more complex output problems, new HDLs perform equal to Verilog even though the LLMs have larger training in Verilog.



Figure 12: HDLEval-Comb performance degrades for larger Verilog codes across LLMs.

It is also interesting to compare across LLMs for a single HDL. Figure 12 presents Verilog success rate with different LLMs. While different LLMs exhibit slightly different curves, the overall trend remains consistent: performance significantly degrades as the output problem requires more lines of code. Another interesting observation is that Mixtral models (Mix-8x7B and Mix-8x22B) seems to improve performance for large problems. Although we attribute this improvement primarily to random variation, it indicates that these models demonstrate greater resilience to large problems.

These results have two important implications: First, solving larger problems remains a challenge that LLMs have yet to address, as evidenced by Mix-8x7B achieving a success rate below 40% even with HDLAgent enabled. Second, HDLAgent facilitates equivalent performance for small examples across different HDLs. This latter contribution is particularly important as it demonstrates the utility of HDLAgent for new HDL learners querying an LLM for small code snippet generation.

5.6 Insights for HDLs at the age of LLMs

The goal of this section is to show shortcomings in HDLs that must addressed to improve accuracy in an LLM world.

5.6.1 Verilog

Verilog is the language that LLMs understand the best. For top-performing LLMs like GPT-4, the main challenge lies in handling pipelining. Verilog allows for unrestricted pipelining, which deviates from the traditional Von Neumann architecture and nonhardware program structure. GPT-4 effectively generates combinational logic because a typical program without recursion or memory access can be directly translated to Verilog. Improving pipelining remains an open research question that must be addressed to enhance the performance of LLMs in hardware design tasks.

5.6.2 Chisel

Besides the common pipelining issue, Chisel LLM code generation needs help with matching Chisel generated Verilog to native Verilog. As a part of compilation process, the generated Verilog module's IO appends "io_" to all names. Additional clock and reset signals are created by default, even if unused in the original Chisel code. Listing 1 shows the resulting Verilog from a compiled Chisel implementation of a full adder circuit.

To interface modules, HDLAgent adjusts the IO to perform testing. Postprocessing is used to remove the unused signals as well as renaming those modified to their originals to match the circuit specification. This is necessary as the first step of the LEC checks that the two modules' IOs match, otherwise a truthful comparison is impossible and the LEC fails.

Additionally, both Chisel and PyRTL, being DSLs suffer from LLMs using incorrect syntax.

```
module full_adder(
  input
           clock,
  input
           reset,
  input
           io_a,
  input
           io_b,
  input
           io_cin,
  output
           io_sum,
  output
           io_cout
);
```



5.6.3 PyRTL

PyRTL shares common problems with Verilog and Chisel, but it also has a problem with semantics.

The PyRTL DSL problem is when the LLM generates Python syntax to implement logic instead of the PyRTL syntax. In Listing 2 the "INVALID" case uses Python "inp»1" instead of the PyRTL shift right logical library call. Many such programs generate errors which are caught and recitifed with further HDLAgent iterations.

```
inp = pyrtl.inpput(4, 'inp')
out = pyrtl.Output(4, 'out')
out <<= inp ^ pyrtl.shift_right_logical(</pre>
   inp, 1)
# equivalent: out <<= pyrtl.concat(inp</pre>
    [3] ^ 0, inp[3] ^ inp[2], inp[2]
   inp[1], inp[1] ^ inp[0])
# CORRECT
            : out <<= pyrtl.concat(inp
           , inp[3] ^ inp[2], inp[2] ^
    [3]
   inp[1], inp[1] ^ inp[0])
            : out <<= inp ^ (inp>>1)
# INVALID
                                        #
   Invalid, >> is a python shift not
   PyRTL
```

Listing 2: PyRTL issues generating right shift.

Besides DSL problems, PyRTL has errors due to inconsistent semantics. In Verilog and Chisel, a right shift logical of a positive number reduces the bus size. For example if "inp" has 4 bits, and it is right shifted once, the output has 3 bits. Whereas in PyRTL, it stays 4 bits but the most significant bit is hardwired to zero. Listing 2 showcases the problem in one HDL-Eval test. The most significant bit is xored with zero which is not the expected result, as detailed in the "equivalent" case.

```
5.6.4 DSLX
```

```
fn add_7_to_11() -> Outputs {
    //add values from 7 to 11 (exclusive)
    let base = u16:7;
    let res = for (i, accum): (u16, u16)
        in u16:0..u16:4 {
        accum + base + i
      }(u16:0);
      Outputs { result: res }
}
```

Listing 3: Rust DSLX special loop syntax.

DSLX presented a different set of challenges than DSLs like Chisel and PyRTL. Since it does not support unrestricted pipelining, only combinational logic is considered in this section's feedback.

DSLX shares IO generation issues with Chisel and PyRTL but faces even greater challenges. DSLX generated Verilog modules have a single output named "out". DSLX's solution to multiple outputs is to return a struct. HDLAgent addresses it by postprocessing the generated Verilog and modifying the output port name to match the desired IO. A better solution that requires DSLX semantic changes would be to adopt a Go-like syntax that allows for multiple named outputs and ensures Verilog generation respects those outputs.

Another interesting source of errors stems from DSLX being "similar to Rust". If the HDLAgent's HDL Description mentions that "DSLX is similar to Rust..." it frequently erroneous code. Even without this sentence, the LLM sometimes generates legal Rust but illegal DSLX code. Some differences are easy to spot, such as DSLX's "assert(cond)" versus Rust's "assert_eq!(cond)," while others, like the presence of Rust annotations like "#[test]" in DSLX code, are more subtle. To address the "similar but not the same" syntax issues, it is suggested to avoid mentioning the similarity and catch any discrepancies during compilation time, generating a compile error for HDLAgent to fix.

A more complicated case involves semantic changes. Since DSLX cannot describe circuits with mutable variables, its expressions cannot describe state changes over a loop, making it incompatible with the Rust loop semantics. Instead, these expressions have an accumulator value separate from the iterator, creating a return value calculated by the body of the for loop. As shown in Listing 3, the for loop body sums the values between 7 and 11 by accumulating the base value of 7 and the iterator value in the range of 0 to 4 each loop "iteration." This deviation from standard loop semantics required a dedicated code snippet and explanation in both the initial and supplemental contexts to correct the LLM's often incorrect assumptions about DSLX's generative for loop syntax. Addressing these changes will help LLMs to perform better with less HDLAgent iterations.

6 Future Work and Conclusions

This paper has demonstrated that Large Language Models (LLMs) hold transformative potential for computer science, particularly in the domain of Hardware Description Languages (HDLs). We introduced HDLAgent, an AI Agent designed to significantly enhance the ability of LLMs to generate code for HDLs that are not commonly represented in training datasets, such as Chisel, PyRTL, and DSLX. The development of new HDLs often relies on the capabilities of LLMs, and HDLAgent facilitates this by enabling effective use of existing LLMs without extensive retraining.

Our evaluations show that HDLAgent achieves a success rate of over 90% on concise examples across all HDLs, making it an excellent tool for educational purposes in teaching new HDL languages. However, the performance of HDLAgent and traditional LLM approaches tends to decline with larger or more complex designs. For instance, even advanced LLMs like GPT-4 see a drop in success rates for Verilog projects exceeding 75 lines of code.

This work identifies several challenges and avenues for future research:

- Quality of Results (QoR) issues observed in specific languages like DSLX need addressing to improve the robustness of generated designs.
- Consistently low success rates for pipelined designs suggest a need for specialized techniques or enhancements in LLM architectures.
- To accommodate complex designs, we recommend further development towards making

HDLs and their compilers more conducive to LLM integration.

Moreover, while HDLAgent has shown to elevate performance significantly—raising the Verilog success rate of GPT-4 from 34% to 72%—it also highlights the scalability challenges when tackling more extensive and intricate designs.

In conclusion, HDLAgent not only broadens the applicability of LLMs in the field of HDLs beyond Verilog but also illuminates key challenges when scaling to larger systems. To aid the community and foster further research, we will open-source the HDLAgent code, providing a valuable resource for developers and researchers aiming to enhance the interaction between LLMs and HDL design.

References

- Artificial Analysis. https://artificialanalysis.ai/ models/gpt-35-turbo. Online; accessed on April 2024.
- [2] slang SystemVerilog Language Services. https:// github.com/MikePopoloski/slang. Online; accessed on 5 August 2021.
- [3] HDLBits Verilog Practice. website, November 2017.
- [4] CWhy. website, November 2023.
- [5] Toufique Ahmed and Premkumar Devanbu. Few-shot training llms for project-specific code-summarization. arXiv preprint arXiv:2207.04237, 2022.
- [6] Jonathan Bachrach, Huy Vo, Brian Richards, Yunsup Lee, Andrew Waterman, Rimas Avižienis, John Wawrzynek, and Krste Asanović. Chisel: constructing hardware in a scala embedded language. In DAC Design Automation Conference 2012, pages 1212–1221. IEEE, 2012.
- [7] Xinyun Chen, Maxwell Lin, Nathanael Schärli, and Denny Zhou. Teaching large language models to self-debug, 2023.
- [8] John Clow, Georgios Tzimpragos, Deeksha Dangwal, Sammy Guo, Joseph McMahan, and Timothy Sherwood. A pythonic approach for rapid hardware prototyping and instrumentation. In *Field Programmable Logic and Applications (FPL), 2017 27th International Conference on*, pages 1–7. IEEE, 2017.
- [9] Yihong Dong, Xue Jiang, Zhi Jin, and Ge Li. Selfcollaboration code generation via chatgpt, 2023.
- [10] efabless. Efabless 1st competition winners. https:// efabless.com/genai/challenges/1, 2023.
- [11] efabless. Efabless 2nd competition winners. https:// efabless.com/genai/challenges/2-winners, 2023.
- [12] Zhiyu Fan, Xiang Gao, Abhik Roychoudhury, and Shin Hwei Tan. Improving automatically generated code from codex via automated program repair. arXiv preprint arXiv:2205.10583, 2022.
- [13] Google. XLS Website. https://github.com/google/xls/, 2022.
- [14] Pranab Islam, Anand Kannappan, Douwe Kiela, Rebecca Qian, Nino Scherrer, and Bertie Vidgen. Financebench: A new benchmark for financial question answering, 2023.

- [15] Xue Jiang, Yihong Dong, Lecheng Wang, Zheng Fang, Qiwei Shang, Ge Li, Zhi Jin, and Wenpin Jiao. Self-planning code generation with large language models, 2023.
- [16] Amit Kumar, Deepak Singh, Nalini Gupta, and Meena Bhatia. Towards llm-powered verilog rtl assistant: Selfverification and self-correction, 2024.
- [17] Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. Retrieval-augmented generation for knowledge-intensive nlp tasks, 2021.
- [18] Bill Yuchen Lin, Abhilasha Ravichander, Ximing Lu, Nouha Dziri, Melanie Sclar, Khyathi Chandu, Chandra Bhagavatula, and Yejin Choi. The unlocking spell on base llms: Rethinking alignment via in-context learning, 2023.
- [19] Haokun Liu, Derek Tam, Mohammed Muqeeth, Jay Mohta, Tenghao Huang, Mohit Bansal, and Colin A Raffel. Few-shot parameter-efficient fine-tuning is better and cheaper than in-context learning. Advances in Neural Information Processing Systems, 35:1950–1965, 2022.
- [20] Mingjie Liu, Nathaniel Pinckney, Brucek Khailany, and Haoxing Ren. Verilogeval: Evaluating large language models for verilog code generation. arXiv preprint arXiv:2309.07544, 2023.
- [21] Shang Liu, Wenji Fang, Yao Lu, Qijun Zhang, Hongce Zhang, and Zhiyao Xie. Rtlcoder: Outperforming gpt-3.5 in design rtl generation with our open-source dataset and lightweight solution, 2024.
- [22] Yao Lu, Shang Liu, Qijun Zhang, and Zhiyao Xie. Rtllm: An open-source benchmark for design rtl generation with large language model, 2023.
- [23] Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, Shashank Gupta, Bodhisattwa Prasad Majumder, Katherine Hermann, Sean Welleck, Amir Yazdanbakhsh, and Peter Clark. Self-refine: Iterative refinement with self-feedback, 2023.
- [24] Seungjun Moon, Yongho Song, Hyungjoo Chae, Dongjin Kang, Taeyoon Kwon, Kai Tzu iunn Ong, Seung won Hwang, and Jinyoung Yeo. Coffee: Boost your code llms by fixing bugs with feedback, 2023.
- [25] Ansong Ni, Srini Iyer, Dragomir Radev, Ves Stoyanov, Wen-tau Yih, Sida I Wang, and Xi Victoria Lin. Lever: Learning to verify language-to-code generation with execution. arXiv preprint arXiv:2302.08468, 2023.
- [26] Theo X. Olausson, Jeevana Priya Inala, Chenglong Wang, Jianfeng Gao, and Armando Solar-Lezama. Is self-repair a silver bullet for code generation?, 2023.
- [27] Sinno Jialin Pan and Qiang Yang. A survey on transfer learning. *IEEE Transactions on knowledge and data engineering*, 22(10):1345–1359, 2010.
- [28] Jean Clarice Scholtz. A study of transfer of skill between programming languages. The University of Nebraska-Lincoln, 1989.
- [29] Florian Tambon, Arghavan Moradi Dakhel, Amin Nikanjam, Foutse Khomh, Michel C. Desmarais, and Giuliano Antoniol. Bugs in large language models generated code: An empirical study, 2024.
- [30] Shailja Thakur, Baleegh Ahmad, Zhenxing Fan, Hammond Pearce, Benjamin Tan, Ramesh Karri, Brendan Dolan-Gavitt, and Siddharth Garg. Benchmarking large

language models for automated verilog rtl code generation. In 2023 Design, Automation and Test in Europe Conference and Exhibition (DATE), pages 1–6, 2023.

- [31] Shailja Thakur, Baleegh Ahmad, Hammond Pearce, Benjamin Tan, Brendan Dolan-Gavitt, Ramesh Karri, and Siddharth Garg. Verigen: A large language model for verilog code generation, 2023.
- [32] Shailja Thakur, Jason Blocklove, Hammond Pearce, Benjamin Tan, Siddharth Garg, and Ramesh Karri. Autochip: Automating hdl generation using llm feedback, 2023.
- [33] Yun-Da Tsai, Mingjie Liu, and Haoxing Ren. Rtlfixer: Automatically fixing rtl syntax errors with large language models, 2024.
- [34] Hanbin Wang, Zhenghao Liu, Shuo Wang, Ganqu Cui, Ning Ding, Zhiyuan Liu, and Ge Yu. Intervenor: Prompt the coding ability of large language models with the interactive chain of repairing, 2023.
- [35] Zejun Wang, Jia Li, Ge Li, and Zhi Jin. Chatcoder: Chatbased refine requirement improves llms' code generation, 2023.
- [36] Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc Le, and Denny Zhou. Chain-of-thought prompting elicits reasoning in large language models, 2023.
- [37] Clifford Wolf. Yosys Open SYnthesis Suite. https:// github.com/YosysHQ/yosys, 2022. Online; accessed on December 2022.
- [38] Chunqiu Steven Xia and Lingming Zhang. Conversational automated program repair. arXiv preprint arXiv:2301.13246, 2023.
- [39] Chengrun Yang, Xuezhi Wang, Yifeng Lu, Hanxiao Liu, Quoc V. Le, Denny Zhou, and Xinyun Chen. Large language models as optimizers, 2023.
- [40] Kaiyuan Yang, Haotian Liu, Yuqin Zhao, and Tiantai Deng. A new design approach of hardware implementation through natural language entry. *IET Collaborative Intelligent Manufacturing*, 5(4):e12087, 2023.
- [41] Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. React: Synergizing reasoning and acting in language models, 2023.
- [42] Xufeng Yao, Haoyang Li, Tsz Ho Chan, Wenyi Xiao, Mingxuan Yuan, Yu Huang, Lei Chen, and Bei Yu. Hdldebugger: Streamlining hdl debugging with large language models, 2024.
- [43] Da Yin, Faeze Brahman, Abhilasha Ravichander, Khyathi Chandu, Kai-Wei Chang, Yejin Choi, and Bill Yuchen Lin. Lumos: Learning agents with unified data, modular design, and open-source llms, 2023.
- [44] Mark Zakharov, Farzaneh Rabiei Kashanaki, and Jose Renau. HDLEval Benchmarking LLMs for Multiple HDLs. In 1st IEEE International Workshop on LLM-Aided Design, 2024.
- [45] Kechi Zhang, Zhuo Li, Jia Li, Ge Li, and Zhi Jin. Selfedit: Fault-aware code editor for code generation. In Anna Rogers, Jordan Boyd-Graber, and Naoaki Okazaki, editors, Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 769–787, Toronto, Canada, Jul. 2023. Association for Computational Linguistics.

- [46] Andrew Zhao, Daniel Huang, Quentin Xu, Matthieu Lin, Yong-Jin Liu, and Gao Huang. Expel: Llm agents are experiential learners. arXiv preprint arXiv:2308.10144, 2023.
- [47] Jun Zhao, Min Lee, Ananya Rastogi, Huan Yu, Samuel Chen, and Li Xiang. Verilogcoder: Autonomous verilog coding agents with graph-based planning and abstract syntax tree (ast)-based waveform tracing tool, 2024.
- [48] Li Zhong and Zilong Wang. Can chatgpt replace stackoverflow? a study on robustness and reliability of large language model code generation, 2024.
- [49] Wangchunshu Zhou, Yuchen Eleanor Jiang, Long Li, Jialong Wu, Tiannan Wang, Shi Qiu, Jintian Zhang, Jing Chen, Ruipu Wu, Shuai Wang, Shiding Zhu, Jiyu Chen, Wentao Zhang, Ningyu Zhang, Huajun Chen, Peng Cui, and Mrinmaya Sachan. Agents: An open-source framework for autonomous language agents, 2023.