Make Shuffling Great Again: A Side-Channel Resistant Fisher-Yates Algorithm for Protecting Neural Networks

Leonard Puškáč, Marek Benovič, Jakub Breier, and Xiaolu Hou

Abstract-Neural network models implemented in embedded devices have been shown to be susceptible to side-channel attacks (SCAs), allowing recovery of proprietary model parameters, such as weights and biases. There are already available countermeasure methods currently used for protecting cryptographic implementations that can be tailored to protect embedded neural network models. Shuffling, a hiding-based countermeasure that randomly shuffles the order of computations, was shown to be vulnerable to SCA when the Fisher-Yates algorithm is used.

In this paper, we propose a design of an SCA-secure version of the Fisher-Yates algorithm. By integrating the masking technique for modular reduction and Blakely's method for modular multiplication, we effectively remove the vulnerability in the division operation that led to side-channel leakage in the original version of the algorithm. We experimentally evaluate that the countermeasure is effective against SCA by implementing a correlation power analysis attack on an embedded neural network model implemented on ARM Cortex-M4. Compared to the original proposal, the memory overhead is $2\times$ the biggest layer of the network, while the time overhead varies from 4% to 0.49% for a layer with 100 and 1000 neurons, respectively.

Index Terms-Neural networks, side-channel attacks, countermeasures, shuffling, hiding, Fisher-Yates.

I. INTRODUCTION

N EURAL network (NN) implementations have become in-creasingly deployed in embedded 1 various applications from autonomous vehicles to smart IoT devices. While these deployments offer great computational efficiency and real-time performance, they also introduce vulnerability to hardware-based attacks such as side-channel attacks (SCAs) [1]. SCAs exploit physical emanations, such as power consumption, electromagnetic leaks, or timing variations to extract the sensitive values used during the computation [2]. Such physical emanations, commonly referred to as leakages, can lead to the compromise of intellectual property by revealing model parameters – weights and biases [3].

As the area of hardware security has been researched for decades in the field of cryptography, it is natural to assess which protection techniques can be adapted for NN implementations. Masking, while providing strong security guarantees, incurs significant overhead when applied to the whole network [4]. The number of parameters in NNs, ranging to millions, naturally calls for lightweight countermeasures that do not significantly increase the required memory or execution time. This is especially true for embedded applications running on resource-constrained computing units.

Hiding-based countermeasures, such as shuffling, on the other hand, can greatly increase the attacker's effort while keeping the overhead manageable even in embedded systems [2]. There have been several proposals to use shuffling for neural network implementations. Nozaki and Yoshikawa [5], and Brosch et al. [6] proposed a software-based shuffling of multiplications within a neuron to make the parameter recovery infeasible. The random shuffle algorithm that is commonly used in such cases is the Fisher-Yates algorithm [7] as it provides optimal $\mathcal{O}(n)$ time complexity and produces an unbiased permutation. However, it was shown by Ganesan et al. [8] that this shuffling method can be easily broken by an SCA targeting the division operation. They provided a way to reorder the parts of SCA traces back to the original order, thus allowing the parameter recovery. To counteract this attack, they proposed to realize the shuffling in hardware, avoiding the usage of the Fisher-Yates algorithm. While their method is secure and efficient, it requires an additional hardware implementation which is not an option for general-purpose microcontrollers. In this paper, we aim to overcome this limitation by developing a side-channel secure way to realize shuffling in software.

Our contribution. In this paper, we investigate the possibility of using a shuffling-based countermeasure in software to shuffle the multiplications within a NN layer. As the original shuffling proposals in [5] and [6] leak the shuffling order via side-channels due to the usage of the Fisher-Yates algorithm [8], we alter the algorithm in a way that the attack shown in [8] is not possible anymore. Figure 1 shows a high-level depiction of the proposed protection. The timing overhead over the original method ranges from 4% for a single layer with 100 neurons and further reduces to 0.49% for a layer with 1000 neurons. As the masking itself requires additional storage, the memory overhead comprises two secret arrays of the size of the biggest layer in the network.

To show that the proposed method does not influence the security level of the original Fisher-Yates shuffle, we experimentally evaluate this countermeasure proposal on a small network. This shows the best-case scenario for the attacker as the number of ways to shuffle such a network is limited. Our results, performed on an ARM Cortex-M4 processor measured with a ChipWhisperer Lite evaluation platform, show that the proposed shuffling method effectively thwarts the attacker's effort to recover model parameters.

Organization. The rest of this paper is organized as follows. Section II provides the necessary background and overviews the related work. Section III presents the main idea of our shuffling-based countermeasure proposal. Section IV shows

L. Puškáč, Marek Benovič and X. Hou are with Slovak University of Technology, Bratislava, Slovakia, e-mail: xpuskac@stuba.sk, marek.benovic@stuba.sk, houxiaolu.email@gmail.com

J. Breier is with TTControl GmbH, Vienna, Austria, e-mail: jbreier@jbreier.com



Fig. 1: A flow chart depiction of the proposed protected version of the Fisher-Yates algorithm.

the experimental evaluation results. Section V provides a discussion, and finally, Section VI concludes this paper and provides directions for future work.

II. BACKGROUND

In this section, we will first give an overview of side-channel attacks and countermeasures. Later, we will detail the current state-of-the-art in the protection of NNs against side-channel attacks.

A. Side-Channel Attacks

SCAs are a class of cybersecurity threats that exploit indirect information leakage from a device rather than targeting its primary algorithmic or protocol vulnerabilities. These attacks utilize physical or behavioral characteristics generated during the sensitive computation, such as execution timing, power consumption, electromagnetic emanation, or cache activation to recover secret data. Originally, SCAs have been proposed for the recovery of cryptographic keys [1]. However, they can be used for recovering any kind of secret data used in the computation, such as parameters of machine learning models that are an intellectual property [3]. Generally, there are two types of SCA analysis methods: profiled and non-profiled. In the profiled setting, the attacker is assumed to possess an identical copy of the device under test (DUT), being able to build the model of the device with preliminary measurements. After this model is created, the attacker can then launch the actual attack on the DUT requiring only a few executions of the sensitive computation in the ideal case. In the non-profiled setting, the attacker only has the DUT in their possession, and therefore, launches the attack directly without creating the device model.

One of the main non-profiled side-channel analysis methods is correlation power analysis (CPA) [9]. In CPA, the attacker first creates a set of hypotheses on a small part of the secret data – this can be, for example, a byte. Then, the attacker measures the power consumption traces capturing the part of the execution utilizing that portion of the secret data while varying the non-secret input. Finally, a statistical correlation is calculated between the hypothetical power consumption (based on the hypotheses of the secret data) and the measured power traces. If the experimental setting is correct, for the correct hypothesis, the absolute correlation is significantly higher than for incorrect ones. Apart from being able to recover secret keys of unprotected block cipher implementations, this type of attack has been shown capable of recovering model parameters of neural networks [10]. In this paper, we utilize CPA to first show how the attack works on unprotected NN implementation and then to show the effectiveness of the proposed countermeasure.

B. Side-Channel Countermeasures

There are two broad categories of side-channel countermeasures: *masking* and *hiding* [2].

The goal of masking is to randomize the intermediate values processed by the DUT to make the leakage independent of these values. For this purpose, we generate a random value, called *mask*, by which the secret intermediate value is concealed using a binary operation. Masking has been shown to be provably secure under certain conditions [11].

The goal of hiding is to either balance or randomize the leakages coming from the DUT to remove the data or operation dependency. This can be done by various techniques implemented either in software or hardware. For example, a so-called dual-rail precharge logic utilizes wires carrying complementary values to balance the leakage in hardware. In software, dummy operations and balanced data encoding [12] are some of the approaches. Generally, hiding-based methods can be overcome with a high number of measurements, however, they can make the attack much harder to execute. They are also often combined with masking-based countermeasures that suffer from the threat of higher-order CPA attacks [13].

C. Related Work

1) SCAs on Neural Networks: The seminal work by Batina et al. [3] showed how to recover the type of activation function, number of layers and neurons, and weights. The type of activation function was recovered by a timing attack, the number of layers/neurons by visual inspection of the traces, and the weights by CPA. The networks were implemented on 8-bit ATmega328P and 32-bit ARM Cortex-M3 microcontrollers.

This was followed by a myriad of works focusing on the practical recovery of various network information implemented on different devices. To mention a few, [14] showed the practical attack on ZYNQ XC7000 SoC on Pynq-Z1 board, [15] on Intel i7-7700 processor, [16] on Nvidia Jetson Nano, and [17] on Google Edge TPU. An embedded OpenVINO framework for implementing models on generic Edge devices was analyzed in [18]. These research efforts show that SCAs on neural network implementations are indeed a practical attack scenario and it is of interest to explore various ways to protect these models. 2) Countermeasures against SCAs on Neural Networks: Masking has been applied to NNs previously in [19]. They proposed a novel design of components such as masked adder trees and masked ReLUs. Apart from the need for a pseudorandom number generator to provide the randomness, the design requires twice the latency and needs $2.7 \times$ more lookup tables, $1.7 \times$ more flip-flops, and $1.3 \times$ more BRAM. The work was later extended in [20] to the entire neural network, resulting in $3.5 \times$ latency overhead and $5.9 \times$ area overhead. They further improved their masked design in [4] by utilizing modular arithmetic in neural networks, allowing more efficient application of masking. However, it was later shown that such an implementation can be broken by a heat-induced power leakage [21].

Hiding has been utilized in the form of shuffling [5] and desynchronization [22]. In [5] the authors shuffle the order of multiplications within a neuron to drastically lower the success rate of a successful attack. In [6], the authors shuffle both the neurons within a network and the multiplications within a neuron. They realize an electromagnetic SCA on an ARM Cortex-M4 microcontroller and provide theoretical estimations on the number of measurements required for a successful attack. For example, even a small network with three layers of 15, 10, 10 neurons per layer would require ≈ 47 million SCA measurements, making the attack impractical.

However, both of the shuffling approaches utilize software shuffling based on the Fisher-Yates algorithm In [8] it was shown that the division operation of this algorithm leaks sidechannel information that can be used to reorder the shuffled parts of the traces back to their original order. Instead, they propose a hardware-based shuffling that avoids the use of that algorithm. Naturally, a hardware solution is efficient and provides a good security level. However, it requires an additional circuit to perform the shuffle, thus such protection needs to be added during the design phase of the chip and is not applicable to general-purpose hardware. In this paper, we aim to overcome this limitation by improving the Fisher-Yates algorithm to make it secure against SCA.

III. COUNTERMEASURE PROPOSAL

We propose utilizing a protected version of the Fisher-Yates shuffling algorithm to randomize multiplication operations as a countermeasure against CPA attacks. The standard Fisher-Yates algorithm, widely known for its efficiency in shuffling, is detailed in Algorithm 1.

This algorithm was previously used for shuffling multiplications in neural networks to defend against CPA attacks, as demonstrated in [5], [6]. However, the algorithm's security was compromised in [8]. In this paper, the authors demonstrated that when a division operation is performed, the values of the dividend and divisor can be deduced by analyzing power variations. Since division is employed during the computation of modular reduction in line 3 of the algorithm, the value of j can be recovered. Consequently, each swapping operation in line 4 can be reversed, allowing the attacker to reorder segments of traces corresponding to individual multiplication operations and align them correctly.

To mitigate these vulnerabilities, we propose a protected Fisher-Yates algorithm that integrates masking techniques for modular reduction and Blakely's method for modular multiplication [23]. The masking conceals the value of j, while Blakely's method eliminates the need for division in modular reduction, thereby enhancing the algorithm's resistance to the attack presented in [8].

Next, we provide a detailed explanation of Blakely's modular multiplication method in Subsection III-A, followed by an analysis of how it can be combined with a multiplicative masking technique to compute j in line 3, as discussed in Subsection III-B. Finally, we present the design of our proposed countermeasure tailored for neural network computations in Subsection III-D.

A. Blakely's method for modular multiplication

Let $n \ge 2$ be an integer. Consider two integers a, b such that $0 \le a, b < n$. The binary representation of a can be expressed as

$$a = a_{\ell_a - 1} a_{\ell_a - 2} \cdots a_1 a_0,$$

where ℓ_a is the bit length of a. The product ab can then be computed as follows

$$ab = \left(\sum_{i=0}^{\ell_a - 1} a_i 2^i\right) b = \sum_{i=0}^{\ell_a - 1} 2^i a_i b.$$
(1)

Blakely's method for computing the modular multiplication $ab \mod n$ leverages this representation. The step-by-step details are provided in Algorithm 2.

In the Algorithm, line 4 computes the product ab as described in Equation (1). Subsequently, lines 5 – 8 calculate $R \mod n$. Specifically, when $i = \ell_a - 1$, in line 3, we have

$$R = a_i b < n - 1$$

In the following iterations of the loop at line 3, the value of R becomes

$$R = 2R + a_i b \le 2(n-1) + (n-1) = 3n - 3i$$

Thus, by comparing R with n twice, $R \mod n$ can be efficiently computed. This approach avoids performing division operations and is therefore resistant to the attack described in [8].

Algorithm 2: Blakely, Blakely's method for computing modular multiplication.

Input: $n, a, b// n \in \mathbb{Z}, n \ge 2; 0 \le a, b < n$ **Output:** $ab \mod n$ 1 ℓ_a = bit length of a**2** R = 03 for $i = \ell_a - 1$, $i \ge 0$, i - - do $R=2R+a_ib//$ compute ab4 if $R \ge n$ then 5 R = R - n6 if R > n then 7 R = R - n8 9 return R

B. Masked Shuffling

To make the shuffling algorithm secure, we introduce masking for the modular reduction operation in line 3 of Algorithm 1 utilizing two secret arrays. The arrays, S_1 and S_2 , are generated such that S_1 contains random positive integers $S_1[k]$ coprime with k + 3, while $S_2[k]$ represents the corresponding multiplicative inverse of $S_1[k]$ modulo k + 3. More specifically, for k = 0, 1, ..., N - 3, the arrays satisfy the following properties:

$$gcd(S_1[k], k+3) = 1, \quad S_1[k] > 0,$$
 (2)

and

$$S_2[k] = S_1[k]^{-1} \mod (k+3), \tag{3}$$

where N denotes the total number of elements to be shuffled. In particular, the following condition holds:

$$1 \leq S_2[k] \leq k+2, \quad k=0,1,\ldots,N-3$$

The details of our protected Fisher-Yates shuffling algorithm are outlined in Algorithm 3. In this algorithm, r from line 2 and r' from line 3 are both random nonnegative integers. Line 4 computes

$$t = (rS_1[i-2] + r'(i+1)) \mod (i+1) = rS_1[i-2] \mod (i+1),$$

where by design, $S_1[i-2]$ is a random integer coprime with i+1 (see Equation (2)). From Equation (3), $S_2[i-2]$ is the multiplicative inverse of $S_1[i-2]$ modulo (i+1), we have

$$S_1[i-2]S_2[i-2] \mod (i+1) = 1.$$

Thus, using Blakely's method, line 5 computes

$$j = tS_2[i-2] \mod (i+1)$$

= $rS_1[i-2]S_2[i-2] \mod (i+1) = r \mod (i+1)$

We have shown that lines 4 and 5 in Algorithm 3 implement

$$j = r \mod (i+1).$$

Consequently, lines 2 to 6 in Algorithm 3 correspond to lines 2 to 4 in Algorithm 1 for i = N - 1, N - 2, ..., 2. It is easy to see that lines 7 to 9 in Algorithm 3 implement lines 2 to 4 from Algorithm 1 for the case i = 1.

C. Security of the implementation against the attack in [8]

We have established that Blakely's method for computing modular multiplication is secure against the attack presented in [8], as it does not involve any division in its computation. In the context of Algorithm 3, the only potentially vulnerable line is line 4. According to the attack described by the authors, the attacker can recover the values of t and

$$rS_1[i-2] + r'(i+1).$$

However, knowing the value of t does not help the attacker in recovering the value of j, since j is computed by multiplying t with a random number modulo i + 1. Furthermore, as $S_1[i-2]$ is a secret value and both r and r' are random numbers, knowledge of $rS_1[i-2] + r'(i+1)$ also provides no useful information to the attacker.

The shuffling algorithm is executed prior to each inference computation. Consequently, each time, the attacker can recover few other values $r'S_1[i-2]+r'_1(i+1)$. In general, the attacker could obtain a series of values:

$$\lambda_1 S_1[i-2] + \beta_1, \ \lambda_2 S_1[i-2] + \beta_2, \ \dots$$

where the λ s and β s are random numbers. It is worth noting that without the β s, the attacker might be able to deduce $S_1[i-2]$ by computing the greatest common divisor (GCD) of the values

$$\lambda_1 S_1[i-2], \ \lambda_2 S_1[i-2], \ \dots$$

However, with the β s being added to each value, the recovered values no longer provide any meaningful information about $S_1[i-2]$. Consequently, no information about $S_2[i-2]$ is revealed, which is essential for determining the value of j.

Algorithm 3: Protected Fisher-Yates algorithm for shuffling.

Input: array, N,S_1,S_2 // array contains	
	elements to be shuffled and N is the number
	of elements in array; S_1 and S_2 are given by
	Equations (2) and (3) respectively
	Output: Shuffled array
1 for $i = N - 1, N - 2, \dots, 2$ do	
2	$r=\mathrm{rand}()$ // rand() generates a random
	nonnegative integer
3	$r' = \operatorname{rand}()$
4	$t = (rS_1[i-2] + r'(i+1)) \mod (i+1)$
5	$j = {\tt Blakely}(i+1,t,S_2[i-2])$ // Compute
	$tS_2[i-2] \mod (i+1)$ using Blakely's method
	in Algorithm 2
6	swap $array[i]$ and $array[j]$
7	$r = \operatorname{rand}()$
8	$j = r \mod 2$
9	swap $array[1]$ and $array[j]$
10	return array
_	

D. Shuffling multiplication

Before each inference computation, we generate a shuffled array for each layer of the network as follows. Let N represent the number of input neurons in the layer, and define:

$$array = \{1, 2, \dots, N\}$$

where each element corresponds to a specific input neuron. The array is shuffled using Algorithm 3, and the resulting shuffled sequence of indices is used to reorder the multiplication operations in the layer's computation during inference. Specifically, for each output neuron in the layer, the multiplications are shuffled independently using the same shuffled array.

It is worth noting that it is unnecessary to create separate secret arrays S_1 and S_2 for each layer. Instead, S_1 and S_2 can be computed based on the maximum number of neurons in any layer of the network. The shuffling for other layers can then utilize the relevant entries from S_1 and S_2 to perform the protected shuffling.

To evaluate the security of the implementation against the attack proposed in [8], one might argue that brute-forcing the values in S_2 is feasible, given that $S_2[k]$ is known to be between 1 and k+2. More specifically, since $S_2[k]$ is coprime with k + 3, the total number of possible values for $S_2[k]$ is $\varphi(k+3)$, where φ denotes Euler's totient function. For an integer $n \geq 2$,

$$\varphi(n) = |\{a \mid a \in \mathbb{Z}, \ 1 \le a \le n-1, \ \gcd(a,n) = 1\}|.$$

Consequently, the total number of possible values in S_2 is given by:

$$\prod_{k=0}^{N-3}\varphi(k+3)=\prod_{k=3}^N\varphi(k)$$

For example, when N = 20, the number of possible values in S_2 is approximately

$$\prod_{k=3}^{20} \varphi(k) \approx 2^{45}.$$

To execute a brute-force attack, the attacker must recover all the weight values to test whether the output for a given input matches (or approximates) a known correct output of the network. This involves re-shuffling the multiplications for each neuron in the hidden layer for every trace. The attacker would then use the recovered weights to deduce the next layer's weights iteratively, continuing this process until the output layer's weights are fully recovered. Assuming each attack requires at least 1 second, the time needed to bruteforce all the possible values in S_2 for a network with at most 20 neurons in each layer would be approximately:

$$2^{45}$$
 seconds $\approx 2^{20}$ years.

This duration is clearly impractical, particularly considering the rapid advancements in AI. It is reasonable to anticipate that within a few years (or months), the secret AI model attacker is trying to recover will likely be replaced by a more advanced and efficient one, rendering such an attack even less relevant.

Algorithm 4: Compute absolute correlations for each possible exponent value.

```
Input: r, W, M_w, q// r is the array of absolute
      correlations obtained in Step (5); W is the
      set of all possible weight values from
     Step (3); M_w is the total number of weights
      in W; q is the number of time samples in
      the target range identified in Step (2)
  Output: Absolute value of correlation coefficients for
           each exponent value
1 array of size 256 \times q r_e
2 Initialized all entries of r_e to 0
3 for j = 0, 1, \dots, M_w - 1 do
      Let b_{31}^j b_{30}^j \cdots b_0^j be the binary representation of w_j
      exponent = b_{30}^j 2^8 + b_{29}^j 2^7 + \dots + b_{23}^j
```

for $t = 0, 1, \dots, q - 1$ do

if
$$r_e[exponent] < r[j,t]$$
 then

 $r_e[exponent] = r[j,t]$

```
9 return r_e
```

4

5

6

7

8

IV. EXPERIMENTAL EVALUATION

As in [3], we adopt an approach to recover the different components of a secret weight individually. We begin by recalling the 32-bit (single-precision) floating-point representation as defined by the IEEE 754 standard. Specifically, the binary string $b_{31}b_{30}\cdots b_0$ represents the floating-point number:

$$(-1)^{b_{31}} \times 2^{b_{30}b_{29}\cdots b_{23}-127} \times 1.b_{22}b_{21}\dots b_0,$$

where $b_{30}b_{29}\cdots b_{23}$ denotes the integer

$$b_{30}2^8 + b_{29}2^7 + \dots + b_{23}$$

and $1.b_{22}b_{21}\cdots b_0$ represents the value

$$1 + \frac{b_{22}}{2} + \frac{b_{21}}{2^2} \dots + \frac{b_0}{2^{23}}.$$

In this representation, b_{31} is referred to as the sign bit, $b_{30}b_{29}\cdots b_{23}$ as the *exponent*, and $b_{22}b_{21}\cdots b_0$ as the *mantissa*. Additionally, we refer to $b_{22}b_{21}\cdots b_{16}, b_{15}b_{14}\cdots b_7$, and $b_6 b_5 \cdots b_0$ as the first byte, second byte, last seven bits of the mantissa.

Although similar approaches have been used in various works for recovering secret weight values during neural network computations, the specific CPA attack steps and successful recovery of the sign bit and exponent bits have not been comprehensively detailed in the literature.

To ensure the completeness of our evaluation, in Subsection IV-A, we will outline the CPA attack methodology for recovering the different components of a secret weight value, ultimately reconstructing the entire weight. Subsequently, in Subsection IV-B, we will demonstrate how the different components of a secret weight value can be successfully recovered in an unprotected implementation, as well as how our proposed countermeasure effectively mitigates such an attack.

A. CPA Attack Steps

Below, we detail the steps to recover the first secret weight value of the first neuron in the first hidden layer. Other weight values can be recovered in a similar manner.

- (1) Collect attack traces. To target the first secret weight value, traces are collected with all inputs fixed except for the first neuron in the input layer. Let $\mathcal{T} = \{l_0, l_1, \ldots, l_{M_L-1}\}$ represent the set of M_L attack traces. For each trace l_i , a_i $(i = 0, 1, \ldots, M_L 1)$ denotes the corresponding random input to the first neuron.
- 2 Identify target range of time samples. As demonstrated before, visual inspection of traces can reveal the time samples corresponding to the first multiplication computation for unprotected implementations [3]. In the case of shuffled implementations, the precise location of the multiplication is unknown, so the entire multiplication computation segment for the first hidden neuron is considered as the target duration. Let q_s and q_e denote the start and end time samples of the identified range, with $q := q_e q_s + 1$ representing the total number of time samples in this range.
- (3) Compute hypothetical weights. Given the vast number of possible weight values, it is impractical to consider every single value. To overcome this issue, we first determine the desired precision, defined by the number of decimal places to be recovered. A reasonable range for the weight values can also be assumed, same as in [3]. Let $W = \{w_0, w_1, \ldots, w_{M_w-1}\}$ represent the set of all possible weight values.
- (4) Compute hypothetical leakages. For each weight value w_j , the hypothetical leakage for input a_i is computed as the Hamming weight (HW) of the product w_ja_i the number of 1s in the binary representation of the 32-bit floating-point number w_ja_i , as defined by the IEEE 754 standard. Specifically, construct the matrix \mathcal{H} of size $M_w \times M_L$ such that

$$\mathcal{H}[j,i] = \mathrm{HW}(w_j a_i),$$

for $j = 0, 1, \dots, M_w - 1$ and $i = 0, 1, \dots, M_L - 1$.

(5) Compute correlations. For each weight value w_j and each time sample t in the target range, calculate the absolute value of the correlation coefficient between the hypothetical and real leakages. Let \mathcal{L} denote the array of real leakages in the target range:

$$\mathcal{L}[t,i] = l_i[t+q_s],$$

for $i = 0, 1, ..., M_L - 1$ and t = 0, 1, ..., q - 1. Compute the $M_w \times q$ matrix r such that

$$r[j,t] = \left| \frac{\sum_{i=0}^{M_L-1} (\mathcal{H}[j,i] - \overline{\mathcal{H}[j]}) (\mathcal{L}[t,i] - \overline{\mathcal{L}[t]})}{\sqrt{\operatorname{Var}(\mathcal{H}[j]) \operatorname{Var}(\mathcal{L}[t])}} \right|,$$

where $\mathcal{H}[j]$ (resp. $\mathcal{L}[t]$) and $Var(\mathcal{H}[j])$ (resp. $Var(\mathcal{L}[t])$) represent the mean and variance of the values in the *j*th (resp. *t*th) row of \mathcal{H} (resp. \mathcal{L})

6 **Recovery of weight value.** As previously mentioned, the recovery process involves extracting different parts of the weight separately. For example, the algorithm for



Fig. 2: Power traces corresponding to the computation of the first hidden layer in (a) unprotected and (b) protected implementations. The durations of each neuron computations are clearly distinguishable in both cases as indicated by red dotted lines.

recovering the exponent bits of the weight is detailed in Algorithm 4. For each time sample (line 6), we record the highest absolute value of the correlation coefficient for each exponent value (lines 7 and 8) in the array r_e . To determine the exponent bits, we plot the absolute correlations corresponding to each exponent value against all q time samples. The exponent value achieving the highest peaks is identified as the correct one. Similarly, the sign bit, the first byte, second byte, and the last seven bits of the mantissa can be recovered using the same approach.

B. Results

To demonstrate our approach, we evaluate it using a small multilayer perceptron (MLP) comprising four layers with 7, 5, 4, 3 neurons, respectively. The hidden layers utilize ReLU activation functions, while the output layer employs a sigmoid activation function. The weight values are randomly generated within the range [-2, 2] with a precision of up to two decimal places.

The power traces for the first hidden layer computations are illustrated in Figure 2 for both the unprotected network and the network with shuffled multiplications. As shown, the computations for the five neurons are clearly distinguishable in both cases, marked by the red dotted lines.

These observations indicate that recovering the network architecture (e.g., the number of neurons per layer) through visual inspection of the power traces remains feasible in both scenarios. This is expected as our countermeasure is



(b) Protected network.

Fig. 3: Power traces for the first neuron computation in the first hidden layer for (a) unprotected and (b) protected implementations. In both cases, the durations of multiplication operations are distinguishable (red dotted lines). However, in the unprotected network, the first multiplication (time samples 490–1010) corresponds to the first input neuron, while in the protected case, this correspondence is obscured.

not designed to conceal the network architecture but rather to protect the secret weight parameters from being extracted using CPA.

To recover the first secret weight, we zoom into the computation of the first neuron. The resulting plots are depicted in Figure 3. For both unprotected and protected networks, the seven multiplications are distinguishable, as marked by the red dotted lines. However, in the unprotected network, the first multiplication (occurring between time samples 490 and 1010) corresponds to the first input neuron, whereas in the protected case, the correspondence between multiplications and input neurons are unknown.

To perform CPA attacks, we follow the steps outlined in Subsection IV-A. For trace collection in Step (1), the first neuron inputs are randomly generated within [-2, 2], while all other input values are set to 0.5. We collect $M_L = 2000$ traces for the unprotected implementation and $M_L = 10,000$ for the protected implementation.

For Step (2), the target time sample range is identified as follows: for the unprotected implementation, as observed in Figure 3(a), the first multiplication occurs between time samples $q_s = 490$ and $q_e = 1010$. For the protected implementation, the start time sample remains $q_s = 490$, but due to shuffling, the range extends to $q_e = 4300$ (see Figure 3(b)), which corresponds to the end of the seventh multiplication.

The weight values are randomly generated within [-2, 2]

with a precision of 0.01, resulting in the set:

$$W = \{-2, -1.99, -1.98, \dots, -0.01, 0, 0.01, \dots, 1.99, 2\}.$$

Following the notation from Step (3), the number of hypothetical weight values is $M_w = 401$.

The weight value we used for the first input neuron is 1.43, corresponding to a sign bit of 0, an exponent value of 127, and mantissa bytes as follows: the first byte is 110, the second byte is 20, and the last seven bits represent the value 61.

The CPA attack results for the unprotected and protected implementations are presented in Figures 4 and 5 respectively, where the absolute correlations for the correct values are highlighted in red, while those for incorrect values are shown in gray. For the first byte of the mantissa, only the maximum absolute correlation among incorrect values for each time sample is plotted due to the large number of possible values.

For the attacks on the unprotected implementation, Figure 4 clearly demonstrates that the correct weight value can be successfully recovered.

For attacks on the protected implementation, Figure 5(a) shows that the sign bit of the weight can still be recovered. We believe the reason lies in the composition of the network's weights and inputs. Among the seven weights used, four are positive. Additionally, the inputs to other neurons were set to 0.5, increasing the likelihood of intermediate values being positive. Consequently, the sign bit value of 0 exhibits higher absolute correlations. We would like to note that recovering the sign bit itself does not significantly reduce the search complexity of the entire floating point value. For other components of the weight value, the peaks corresponding to the correct values are significantly lower compared to those of incorrect values.

Moreover, in all cases, the absolute correlations for the protected implementation remain far from 1, in contrast to the results for the unprotected implementation. These findings demonstrate that the CPA attack is ineffective in recovering the target weight value in the presence of our proposed countermeasure.

V. DISCUSSION

A. Overheads

Compared to the original Fisher-Yates shuffling method, the masked shuffling introduces an overhead of $3.38 \times$ for N = 1000 (i.e., with 1000 input neurons) and $2.48 \times$ for N = 100.

For a single layer's shuffled computation, incorporating our proposed shuffling operation (Algorithm 3) introduces an overhead of 4% compared to the standard shuffled computation using the original Fisher-Yates algorithm (Algorithm 1) when the layer has 100 input neurons and 100 output neurons, with ReLU as the activation function. When the number of input and output neurons increases to 1000, the overhead decreases to 0.49%. A plot illustrating the overhead as a function of the number of neurons (assuming an equal number of input and output neurons) is provided in Figure 6.

The memory overhead compared to Fisher-Yates shufflingbased countermeasures arises from storing the two secret arrays, S_1 and S_2 . As previously noted, the size of S_1 and



Fig. 4: CPA attack results for the unprotected implementation. The y-axis represents the absolute correlation. The red lines correspond to the correct values associated with the correct weight of 1.43, while the gray lines correspond to incorrect values.



Fig. 5: CPA attack results for the protected implementation. The *y*-axis represents the absolute correlation. The red lines correspond to the correct values associated with the correct weight of 1.43, while the gray lines correspond to incorrect values.

 S_2 is determined by the maximum number of neurons in any layer of the network. Specifically, their size is equal to this maximum number minus two.

VI. CONCLUSION

It was shown before that the shuffling-based countermeasure is effective in significantly increasing the attacker's effort required to reverse-engineer the model parameters utilizing a side-channel attack [5], [6]. However, software-based shuffling using the Fisher-Yates algorithm leaks side-channel information through its division operation, making it possible for the attacker to recover the model parameters [8]. In this paper, we showed how to make the algorithm resistant to that type of attack. Our experimental results indicate that the adjusted algorithm provides the expected level of resistance while adding a small overhead that is negligible when considering the entire model computation.

For the future work, it would be interesting to evaluate a combination of different hiding-based countermeasures, such as shuffling and desynchronization, or a combination of hiding and masking.

REFERENCES

- P. Kocher, "Differential power analysis," in *Proc. Advances in Cryptology (CRYPTO'99)*, 1999.
- [2] X. Hou and J. Breier, Cryptography and Embedded Systems Security. Springer, 2024.



Fig. 6: Computation overhead of the proposed protected single-layer computation compared to standard shuffled single-layer computation. The x-axis represents the number of input and output neurons, which are assumed to be equal.

- [3] L. Batina, S. Bhasin, D. Jap, and S. Picek, "{CSI}{NN}: Reverse engineering of neural network architectures through electromagnetic side channel," in 28th USENIX Security Symposium (USENIX Security 19), 2019, pp. 515–532.
- [4] A. Dubey, A. Ahmad, M. A. Pasha, R. Cammarota, and A. Aysu, "Modulonet: Neural networks meet modular arithmetic for efficient hardware masking," *IACR Transactions on Cryptographic Hardware and Embedded Systems*, pp. 506–556, 2022.
- [5] Y. Nozaki and M. Yoshikawa, "Shuffling countermeasure against power side-channel attack for mlp with software implementation," in 2021 IEEE 4th International Conference on Electronics and Communication Engineering (ICECE). IEEE, 2021, pp. 39–42.
- [6] M. Brosch, M. Probst, and G. Sigl, "Counteract side-channel analysis of neural networks by shuffling," in 2022 Design, Automation & Test in Europe Conference & Exhibition (DATE). IEEE, 2022, pp. 1305–1310.
- [7] R. A. Fisher, F. Yates et al., Statistical tables for biological, agricultural and medical research, edited by ra fisher and f. yates. Edinburgh: Oliver and Boyd, 1963.
- [8] K. Ganesan, M. Fishkin, O. Lin, and N. E. Jerger, "Blackjack: Secure machine learning on iot devices through hardware-based shuffling," arXiv preprint arXiv:2310.17804, 2023.
- [9] E. Brier, C. Clavier, and F. Olivier, "Correlation power analysis with a leakage model," in *Cryptographic Hardware and Embedded Systems-CHES 2004: 6th International Workshop Cambridge, MA, USA, August* 11-13, 2004. Proceedings 6. Springer, 2004, pp. 16–29.
- [10] L. Batina, S. Bhasin, J. Breier, X. Hou, and D. Jap, "On implementationlevel security of edge-based machine learning models," in *Security and Artificial Intelligence: A Crossdisciplinary Approach*. Springer, 2022, pp. 335–359.
- [11] E. Prouff and M. Rivain, "Masking against side-channel attacks: A formal security proof," in Annual International Conference on the Theory and Applications of Cryptographic Techniques. Springer, 2013, pp. 142–159.
- [12] X. Hou, J. Breier, and M. Kovačević, "Another look at side-channelresistant encoding schemes," *IEEE Transactions on Very Large Scale Integration (VLSI) Systems*, 2024.
- [13] F.-X. Standaert, E. Peeters, and J.-J. Quisquater, "On the masking countermeasure and higher-order power analysis attacks," in *International Conference on Information Technology: Coding and Computing* (*ITCC'05*)-Volume II, vol. 1. IEEE, 2005, pp. 562–567.
- [14] M. Yan, C. W. Fletcher, and J. Torrellas, "Cache telepathy: Leveraging shared resource attacks to learn {DNN} architectures," in 29th USENIX Security Symposium (USENIX Security 20), 2020, pp. 2003–2020.
- [15] C. Gongye, Y. Fei, and T. Wahl, "Reverse-engineering deep neural networks using floating-point timing side-channels," in 2020 57th ACM/IEEE Design Automation Conference (DAC). IEEE, 2020, pp. 1–6.
- [16] Ł. Chmielewski and L. Weissbart, "On reverse engineering neural network implementation on gpu," in *Applied Cryptography and Network Security Workshops: ACNS 2021 Satellite Workshops, AIBlock, AIHWS, AIOTS, CIMSS, Cloud S&P, SCI, SecMT, and SiMLA, Kamakura, Japan, June 21–24, 2021, Proceedings.* Springer, 2021, pp. 96–113.
- [17] A. Kurian, A. Dubey, F. Yaman, and A. Aysu, "Tpuxtract: An exhaustive hyperparameter extraction framework," *IACR Transactions on Cryptographic Hardware and Embedded Systems*, vol. 2025, no. 1, pp. 78–103, 2025.
- [18] D. Jap, J. Breier, Z. Lehockỳ, S. Bhasin, and X. Hou, "Side-channel analysis of openvino-based neural network models," *arXiv preprint* arXiv:2407.16467, 2024.

- [19] A. Dubey, R. Cammarota, and A. Aysu, "Maskednet: The first hardware inference engine aiming power side-channel protection," in 2020 IEEE International Symposium on Hardware Oriented Security and Trust (HOST). IEEE, 2020, pp. 197–208.
- [20] —, "Bomanet: Boolean masking of an entire neural network," in 2020 IEEE/ACM International Conference On Computer Aided Design (ICCAD). IEEE, 2020, pp. 1–9.
- [21] D. M. Mehta, M. Hashemi, D. S. Koblah, D. Forte, and F. Ganji, "Bake it till you make it: Heat-induced power leakage from masked neural networks," *IACR Transactions on Cryptographic Hardware and Embedded Systems*, vol. 2024, no. 4, pp. 569–609, 2024.
- [22] J. Breier, D. Jap, X. Hou, and S. Bhasin, "A desynchronization-based countermeasure against side-channel analysis of neural networks," in *International Symposium on Cyber Security, Cryptology, and Machine Learning.* Springer, 2023, pp. 296–306.
- [23] G. R. Blakely, "A computer algorithm for calculating the product ab modulo m," *IEEE Transactions on Computers*, vol. 100, no. 5, pp. 497– 500, 1983.

Acknowledgment. OpenAI's ChatGPT-4 was used to improve the clarity and readability of this manuscript. After using this tool, the authors reviewed and edited the content as needed and take full responsibility for the manuscript's content.