Advancing Singlish Understanding: Bridging the Gap with Datasets and Multimodal Models

Bin Wang*♢ Xunlong Zou*♢ Shuo Sun♢ Wenyu Zhang♢ Yingxu He♢

Zhuohan Liu[◇] Chengwei Wei[◇] Nancy F. Chen^{◇,†} AiTi Aw[◇]

 \Diamond Institute for Infocomm Research (I²R), A*STAR, Singapore

†Centre for Frontier AI Research (CFAR), A*STAR

wang bin@i2r.a-star.edu.sg

Abstract

Singlish, a Creole language rooted in English, is a key focus in linguistic research within multilingual and multicultural contexts. However, its spoken form remains underexplored, limiting insights into its linguistic structure and applications. To address this gap, we standardize and annotate the largest spoken Singlish corpus, introducing the Multitask National Speech Corpus (MNSC). These datasets support diverse tasks, including Automatic Speech Recognition (ASR), Spoken Question Answering (SQA), Spoken Dialogue Summarization (SDS), and Paralinguistic Question Answering (PQA). We release standardized splits and a human-verified test set to facilitate further research. Additionally, we propose SingAudioLLM, a multi-task multimodal model leveraging multimodal large language models to handle these tasks concurrently. Experiments reveal our models' adaptability to Singlish context, achieving state-of-the-art performance and outperforming prior models by 10–30% in comparison with other AudioLLMs and cascaded solutions.^{[1](#page-0-0)}

1 Introduction

Speech technologies have evolved over decades, progressing from modularized solutions for speech recognition [\(Povey et al.,](#page-9-0) [2011;](#page-9-0) [Radford et al.,](#page-9-1) [2023\)](#page-9-1), speaker identification [\(Togneri and Pul](#page-9-2)[lella,](#page-9-2) [2011\)](#page-9-2), and gender recognition [\(Hechmi et al.,](#page-8-0) [2021\)](#page-8-0) with modularized toolkits like Kaldi [\(Povey](#page-9-0) [et al.,](#page-9-0) [2011\)](#page-9-0) and ESPnet [\(Watanabe et al.,](#page-10-0) [2018\)](#page-10-0) to advanced solutions integrating large language models for multimodal understanding in an allencompassing, omni-style approach [\(Team et al.,](#page-9-3) [2023;](#page-9-3) [Zhang et al.,](#page-10-1) [2025;](#page-10-1) [Li et al.,](#page-9-4) [2024\)](#page-9-4). Nevertheless, the combination of speech and language

technology is deemed the trend for solving more complex multimodal tasks requiring a holistic understanding of information from different sources.

In the field of speech and audio understanding, there is a growing trend and initial success of utilizing large language models for complex and direct reasoning over audio signals, which we refer to as Audio Large Language Models (AudioLLMs) [\(Cui](#page-8-1) [et al.,](#page-8-1) [2024;](#page-8-1) [Chu et al.,](#page-8-2) [2024;](#page-8-2) [Nguyen et al.,](#page-9-5) [2024;](#page-9-5) [He et al.,](#page-8-3) [2024\)](#page-8-3). This approach offers several advantages over traditional modular solutions [\(Wang](#page-9-6) [et al.,](#page-9-6) [2024\)](#page-9-6), including but not limited to: 1) the ability to leverage pre-trained models for more sophisticated reasoning, 2) faster decoding time by avoiding multiple decoding steps, as in end-toend models, 3) reduced error propagation between modules, and 4) the capacity for a more holistic understanding of audio signals. Building on this paradigm, our work explores the application of AudioLLMs for Singlish spoken understanding [\(De](#page-8-4)[terding,](#page-8-4) [2007\)](#page-8-4), aiming to address the unique characteristics of Singlish, which include its multilingual nature, diverse accents, and complex syntactic structures.

Existing Singlish spoken corpora have primarily focused on linguistic analysis and speech recognition tasks [\(Deterding and Low,](#page-8-5) [2001;](#page-8-5) [Chen et al.,](#page-8-6) [2010;](#page-8-6) [Lyu et al.,](#page-9-7) [2010;](#page-9-7) [Tan,](#page-9-8) [2019\)](#page-9-8). Given the relatively small population of Singlish speakers, estimated at just a few million, resources for Singlish speech corpora are significantly more limited compared to major languages like English, Chinese, French, and Spanish. Singapore's government agency, IMDA, has open-sourced the largest available Singlish corpus, known as the National Speech Corpus [\(Koh et al.,](#page-9-9) [2019\)](#page-9-9). Despite its great value, this corpus still has several limitations: inconsistent recording scenarios across its components, the absence of standardized splits for benchmarking, and a sole focus on speech recognition tasks. To address these issues, we establish standardized mul-

 1 To facilitate future work, we released our datasets, model, and code at [https://github.com/AudioLLMs/](https://github.com/AudioLLMs/Singlish) [Singlish](https://github.com/AudioLLMs/Singlish)

[∗]Equal Contributions

Figure 1: A demonstration of our target multi-task learning datasets and end-to-end multimodal models for understanding spoken Singlish. The tasks include Automatic Speech Recognition (ASR), Spoken Question Answering (SQA), Spoken Dialogue Summarization (SDS), and Paralinguistic Question Answering (PQA).

titask spoken understanding datasets, expanding beyond basic ASR to include sentence and dialogue speech recognition, spoken question answering, spoken dialogue summarization, and paralinguistic question answering. These datasets are developed through metadata extraction, cleaning of the existing corpus, and synthesis using large language models. All test sets are either pre-annotated or post-edited by our human annotators to ensure high quality and reliability. The datasets, collectively named the Multitask National Speech Corpus (MNSC), are publicly released to support future research on Singlish spoken understanding tasks. This resource is especially valuable in the era of multimodal large language models, which aim to handle multiple tasks within a single unified framework. An illustration can be found in Figure [1.](#page-1-0)

To enhance analysis and set a robust baseline for future benchmarks, we investigate best practices for leveraging audio large language models with different architectural designs. Our model, SingAudioLLM, utilizes joint training across multiple tasks. The results demonstrate that the fusion model achieves state-of-the-art (SOTA) performance, outperforming both generalized AudioLLMs and specialized speech recognition models (e.g., Whisper) by over 10%. Additionally, we analyzed the impact of audio encoder selection, adaptors, and pre-trained LLMs, offering insights into which components contribute most significantly to performance across various tasks.

Our major contributions are as follows:

• We present the MNSC datasets for Singlish spoken understanding, featuring four tasks with standardized training datasets and human-annotated test sets. Baselines are established across all tasks to support future benchmarking and research advancements. MNSC marks the largest

well-organized resource for Singlish-specific spoken language processing, enabling comprehensive evaluation and fostering innovation in multilingual and code-switched NLP research.

- We developed SingAudioLLM, a multimodal audio large language model designed for diverse Singlish spoken understanding tasks. The model incorporates joint training across multiple tasks, leveraging a fusion architecture to maximize performance. Our experiments highlight its ability to capture multilingual nuances, achieving stateof-the-art results across various benchmarks and outperforming prior models by significant margins.
- We analyzed the impact of various components on the performance of Singlish spoken understanding. Our study evaluated factors such as audio encoders, adaptors, and pre-trained language models to determine their contribution to overall effectiveness. The findings provide insights into which elements play a more critical role in enhancing task-specific performance.

2 Related Work

Audio Large Language Model. There is a growing trend of integrating large language models with audio understanding capabilities (including speech, music, and more) to handle human instructions conditioned on the audio modality [\(Peng et al.,](#page-9-10) [2024;](#page-9-10) [Ji et al.,](#page-8-7) [2024;](#page-8-7) [Cui et al.,](#page-8-1) [2024\)](#page-8-1). Most approaches treat large language models (LLMs) as foundation, incorporating audio representations in either continuous or discrete forms [\(Rubenstein et al.,](#page-9-11) [2023\)](#page-9-11). Using discrete tokenizers offers potential advantages, such as extracting more abstract features, reducing the risk of overfitting, and facilitating integration into audio generation scenarios [\(Défos](#page-8-8)[sez et al.,](#page-8-8) [2024\)](#page-8-8). To seamlessly integrate multiple

modalities while preserving the LLM's capabilities, cross-modality instruction tuning is applied to enhance the fusion of different modalities effectively or interleaved modality features [\(Pan et al.,](#page-9-12) [2023;](#page-9-12) [Kim et al.,](#page-8-9) [2024;](#page-8-9) [Nguyen et al.,](#page-9-5) [2024\)](#page-9-5).

Fusion models offer several key advantages over cascaded models, including minimizing information loss, avoiding cumulative errors, and enabling faster decoding times. They also hold the potential to handle more complex tasks, such as decoding speaker-specific information and performing context-dependent question answering that incorporates paralinguistic features (e.g., accent, emotion, and gender) or environmental cues. However, existing research efforts are predominantly focused on high-resource languages such as English [\(Tang](#page-9-13) [et al.,](#page-9-13) [2024;](#page-9-13) [Lu et al.,](#page-9-14) [2024\)](#page-9-14) and Chinese [\(Chu](#page-8-2) [et al.,](#page-8-2) [2024;](#page-8-2) [Yang et al.,](#page-10-2) [2024\)](#page-10-2). Research on AudioLLMs for low-resource and Creole languages remains limited, largely because these technologies are still in their early stages of development and suitable resources are scarce.

Singlish Spoken Understanding. Previous research on Singlish spoken corpora has primarily focused on ASR [\(Deterding and Low,](#page-8-5) [2001;](#page-8-5) [Lyu](#page-9-7) [et al.,](#page-9-7) [2010;](#page-9-7) [Boo et al.,](#page-8-10) [2023\)](#page-8-10), code-switching tasks [\(Lyu et al.,](#page-9-7) [2010;](#page-9-7) [Koh et al.,](#page-9-9) [2019\)](#page-9-9), and linguistic pattern analysis [\(Lim,](#page-9-15) [2011;](#page-9-15) [Goh,](#page-8-11) [2016;](#page-8-11) [Lee,](#page-9-16) [2022\)](#page-9-16). However, the speech corpus is still limited and contains just a few hundred hours of speech [\(Chen et al.,](#page-8-6) [2010\)](#page-8-6). To address this, the Info-communications and Media Development Authority (IMDA), a government agency in Singapore, launched a major initiative called National Speech Corpus (NSC) to collect the first large-scale Singapore English corpus for ASR tasks. Released in multiple stages, the corpus comprises approximately 10,000 hours of speech, predominantly featuring the Singaporean accent (Singlish) and codeswitching patterns. Despite the availability of abundant resources under a publicly accessible license, Singlish spoken understanding tasks remain underexplored due to several challenges: 1) the focus is largely limited to automatic speech recognition, 2) the absence of standardized train/test splits for consistent benchmarking, and 3) difficulties in processing data with misaligned annotations. Therefore, in this work, we release the Multitask National Speech Corpus (MNSC), designed to support complex reasoning tasks beyond speech recognition for research and practical applications.

3 Multitask National Speech Corpus

A major challenge in spoken Singlish understanding is the lack of standardized data and limited resources. While the National Speech Corpus [\(Koh](#page-9-9) [et al.,](#page-9-9) [2019\)](#page-9-9) focuses on ASR, it lacks support and evaluation sets for broader tasks. To address this, we introduce the Multitask National Speech Corpus (MNSC), which extends coverage to dialogue summarization, spoken understanding, and paralinguistic analysis, accompanied by newly created human-labeled test sets and standardized train-test splits. All datasets are publicly available, offering a robust, multitask-oriented resource to advance research in spoken Singlish understanding.

3.1 Source

National Speech Coprus is the first large-scale Singapore English corpus spearheaded by the Infocommuications and Media Development Author-ity (IMDA) of Singapore^{[2](#page-2-0)}. Its release is divided into two phases and 9 parts, encompassing approximately 10,000 hours of recorded audio from around 1,000 local Singaporeans. The six parts are organized into distinct themes and conditions, detailed as follows:

- **PART 1.** This part contains prompted recordings of phonetically-balanced scripts, featuring standard English sentences with local accents that reflect the unique linguistic characteristics of the speakers.
- **PART 2.** This part includes prompted recordings of sentences randomly generated from topics such as people, food, locations, and brands. The recordings incorporate a rich use of local terms and locations and are accompanied by orthographic transcriptions, highlighting the linguistic and cultural diversity of the context.
- **PART 3**. This part features conversational data where speakers engage in discussions covering topics from daily life and structured interactions such as gameplay.
- **PART 4**. This part focuses on **code-switching**, where speakers alternate between Singapore English and their mother tongue languages including Mandarin, Malay, or Tamil.
- **PART 5**. This part includes recordings of speakers adopting specific speaking styles, such as debates, finance-related discussions, and expressions of positive and negative emotions.

²[https://www.imda.gov.sg/](https://www.imda.gov.sg/how-we-can-help/national-speech-corpus) [how-we-can-help/national-speech-corpus](https://www.imda.gov.sg/how-we-can-help/national-speech-corpus)

Category	Source	Split	#Samples Total hours		Avg./Min./Max. Len
ASR - Automatic Speech Recognition					
Sentence-Level	$NSC-PART$ 1-2	Train	2.3M, 2.5M	3.3K, 3.2K	4.9s, 1.2s, 27.4s
		Test	3K, 3K	4.0K, 4.9K	5.4s, 1.9s, 14.9s
Dialogue-Level	96K, 9K, 24K, 104K 741, 70, 168, 697 Train NSC-PART 3-6		25s, 15s, 30s		
		Test	1K, 1K, 1K, 1K	7.7, 7.3, 6.9, 6.8	25s, 15s, 30s
SQA - Spoken Question Answering					
Dialogue-Level	NSC-PART 3-6	Train	96K, 9K, 24K, 104K	741, 70, 168, 697	25s, 15s, 30s
		Test	100, 100, 100, 100	0.8, 0.8, 0.8, 0.8	27s, 15s, 30s
SDS - Spoken Dialogue Summarization					
Dialogue-Level	NSC-PART 3-6	Train	96K, 9K, 24K, 104K	741, 70, 168, 697	25s, 15s, 30s
		Test	100, 100, 100, 100	0.8, 0.8, 0.8, 0.8	27s, 15s, 30s
POA - Pralinguistic Ouestion Answering					
Sentence-Level	NSC-PART 1-2	Train	4.7M	6.5K	4.9s, 1.2s, 27s
(Gender/Accent)		Test	6K	9	5.4s, 1.9s, 14.9s
Dialogue-Level	NSC-PART 3-5	Train	130K	979	27s, 15s, 30s
(Gender/Accent)		Test	3K	21.9	26.3s, 15s, 30s

Table 1: Statistics for MNSC - Multitask National Speech Corpus.

• **PART 6.** This part comprises recordings of speakers participating in scenarios designed around three themes: holiday / hotel / restaurant, bank / telephone / insurance, and HDB / MOE / MSF.

We classify the recordings into monologue and dialogue categories. For dialogue scenarios, audio channels from different rooms or speakers are merged into a single unified channel covering the entire conversation, with a maximum dialogue duration capped at 30 seconds. Recordings that could not be perfectly aligned were excluded from the MNSC dataset.

3.2 Data Generation and Human Annotation

For multitasking, we construct the dataset to support four tasks. The complete dataset statistics for each task are presented in Table [1.](#page-3-0) For ASR, the transcriptions are split into sentence-level and dialogue-level categories, with dialogue-level transcriptions created by combining original orthographic transcripts.

For the SQA (Spoken Question Answering) and SDS (Spoken Dialogue Summarization) tasks, we synthesized question-answer pairs and dialogue summaries for training, while employing human annotators to create a high-quality, humanlabeled test set. To generate the training data, we utilized the LLM (LLAMA-3.1-70B-Instruct model [\(Dubey et al.,](#page-8-12) [2024\)](#page-8-12)), prompting it with transcriptions to elicit meaningful instructions [\(Wang](#page-9-17) [et al.,](#page-9-17) [2023b,](#page-9-17)[a\)](#page-9-18). This form of data augmentation is a commonly adopted practice, enabling the efficient generation of diverse and contextually rich

training samples.

For evaluation, human annotators, who were fully informed about the task and compensated appropriately, conducted detailed annotations, employing cross-validation techniques to ensure quality and consistency. This process yielded 100 test samples for each subtask, culminating in a total of 800 high-quality samples spanning the QA and summarization tasks. In part 4, where codeswitching occurs, all data is labeled in English but requires an understanding of multilingual exchanges. This approach ensures annotation consistency while addressing the content's multilingual nature.

For PQA (Paralinguistic Question Answering), we utilize metadata such as speaker ethnicity and gender. This metadata allows us to assess the model's ability to infer beyond basic transcriptions by identifying attributes such as gender and accents, thereby enriching the multitasking framework with paralinguistic understanding. The task is divided into sentence-level and dialogue-level categories, with the former involving a single speaker and the latter encompassing interactions between multiple speakers.

4 SingAudioLLM

As shown in Figure [2,](#page-4-0) we explore the fusion model by extracting audio features and adapting the feature to the token embedding space of LLMs through adaptor modules. Such features are concatenated with token embedding of texture instructions and learned jointly with corresponding responses end-to-end. In this section, we will intro-

Figure 2: The architecture of SingAudioLLM incorporates a modality adaptor that processes audio features extracted for representation. These adapted features are then combined with textual instructions and input into the large language model, enabling it to handle a variety of tasks effectively.

duce the components leveraged and the training scheme of our AudioLLM for Singlish spoken understandings.

4.1 Encoder

To understand speech signals, we need to extract features and encode their semantic and contextual meanings into a representation space. In this context, we utilize the Whisper model, specifically Whisper-Large-v3 [\(Radford et al.,](#page-9-1) [2023\)](#page-9-1), due to its robust performance in multilingual automatic speech recognition and speech translation. Given that Singlish is an evolving language incorporating accents and terms from its diverse multilingual cultural mix, leveraging a multilingual encoder as a foundational feature extractor can be advantageous.

Formally, with a sequence of audio signals as $\mathbf{x} = \{x_1, x_2, \dots, x_T\}$, the audio signal x is encoded with the encoder of Whisper model ϕ , which consists of extracting mel-spectrum features and multiple layers of self-attention and feed-forward networks, to hidden representations h.

$$
\mathbf{h} = \phi(\mathbf{x}), \mathbf{h} \in \mathbb{R}^{\tau \times d}
$$

where $d = 1280$ is the size of the hidden dimension and $\tau = 1500$ is the encoded sequence length. Note for Whisper encoder, the input audio signal is always padded to 30 seconds and the sequence length τ is fixed and $\tau \ll T$.

4.2 Modality Adapter

After encoding, we further adapt the feature through adaptors to match the representation of token embeddings from LLMs. Here, we experiment with three variances: Rescale-MLP, 1-Dimensional Convolutional Layer (Conv-1D) [\(Li et al.,](#page-9-19) [2023a\)](#page-9-19) and Q-Former [\(Li et al.,](#page-9-20) [2023b\)](#page-9-20).

Rescale-MLP: With the encoder output sequence $h \in \mathbb{R}^{\tau \times d}$, we first reshape the embedding to match the desired sequence length for the LLM embedding layers. Specifically, the reshaped embedding is given by $h' \in \mathbb{R}^{(\tau/s) \times (d \cdot s)}$, where s is the scaling factor that adjusts the original sequence length τ to τ/s .

Subsequently, we apply three MLP layers sequentially to transform the embedding dimensions. These layers map the embedding size from $d \cdot s$ to d , then from d to 4d, and finally from 4d to γ , where γ denotes the embedding size of the subsequent LLM. We apply two SiLU activations [\(Elfwing](#page-8-13) [et al.,](#page-8-13) [2018\)](#page-8-13) between the MLP layers. In our experiments, we evaluated different scaling factors s, which resulted in varying sequence lengths derived from speech features for integration with LLMs, where a larger s produces fewer audio tokens.

Conv-1D: We employ a 1-dimensional convolutional layer followed by a single MLP layer for feature reorganization. Specifically, we use a kernel size of 8 with a stride of 8. The number of output channels for the 1-dimensional convolutional layer is set to γ , which corresponds to the embedding size of LLMs. Consequently, the output sequence length is downsampled to approximately $\tau/8$. Following this, we apply a single MLP layer with both input and output embedding sizes equal to γ .

Unlike [Li et al.](#page-9-19) [\(2023a\)](#page-9-19), we utilize a 1D convolutional layer instead of 2D, as our focus is on processing 1D audio features. The downsampled output sequence length facilitates faster training and inference when integrated with LLMs.

Q-Former: Instead of using the original Q-Former proposed in [Li et al.](#page-9-20) [\(2023b\)](#page-9-20), we adopt the windowbased Q-Former as introduced in [Tang et al.](#page-9-13) [\(2024\)](#page-9-13). The window-based Q-Former is designed to improve efficiency, particularly when the encoder sequence length is long, which can result in significant memory consumption due to the computation of cross-attentions within transformer layers. Similarly, we randomly initialize the Q-Former layers, and the Query tokens are trainable parameters integrated into the network structure.

4.3 Large Language Model

As Singlish incorporates a mix of multiple dialects and involves code-switching in certain data samples, we aim to examine whether a more advanced multilingual large language model can improve spoken understanding tasks in this scenario. To this end, our study compares both Gemma models [\(Team et al.,](#page-9-21) [2024\)](#page-9-21) and Llama models [\(Dubey](#page-8-12) [et al.,](#page-8-12) [2024\)](#page-8-12). Additionally, we also investigate the impact of model size on performance. Specifically, the speech token embeddings are concatenated with the token embeddings from prompts using the following template after the embedding layer of the LLMs: "<speech> s_{tokens} </speech> t_{prompt} ". Additionally, the corresponding LLM chat template is applied to align with the instruction-tuned capabilities of the LLM.

4.4 Training Method

In our approach, the encoder and adaptor are fully fine-tuned, while the decoder undergoes LoRA tuning [\(Hu et al.,](#page-8-14) [2021\)](#page-8-14), with the model designed for autoregressive text generation tasks. In our experiments, we explored alternative training setups. We observed that without adapting the encoder, it becomes challenging to learn new accents, phonetics, and local terms, which are prevalent in Singlish but beyond standard English. Additionally, replacing LoRA tuning with full fine-tuning of the LLM significantly impacts its original capabilities, resulting in diminished performance in following diverse instructions. This is why we adopt the above training configuration in all experiments. Furthermore, some existing studies have investigated various alternative approaches to address these challenges through multi-task learning, multi-stage training, and others [\(Tang et al.,](#page-9-13) [2024;](#page-9-13) [He et al.,](#page-8-3) [2024;](#page-8-3) [Chu](#page-8-2) [et al.,](#page-8-2) [2024;](#page-8-2) [Lu et al.,](#page-9-14) [2024\)](#page-9-14).

5 Experiments

We train SingAudioLLM on the full MNSC corpus to evaluate its effectiveness for experiments. For the main results, we employ Whisper-large-v3 as

the encoder, Conv-1D as the modality adaptor, and Gemma2-9B-Instruct as the decoder, selected for their robust performance and efficiency. Additionally, we conduct an ablation study using alternative variants to provide further insights. For evaluation, in addition to standard in-domain evaluations using MNSC subsets, we include three external evaluation sets: CN-College-Listen-Test [\(Wang](#page-9-6) [et al.,](#page-9-6) [2024;](#page-9-6) [Hu et al.,](#page-8-15) [2024\)](#page-8-15), Singapore Public Speech QA [\(Wang et al.,](#page-9-6) [2024\)](#page-9-6), and SEAME [\(Lyu](#page-9-7) [et al.,](#page-9-7) [2010\)](#page-9-7). These evaluation sets focus on English comprehension, question answering based on Singapore public speeches, and code-switching Singlish ASR for English and Mandarin, respectively, providing a comprehensive understanding of the model's generalizability. All evaluation metrics adhere to the original design, utilizing either Word Error Rate (WER) or model-as-judge scores.

Baselines. For comparison, we include four end-to-end multimodal models Qwen2-Audio-Instruct [\(Chu et al.,](#page-8-2) [2024\)](#page-8-2), WavLLM [\(Hu et al.,](#page-8-15) [2024\)](#page-8-15), Qwen-Audio-Chat [\(Chu et al.,](#page-8-16) [2023\)](#page-8-16) and SALMONN [\(Tang et al.,](#page-9-13) [2024\)](#page-9-13), and a cascaded model that integrates ASR outputs from Whisper-Large-v3 into the Llama-3-8B-Instruct model. We also fine-tuned Whisper using our ASR subsets to evaluate its performance with adaptation as a standalone ASR model. The results are included.

Results and Analysis. As shown in Table [2,](#page-6-0) Sing-AudioLLM demonstrates superior in-domain performance compared to all other models. For ASR tasks, Whisper provides a strong baseline. Notably, the MNSC-ASR-PART 1 dataset achieves strong results, with all models reaching below 10 WER, as it features read speech without significant use of local terminology. However, other scenarios, such as local adaptation in PART 2 and dialogue-based tasks, require substantial adaptation. In these cases, the LLM used as a decoder proves effective, successfully learning and decoding Singapore-specific terms.

For SQA and SDS tasks, the cascade model outperforms other AudioLLMs by a clear margin. This highlights the advantage of decoupling transcription generation and instruction following, preserving the LLM's reasoning capabilities and flexibility. The cascade model handles noisy inputs more effectively, leading to second-best performance. Nevertheless, domain adaptation remains critical, as evidenced by the improved results from our model.

For paralinguistic tasks, gender inference shows

Table 2: Main results of four AudioLLMs and one cascade model. The word-error-rate (WER) for ASR tasks is the lower the better $_{(\downarrow)}$. The best performance is highlighted in bold.

Dataset		AudioLLM FT-Whisper	Whisper-Large-v3
MNSC-ASR PART 1	4.4	4.4	6.9
MNSC-ASR PART 2	4.2	3.8	31.9
MNSC-ASR PART 3	23.7	18.8	30.0
MNSC-ASR PART 4	34.8	29.8	47.5
MNSC-ASR PART 5	19.4	20.6	22.0
MNSC-ASR PART 6	13.4	24.0	17.5
SEAME-Dev-SGE	31.7	27.2	54.9
SEAME-Dev-MAN	35.2	28.8	55.2

Table 3: Comparison of three models on Singlish ASR performance. The AudioLLM and FT-Whisper are further fine-tuned with ASR data from NMSC.

moderate success with existing AudioLLMs. Among the baselines, Qwen2-Audio-Instruct delivers the best results but struggles with Singlish speakers, especially in multi-speaker settings. Accent recognition, in particular, requires significant domain adaptation to achieve reasonable performance. All existing AudioLLMs fail to generalize effectively to our scenarios.

In zero-shot evaluations on hold-out datasets, Sing-AudioLLM demonstrates strong transferability from Singlish datasets to general English domains. For instance, it achieves the highest performance on the CN-College-Listen-Test dataset among all AudioLLMs, despite not being trained on general domain data. Additionally, SEAME

datasets show strong zero-shot performance, outperforming Whisper models. These results indicate that MNSC datasets generalize well to other accents and code-switching scenarios.

ASR Performance. To further evaluate the effectiveness of the MNSC datasets beyond their use in AudioLLMs, we adapted the Whisper-large model and compared it to our SingAudioLLM, which was trained exclusively on MNSC-ASR datasets without incorporating additional Singlish understanding tasks. As shown in Table [3,](#page-6-1) the MNSC datasets significantly enhance Whisper's adaptation to the Singlish domain, demonstrating strong performance even in zero-shot evaluations on SEAME datasets. Additionally, ASR-only AudioLLM models outperform multitask AudioLLMs as task-specific solutions, highlighting the effectiveness of task-specific models in maintaining a sharper focus on the target objective (e.g ASR).

Impact of Encoder. For the decoder size study, we varied the encoder configurations of Whisper while keeping other settings fixed, using Conv-1D as the adaptor and Gemma-9B as the LLM decoder. As shown in Figure [3,](#page-7-0) performance generally degrades across all three tasks with smaller encoders. An exception is observed with Whisper-

Figure 3: We conducted a study to assess the effectiveness of different encoder sizes, decoder sizes, adaptor types, and decoder types across three tasks, reporting the average performance for each task. Encoder sizes were evaluated using five variants ranging from 8M to 637M parameters, represented along the x-axis. The comparison of adaptors and decoders is represented with diamonds and circles.

large and Whisper-medium, where ASR performance remains comparable. Notably, Whispermedium outperforms Whisper-large in dialogue summarization tasks, indicating that both models can generate robust semantic representations of speech content. However, with smaller encoders, performance drops significantly, with noticeable degradations across tasks. These findings suggest that a strong speech encoder is critical to effectively integrating LLMs.

Effect on Adaptors. We evaluated three adaptor variants, as introduced in Section [4.2,](#page-4-1) with results illustrated by the dotted points in Figure [3.](#page-7-0) MLP-100 ($s = 15$) and MLP-500 ($s = 3$) demonstrated comparable performance to the Conv-1D model. The Conv-1D model compresses the input sequence length of audio embeddings to approximately 180 tokens, while MLP-100 and MLP-500 compress to 100 and 500 tokens, respectively. Theoretically, longer input sequences to the LLM decoder increase generation time and latency, and may not be necessary to effectively encode audio information. Considering the balance between encoding efficiency, generation speed, and overall task performance, Conv-1D is selected as the default adaptor. We found no significant advantage with Q-Former. One possible reason is that we fine-tune the speech feature extractor with full parameters, whereas BLIP-2 [\(Li et al.,](#page-9-20) [2023b\)](#page-9-20) keeps the feature extractor frozen when using Q-Former as an adaptor. This difference in parameter tuning may explain the lack of performance improvement with Q-Former in our setup.

LLM Decoder Size and Type. We compared two sizes of LLM decoders: Gemma-9B and Gemma2B. The results vary across tasks. For ASR, the decoder size has minimal impact on performance. However, for understanding and reasoning tasks, such as question answering and summarization, the larger decoder size significantly outperforms the smaller one. This suggests that ASR primarily relies on superficial features like phoneme and phonetic information, which do not require a large language model for complex reasoning. This also explains why CTC-based models [\(Kim et al.,](#page-8-17) [2017\)](#page-8-17) continue to achieve strong performance in certain scenarios compared to LM-based approaches. In contrast, reasoning and summarization tasks benefit substantially from the enhanced capabilities of a larger LLM. We also evaluated LLAMA-3- 8B-Instruct as the decoder. Consistent with earlier observations, it demonstrated inferior performance on SQA and SDS tasks, indicating weaker reasoning capabilities compared to the Gemma models. However, LLAMA-3-8B outperformed Gemma-2B in the ASR task, the stronger decoder does not have obvious effect on ASR task.

6 Conclusion

This study addresses the critical gap in spoken Singlish research by introducing the largest standardized spoken Singlish corpus, MNSC, and the novel SingAudioLLM model. The proposed datasets and model demonstrate significant advancements in multilingual and multimodal audio understanding, achieving state-of-the-art performance across diverse tasks. By releasing the datasets, model, and code, we aim to foster future research and innovation in Singlish language processing and beyond.

Limitations

The primary limitation of this work arises from the data preparation of the original National Speech Corpus, which was not specifically designed for dialogue tasks, and the variability in recording environments, as discussed in Section [3.](#page-2-1) To ensure high data quality, we prioritized releasing only data with high confidence. However, a substantial portion of the data was excluded from this release due to issues with alignment noise and inappropriate annotations. This highlights that not all data sources were fully utilized, leaving room for improvement by incorporating more available data in the future.

Acknowledgement

This research is supported by the National Research Foundation, Singapore and Infocomm Media Development Authority, Singapore under its National Large Language Models Funding Initiative. Any opinions, findings and conclusions or recommendations expressed in this material are those of the author(s) and do not reflect the views of National Research Foundation, Singapore and Infocomm Media Development Authority, Singapore.

References

- Ashley Boo, Junwen Lee, and Ying-Ying Tan. 2023. Particle stacking in singlish–new data from the national speech corpus. *Lingua*, 287:103513.
- Wenda Chen, Y Tan, E Chng, and Haizhou Li. 2010. The development of a singapore english call resource. *Oriental COCOSDA, Nepal*.
- Yunfei Chu, Jin Xu, Qian Yang, Haojie Wei, Xipin Wei, Zhifang Guo, Yichong Leng, Yuanjun Lv, Jinzheng He, Junyang Lin, et al. 2024. Qwen2-audio technical report. *arXiv preprint arXiv:2407.10759*.
- Yunfei Chu, Jin Xu, Xiaohuan Zhou, Qian Yang, Shiliang Zhang, Zhijie Yan, Chang Zhou, and Jingren Zhou. 2023. Qwen-audio: Advancing universal audio understanding via unified large-scale audiolanguage models. *arXiv preprint arXiv:2311.07919*.
- Wenqian Cui, Dianzhi Yu, Xiaoqi Jiao, Ziqiao Meng, Guangyan Zhang, Qichao Wang, Yiwen Guo, and Irwin King. 2024. Recent advances in speech language models: A survey. *arXiv preprint arXiv:2410.03751*.
- Alexandre Défossez, Laurent Mazaré, Manu Orsini, Amélie Royer, Patrick Pérez, Hervé Jégou, Edouard Grave, and Neil Zeghidour. 2024. Moshi: a speechtext foundation model for real-time dialogue. *arXiv preprint arXiv:2410.00037*.
- David Deterding. 2007. *Singapore English*. Edinburgh University Press.
- David Deterding and Ee Ling Low. 2001. The nie corpus of spoken singapore english (niecsse). *SAAL Quarterly*, 56(1):2–5.
- Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, et al. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.
- Stefan Elfwing, Eiji Uchibe, and Kenji Doya. 2018. Sigmoid-weighted linear units for neural network function approximation in reinforcement learning. *Neural networks*, 107:3–11.
- Robbie BH Goh. 2016. The anatomy of singlish: globalisation, multiculturalism and the construction of the 'local'in singapore. *Journal of Multilingual and Multicultural Development*, 37(8):748–758.
- Yingxu He, Zhuohan Liu, Shuo Sun, Bin Wang, Wenyu Zhang, Xunlong Zou, Nancy F Chen, and Ai Ti Aw. 2024. Meralion-audiollm: Technical report. *arXiv preprint arXiv:2412.09818*.
- Khaled Hechmi, Trung Ngo Trong, Ville Hautamäki, and Tomi Kinnunen. 2021. Voxceleb enrichment for age and gender recognition. In *2021 IEEE Automatic Speech Recognition and Understanding Workshop (ASRU)*, pages 687–693. IEEE.
- Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2021. Lora: Low-rank adaptation of large language models. *arXiv preprint arXiv:2106.09685*.
- Shujie Hu, Long Zhou, Shujie Liu, Sanyuan Chen, Hongkun Hao, Jing Pan, Xunying Liu, Jinyu Li, Sunit Sivasankaran, Linquan Liu, et al. 2024. Wavllm: Towards robust and adaptive speech large language model. *arXiv preprint arXiv:2404.00656*.
- Shengpeng Ji, Yifu Chen, Minghui Fang, Jialong Zuo, Jingyu Lu, Hanting Wang, Ziyue Jiang, Long Zhou, Shujie Liu, Xize Cheng, et al. 2024. Wavchat: A survey of spoken dialogue models. *arXiv preprint arXiv:2411.13577*.
- Heeseung Kim, Soonshin Seo, Kyeongseok Jeong, Ohsung Kwon, Soyoon Kim, Jungwhan Kim, Jaehong Lee, Eunwoo Song, Myungwoo Oh, Jung-Woo Ha, et al. 2024. Paralinguistics-aware speechempowered large language models for natural conversation. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*.
- Suyoun Kim, Takaaki Hori, and Shinji Watanabe. 2017. Joint ctc-attention based end-to-end speech recognition using multi-task learning. In *2017 IEEE international conference on acoustics, speech and signal processing (ICASSP)*, pages 4835–4839. IEEE.
- Jia Xin Koh, Aqilah Mislan, Kevin Khoo, Brian Ang, Wilson Ang, Charmaine Ng, and YY Tan. 2019. Building the singapore english national speech corpus. *Malay*, 20(25.0):19–3.
- Junwen Lee. 2022. An analysis of colloquial singapore english lah and its interpretation across speech acts. *Languages*, 7(3):203.
- Jiachen Li, Ali Hassani, Steven Walton, and Humphrey Shi. 2023a. Convmlp: Hierarchical convolutional mlps for vision. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6307–6316.
- Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. 2023b. Blip-2: Bootstrapping language-image pretraining with frozen image encoders and large language models. In *International conference on machine learning*, pages 19730–19742. PMLR.
- Yadong Li, Haoze Sun, Mingan Lin, Tianpeng Li, Guosheng Dong, Tao Zhang, Bowen Ding, Wei Song, Zhenglin Cheng, Yuqi Huo, et al. 2024. Baichuan-omni technical report. *arXiv preprint arXiv:2410.08565*.
- Lisa Lim. 2011. Tone in singlish: Substrate features from sinitic and malay. *Substrate Features in Creole Languages*, pages 271–288.
- Ke-Han Lu, Zhehuai Chen, Szu-Wei Fu, Chao-Han Huck Yang, Jagadeesh Balam, Boris Ginsburg, Yu-Chiang Frank Wang, and Hung-yi Lee. 2024. Developing instruction-following speech language model without speech instruction-tuning data. *arXiv preprint arXiv:2409.20007*.
- Dau-Cheng Lyu, Tien Ping Tan, Engsiong Chng, and Haizhou Li. 2010. Seame: a mandarin-english codeswitching speech corpus in south-east asia. In *Interspeech*, volume 10, pages 1986–1989.
- Tu Anh Nguyen, Benjamin Muller, Bokai Yu, Marta R Costa-Jussa, Maha Elbayad, Sravya Popuri, Paul-Ambroise Duquenne, Robin Algayres, Ruslan Mavlyutov, Itai Gat, et al. 2024. Spirit-lm: Interleaved spoken and written language model. *arXiv preprint arXiv:2402.05755*.
- Jing Pan, Jian Wu, Yashesh Gaur, Sunit Sivasankaran, Zhuo Chen, Shujie Liu, and Jinyu Li. 2023. Cosmic: Data efficient instruction-tuning for speech in-context learning. *arXiv preprint arXiv:2311.02248*.
- Jing Peng, Yucheng Wang, Yu Xi, Xv Li, and Kai Yu. 2024. A survey on speech large language models. *arXiv preprint arXiv:2410.18908*.
- Daniel Povey, Arnab Ghoshal, Gilles Boulianne, Lukas Burget, Ondrej Glembek, Nagendra Goel, Mirko Hannemann, Petr Motlicek, Yanmin Qian, Petr Schwarz, et al. 2011. The kaldi speech recognition toolkit. In *IEEE 2011 workshop on automatic speech recognition and understanding*. IEEE Signal Processing Society.
- Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. 2023. Robust speech recognition via large-scale weak supervision. In *International Conference on Machine Learning*, pages 28492–28518. PMLR.
- Paul K Rubenstein, Chulayuth Asawaroengchai, Duc Dung Nguyen, Ankur Bapna, Zalán Borsos, Félix de Chaumont Quitry, Peter Chen, Dalia El Badawy, Wei Han, Eugene Kharitonov, et al. 2023. Audiopalm: A large language model that can speak and listen. *arXiv preprint arXiv:2306.12925*.
- Ying-Ying Tan. 2019. Spontaneous speech elicitation for large speech corpus in multilingual singapore. *IPSS*.
- Changli Tang, Wenyi Yu, Guangzhi Sun, Xianzhao Chen, Tian Tan, Wei Li, Lu Lu, Zejun MA, and Chao Zhang. 2024. SALMONN: Towards generic hearing abilities for large language models. In *International Conference on Learning Representations (ICLR)*.
- Gemini Team, Rohan Anil, Sebastian Borgeaud, Yonghui Wu, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, et al. 2023. Gemini: a family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*.
- Gemma Team, Thomas Mesnard, Cassidy Hardin, Robert Dadashi, Surya Bhupatiraju, Shreya Pathak, Laurent Sifre, Morgane Rivière, Mihir Sanjay Kale, Juliette Love, et al. 2024. Gemma: Open models based on gemini research and technology. *arXiv preprint arXiv:2403.08295*.
- Roberto Togneri and Daniel Pullella. 2011. An overview of speaker identification: Accuracy and robustness issues. *IEEE circuits and systems magazine*, 11(2):23–61.
- Bin Wang, Zhengyuan Liu, and Nancy Chen. 2023a. [Instructive dialogue summarization with query ag](https://doi.org/10.18653/v1/2023.emnlp-main.474)[gregations.](https://doi.org/10.18653/v1/2023.emnlp-main.474) In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 7630–7653, Singapore. Association for Computational Linguistics.
- Bin Wang, Xunlong Zou, Geyu Lin, Shuo Sun, Zhuohan Liu, Wenyu Zhang, Zhengyuan Liu, AiTi Aw, and Nancy F Chen. 2024. Audiobench: A universal benchmark for audio large language models. *arXiv preprint arXiv:2406.16020*.
- Yizhong Wang, Yeganeh Kordi, Swaroop Mishra, Alisa Liu, Noah A. Smith, Daniel Khashabi, and Hannaneh Hajishirzi. 2023b. [Self-instruct: Aligning language](https://doi.org/10.18653/v1/2023.acl-long.754) [models with self-generated instructions.](https://doi.org/10.18653/v1/2023.acl-long.754) In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 13484–13508, Toronto, Canada. Association for Computational Linguistics.
- Shinji Watanabe, Takaaki Hori, Shigeki Karita, Tomoki Hayashi, Jiro Nishitoba, Yuya Unno, Nelson Enrique Yalta Soplin, Jahn Heymann, Matthew Wiesner, Nanxin Chen, Adithya Renduchintala, and Tsubasa Ochiai. 2018. [ESPnet: End-to-end speech process](https://doi.org/10.21437/Interspeech.2018-1456)[ing toolkit.](https://doi.org/10.21437/Interspeech.2018-1456) In *Proceedings of Interspeech*, pages 2207–2211.
- Chih-Kai Yang, Yu-Kuan Fu, Chen-An Li, Yi-Cheng Lin, Yu-Xiang Lin, Wei-Chih Chen, Ho Lam Chung, Chun-Yi Kuan, Wei-Ping Huang, Ke-Han Lu, et al. 2024. Building a taiwanese mandarin spoken language model: A first attempt. *arXiv preprint arXiv:2411.07111*.
- Wenyu Zhang, Shuo Sun, Bin Wang, Xunlong Zou, Zhuohan Liu, Yingxu He, Geyu Lin, Nancy F Chen, and Ai Ti Aw. 2025. Mowe-audio: Multitask audiollms with mixture of weak encoders. *ICASSP 2025*.

A MNSC Samples

The following table presents examples from various MNSC subsets.

B Hardward

Experiments were conducted on multiple DGX nodes featuring 8 NVIDIA H100 GPUs with 80GB VRAM each. These specifications ensure efficient training and evaluation across various tasks.

C License

In terms of licensing, the MNSC datasets follow the NSC dataset to be under the Singapore Open Data Licence^{[3](#page-10-3)}, allowing free use with proper attribution. Restrictions include no rights to personal data, unauthorized third-party rights, or intellectual property.

³<https://data.gov.sg/open-data-licence>

Table 4: Examples from MNSC ASR datasets and responses from models. Table 4: Examples from MNSC ASR datasets and responses from models.

Table 5: Examples from MNSC SQS, SDS datasets and responses from models. Table 5: Examples from MNSC SQS, SDS datasets and responses from models.

Table 6: Examples from MNSC PQA datasets and responses from models. Table 6: Examples from MNSC PQA datasets and responses from models.