# Machine Learning-Driven Insights into Excitonic Effects in 2D Materials

Ahsan Javed<sup>1,2</sup>, Sajid Ali<sup>\*,3</sup>

<sup>1</sup>Department of Physics, Syed Babar Ali School of Science and Engineering, Lahore University of Management Sciences (LUMS), Lahore-54792, Pakistan

<sup>2</sup>Department of Physics, COMSATS University Islamabad, Lahore Campus, Lahore, Pakistan

<sup>3</sup>Department of Materials Science and Engineering, Monash University, Victoria 3800, Australia <sup>∗</sup>Corresponding Author : sajid.ali@monash.edu

# Abstract

Understanding excitonic effects in two-dimensional (2D) materials is critical for advancing their potential in next-generation electronic and photonic devices. In this study, we introduce a machine learning (ML)-based framework to predict exciton binding energies in 2D materials, offering a computationally efficient alternative to traditional methods such as many-body perturbation theory (GW) and the Bethe-Salpeter equation. Leveraging data from the Computational 2D Materials Database (C2DB), our ML models establish connections between cheaply available material descriptors and complex excitonic properties, significantly accelerating the screening process for materials with pronounced excitonic effects. Additionally, Bayesian optimization with Gaussian process regression was employed to efficiently filter materials with largest exciton binding energies, further enhancing the discovery process. Although developed for 2D systems, this approach is versatile and can be extended to three-dimensional materials, broadening its applicability in materials discovery. Keywords: Excitonic effects, 2D Materials, Machine learning, Regression, exciton binding energy

## 1. Introduction

Two-dimensional materials (2DMs) have garnered substantial interest due to their exceptional optical and electronic properties, positioning them as promising candidates for next-generation optoelectronic technologies. A defining feature of these materials is their pronounced excitonic effects, which are significantly more pronounced in 2D systems compared to bulk materials [\[1\]](#page-12-0). This enhanced excitonic behavior arises from reduced dielectric screening and increased Coulomb interactions in monolayers [\[2,](#page-12-1) [3\]](#page-12-2). Consequently, understanding these excitonic properties is crucial for optimizing the performance of devices based on such materials.

First-principles calculations of exciton binding energy (EBE) in 2DMs involve computationally expensive and laborious methods, such as the GW approximation and the Bethe-Salpeter Equation (BSE) [\[4\]](#page-12-3). The GW approximation surpasses mean-field, independentparticle DFT by accounting for many-body electron-electron interactions, offering a more accurate understanding of electronic properties, including excitation energies, band gaps, and optical characteristics. This method involves iteratively solving for the Green's function (G), the screened Coulomb interaction (W), and the self-energy  $(\Sigma)$  until self-consistency is achieved, yielding an improved description of the electronic structure [\[5\]](#page-13-0). Following the GW calculation, the BSE method is employed to compute excitonic effects by incorporating electron-hole interactions, providing precise estimates of EBE through electron-hole correlation [\[3\]](#page-12-2). However, these methods are computationally demanding, making them less practical for large-scale material screening.

To tackle this challenge, we propose a machine learning-assisted approach to efficiently predict EBE. This approach takes advantage of data from first-principles calculations, such as band gaps obtained from PBE and HSE06 as presented in C2DB [\[6,](#page-13-1) [7,](#page-13-2) [8\]](#page-13-3).

Machine learning (ML) approach requires a fine balance between accuracy and computational efficiency in predicting complex quantities from simpler, readily available parameters [\[9\]](#page-13-4). By linking these simpler features to exciton binding energy estimates—which would otherwise require advanced computational methods—our approach accelerates the materials discovery process. This study highlights the potential of ML to streamline the identification of 2D materials with large excitonic effects, enabling faster screening for optoelectronic applications.

# 2. Methodology

#### 2.1. Dataset

In the context of machine learning in materials science, material databases are essential for the success of predictive models. Using a large amount of high-quality data is mandatory to achieve a robust and accurate predictions. In this study, we used C2DB database to train and evaluate our machine learning models, which comprises band gap data for around 4001 monolayers. These materials include transition metal dichalcogenide, transition metal oxides and other technologically important materials like hexagonal boron nitride  $[10]$ ,  $Mgl_2$ ,  $MgBr<sub>2</sub>$  [\[11\]](#page-13-6) etc.

In our study, the data is randomly partitioned into two sets: a training dataset and a test dataset. The partitioning allocates 60% of the data for training and 40% for testing, a ratio deemed optimal for achieving accurate machine learning predictions[\[12\]](#page-13-7).

#### 2.2. Features selection

The Pearson correlation coefficient quantifies the linear relationship between variables, providing insight into how one property influences another in monolayer materials. In this study, it serves as a critical tool to evaluate the dependencies between different features, A high Pearson coefficient indicates a strong linear association, such as between PBE and HSE06 band gaps, suggesting that trends in simpler PBE calculations can predict more computationally intensive HSE06 results. Similarly, correlations between  $G_0W_0$  band gaps and other properties reflect how electronic interactions evolve between computational methods. Understanding these relationships helps optimize feature selection for predicting EBE.

The wrapper method evaluates the predictive power of features by assessing their impact on model performance. Unlike statistical filter methods, it iteratively trains a model with different feature subsets, capturing both linear and nonlinear dependencies. In this study, the wrapper method identified band gap values for PBE and HSE06 as the most significant predictors of EBE.

# 2.3. Algorithm selection

To predict the exciton binding energy, we evaluated multiple machine learning algorithms, each with distinct advantages. Neural Networks (NNs) excel at capturing complex, nonlinear relationships by adjusting weights through layers of interconnected neurons [\[13\]](#page-13-8). Random Forest (RF) and Gradient Boosting (GB) are ensemble tree-based methods [\[14\]](#page-14-0): RF combines predictions from multiple decision trees to reduce variance, while GB sequentially builds trees to minimize prediction error. Support Vector Machines (SVM) define optimal hyperplanes to separate data, useful for high-dimensional spaces [\[15\]](#page-14-1). Kernel Ridge Regression (KRR) combines ridge regularization with kernel methods to handle nonlinearity [\[16\]](#page-14-2). We used the these models as implemented in scikit-learn [\[17\]](#page-14-3) package. In the following section, we present the results of these ML models in predicting EBE.

# 3. Results and discussion

#### 3.1. Predicting Quasi-particle energies

The Random Forest regression model demonstrates strong performance in predicting  $G_0W_0$  band gaps, which correspond to quasiparticle  $(QP)$  energies. The model's effectiveness <span id="page-4-0"></span>is illustrated in Figure [1.](#page-4-0) The distribution of prediction errors for the  $G_0W_0$  band gaps, using RF algorithm, demonstrates a strong alignment with actual values from the C2DB database,



<span id="page-4-1"></span>Figure 1: Random forest-based machine learning model for predicting  $G_0W_0$  band gaps in 2D materials.



Figure 2: Distribution of prediction errors for  $G_0W_0$  band gaps using the Random Forest model, showing a peak at zero, indicating high accuracy with minimal deviation between predicted and actual values.

indicating the model's high predictive accuracy and reliability. The histogram of errors has a clear peak around zero, as shown in Figure [2,](#page-4-1) indicating that most of the predictions are very close to the actual band gap values. This means that the RF model is accurate and effectively captures the relationships in the data.

## 3.2. Exciton binding Energy

The exciton binding energy is the energy needed to separate an exciton—a bound state of an electron and a hole—into free, independent charge carriers. EBE can be estimated using the band gaps obtained from HSE06 and  $G_0W_0$  methods [\[18,](#page-14-4) [19\]](#page-14-5) as:

$$
EBE = E_g \ (G_0 W_0) - E_g \ (HSE06) \tag{1}
$$

<span id="page-5-0"></span>The EBE prediction trained using the RF algorithm is presented in Fig. [3,](#page-5-0) demonstrating that the this model effectively captures the EBE with high accuracy. The distribution of



Figure 3: Exciton Binding Energy predicted using the RF model, illustrating the relationship between machine learning predictions and C2DB values, with a focus on capturing the accuracy and reliability of excitonic effects in 2D materials.

<span id="page-6-0"></span>prediction errors for EBE, shown for the RF model in Fig. [4,](#page-6-0) exhibits a sharp peak at zero, highlighting minimal deviation between predicted and actual values and underscoring the model's precision.



Figure 4: Distribution of prediction errors for EBE for RF, with a peak at zero, indicating high accuracy with minimal deviation between predicted and actual values.

The radar plots in Figure [5](#page-7-0) illustrate the performance of five ML algorithms i.e. Gradient Boosting, Random Forest, Support Vector Regression, Kernel Ridge Regression, and Neural Networks—across training and testing sets, evaluated by mean absolute error (MAE), root mean square error (RMSE), and  $R^2$  metrics.

These metrics collectively assess each model's prediction accuracy and capacity to generalize to new data set. In both training and testing sets, the RF model demonstrates superior performance, achieving a training MAE of 0.011 and RMSE of 0.025. Its testing metrics are also impressive, with MAE of 0.021 and RMSE of 0.043, indicating strong generalization with a minimal increase in error on unseen data.  $\mathbb{R}^2$  scores of 0.994 signifies that it captures nearly all variance in the exciton binding energy as shown in Fig. [5.](#page-7-0)

<span id="page-7-0"></span>

Figure 5: Radar plots comparing the performance of different ML algorithms in predicting exciton binding energy. The area under each curve represents the MAE and RMSE, with larger areas indicating higher error. The RF model shows the smallest area, indicating the lowest prediction error.

Gradient Boosting model follows closely, with an  $R<sup>2</sup>$  of 0.981 as well in other statistical parameters as illustrated in Fig. [5.](#page-7-0) The Neural Network, KRR, and SVR algorithms relatively under-perform having  $R^2$  of around 0.95. Random Forest is particularly effective in modeling exciton binding energy due to its ensemble nature, which combines multiple decision trees to reduce over fitting and improve generalization. It captures complex, nonlinear relationships between the features and the target variable with high accuracy, as indicated by its  $R^2$  of 0.994. RF also handles feature interactions well and is robust to noise, making it suitable for datasets with moderate complexity, as demonstrated by its consistently low MAE and RMSE on both training and test sets.

Lin et al. [\[20\]](#page-14-6) used features such as the highest occupied molecular orbital (HOMO) and lowest unoccupied molecular orbital (LUMO) from the C2DB database to predict exciton binding energies in 2D materials. Their model achieved an  $R<sup>2</sup>$  value of 0.802 and a mean absolute error (MAE) of 0.214 eV with a gradient boosting regression model. Our RF-based model improves on these results by incorporating exciton-related features, achieving better  $R^2$  and MAE values.

The derived linear regression equation for EBE demonstrates its dependence on the PBE and HSE06 band gaps.

$$
EBE = 0.48 E_{PBE} + 0.01 E_{HSE06} + 0.28
$$
\n<sup>(2)</sup>

The equation indicates that PBE contributes significantly to predicting the EBE, highlighting its dominant role. In contrast, the HSE06 band gap has a minimal influence, as reflected by its small coefficient of 0.01. The constant term 0.28 accounts for the base offset in EBE values. This model provides a simple, interpretable relationship between the EBE and the electronic properties i.e. PBE and HSE06 band gap methods, enabling a straightforward estimation of EBE using cheaply available features.

#### 3.3. Bayesian Optimization

This study implements a Bayesian optimization (BO) framework to identify 2D materials with highest excitonic binding energy from the C2DB database. BO is a data-driven, efficient approach that combines surrogate modeling with iterative optimization to explore the dataset and predict materials with desired properties. The framework leverages Gaussian Process Regression (GPR) as the surrogate model, which not only predicts EBE but also estimates uncertainties, enabling a balance between exploration of uncertain regions and exploitation of high-performing candidates [\[21\]](#page-14-7).

The GPR model employs a composite kernel comprising a radial basis function, a dotproduct kernel, and a constant kernel. This kernel effectively captures complex non-linear relationships in the dataset while ensuring numerical stability during optimization. The hyperparameters of the kernel are optimized during each iteration using the L-BFGS-B algorithm to ensure accurate surrogate modeling [\[22\]](#page-14-8). This BO algorithm explores a search space of 4001 two-dimensional materials from the C2DB database.



Figure 6: A Bayesian optimization algorithm is implemented, starting with a dataset from C2DB containing 4001 monolayers. Gaussian Process Regression is used as the surrogate model, employing Expected Improvement as the acquisition function, with the dataset updated iteratively.

An important function is Expected Improvement (EI) acquisition function, which directs the search by selecting materials expected to offer the greatest improvement in EBE. The optimization workflow involves iteratively training the GPR model on available data, computing EI for all candidates, and selecting the material with the highest EI for evaluation [\[23\]](#page-15-0). The predicted EBE is then added to the training dataset, and the process repeats until convergence or a predefined number of iterations is reached. The EI used in the current study is given by:

$$
EI = (\mu - f_{\text{best}}) \cdot \Phi(Z) + \sigma \cdot \phi(Z)
$$

Where the standardized improvement  $Z$  is expressed as:

$$
Z = \frac{\mu - f_{\text{best}}}{\sigma}
$$

Here  $\mu$  is the predicted mean,  $\sigma$  is the predicted uncertainty,  $f_{\text{best}}$  is the current best EBE,  $\Phi$ and  $\phi$  are the cumulative and probability density functions of the standard normal distribution respectively. This BO-based approach is particularly advantageous for predicting EBE in 2D materials, where experimental or computational evaluations are resource-intensive. By prioritizing candidates with the highest potential, the framework reduces the number of evaluations required while ensuring that top-performing materials are identified. The results highlight Bayesian optimization as a powerful and scalable methodology for accelerating the discovery of 2D materials with desirable excitonic properties.

The table [1](#page-10-0) lists the highest predicted EBE values through BO. Additionally, our model has also predicted EBE values for monolayers that are not covered in the C2DB database.

<span id="page-10-0"></span>

Formula	<b>Space Group</b>	EBE (Predicted)	EBE (C2DB)
Li <sub>3</sub> Cl <sub>3</sub>	p4/mmm	2.67	
SrCl <sub>2</sub>	$p$ -6m2	2.63	2.63
$Y_2F_2O_2$	$p-3m1$	2.62	
CaCl <sub>2</sub>	$p-6m2$	2.61	2.60
$Mg_4Cl_8$	pmmm	2.60	
$Be2Br2Cl2$	$pm2_1$	2.60	
BaCl <sub>2</sub>	$p$ -6m2	2.60	2.58
$Li_6Cl_6$	$p-3m1$	2.60	
$Ca_2Cl_4H_8O_4$	pman	2.59	
CaCl <sub>2</sub>	$p-3m1$	2.58	2.56

Table 1: Monolayers with highest exciton binding energies

The high EBE observed in monolayers of alkaline earth metal chlorides i.e.,  $ACl<sub>2</sub>$  where A = Sr, Ca, Ba and other 2D materials containing chlorine. The atoms of chlorine have a high electron affinity, which contributes to stronger Coulombic attraction between electrons and holes. This enhances the binding energy of excitons, particularly in low-dimensional systems where dielectric screening is already reduced.

<span id="page-11-0"></span>The table [2](#page-11-0) tabulates the predicted EBE for TMDC monolayers, which are well-known for their excitonic properties. The strong excitonic effects are attributed to their direct bandgap in monolayer form, which enhances their optical absorption capabilities.

	Formula EBE (Predicted) EBE (C2DB)	
HfS <sub>2</sub>	1.15	1.29
ZrS <sub>2</sub>	1.14	1.18
HfSe <sub>2</sub>	1.14	0.95
TiS <sub>2</sub>	0.94	0.98
ZrSe <sub>2</sub>	0.89	0.90

Table 2: TMDC monolayers with highest exciton binding energies

Theoretical predictions indicate that  $MoS<sub>2</sub>$ , the most studied TMDC monolayer, exhibits a large EBE ranging from 526 meV to 1 eV [\[24\]](#page-15-1). However, the table suggests there are other candidates with EBEs exceeding that of  $MoS<sub>2</sub>$ , which remain underexplored and merit further investigation.

## 4. Conclusion

In this study, we demonstrated a machine learning-assisted approach for predicting exciton binding energies in two-dimensional materials, using band gap data from simple DFT calculations. By training and evaluating multiple ML algorithms, we found that the RF model provided the most reliable predictions, effectively bridging the gap between computational efficiency and accuracy. Our model, trained on PBE and HSE06 band gap data from the C2DB, offers a rapid and cost-effective alternative to traditional GW and BSE methods, enabling faster screening and discovery of materials with significant excitonic effects. Additionally, we implemented a Bayesian optimization framework, which further streamlined the identification of top EBE monolayers by efficiently guiding the search for promising candidates. This integration of BO with machine learning underscores the potential for data-driven approaches to revolutionize materials discovery processes.

## 5. Author contributions

A. Javed conceived the idea, developed initial concepts and performed the calculations and analysis. A. Sajid supervised the project and helped editing the manuscript.

## 6. Competing interests

The authors declare no competing interests.

# References

- <span id="page-12-0"></span>[1] S. A. Ali, B. Ahmed, et al., Room temperature polarization-resolved raman and photoluminescence in uniaxially strained layered mos2, Applied Physics Letters 125 (2024).
- <span id="page-12-1"></span>[2] D. X., W. C., P. A., Y. R., Two-dimensional transition metal dichalcogenides as atomically thin semiconductors: opportunities and challenges, Chemical Society Reviews 24 (2015) 8859–8876.
- <span id="page-12-2"></span>[3] A. Ramasubramaniam, Large excitonic effects in monolayers of molybdenum and tungsten dichalcogenides, Physical Review B 86 (2012) 115409.
- <span id="page-12-3"></span>[4] A. Javed, M. Asif, R. Ullah, Investigation of strain modulated opto-electronic properties in monolayer wx2 ( $x=$  se and s): Dft and beyond dft study, Journal of Inorganic and Organometallic Polymers and Materials (2024) 1–10.
- <span id="page-13-0"></span>[5] X. Leng, F. Jin, M. Wei, Y. Ma, Gw method and bethe–salpeter equation for calculating electronic excitations, Wiley Interdisciplinary Reviews: Computational Molecular Science 6 (2016) 532–550.
- <span id="page-13-1"></span>[6] S. Haastrup, M. Strange, M. Pandey, T. Deilmann, P. S. Schmidt, N. F. Hinsche, M. N. Gjerding, D. Torelli, P. M. Larsen, A. C. Riis-Jensen, et al., The computational 2d materials database: high-throughput modeling and discovery of atomically thin crystals, 2D Materials 5 (2018) 042002.
- <span id="page-13-2"></span>[7] M. N. Gjerding, A. Taghizadeh, A. Rasmussen, S. Ali, F. Bertoldo, T. Deilmann, N. R. Knøsgaard, M. Kruse, A. H. Larsen, S. Manti, et al., Recent progress of the computational 2d materials database (c2db), 2D Materials 8 (2021) 044002.
- <span id="page-13-3"></span>[8] A. Javed, S. A. Ali, M. Asif, R. Ullah, Structural and electronic properties of monolayers: Enhancing computational accuracy, Materials Letters 380 (2025) 137661.
- <span id="page-13-4"></span>[9] A. Sajid, K. S. Thygesen, Spin coherence times of point defects in two-dimensional materials from first principles, Physical Review B 106 (2022) 104108.
- <span id="page-13-5"></span>[10] A. Sajid, M. J. Ford, J. R. Reimers, Single-photon emitters in hexagonal boron nitride: a review of progress, Reports on Progress in Physics 83 (2020) 044501.
- <span id="page-13-6"></span>[11] S. Ali, F. A. Nilsson, S. Manti, F. Bertoldo, J. J. Mortensen, K. S. Thygesen, Highthroughput search for triplet point defects with narrow emission lines in 2d materials, ACS nano 17 (2023) 21105–21115.
- <span id="page-13-7"></span>[12] V. R. Joseph, Optimal ratio for data splitting, Statistical Analysis and Data Mining: The ASA Data Science Journal 15 (2022) 531–538.
- <span id="page-13-8"></span>[13] J. Kang, R. Schwartz, J. Flickinger, S. Beriwal, Machine learning approaches for predicting radiation therapy outcomes: a clinician's perspective, International Journal of Radiation Oncology\* Biology\* Physics 93 (2015) 1127–1135.
- <span id="page-14-0"></span>[14] S. B. Nadkarni, G. Vijay, R. C. Kamath, Comparative study of random forest and gradient boosting algorithms to predict airfoil self-noise, Engineering Proceedings 59 (2023) 24.
- <span id="page-14-1"></span>[15] S. Salcedo-Sanz, J. L. Rojo-Álvarez, M. Martínez-Ramón, G. Camps-Valls, Support vector machines in engineering: an overview, Wiley Interdisciplinary Reviews: Data Mining and Knowledge Discovery 4 (2014) 234–267.
- <span id="page-14-2"></span>[16] V. Vovk, Kernel ridge regression, in: Empirical inference: Festschrift in honor of vladimir n. vapnik, Springer, 2013, pp. 105–116.
- <span id="page-14-3"></span>[17] F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, E. Duchesnay, Scikit-learn: Machine learning in Python, Journal of Machine Learning Research 12 (2011) 2825–2830.
- <span id="page-14-4"></span>[18] X. Wang, W. Meng, Y. Yan, Electronic band structures and excitonic properties of delafossites: A gw-bse study, arXiv preprint arXiv:1706.03877 (2017).
- <span id="page-14-5"></span>[19] S. A. Tawfik, S. P. Russo, Naturally-meaningful and efficient descriptors: machine learning of material properties based on robust one-shot ab initio descriptors, Journal of Cheminformatics 14 (2022) 78.
- <span id="page-14-6"></span>[20] Z. Lin, J. Liu, S. Zhong, K. Hsiao, X. Chen, Machine-learning prediction of exciton binding energies in two-dimensional materials for photonics application (2023).
- <span id="page-14-7"></span>[21] J. Snoek, H. Larochelle, R. P. Adams, Practical bayesian optimization of machine learning algorithms, Advances in neural information processing systems 25 (2012).
- <span id="page-14-8"></span>[22] N. Di Pasquale, S. J. Davie, P. L. Popelier, Optimization algorithms in optimal predictions of atomistic properties by kriging, Journal of chemical theory and computation 12 (2016) 1499–1513.
- <span id="page-15-0"></span>[23] P. I. Frazier, Bayesian optimization, in: Recent advances in optimization and modeling of contemporary problems, Informs, 2018, pp. 255–278.
- <span id="page-15-1"></span>[24] N. Saigal, V. Sugunakar, S. Ghosh, Exciton binding energy in bulk mos2: A reassessment, Applied Physics Letters 108 (2016).