The Efficiency vs. Accuracy Trade-off: Optimizing RAG-Enhanced LLM Recommender Systems Using Multi-Head Early Exit

Huixue Zhou 1,2 , Hengrui Gu 3 , Xi Liu 1 , Kaixiong Zhou 3 , Mingfu Liang 1 , Yongkang Xiao 2 ,

Srinivas Govindan¹, Piyush Chawla¹, Jiyan Yang¹, Xiangfei Meng¹, Huayu Li¹, Buyun Zhang¹,

Liang Luo¹, Wen-Yen Chen¹, Yiping Han¹, Bo Long¹, Rui Zhang², Tianlong Chen⁴

Meta Platforms¹, University of Minnesota², NCSU³, UNC at Chapel Hill⁴

zhou1742@umn.edu, xliu1@meta.com, tianlong@cs.unc.edu

Abstract

The deployment of Large Language Models (LLMs) in recommender systems for predicting Click-Through Rates (CTR) necessitates a delicate balance between computational efficiency and predictive accuracy. This paper presents an optimization framework that combines Retrieval-Augmented Generation (RAG) with an innovative multi-head early exit architecture to concurrently enhance both aspects. By integrating Graph Convolutional Networks (GCNs) as efficient retrieval mechanisms, we are able to significantly reduce data retrieval times while maintaining high model performance. The early exit strategy employed allows for dynamic termination of model inference, utilizing real-time predictive confidence assessments across multiple heads. This not only quickens the responsiveness of LLMs but also upholds or improves their accuracy, making it ideal for real-time application scenarios. Our experiments demonstrate how this architecture effectively decreases computation time without sacrificing the accuracy needed for reliable recommendation delivery, establishing a new standard for efficient, real-time LLM deployment in commercial systems.

1 Introduction

Due to their remarkable capabilities in semantic understanding and knowledge retention, Large Language Models (LLMs) have demonstrated impressive performance across various domains, becoming essential components of various text-based recommendation systems, such as sequential recommendation (Wang et al., 2023; Harte et al., 2023; Li et al., 2023; Zheng et al., 2024) and raking (Zhao et al., 2024; Acharya et al., 2023). In light of this, numerous researchers have sought to adapt LLMs for Click-Through Rate (CTR) prediction problem (Wang and Lim, 2023; Bao et al., 2023a; Lin et al., 2024a), leveraging their text-mining capabilities to analyze textual user behaviors for more accurate preference modeling.

The performance of LLM-based CTR predictors is enhanced by Retrieval-Augmented Generation (RAG) modules (Lin et al., 2024b; Hajiaghayi et al., 2024), which integrate diverse and user-relevant texts into the input contexts. This enrichment allows LLMs to extract more accurate user features for preference prediction. However, the integration of RAG introduces significant efficiency challenges: By reasoning conditioned on the contextual input information, LLMs can extract more precise user features for preference prediction. However, while we benefit from the improved accuracy provided by RAG, it also introduces two critical efficiency bottlenecks: **1** Inference Delay: The sequential execution of retrieval and inference leads to significant delays in starting the inference process due to the additional time required for retrieval. **2** Inference Slowdown: The extended inputs introduce extra computational overhead, drastically slowing down model inference as LLMs suffer from quadratic time complexity w.r.t. input length. These bottlenecks significantly undermine the realtime responsiveness of these predictors, hindering their broader application in real-world recommendation scenarios.

To address these challenges, we propose two innovative acceleration techniques tailored to these bottlenecks, aiming to enhance the efficiency of LLM-based CTR predictors without overly compromising recommendation quality. Regarding the retrieval strategies (*Bottleneck* **①**), we introduce a lightweight yet effective retrieval scheme called GCN-Retriever. Leveraging the impressive capability of Graph Convolutional Networks (GCNs) (Kipf and Welling, 2016; Chen et al., 2020) to model structural data, we employ them as feature embedders to comprehensively capture multi-order interaction information within user-item graphs, generating precise and informative representations for subsequent reasoning. By replacing the timeconsuming LLM embedders with GCN-Retriever, we significantly reduce retrieval times, enabling our system to minimize intractable inference delays while maintaining high recommendation performance. As for inference accelerating (*Bottleneck* **2**), we introduce a multi-head early exit strategy integrated with an exit scoring mechanism tailored to the LLM-based CTR prediction task. By applying this early exit strategy, the system can terminate the inference process at intermediate layers based on the confidence level of the predictions, thereby reducing unnecessary computational overhead and accelerating response without sacrificing the accuracy of the recommendations. The contributions are summarized below:

- Enhanced LLM for CTR Prediction via RAG: Demonstrates significant improvements in accuracy by incorporating interaction data into RAG-based LLM models.
- Efficient GCN-Retriever: Introduces a simplified GCN-based retriever for recommendation, reducing data retrieval time without impacting model performance.
- Inference Time Optimization through Early Exit: Employs an early exit strategy in model training and inference to effectively enhance online efficiency.
- Novel Multi-Head Early Exit Adjustment: Introduces an innovative adjustment in the early exit strategy implemented within a multi-head architecture, maintaining accuracy while improving efficiency.

2 Related Work

2.1 Language Models for Recommendation

Building on prior research(Wu et al., 2023), the integration of language models into recommender systems often focuses on their distinct functions within the recommendation process. These roles include serving as feature extractors(Bian et al., 2022; Zheng et al., 2023; Zhang et al., 2024), where language models analyze item and user data to produce embeddings or tokens. These embeddings can be utilized by traditional recommender system models to enhance task-specific recommendations through knowledge-aware embeddings.

Furthermore, language models can function within scoring or ranking mechanisms(Wang et al., 2023; Zhu et al., 2024; Kim et al., 2024). This

approach leverages pre-trained language models to transform recommendation systems significantly. Typically, the input sequence includes task instructions, behavioral prompts, with the output generating pertinent recommendation results.

Our methodology diverges from previous practices by employing the language model primarily within the scoring functions, while using a simple traditional model, specifically a GNN, as a retriever. This model extracts similar user profiles to construct the prompts for the language model, capitalizing on its ability to comprehend and synthesize user data and interactions, thereby generating personalized recommendations.

2.2 Efficient Inference

The inference performance of LLMs is often constrained by the sequential nature of auto-regressive decoding, where the generation of each token necessitates a full network forward pass. To address the high inference latency inherent in LLMs, several strategies have been proposed: Techniques such as quantization (Fan et al., 2020; Bai et al., 2022; Tao et al., 2022), pruning (Ma et al., 2023; Sun et al., 2023; Xia et al., 2023; Frantar and Alistarh, 2023), and knowledge distillation (Liang et al., 2023; Sahu et al., 2023; Gu et al., 2024), aim to reduce the memory footprint of LLMs, thus lowering the computational demands. Early Exit Strategies allow a model to terminate the computation at intermediate layers if certain conditions are met, thereby accelerating inference and reducing computational overhead. Early exit has been explored across various machine learning domains, focusing on designing efficient early exit networks (Bae et al., 2023a; Chen et al., 2023), and refining exit rules to balance accuracy and computational efficiency(Zhou et al., 2020; Li et al., 2021; Xin et al., 2021; Bae et al., 2023b).

3 Problem Formulation

CTR prediction. We utilize LLMs for CTR prediction, treating it as a binary classification task. In particular, each data sample x_i is transformed into textual sentences x_i^{text} . Correspondingly, the binary label $y_i \in \{0, 1\}$ is converted into a pair of binary key answer words y_i^{text} in {"Yes", "No"}.

LLMs for Recommender System. The LLM then processes the input x_i^{text} and aims to generate the next token \hat{y}_i^{text} , which can be mathematically ex-

pressed as follows:

$$s_i = \text{LLM}(x_i^{\text{text}}),$$
$$\hat{p}_i = \text{Softmax}(s_i)$$
$$\hat{y}_i^{\text{text}} \sim \hat{p}_i,$$

where $s_i \in \mathbb{R}^V$ is the estimated scores, V is the vocabulary size, and \hat{y}_i^{text} is the next predicted token sampled from the probability distribution \hat{p}_i .

Following previous works (Wang and Lim, 2023; Bao et al., 2023a; Lin et al., 2024a), we apply a bidimensional softmax to the scores associated with the binary key answer words. Assuming the vocabulary indices for "Yes" and "No" are *a* and *b* The pointwise scoring formula for LLMs in CTR prediction is articulated as:

$$\hat{y}_i = \frac{\exp(s_i^a)}{\exp(s_i^a) + \exp(s_i^b)} \in (0, 1)$$

4 GCN-Retriever for Retrieval Acceleration

To prepare our model for accurate learning and prediction, we construct textual sentences, denoted as X_{text} , by integrating instructions, representative examples, and actual user input data. This process is crucial for aligning the model's understanding with the specific requirements and contexts of the tasks it needs to perform.

Consider a recommendation system designed to suggest products based on user reviews and metadata. The construction of X_{text} proceed as follows: 1) **Instruction:** Embed clear directives that guide the model on the task, such as "Predict whether the user will click on the given item." 2) **Examples:** We incorporate examples of similar users' interactions to inform the model's context, e.g., "User A rated Book X with 5 stars." 3) **Input:** Add actual real-time user interaction and query.

To tackle the challenge of time efficiency in recommendation systems, we have developed a streamlined approach using GCNs. Specifically, we implemented a simplified graph model to represent both users and items. This model leverages the structural advantages of GCNs to facilitate the rapid retrieval of similar users, thus enhancing the system's overall efficiency. The GCN-Retriever model constructs a bipartite graph where nodes correspond to users and items, and edges represent interactions between them. The model utilizes GCNs to process these structural features through multiple layers of message passing. Specifically, the embedding for a user u at the next layer k + 1 is updated by aggregating features from its neighbors in the graph, as described by the following equation:

$$e_{u}^{(k+1)} = \operatorname{AGG}\left(e_{u}^{(k)}, \{e_{i}^{(k)} : i \in N_{u}\}\right)$$

 ϵ

where e_u is the embedding of user u, N_u denotes the neighbors of u, and AGG represents the aggregation function which combines features of a node with those of its neighbors to generate new representations.

To effectively capture the multidimensional signal of users, our GCN-Retriever model employs a strategy of averaging the embeddings obtained from different layers of GCNs. This approach provides a comprehensive representation that integrates diverse aspects of user behavior and attributes captured at the various levels of graph structure. The average of user embeddings across multiple convolutional layers is described by the following equation:

$$\overline{e_u} = \frac{1}{K} \sum_{k=1}^{K} e_u^{(k)}.$$

 $\overline{e_u}$ represents the final averaged embedding for user u, K is the number of layers from which embeddings are extracted and averaged, and $e_u^{(k)}$ is the embedding of user u at layer k.

Cosine similarity is used to measure the similarity between users based on their averaged embeddings:

similarity
$$(u, v) = \frac{e_u \cdot e_v}{\|e_u\| \|e_v\|}$$

To identify the user v most similar to user u, we calculate:

$$v^* = \operatorname*{arg\,max}_{v} \operatorname{similarity}(u, v).$$

5 Dynamic Predictive Exiting for Inference Acceleration

In this section, we introduce **Dynamic Predictive Exiting** as a solution to Inference Slowdown. Motivated by (Xin et al., 2021), this mechanism leverages additional language heads to enable flexible inference termination while maintaining prediction quality. Specifically, during the forward pass through model layers, these language heads, attached to designated exit layers, decode the intermediate hidden states into next-token distributions. We design straightforward yet effective strategies to dynamically monitor the prediction confidence at different layers, using it as a real-time criterion to determine when to terminate inference and accept these intermediate distributions as final outputs.

5.1 Preliminaries

Notations. The typical architectures of LLMs comprise N transformer layers and a language head Head (\cdot) for predicting the next-word distribution. Given a sequence of tokens $\{x_1, \ldots, x_{t-1}\}$ as input, the standard decoding process for LLMs is described as below:

$$p(x_t|x_{< t}) = \operatorname{softmax}(\operatorname{Head}(h_{t-1}^{(N)}))_{x_t} \quad (1)$$

where $h_{t-1}^{(N)}$ represents the mature hidden states that have already processed by the N-th layer (i.e., the final layer) and $p(x_t|x_{< t})$ denotes the standard prediction distribution from which the next token x_t is expected to be sampled.

Early Exit. Early exit has proven to be an effective technique to interpret the evolution of predicting preferences across model layers in LLMs, even without special training process (Chuang et al., 2024; Kao et al., 2020; Schuster et al., 2022). By applying the language head to the immature hidden states of the intermediate layers, we can calculate the probability of the next token solely conditioned on $h_{t-1}^{(j)}, j \in \{0, ..., N-1\}$, without finishing the entire inference process:

$$p^{(j)}(x_t|x_{< t}) = \operatorname{softmax}(\operatorname{Head}(h_{t-1}^{(j)}))_{x_t}$$
 (2)

While effectively analyzing the layer-wise predictive trends in LLMs, it's widely acknowledged that the intermediate hidden states in LLMs exhibit an unavoidable information gap (i.e., distribution shift) compared to the final hidden states, leading to an unacceptable trade-off between efficency and response quality (Elhoushi et al., 2024; Liu et al., 2024). In the following section, we introduce additional language heads and propose a customized fine-tuning scheme for them. These fine-tuned language head can better "understand" the hidden states of earlier layers, thereby mitigating the information gap.

5.2 Optimization of Multi Heads

In prior to fine-tuning language models, we predefine a set of exit layers $\mathcal{L} \subset \{1, \ldots, N-1\}$ and mount an additional language head Head_{ℓ}, with randomly initialized parameters at each exit layer $\ell \in \mathcal{L}$. Besides decoding, another crucial function of these language heads is to approximate the inference process of subsequent layers, allowing for the acquisition of high-quality predictive distributions solely from the exited intermediate hidden states.

In our customized fine-tuning scheme, we first perform comprehensive instruction-tuning on the entire vanilla model. This step ensures the model is optimally tailored to the specific requirements of the target application. Given a textual input x and its ground truth token y, we use the cross-entropy loss as the training objective:

$$L_{CE} = -\log p(y|x)$$

After fine-tuning the model, we freeze its existing parameters and integrate the multi-early-exit heads (i.e., additional language heads) at different exit layers. Our empirical results show that fine-tuning only these heads improves training stability and leads to a better convergence rate. Specifically, for a given textual input x and its ground truth token y, the layer-specific training loss for layer ℓ is defined as:

$$L_{\text{exit}}^{(\ell)} = -\log p^{(\ell)}(y|x),$$

where $p^{(\ell)}(y|x)$ is the probability that Head_{ℓ} assigns to the correct ground truth token y.

In the training of multi-head architectures, it is beneficial to adopt a learning rate strategy that varies across the depth of the network. Specifically, shallower layers' heads are assigned higher learning rates compared to deeper layers. This strategy recognizes that shallower layers capture more generic features which are crucial early in the training process and may require more aggressive updates. Conversely, deeper layers, which adapt to more specific features, benefit from finer, more gradual updates. The learning rate for each head n, located at depth d_n in the architecture, is defined as follows:

$$\lambda_n = \lambda_0 \cdot e^{-\beta \cdot d_\ell},$$

where:

- λ_0 is the base learning rate.
- β is a decay constant that determines the rate of reduction in learning rate with increasing depth.
- *d*_ℓ is the depth of the head, with shallower heads having a smaller *d*_ℓ.

5.3 Workflow of Dynamic Predictive Exiting

After obtaining the set of fine-tuned language heads $\{\text{Head}_{\ell} | \ell \in \mathcal{L}\}\$ mounted at these specified exit layers ℓ , LLMs can decode intermediate hidden states in real-time to generate predictive distributions in advance. At this point, our proposed **Dynamic Predictive Exiting** mechanism can be applied to the target model for inference acceleration. The detailed workflow of this mechanism involves two steps as follows:

1. Dynamic real-time decoding. When the forward computation of LLMs reaches the ℓ -th decoding layer, we perform real-time decoding on the hidden states h_{ℓ} output from that layer to obtain the immature predictive distribution P_{ℓ} , which reflects the prediction tendencies of the LLMs at the current layer.

2. Predictive exiting strategies. Each time we obtain the immature predictive distribution P_{ℓ} at an exiting layer ℓ , we need a criterion to determine whether to accept this distribution as the final prediction distribution and terminate the inference early. To this end, we propose the strategy for LLM earlyexit for CTR. This strategy are inspired by an interesting finding (Chuang et al., 2024) that LLMs progressively refine their hidden states across decoding layers. For some simple prediction steps, the hidden states at intermediate layers have already encoded sufficient information to predict the next token and remain relatively stable throughout the rest of the inference process. The goal of these strategies is to avoid unnecessary computations on such steps, thereby reducing the time spent on "over-thinking". We provide a detailed description of the strategy below, namely the Probability-Based Method for CTR.

Probability-Based Method for CTR: Define $k_{a,b}$ as the label receiving of position a and b probability at layer ℓ , and $P_{\ell}^{a,b}$ denotes the probability distribution at the exit of layer ℓ . The measure of disagreement between the predictions at layers ℓ and $\ell - 1$ is quantified by the function:

$$D(P_{\ell}^{a,b}, P_{\ell'}^{a,b}) = |P_m(k_{a,b}) - P_{\ell'}(k_{a,b})|,$$

where this discrepancy is represented by $D_{\ell\ell'} \in \mathbb{R}$ and the distance between consecutive layers ℓ and $\ell - 1$ is represented as D_{ℓ} . A lower value of D_{ℓ} signifies a greater consistency between the distributions P_{ℓ} and $P_{\ell-1}$.

To systematically assess consistency across multiple layers, we calculate the mean discrepancy over a defined window of m layers as:

$$\overline{D_{\ell}^m} = \frac{1}{m} \sum_{i=\ell}^{\ell+m} D_i,$$

If the difference between the discrepancy at layer ℓ and the average discrepancy over the last ℓ layers from $\ell - 1$ back to $\ell - l$, $|D_{\ell} - \overline{D_{\ell-1}^m}|$, falls below a predefined threshold τ , it indicates that the current layer's output does not significantly deviate from the trend established by previous layers, thus allowing the process to terminate early.

6 Experiments

Dataset. We conduct experiments on three realworld datasets: BookCrossing(Ziegler et al., 2005), Amazon Beauty, and Amazon video games(Ni et al., 2019). We present the processed dataset statistics in Table 1. **BookCrossing:** The BookCrossing dataset comprises user ratings and detailed textual descriptions of books. In our analysis, we randomly choose one item that each user has interacted with as the target for our predictions. Additionally, we select up to 15 items that the user has previously interacted with to represent their historical interactions. User ratings are converted to a binary format using a threshold of 5, where ratings of 5 or higher are categorized as positive. Amazon dataset: The Amazon dataset comprises user purchase actions and rating information sourced from the Amazon platform. For our experiments, we selected two domains with a substantial number of overlapping users: Beauty 2018 and Video Games 2018. To prepare the dataset for the recommender system experiments, we initially processed the original data by organizing past interactions chronologically for each user. We then filtered out samples that had fewer than three past interactions to ensure sufficient data quality and reliability in the training set. For the construction of recommendation tuning samples, we retained up to 15 interactions that occurred prior to the target item. We further binarize the ratings according to a threshold of 3. The refined dataset was subsequently divided into training, validation, and testing sets, maintaining a ratio of 8:1:1.

Baseline Methods. Traditional CTR models are typically divided into two main categories: feature interaction models and user behavior models. For our study, we selected DeepFM(Guo et al., 2017) as representative feature interaction models. Additionally, we chose GRU4Rec(Hidasi et al., 2016),



Figure 1: The process of GCN-earlyexit: Section 1 GCN-Retriever: Constructs a GCN to generate user embeddings for identifying similar users; Section 2 Construct the Prompt with the Retrieved information: Forms LLM input by combining interaction data of the query user with similar users' data; Section 3 Multi-head Early Exit: Implements an early exit strategy in the LLM by designating potential exit layers and setting probability-based termination criteria.

Table 1: Summary of Datasets.

Dataset	Users	Items	Samples
BookCrossing	278,858	271,375	17,714
Beauty	324,037	32,892	6,525
Video Games	41,996	17,303	294,135

DIN(Zhou et al., 2017), and SIM(Zhao et al., 2023) as representative user behavior models. We also evaluate the TALLRec(Bao et al., 2023b) as a LLM-based CTR model.

Implementation Details. For our experiments, we used Vicuna-7B, a model released by FastChat, as the base language model. We employed fewshot training methods (using less than 10% of the training data) to fine-tune the model for our specific CTR task, while using the entire training dataset for the traditional models. The example number were setting as four in GCN-earlyexit. To reduce the time cost by calculating the exit scores, we designated the layer (5,10,15, 20, 25, 30) for Beauty and Vedio Games dataset, the layer (5,10,15, 20) for BookCrossing. Notably, the final early exit layer was set at the highest designated layer for BookCrossing to ensure maximal processing.

Measurement. Each configuration's performance was assessed using the Area Under the Curve (AUC) metric for accuracy. The retrieval times, indicating computational demand, were nor-

malized to the baseline (1x) set by the LLM retrievor. Inference speed was measured by the requests per second (RPS) per NVIDIA A100 GPU.

Q1: Does Our Method Outperform traditional recommendation Models? The analysis of the results in Table 2 allows us to make several critical observations. Our method, as evidenced by the data, outperforms both traditional recommendation models and the LLM based based methods, with an average improvements of 4.72 for BookCrossing, 27.16 for Beauty, and 16.71 for Video Games in AUC. This performance enhancement substantiates the efficacy of our specialized framework for tuning LLMs in recommendation settings. Compared to traditional methods, the LLM-based models demonstrate enhanced capability in CTR predictions based on past interactions, particularly for text-rich recommendation datasets such as BookCrossing and Amazon reviews. These datasets predominantly contain item information such as titles, publication years, and prices. In comparison to existing LLM-based methods, such as TallRec, our approach incorporates similar users' interactions, which significantly enhances performance by providing a more comprehensive view of user preferences, thereby outperforming current user-only LLM frameworks for CTR.

Q2: Is a GCN-Retriever More Effective and Accurate Than LLM Retriever Methods? As shown in our comparative analysis (Figure 2),

Category	Model	BookCrossing	Beauty	Video Games
Metric		AUC	AUC	AUC
Full-shot	DeepFM	71.15	70.05	77.25
Full-shot	DIN	71.17	69.02	77.03
Full-shot	SIM	68.10	61.11	74.75
Full-shot	GRU4Rec	60.75	70.04	63.20
Few-shot	Tallrec	70.74	90.37	81.41
Few-shot	LLM-retriever	69.05	89.65	83.15
Few-shot	GCN-retriever	72.51	94.72	93.46
Few-shot	GCN-earlyexit	73.28	96.37	97.19

Table 2: Performance Comparison of Sequential Recommendation Models: Conventional Baselines, LLM Baseline, and Our Enhancements with GCN-Retriever and GCN-Early Exit.

GCN-retriever demonstrate significantly faster retrieval speeds compared to LLM-based retriever across all evaluated datasets, including BookCrossing, ml-1m, and Amazon-Review-Beauty. Our results further indicate that GCN-retriever consistently outperform LLM-based retrievers in terms of accuracy across all tested datasets. For example, on the BookCrossing dataset, the GCN retriever achieves an AUC of 72.51 without early exit. In contrast, the LLM retriever achieves a lower AUC of 69.05 without early exit, underscoring the superior capability of the GCN-Retriever in extracting relevant features for recommendation tasks.

LLM-based methods typically require the construction of detailed prompts from each user's past interactions to generate user embeddings. This process, while detailed, introduces significant computational overhead, particularly for large-scale datasets. The need to generate extensive prompts for each user interaction can severely limit the scalability of LLM retrievers. In contrast, GCNretrievers adopt a more direct and efficient approach to explore user-item interactions. By inherently encoding relationships within the interaction graph, GCNs eliminate the necessity for extensive textual prompts, thereby significantly reducing retrieval times. The streamlined process not only enhances computational efficiency but also ensures that no valuable interaction data is truncated, as is often the case with LLMs due to input length constraints.

Q3: Is Averaging GCN Layer Embeddings More Effective Than Using the Final Layer Alone? Our analysis indicates that the efficacy of GCN-retrievers is influenced by the choice of embedding layer (Table 3). Across various It is evi-



Figure 2: Speedup Comparison between LLM and GCN by Dataset.

dent that using averaged embeddings from multiple layers results in a more robust representation. This suggests that embeddings averaged across multiple layers provide a richer, more generalized representation that captures a broader spectrum of user-item interaction patterns.

Dataset	Retrieval Layer	AUC	
BookCrossing	Average Last Layer	72.51 69.45	
Beauty	Average Last Layer	94.72 93.55	
Video Games	Average Last Layer	89.77 85.63	

Table 3: AUC Scores by Dataset and Retrieval Layer.

Q4: Is Retrieval Mechanisms More Efficient When Combined with Early Exit? Table 4 indicated that combining retrieval mechanisms with early exit strategies substantially increases efficiency, as evidenced by improved RPS across different datasets. For example, in the Video Games dataset, the RPS increased from 3.828 to 4.570 with the integration of early exit, confirming that this strategy enhances system responsiveness and computational speed effectively.

Q5: Is the Accuracy Maintained When Incorporating Early Exit? The examination of the experimental data across different datasets reveals that the incorporation of early exit strategies alongside retrieval mechanisms either maintains or enhances the accuracy of the systems. Notably, in the Beauty dataset, the AUC improves from 94.72 to 96.37 with the introduction of early exit.

7 Conclusion

With the increasing sophistication of LLMs, the research community is recognizing their potential to revolutionize recommendation systems (Bao et al., 2023b). In this work, we explored the integration of advanced retrieval mechanisms and early exit strategies with LLMs to enhance both the efficiency and accuracy of recommendations. Our findings indicate that by incorporating GCNs as retrieval mechanisms and leveraging multi-head early exit architectures, we can significantly reduce computation time while maintaining or improving the accuracy of the system. This optimized approach not only accelerates the responsiveness of LLMs but also upholds their decision-making quality, making them highly suitable for real-time application scenarios in commercial systems.

8 Limitation

The effectiveness of our approach is constrained by the necessity for textual descriptions in the recommendation data, as it relies heavily on processing item titles. This limitation restricts its applicability to datasets with substantial textual metadata, potentially excluding a broad array of recommendation environments where such data is sparse.

References

- Arkadeep Acharya, Brijraj Singh, and Naoyuki Onoe. 2023. Llm based generation of item-description for recommendation system. In *Proceedings of the 17th* ACM Conference on Recommender Systems, pages 1204–1207.
- Sangmin Bae, Jongwoo Ko, Hwanjun Song, and Se-Young Yun. 2023a. Fast and robust early-

Table 4: Ablation Study.

Dataset	Retrie -ver	Early- Exit	AUC- (RPS)
BookCrossing	w/o	w/o	70.74 (15.77)
	w/	w/o	72.51 (4.66)
	w/o	w/	53.17 (17.85)
	w/	w/	73.28 (5.59)
Beauty	w/o	w/o	90.37 (15.09)
	w/	w/o	94.72 (4.78)
	w/o	w/	92.56 (20.32)
	w/	w/	96.37 (4.96)
Video Games	w/o	w/o	81.41 (8.91)
	w/	w/o	89.77 (3.83)
	w/o	w/	82.32 (7.89)
	w/	w/	97.19 (4.57)

Note: Four samples were retrieved for each dataset in GCNretriever and GCN-earlyexit.

exiting framework for autoregressive language models with synchronized parallel decoding. *Preprint*, arXiv:2310.05424.

- Sangmin Bae, Jongwoo Ko, Hwanjun Song, and Se-Young Yun. 2023b. Fast and robust early-exiting framework for autoregressive language models with synchronized parallel decoding. In Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing, pages 5910–5924, Singapore. Association for Computational Linguistics.
- H. Bai, L. Hou, L. Shang, X. Jiang, I. King, and M. R. Lyu. 2022. Towards efficient post-training quantization of pre-trained language models. In *Advances in Neural Information Processing Systems*, volume 35, pages 1405–1418.
- Keqin Bao, Jizhi Zhang, Yang Zhang, Wenjie Wang, Fuli Feng, and Xiangnan He. 2023a. Tallrec: An effective and efficient tuning framework to align large language model with recommendation. *arXiv* preprint arXiv:2305.00447.
- Keqin Bao, Jizhi Zhang, Yang Zhang, Wenjie Wang, Fuli Feng, and Xiangnan He. 2023b. Tallrec: An effective and efficient tuning framework to align large language model with recommendation. In Proceedings of the 17th ACM Conference on Recommender Systems, volume 33 of RecSys '23, page 1007–1014. ACM.
- Shuqing Bian, Wayne Xin Zhao, Jinpeng Wang, and Ji-Rong Wen. 2022. A relevant and diverse retrievalenhanced data augmentation framework for sequential recommendation. In *Proceedings of the 31st ACM International Conference on Information & Knowledge Management*, CIKM '22, page 2923–2932, New York, NY, USA. Association for Computing Machinery.

- Ming Chen, Zhewei Wei, Zengfeng Huang, Bolin Ding, and Yaliang Li. 2020. Simple and deep graph convolutional networks. In *International conference on machine learning*, pages 1725–1735. PMLR.
- Yanxi Chen, Xuchen Pan, Yaliang Li, Bolin Ding, and Jingren Zhou. 2023. Ee-llm: Large-scale training and inference of early-exit large language models with 3d parallelism. *Preprint*, arXiv:2312.04916.
- Yung-Sung Chuang, Yujia Xie, Hongyin Luo, Yoon Kim, James Glass, and Pengcheng He. 2024. Dola: Decoding by contrasting layers improves factuality in large language models. *Preprint*, arXiv:2309.03883.
- Mostafa Elhoushi, Akshat Shrivastava, Diana Liskovich, Basil Hosmer, Bram Wasti, Liangzhen Lai, Anas Mahmoud, Bilge Acun, Saurabh Agarwal, Ahmed Roman, et al. 2024. Layer skip: Enabling early exit inference and self-speculative decoding. *arXiv* preprint arXiv:2404.16710.
- A. Fan, P. Stock, B. Graham, E. Grave, R. Gribonval, H. Jegou, and A. Joulin. 2020. Training with quantization noise for extreme model compression. arXiv preprint arXiv:2004.07320.
- Elias Frantar and Dan Alistarh. 2023. Sparsegpt: Massive language models can be accurately pruned in one-shot. *Preprint*, arXiv:2301.00774.
- Yuxian Gu, Li Dong, Furu Wei, and Minlie Huang. 2024. Minillm: Knowledge distillation of large language models. In *The Twelfth International Conference on Learning Representations*.
- Huifeng Guo, Ruiming Tang, Yunming Ye, Zhenguo Li, and Xiuqiang He. 2017. Deepfm: A factorizationmachine based neural network for ctr prediction. *Preprint*, arXiv:1703.04247.
- MohammadTaghi Hajiaghayi, Sébastien Lahaie, Keivan Rezaei, and Suho Shin. 2024. Ad auctions for llms via retrieval augmented generation. *Preprint*, arXiv:2406.09459.
- Jesse Harte, Wouter Zorgdrager, Panos Louridas, Asterios Katsifodimos, Dietmar Jannach, and Marios Fragkoulis. 2023. Leveraging large language models for sequential recommendation. In *Proceedings of the 17th ACM Conference on Recommender Systems*, pages 1096–1102.
- Balázs Hidasi, Alexandros Karatzoglou, Linas Baltrunas, and Domonkos Tikk. 2016. Session-based recommendations with recurrent neural networks. *Preprint*, arXiv:1511.06939.
- Wei-Tsung Kao, Tsung-Han Wu, Po-Han Chi, Chun-Cheng Hsieh, and Hung-Yi Lee. 2020. Bert's output layer recognizes all hidden layers? some intriguing phenomena and a simple way to boost bert. *arXiv preprint arXiv:2001.09309*.

- Sein Kim, Hongseok Kang, Seungyoon Choi, Donghyun Kim, Minchul Yang, and Chanyoung Park. 2024. Large language models meet collaborative filtering: An efficient all-round llm-based recommender system. In Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining, KDD '24, page 1395–1406, New York, NY, USA. Association for Computing Machinery.
- Thomas N Kipf and Max Welling. 2016. Semisupervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*.
- Lei Li, Yongfeng Zhang, and Li Chen. 2023. Prompt distillation for efficient llm-based recommendation. In *Proceedings of the 32nd ACM International Conference on Information and Knowledge Management*, pages 1348–1357.
- X. Li, Y. Shao, T. Sun, H. Yan, X. Qiu, and X. Huang. 2021. Accelerating bert inference for sequence labeling via early-exit. arXiv preprint arXiv:2105.13878.
- Chen Liang, Simiao Zuo, Qingru Zhang, Pengcheng He, Weizhu Chen, and Tuo Zhao. 2023. Less is more: Task-aware layer-wise distillation for language model compression. In *International Conference on Machine Learning*, pages 20852–20867. PMLR.
- J. Lin, R. Shan, C. Zhu, K. Du, B. Chen, S. Quan, R. Tang, Y. Yu, and W. Zhang. 2024a. Rella: Retrieval-enhanced large language models for lifelong sequential behavior comprehension in recommendation. In *Proceedings of the ACM on Web Conference 2024*, pages 3497–3508.
- Jianghao Lin, Rong Shan, Chenxu Zhu, Kounianhua Du, Bo Chen, Shigang Quan, Ruiming Tang, Yong Yu, and Weinan Zhang. 2024b. Rella: Retrievalenhanced large language models for lifelong sequential behavior comprehension in recommendation. In *Proceedings of the ACM Web Conference 2024*, volume 11 of *WWW '24*, page 3497–3508. ACM.
- Fangcheng Liu, Yehui Tang, Zhenhua Liu, Yunsheng Ni, Kai Han, and Yunhe Wang. 2024. Kangaroo: Lossless self-speculative decoding via double early exiting. *arXiv preprint arXiv:2404.18911*.
- Xinyin Ma, Gongfan Fang, and Xinchao Wang. 2023. Llm-pruner: On the structural pruning of large language models. *Advances in neural information processing systems*, 36:21702–21720.
- Jianmo Ni, Jiacheng Li, and Julian McAuley. 2019. Justifying recommendations using distantly-labeled reviews and fine-grained aspects. In Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP), pages 188–197, Hong Kong, China. Association for Computational Linguistics.
- Gaurav Sahu, Olga Vechtomova, Dzmitry Bahdanau, and Issam H. Laradji. 2023. Promptmix: A class

boundary augmentation method for large language model distillation. *Preprint*, arXiv:2310.14192.

- Tal Schuster, Adam Fisch, Jai Gupta, Mostafa Dehghani, Dara Bahri, Vinh Tran, Yi Tay, and Donald Metzler. 2022. Confident adaptive language modeling. *Advances in Neural Information Processing Systems*, 35:17456–17472.
- Mingjie Sun, Zhuang Liu, Anna Bair, and J Zico Kolter. 2023. A simple and effective pruning approach for large language models. *arXiv preprint arXiv:2306.11695*.
- C. Tao, L. Hou, W. Zhang, L. Shang, X. Jiang, Q. Liu, and N. Wong. 2022. Compression of generative pre-trained language models via quantization. *arXiv preprint arXiv:2203.10705*.
- Dong Wang, Kavé Salamatian, Yunqing Xia, Weiwei Deng, and Qi Zhang. 2023. Bert4ctr: An efficient framework to combine pre-trained language model with non-textual features for ctr prediction. In *Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, KDD '23, page 5039–5050, New York, NY, USA. Association for Computing Machinery.
- Lei Wang and Ee-Peng Lim. 2023. Zero-shot next-item recommendation using large pretrained language models. *arXiv preprint arXiv:2304.03153*.
- Likang Wu, Zhi Zheng, Zhaopeng Qiu, Hao Wang, Hongchao Gu, Tingjia Shen, Chuan Qin, Chen Zhu, Hengshu Zhu, Qi Liu, Hui Xiong, and Enhong Chen. 2023. A survey on large language models for recommendation. *Preprint*, arXiv:2305.19860.
- Mengzhou Xia, Tianyu Gao, Zhiyuan Zeng, and Danqi Chen. 2023. Sheared Ilama: Accelerating language model pre-training via structured pruning. *arXiv preprint arXiv:2310.06694*.
- J. Xin, R. Tang, Y. Yu, and J. Lin. 2021. Berxit: Early exiting for bert with better fine-tuning and extension to regression. In *Proceedings of the 16th conference* of the European chapter of the association for computational linguistics: Main Volume, pages 91–104.
- An Zhang, Yuxin Chen, Leheng Sheng, Xiang Wang, and Tat-Seng Chua. 2024. On generative agents in recommendation. *Preprint*, arXiv:2310.10108.
- Kesen Zhao, Shuchang Liu, Qingpeng Cai, Xiangyu Zhao, Ziru Liu, Dong Zheng, Peng Jiang, and Kun Gai. 2023. Kuaisim: A comprehensive simulator for recommender systems. *Preprint*, arXiv:2309.12645.
- Yuyue Zhao, Jiancan Wu, Xiang Wang, Wei Tang, Dingxian Wang, and Maarten de Rijke. 2024. Let me do it for you: Towards llm empowered recommendation via tool learning. In Proceedings of the 47th International ACM SIGIR Conference on Research and Development in Information Retrieval, pages 1796–1806.

- Zhi Zheng, Wenshuo Chao, Zhaopeng Qiu, Hengshu Zhu, and Hui Xiong. 2024. Harnessing large language models for text-rich sequential recommendation. In *Proceedings of the ACM on Web Conference* 2024, pages 3207–3216.
- Zhi Zheng, Zhaopeng Qiu, Xiao Hu, Likang Wu, Hengshu Zhu, and Hui Xiong. 2023. Generative job recommendations with large language model. arXiv preprint arXiv:2307.02157.
- Guorui Zhou, Chengru Song, Xiaoqiang Zhu, Ying Fan, Han Zhu, Xiao Ma, Yanghui Yan, Junqi Jin, Han Li, and Kun Gai. 2017. Deep interest network for clickthrough rate prediction. *Preprint*, arXiv:1706.06978.
- Wangchunshu Zhou, Canwen Xu, Tao Ge, Julian McAuley, Ke Xu, and Furu Wei. 2020. Bert loses patience: Fast and robust inference with early exit. In *Advances in Neural Information Processing Systems*, volume 33, pages 18330–18341.
- Yaochen Zhu, Liang Wu, Qi Guo, Liangjie Hong, and Jundong Li. 2024. Collaborative large language model for recommender systems. In *Proceedings* of the ACM Web Conference 2024, volume 20 of WWW '24, page 3162–3172. ACM.
- Cai-Nicolas Ziegler, Sean M. McNee, Joseph A. Konstan, and Georg Lausen. 2005. Improving recommendation lists through topic diversification. In Proceedings of the 14th International Conference on World Wide Web, WWW '05, page 22–32, New York, NY, USA. Association for Computing Machinery.

A Appendix



Figure 3: AUC and RPS by Threshold.



Figure 4: AUC and RPS by Windows.



Figure 5: AUC and RPS by retrieval examples.