Prepending or Cross-Attention for Speech-to-Text? An Empirical Comparison

Tsz Kin Lam^{1†}, Marco Gaido^{2†}, Sara Papi², Luisa Bentivogli², Barry Haddow¹

¹School of Informatics, University of Edinburgh

²Fondazione Bruno Kessler {tlam, bhaddow}@ed.ac.uk {mgaido, spapi, bentivo}@fbk.eu

Abstract

Following the remarkable success of Large Language Models (LLMs) in NLP tasks, there is increasing interest in extending their capabilities to speech-the most common form in communication. To integrate speech into LLMs, one promising approach is dense feature prepending (DFP) which prepends the projected speech representations to the textual representations, allowing end-to-end training with the speech encoder. However, DFP typically requires connecting a text decoder to a speech encoder. This raises questions about the importance of having a sophisticated speech encoder for DFP, and how its performance compares with a standard encoder-decoder (i.e. cross-attention) architecture. In order to perform a controlled architectural comparison, we train all models from scratch, rather than using large pretrained models, and use comparable data and parameter settings, testing speech-to-text recognition (ASR) and translation (ST) on MuST-C v1.0 and CoVoST2 datasets. We study the influence of a speech encoder in DFP. More importantly, we compare DFP and cross-attention under a variety of configurations, such as CTC compression, sequence-level knowledge distillation, generation speed and GPU memory footprint on monolingual, bilingual and multilingual models. Despite the prevalence of DFP over cross-attention, our overall results do not indicate a clear advantage of DFP.

1 Introduction

As the NLP community has witnessed the emergence of Large Language Models (LLMs) and their remarkable performance in tackling NLP tasks (Radford et al., 2019; Touvron et al., 2023; Jiang et al., 2023; Team et al., 2024), there is increasing interest in extending their capabilities to other modalities, such as audio (Latif et al., 2023; Chu et al., 2023; Huang et al., 2024b) and images (Radford et al., 2021; Team, 2024), to broaden their applicability. One of the most natural extensions of LLMs is represented by injecting them with speech – the most common form through which humans express their language (Munteanu et al., 2013) – to exploit the LLM linguistic fluency and skills to tackle speech-to-text (S2T) tasks, such as automatic speech recognition (ASR) and S2T translation (ST).

This goal has been predominantly pursued by dense feature prepending (DFP) which adapts the embedded speech representations to the input feature space of an LLM via a modality adapter (Wu et al., 2023; Pan et al., 2023; Wang et al., 2023) and prepends them to a textual prompt describing the tasks to be performed. Existing works on DFP mainly include a speech encoder or Speech Foundation Model (SFM) to extract the speech representations (Gaido et al., 2024), such that the speech encoder or SFM, modality adapter and low-rank adapters of the LLM could be trained in an end-toend fashion (Chen et al., 2024a; Hu et al., 2024). An alternative approach that had been initially neglected but is receiving increasing attention is the direct prepending of speech to text embeddings without a speech encoder, i.e., decoder-only S2T models. Works on these models have shown the need to relax the causal attention masking typical of autoregressive decoders for the speech features so that they can freely look at each other without being constrained to focus only on previous elements (Wu et al., 2023; Gupta et al., 2024).

We refer to the DFP solution based on a speech encoder or SFM as *decoder-prepend* which, in contrast to decoder-only, could be considered as an encoder-decoder model and, in this context, the effect of causality property¹ via causal masking has not been thoroughly investigated. More

[†]These authors contributed equally to this work

¹It refers to prohibiting a token from accessing successive tokens in the sequence, both at training and inference time, and is typically achieved through a diagonal masking matrix in the self-attention computation of Transformer decoders.

importantly, on the basis of the analogy with encoder-decoder models, its performance over cross-attention in the traditional encoder-decoder architecture (Ao et al., 2021; Radford et al., 2023; Barrault et al., 2023) has been recently contested (Chen et al., 2024c; Żelasko et al., 2024). On the other hand, Gupta et al. (2024) has shown that DFP without a speech encoder, i.e., decoder-only, could be on par or even suppress cross-attention based encoder-decoder model on ASR task.

We note that a thorough comparison of these architectural choices is missing, so to fill this gap, we carry out an extensive comparison of crossattention and DFP, including decoder-prepend and decoder-only, by training from scratch on models with size appropriate to the two publicly available datasets: MuST-C v1.0 (Di Gangi et al., 2019a) and CoVoST2 (Wang et al., 2021). Our comparison extends to commonly used S2T techniques, such as CTC compression (Liu et al., 2020; Gaido et al., 2021) for acoustic sequence length reduction and sequence-level knowledge distillation (seqKD) (Kim and Rush, 2016). Despite their usefulness, their effectiveness on cross-attention and DFP under comparable conditions has not been studied. Our experiments use controlled data conditions to ensure a fair comparison of the methods and cover monolingual, bilingual and multilingual settings, as well as multiple datasets and tasks, leading to the following findings, which we believe can inform future research on integrating dense speech features into LLM:

- Overall, there is no clear indication that DFP is strictly better in quality than cross-attention on either ASR or ST. Cross-attention is more efficient in terms of generation speed and GPU memory footprint.
- Given the same speech encoder, DFP leverages CTC compression better than crossattention in both ASR and ST results.
- Given similar model size, DFP using a speech encoder presents stronger results than decoderonly over a variety of settings, including ASR, ST, generation speed and GPU memory footprint.
- The inclusion of a speech encoder affects the causality behaviour of DFP models. Applying causal masking on the speech inputs hurts both the ASR and ST performances of

decoder-only. In contrast, DFP with a speech encoder slightly benefits from masking.

2 Relevant Work for S2T

2.1 (Cross-) Attention-based encoder-decoder

The cross-attention based encoder-decoder has been one of the major research directions for S2T (Chan et al., 2015; Bérard et al., 2016; Weiss et al., 2017; Bansal et al., 2017; Fang et al., 2022; Tsiamas et al., 2024). In addition to its end-to-end (E2E) properties, e.g., simpler pipeline over the traditional methods and E2E optimisation, crossattention allows full attention on the sequences, making it more attractive than CTC (Graves et al., 2006) and Transducer in learning sequences of switching word order, such as machine translation (MT) (Sperber and Paulik, 2020; Li et al., 2022).

2.2 DFP: modelling S2T with decoder-only language models

With the tremendous success of decoder-only language models (LM) for modelling text, there have been explorations of using them for modelling S2T, such that the speech (source) embeddings are passed to the decoder via prepending to the target text embeddings rather than using cross-attention. However, unlike text modelling, not all DFP methods for S2T are decoder-only.

decoder-only S2T. We refer to decoder-only S2T as a model that could have a length adapter for the speech inputs, but not a speech encoder, before prepending. These works include Wu et al. (2023) that is trained on in-house ST data and Gupta et al. (2024) for ASR. In contrast, our decoder-only models are all trained on publicly available data and evaluated over a wide range of settings.

decoder-prepend S2T. When the projected speech embeddings are fed directly from a speech encoder or SFM, we call the model decoder-prepend rather tha decoder-only to highlight its reliance on a speech encoder. There have been more works on this line, including ASR (Lakomkin et al., 2024; Hono et al., 2024; Fathullah et al., 2024; Tsunoo et al., 2024, 2023), ST (Huang et al., 2024a; Chen et al., 2024a) and multi-tasks (Chen et al., 2024c; Żelasko et al., 2024; Chen et al., 2024b). Despite their valuable comparisons, their experiments are based on large pretrained models and lack transparency and comparability. In contrast, we remove such dependency, so that the

comparison between cross-attention and prepending is clearer. In addition, we evaluate these models over a more comprehensive setting.

3 Methods

3.1 Encoder-Decoder with Cross Attention

Transformer-based architectures (Vaswani, 2017) are encoder-decoder sequence-to-sequence models, where the encoder maps the input sequence $\mathbf{X} = [x_1, ..., x_n]$ into an internal representation or *encoder output* (Figure 1a), which are then processed by the decoder to generate the output sequence $\mathbf{Y} = [y_1, ..., y_m]$. Both encoder and decoder are composed of a stack of Transformer-based layers that exploit dot-product *attention A* (Chan et al., 2016) as the core mechanism, which is formulated as:

$$A(Q, K, V) = softmax\left(\frac{QK^T}{\sqrt{d_k}}\right)V$$

where Q is the query matrix, K is the key matrix, V is the value matrix, and d_k is the dimension of K. In the encoder, the Q, K, and V matrices are all obtained from the input sequence \mathbf{X} , and A is called *self-attention* (A_s) . In the decoder, apart from the self-attention, there is another attention mechanism called *cross-attention* (A_c) that links the encoder with the decoder representations. In this case, the Q matrix is obtained from the previous decoder layer (or from the previously generated output \mathbf{Y} , in the case of the first decoder layer) while K and V from the encoder output. The resulting output of the encoder-decoder model can be expressed as:

$$Output = EncDec(A_s(\mathbf{X}), A_c(\mathbf{X}, \mathbf{Y}))$$

In the context of speech processing, the input sequence \mathbf{X} is an audio segment that is usually downsampled by a factor of 4 with a stack of Convolutional layers before feeding it to the stack of encoder layers (Bérard et al., 2018; Di Gangi et al., 2019b). The downsampling serves to map the input representation into a shorter sequence suitable for processing, as audio is about 10 times longer than the corresponding text sequence.

3.2 Decoder-only and Decoder-prepend

In the decoder-only architecture (Brown, 2020) for speech-to-text processing (Chen et al., 2023), the input audio sequence X is not processed by an encoder but its downsampled representation is

directly fed into the decoder after being concatenated² with the previously emitted tokens \mathbf{Y} (Figure 1b). The output of the decoder-only model can be expressed as:

$$Output = DecOnly(A_s(concat(\mathbf{X}, \mathbf{Y}))) \quad (1)$$

In this case, the cross-attention is dropped and selfattention is applied to both the input audio sequence \mathbf{X} and the previous tokens \mathbf{Y} . A variant of the decoder-only architecture is the decoder-prepend (Figure 1c), which exploits the representation obtained from a speech encoder, as in the encoderdecoder models equipped with cross-attention, but processes it as in the decoder-only model, i.e., by concatenating the encoder output with previous tokens and only applying self-attention. Another notable difference to decoder-only is that, the audio frames in decoder-prepend can attend to each other in the encoder before concatenation (prepending).

3.3 Audio Causal Masking

During training of encoder-decoder models, the target tokens in the decoder are causally masked to prevent them from looking at future information. The causal masking can be represented as a mask matrix M:

$$M_{ij} = \begin{cases} 1 & \text{if } i \ge j \\ 0 & \text{if } i < j \end{cases}$$

that is applied to a generic matrix G to make sure that each element i can only attend to itself and elements before it (i.e., $j \leq i$), obtaining $causal_mask = M \odot G$, where \odot is the elementwise multiplication.

In standard settings, causal masking is also applied in the decoder-only models, where both previous tokens \mathbf{Y} and the input audio representation \mathbf{X} are masked. Therefore, the self-attention mechanism in Equation 1 is applied to the masked sequence $causal_mask(concat(\mathbf{X}, \mathbf{Y}))$ (Figure 1b and 1c). Recent works (Wu et al., 2023) propose an alternative solution for causal masking, where only the previous tokens are masked while the input sequence is completely accessible. In this case, A_s in Equation 1 is applied to $concat(\mathbf{X}, causal_mask(\mathbf{Y}))$, making the behavior of DFP models more similar to encoder-decoder models with cross-attention.

²We use prepending and concatenation interchangeably.



Figure 1: Representation of the architectures analyzed in the paper. Both (a) and (c) are based on encoder-decoder architecture but (a) uses cross-attention, whereas (c) uses DFP. Secondly, both (b) and (c) uses DFP, but (c) contains a speech encoder, making it not decoder-only. The causal masking is optional.

Line	Model	#Params (M)	CoVoST2		MuST-C			
Line			ca/de/es/fr (\downarrow)	ca/de/es/fr-en (†)	en (\downarrow)	en-es	en-de	en-x (†)
1	cross-attention TF	71.2 - 98.8	23.7	25.6	12.1	26.9	22.0	25.1
2	decoder-prepend TF	64.9 - 92.5	$24.7^{\dagger 4}$	$24.6^{\dagger 4}$	12.4	26.9	21.1^{\dagger}	$24.6^{\dagger 4}$
3	decoder-only 18L		$26.1^{\dagger 4}$	$24.6^{\dagger 4}$	13.2†	27.4†	21.9	$25.3^{\dagger 1}$
4	cross-attention CF-CTC	111 - 153	19.6	29.7	10.4	29.9	25.2	28.6
4.1	(+) compr		$21.8^{\ddagger 4}$	$28.5^{\ddagger 4}$	10.3	30.2	25.5	$28.1^{\ddagger 5}$
5	decoder-prepend CF-CTC	105 - 147	19.9	29.7	10.3	30.2	25.4	$28.3^{\ddagger 2}$
5.1.	(+) compr		19.9	29.7	10.4	30.7 [‡]	25.9 [‡]	$28.0^{\ddagger 5}$
6	decoder-only 32L	109 - 137	$24.3^{\ddagger 4}$	$25.3^{\ddagger 4}$	13.2 [‡]	27.2 [‡]	22.2^{\ddagger}	26.8 ^{‡8}

Table 1: Comparison between cross-attention, decoder-only and decoder-prepend using transformer (TF) and conformer (CF) encoders. CTC compression is denoted by "compr". For multilingual models, we report the average over their target languages, i.e., top-4 high resourced pairs for CoVoST2 and the 8 target languages for MuST-C (the "en-x" column). We evaluate ASR and ST with WER (\downarrow) and BLEU (\uparrow), respectively. \dagger (N) and \ddagger (N) refer to the number (N) of language pairs that are significantly different with p < 0.05 to line (1) and line (4), respectively.

4 Experimental Settings

4.1 Data

MuST-C data set is derived from TED talks with English audios transcribed and translated into 8 languages. We trained ASR models using its English transcripts while for ST we also used all 8 target languages, namely Dutch (nl), French (fr), German (de), Italian (it), Portuguese (pt), Romanian (ro), Russian (ru) and Spanish (es). More specifically, we trained two bilingual ST models translating English speech into Spanish and German texts respectively, and a single multilingual ST model translating into all 8 target languages.

One limitation of MuST-C is that its speech data is English only. In order to compare the models on non-English speech, we run further experiments on the x-en language directions of the CoVoST2 data. There are 21 non-English languages, e.g., Catalan (ca) and Chinese (zh) for the speech inputs. A complete list of supported languages can be found in (Wang et al., 2021). For each model architecture, we trained a single multilingual ASR³ model and a multilingual ST model with transcripts of the 21 non-English languages and the English translations as target inputs, respectively.

Audio processing. We extract log Mel-filterbank features of size 80 computed every 10ms with a window size of 25ms. The resulting spectrograms are normalized using Utterance-level Cepstral Mean and Variance Normalization (CMVN). During training, we also apply SpecAugment (Park et al., 2019) with frequency and temporal masks of size 27 and 100 respectively.

Text processing. The text is tokenized with unigram models trained using SentencePiece (Kudo and Richardson, 2018). On CoVoST2, the vocabulary size for ASR and ST is 32k and 5k respectively. On MuST-C, the vocabulary size is 5k for ASR, 8k for bilingual ST, and 32k for multilingual ST.

³English ASR data was excluded from training.

4.2 Model architecture

For our experiments, we use both Transformer and Conformer (Gulati et al., 2020) architectures, the latter being an improved version of Transformer for speech achieving state-of-the-art results. All models in our experiments have 18 layers that are distributed between the encoder-decoder (12 layers for the encoder and 6 layers for the decoder) or the decoder, except in decoderonly32L which contains 32 layers to match its number of parameters to the Conformer models. The embedding layer and the feed-forwad layers have dimensions of 512 and 2048, respectively across all the models, and the number of attention heads is set to 8. Encoder dropout is set as 0.1 for feed-forward, attention, and convolution layers. Also, in the convolution layer of the Conformer, the kernel size of the point- and depth-wise convolutions is set to 31. The smallest model has about 64.9M parameters, whereas the largest one has 153M parameters.

In the experiments with CTC loss, a linear layer having the vocabulary size is added after the 8th encoder layer. The softmax function is applied to this layer and then the CTC loss is computed with a weight of 0.5. When CTC compression is applied, vectors having the same predictions are merged by averaging them, following Gaido et al. (2021).

We use Fairseq (Ott et al., 2019; Wang et al., 2020) for all the experiments. When using the Conformer encoder, we adopt the implementation from (Papi et al., 2024) which fixes the padding bugs in the convolution layers and the relative positional encoding.

4.3 Training and Evaluation

Training. In all experimental settings, we use the Adam optimizer for training. The learning rate follows a Noam scheduler with a maximum value of 2×10^{-3} and a linear warmup of 25k steps, after which it follows an inverse square root decay.

On MuST-C, all models are trained with a total batch size of 320k audio frames for at most 100k steps along with an early stopping strategy with patience of 10. For the multilingual ST models, we further prepend a language tag to the translations corresponding to the target language. On CoVoST2, all (multilingual) ASR and ST models are trained with a total batch size of 256k frames for 60k steps. On both datasets, all ST encoders are initialized by the corresponding ASR encoders. In case of decoder-only, we use the corresponding decoder-only ASR model for initialization, but both the embedding and output layer are randomly initialized. Experiments are ran on 4 Nvidia A100-40GB GPUs for about 2 days. The final model is obtained by averaging the last 5 checkpoints.

Evaluation. We use beam search for inference with beam size of 5 and no-repeat-ngram-size of 5, performed on one Nvidia A100-40GB GPU with a batch size of 80k frames. ASR models are evaluated by computing word error rate (WER), whereas we use sacreBLEU⁴ (Post, 2018) to compute BLEU scores for the ST models. We provide statistical significance tests to major comparisons using bootstrap resampling (Koehn, 2004) for ASR and approximate randomization (Riezler and Maxwell, 2005) for ST.

5 Results

In this section, we conduct a series of experiments to examine cross-attention and DFP from a variety of angles under comparable data and model size conditions. To begin with, we first discuss the ASR and ST results between cross-attention, decoderonly and decoder-prepend using transformer and conformer architectures. Then, we present their results under the effect of audio sequence compression via CTC and seqKD. In addition, we analyze their difference in terms of generation speed and GPU memory footprint. Finally, we present an ablation study about the causality masking of decoder-only and decoder-prepend.

5.1 Cross-attention, decoder-only and decoder-prepend

We present the reported results on Table 1. In addition, we compute *p*-values between each configuration against the cross-attention baseline of similar model size.

Transformer encoder. Compared to both DFP methods, cross-attention on average has stronger ASR and ST results. On the CoVoST2 dataset, its improvement on multilingual ASR and ST could reach 2.4 WER (line 1 vs line 3) and 1 BLEU point, respectively. On the MuST-C dataset, it is still better than decoder-prepend (line 2) and all settings of decoder-only (line 3), except ST on the en-es and en-x directions. These differences are significantly different for at least one language pair with p < 0.05.

⁴nrefs:1lcase:mixedleff:noltok:13alsmooth:explversion:2.4.2



Figure 2: Comparison between cross-attention and decoder-prepend using sequence-level knowledge distillation (seqKD) for ST on MuST-C (*en-de*). "TF", "CF-CTC" and "CF-compr" refer to transformer encoder, conformer encoder with auxiliary CTC loss and conformer with CTC compression, respectively.

Despite its slightly stronger ST results, decoderonly falls behind to decoder-prepend on ASR (line 3 vs line 2), which WER is 1.4 and 0.8 points lower on CoVoST2 and MuST-C, respectively. The mixed results on MuST-C, especially on ST, indicate the importance of having several test sets, modelling choices and tasks for evaluation.

Conformer with auxiliary CTC. Since the conformer encoder is known to be better than transformer at capturing the local features of the speech inputs, and larger in size, we conducted another evaluation using it. Additionally, we apply auxiliary CTC loss on the transcripts during training.

On the same table, we can observe that both cross-attention (line 4) and decoder-prepend (line 5) have similar ASR and ST results. On CoVoST2, both models have the same 29.7 BLEU points on multilingual ST, whereas cross-attention has a tiny advantage of 0.3 WER on ASR. On MuST-C ASR, on the contrary, decoder-prepend has an WER of 0.1 point lower. In terms of ST, decoder-prepend can be up to 0.3 BLEU points higher, but it is also 0.3 BLEU points lower in the multilingual case. None of these differences are statistically significant with p < 0.05.

Regarding decoder-only, we scale its number of layers from 18 to 32 to match the conformer size. Such scaling up improves its overall performance substantially, resulting in a maximum improvement of 1.8 WER for ASR and 0.7 BLEU points for ST (line 3 vs line 6). In spite of this, it is roughly 2 points worse than the conformer models in all evaluation settings.

The above results show that decoder-prepend

could be on par with cross-attention, but not necessarily better. Such on par situation remains when applying auxiliary CTC loss to the conformer encoder. Furthermore, our results clearly show that a properly designed speech encoder, such as the conformer, substantially improves the performance over a plain decoder-only model of similar size for both ASR and ST. Because of its competitive performance, we further compare decoder-prepend with cross-attention in the following sections.

5.2 Effect of audio sequence compression

Despite their similar qualities in auxiliary CTC loss training (lines 4-5), the behaviours between cross-attention and decoder-prepend are more complicated when CTC compression is applied. On the CoVoST2 dataset, compression on cross-attention (line 4.1) causes a degradation of 2.2 points in WER and 1.2 points in BLEU (with p < 0.05), whereas it does not cause harm to decoder-prepend (line 5.1). On the MuST-C dataset, both cross-attention and decoder-prepend get better on bilingual ST and worse on multilingual ST after applying compression, while remaining stable for ASR. Despite the similar pattern, the improvements in decoderprepend are slightly bigger, while its degradations are smaller. Thus, overall decoder-prepend better leverages CTC compression.

Our results indicate that applying CTC compression to decoder-prepend is better than to crossattention, but it is not straightforward to claim that decoder-prepend is better. Cross-attention with CTC (line 4) and decoder-prepend with compression (line 5.1) have almost identical results on CoV- oST2, whereas, on MuST-C, cross-attention is 0.6 BLEU points better in multilingual ST despite being 0.8 BLEU points worse on bilingual ST.

5.3 Effect of seqKD

SeqKD helps to reduce the translation data complexity by making the target sentence more monotonically aligned to its source sentence (Zhou et al., 2019). This makes seqKD not only useful for improving non-autoregressive translation but also endto-end ST (Inaguma et al., 2021), which has an additional challenge brought by the modality gap. Despite its usefulness, there is a lack of studies about applying seqKD on ST models using DFP. In the following, we fill the gap with experiments on the MuST-C en-de language direction, where cross-lingual alignment is more complicated, to demonstrate better the effect of the seqKD data. We employ NLLB (3.3B) (Costa-jussà et al., 2022) to machine translate the English transcripts in the training set into German as our seqKD data.

Figure 2 presents the results on cross-attention and decoder-prepend⁵. For each model configuration, we train once using the original data, denoted by "Original", and once using the combined data, denoted by "Original+seqKD". As we can observe, training on the combined data brings a substantial gain of more than 2 BLEU points ("+seqKD") in all configurations. This indicates that seqKD also works effectively on decoder-prepend.

Despite the remarkable gain, there are no clear indications of whether cross-attention or decoderprepend benefits more from seqKD data. In fact, in the case of Transformer, decoder-prepend gets a higher BLEU improvement (4.18 vs 3.44) with respect to cross-attention. However, in the case of conformer, we observe different behaviours: the gain for decoder-prepend is higher only when CTC compression is applied. In terms of their best BLEU scores, both cross-attention and decoderprepend are very similar: cross-attention using Transformer is 0.22 BLEU points higher than decoder-prepend, whereas the conformer results show the opposite: decoder-prepend with compression is 0.13 BLEU points slightly better than crossattention (28.15 vs 28.02).

5.4 Generation speed and memory footprint

In addition to ASR and ST performances, we evaluate our models in terms of generation speed and

Model	#Params	Ratio			
		speed \uparrow	memory \downarrow		
cross-attention TF	98.8M	1	1		
decoder-prepend TF	92.5M	0.96	1.59		
decoder-only 18L		0.83	3.01		
cross-attention CF-CTC	139M	0.97	2.16		
(+) compr		0.98	1.88		
decoder-prepend CF-CTC	133M	0.94	3.11		
(+) compr		0.96	2.50		
decoder-only 32L	136M	0.70	5		

Table 2: A comparison between cross-attention and DFP in terms of model parameters, relative generation speed (tokens/s) and relative GPU memory footprint.

GPU memory footprint. For each metric, we compute the average over the 8 language pairs using the multilingual ST on MuST-C, which has longer inputs and covers diverse languages, so that its average is more robust. We report the relative value using cross-attention with Transformer encoder as the baseline, resulting in a value of one to both its generation speed and memory footprint. The batch size and GPU settings follow section 4.3, except that only one GPU is used.

Table 2 presents the results of this comparison. Compared to cross-attention, decoder-prepend has fewer parameters, i.e., 98.8M vs 92.5M, but is 4% slower. If we allocate all encoder parameters to the decoder, i.e., decoder-only(18L), the resulting model is even 17% slower than cross-attention, while requiring about three times as much GPU memory. Similar patterns could be found in conformer with CTC, where crossattention is a bit faster and less memory demanding than its decoder-prepend despite having 6M more parameters. Again, decoder-only, i.e., decoder-only(32L), appears to be the worst. It has only 70% generation speed and requires 5 times as much GPU memory footprint to the baseline. It is worth noting that cross-attention CF-CTC still remains faster and more memory efficient than decoder-only(18L) despite having 43% more parameters. As expected, CTC compression (compr) makes the generation faster and reduces the GPU memory footprint. The improvement to crossattention and decoder-prepend in speed is about 1% and 2%, respectively, whereas it is respectively about 13% and 19% in memory footprint. Decoderprepend has a bigger improvement, but its overall performance is still behind that of cross-attention.

Despite the removal of the cross-attention lay-

⁵We exclude decoder-only since decoder-prepend has been shown better ASR and ST qualities than decoder-only.

Model	#Parameters	CoVoST2		MuST-C			
		ca/de/es/fr (\downarrow)	ca/de/es/fr-en (†)	en (\downarrow)	en-es	en-de	en-x (†)
decoder-prepend TF	64.9M - 92.5M	24.7	24.6	12.4	26.9	21.1	24.6
(-) causal mask		24.6	24.9	13.2 [†]	25.8†	20.8	$16.5^{\dagger 8}$
decoder-only 18L		26.1	24.6	13.2	27.4	21.9	25.3
(+) causal mask		$28.7^{\dagger4}$	$22.2^{\dagger 4}$	13.9†	26.0†	20.1^{\dagger}	$24.2^{\dagger 8}$
decoder-prepend CF-CTC	105M - 147M	19.9	29.7	10.3	30.2	25.4	28.3
(-) causal mask		20.1	29.9	10.6	30.2	25.3	28.3
(+) compr		19.9	29.7	10.4	30.7	25.9	28.0
(-) causal mask		19.9	29.7	10.4	30.7	25.5	28.1
decoder-only 32L	109M - 137M	24.3	25.3	13.2	27.2	22.2	26.8
(+) causal mask		$26.6^{\dagger 4}$	$23.3^{\dagger 4}$	14.4^{\dagger}	26.0†	20.2^{\dagger}	$25.5^{\dagger 8}$

Table 3: Causality masking in decoder-only and decoder-prepend. \dagger (N) refers to the number (N) of language pairs that are significantly different with p < 0.05 to its baseline. Other acronyms follow Table 1.

ers, our study reveals that DFP is still worse in terms of generation speed and memory footprint. The quadratic time and memory complexity of selfattention in sequence length is a more severe issue for DFP when considering speech inputs.

5.5 Causality masking in decoder-only and decoder-prepend

In previous sections, we presented each DFP configuration using its optimal causal masking strategy: 1) causal masking is not applied on decoder-only, whereas 2) it is applied on decoder-prepend. In the following, we provide an ablation study of causal masking, which is summarised in Table 3. The significance tests are computed between the pairs with and without causal masking.

As we can observe, decoder-only (both 18L and 32L) performs worse on all experimental settings when causal masking is applied. On CoVoST2, the performance degrades by at least 2 points, whereas the degradation can be up to 2.4 points on MuST-C. This indicates the importance of allowing the speech frames to attend each other in decoder-only models. Our finding fits with the conclusion drawn by Gupta et al. (2024) for ASR, and we further confirm it for ST.

Do the above results also hold when there is a speech encoder? When causal masking is removed from decoder-prepend (decoder-prepend TF), we observe a performance degradation of 1.2 WER and up to 0.9 BLEU points on MuST-C ASR and bilingual ST, respectively. What is even worse is the degradation of 8.1⁶ BLEU points on multilingual ST. On the CoVoST2 dataset, however, removal of

causal masking causes tiny improvement to both ASR and ST. In the case of conformer encoder, there are almost no performance changes on the CoVoST2 dataset when causal masking is removed, but a small degradation of 0.4 BLEU points (25.9 \rightarrow 25.5) on the MuST-C en-de direction when CTC compression is also applied.

Our results suggest two interesting observations. Firstly, the behaviours of DFP models are quite different under causal masking, depending on whether a speech encoder is used. We hypothesise that the non-adversarial effect of causal masking on decoder-prepend is attributed to the self-attention within the speech encoder, which allows full attention within the speech frames. Secondly, applying causal masking on decoder-prepend is likely to help improving model performance on longer speech inputs, such as the MuST-C dataset.

6 Conclusion

In this paper, we aim to validate the modelling choice of using DFP (decoder-only and decoderprepend) over cross-attention for integrating speech into decoder-only LLMs, especially S2T. In order to perform a controlled comparison under limited computational budget, we train all models from scratch without using large pretrained models. Our series of comparisons, including mono/bi/multilingual settings, indicate that DFP is not strictly better in ASR and ST qualities than cross-attention but that the latter is indeed more efficient in terms of generation speed and GPU memory footprint. Our studies further suggest that: (1) decoder-prepend with a strong speech encoder is more efficient than decoder-only of similar size, and (2) a variety of test sets, language pairs (and directions) as well as

⁶The degradation is similar when the experiment is repeated with another random seed.

tasks, e.g., bi/multi-lingual ST models, are needed to validate the effective scope of a S2T technique, such as causal masking.

7 Limitations

We note the limitations of our experiments. Firstly, our study is based on a single scale point, i.e., without covering a wide range of model parameters, so that the conclusion might change with scale. Secondly, LLMs have slightly different modelling options than our settings, such as having instructions between the speech inputs and the target texts as well as using rotary positional encoding rather than absolute. Given the limited computational budget, we could not include exhaustive comparisons, but our studies have confirmed existing findings and brought it to wider scopes.

References

- Junyi Ao, Rui Wang, Long Zhou, Chengyi Wang, Shuo Ren, Yu Wu, Shujie Liu, Tom Ko, Qing Li, Yu Zhang, Zhihua Wei, Yao Qian, Jinyu Li, and Furu Wei. 2021. Speecht5: Unified-modal encoder-decoder pre-training for spoken language processing.
- Sameer Bansal, Herman Kamper, Adam Lopez, and Sharon Goldwater. 2017. Towards speech-to-text translation without speech recognition. In Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics: Volume 2, Short Papers, pages 474–479, Valencia, Spain. Association for Computational Linguistics.
- Loïc Barrault, Yu-An Chung, Mariano Cora Meglioli, David Dale, Ning Dong, Paul-Ambroise Duquenne, Hady Elsahar, Hongyu Gong, Kevin Heffernan, John Hoffman, et al. 2023. Seamlessm4t-massively multilingual & multimodal machine translation. *arXiv preprint arXiv:2308.11596*.
- Alexandre Bérard, Laurent Besacier, Ali Can Kocabiyikoglu, and Olivier Pietquin. 2018. End-to-End Automatic Speech Translation of Audiobooks. In Proceedings of ICASSP 2018 - IEEE International Conference on Acoustics, Speech and Signal Processing, Calgary, Alberta, Canada.
- Alexandre Bérard, Olivier Pietquin, Christophe Servan, and Laurent Besacier. 2016. Listen and translate: A proof of concept for end-to-end speech-to-text translation. *arXiv preprint arXiv:1612.01744*.
- Tom B Brown. 2020. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*.
- William Chan, Navdeep Jaitly, Quoc Le, and Oriol Vinyals. 2016. Listen, attend and spell: A neural network for large vocabulary conversational speech

recognition. In 2016 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), pages 4960–4964.

- William Chan, Navdeep Jaitly, Quoc V Le, and Oriol Vinyals. 2015. Listen, attend and spell. *arXiv* preprint arXiv:1508.01211.
- Feilong Chen, Minglun Han, Haozhi Zhao, Qingyang Zhang, Jing Shi, Shuang Xu, and Bo Xu. 2023. Xllm: Bootstrapping advanced large language models by treating multi-modalities as foreign languages. *arXiv preprint arXiv:2305.04160*.
- Xi Chen, Songyang Zhang, Qibing Bai, Kai Chen, and Satoshi Nakamura. 2024a. LLaST: Improved endto-end speech translation system leveraged by large language models. In *Findings of the Association for Computational Linguistics ACL 2024*, pages 6976– 6987, Bangkok, Thailand and virtual meeting. Association for Computational Linguistics.
- Zhehuai Chen, He Huang, Andrei Andrusenko, Oleksii Hrinchuk, Krishna C Puvvada, Jason Li, Subhankar Ghosh, Jagadeesh Balam, and Boris Ginsburg. 2024b. Salm: Speech-augmented language model with incontext learning for speech recognition and translation. In *ICASSP 2024-2024 IEEE International Conference on Acoustics, Speech and Signal Processing* (*ICASSP*), pages 13521–13525. IEEE.
- Zhehuai Chen, He Huang, Oleksii Hrinchuk, Krishna C. Puvvada, Nithin Rao Koluguri, Piotr Żelasko, Jagadeesh Balam, and Boris Ginsburg. 2024c. Bestow: Efficient and streamable speech language model with the best of two worlds in gpt and t5. *Preprint*, arXiv:2406.19954.
- Yunfei Chu, Jin Xu, Xiaohuan Zhou, Qian Yang, Shiliang Zhang, Zhijie Yan, Chang Zhou, and Jingren Zhou. 2023. Qwen-audio: Advancing universal audio understanding via unified large-scale audiolanguage models. arXiv preprint arXiv:2311.07919.
- Marta R Costa-jussà, James Cross, Onur Çelebi, Maha Elbayad, Kenneth Heafield, Kevin Heffernan, Elahe Kalbassi, Janice Lam, Daniel Licht, Jean Maillard, et al. 2022. No language left behind: Scaling human-centered machine translation. *arXiv preprint arXiv:2207.04672*.
- Mattia A. Di Gangi, Roldano Cattoni, Luisa Bentivogli, Matteo Negri, and Marco Turchi. 2019a. MuST-C: a Multilingual Speech Translation Corpus. In Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), pages 2012–2017, Minneapolis, Minnesota. Association for Computational Linguistics.
- Mattia Antonino Di Gangi, Matteo Negri, Roldano Cattoni, Roberto Dessi, and Marco Turchi. 2019b. Enhancing transformer for end-to-end speech-to-text translation. In *Proceedings of Machine Translation Summit XVII: Research Track*, pages 21–31, Dublin,

Ireland. European Association for Machine Translation.

- Qingkai Fang, Rong Ye, Lei Li, Yang Feng, and Mingxuan Wang. 2022. STEMM: Self-learning with speech-text manifold mixup for speech translation. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 7050–7062, Dublin, Ireland. Association for Computational Linguistics.
- Yassir Fathullah, Chunyang Wu, Egor Lakomkin, Junteng Jia, Yuan Shangguan, Ke Li, Jinxi Guo, Wenhan Xiong, Jay Mahadeokar, Ozlem Kalinli, et al. 2024. Prompting large language models with speech recognition abilities. In ICASSP 2024-2024 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), pages 13351–13355. IEEE.
- Marco Gaido, Mauro Cettolo, Matteo Negri, and Marco Turchi. 2021. CTC-based compression for direct speech translation. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, pages 690–696, Online. Association for Computational Linguistics.
- Marco Gaido, Sara Papi, Matteo Negri, and Luisa Bentivogli. 2024. Speech translation with speech foundation models and large language models: What is there and what is missing? In *Proceedings of the* 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pages 14760–14778, Bangkok, Thailand. Association for Computational Linguistics.
- Alex Graves, Santiago Fernández, Faustino Gomez, and Jürgen Schmidhuber. 2006. Connectionist temporal classification: labelling unsegmented sequence data with recurrent neural networks. In *Proceedings of the* 23rd international conference on Machine learning, pages 369–376.
- Anmol Gulati, James Qin, Chung-Cheng Chiu, Niki Parmar, Yu Zhang, Jiahui Yu, Wei Han, Shibo Wang, Zhengdong Zhang, Yonghui Wu, and Ruoming Pang. 2020. Conformer: Convolution-augmented transformer for speech recognition. In *Interspeech 2020*, pages 5036–5040.
- Ankit Gupta, George Saon, and Brian Kingsbury. 2024. Exploring the limits of decoder-only models trained on public speech recognition corpora. In *Interspeech* 2024, pages 252–256.
- Yukiya Hono, Koh Mitsuda, Tianyu Zhao, Kentaro Mitsui, Toshiaki Wakatsuki, and Kei Sawada. 2024. Integrating pre-trained speech and language models for end-to-end speech recognition. In *Findings of the Association for Computational Linguistics ACL 2024*, pages 13289–13305, Bangkok, Thailand and virtual meeting. Association for Computational Linguistics.
- Shujie Hu, Long Zhou, Shujie Liu, Sanyuan Chen, Hongkun Hao, Jing Pan, Xunying Liu, Jinyu Li, Sunit Sivasankaran, Linquan Liu, et al. 2024. Wavllm:

Towards robust and adaptive speech large language model. *arXiv preprint arXiv:2404.00656*.

- Chao-Wei Huang, Hui Lu, Hongyu Gong, Hirofumi Inaguma, Ilia Kulikov, Ruslan Mavlyutov, and Sravya Popuri. 2024a. Investigating decoder-only large language models for speech-to-text translation. *arXiv preprint arXiv:2407.03169*.
- Rongjie Huang, Mingze Li, Dongchao Yang, Jiatong Shi, Xuankai Chang, Zhenhui Ye, Yuning Wu, Zhiqing Hong, Jiawei Huang, Jinglin Liu, et al. 2024b. Audiogpt: Understanding and generating speech, music, sound, and talking head. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 23802–23804.
- Hirofumi Inaguma, Tatsuya Kawahara, and Shinji Watanabe. 2021. Source and target bidirectional knowledge distillation for end-to-end speech translation. In Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, pages 1872–1881, Online. Association for Computational Linguistics.
- Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. 2023. Mistral 7b. arXiv preprint arXiv:2310.06825.
- Yoon Kim and Alexander M. Rush. 2016. Sequencelevel knowledge distillation. In *Proceedings of the* 2016 Conference on Empirical Methods in Natural Language Processing, pages 1317–1327, Austin, Texas. Association for Computational Linguistics.
- Philipp Koehn. 2004. Statistical significance tests for machine translation evaluation. In Proceedings of the 2004 Conference on Empirical Methods in Natural Language Processing, pages 388–395, Barcelona, Spain. Association for Computational Linguistics.
- Taku Kudo and John Richardson. 2018. SentencePiece: A simple and language independent subword tokenizer and detokenizer for neural text processing. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 66–71, Brussels, Belgium. Association for Computational Linguistics.
- Egor Lakomkin, Chunyang Wu, Yassir Fathullah, Ozlem Kalinli, Michael L Seltzer, and Christian Fuegen. 2024. End-to-end speech recognition contextualization with large language models. In *ICASSP* 2024-2024 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), pages 12406–12410. IEEE.
- Siddique Latif, Moazzam Shoukat, Fahad Shamshad, Muhammad Usama, Heriberto Cuayáhuitl, and Björn W Schuller. 2023. Sparks of Large Audio Models: A Survey and Outlook. *arXiv preprint arXiv:2308.12792*.

- Jinyu Li et al. 2022. Recent advances in end-to-end automatic speech recognition. *APSIPA Transactions* on Signal and Information Processing, 11(1).
- Yuchen Liu, Junnan Zhu, Jiajun Zhang, and Chengqing Zong. 2020. Bridging the modality gap for speechto-text translation. arXiv preprint arXiv:2010.14920.
- Cosmin Munteanu, Matt Jones, Sharon Oviatt, Stephen Brewster, Gerald Penn, Steve Whittaker, Nitendra Rajput, and Amit Nanavati. 2013. We need to talk: HCI and the delicate topic of spoken language interaction. In CHI '13 Extended Abstracts on Human Factors in Computing Systems, page 2459–2464, Paris, France. Association for Computing Machinery.
- Myle Ott, Sergey Edunov, Alexei Baevski, Angela Fan, Sam Gross, Nathan Ng, David Grangier, and Michael Auli. 2019. fairseq: A fast, extensible toolkit for sequence modeling. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics (Demonstrations)*, pages 48–53, Minneapolis, Minnesota. Association for Computational Linguistics.
- Jing Pan, Jian Wu, Yashesh Gaur, Sunit Sivasankaran, Zhuo Chen, Shujie Liu, and Jinyu Li. 2023. Cosmic: Data efficient instruction-tuning for speech in-context learning. *arXiv preprint arXiv:2311.02248*.
- Sara Papi, Marco Gaido, Andrea Pilzer, and Matteo Negri. 2024. When good and reproducible results are a giant with feet of clay: The importance of software quality in NLP. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3657–3672, Bangkok, Thailand. Association for Computational Linguistics.
- Daniel S. Park, William Chan, Yu Zhang, Chung-Cheng Chiu, Barret Zoph, Ekin D. Cubuk, and Quoc V. Le. 2019. Specaugment: A simple data augmentation method for automatic speech recognition. In *Inter-speech 2019*, pages 2613–2617.
- Matt Post. 2018. A call for clarity in reporting BLEU scores. In Proceedings of the Third Conference on Machine Translation: Research Papers, pages 186– 191, Brussels, Belgium. Association for Computational Linguistics.
- Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. 2021. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pages 8748–8763. PMLR.
- Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. 2023. Robust speech recognition via large-scale weak supervision. In *International conference on machine learning*, pages 28492–28518. PMLR.
- Alec Radford, Jeff Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. 2019. Language Models are Unsupervised Multitask Learners.

- Stefan Riezler and John T. Maxwell. 2005. On some pitfalls in automatic evaluation and significance testing for MT. In Proceedings of the ACL Workshop on Intrinsic and Extrinsic Evaluation Measures for Machine Translation and/or Summarization, pages 57–64, Ann Arbor, Michigan. Association for Computational Linguistics.
- Matthias Sperber and Matthias Paulik. 2020. Speech translation and the end-to-end promise: Taking stock of where we are. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 7409–7421, Online. Association for Computational Linguistics.
- Chameleon Team. 2024. Chameleon: Mixed-modal early-fusion foundation models. *arXiv preprint arXiv:2405.09818*.
- Gemma Team, Thomas Mesnard, Cassidy Hardin, Robert Dadashi, Surya Bhupatiraju, Shreya Pathak, Laurent Sifre, Morgane Rivière, Mihir Sanjay Kale, Juliette Love, et al. 2024. Gemma: Open models based on gemini research and technology. *arXiv preprint arXiv:2403.08295*.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. 2023. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*.
- Ioannis Tsiamas, Gerard Gállego, José Fonollosa, and Marta Costa-jussà. 2024. Pushing the limits of zeroshot end-to-end speech translation. In *Findings of the Association for Computational Linguistics ACL 2024*, pages 14245–14267, Bangkok, Thailand and virtual meeting. Association for Computational Linguistics.
- Emiru Tsunoo, Hayato Futami, Yosuke Kashiwagi, Siddhant Arora, and Shinji Watanabe. 2023. Decoderonly architecture for speech recognition with ctc prompts and text data augmentation. *arXiv preprint arXiv:2309.08876*.
- Emiru Tsunoo, Hayato Futami, Yosuke Kashiwagi, Siddhant Arora, and Shinji Watanabe. 2024. Decoderonly architecture for streaming end-to-end speech recognition. arXiv preprint arXiv:2406.16107.
- A Vaswani. 2017. Attention is all you need. Advances in Neural Information Processing Systems.
- Changhan Wang, Yun Tang, Xutai Ma, Anne Wu, Dmytro Okhonko, and Juan Pino. 2020. Fairseq S2T: Fast speech-to-text modeling with fairseq. In Proceedings of the 1st Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics and the 10th International Joint Conference on Natural Language Processing: System Demonstrations, pages 33–39, Suzhou, China. Association for Computational Linguistics.
- Changhan Wang, Anne Wu, Jiatao Gu, and Juan Pino. 2021. Covost 2 and massively multilingual speech translation. In *Interspeech*, pages 2247–2251.

- Mingqiu Wang, Wei Han, Izhak Shafran, Zelin Wu, Chung-Cheng Chiu, Yuan Cao, Yongqiang Wang, Nanxin Chen, Yu Zhang, Hagen Soltau, et al. 2023. Slm: Bridge the thin gap between speech and text foundation models. *arXiv preprint arXiv:2310.00230*.
- Ron J Weiss, Jan Chorowski, Navdeep Jaitly, Yonghui Wu, and Zhifeng Chen. 2017. Sequence-to-sequence models can directly translate foreign speech. *arXiv* preprint arXiv:1703.08581.
- Jian Wu, Yashesh Gaur, Zhuo Chen, Long Zhou, Yimeng Zhu, Tianrui Wang, Jinyu Li, Shujie Liu, Bo Ren, Linquan Liu, and Yu Wu. 2023. On decoderonly architecture for speech-to-text and large language model integration. In 2023 IEEE Automatic Speech Recognition and Understanding Workshop (ASRU), pages 1–8.
- Piotr Żelasko, Zhehuai Chen, Mengru Wang, Daniel Galvez, Oleksii Hrinchuk, Shuoyang Ding, Ke Hu, Jagadeesh Balam, Vitaly Lavrukhin, and Boris Ginsburg. 2024. Emmett: Efficient multimodal machine translation training. *arXiv preprint arXiv:2409.13523*.
- Chunting Zhou, Graham Neubig, and Jiatao Gu. 2019. Understanding knowledge distillation in non-autoregressive machine translation. *arXiv preprint arXiv:1911.02727*.