

Various approaches to solving nonlinear equations

John C. Nash and Ravi Varadhan

2024-05-31

Abstract

Modelling real world systems frequently requires the solution of systems of nonlinear equations. A number of approaches have been suggested and developed for this computational problem. However, it is also possible to attempt solutions using more general nonlinear least squares or function minimization techniques. There are concerns, nonetheless, that we may fail to find solutions, or that the process will be inefficient. Examples are presented with R with the goal of providing guidance on the solution of nonlinear equations problems.

1 Background

Mathematical modelling translates real-world phenomena into equations and inequalities, the solution of which allows us to explain and predict the behaviour of the real-world system of interest. This is illustrated by an example of from Nelson and Hodgkin ([16]1981) that has been translated to a test problem for nonlinear equations and nonlinear least squares in John E. Dennis, Gay, and Vu ([5]1983).

We will write our nonlinear equations in the form

$$r(x) = 0$$

where x are the **parameters** we wish to determine by solving the equations that the **residuals** $r(x)$ provide. Usually we anticipate there will be an equal number n of parameters and equations. However, there can be systems with no solution, or sets of $m > n$ equations which satisfy the equations. Alternatively, minimizing the **sum**

of squares $r(x)^2$ provides an approach to solving the nonlinear equations if we can find a solution with the sum of squares equal to zero. Similarly, general function minimization tools can be applied to try to minimize the sum of squares to zero.

We therefore will seek to examine the solution of nonlinear equations problems through tools for

- solution of nonlinear equations, generally through providing program code to evaluate the residuals $r(x)$
- solution of nonlinear least squares problems by the same mechanism. However, in this case there may be more residuals than parameters, and the returned “solution” may not be have all residuals effectively zero
- minimization of the sum of squares $r'(x) * r(x)$. Again, unless the sum of squares is zero, we have not solved the nonlinear equations.

2 Nonlinear equations tools

The software tools for nonlinear equations largely parallel those for nonlinear function minimization and nonlinear least squares. Many of these have at least a motivation in what is referred to as Newton’s method (Polyak ([17]2007), Ypma ([21]1995)). This discussion uses tools in R for approaching nonlinear equations problems. Unfortunately, R is less well-provided with tools directly for nonlinear equations than, say, Julia. (See, for example, <https://docs.sciml.ai/NonlinearSolve/stable/solvers/nonlinear>). Nevertheless, using the Consolidated R Archive Network repository (<https://cran.r-project.org/>) we do recognize the following R tools for nonlinear equations (there may be others, and we welcome communications):

- package `nleqslv` uses Newton or Broyden methods to try to solve a set of nonlinear equations, of which Broyden is the default. Within each general approach, the stepsize is adjusted by several “global” strategies, of which the “double dogleg” strategy of J. E. Dennis and Schnabel ([6]1983) is the default.
- function `dfsane()` from package `BB` (Varadhan and Gilbert ([20]2009)), which uses a projected gradient approach of LaCruz, Martinez, and Raydan ([8]2006)

- package `dfsaneacc` is an independent implementation of the same approach as `BB::dfsane()` (Birgin et al. ([3]2024))

We note that the package `ktsolve` (**Configurable function for solving families of nonlinear equations**) uses solvers from `BB` and `nleqslv`.

3 Nonlinear least squares tools

R is quite well-served for tools for the related tasks of nonlinear least squares (the minimization of the sum of squares) and nonlinear regression (where we seek the model parameters and their properties). Base R (R Development Core Team ([18]2008)) has the `nls()` function which, while now quite dated, still has very wide-ranging capability, though it lacks a stabilized (i.e., Levenberg-Marquardt) solver. By contrast, both packages `minpack.lm` (Mullen, Elzhov, and Bolker ([10]2012)) and `nlsr` (John C. Nash and Murdoch ([14]2017)) have stabilized solvers. Moreover, `nlsr` attempts to use analytic or automatic differentiation to get derivatives required by the solver. The forthcoming article John C. Nash and Bhattacharjee ([13]2023) and the slightly more general John C. Nash ([12]2022) provide discussion and comparison of the tools.

4 Nonlinear function minimization tools

There are quite a lot of R tools for function minimization. This is quite often called “optimization” within the R community, though strictly **function minimization** is a sub-class of problems in optimization. For a very good overview, the *CRAN Task View: Optimization and Mathematical Programming* by Schwendinger and Borchers ([19]2024) is highly recommended.

For this article, we focus our attention to the tools available in package `optimx` (John C. Nash and Varadhan ([15]2011)). For solvers that seek local minima of functions of several parameters, `optimx` offers more than enough choices. It is, however, possible that we might want to explore problems that have multiple solutions, that is, multiple minima of the sum of squares function, hopefully with zero residuals. For such cases, it seems sensible to look at global or stochastic minimization solvers (John C. Nash ([11]2014, chap. 15),

Cortez ([4]2014)). We explore such ideas briefly, but note that a wrapper for such methods to allow convenient use via a unified call as in package `optimx` is not yet openly available.

5 Dennis, Gay, Vu test problem

This problem is described, with Fortran code, in John E. Dennis, Gay, and Vu ([5]1983). The problem, in its original statement, has 8 parameters, but two of the equations (i.e., residual functions) are linear in the parameters, and a **reduced** problem with 6 parameters and 6 residual functions can be easily set up. The technical report provides five sets of data, that is, five sample problems. Also the report suggests starting sets of parameters, but also looks at scaling these “starts” by 10 and 100. It seems that this problem is relatively difficult to solve.

We have coded the full and reduced problems in R as `dgvf.R` and `dgvr.R`, with a function `dgbprep()` that takes as its argument the “Problem ID” for each of the suggested data sets. The technical report also suggests solutions. The problem ID values are “791129”, “791226”, “0121a”, “0121b” and “0121c”. We also wrote `dgvreduce()` and `dgvunreduce()` to convert parameter vectors from the full to reduced problem or vice-versa. All codes are provided in the Appendices before the References.

While we will not include the output here, we can confirm that running the program in file `dgvtry.R` (via the `source()` command) gives residuals that are essentially zero for the proposed solution vectors `xstar` or `xstrr` for all five problems in both full and reduced forms.

Now let us attempt some solutions with R tools for the example problem “0121a”.

5.1 DGV with `nleqslv`

For the default method and global strategy, neither full nor reduced solutions are acceptable from starting parameters (`x0` for the full problem). However, we see that the termination code (`termcd`) is not 1, so the software is informing us that a satisfactory solution has not been found.

```
#> Prepare Dennis-Gay-Vu problem for id= 0121a
```

```

#> Using dgvf()

#> Solution:[1] 0.002468503 -0.825902531 0.002126131 -0.020796338 -2.648814611
#> [6] 2.241598979 -19.644981645 0.708379863
#> SS= 0.005900999 termination code= 4

#> NULL

#> Using dgvr()

#> Solution:[1] 0.002810679 0.001124791 -0.444240100 2.245941731 -20.424571868
#> [6] 0.744305155
#> SS= 0.006554426 termination code= 4

#> NULL

```

We can try different options for method and step length, and package `nleqslv` has a tool, `testnslv()`, to allow this to be carried out easily.

```

#> Prepare Dennis-Gay-Vu problem for id= 0121a

#> Using dgvf()

#> Call:
#> testnslv(x = x0, fn = dgvf, rhs = sigma)
#>
#> Results:
#>   Method Global termcd Fcnt Jcnt Iter Message      Fnorm
#> 1 Newton  cline      1  72  38  38  Fcrit 1.153e-27
#> 2 Newton  qline      1  72  38  38  Fcrit 1.153e-27
#> 3 Newton  gline      1  75  24  24  Fcrit 2.888e-22
#> 4 Newton  pwldog     1 192 136 136  Fcrit 1.459e-29
#> 5 Newton  dbldog     1  89  83  83  Fcrit 1.599e-28
#> 6 Newton  hook       1 140 132 132  Fcrit 6.456e-18
#> 7 Newton  none        1  19  19  19  Fcrit 2.593e-28
#> 8 Broyden cline      1 102  4  46  Fcrit 2.669e-19
#> 9 Broyden qline      1 109  5  50  Fcrit 5.047e-22
#> 10 Broyden gline     1 130  4  38  Fcrit 1.968e-19
#> 11 Broyden pwldog    4 214  8 150 Maxiter 5.835e-03
#> 12 Broyden dbldog    4 214  7 150 Maxiter 2.950e-03
#> 13 Broyden hook      4 241  7 150 Maxiter 1.445e-02
#> 14 Broyden none      4  20  1  20 Maxiter 1.673e+04

#>
#> Using dgvr()

#> Call:
#> testnslv(x = x0, fn = dgvf, rhs = sigma)
#>
#> Results:
#>   Method Global termcd Fcnt Jcnt Iter Message      Fnorm
#> 1 Newton  cline      1  72  38  38  Fcrit 1.153e-27
#> 2 Newton  qline      1  72  38  38  Fcrit 1.153e-27
#> 3 Newton  gline      1  75  24  24  Fcrit 2.888e-22
#> 4 Newton  pwldog     1 192 136 136  Fcrit 1.459e-29
#> 5 Newton  dbldog     1  89  83  83  Fcrit 1.599e-28
#> 6 Newton  hook       1 140 132 132  Fcrit 6.456e-18
#> 7 Newton  none        1  19  19  19  Fcrit 2.593e-28
#> 8 Broyden cline      1 102  4  46  Fcrit 2.669e-19
#> 9 Broyden qline      1 109  5  50  Fcrit 5.047e-22
#> 10 Broyden gline     1 130  4  38  Fcrit 1.968e-19
#> 11 Broyden pwldog    4 214  8 150 Maxiter 5.835e-03
#> 12 Broyden dbldog    4 214  7 150 Maxiter 2.950e-03
#> 13 Broyden hook      4 241  7 150 Maxiter 1.445e-02
#> 14 Broyden none      4  20  1  20 Maxiter 1.673e+04

```

Running the multiple solutions as `testnslv()` does is possibly inefficient. In preparing this vignette, the following crude script was devised to exit after the first satisfactory solution has been achieved. The code to do this follows.

```
seqnslv <- function(x, fn, jac=NULL, ...,
                  method=c("Newton", "Broyden"),
                  global=c("qline", "cline", "gline", "pwlldog", "dbldog", "hook", "none"))
{
  methods <- method
  globals <- global
  reslist<-list()
  doneOK <- FALSE # JN: used to break out of loops
  for(m in methods) {
    cat("method ",m,"\n")
    for(g in globals) {
      cat("global ",g,"\n")
      res <- try(nleqslv(x, fn, jac, ..., method=m, global=g,silent=TRUE)
                if(inherits(res,"try-error")) {
                  cat("method ",m," global ",g," FAILED\n")
                } else {
                  ss <- sum((res$fvec)^2)
                  cat("method ",m," global ",g," termcd=",res$termcd," sumsq=",ss,"\n")
                  if (res$termcd ==1){
                    doneOK<- TRUE
                    attr(res,"method") <- m
                    attr(res,"global") <- g
                    break
                  }
                }
    } # end g
    if (doneOK) break
  } # end m
  res
}
```

This approach gives the following result

```
#> Prepare Dennis-Gay-Vu problem for id= 0121a

#> Using dgvf()

#> method Newton
#> global qline
#> method Newton global qline termcd= 1 sumsq= 2.305261e-27

#> Solution:[1] 3.099869e-03 -8.190999e-01 -2.239405e-04 -1.677606e-02 2.681514e+00
#> [6] 2.250216e+00 -2.024170e+01 7.970983e-01
#> SS= 2.305261e-27 termination code= 1

#> NULL

#> Using dgvr()

#> method Newton
#> global qline
#> method Newton global qline termcd= 1 sumsq= 4.576478e-27

#> Solution:[1] 3.099869e-03 -2.239405e-04 2.681514e+00 2.250216e+00 -2.024170e+01
#> [6] 7.970983e-01
#> SS= 4.576478e-27 termination code= 1

#> NULL
```

5.2 DGV with BB::dfsane and dfsaneacc

The spectral gradient routines in package `BB::dfsane()` and in package `dfsaneacc` are intended to solve nonlinear equations problems, but unfortunately do not seem to give satisfactory solutions with the default options. Even with some variation of the options available to each program, it seems difficult to get a solution. `dfsaneacc` was able to get to a solution after over 100,000 iterations and a quite large setting (25) in the number of previous iterates considered in the secant acceleration update (default is 6, which was much slower).

```
#> Prepare Dennis-Gay-Vu problem for id= 0121a
#> Warning in dfsane(x0, dgvf, quiet = TRUE, rhs = sigma): Unsuccessful
#> convergence.
#> dsolr$par for fn= dgvf SS= 274.2222 at
#> [1] -0.42517901 -0.77500000 0.06898961 -0.03542919 -2.65623588 2.50630841
#> [7] -0.31907139 -0.13885158
#> residuals: [1] -0.38417901 0.05056042 1.03007993 0.72522327 -3.11248693
#> [6] 3.33557503 9.92863312 -12.37310089
#> Warning in dfsane(x0r, dgvr, quiet = TRUE, rhs = sigma): Unsuccessful
#> convergence.
#> dsolr$par for fn= dgvr SS= 151.8927 at
#> [1] -0.56678206 -0.02359818 -2.60639467 2.65553824 -1.91014963 1.83848441
#> residuals: [1] 2.584243 1.457483 2.312137 -4.867993 8.962342 -5.807173
#> Prepare Dennis-Gay-Vu problem for id= 0121a
#> daasolx for fn= dgvf SS= 1.324049e-12 at
#> [1] 3.099812e-03 -8.190991e-01 -2.239393e-04 -1.677666e-02 2.681530e+00
#> [6] 2.250219e+00 -2.024183e+01 7.970978e-01
#> residuals: [1] 6.647103e-07 -6.004497e-07 -6.437725e-07 2.965854e-07 1.354081e-07
#> [6] -2.972639e-08 -3.730332e-10 6.652416e-09
#> 2e+05 iterations
#> daasolrx for fn= dgvr SS= 5.900543e-13 at
#> [1] 3.099867e-03 -2.239404e-04 2.681515e+00 2.250216e+00 -2.024171e+01
#> [6] 7.970983e-01
#> residuals: [1] -6.130108e-08 3.162569e-08 -1.747531e-08 -4.538748e-09 -1.037709e-07
#> [6] 7.577611e-07
#> 118611 iterations
5
```

5.3 DGV with nlsv::nlfb()

```
#> Prepare Dennis-Gay-Vu problem for id= 0121a
#> Using dgvf()
#> nlfbnsol <- nlfb(x0, dgvf, jac="jacentral", rhs=sigma)
#> residual sumsqares = 3.2693e-17 on 8 observations
#> after 190 Jacobian and 263 function evaluations
#> name      coeff      SE      tstat      pval      gradient      JSingval
#> p1      0.00309987      Inf      0      NaN      -3.093e-06      8523
#> p2      -0.8191      Inf      0      NaN      -5.002e-09      8523
#> p3     -0.000223941      Inf      0      NaN      1.678e-06      7.622
#> p4     -0.0167761      Inf      0      NaN      -2.507e-09      7.622
#> p5      2.68151      Inf      0      NaN      4.708e-10      0.8517
#> p6      2.25022      Inf      0      NaN      4.102e-09      0.8517
#> p7      -20.2417      Inf      0      NaN      1.588e-09      0.009023
#> p8      0.797098      Inf      0      NaN      4.051e-09      0.009023

#> Using dgvr()
#> nlfbnsolr <- nlfb(x0r, dgvr, jac="jacentral", rhs=sigma)
#> residual sumsqares = 6.05e-16 on 6 observations
#> after 209 Jacobian and 290 function evaluations
#> name      coeff      SE      tstat      pval      gradient      JSingval
#> p1      0.00309987      Inf      0      NaN      1.934e-05      8515
#> p2     -0.00022394      Inf      0      NaN     -6.953e-06      8515
```

```
#> p3          2.68151          Inf          0          NaN -1.651e-09          4.198
#> p4          2.25022          Inf          0          NaN -2.01e-08          4.198
#> p5         -20.2417          Inf          0          NaN -9.281e-09          0.01397
#> p6          0.797098          Inf          0          NaN -2.706e-08          0.01397
```

For both full and reduced problems we have good solutions. However, the singular values of the Jacobian at the solution are extreme, underlining the difficulty of solution of these problems. We have not explored the use of `nls()` from base R nor the package `minpack.lm`.

5.4 DGV with optimx function minimizers

We will minimize the functions

```
ssdgvf<-function(x, rhs){
  res<-dgvf(x,rhs)
  ss<-sum(res^2)
  ss
}
ssdgv<-function(x, rhs){
  res<-dgv(x,rhs)
  ss<-sum(res^2)
  ss
}
```

Trying “MOST” methods in package `optimx` showed only method “Rvmin” succeeded for the full problem, while a half dozen gave solutions for the reduced problem. The calls are

```
library(optimx)
osol <- opm(x0, ssdgvf, gr="grcentral", method="MOST",
  control=list(maxit=20000, maxfeval=25000), rhs=sigma)
osolr <- opm(x0r, ssdgv, gr="grcentral", method="MOST",
  control=list(maxit=20000, maxfeval=25000),rhs=sigma)
```

To keep the display tidy, we show the results for seven methods, namely

```
cmeth <- c("Rvmin", "nlm", "ucminf", "slsqp", "nlg", "Rcgmin", "mla")
```

and limit the output to the two first parameters.

```
#> Prepare Dennis-Gay-Vu problem for id= 0121a
#> Using dgvf()
#>
#>      p1 s1      p2 s2      value fevals gevals hevals conv kkt1
#> Rvmin 3.0999e-03 -0.81910 7.1117e-17 5616 4270 0 0 TRUE
#> Rcgmin 2.5794e-03 -0.82092 3.8466e-04 60003 17967 0 1 FALSE
#> mla 2.5202e-03 -0.82355 6.3165e-04 2543 6800 0 0 FALSE
#> ncg 1.7646e-03 -0.82320 2.2800e-03 60003 16682 0 1 FALSE
#> ucminf 3.1709e-06 -0.72498 2.0638e-02 20000 20000 0 3 FALSE
#> slsqp -1.6049e-05 -0.72611 2.3149e-02 3453 3452 0 0 FALSE
#> nlm -5.3352e-06 -0.71878 2.5649e-02 56585 56585 0 1 FALSE
#>
#>      kkt2 xtime
#> Rvmin FALSE 1.044
#> Rcgmin FALSE 4.257
#> mla FALSE 1.374
```

```

#> ncg FALSE 4.010
#> ucminf FALSE 4.008
#> slsqp FALSE 0.717
#> nlm FALSE 11.300
#> Using dgvr()
#>
#>      p1 s1      p2 s2      value fevals gevals hevals conv kkt1
#> Rvmin 3.0999e-03 -2.2394e-04 3.0171e-17 2706 2071 0 0 TRUE
#> Rcgmin 3.0999e-03 -2.2394e-04 8.1709e-15 7002 2201 0 0 TRUE
#> ncg 3.0998e-03 -2.2380e-04 1.9253e-11 7554 2220 0 0 TRUE
#> mla 3.2226e-03 2.6311e-04 2.4318e-04 1816 3016 0 0 FALSE
#> nlm -2.6134e-05 8.3822e-06 6.1437e-02 1739 1739 0 0 FALSE
#> slsqp 1.1367e-12 1.1110e-11 7.1366e-02 8338 8337 0 0 FALSE
#> ucminf 7.1861e-08 -2.2112e-07 7.2835e-02 20000 20000 0 3 FALSE
#>      kkt2 xtime
#> Rvmin FALSE 0.561
#> Rcgmin FALSE 0.595
#> ncg FALSE 0.595
#> mla FALSE 0.683
#> nlm FALSE 0.405
#> slsqp FALSE 1.910
#> ucminf FALSE 4.385

```

Note that parameter scaling seems to give slightly better results. However, we have not explored this possibility further.

```

osolrs <- opm(x0r, ssdgvr, gr="grcentral", method="cmeth",
             control=list(maxit=20000, maxfeval=25000,
                          parscale=c(.001, .0001, 1, 1, 10, 1)),rhs=sigma)
cat("Using dgvr()\n")
#> Using dgvr()
summary(osolrs, order=value, par.select=1:2)
#>      p1 s1      p2 s2      value fevals gevals hevals conv kkt1
#> Rvmin 0.0030999 -2.2394e-04 1.4274e-17 2772 2101 0 0 TRUE
#> nlm 0.0030999 -2.2394e-04 2.1059e-17 3136 3136 0 0 TRUE
#> ucminf 0.0030999 -2.2394e-04 4.5830e-17 19250 19250 0 0 TRUE
#> slsqp 0.0030999 -2.2394e-04 9.4500e-17 21395 21394 0 0 TRUE
#> ncg 0.0030999 -2.2102e-04 8.3162e-09 14872 5054 0 0 FALSE
#> Rcgmin 0.0031000 -2.2021e-04 1.3579e-08 13030 4621 0 0 FALSE
#> mla 0.0031172 -2.8545e-05 3.7627e-05 4816 4732 0 0 FALSE
#>      kkt2 xtime
#> Rvmin FALSE 0.573
#> nlm FALSE 0.710
#> ucminf FALSE 4.276
#> slsqp FALSE 4.789
#> ncg FALSE 1.310
#> Rcgmin FALSE 1.191
#> mla FALSE 1.106

```

5.5 Residual scaling

If we look at the residuals from the starting value x_0 , the magnitudes of the elements vary quite widely. Multiplying the residuals by a scaling to equalize the contribution from each might help, but the following experiments were unsuccessful. We use the following calls on the reduced problem only and will not include the output here.

```

rscale<-c(1e8, 1e8, 1e3, 1e3, 1, 1)
ssdgvrres<-function(x, rhs){
  res<-dgvr(x,rhs)*rscale
  ss<-sum(res^2)
  ss
}
cat("Using dgvr() with residual scaling\n")

```

```

osolrrs <- opm(x0r, ssdgvrrs, gr="grcentral", method=cmeth,
              control=list(maxit=20000, maxfeval=25000),rhs=sigma)
summary(osolrrs, order=value)
nmeth<-length(cmeth)
npar<-length(x0r)
for (ii in 1:nmeth){
  par<-as.numeric(osolrrs[ii, 1:npar])
  cat(cmeth[ii],"  ssdgvrr = ",ssdgvrr(par, rhs=sigma),"\n")
}
cat("Using dgvr() with residual and parameter scaling\n")
osolrprs <- opm(x0r, ssdgvrrs, gr="grcentral", method=cmeth,
              control=list(maxit=20000, maxfeval=25000,
                          parscale=c(.001, .0001, 1, 1, 10, 1)),rhs=sigma)
summary(osolrprs, order=value)
for (ii in 1:nmeth){
  par<-as.numeric(osolrrs[ii, 1:npar])
  cat(cmeth[ii],"  ssdgvrr = ",ssdgvrr(par, rhs=sigma),"\n")
}

```

5.6 DGV with stochastic function minimizers

In 2017 Hans Werner Borchers prepared a prototype wrapper for stochastic and global optimization solvers under the name `gloptim`. A Google Summer of Code project in 2022 was started under the name `stochoptim` to add better checks and documentation to these ideas, but this effort was abandoned due to difficulties in effectively communicating with the student. One of us has resurrected the `gloptim` package. (Several of the solvers are no longer in the active CRAN repository and needed to be de-archived.)

We tried a small selection of such minimizers with rather unsatisfactory results. We will include the code to run the examples and a saved version of the output, as running times are quite long.

```

# dvgvlopt.R
library(gloptim)
source("dgvprep.R")
source("dgvf.R")
source("nleqsum.R")
source("chknleqsol.R")
pid <- "0121a"
prob<-dgvprep(pid)
sigma<-prob$sigma
x0<-prob$x0
source("dgvreduce.R")
source("dgvrr.R")
x0r<-dgvreduce(x0)
shift <- 100
lbf <- x0 - shift
ubf <- x0 + shift
lbr <- x0r - shift
ubr <- x0r +shift
dgvfss<-function(x){
  res<-dgvf(x, rhs=sigma)
  val<-sum(res^2)
}
dgvrrs<-function(x){
  res<-dgvrr(x, rhs=sigma)
  val<-sum(res^2)
}

```

```

tgf <- glopt(dgvfss, lb=lb, ub=ub, incl=c("deoptimr", "genoud", "ga", "pso"))
print(tgf)
tgr <- glopt(dgvrss, lb=lbr, ub=ubr, incl=c("deoptimr", "genoud", "ga", "pso"))
print(tgr)

```

The results and timings are, unfortunately in this case, uninspiring.

```

> # dvglopt.R
> library(gloptim)
> source("dgvprep.R")
> source("dgvf.R")
> source("nleqsum.R")
> source("chknleqsol.R")
> pid <- "0121a"
> prob<-dgvprep(pid)
Prepare Dennis-Gay-Vu problem for id= 0121a
> sigma<-prob$sigma
> x0<-prob$x0
> source("dgvreduce.R")
> source("dgv.R")
> x0r<-dgvreduce(x0)
> shift <- 100
> lbf <- x0 - shift
> ubf <- x0 + shift
> lbr <- x0r - shift
> ubr <- x0r +shift
> dgvfss<-function(x){
+   res<-dgvf(x, rhs=sigma)
+   val<-sum(res^2)
+ }
> dgvrss<-function(x){
+   res<-dgv(x, rhs=sigma)
+   val<-sum(res^2)
+ }
> tgf <- glopt(dgvfss, lb=lb, ub=ub, incl=c("deoptimr", "genoud", "ga", "pso"))
glopt: control=NULL
> print(tgf)

```

	method	fmin	time	p1	p2	p3	p4	p5	p6	p7
1	ga	-5.916629e+17	5.193	-0.8917380	-0.06962564	-2.33956716	1.412347	0.7197578	-0.2825009	-1.4710387
2	pso	3.811090e-01	0.640	2.3000552	-4.95105203	-6.48411329	3.948841	2.0430412	2.3940513	0.8257454
3	deoptimr	2.751122e+00	5.143	99.4039055	-99.90418468	-98.99600227	-98.101759	96.4349572	102.0188937	98.6155200
4	genoud	2.477102e+01	29.179	0.0938765	-1.12740949	0.01184009	0.275271	0.9978030	1.2503798	-6.1394841

```


```

	p8
1	-2.4391020
2	0.3536293
3	-98.7978192
4	0.6878692

```

> tgr <- glopt(dgvrss, lb=lbr, ub=ubr, incl=c("deoptimr", "genoud", "ga", "pso"))
glopt: control=NULL
> print(tgr)

```

	method	fmin	time	p1	p2	p3	p4	p5	p6
1	ga	-6.754425e+17	3.517	-0.009364945	0.04527876	-3.3798955	2.0277091	-6.843039	0.3015986
2	deoptimr	3.992541e-01	3.089	-1.677136320	-0.07111157	1.1226002	1.3877193	-6.418279	-8.1433227
3	pso	3.158459e+00	0.494	99.166368787	-99.33306963	-101.9835323	101.8854603	-99.791963	100.6789897
4	genoud	3.516621e+02	3.131	0.456135104	0.35255385	0.1855194	0.9448873	-3.225310	-0.7321973

6 nleqslv test problem

Package nleqslv includes a test problem which we use here for illustration.

$$r_1(x) = x_1^2 + x_2^2 - 2 = 0$$

$$r_2(x) = \exp(x_1 - 1) + x_2^3 - 2 = 0$$

This seems to be a problem that is relatively easy to solve by most methods, though we note that some approaches perform poorly. Notably, a number of function minimization solvers find a local minimum that is not a solution to the nonlinear equations. This is indicated by the residual sum of squares value near 0.18336, with parameters near the suggested start `xstart3<-c(1.48508, -1.0886e-06)`

We have suppressed most of the output for space reasons.

```

#> Sumsquares results of methods
#>      method      start      ss
#> 1      nleqslv xstart1 7.91546228567908e-20
#> 2      nleqslv xstart2 6.47806667252515e-18
#> 3      nleqslv xstart3 0.183361725333783
#> 4      BB::dfsane xstart1 2.40003077549e-17
#> 5      BB::dfsane xstart2 2.44274187984104e-19
#> 6      BB::dfsane xstart3 1.25066039269404e-14
#> 7      dfsaneacc xstart1 1.67101720053509e-21
#> 8      dfsaneacc xstart2 1.50592337150088e-16
#> 9      dfsaneacc xstart3 1.00022577995405e-19
#> 10 nlfb-jacentral xstart1 1.35165621000982e-15
#> 11 nlfb-jacentral xstart2 9.76473803243686e-18
#> 12 Nelder-Mead xstart1 1.66815320909569e-08
#> 13      nlm xstart1 5.65111729255102e-16
#> 14      nlminb xstart1 0.183361654679628
#> 15      lbfgsb3c xstart1 1.27770986049496e-14
#> 16      Rtnmin xstart1 5.11399868633245e-15
#> 17      spg xstart1 2.03208269671654e-17
#> 18      ucminf xstart1 1.42472672550097e-19
#> 19      bobyqa xstart1 3.02237589087772e-14
#> 20      nmkb xstart1 0.183361747085402
#> 21      subplex xstart1 0.183361654677934
#> 22      ncg xstart1 6.54745022259549e-15
#> 23      Rcgmin xstart1 8.47277001984322e-21
#> 24      nvm xstart1 1.18526351009457e-24
#> 25      Rvmmmin xstart1 1.18526351009457e-24
#> 26      mla xstart1 1.51249045387053e-10
#> 27      slsqp xstart1 1.2593529121072e-17
#> 28      tnewt xstart1 1.66994916589703e-24
#> 29      pracmanm xstart1 0.183361654677934
#> 30      nlmm xstart1 0
#> 31 Nelder-Mead xstart2 9.14907810780667e-08
#> 32      nlm xstart2 0.183361654679974
#> 33      nlminb xstart2 0.183361654678151
#> 34      lbfgsb3c xstart2 0.183361654748689
#> 35      Rtnmin xstart2 1.71720848945297e-18
#> 36      spg xstart2 0.183361654677936
#> 37      ucminf xstart2 0.183361654677995
#> 38      bobyqa xstart2 0.183361654678425
#> 39      nmkb xstart2 0.183362331170298
#> 40      subplex xstart2 0.183361654677934
#> 41      ncg xstart2 0.18336165470041
#> 42      Rcgmin xstart2 0.183361654738436
#> 43      nvm xstart2 0.183361654678022
#> 44      Rvmmmin xstart2 0.183361654678022
#> 45      mla xstart2 6.69885437003902e-09
#> 46      slsqp xstart2 0.183361654686446
#> 47      tnewt xstart2 0.183361654732427
#> 48      pracmanm xstart2 0.183361654677934
#> 49      nlmm xstart2 5.40241409895111e-13
#> 50 Nelder-Mead xstart3 0.183361654694565
#> 51      nlm xstart3 0.183361654679259
#> 52      nlminb xstart3 0.183361654680113
#> 53      lbfgsb3c xstart3 1.58628930536124e-15
#> 54      Rtnmin xstart3 0.183361654678318
#> 55      ucminf xstart3 0.183361654694565
#> 56      bobyqa xstart3 0.183361654677934
#> 57      nmkb xstart3 1.5183070349323e-06
#> 58      subplex xstart3 1.97215226305253e-31
#> 59      ncg xstart3 0.183361654681022
#> 60      Rcgmin xstart3 0.1833616546784
#> 61      nvm xstart3 0.183361654679689
#> 62      Rvmmmin xstart3 0.183361654679689
#> 63      slsqp xstart3 0.183361654678086
#> 64      tnewt xstart3 0.183361654681015
#> 65      pracmanm xstart3 3.51800409292362e-26
#> 66      nlmm xstart3 0.183361654678596
#> 67 nlfb-jacentral xstart3 0.183361654678426
#> 68 nlfb-jafwd xstart2 0.183361654678427
#> 69 nlfb-jaback xstart3 0.183361654678425
#> 70 nlfb-jand xstart3 0.183361654677938
#> 71      ncg xstart3 0.183361654681022
#> 72      nvm xstart3 0.183361654679689
#> 73      lbfgsb3c xstart3 1.58628930536124e-15
#> times for different methods (10 repetitions)
#>      method      start      tmin      tmean      tmax

```

```

#> 1          nleqslv xstart1 109936 120334.8 196663
#> 2          nleqslv xstart2 112321 123596.4 178748
#> 3          nleqslv xstart3  88166  98686.5 159058
#> 4  lbfgsb3c-grcentral xstart1 822240 857358.3 985864
#> 5  lbfgsb3c-grcentral xstart2 1612390 1649005.5 1802940
#> 6  lbfgsb3c-grcentral xstart3 1076268 1111966 1280132
#> 7          dfsane xstart1 285125 303686.4 440083
#> 8          dfsane xstart2 344259 355297 419262
#> 9          dfsane xstart3 387176 397593.1 460252
#> 10         nlfb xstart1 1555174 1616051.3 1727092
#> 11         nlfb xstart2 1713308 1809668 2315558
#> 12         nlfb xstart3 327300 346383.9 440649
#> 13         dfsaneacc xstart1 710574 740496.5 819892
#> 14         dfsaneacc xstart2 526905 568740 764327
#> 15         dfsaneacc xstart3 1539579 1628672.8 1922037

```

We note for this problem that most methods fail from `xstart3`, as the Jacobian at this point is essentially singular and one component of the gradient is also small. Interestingly, quite large changes to this particular start are needed to escape the local minimum, though some derivative-free methods succeed in finding a solution. This is likely due to these methods taking large trial steps in the parameters in early stages of their execution.

7 trigexp test problem

The quite well-known **trigexp** test problem (see La Cruz and Raydan ([7]2003, Problem 12)) is relatively easy to solve.

```

trigexp <- function(x) {
  # Test function No. 12 in the Appendix of LaCruz and Raydan (2003)
  n <- length(x)
  F <- rep(NA, n)
  F[1] <- 3*x[1]^2 + 2*x[2] - 5 + sin(x[1] - x[2]) * sin(x[1] + x[2])
  tn1 <- 2:(n-1)
  F[tn1] <- -x[tn1-1] * exp(x[tn1-1] - x[tn1]) + x[tn1] * (4 + 3*x[tn1]^2) +
    2 * x[tn1 + 1] + sin(x[tn1] - x[tn1 + 1]) * sin(x[tn1] + x[tn1 + 1]) - 8
  F[n] <- -x[n-1] * exp(x[n-1] - x[n]) + 4*x[n] - 3
  F
}
#> dfsane solution. SS = 2.5518e-13
#> nlsr::nlfb solution. SS = 2.916e-23
#> nleqslv solution. SS = 5.9479e-21
#> dfsaneacc solution. SS = 2.4239e-13

```

8 The Abbott and Brent problem

This problem seems to have first appeared as Example 7 in Abbott and Brent ([1]1975), then again as Example 1 in Alefeld, Gienger, and Potra ([2]1994) and yet later in the quite large collection of problems Luksan and Vlcek ([9]2018). It is a relatively straightforward problem as seen by our computational results below. The code for the residuals is as follows.

```

brent <- function(x) {
# Luksan (2018) #63, Alefeld(1994) Example 1, Abbot & Brent (1975) Ex. 7
  n <- length(x)
  tnm1 <- 2:(n-1)
  F <- rep(NA, n)
  F[1] <- 3 * x[1] * (x[2] - 2*x[1]) + (x[2]^2)/4
  F[tnm1] <- 3 * x[tnm1] * (x[tnm1+1] - 2 * x[tnm1] + x[tnm1-1]) +
    (x[tnm1+1] - x[tnm1-1])^2 / 4
  F[n] <- 3 * x[n] * (20 - 2 * x[n] + x[n-1]) + ((20 - x[n-1])^2) / 4
  F
}
#> Function at start has SS= 6159.9
#> dfsane default SS= 1.7461e-13
#> dfsane M=200 SS= 4.4505e-13
#> nleqslv SS= 2.7741e-17
#> Check with nleqslv fvec SS= 2.7741e-17
#> nlfb SS= 3.2236e-15
#> dfsaneacc SS= 9.9399e-13

```

Optimization solvers using the sum of squares give the following sample of results. The stochastic optimizers, of which only four were chosen more or less at random, were particularly unsuccessful and time-consuming, and are deemed not worth reporting here, though code to run them is included but commented-out in the example. Moreover, the solvers are such that some cannot easily be limited by a maximum number of iterations or function counts.

```

#> Function at start has SS= 6159.9

#> Brent-Abbot problem

#> Warning in BB::spg(par = spar, fn = efn, gr = egr, lower = slower, upper =
#> supper, : Unsuccessful convergence.

#>
#>          p1 s1          p2 s2      value fevals gevals hevals conv
#> nlm      -0.00037063    0.0050205    6.2346e-13    419    419     0     0
#> nvm      -0.00076012   -0.0011585    2.3907e-12   1460    528     0     0
#> lbfgsb3c -0.03631404   -0.0872774    6.8173e-02   3501   3501     0     1
#> ncg       0.21993861    0.4476898    1.0761e+00   7630   3500     0     1
#> spg       0.35303095    0.6118932    1.1604e+00   4631   3503     0     1
#> nlminb    0.55820648    0.8947510    5.4060e+00    160    151     0     1
#> pracmann 0.48442607    0.7474630    8.3493e+00  35053     0     0     1
#>
#>          kkt1 kkt2 xtime
#> nlm      TRUE FALSE 0.613
#> nvm      TRUE FALSE 0.894
#> lbfgsb3c FALSE FALSE 5.275
#> ncg      FALSE FALSE 5.296
#> spg      FALSE FALSE 5.350
#> nlminb   FALSE FALSE 0.301
#> pracmann FALSE FALSE 1.156

```

9 Observations

The illustrative examples above suggest the following summary advice for workers wanting to solve nonlinear equations:

- The speed of the methods was of the same general order of magnitude, except for stochastic optimizers which could take very much more time and effort.
- Nonlinear equation tools, when they work, are easy to apply. `nleqslv`, moreover, had the fastest running time in the limited trials we made. This is not unexpected, since it calls code in Fortran, and these codes are tailored to the nonlinear equations problem.
- Function minimization methods had the highest failure rate. Since we square the residuals, we are likely losing information useful to the minimization process. This also applies to stochastic solvers. There is, unfortunately, inconsistency of success – sometimes normally “good” solvers do poorly and less well-regarded methods do well. We note that success is obvious if a zero sum of squared residuals is obtained.
- Nonlinear least squares via `nlsr::nlfb()` was generally reliable. We automatically have the size of the residuals and their sum of squares as a measure of success. Moreover, the singular values of the Jacobian provided by tools in package `nlsr` are helpful to understand when problems may be difficult to solve. Note that computing the singular values may slow down the performance of this particular tool, which is, moreover, coded entirely in R.

10 Appendices

The appendices provide code for some of the examples.

10.1 `dgvprep()`

```
# code for different DGV problems -- dgvprep.R
dgvprep <- function(pid="791129", reduced=FALSE){
  snames <- c("sigmax", "sigmay", "sigmaa", "sigmab", "sigmac",
             "sigmad", "sigmae", "sigmaf")
  #
  #
  dostop<-FALSE
  cat("Prepare Dennis-Gay-Vu problem for id=",pid,"\n")
  if (pid == "791129"){
    sigma<-c(0.485, -0.0019, -0.0581, 0.015, 0.105, 0.0406, 0.167, -0.399)
    x0 <- c(0.299, 0.186, -0.0273, 0.0254, -0.474, 0.474, -0.0892, 0.0892)
    xstar<-c(-6.321349025e-3, 4.913213490e-1, -1.998156408e-3, 9.815640840e-5,
             1.226569755e-1, -1.003153205e-1, -4.023517593, -2.071785527e-2)
  }
}
```

```

#
} else if (pid == "791226"){
  sigma<-c(-0.69, -0.044, -1.57, -1.31, -2.65, 2.0, -12.6, 9.48)
  x0 <- c(-0.3, -0.39, 0.3, -0.344, -1.2, 2.69, 1.59, -1.5)
  xstar<-c(-3.116266056e-1, -3.783733944e-1, 3.282442301e-1, -3.722442301e-1,
    -1.282227094, 2.494300312, 1.554865879, -1.384637843)
#
} else if (pid == "0121a") {
  sigma<-c(-0.816, -0.017, -1.826, -0.754, -4.839, -3.259, -14.023, 15.467 )
  x0 <- c(-0.41, -0.775, 0.03, -0.047, -2.565, 2.565, -0.754, 0.754)
  xstar<-c(3.099869097e-3, -8.190998691e-1, -2.239405352e-4, -1.677605946e-2,
    2.681514498, 2.250215931, -2.024170463e+1, 7.970982952e-1)
#
} else if (pid == "0121b"){
  sigma<-c(-0.809, -0.021, -2.04, -0.614, -6.903, -2.934, -26.328, 18.639)
  x0 <- c(-0.056, -0.753, 0.026, -0.047, -2.991, 2.991, -0.568, 0.568)
  xstar<-c(9.034542990e-3, -8.180345430e-1, -4.450738446e-4, -2.055492616e-2,
    2.773429036, 2.529477259, -1.480097186e+1, 5.220468844e-1)
} else if (pid == "0121c"){
  sigma<-c(-0.807, -0.021, -2.379, -0.364, -10.541, -1.961, -51.551, 21.053)
  x0 <- c(-0.074, -0.733, 0.013, -0.034, -3.632, 3.632, -0.289, 0.289)
  xstar<-c(5.140417418e-2, -8.584041742e-1, 1.047333626e-3, -2.204733363e-2,
    2.861205288, 2.949155438, -8.304243489, -1.454992413e-1)
} else {
  cat("Unrecognized problem id\n")
  dostop<-TRUE
}
}
if(dostop) stop("unrecognized problem")
names(sigma)<-snames
if (reduced) {
  xr <- rep(NA, 6)
  xr[1]<-x0[1]
  xr[2]<-x0[3]
  xr[3]<-x0[5]
  xr[4]<-x0[6]
  xr[5]<-x0[7]
  xr[6]<-x0[8]
  x0<-xr
  xs <- rep(NA, 6)
  xs[1]<-xstar[1]
  xs[2]<-xstar[3]
  xs[3]<-xstar[5]
  xs[4]<-xstar[6]
  xs[5]<-xstar[7]
  xs[6]<-xstar[8]
}
dgv <- list(pid=pid, sigma=sigma, x0=x0, xstar=xstar, reduced=reduced)
dgv
}

```

10.2 dgvf()

```

dgvf <- function(x, rhs=RHS){ # Dennis, Gay, Vu NLLS/NLEQ prob
# John C. Nash 2024-4020
# From TR83 article:
# John Dennis, David Gay, Phuong Vu,
# A new nonlinear equations test problem,
# Technical Report 83-16,
# Mathematical Sciences Department,
# Rice University, 1983
#
# x = vector of 8 elements for full DGV problem
# Full problem:
# a=x[1], b=x[2], c=x[3], d=x[4]
# t=x[5], u=x[6], v=x[7], w=x[8]
# rhs=c(sigmamax, sigmay, sigmaa, sigmab, sigmac,
#       sigmad, sigmae, sigmaf) (transposed)
#
  sigmax <- rhs[1]
  sigmay <- rhs[2]
  sigmaa <- rhs[3]
  sigmab <- rhs[4]
  sigmac <- rhs[5]
  sigmad <- rhs[6]

```

```

sigmae <- rhs[7]
sigmaf <- rhs[8]
#
t2mv2 <- x[5]^2 - x[7]^2
u2mw2 <- x[6]^2 - x[8]^2
t2m3v2 <- x[5]^2 - 3.0*x[7]^2
v2m3t2 <- x[7]^2 - 3.0*x[5]^2
u2m3w2 <- x[6]^2 - 3.0*x[8]^2
w2m3u2 <- x[8]^2 - 3.0*x[6]^2
ctv <- x[3] * x[5] * x[7]
duw <- x[4] * x[6] * x[8]
atv <- x[1] * x[5] * x[7]
buw <- x[2] * x[6] * x[8]
at <- x[1] * x[5]
bu <- x[2] * x[6]
cv <- x[3] * x[7]
dw <- x[4] * x[8]
ct <- x[3] * x[5]
av <- x[1] * x[7]
du <- x[4] * x[6]
bw <- x[2] * x[8]
#
fvec<-rep(NA,8)
fvec[1] <- x[1] + x[2] - sigmax
fvec[2] <- x[3] + x[4] - sigmay
fvec[3] <- at + bu - cv - dw - sigmaa
fvec[4] <- av + bw + ct + du - sigmab
fvec[5] <- x[1]*t2mv2 - 2.0*ctv +x[2]*u2mw2 -
2.0*duw -sigmac
fvec[6] <- x[3]*t2mv2 + 2.0*atv +x[4]*u2mw2 +
2.0*buw -sigmad
fvec[7] <- at*t2m3v2 + cv*v2m3t2 + bu*u2m3w2 +
dw*w2m3u2 - sigmae
fvec[8] <- ct*t2m3v2 - av*v2m3t2 + du*u2m3w2 -
bw*w2m3u2 - sigmaf
fvec # return
}

```

10.3 dgvr()

```

dgvr <- function(x, rhs=RHS){ # Dennis, Gay, Vu NLLS/NLEQ prob
# John C. Nash 2024-4020
# From TR83 article:
# John Dennis, David Gay, Phuong Vu,
# A new nonlinear equations test problem,
# Technical Report 83-16,
# Mathematical Sciences Department,
# Rice University, 1983
#
# x = vector of 8 elements for full DGV problem
# REDUCED PROBLEM
# rhs=c(sigmax, sigmay, sigmaa, sigmab, sigmac,
#       sigmad, sigmae, sigmaf) (transposed)
#
sigmax <- rhs[1]
sigmay <- rhs[2]
sigmaa <- rhs[3]
sigmab <- rhs[4]
sigmac <- rhs[5]
sigmad <- rhs[6]
sigmae <- rhs[7]
sigmaf <- rhs[8]
#
# Reduced problem
# a=x[1], c=x[2], t=x[3], u=x[4], v=x[5], w=x[6]
t2mv2 <- x[3]^2 - x[5]^2
u2mw2 <- x[4]^2 - x[6]^2
t2m3v2 <- x[3]^2 - 3.0*x[5]^2
v2m3t2 <- x[5]^2 - 3.0*x[3]^2
u2m3w2 <- x[4]^2 - 3.0*x[6]^2
w2m3u2 <- x[6]^2 - 3.0*x[4]^2
b <- sigmax - x[1]
d <- sigmay - x[2]
ctv <- x[2] * x[3] * x[5]

```

```

duw <- d * x[4] * x[6]
atv <- x[1] * x[3] * x[5]
buw <- b * x[4] * x[6]
at <- x[1] * x[3]
bu <- b * x[4]
cv <- x[2] * x[5]
dw <- d * x[6]
ct <- x[2] * x[3]
av <- x[1] * x[5]
du <- d * x[4]
bw <- b * x[6]
#
fvec<-rep(NA,6)
fvec[1] <- at + bu - cv - dw - sigmaa
fvec[2] <- av + bw + ct + du - sigmab
fvec[3] <- x[1]*t2mv2 - 2.0*ctv + b*u2mw2 -
  2.0*duw - sigmac
fvec[4] <- x[2]*t2mv2 + 2.0*atv + d*u2mw2 +
  2.0*buw - sigmad
fvec[5] <- at*t2m3v2 + cv*v2m3t2 + bu*u2m3w2 +
  dw*w2m3u2 - sigmae
fvec[6] <- ct*t2m3v2 - av*v2m3t2 + du*u2m3w2 -
  bw*w2m3u2 - sigmaf
fvec # return
}

```

10.4 dgvreduce()

```

# code for different DGV problems -- dgvreduce.R
dgvreduce <- function(xin){
# sigma NOT needed
  xr <- rep(NA, 6)
  xr[1]<-xin[1]
  xr[2]<-xin[3]
  xr[3]<-xin[5]
  xr[4]<-xin[6]
  xr[5]<-xin[7]
  xr[6]<-xin[8]
  xr
}

```

10.5 dgvunreduce()

```

dgvunreduce <- function(xred, sigma){ # change from reduced to full
  snames <- c("sigmax", "sigmay", "sigmaa", "sigmab", "sigmac",
    "sigmad", "sigmae", "sigmaf")
#
#
  x <- rep(NA, 8)
  x[1]<-xred[1]
  x[2]<-sigma[1] - xred[1]
  x[3]<-xred[2]
  x[4]<-sigma[2] - xred[2]
  x[5]<-xred[3]
  x[6]<-xred[4]
  x[7]<-xred[5]
  x[8]<-xred[6]
  x
}

```

10.6 dgvtry()

```

# code for different DGV problems -- dgvprep.R
source("dgvprep.R")
source("dgvf.R")
source("dgvr.R")
source("dgvreduce.R")

```

```

source("dgvunreduce.R")

pidvec<-c( "791129", "791226", "0121a", "0121b", "0121c")

for (pid in pidvec){
  prob<-dgvprep(pid)
  cat("pid:",pid,"\n")
  sigma<-prob$sigma
  x0<-prob$x0
  xstar<-prob$xstar
  cat("rhs:"); print(sigma)
  cat("x0:");print(x0)
  val0 <- dgvf(x0, rhs=sigma)
  cat("dgvf(x0:"); print(val0)
  val10 <- dgvf(10*x0, rhs=sigma)
  cat("dgvf(10*x0:"); print(val10)
  val100 <- dgvf(100*x0, rhs=sigma)
  cat("dgvf(100*x0:"); print(val100)
  vstar<- dgvf(xstar, rhs=sigma)
  cat("dgvf(xstar:"); print(vstar)
  cat("SS=", sum(vstar^2),"")
  cat("\n\nREDUCED:\n")
  prob<-dgvprep(pid, reduced=TRUE)
  cat("pid:",pid,"\n")
  sigma<-prob$sigma
  x0r<-prob$x0
  xstrr<-dgvreduce(prob$xstar)
  cat("xstrr:"); print(xstar)
  cat("check unred:"); dgvunreduce(xstrr, sigma)
  cat("x0r:");print(x0r)
  val0r <- dgvr(x0r, rhs=sigma)
  cat("dgvr(x0r:"); print(val0r)
  val10r <- dgvr(10*x0r, rhs=sigma)
  cat("dgvr(10*x0r:"); print(val10r)
  val100r <- dgvr(100*x0r, rhs=sigma)
  cat("dgvr(100*x0r:"); print(val100r)
  vstrr<- dgvr(xstrr, rhs=sigma)
  cat("dgvr(xstrr:"); print(vstrr)
  cat("SS=", sum(vstrr^2),"")
  cat("unreduced xstrr:")
  xsu<-dgvunreduce(xstrr, sigma)
  print(xsu)
  fres<-dgvf(xsu, sigma)
  cat("full resids ="); print(fres)
  cat("SS=",sum(fres^2),"")
  cat("=====\n\n")
}

```

References

- [1] J. P. ABBOTT AND R. P. BRENT, *Fast local convergence with single and multistep methods for nonlinear equations*, The Journal of the Australian Mathematical Society. Series B. Applied Mathematics, 19 (1975), pp. 173 – 199.
- [2] G. ALEFELD, A. GIENGER, AND F. POTRA, *Efficient validation of solutions of nonlinear systems*, SIAM Journal on Numerical Analysis, 31 (1994), pp. 252–260.
- [3] E. G. BIRGIN, J. L. GARDENGI, D. S. MARCONDES, AND J. M. MARTINEZ, *dfsaneacc: Accelerated Derivative-*

Free Method for Large-Scale Nonlinear Systems of Equations, 2024. R package version 1.0.2.

- [4] P. CORTEZ, *Modern Optimization with R*, Springer, Sept. 2014.
- [5] J. E. DENNIS, D. M. GAY, AND P. A. VU, *A new nonlinear equations test problem*, tech. rep., Mathematical Sciences Department, Rice University, 1983. TR83-16.
- [6] J. E. DENNIS AND R. B. SCHNABEL, *Numerical Methods for Unconstrained Optimization and Nonlinear Equations*, Prentice-Hall, Englewood Cliffs, NJ, 1983.
- [7] W. LA CRUZ AND M. RAYDAN, *Nonmonotone spectral methods for large-scale nonlinear systems*, *Optimization Methods & Software*, 18 (2003), pp. 583–599.
- [8] W. LACRUZ, J. MARTINEZ, AND M. RAYDAN, *Spectral residual method without gradient information for solving large-scale nonlinear systems of equations*, *Mathematics of Computation*, 75 (2006), pp. 1429 – 1448.
- [9] L. LUKSAN AND J. VLCEK, *Test problems for unconstrained optimization*, tech. rep., Institute of Computer Science, Academy of Sciences of the Czech Republic, Sept 2018. Technical Report No. 897.
- [10] K. M. MULLEN, T. V. ELZHOV, AND B. BOLKER, *minpack.lm: R interface to the Levenberg-Marquardt nonlinear least-squares algorithm found in MINPACK, plus support for bounds*, 2012. R package version 1.1-6.
- [11] J. C. NASH, *Nonlinear Parameter Optimization Using R Tools*, John Wiley & Sons: Chichester, May 2014.
- [12] J. C. NASH, *Function minimization and nonlinear least squares in r*, *WIREs Computational Statistics*, (2022). JN-file: JNWireSOpt.pdf.
- [13] J. C. NASH AND A. BHATTACHARJEE, *A comparison of R tools for nonlinear least squares modeling*, *R Journal*, (2023). Accepted for publication in the R Journal, in November 2023.

- [14] J. C. NASH AND D. MURDOCH, *nlsr: Functions for Non-linear Least Squares Solutions*, 2017. R package version 2017.2.19. Package contains 3 vignettes, "nlsr Background, Development, Examples and Discussion", "nlsr Derivatives", and "Specifying Fixed Parameters". <https://cran.r-project.org/package=nlsr>.
- [15] J. C. NASH AND R. VARADHAN, *Unifying optimization algorithms to aid software system users: optimx for R*, Journal of Statistical Software, 43 (2011), pp. 1–14.
- [16] C. V. NELSON AND B. C. HODGKIN, *Determination of magnitudes, directions, and locations of two independent dipoles in a circular conducting region from boundary potential measurements*, IEEE Transactions on Biomedical Engineering, BME-28 (1981), pp. 817–823.
- [17] B. POLYAK, *Newton's method and its use in optimization*, European Journal of Operational Research, 181 (2007), pp. 1086–1096.
- [18] R DEVELOPMENT CORE TEAM, *R: A Language and Environment for Statistical Computing*, R Foundation for Statistical Computing, Vienna, Austria, 2008. ISBN 3-900051-07-0.
- [19] F. SCHWENDINGER AND H. W. BORCHERS, *CRAN Task View: Optimization and Mathematical Programming*, mar 2024. Version 2024-03-17.
- [20] R. VARADHAN AND P. GILBERT, *BB: An R package for solving a large system of nonlinear equations and for optimizing a high-dimensional nonlinear objective function*, Journal of Statistical Software, 32 (2009), pp. 1–26. R package version 2019.10-1.
- [21] T. J. YPMA, *Historical development of the Newton-Raphson method*, SIAM Review, 37 (1995), pp. 531–551.

Addresses

John C. Nash
 University of Ottawa (retired)

Telfer School of Management
Ottawa, Ontario
ORCID: <https://orcid.org/0000-0002-2762-8039>
<mailto:profjcnash@gmail.com>

Ravi Varadhan
Johns Hopkins University
Johns Hopkins University Medical School
Baltimore, Maryland
<mailto:ravi.varadhan@jhu.edu>